

1938

1938

1938

1938
198Field Notes of the First Guide

BOOK 1938

Meridian, from 1st Standard Parallel to North Boundary of Navajo Indian Reservation, and Second Standard Parallel from West to East Boundary of said Reservation, surveyed by E. W. Darling, U.S. Surveyor, under his contract with Hon. Jas. S. Wilson, Commissioner of the General Land Office, dated Washington, D.C., April 29th 1869.

Commenced October 1st 1869 and completed October 14th 1869.

Names of Assistants.

Willard S. Paul. Compassman.

William J. Hare.

John Howe } Chainmen.

Selden W. Shafer.

Robert C. Darling } Cornermen.

Measuring chain compared with standard and found correct.

1938

1938

1938

Township 6 North.

99

BOOK

1938

Field Notes of the First Guide Meridian, from the First to the Second Standard Parallel, between Ranges 8 and 9 West of the Navajo Special meridian,

As the corner to the First Guide meridian is in Canon De Chille, and it being impracticable to reach the same, I commenced at the Witness corner on North East side of canon 18.75 chs. West of corner to Township 6, Ranges 8 and 9 West, thence North.

Var. 15° 33' East.

72.00 Offset East 18.75 chains to First Guide meridian, on the Edge of canon, course S. S. W.

The canon is about 1000 feet deep, with nearly perpendicular sand stone sides, its average width being about 40 chains.

There is a fine stream of clear water running through the canon. Set sand stone, 14 x 8 x 6, marked as per instructions, for the cor. to secs. 20, 30, 31 and 36.

Surface broken. Soil $3\frac{1}{2}$ rate.

Scattering Cedar and Pinon $3\frac{1}{2}$ rate.

North on East Boundary of Sec. 20,
Var. 15° 33' E.

19.50 Bend in Canon "De Chille" course S. E. Offset west 3 chains, thence N. 7 chains, then offset east 3.00 chains to line. Canon about 1000 ft. deep, with nearly perpendicular sand stone bluffs.

Set sand stone, 16 x 14 x 3, for 1/2 sec. corner, as per instructions.

Set sand stone, 15 x 14 x 4, marked as per instructions, for the

Dec 1938

100

BOOK 1938

Utah

12	86
12	87
24	2 718
24	2 719
25	2 730
36	2 631

12	66
12	67
24	2 618
24	2 519
25	2 530
36	2 531

13	06
12	91
24	2 918
24	2 919
25	2 930
36	2 831

BOOK 1938

11	71, R. 10 H.
11	71, R. 9 H.
24	2 418
24	2 319
25	2 330

11	71, R. 7 H.
----	-------------

11	71, R. 6 H.
----	-------------

22	31	32	33	34	35	36	31	32	33	34	35	36	31	32	33	34	35	36
36	22	22	21	21	20	20	20	19	19	19	19	19	18	18	18	18	18	18
6	5	4	3	2	1	6	5	4	3	2	1	9	6	5	4	3	2	1

10	71, R. 10 H.
----	--------------

10	71, R. 9 H.
24	2 918

10	71, R. 7 H.
----	-------------

10	71, R. 6 H.
----	-------------

24	2 19
----	------

25	2 30
----	------

36	2 31
----	------

1	86
---	----

12	77
----	----

9	718
---	-----

24	2 19
----	------

25	2 30
----	------

36	2 31
----	------

1	66
---	----

12	67
----	----

8	718
---	-----

24	2 19
----	------

25	2 30
----	------

36	2 31
----	------

1	46
---	----

12	77
----	----

7	718
---	-----

24	2 19
----	------

25	2 30
----	------

36	2 31
----	------

1	26
---	----

12	77
----	----

6	718
---	-----

24	2 19
----	------

25	2 30
----	------

36	2 31
----	------

Arizona

11	71, R. 5 H.
----	-------------

10	71, R. 5 H.
----	-------------

New Mexico

Field Notes of the J. L. M. from the 1st to the 2nd S. Parallel, between
Ranges 6 & 7 west of the M. & M.

Chains

101

BOOK 1938

corner to sees. 19. 24. 25 and 30.
Surface rolling. Partly covered
with Cedar and Pinon, 3rd rate.
Soil 3rd rate.

North on East Boundary of Sec. 24

Var. 15° 30' E. S.

\$0.00 Set sand stone, 16 x 12 x 3, for 1/4 sec. cor.
as per instructions.

\$0.00 Set sand stone, 14 x 12 x 3, marked as
per instructions, for the corner to
sees. 13. 18. 19 and 24.

Surface rolling, covered with scattering
Cedar and Pinon, 3rd rate,
Soil 2nd rate.

North on East Boundary of Sec. 13.

Var. 15° 30' E.

\$0.00 Set sand stone, 16 x 10 x 6, for 1/4 sec cor.
as per instructions,

\$0.00 Set sand stone, 16 x 12 x 4, marked as
per instructions, for the corner
to sees. 7. 12. 13 and 18.

Surface rolling, scattering
Pinon and Cedar, 3rd rate,
Soil 2nd rate.

North on East Boundary of

Sec. 12.

Var. 15° 30' E.

\$0.00 Marked surface rock, for 1/4 sec cor.
as per instructions.

\$0.00 Set sand stone, 14 x 8 x 6, marked
as per instructions, for the cor.
to sees. 1. 6. 7 and 12.

Surface rolling, scattering Pinon
and Cedar, 3rd rate, Soil 3rd rate.

North on East Boundary of Sec. 6

Var. 15° 30' E.

\$0.00 Set sand stone, 24 x 18 x 3, for 1/4
sec cor. as per instructions.

Field Notes of the First Guide Meridian from the Survey

10th BOOK 1938	<p><i>Chambers</i></p> <p>52.00 Indian Trail, Bears Cr. Co. and S.W. Set sand stone, 30 x 24 x 6. marked as per instructions and built mound of stone, for the corner to Townships 6 and 7 North, Ranges 8 and 9 west and sections 1, 6, 31 and 36. Surface rolling. Scattering Cedar and Pinon. Soil 2^d rate.</p>
	<p style="text-align: center;">Township 7 North.</p> <p>North on East Boundary of Sec. 36. Var. 15° 25' E.</p> <p>Leave scattering Pinon and Cedar timber. Set sand stone, 16 x 14 x 3. for 1/4 Sec. corner, as per instructions. Prairie. 60' Chks. wide, coarse d.W. Canyon 70 links wide, coarse d.W. Set sand stone, 40 x 36 x 2 4. marked as per instructions, for the corner to Secs. 25, 30, 31 and 36. Surface rolling. Prairie. Soil 2^d rate.</p>
	<p style="text-align: center;">North on East Boundary of Sec. 25. Var. 15° 25' East</p> <p>Set charred post and built mound for 1/4 Sec. corner, as per instruc- tions. Surface rolling. Prairie. Soil 2^d rate. Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to Secs. 19, 24, 29 & 30. Surface rolling. Prairie. Soil 2^d rate.</p>
	<p style="text-align: center;">North on East Boundary of Sec. 24. Var. 15° 25' East.</p> <p>Set sand stone, 16 x 8 x 6. for 1/4 Sec. Cor. as per instructions.</p>

To the Second Standard Parallel, Between Ranges 8 & 9 west
of the N. D. m.

chains.

80.00

Set sand stone, 18 x 12 x 10, marked
as per instructions, for the corner
to Secs. 13, 18, 19, and 24.
Surface rolling. Prairie.
Soil 2 $\frac{1}{4}$ rate.

103
BOOK 1938

40.00

North on East Boundary of sec. 13.

Var. 15^a 25° E.

Set charred post and built
mound for $\frac{1}{4}$ sec. corner as
per instructions.

80.00

Deposited marked stone, set
charred post, marked built
mound and dug pits, as per
instructions, for the corner
to Secs. 7, 12, 13, and 18.

Surface rolling. Prairie.
Soil 2 $\frac{1}{4}$ rate.

North on East Boundary of
sec. 12.

Var. 15^a 25° E.

40.00

Set charred post and built
mound, for $\frac{1}{4}$ sec. corner as
per instructions.

40.00

Ravine. 80 links wide, course N.W.
Set sand stone, 30 x 12 x 4, marked
as per instructions, for the cor.
to Secs. 1, 6, 7 and 12.

80.00

Surface rolling. Prairie.
Soil 3 $\frac{1}{4}$ rate.

North on West Boundary of
Sec. 1.

Var. 15^a 25° E.

40.00

Set sand stone, 24 x 10 x 4, for $\frac{1}{4}$
sec. corner, as per instructions.

80.00

Set sand stone, 24 x 18 x 10,
marked as per instructions,
for the corner to Secs. 1, 6, 31 &
36, and Townships 7 and 8
North. Ranges 8 and 9 west.

Surface rolling. Prairie. Soil 2 $\frac{1}{4}$ rate.

Field Notes of the First Guide Meridian

104

BOOK

1938

Chains

October 1st 1869.

Township 8 North,
North on East Boundary of sec 36.
Var. 15° 25' East

- | | |
|-------|--|
| 33.00 | Canon, 250 feet deep, course W.W.W. |
| 40.00 | Set sand stone, 16 x 14 x 5. for 1/4 see.
corner, as per instructions. |
| 43.00 | Leave canon, course W. N. W. |
| 66.50 | Canon, 80 feet deep, course West |
| 69.00 | Leave same. |
| 80.00 | Set sand stone, 34 x 23 x 5. marked as
per instructions, for the corner
to Secs. 25, 30, 31 and 36.
Surface broken. Prairie. Soil 2 nd & 3 rd rate. |

North on East Boundary of sec 25.
Var. 15° 20' E.

- | | |
|-------|--|
| 6.00 | Canon, 150 feet deep, course West |
| 10.50 | Leave same. |
| 40.00 | Set sand stone, 16 x 8 x 6. for 1/4
see, corner, as per instructions. |
| 80.00 | Set sand stone, 24 x 12 x 3. marked
as per instructions, for the corner to
secs. 19, 24, 25 and 30.
Surface rolling. Soil 2 nd and 3 rd rate.
Prairie. |

North on East Boundary of sec. 24.
Var. 15° 20' E.

- | | |
|-------|---|
| 40.00 | Set sand stone, 16 x 12 x 3. for 1/4
see, corner, as per instructions. |
| 80.00 | Set sand stone, 24 x 14 x 3. marked
as per instructions, for the corner
to Secs. 13, 18, 19 and 24.
Surface rolling. Prairie
Soil 3 rd rate. |

North on East Boundary of sec. 13.
Var. 15° 20' E.

- | | |
|-------|--|
| 40.00 | Set sand stone, 16 x 14 x 3. for 1/4 sees. |
|-------|--|

from the First to the Second Standard Parallel, between
Ranges 8 and 9 West of the R. S. m.

chains

105

63.00

corner, as per instructions.

BOOK

1938

74.00

Canyon, 200 feet deep, course west.
Leave same. Sand stone sides.
Set sand stone, 16 x 14 x 3, marked
as per instructions, for the corner
to sections 7, 12, 13 and 18.

Surface rolling. Prairie.

Soil 2nd rate.

40.00

North or East Boundary of sec. 12.

Var. 15° 20' East

80.00

Set sand stone, 18 x 8 x 6, for 1/2 sec. cor.,
as per instructions.

Set sand stone, 18 x 10 x 8, marked
as per instructions, for the corner to
secs. 1, 6, 7 and 12.

Surface rolling. Prairie. Soil 2nd rate.

North or East Boundary of sec. 1.

Var. 15° 20' East

2.00

Canyon, 200 feet deep, course west.

15.00

Leave same. Sand stone sides.

40.00

Set sand stone, 16 x 12 x 3, for 1/2
sec. corner, as per instructions.

80.00

Set sand stone, 30 x 12 x 4, marked as
per instructions, for the corner
to secs. 1, 6, 31 and 36, and
Townships 8 and 9 North,
Ranges 8 and 9 West.

Surface rolling. Prairie.

Soil 2nd rate.

Township 9 North.

North on East Boundary of sec. 36.

Var. 15° 10' East

40.00

Set sand stone, 24 x 14 x 3, for 1/2 sec.
corner, as per instructions.

80.00

Set sand stone, 18 x 16 x 6, marked
as per instructions, for the
corner to secs. 25, 30, 31 & 36.

Surface rolling. Prairie. Soil 2nd rate.

Field Notes of the First Guide Meridian from the

BOOK	Chains	North on East Boundary of Sec. 25. Var. $15^{\circ} 10' E.$
106	1938	Set charred post and built mound for 1/4 Sec. corner as per instructions.
	40.00	Set sand stone, 18 x 12 x 3. marked as per instructions, for the corner to secs. 19, 24, 25 and 30.
	80.00	Surface rolling. Prairie. Soil 2 ^d rate.
		North on East Boundary of Sec. 24. Var. $15^{\circ} 10' E.$
	13.00	Canyon, 100 feet deep, course W.S.W.
	15.00	Creek, 20 eks. wide, clear water, gentle current, course West.
	17.00	Leave canyon, sand stone sides.
	40.00	Set sand stone, 26 x 18 x 3. for 1/4 Sec. corner as per instructions.
	80.00	Set volcanic stone, 24 x 18 x 4. marked as per instructions, for the corner to secs. 18, 19, 19 and 24.
		Surface rolling. Prairie. Soil 2 ^d & 3 ^d rate.
		North on East Boundary of Sec. 13. Var. $15^{\circ} 50' E.$
	40.00	Set charred post and built mound for 1/4 Sec. corner as per instructions.
	78.00	Enter valley of "Rio Carrissa".
	79.00	"Rio Carrissa". Low banks, sandy bottom, dry at this point, but in places there is quite a stream of running water, course west.
	80.00	Set sand stone, 16 x 14 x 3. marked as per instructions, for the corner to secs. 7, 12, 13 and 18.
		Surface rolling. Prairie. Soil 1 st rate.
		North on East Boundary of Sec. 12. Var. $15^{\circ} 05' E.$
	62.00	Leave bottom, bears East & west
	40.00	Set charred post and built mound

~~1st to the 2nd Standard Parallel, Between Ranges 8 and
9 West of the N. & S. Meridian~~

~~chains~~

61.00	for $\frac{1}{4}$ See. Corner, as per instructions.	107
80.00	Bluff, bears East and West, Set sand stone, 20 x 14 x 6. marked as per instructions, for the corner to secs. 1. 6. 7 and $\frac{1}{2}$. Surface rolling. Prairie. Soil 2 nd & 3 rd rate.	BOOK 1938

North on East Boundary of Sec. 1.

Var. 15° 05' East.

22.00	Dry bed of Creek, 100 lks. wide, course E.
40.00	Set sand stone, 16 x 12 x 6. for $\frac{1}{4}$ See. Corner, as per instructions.
80.00	Set sand stone, 14 x 12 x 8 and built mound of stone, for the corner to secs. 1. 6. 31 and 36. and Townships 9 and 10 North. Ranges 8 and 9 west. Surface rolling. Prairie. Soil 2 nd rate.

Township 10 North.

North on East Boundary of Sec. 36.

Var 15° East.

23.00	Creek, 10 lks. wide, course West.
40.00	Set sand stone, 14 x 12 x 4. for $\frac{1}{4}$ See. Corner, as per instructions.
43.00	Pavine, 80 links wide, course west.
80.00	Set sand stone, 12 x 12 x 6. marked as per instructions, for the corner to secs. 25. 30. 31 and 36. Surface rolling. Soil 2 nd and 3 rd rate. Prairie.

North on East Boundary of Sec. 25.

Var. 15° 10' East.

40.00	Set sand stone, 16 x 10 x 4. for $\frac{1}{4}$ See. Corner, as per instructions.
44.00	Granite Bluff, 60 feet high. Bears E. and west.
80.00	Deposited marked stone, set charred post, marked, built mound and dug pits, as per instructions, for the corner to secs. 19. 24. 25 and 30.

Field Notes of the First Guide Meridian from the 1st

108 BOOK chains 1938	Surface broken. Soil 3 rd rate. Prairie.
	North on East Boundary of Sec. 24. Var. 15° 10' E.
40.00	Set sand stone, 15 x 14 x 4. far & see. Cor as per instructions
59.70	Dry bed of creek, 90 lks. wide, coarse debris
80.00	Set sand stone, 14 x 10 x 5. marked as per instructions, for the corner to secs. 13, 18, 19, and 24. Surface rolling. Prairie. Soil 2 nd & 3 rd rate.
	North on East Boundary of Sec. 13. Var. 15° 10' East
40.00	Set charred post and built. far & see. corner, as per instructions. A conical sand stone peak, about 200 feet high, bears S. 89° W. distant 3 1/2 chains.
80.00	Set granite, 16 x 12 x 5. marked as per instructions, for the corner to secs. 7, 12, 13 and 18. Surface rolling. Prairie. Soil 2 nd rate.
	North on East Boundary of sec. 12. Var. 15° 10' East
.30	Dry bed of creek, 20 lks. wide, coarse West.
40.00	Set sand stone, 14 x 12 x 3. far & see. corner, as per instructions.
80.00	Set granite, 18 x 7 x 6. marked as per instructions. for the corner to Secs. 1, 6, 7 and 12. Surface rolling. Prairie. Soil 2 nd rate.
	North on East Boundary of Sec. 1. Var. 15° 10' E.

the First Guide Meridian to the E. Boundary of Resr.

Chains
32.50

On Sandy bed of creek .50 ltrs wide
course north.

109

40.00

Set charred post and built mound for
1/4 sec. corner, as per instructions.

BOOK 1938


80.00

Deposited marked stone, set charred post,
marked, built mound and dug pits, as
per instructions, for the corner to Secs
1. 6. 31 and 36, and Township 10 North,
Ranges 8 and 9 West.

Surface rolling. Prairie.

Soil Qd. rate.

October 2nd 1869.



Field notes off the Second Standard Parallel from

110

BOOK 1938

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

Y

+

+

✓

+

+

+

+

+

+

+

+

+

+

Township 11 North Range
5 West.

West on South Boundary of
Sec. 36.

Ra. $14^{\circ} 08'$ E.

40.00 Set Sand Stone 14 + 12 + 3 for 1/4 Sec.
corner as per instructions.

the First Guide Meridian to the E. Boundary of the
Navajo Indian Reservation.

111

Chains

80.00

Set sand stone, 16 x 12 x 3. marked
as per instructions, for the corner
to Secs. 35 and 36.

BOOK 1938

Surface broken, a few scatter-
ing cedar and pinon trees.
Soil 3rd rate.

West on South Boundary of Sec. 35.

Var. 14° 08' E.

40.00

Set charred post and built mound for
1/4 sec. corner, as per instructions.

80.00

Deposited marked stone, set charred
post, marked, built mound and
dug pits, as per instructions, for
the corner to Secs. 34 and 35.

Surface rolling, ^{mostly} Prairie. Soil 2nd rate.

West on South Boundary of Sec. 34.

Var. 14° 08' East.

40.00

Set charred post and built mound
for 1/4 sec. corner, as per instructions.

80.00

Deposited marked stone, set charred
post, marked, built mound and
dug pits, as per instructions, for
the corner to Secs. 33 and 34.

Surface rolling. Prairie.

Soil 2nd rate.

West on South Boundary of Sec. 33.

Var. 14° 15' E.

40.00

Set charred post and built mound
for 1/4 sec. corner, as per instructions.

80.00

Deposited marked stone, set
charred post, marked, built
mound and dug pits, as per
instructions, for the corner to
Secs. 32 and 33.

Surface rolling. Prairie.
Soil 2nd rate.

Fiel Notes of the Second Standard Parallel from

BOOK	chains	Weston South Boundary of Sec. 32. Var. 14 ^a 15' E.
112	1938 \$10.00	Set charred post and built mound for $\frac{1}{4}$ sec corner, as per instructions. Creek, 30 lbs. wide, coarse marsh.
	78.50	Set sand stone, 18 x 10 x 4, marked as per instructions, for the corner to secs. 31 and 32.
	80.00	Surface rolling, Prairie. Soil 2 $\frac{1}{4}$ rate.
		Weston South Boundary of Sec. 31. Var. 14 ^a 15' E.
	\$10.00	Set sand stone, 16 x 12 x 3, for $\frac{1}{4}$ sec. cor as per instructions.
	80.00	Set sand stone, 24 x 24 x 6, marked as per instructions, for the corner to Secs. 31 and 36, and Township 11 North, Range 5 and 6 West.
		Surface broken, Prairie. Soil 3 $\frac{1}{4}$ rate.
		Township 11 North, Range 6 West. Weston South Boundary of Sec. 36. Var. 14 ^a 18' East
	\$30.00	Descend sand stone ledge, 40 ft. high, bears North and South.
	\$40.00	Set sand stone, 18 x 12 x 3, for $\frac{1}{4}$ sec. corner, as per instructions.
	\$80.00	Set sand stone, 18 x 12 x 3, marked as per instructions, for the corner to Secs. 35 and 36.
		Surface broken, Prairie. Soil 3 $\frac{1}{4}$ rate.
		Weston South Boundary of Sec. 35. Var. 14 ^a 18' East.
	\$9.75	Creek, 20 lbs. wide, coarse d.e.
	\$12.00	Leave same.
	\$40.00	Set sand stone, 18 x 12 x 4, for $\frac{1}{4}$ sec. corners as per instructions.

The 1st Guide Meridian to the East Boundary of the
Ward Indian Reservation.

chains

80.00

Set sand stone, 18 x 12 x 4. marked as per instructions, for the corner to Secs. 34 and 33.

113

BOOK 1938

Surface broken. Prairie, Soil 3rd rate.

West on South Boundary of Sec.

34.

Var. 14° 15' East.

12.90

Creek 20 lbs. wide, course N. East.

21.00

Creek, 20 lbs. wide, course S. E.

26.00

Creek 20 lbs. wide, course N. E.

40.00

Set sand stone, 16 x 12 x 3. for $\frac{1}{4}$ sec. corner, as per instructions.

80.00

Set sand stone, 16 x 14 x 3. marked as per instructions, for the corner to Secs. 33 and 34.

Surface broken. Prairie, Soil 3rd rate.

October 9th / 1869.

West on South Boundary of Sec. 33.

Var. 14° 18' E.

40.00

Set sand stone, 16 x 12 x 3. for $\frac{1}{4}$ sec. cor. as per instructions.

60.00

Creek, 20 lbs. wide, course S. E.

80.00

Set sand stone, 20 x 10 x 4. marked as per instructions, for the corner to Sections 32 and 38.

Surface broken. Prairie. Soil 2nd rate.

West on South Boundary of Sec. 32.

Var. 14° 18' E.

40.00

Set sand stone, 16 x 12 x 3. for $\frac{1}{4}$ sec. corner, as per instructions.

80.00

Set sand stone, 18 x 12 x 4. marked as per instructions, for the corner to Secs. 31 and 32.

Surface broken. Prairie mostly, a few scattering cedar and Pinon trees. Soil 3rd rate.

Field Notes of the Second Standard Parallel

Chains	
114	Weston South Boundary of Sec. 31. Var. 14° 18' East.
BOOK 1938	Set sand stone, 16 x 10 x 6, for $\frac{1}{4}$ sec. corner, as per instructions.
40.00	Set sand stone, 18 x 10 x 6, marked as per instructions, for the corner to Secs. 31 and 36, and Township to 11 North, Range 6 and 7 West. Surface broken. Prairie mostly, Soil 3 ^d rate.
	Township 11 North. Range 7 west Weston South Boundary of Sec. 36. Var. 14° 18' East.
5.00	Foot of sand stone bluff, 300 feet high, bears N. and South. Offset North 50 chains, then West 40 chains; then 50 chains South to West side of bluff, at 4 s. chs. Arroya, 40 feet deep, 80 ft. wide, with small stream in bottom, course North.
54.00	Set sand stone, 20 x 20 x 4, marked as per instructions, for the corner to Secs. 35 and 36. Surface broken. Prairie mostly, Soil 3 ^d rate.
8000	Weston South Boundary of Sec. 35. Var. 14° 18' E.
40.00	Set sand stone, 18 x 12 x 3, for $\frac{1}{4}$ sec. corner, as per instructions.
80.00	Set sand stone, 20 x 12 x 3, marked as per instructions, for the corner to Secs. 34 & 35. Surface broken. Prairie. Soil 3 ^d rate.
	Weston South Boundary of Sec. 34. Var. 14° 18' E.
40.00	Set sand stone, 14 x 12 x 3.

from the 1st Guide Meridian to the East Boundary
of the Otoe Indian Reservation

Chains		115
70,00	for $\frac{1}{4}$ sec. corner, as per instructions. Foot of sand stone cliff.	BOOK 1938
80,00	Place for corner to secs. 33 and 34. on side of bluff. Impossible to establish same. Surface broken. Prairie. Soil 2 nd rate.	

West on South Boundary of Sec. 33.
Var. 1⁴° 18' E.

4000	Place for corner on side of bluff. Impossible to establish same. Surface broken. Scattering Pinon and cedar, 3 rd rate. Soil 3 rd rate. October 10 th 1869.
------	--

West on South Boundary of Sec. 32.
Var. 1⁴° 18' E.

40,00	Place for $\frac{1}{4}$ sec. corner on bluff. Impossible to establish same.
80,00	Set sand stone, 18 x 16 x 3, marked as per instructions, for the cor. to secs. 31 and 32. Surface rolling. Prairie mostly. Soil 3 rd rate.

West on South Boundary of
Sec. 31. Var. 1⁵° 30' E.

40,00	Set sand stone, 16 x 14 x 3, for $\frac{1}{4}$ sec. corner, as per instructions.
80,00	Set sand stone, 24 x 16 x 3, marked as per instructions, for the cor. to secs. 31 and 36, and Township No. 11 North. Ranges 7 and 8 West. Surface rolling. Prairie. Soil 2 nd rate.

Township 11 North. Range 8 West.
West on South Boundary of Sec. 36.
Var. 1⁵° 30' E.
Impracticable to establish the

~~Field Notes of the Second Standard Parallel from the 1st G.M.
to the East Boundary of the N. J. Reservation.~~

Chains
116
BOOK 1938

corners on South Boundary of secs.
86, 35 and 34 on account of high,
precipitous bluffs and deep canons.

West on South Boundary of Sec. 35.

Var. 15° 30' E.

40.00 Place for corner on bluff. Impossible
to establish same.

56.50 Leave mountains and enter valley.

80.00 Deposited marked stone, set
charred post, marked, built mound
and dug pits, as per instructions,
for the corner to secs. 32 and 33.

Surface mountainous. Soil 3⁴ rate.
Scattering cedar and Pinon.

West on South Boundary of Sec. 32.

Var. 15° 30' E.

13.00 Dry Creek, 15 lks. wide, course S.W.

46.00 Set charred post and built mound
for 1/4 sec. corner, as per instructions.

80.00 Deposited marked stone, set
charred post, marked, built
mound and dug pits, as per
instructions, for the corner
to secs. 31 and 32.

Surface rolling. Prairie, soil 2^{1/4} rate.

West on South Boundary of Sec. 31.

Var. 15° 30' E.

40.00 Set charred post and built mound
for 1/4 sec. cor. as per instructions.

56.20 Closing corner of First Inside
meridian.

80.00 Deposited marked stone, set
charred post, built mound and
dug pits, as per instructions,
for the corner to Township 11
North, Ranges 8 and 9 west.

General Description of First Guide Meridian from First to Second Standard Parallel and Second Standard Parallel from First Guide Meridian to East Boundary of Navajo Indian Reservation.

The First Guide meridian between the 1st and 2nd Standard Parallel, passes over a rolling country, about half of which is covered with Cedar and Pinon, 3rd rate. The soil is generally 2nd rate and well adapted to grazing purposes.

The Second Standard Parallel, beginning at the East, crosses the "Hog Back Mountain", then passes through a gently rolling country as far as Range 4, where the country becomes broken and rocky, and is partially covered with Cedar and Pinon, From this point the line runs through wooded valley to the 39th mile, where it intersects a precipice of red sand stone, which extends from the "Carrissa" Range on the North, to the Juniper, on the South.

The rougher portion of the country along the line is well watered and wooded, and admirably adapted to grazing.

From this point to the First Guide Meridian, the country is very mountainous, and cut up with deep and almost impassable canons.

Field Notes of the Second Standard parallel from

chains
118
BOOK 1938

Field Notes of the 2nd Standard Parallel from the First Guide Meridian to the West Boundary of the Navajo Indian Reservation.

Weston True Line, South Boundary of Sec. 36. Var. 15° E. L.

\$0.00 Set sand stone, 16 x 14 x 3. for $\frac{1}{4}$ See, corner, as per instructions.
\$0.00 Sand stone bluff bears N.E. & S.W.
\$0.00 Place for corner to Secs. 35 and 36, on side of bluff. Impractical to establish same, surface broken. Soil 2nd rate. Prairie.

Weston South Boundary of Sec. 35. Var. 15° East.

\$0.00 Place for $\frac{1}{4}$ See, corner on bluff, impractical to establish same, surface broken. Prairie, soil 3rd rate.

Weston South Boundary of Sec. 39.

Var. 15° East.

\$2.00 Leave bluff, bears NW. and S.E.
\$0.00 Set sand stone, 15 x 12 x 4. for $\frac{1}{4}$ See, corner, as per instructions.
\$0.00 Deposited marked stone, set charred post, marked, built round and dug pits, as per instructions, for the Cos. to Secs. 33 and 34. Surface, first 20 chs. excepted, is rolling. Prairie. Soil 2nd rate.

Weston South Boundary of Sec. 33. Var. 15° East.

\$0.00 Set sand stone, 14 x 12 x 3. for $\frac{1}{4}$ See, corner, as per instructions.
\$8.00 Ravine. 60 lks. wide, course \$2.00

* \$0.00 Place for corner to Secs. 34 and 35, on bluff, impractical to establish same.

the 1st G. M. to the W. Boundary of the N. S. Reservation

Chains			
80.00	Set sand stone, 18x12x4, marked as per instructions, for the corner to Secs. 32 and 33. Surface rolling. Prairie. Soil 2 nd rate.	119 BOOK 1938	
	Weston South Boundary of Sec. 32. Var. 15 th East.		
40.00	Set granite, 14x10x4, for 1/4 Sec. cor., as per instructions.		
71.00	"Rio Carrissa". 15' 0 links wide, coarse ch.		
80.00	Set granite, 16x12x4, marked as per instructions, for the corner to Secs. 31 and 32. Surface rolling. Prairie. Soil 2 nd rate.		
	Weston South Boundary of Sec. 31. Var. 15 th East.		
5.00	"Rio Carrissa" 20 lks. wide, coarse S.W.		
19.50	"Rio Carrissa" coarse ch.		
40.00	Set sand stone, 14x12x3, for 1/4 Sec. corner, as per instructions.		
80.00	Set granite, 14x12x10, marked as per instructions, for the corner to Secs. 31 and 36, and Township 11 North, Range 9 & 10. West. Surface rolling. Prairie. Soil 2 nd rate.		
	Township 11 North. Range 10 E. Weston South Boundary of Sec. 36. Var. 15 th East.		
40.00	Set charred post and built mound for 1/4 Sec. corner, as per instructions.		
60.00	"Rio Carrissa" 25' 0 lks. wide, coarse S.W.		
80.00	Set sand stone, 20x10x3, marked as per instructions, for the corner to Secs. 35 and 36.		

Field Notes of the 2nd Standard Parallel from the 1st

Chains

120

BOOK

1938

Surface rolling. Prairie. Soil 2nd rate.

Weston South Boundary of sec. 35.
Twp. 15th East.

40.00 Set charred post and built mound
for 1/4 sec. corner, as per instructions.

80.00 Deposited marked stone, set
charred post, marked, built
mound and dug pits, as per
instructions, for the corner to
secs. 34 and 35.

Surface rolling. Prairie. Soil 2nd rate.

Weston South Boundary of sec. 34.

Twp. 15th East.

15.00 Sand stone bluff, bears N & S.

40.00 Place for 1/4 sec. corner on bluff
impracticable to establish
same.

80.00 Place for corner to secs. 33 and
34 on bluff. Impracticable
to establish same.

Surface mostly sand stone.
Soil 3rd rate.

Weston South Boundary of sec. 33.

Twp. 15th East.

25.00 Top of bluff, 400 feet high, bears
north and south.

Leave same.

40.00 Set sand stone, 14 x 12 x 3, for 1/4
sec. corner, as per instructions.

80.00 Deposited marked stone, set charred
post, marked, built mound and
dug pits, as per instructions, for
the corner to secs. 32 and 33.

Surface partly rolling,
Prairie. Soil 2nd rate.

1st G. M. to the West Boundary of the Navajo I. Res.

Chains	Weston South Boundary of sec. 32 Var. 15° E.	121 BOOK 1938
40.00	Set sand stone, 14 x 12 x 3. for § sec. corner, as per instructions. "Rio Carrissa", 200 lbs wide course north.	
53.00		
80.00	Deposited marked stone, set charred post, and built mound and dug pit, as per instructions, for the corner to Secs. 31 and 32. Surface level. Prairie. Soil 1 st rate.	

Weston South Boundary of sec. 31.
Var. 15° East,

1000	"Rio De Chille" Course north.
12.50	Leave same. High banks, sandy bottom and gentle current.
40.00	Set sand stone, 14 x 12 x 3. for § sec. corner, as per instructions.
64.00	Leave valley and foot of sand stone bluff, bears north and south.
80.00	Set sand stone, 20 x 10 x 4, marked as per instructions, for the corner to Secs. 31 and 36, and Township 11 north. Range 10 and 11 west. Surface level, except bluff. Prairie. Soil 1 st rate.

Impracticable to proceed any further
on line on account of the per-
pendicular sand stone bluff,
therefore offset north one mile,
thence west and at 60.50 chs.
intersect west boundary of
Navajo Indian Reservation.

170 links north of 61st mile
corner, therefore if the line
had been projected it would
have intersected the west
Boundary of the Navajo
Reservation 170 lbs. north

BOOK

1908

of the 60th mile corner,

October 12th 1869.

Measuring chain compared with
Standard and found correct.

Township 11 North.

Field Notes of the First Guide Meridian from the 2nd Standard Parallel to the North Boundary of the Navajo Indian Reservation.

North on East Boundary of Sec. 36.

Var. 14° 33' E.

37.80	Top of sand stone bluff, 250 feet high, bears 68° W.
40.00	Marked surface rock, for 1/4 sec. corner, as per instructions.
80.00	Deposited marked stone, set charred post, marked, built mound and dug pit, as per instructions, for the corner to Secs. 28, 30, 31 and 36. Surface broken. Prairie. Soil 3 rd rate.

North on East Boundary of Sec. 28.

Var. 15° East.

40.00	Set sand stone, 16 x 14 x 3. for 1/4 sec. cor. as per instructions.
72.00	Canon, 100 feet deep, course West.
79.00	Leave same.
80.00	Marked surface rock, as per instructions, for the corner to Secs. 19, 24, 28 and 30. Surface rolling. Prairie. Soil 2 nd rate.

North on East Boundary of Sec. 24.

Var. 15° 20' E.

10.00	Canon, 75 feet deep, course S.W.
13.50	Leave same.
40.00	Set charred post and built mound for 1/4 sec. corner as per instructions, for the corner to Secs. 13, 18, 19 and 24.

~~chains~~ Surface broken. Prairie. Soil 3rd rate. BOOK 1938

North on East Boundary of Sec. 13.
Twp. 15^e R. 8^w.

- 9.00 Ravine, 120 lks. wide, course West.
40.00 Set sand stone, 16 x 14 x 4. for 1/4 See
corner, as per instructions.
76.00 Ravine, 130 lks. wide, course West.
80.00 Set sand stone, 16 x 15 x 3. marked as
per instructions, for the corner to Secs.
7, 12, 13 and 18.
Surface broken. Prairie. Soil 3rd rate.

North on East Boundary of
Sec. 12. Twp. 15^e R. 8^w.

- 19.50 Ravine, 100 lks. wide, course West.
40.00 Set sand stone, 16 x 14 x 4. for 1/4 See
corner, as per instructions.
45.00 Edge of mesa, 15' feet high. bears E & W.
80.00 Set sand stone, 30 x 12 x 3. marked
as per instructions, for the corner to
secs. 1, 6, 7 and 12.
Surface rolling. Prairie. Soil 2nd rate.

North on East Boundary of Sec. 1.

Twp. 15^e R. 8^w.

- 40.00 Set sand stone, 14 x 12 x 3. for 1/4 See
corner, as per instructions.
80.00 Set sand stone, 26 x 14 x 8 marked as
per instructions, for the corner to
secs. 1, 6, 31 and 36, and
Townships 12 and 13 North.
Ranges 8 and 9 West.
Surface rolling. Prairie. Soil 2nd rate.

Field Notes of the First Guide meridian from the 2nd Standard

Chains 124 BOOK	1938	North on East Boundary of Sec. 1. Var. 15° 45' East.
3.20		Edge of Mesa, bears East and west.
4.00		Set sand stone, 14 x 10 x 4. for 1/4 sec. cor. as per instructions.
75.00		Canyon, 200 feet deep, course N. 20.
80.00		Place for corner in canon, impracticable to establish same. Set sand stone, 14 x 12 x 3. marked "W.C." 1.00 chn. East of place for corner for witness corner. Surface broken. Prairie. Soil 3 ⁴ rate.
		Township 12 North. North on East Boundary of Sec. 36. Var. 15° 45' E.
40.00		Set sand stone, 16 x 14 x 3. for 1/4 sec. cor. as per instructions.
80.00		Set sand stone, 20 x 16 x 2. marked as per instructions, for the corner to secs. 28, 30, 31 and 36. Surface broken. Prairie. Soil 3 ⁴ rate.
		North on East Boundary of Sec. 25. Var. 15° 45' E.
40.00		Marked surface rock for 1/4 sec. cor. as per instructions.
80.00		Set sand stone, 30 x 24 x 3. marked as per instructions, for the corner to secs. 19, 24, 28 and 30. Surface broken. Prairie. Soil 3 ⁴ rate.
		North on East Boundary of Sec. 24. Var. 15° 45' East.
40.00		Marked surface rock, for 1/4 sec. cor. as per instructions.
80.00		Set sand stone, 28 x 14 x 4. marked as per instructions, for the corner to secs. 18, 19 & 24.

parallel to the North Boundary of the N. Reservation.

Chains

Surface broken. Prairie. Soil 8% rate.

175
BOOK
1938

North on East Boundary of Sec. 13.

Var. 15° 45' East.

\$10.00 Set sand stone, 26 x 12 x 3. for 3/ See Cor. as per instructions.

\$80.00 Set granite, 15 x 8 x 6. marked as per instructions, for the corner to Secs. 7, 12, 13 and 18.

Surface broken. Prairie. Soil 3% rate.

North on East Boundary of Sec. 12.

Var. 15° 45' E.

\$31.00 Dry Creek 1.50 wide, course West.

\$40.00 Set sand stone, 14 x 14 x 3. for 4/ see corner. as per instructions.

\$56.50 Creek, 30 lba. wide, course West.

\$80.00 Set sand stone, 14 x 14 x 3. marked as per instructions. for the corner to Secs. 1, 6, 7 and 12.

Surface rolling. Prairie. Soil 2% rate.

North on East Boundary of Sec. 1.

Var. 15° 45' East.

\$40.00 Set sand stone, 14 x 12 x 3. for 3/ See corner. as per instructions.

\$80.00 Setsand stone, 26 x 14 x 8. marked as per instructions, for the corner to Secs. 1, 6, 31 and 36, and Townships 12 and 13 North.

Ranges 8 and 9 west

Surface rolling. Prairie.
Soil 2% rate.

Township 13th. North.

North on East Boundary of Sec. 36.

Var. 15° 45' East.

\$10.00 Set sand stone, 16 x 12 x 3. for 3/

Field notes of the First Guide Meridian from the

27 126 BOOK 1938	<p><u>Chains</u></p> <p>sec. corner, as per instructions. Set sand stone, 15 x 12 x 3. marked as per instructions, for the corner to Secs. 25, 30, 31 and 36. Surface broken. Prairie, Soil 2nd rate.</p> <hr/> <p><i>North on East Boundary of Sec. 25. Var. 15° 35' E.</i></p> <p>40.00 Set sand stone, 16 x 14 x 3. for 1/4 sec. corner as per instructions. 80.00 Deposited marked stone, set charred post marked, built mound and dug pit, as per instructions, for the corner to Secs. 19, 24, 25 and 30. Surface rolling. Prairie. Soil 2nd rate.</p> <hr/> <p><i>North on East Boundary of Sec. 24. Var. 15° 35' E.</i></p> <p>40.00 Set sand stone, 14 x 12 x 3. for 1/4 sec. cor. as per instructions. 80.00 Set sandstone, 30 x 18 x 2. marked as per instructions, for the corner to Secs. 13, 18, 19 and 24. Surface rolling. Prairie. Soil 2nd rate. Oct 13 ^{\$} 1869.</p> <hr/> <p><i>North on East Boundary of Sec. 13. Var. 15° 35' E.</i></p> <p>11.00 Dry bed of Creek, 40 lks. wide, course West. 40.00 Set sand stone, 14 x 12 x 4. for 1/4 sec. cor. as per instructions. 80.00 Set sand stone, 16 x 12 x 3. marked as per instructions, for the corner to Secs. 7, 12, 13 and 18. Surface rolling. Prairie. Soil 2nd rate.</p>
------------------------	--

2nd Standard Parallel to the South Boundary of the
Navajo Indian Reservation.

Chains run	North on East Boundary of Sec. 1, 2, Var. 15° 45' East.	177 BOOK 1938
40.00	Set sand stone, 18x14x6. for 1/4 sec. con. as per instructions.	
80.00	Set sand stone, 18x16x3. marked as per instructions, for the corner to Secs. 1, 6, 7 and 8. Surface rolling. Prairie. Soil 2 nd rate.	
	North on East Boundary of Sec. 1. Var. 15° 45' E.	
38.00	Dry bed of creek, 35 ¹ / ₂ lks. wide, course S.W.	
40.00	Set granite, 20 x 16 x 10. for 1/4 sec., corner, as per instructions.	
44.00	Ravine 30 lks wide, course S.W.	
72.00	Ravine 30 lks. wide, course S.W.	
80.00	Marked sand stone boulder 84 x 48 x 36. as per instructions, for the corner to Secs. 1, 6, 31 and 36. and Townships 13 and 14 North. Ranges 8 and 9 West. Surface broken, Prairie. Soil 2 nd rate.	
	Township 14 North. North on East Boundary of Sec. 36. Var. 15° 45' E.	
11.50	Edge of mesa, 400 feet high, bears East and West.	
40.00	Set charred post and built mound for 1/4 sec. corner, as per instruc- tions.	
58.50	Edge of mesa, bears East and West,	
80.00	Set sand stone, 14 x 12 x 8, marked as per instructions, for the corner to Secs. 20, 30, 31 & 36. Surface broken. Mesa covered with Cedar and Pinon, 3 rd rate. Soil 3 rd rate.	

Field dates of the First Guide Meridian from the

BOOK	Chains 128 1938	North on East Boundary of Sec. 25. Var. 16° East. Set sand stone, 14 x 10 x 6, for § sec., corner, as per instructions. Set sand stone, 18 x 12 x 6, marked as per instructions, for the corner to secs. 19, 24, 25 and 30. Surface broken. Prairie. Soil 3 rd rate.
	12,60 40,00 80,00	Ravine, 15 lks. wide, course 11.20. Set granite, 28 x 18 x 4, for § sec., corner, as per instructions, Set sand stone, 18 x 10 x 3, marked as per instructions, for the corner to secs. 13, 18, 19 and 24. Surface broken. Prairie. Soil 3 rd rate,
	40,00 80,00	North on East Boundary of Sec. 13. Var. 16° East. Set sand stone, 16 x 14 x 3, for § sec., corner, as per instructions. Set sand stone, 14 x 12 x 5, marked as per instructions, for the corner to secs. 7, 12, 13 and 18. Surface level. Prairie. Soil 1 st rate.
	40,00 80,00	North on East Boundary of Sec. 12. Var. 16° East. Set sand stone, 14 x 10 x 6, for § sec., cor. as per instructions, Set sand stone, 18 x 10 x 3, marked as per instructions, for the corner to secs. 1, 6, 7 and 12. Surface level. Prairie. Soil 1 st rate.

2nd Standard Parallel to the N. Boundary of the N.D. R.

chains

North on East Boundary of Sec. 1.

Var. 16° East.

129

BOOK 1938

40.00

Setsand stone, 18x12x3. for 4 sec. cor.
as per instructions.

80.00

Setsand stone, 18x10x3. marked as
per instructions. for the corner to Secs.
1, 6, 31 and 36, and Townships 14 and
15th North. Ranges 8 and 9 west,
Surface level. Prairie. Soil 1st rate.

40.00

North on East Boundary of Sec. 36.
Var. 16° East

45.80

Setsand stone, 18x10x3, for 4 sec cor.
as per instructions.

66.30

Ravine, 110 lks. wide, coarse west,
intersect North Boundary of
Reservation, 41. 20 chs. East of
19th mile, West of Territorial
corner.

Surface level. Prairie. Soil 1st rate
Completed October 14th 1887.

General Description of the First
Guide Meridian, from the First
Standard Parallel to the North
Boundary of the Navajo-Indian
Reservation, and the Second
Standard Parallel from the East
to the West Boundary of said
Reservation

The land along the Meridian for the
first seven miles is rolling, soil
2nd rate, covered with scattering
Pinon and cedar timber.

The next three miles and a half
runs over a mesa, 600 feet
in height. The balance of the
line runs over a level country,
soil 1st rate, well adapted to
either farming or grazing.

BOOK 1888

The Parallel runs over a gently rolling country, soil 1st and 2nd rate, covered with a fine variety of grass. About seven and a half miles from the Meridian, it crosses a ridge of red sand stone, gradually sloping up from the East and dropping off nearly perpendicular at the West. Estimated 350 feet high.

It then enters the valley of the "De Chille", which is level, 1st rate land. After crossing the river, it intersects sand stone bluff about 300 feet high, which is inaccessible.

We hereby certify that we assisted E. V. Darling U.S. Surveyor, in surveying the First Guide Meridian from the First Standard Parallel to the North Boundary of the Reservation and the Second Standard Parallel from the East to the West Boundary of the Navajo Indian Reservation, and that said meridian and Parallel have been in all respects to the best of our knowledge and belief, well and faithfully surveyed, and the boundary monuments planted according to the instructions furnished by the Commissioner of the General Land Office.

Willard S Paul Compassman.

William J Hare,
John Howe } Chainmen.

Robert S Darling.
Sheldon W Shafer } Cornermen.

BOOK 3
1938

Subscribed and sworn to, by the above named persons, before me, E. V. Darling, U.S. Surveyor, in Township 1 North, Range 6 West of the Navajo Special Meridian, in the Territory of Arizona this 28th day of January, 1869.

Ehud V. Darling,
U.S. Surveyor.

I, E. V. Darling, U.S. Surveyor, do solemnly swear that in pursuance of a contract with the Commissioners of the General Land Office, dated Washington D.C. April 29th, 1869, and in strict conformity to the laws of the United States, and the instructions furnished by the said Commissioner, I have faithfully surveyed the First Guide Meridian from the First Standard Parallel to the North Boundary of the Reservation and the Second Standard Parallel from the East to the West Boundary of the Navajo Indian Reservation and do further solemnly swear that the foregoing are the true and original field notes of such survey.

Ehud V. Darling
U.S. Surveyor.

Subscribed by said E. V. Darling, U.S. Surveyor, and sworn to before me, this 5th day of February A.D. 1870.

Wm. Breeden
Clerk U.S. District Court
1st Judicial Dist. of Mexico.

BOOK

1938

Department of the Interior.
General Land Office.

February 28th, 1870.

The foregoing field notes of the survey of the First Guide Meridian from the First Standard Parallel to the North Boundary of the Reservation and the Second Standard Parallel from the East Boundary to the West Boundary of the Navajo Indian Reservation in the Territories of New Mexico and Arizona, executed by E. H. C. Darling, U.S. Surveyor, under his contract with the Commissioner of the General Land Office, having been critically examined, the necessary corrections and explanations made, the said field notes and the surveys they describe, are hereby approved.

Jos. S. Wilson,
Commissioner

Department of the Interior
General Land Office

February 26th, 1877

A. J. Moulton

J. A. Williamson
Commissioner