Book "M."

(Subdivisions)

FIELD NOTES

OF THE SURVEY OF THE

	SUBDIVISION LINES
.	<u>of</u>
•	TOWNSHIP 3 NORTH, RANGE 5 WEST,
	·
Гn	Of the Gila and Salt River Base and Meridian, the State of Arizona.
	EXECUTED BY
	Woodbury Abbey, U. S. Surveyor,
-	and
	Roy J.Gill & Hans D.Woigt, U.S. Transitmen,
In	the capacity of U.S. Surveyor, under instructions dated December 12, , 1914
iss	ued by the United States Surveyor General to govern surveys included in
Gr	oup No39, which were approved by the Commissioner of the General Land
Off	ice, January 7, , 1915.
	Survey commenced MAY 4 , 191.5.

Executed under Assignment Instructions dated Dec. 12.1914 + from 26.1915

BOOK 3053

Book "M"
(Subdivisions)

Group 39 - Arizona.

INDEX DIAGRAM.

	Town	ship		3 N	orth,	· · · · · · · · · · · · · · · · · · ·	,	Range		5 West	•			
	6	24	5	1	8 4	•	4	3	1	0 2	5	1 -		
-	24		24		18			14		10		5		
	23	23	8 22	1	7 °	1	•	10 13	g	11 9	4	12 - 4	West	
	- 18 7	22	17	1	7 16	1	2	15	8	14	4	18 -	Meridian	,
	22	+	21		16)		12		0		2	—	
	19 ;	21	20	ב	6 21	1	2	22 11		, ₂₃	3	24 - 3	Guide	
		+	- 20					ale ale						
		20	29		5 28	1	<u>ի</u>	27		26 °	2	25	First	
	19	+	19		15			11		6	\dashv	2		
-	31	19	32	14	33	1	þ	34	6	35	1	36 -		
		.a. species		STORY OF			Bar 146, 2542	46.30	t setting					
		ſ		F	1	ļ	•		P	ı	P			
•	.	. Su	b div i	.sic	n lin	es s	ur	veyed	uı	nder th:	is	Group.		
_					ounda Book "		S '	urvey	ed	under	thi	s Group.		
=					ounda: Book "		r	esurv	eye	ed under	r t	his Group	•	
=					lines Book ".		ve	yed u	n d e	er this	Gr	oup.		
•					Lines Book			veyed	uı	nder thi	is	group.		
-		Ac	cepte	d s	ur v ey	s.								

Subdivision of T. 3 N. R. 5 W.

Survey of the east portion of the township commenced May 4, 1915, and executed jointly by Woodbury Abbey, U. S. Surveyor, using transit No. 8588, and Roy J. Gill, U. S. Transitman, using transit No. 8583; and survey of west portion of township commenced Dec. 6, 1915, and executed jointly by U. S. Transitmen Roy J. Gill and Hans D. Voigt, using instruments numbers 8147 and 8293, respectively on dates shown on the diagram on page 27 respectively. on dates shown on the diagram on page 27 of this book.

A complete description of the instruments used, with record of approval by the assistant supervisor of surveys, and field tests, appears in Book "B."

The lines surveyed by Abbey and Gill were originated by deflection from the transit line run from the SE. cor. W. to the SW. cor. of the Tp., during the survey of the S. bdy. described in Book "B," and the lines run by Gill and Voigt were originated from meridians determined by solar ovservations, a record of which follows herein.

The magnetic bearing of the true meridian, at 8h 00m, a.m., l.m.t., is N.14°30'W.; which gives for the mag. decl., 14°30' E.

MERIDIONAL OBSERVATIONS

	_		T (T T T T T T T T T T T T T T T T T T	ODO LEMIC	FUATION	D•
Kind	Station	Date 1915	Hour	Lat.	Decl.	Remarks
Solar	31 32 6 5 on S. bdy	Dec. 6	9h 30m A. M. 1. m. t.	3 3 °,331	2 2 °24'S	Long.,112°48 'W. by Roy J. Gill.
Solar	16 17 20 21	Dec. 7	8h 00m A. M. 1.m.t.	33°35 2 ₁	22° 2 9½';	S. Long.,112°47' W. by Hans D. Voigt
Solar	7 8 18 17	Dec. 7	8 h 30m A. M. 1. m. t.	,33°36∄†	22°30½1	3. Long. 112°48' W. by Roy J. Gill.

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., described in Book "B.

N.0°01'W., bet. secs. 35 and 36, over hilly desert, through scattering timber and dense undergrowth.

24.10

Wash, 30 lks. wide, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked 40.00

½ in N., S 35 in W., and S 36 in E. half; and 1915 in S. rim;

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,

Chains

W. of cor.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass 80.00 cap, marked

```
Subdivision of T. 3 N. R. 5 W.
Chains
                  T 3 N S 26 in NW.,
R 5 W S 25 in NE.,
S 36 in SE., and
S 35 in SW. quadrant; and
1915 in S. rim;
and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
                  W. of cor.
               Land, hilly and broken.
               Soil, gravelly; 2nd and 3rd rate.
               Timber, ironwood and paloverde.
               Undergrowth, greasewood, cactus and sage.
              East, on a random line, bet. secs. 25 and 36. Set temp. \(\frac{1}{4}\) sec. cor.

Intersect E. bdy. of Tp. 10 lks. N. of the cor. of secs.
 40.00
 79.96
                   25, 30, 31 and 36, on 1st G. M. W., described in Book
               Thence N.89°56'W., on a true line, bet. secs. 25 and 36, over broken and hilly desert, through scattering timber
              and dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked \( \frac{1}{4} \) S 25 in N., and, \( \frac{1}{4} \) S in S. half; and \( \frac{1}{2} \) in S. rim; \( \text{dig pits, } 18x18x12 \) ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3\( \frac{1}{2} \) ft. base, 1\( \frac{1}{2} \) ft. high,
 39.98
                   N. of cor.
               The cor. of secs. 25, 26, 35 and 36.
 79.96
                   Land, broken and hilly. Soil, rocky; 3rd rate.
                   Timber, paloverde and ironwood.
                   Undergrowth, greasewood, cactus and sage.
               N.0^{\circ}Ol_{\cdot}W., bet. secs. 25 and 26,
                   over broken hilly desert, through scattering timber and
                   dense undergrowth.
               Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} in N., S 25 in E., and S 26 in W. half; and 1915 in S. rim;
  40.00
                   and raise a mound of stone, 2 ft. base, l^{\frac{1}{2}} ft. high,
                   W. of cor.
               Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass
  80.00
                                                                                                     24 ins. in the
                    cap, marked
                   T 3 N S 23 in NW.,
R 5 W S 24 in NE.,
S 25 in SE., and
S 26 in SW. quadrant; and
1915 in S. rim;
and raise a mound of stone, 2 ft. base, l\frac{1}{2} ft. high,
                   W. of cor.
                Land, broken and hilly.
Soil, rocky; 2nd and 3rd rate.
Timber, ironwood and paloverde.
                Undergrowth, greasewood.
```

,	Subdivision of T. 3 N. R. 5 W.	
Chains		T
40.00 79.98	East, on a random line, bet. secs. 24 and 25. Set temp. \(\frac{1}{4} \) sec. cor. Intersect E. bdy. of Tp. 2 lks. N. of the cor. of secs. 19, 24, 25 and 30, on lst G. M. W., described in Book "A."	
39.99	Thence N.89°59'W., on a true line, bet. secs. 24 and 25, over broken and hilly desert, through scattering timber and dense undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., with brass cap, marked ½ S 24 in N. and , S 25 in S. half; and 1915 in S. rim; dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist. and raise a mound of earth, 3½ ft. base, 1½ ft. high,	
79.98	N. of cor. The cor. of secs. 23, 24, 25 and 26. Land, broken and hilly. Soil, gravelly; 2nd rate. Timber, paloverde and catclaw. Undergrowth, greasewood.	
40.00 48.00 57.00 80.00	N.0°01'W., bet. secs. 23 and 24, over broken desert, through scattering timber and dense undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ wec. cor., with brass cap, marked ½ in N., S 23 in W., and S 24 in E. half; and 1915 in S. rim; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Wash, 50 lks. wide, course W. Wash, 60 lks. wide, course W. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap, marked T 3 N S 14 in NW., R 5 W S 13 in NE., S 24 in SE., and S 23 in SW. quadrant; and 1915 in S. rim; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land, broken. Soil, rocky; 3rd rate. Timber, ironwood and paloverde. Undergrowth, greasewood.	W. W
40.00 80.08 28.00 40.04	East, on a random line, bet. secs. 13 and 24. Set temp. ½ sec. cor. Intersect E. bdy. of Tp. 12 lks. S. of the cor. of secs. 13, 18, 19 and 24, on 1st G. M. W., described in Book "A Thence S.89°55'W., on a true line, bet. secs. 13 and 24, over broken land, through scattering timber and dense undergrowth. Wash, 2 chs. wide, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the	11
	ground, for ½ sec. cor., with brass cap, marked ½ \$ 13 in N., and \$ 24 in S. half; and 1915 in S. rim; and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.	

```
Subdivision of T. 3 N., R. 5 W.
Cha ins
80.08
            The cor. of secs. 13, 14, 23 and 24.
                Land, broken.
                Soil, rocky; 2nd and 3rd rate.
               Timber, ironwood and paloverde.
                Undergrowth, greasewood.
            N.0°01'W., bet. secs 13 and 14,
over level land, through scattering timber and undergrowth.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
40.00
               ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} in N., \frac{1}{5} 13 in E., and \frac{1}{5} 14 in W. half; and
                                 1915 in S. rim;
               and raise a mound of stone, 2 ft. base, 12 ft. high,
                W. of cor.
            Bed of Hassayampa River, 2 chs. wide, course S.20°W.
Stream, 50 lks. wide, 3 ins. deep.
Point for cor. of secs. 11, 12, 13 and 14 falls in bed of River; therefore continue N.0°1'W., and at
42.50
80.00
            Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to the cor. of secs. 11, 12, 13 and 14, with brass cap, marked

WC in S. half,
82.70
                                T 3 N S 11 in NW.,
R 5 W S 12 in NE.,
S 13 in SE., and
S 14 in SW. quadrant; and
                                 1915 in S. rim;
               and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
               W. of cor.
            Land, level. Soil, sandy; 1st rate.
            Timber, paloverde.
            Undergrowth, greasewood and sage.
            East, on a random line, bet. secs. 12 and 13, from true pt. for cor. of secs. 11, 12, 13 and 14. Set temp. 1 sec. cor. Intersect E. bdy. of Tp. 10 lks. S. of the cor. of secs.
40.00
80.06
               7, 12, 13 and 18, on 1st G. M. W., described in Book "A."
            Thence S.89°56'W., on a true line, bet. secs. 12 and 13, over broken desert, through scattering timber and dense
               undergrowth.
            Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked \( \frac{1}{4} \) S 12 in N. and
40.03
                                 $ 13 in S. half; and 1915 in S. rim;
               and raise a mound of stone, 2 ft. base, 12 ft. high,
            N. of cor.
Enter river bottom; bears N. and S.
Hassayampa River, stream 20 lks. wide, 1 in. deep, course
66.00
69.00
            The true pt. for cor. of secs. 11, 12, 13 and 14.

Land, 66 chs. broken desert, and balance river bottom.

Soil, rocky; 2nd and 3rd rate.

Timber, paloverde and ironwood.
80.06
               Undergrowth, greasewood.
                  From true pt. for cor. of secs. 11, 12, 13 and 14,
            N.0°01'W., bet. secs. 11 and 12,
               over level river bottom, through sparse timber and
```

undergrowth.

```
Subdivision of T. 3 N. R. 5 W.
Chains.
 2:70
            Witness cor.to cor.of secs.11,12,13 & 14, hereinbefore described
            Dry bed of Hassayampa River, 2 chs. wide, course S.20°E. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked
18.00
40.00
               ground, for $\frac{1}{4}$ sec. cor., with stass cap, marked $\frac{1}{4}$ in N.,
$$ 11 in W., and
$$ 12 in E. half; and
$$ 1915 in S. rim;
$$ dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,
and raise a mound of earth, $$\frac{1}{2}$ ft. base, $$\frac{1}{2}$ ft. high,
                W. of cor.
            Dry bed of Hassayampa River, 2 chs. wide, course S.20°W. Road bears NE. and SW.
52.00
68.00
            Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass
80.00
                cap, marked
                                  T 3 N S 2 in NW.,
R 5 W S 1 in NE.,
                                  S 12 in SE., and
                                  S 11 in SW. quadrant; and
                1915 in S. rim; and raise a mound of stone, 2 ft. base, l^{\frac{1}{2}} ft. high,
                W. of cor.
             Land, level river bottom.
             Soil, sandy; 1st rate.
            Timber, paloverde.and
            Undergrowth, greasewood.
            East, on a random line, bet. secs. 1 and 12.

Set temp. ½ sec.cor.

Intersect E. bdy. of Tp. 12 lks. S. of the cor. of secs.

1, 6, 7 and 12, on 1st G. M. W., described in Book "A."
40.00
79.98
             Thence S.89°55'W., on a true line, bet. secs. 1 and 12, over level desert, through scattering timber and dense
                undergrowth.
            Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} S 1 in N., and S 12 in S. half; and
39.99
                                   1915 in S. rim;
                dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high,
                N. of cor.
             Hassayampa River, stream 20 lks. wide, 3 ins. deep, course
57.50
                 S.; thence across level river bottom.
             Dry bed of Hassayampa River, 2.80 chs. wide, course S.
77.60
             Road bears N. and S.
The cor. of secs. 1, 2, 11 and 12.
Land, level.
77.80
79.98
                 Soil, gravelly; 2nd rate.
                 Timber, paloverde and ironwood.
                Undergrowth, greasewood and sage.
             N.0°01'W., on a random line, bet. secs. 1 and 2. Set temp. 4 sec. cor. Intersect N. bdy. of Tp. 2 lks. E. of the cor. of secs.
40.00
 79.99
                 1, 2, 35 and 36, described in Book "B."
             Thence S.0°02'E., on a true line, bet. secs. 1 and 2, over broken and hilly desert, through scattering timber
                 and dense undergrowth.
             Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} in N.,
39.99
                                   $\frac{1}{5} \text{l in \text{\text{E.}, and}} \\ \text{S 2 in W. half; and} \end{area}
```

1915 in S. rim;

```
Subdivision of T. 3 N., R. 5 W
  Chains
              Land, level in river bottom and broken in balance.
              Soil, gravelly; 1st and 2nd rate.
              Timber, ironwood and paloverde.
              Undergrowth, greasewood and cactus.
           N.0°01'W., bet. secs. 26 and 27, over broken and hilly desert, through scattering timber
              and dense undergrowth.
40.00
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins.
              ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} in N.,
S 26 in E., and
S 27 in W. half; and
1915 in S. rim;
              and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
              W. of cor.
68.00
           Draw, course E.
           Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass
80.00
              cap, marked
                              T 3 N S 22 in NW.,
R 5 W S 23 in NE.,
S 26 in SE., and
S 27 in SW. quadrant; and
                              1915 in S. rim;
              and raise a mound of stone, 2 ft. base, 12 ft. high,
           W. of cor.
Land, hilly and broken.
           Soil, rocky; 3rd rate.
           Timber, ironwood, mesquite and paloverde.
           Undergrowth, greasewood and cactus.
           East, on a random line, bet. secs. 23 and 26. Set temp. ½ sec. cor. Intersect N. and S. line 14 lks. N. of the cor. of secs.
40.00
80.18
              23, 24, 25 and 26.
           Thence N.89°54' W., on a true line, bet. secs. 23 and 26, over level riverbottom, through scattering timber and
          dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked \(\frac{1}{4}\) S 23 in N., and \(\frac{1}{2}\) S 26 in S. half; and
40.09
                              1915 in S. rim;
              dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dis and raise a mound of earth, 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high,
                                                                                     3 ft. dist.,
              N. of cor.
          Bed of Hassayampa River, 2 chs. wide, course S. Stream, 50 lks. wide, 3 ins. deep, course S. Road bears N. and S.
47.00
48.50
80.18
          The cor. of secs. 22, 23, 26 and 27.

Land, level river bottom.

Soil, gravelly; 2nd rate.

Timber, paloverde, ironwood and mesquite.
              Undergrowth, greasewood and catclaw.
           N.0°01'W., bet. secs. 22 and 23, over hilly desert, through scattering timber and dense
              undergrowth.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
40.00
              ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
```

```
Subdivision of T. 3 N., R. 5 W
Chains
                                   in N.,
22 in W., and
S 23 in E. half; and
1915 in S. rim;
                 and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
                 W. of cor.
             Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass
 80.00
                 cap, marked
                                   T 3 N S 15 in NW.,
R 5 W S 14 in NE.,
S 23 in SE., and
S 22 in SW. quadrant; and
                                   1915 in S. rim;
                 and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
                 W. of cor.
              Land, hilly and broken desert. Soil, rocky; 3rd rate.
              Timber, ironwood and paloverde.
              Undergrowth, greasewood and cactus.
              East, on a random line, bet. secs. 14 and 23. Set temp. \frac{1}{4} sec. cor.
 40.00
              Intersect N. and S. line 10 lks. S. of the cor. of secs.
 80.04
                  13, 14, 23 and 24.
              Thence S.89°56'W., on a true line, bet. secs. 14 and 23, over level river bottom, through scattering timber and
                  dense undergrowth.
 16.00
              Bed of Hassayampa River, 2½ chs. wide, course S.; stream
              50 lks. wide, 3 ins. deep, Road bears N. and S.
 38.50
40.02
              Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked \( \frac{1}{4} \) $14 in N., and ,
                 $ 14 in N., and,
$ 23 in S. half; and
$ 1905 in S. rim;
dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.,
and raise a mound of earth, 3½ ft. base, 1½ ft. high,
                 N. of cor.
              Leave river bottom and enter broken land; bears N. and S. The cor. of secs. 14, 15, 22 and 23.

Land, E. 56 chs. level and balance broken.

Soil, gravelly; 2nd rate.
  56.00
  80.04
                  Timber, ironwood and paloverde.
                  Undergrowth, greasewood and catclaw.
              N.O°OI'W., bet. secs. 14 and 15,
                  over hilly land, through scattering timber and dense
                 undergrowth:
              Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked
 40.00
                                       in N.,
                 in N.,
$\frac{1}{5}$ 14 in E., and
$\frac{1}{5}$ 15 in W. half; and
$\frac{1}{5}$ 10 S. rim;

dig pits, $18\times18\times12$ ins., N. and S. of post, 3 ft. dist.,
and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,
                  W. of cor.
              Wash, 60 lks. wide, course SE.
Set an ironpost, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor, of secs. 10, 11, 14 and 15, with brass
  50.00
  80.00
                  cap, marked
                                   T 3 N S 10 in N
R 5 W S 11 in N
S 14 in SE., and
                                               S 10 in NW.,
S 11 in NE.,
                                    S 15 in SW. quadrant; and 1915 in S. rim;
```

```
Subdivision of T. 3 N. R.
Cha ins
             and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high.
             W. of cor.
          Land, broken and hilly.
          Soil, gravelly; 2nd rate.
          Timber, ironwood, paloverde and mesquite.
          Undergrowth, greasewood, catclaw and cactus.
          East, on a random line, bet. secs. 11 and 14.
          Set temp. \(\frac{1}{4}\) sec. cor.

Intersect N. and S. line 5 lks. S. of the true pt. for cor.

of secs. 11, 12, 13 and 14.
40.00
80.20
           Thence S.89°58'W., on a true line, bet. secs. 11 and 14,
              across dry bed of Hassayampa River, course S.
            Leave bed of river; thence over level river bottom, through
   3.00
               scattering timber and dense undergrowth.
            Road bears N. and S.
 26.00
            Leave river bottom; bears N. and S.; thence over broken
 32.00
               land.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} S 11 in N., and
 40.10
                              $ 14 in S. half; and
                              1915 in S. rim:
               and raise a mound of stone, 2 ft. base, 12 ft. high,
           N. of cor.
The cor. of secs. 10, 11, 14 and 15.
Land, level river bottom for E. 32 chs., and broken for balance.

2nd rate.
 80.20
               Timber, paloverde and ironwood.
               Undergrowth, greasewood.
            N.0°01'W., bet. secs. 10 and 11, over rolling land, through scattering timber and dense
               undergrowth.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked
 40.00
               $\frac{1}{4}$ in N.,
$\frac{1}{5}$ in in W., and
$\frac{1}{5}$ in E. half; and
$1915$ in S. rim;
$\frac{1}{5}$ dig pits, $18x18x12$ ins., N. and S. of post, 3 ft. dist.,
and raise a mound of earth, $\frac{1}{5}$ ft. base, $1\frac{1}{5}$ ft. high,
               W. of cor.
            Wash, 100 lks. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass
 60.00
 80.00
               cap, marked
              T 3 N S 3 in NW.,

R 5 W S 2 in NE.,

S 11 in SE., and

S 10 in SW. quadrant; and

1915 in S. rim;

and raise a mound of stone, 2 ft. base, 1½ ft. high,
               W. of cor.
            Land, rolling.
            Soil, gravelly; 2nd rate.
            Timber, ironwood, paloverde and mesquite.
            Undergrowth, greasewood and sage.
```

```
Subdivision of T. 3 N., R. 5 W.
10
   Chains
               East, on a random line, bet. secs. 2 and 11.
              Set temp. \frac{1}{4} sec. cor. Intersect N. and S. line at the cor. of secs. 1, 2, 11 and
    40.00
    80.20
                  12.
               Thence West, on a true line, bet. secs. 2 and 11, over broken land, through scattering timber and dense
                  undergrowth.
              Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} S 2 in N., and
    40.10
                                 S 11 in S. half; and
                                 1915 in S. rim;
                  and raise a mound of stone, 2 ft. base, 11 ft. high.
                  N. af cor.
              Wash, 50 lks. wide, course S. The cor. of secs. 2, 3, 10 and 11.
    78.00
    80.20
                  Land, broken.
                  Soil, gravelly; 2nd rate.
                  Timber, ironwood and paloverde.
                 Undergrowth, greasewood and sage.
              N.O°Ol'W., on a random line, bet. secs. 2 and 3. Set temp. \(\frac{1}{4}\) sec. cor.
Intersect N. bdy. of Tp. 25 lks. W. of the cor. of secs.
    40.00
80.36
                  2, 3, 34 and 35, described in Book "B.
               Thence S.O°10'W., on a true line, bet. secs. 2 and 3,
                  over slightly broken land, through scattering timber
                 and dense undergrowth.
              Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{2} \) sec. cor., with brass cap, marked
    40.36
                 ground, for \frac{1}{4} sec.
                                 Š 2 in É., and
                                 S 3 in W. half; and
                 1915 in S. rim; and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
                 W. of cor.
              Wash, 301ks. wide, course SE. The cor. of secs. 2, 3, 10 and 11.
                  Land, slightly broken.
                  Soil, gravelly; 2nd rate.
                 Timber, ironwood, paloverde and catclaw.
                 Undergrowth, greasewood, cactus and catclaw.
              From the cor. of secs. 3, 4, 33 and 34, on S. bdy., described in Book "B."
              N.0°02'W., bet. secs. 33 and 34, over rolling desert, through scattering timber and dense
                 undergrowth.
              Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., with brass cap, marked ½ in N.,

S 33 in W., and
S 34 in E. half; and
1915 in S. rim;
and raise a mound of stone, 2 ft. base, 1½ ft. high,
W. of cor.
    40.00
                 W. of cor.
              Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass
    80.00
                 cap, marked
                                T 3 N S 28 in NW.
                                R 5 W S 27 in NE.,
```

S 34 in SE., and

```
Subdivision of T. 3 N. R. 5 W.
Chains
                              S 33 in SW. quadrant; and 1915 in S. rim;
              and raise a mound of stone, 2 ft. base, 12 ft. high,
              W. of cor.
           Land, broken and hilly.
Soil, rocky; 2nd and 3rd rate.
Timber, ironwood and paloverde.
           Undergrowth, greasewood and cactus.
           East, on a random line, bet. secs. 27 and 34,
           Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line 5 lks. S. of the cor. of secs. 26.
40.00
80.06
              27, 34 and 35.
           Thence S.89°58'W., on a true line, bet. secs. 27 and 34,
              over hilly desert, through scattering timber and dense
              undergrowth.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{2} sec. cor., with brass cap, marked \frac{1}{2} S 27 in N., and , S 34 in S. half; and 1915 in S. rim;
40.03
              and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
              N. of cor.
           The cor. of secs. 27, 28, 33 and 34. Land, hilly. Soil, rocky; 3rd rate.
80.06
              Timber, ironwood and paloverde.
              Undergrowth, greasewood and cactus.
           N.0^{\circ}02^{\dagger}W., bet. secs. 27 and 28,
              over slightly broken desert, through scattering timber
          and dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked \( \frac{1}{4} \) in N.,

S 27 in E., and
S 28 in W. half; and
1915 in S. rim;
dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.,
and raise a mound of earth, \( \frac{1}{2} \) ft. base, \( \frac{1}{2} \) ft. high,

W. of cor.
              and dense undergrowth.
40.00
              W. of cor.
           set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass
80.00
              cap, marked
                              T 3 N S 21 in NW.,
R 5 W S 22 in NE.,
S 27 in SE., and
                              S 28 in SW. quadrant; and
                              1915 in S. rimp
              and raise a mound of stone, 2 ft. base, 12 ft. high,
              W. of cor.
           Land, broken.
           Soil, rocky; 2nd and 3rd rate.
           imber, ironwood and paloverde.
           Undergrowth, greasewood, catclaw and sage.
           East, on a random line, bet. secs. 22 and 27.
           Set temp. 4 sec. cor. Intersect N. and S. line 12 lks. N. of the cor. of secs.
40.00
80.06
              22, 23, 26 and 27.
           Thence N.89°55'W., on a true line, bet. secs. 22 and 27, over broken and hilly land, through scattering timber and
```

dense undergrowth.

2	Subdivision of T. 3 N., R. 5 W.
Chains	
40.03	ground, for ½ sec. cor., with brass cap, marked ½ S 22 in N., and , S 27 in S. half; and
80.06	1915 in S. rim; and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. The cor. of secs. 21, 22, 27 and 28. Land, broken and hilly. Soil, rocky; 2nd and 3rd rate. Timber, paloverde and ironwood. Undergrowth, greasewood and sage.
40.00	N.0°02'W., bet. secs. 21 and 22, over slightly broken desert, through scattering timber and dense undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked \(\frac{1}{4} \) in N., \(\frac{5}{21} \) in W., and
The second particular and the second particu	S 22 in E. half; and 1915 in S. rim; dig pits, $18x18x12$ ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00	
	1915 in S. rim; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land, slightly broken. Soil, gravelly; 2nd rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cactus.
40.00 79.92	
39.96	
	ground, for ½ sec. cor., with brass cap, marked ½ \$ 15 in N., and \$ 22 in S. rim; and 1915 in S. rim;
79•9	and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high, N. of cor. The cor. of secs. 15, 16, 21 and 22. Land, slightly broken. Soil, rocky; 2nd and 3rd rate. Timber, paloverde and ironwood. Undergrowth, greasewood.
The second secon	
	N.0°02'W., bet. secs. 15 and 16, over level desert, through scattering timber and dense undergrowth.

```
Subdivision of T. 3 N. R. 5 W
Chains
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} in N., S 15 in E., and S 16 in W. half; and 1915 in S. rim;
40.00
              dig pits, 18x18x12 ins., N. and S. of post, 3 ft. distand raise a mound of earth, 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high,
              W. of cor.
           Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass
80.00
              cap, marked
                              T 3 N S 9 in NW.,
R 5 W S 10 in NE.,
S 15 in SE., and
S 16 in SW. quadrant; and
                              1915 in S. rim;
              and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
              W. of cor.
           Land, level.
Soil, rocky; 3rd rate.
           Timber, paloverde and ironwood.
           Undergrowth, greasewood and sage.
           East, on a random line, bet. secs. 10 and 15.
           Set temp. ½ sec. cor. Intersect N. and S. line 32 lks. N. of the cor. of secs.
40.00
79.90
              10, 11, 14 and 15,
           Thence N.89°46'W., on a true line, bet. secs. 10 and 15,
              over level desert, through scattering timber and dense
              undergrowth.
           Wash, 30 lks. wide, course SE.
Set an iron pest, 3 ft. long, l in. diam., 26 ins. in the ground, for 4 sec.cor., with brass cap, marked

4 S 10 in N., and
11.90
39.95
              $ 10 in N., and,
$ 15 in S. half; and
1915 in S. rim;
and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
              N. of cor.
          Old road bears NW. and SE.
The cor. of secs. 9, 10, 15 and 16.
Land, level in W. half, and slightly rolling in E.
48.40
79.90
              Soil, gravelly; 2nd rate.
              Timber, paloverde and ironwood.
              Undergrowth, greasewood.
              0°02'W., bet. secs. 9 and 10, over slightly rolling desert, through scattering timber
          and dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
40.00
              ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
                             in N.,
S 9 in W., and
S 10 in E. half; and
                              1915 in S. rim;
              and raise a mound of stone, 2 ft. base, 1 ft. high.
              W. of cor.
          Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass
80:00
              cap, marked
                             T 3 N S 4 in NW.,
R 5 W S 3 in NE.,
                             S 10 in SE., and
S 9 in SW. quadrant; and
1915 in S. rim;
```

```
14
                              Subdivision of T. 3 N. R.
    Chains
                and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high.
                W. of cor.
             Land, slightly rolling.
             Soil, gravelly; 2nd rate.
             Timber, paloverde.
             Undergrowth, greasewood and sage.
             East, on a random line, bet. secs. 3 and 10. Set temp. \frac{1}{4} sec. cor. Intersect N. and S. line 16 lks. N. of the cor. of secs.
    40.00
    79.88
                2, 3, 10 and 11.
             Thence N.89°53'W., on a true line, bet. secs. 3 and 10,
                over slightly rolling land, through scattering timber
                and dense undergrowth.
             Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked \( \frac{1}{4} \) S 3 in N., and,
    39.94
                              $ 10 in S. half; and
                1915 in S. rim; and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
             N. of cor.
The cor. of secs. 3, 4, 9 and 10.
    79.88
                Land, slightly rolling.
                Soil, gravelly; 2nd rate.
                Timber, ironwood and paloverde.
                Undergrowth, greasewood and cactus.
             N.0°02'W., on a random line, bet. secs. 3 and 4. Set temp. \frac{1}{4} sec. cor.
             Set temp. \frac{1}{4} sec. cor. Intersect N. bdy. of Tp. 5 lks. W. of the cor. of secs.
    40.00
    80.31
                3, 4, 33 and 34, described in Book "B."
             Thence South, on a true line, bet secs. 3 and 4, over level desert, through scattering timber and dense
                undergrowth.
    40.31
             Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
                ground, for \frac{1}{4} sec. cor., with brass cap, marked
                              ½ in N.,
S 3 in E., and
                              S 4 in W. half; and
                              1915 in S. rim;
                dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high,
                W. of cor.
             The cor. of secs. 3, 4, 9 and 10.
    80.31
                Land, level desert.
                Soil, gravelly; 2nd rate.
                Timber, paloverde.
                Undergrowth, greasewood.
             From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp., described in Book "B,"
             N.0^{\circ}02 W., bet. secs. 32 and 33.
                over slightly rolling land, through dense timber and
                undergrowth.
             set an iron post, 3 ft. long, 1 in. diam, 26 ins. in the
   40.00
                ground, for \( \frac{1}{4} \) sec.cor., with brass cap, marked \( \frac{1}{4} \) in N.,
\( \text{S} \) 32 in W., and
                             S 33 in E. half; and 1915 in S. rim;
```

```
Subdivision of T. 3 N. R. 5 W.
Chains
              dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high,
              W. of cor.
           Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, with brass
80.00
              cap, marked
                              T 3 N S 29 in NW.,
R 5 W S 28 in ME.,
S 33 in SE., and
S 32 in SW. quadrant; and
1915 in S. rim;
              dig pits, 18x18x12 ins., in each sec., 5\frac{1}{2} ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.
           Land, slightly rolling.
           Soil, gravelly; 2nd rate.
           Fimber, paloverde and ironwood.
           Undergrowth, greasewood, cactus and catclaw.
           East, on a random line, bet. secs. 28 and 33.
          Set temp. ½ sec. cor.
Intersect N. and S. line 5 lks. S. of the cor. of secs.
27, 28, 33 and 34.
40.00
80.02
           Thence S.89°58'W., on a true line, bet. secs. 28 and 33, over nearly level desert, through scattering timber and
              dense undergrowth.
          Wash, 60 lks. wide, course S.
Wash, 50 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked 4 S 28 in N., and 5 33 in S. half; and 1915 in S. rim;
35.50
39.00
40.01
              and raise a mound of stone, 2 ft. base, 1 ft. high,
           N. of cor.
The cor. of secs. 28, 29, 32 and 33.
80.02
              Land, nearly level.
Soil, rocky; 2nd and 3rd rate.
              Timber, ironwood and paloverde.
              Undergrowth, greasewood and cactus.
          N.0°02'W., bet. secs. 28 and 29, over hilly desert, through scattering timber and dense
             undergrowth.
          Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
40.00
             ground, for \frac{1}{4} sec. cor., with brass cap, marked \frac{1}{4} in N., S 28 in E., and S 29 in W. half; and
                              1915 in S. rim;
              and raise a mound of stone, 2 ft. base, 12 ft. high,
              W. of cor.
          Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass
80.00
              cap, marked
                             T 3 N S 20 in NW.,
R 5 W S 21 in NE.,
S 28 in SE., and
                             S 29 in SW. quadrant; and 1915 in S. bim;
             and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high,
          W. of cor.
Land, broken and hilly.
           Soil, rocky; 3rd rate.
           Timber, ironwood and paloverde.
           Undergrowth, greasewood and cactus.
```

Chains	Subdivision of T.3 N.R.5 W.
79.92	The cor. of secs. 16, 17, 20 and 21.
	Land, slightly broken.
	Soil, gravelly and rocky, 3rd rate.
	Timber, iron wood, mesquite and palo verde. Undergrowth, greasewood, cacti and cat claw.
	ondergrowen, greasewood, cacti and cat claw.
	<u> </u>
	N OO OI W hat many 16 and 18
	N. 0° 2' W. bet. secs. 16 and 17. Over gently rolling land, through scattering timber and
a vicani	undergrowth.
2.80	S. bank of wash, 4 ft. deep, course, E.
3.90	N. bank of wash, course, E.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
,	the ground for \frac{1}{4} sec. cor. with brass cap mkd.
	S 17 :S 16
	. 1 91 5
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high
75 50	W. of cor.
75.50 75.80	S. bank of wash, 4 ft. deep, course, E. N. bank of wash, 4 ft. deep, course, E.
80.00	Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. in
	the ground for cor. of secs. 8, 9, 16 and 17, with
	brass cap mkd.
The state of the s	T 3 N R 5 W
	<u>S 8 :S 9</u> S 17:S 16
	1915
The state of the s	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high
	W. of cor.
	Land, gently rolling.
•	Soil, rocky, 3rd rate.
	Timber, scattering palo verde. Undergrowth, greasewood, sagebrush and cadi.
	East on a random line bet. secs. 9 and 16.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect N. and S. line 10 lks. N. of cor. of secs.
	9, 10, 15 and 16.
100	Thence
	N. 89° 56' W. on a true line bet. secs. 9 and 16.
	Over gently rolling land, though scattering timber and undergrowth.
39.97	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
	the ground for \(\frac{1}{2} \) sec. cor. with brass cap mkd.
	4 <u>8 9</u> 4 5 16
	*S 16 1916
	dig pits 18 X 18 X 12 ins. E. and W. of post, 3 ft.
	dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft.
	high N. of cor.
63.75	Wash, 30 lks. wide, 4 ft. deep, course, SE.
67.70	Wash, 70 lks wide, 3 ft. deep, course, SE.
74.30 79.94	Wash, 30 lks. wide, 3 ft. deep, course, S. Cor. of secs. 8, 9, 16 and 17.
10.04	Land, gently rolling.
	Soil, rocky, 3rd rate.
	Timber, scattering palo verde.
	Undergrowth, greasewood, sagebrush, cat claw.
	N. 0° 2' W. bet. secs. 8 and 9.
	Through timber and undergrowth.
8.10	Wash, 65 lks. wide, 5 ft. deep, course, S. 70° E.
	A Company of the Comp

80.03

Cor. of secs. 4, 5, 8 and 9.

```
18
                    Subdivision of T.3 N. R.5 W.
 Chains
           S. bank of wash, 5 ft. deep, course, E. N. bank of wash.
 13.50
 18.10
           Enter wash, 30 lks. wide, 8 ft. deep, course, SW.
Leave wash, course, SW.
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
the ground for 4 sec. cor. with brass cap mkd.
 30.00
 39,20
 40.00
                                  S 8:S 9
                                   1915
           dig pits 18 X 18 X 12 ins. N. and S. of cor. 3 ft. dist.
                and raise a mound of earth 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high
                W. of cor.
           Set an iron post 3 ft. long, 2 ins. in diam., 26 ins. the ground for cor. of secs. 4, 5, 8 and 9, with
 80.00
                                                                     26 ins. in
                brass cap mkd.
                                  T 3 N R 5 W
                                   S 5 :S 4
S 8 :S 9
                                     1915
                and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high
                W. of cor.
          Land, rolling.
Soil, rocky, 3rd and 4th rate.
Timber, palo verde.
           Undergrowth, greasewood, cat claw and cacti.
           East on a random line betweecs. 4 and 9: and 9.
 40.00
           Set temp. # sec. cor.
 79.92
           Intersect N. and S. line, 30 lks. N. of cor. of secs.
                3, 4, 9 and 10.
           Thence
           N. 89° 47' W. on a true line bet. secs. 4 and 9.
           Over rolling land, through scattering timber and under-
                growth.
           Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
 39.96
                the ground for 4 sec. cor. with brass cap mkd.
                                  S 4
                               # S 9
                                  1915
                dig pits 18 X 18 X 12 ins. E and W. of cor. 3 ft.
                dist. and raise a mound of earth 3\frac{1}{2} ft. base, 1\frac{1}{2} ft.
           high N. of cor.
Wash, 120 lks. wide, course, S.
Cor. of secs. 4, 5, 8 and 9.
 73.10
 79.92
           Land, rolling.
           Soil, stony, 3rd and 4th rates.
           Timber, scattering palo verde.
           Undergrowth, greasewood, cat claw and cacti.
           N. 0° 2' W. on a random line bet. secs. 4 and 5.
           Set temp. 1 sec. cor
 40.00
           Intersect N. bdy. of tp. 6 lks. E. of cor. of secs. 4, 5, 32 and 33, as described in book "B.".
 80.03
           Thence
           S. 0° 5' E. on a true line bet. secs. 4 and 5.
           Over gently rolling land, through scattering timber
                and undergrowth.
           Wash, 30 lks. wide, 4 ft. deep, course, E. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
 17.70
 40.03
                 the ground, for 4 sec. cor. with brass cap mkd.
                                  S 4:S 5
                                   1915
                 and raise a mound of stone, 2 ft. base, 12 ft. high
                W. of cor.
```

```
Subdivision of T.3 N.R.5 W.
                                                                               19
 Chains
          Land, gently rolling.
          Soil, rocky, 3rd and 4th rates. Timber, scattering palo verde.
          Undergrowth, greasewood, cat claw and cacti.
          From the cor. of secs. 5, 6, 31 and 32, on S. bdy. of tp. described in book "B"."
          N. 0° 3' W. bet. secs. 31 and 32.
          Over level land, through scattering timber and under-
              growth.
40,.00
          Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
              the ground for \frac{1}{4} sec. cor. with brass cap mkd.
                               S 31:S 32
              1915 dig pits 18 X 18 X 12 ins. N. and S. of post, 3 ft. dist. and raise a mound of earth, 3\frac{1}{2} ft. base, 1\frac{1}{2} ft.
              high W. of cor.
         Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in
00.08
              the ground for cor. of secs. 29, 30, 31 and 32, with
              brass cap mkd.
                               T 3 N R 5 W
                                 S 30:S 29
                                   31:8.32
                                   1915
              and raise m mound of stone, 2 ft. base, 1\frac{1}{2} ft. high
              W. of cor.
         Land, level.
                        3rd rate.
         Soll, rocky,
         Timber, scattering palo verde. Undergrowth, greasewood, cat claw and cacti.
         East on a random line bet. secs. 29 and 32.
40.00
         Set temp. \(\frac{1}{2}\) sec. cor.
79.92
         Intersect N. and S. line, at cor. of secs. 28, 29, 32 and
              33.
         Thence
         West on a true line bet. secs. 29 and 32.
         Over rolling land, through scattering timber and under-
              growth.
20.27
         Asc. 97 ft. to
         Point of spur slopes S., desc. W. slope, 115 ft. to
28.47
39.96
         Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
              the ground for \frac{1}{4} sec. cor. with brass cap mkd.
                               1915
              and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high
              N. of cor.
         Thence over gent, y rolling land, through dense undergrowth. Cor. of secs. 29, 30, 31 and 32. Land, rolling and hilly. Soil, rocky, 3rd and 4th rate.
79.92
         Timber, scattering palo verde.
         Undergrowth, greasewood, cat claw, ocotillos and cacti.
         West on a random line bet. secs. 30 and 31.
40.00
         Set temp. \frac{1}{4} sec. cor.
         Intersect W. bdy. of tp. 8 lks. N. of cor. of secs.
76.35
              25, 30, 31 and 36, and described in book "B:
         N. 89° 57' E. on a true line bet. secs. 30 and 31.
         Over rolling land, through scattering timber and under-
```

growth.

- 1	20.	Subdivision of T.3 N., R.5 W.
	Chains 36.35	Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for \(\frac{1}{4}\) sec. cor. with brass cap mkd.
	40.00	18 30 48 31 1915 and raise a mound of stone, 2 ft. base, 1½ ft. high N. of cor. Asc. gradual slope 77 ft. to
Andrew Martine Martine Martine Control of the Andrew Martine Control of	68.10 76.35	Top of ridge. Desc. 102 ft. to Cor. of secs. 29, 30, 31 and 32. Land, rolling and hilly. Soil, rocky, 3rd and 4th rates. Timber, scattering palo verde.
	·	Undergrowth, greasewood, cat claw and cacti.
		N. 0° 3 'W. bet. secs. 29 and 30. Over hilly land, through scattering timber and undergrowth.
	14.37 29.95 40.00	Asc.gradual slope 53 ft. to Top of knoll. Desc. 53 ft. to Over rolling land. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
	40.00	the ground for $\frac{1}{4}$ sec. cdr. with brass cap mkd.
		1915
	60.00 68.90 80.00	and raise a mound of stone, 2 ft. base, 12 ft. high W. of cor. Asc. 132 ft. to Top of ridge, brs. E. and W., desc. 60 ft. to Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs 19, 20, 29 and 30, with brass cap mkd.
		T 3 N R 5 W S 19:S 20 S 30:S 29 1915
	Total of the state	and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high W. of cor.
		Land, rolling and hilly. Soil, rocky, 3rd and 4th rates. Timber, scattering palo verde. Undergrowth, greasewood, cat claw and cacti.
		Undergrowth, greasewood, cat craw and bactr.
	40.00	East on a random line bet. secs. 20 and 29. Set temp. \(\frac{1}{4}\) sec. cor.
	79.92	Intersect N. and S. line, 12 lks. N. of cor. of secs. 20, 21, 28 and 29. Thence
•	3.4.00	N, 89° 55' W. on a true line bet. secs. 20 and 29. Over rolling and hilly land, through scattering timber and undergrowth.
	14.99 39.96	Wash, 40 lks. wide, course, SE. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for \(\frac{1}{4}\) sec. cor. with brass cap mkd.
		$\frac{15}{45}\frac{20}{29}$ 1915 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high
	49.12	N. of cor. Asc. gradual slope, 70 ft. to Top of spur slopes, N., desc. W. slope, 97 ft. to
	79.92	Cor. of secs. 19, 20, 29 and 30. Land, rolling and hilly. Soil, rocky, 3rd and 4th rates.
		Timber, palo verde. Undergrowth, greasewood, sagebrush and cacti.

FOOT 3053

```
Subdivision of T.3 N. R.5 W.
 Chains
           West on a random line bet. secs. 19 and 30.,
           Set temp. ½ sec. cor. Intersect W. bdy. of tp. 16 lks. S. of cor. of secs. 19,
 40.00
 76.41
                24, 25 and 30, as described in book "B"!
           S. 89° 53' E. on a true line bet. secs. 19 and 30.
           Over rolling land, through scattering timber and under-
                growth.
           Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
 36.41
                the ground for \frac{1}{4} sec. cor. with brass cap mad.
                                  1915
                and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high N
                of cor.
76.41
           Cor. of secs. 19, 20, 29 and 30.
         Land, rolling.
           Soil, rocky, 3rd and 4th rates.
           Timber, palo verde.
          Undergrowth, greasewood, at claw and cacti.
          N. 0° 3' W. bet. secs. 19 and 20.
          Over rolling land, through scattering timber and under-
               growth.
           Asc. gradual slope, 61 ft. to
         Topof spur slopes W., desc. over N. slope, 56 ft. to
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
the ground for 4 sec. cor. with brass cap mkd.
18.44
40.00
                                  s 19:s 20
               dig pits 18 X 18 \overline{X} 12 ins. N. and S. of post, 3 ft. dist. and raise a mound of earth 3\frac{1}{2} ft. base, 1\frac{1}{2} ft.
              high W. of cor.
          Thence over level land, through dense undergrowth.
Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in
the grand for cor. of secs. 17, 18, 19 and 20, with
00.08
               brass cap mkd.
                                  T 3 N R 5 W
S 18:S 17
                                     18:S
                                   S 19:S 20
                                     1915
               and raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high
               W. of cor.
          Land, rolling, and hilly. Soil, rocky, 3rd rate.
          Timber, palo verde.
         Undergrowth, greasewood, sagerush and cactia
          East on a random line bet. secs. 17 and 20.
          Set temp. \frac{1}{4} sec. cor.
40.00
79.85
          Intersect N. and S. line , 16 lks. N. of cor. of secs.
               16, 17, 20 and 21.
          Thence
          N. 89° 53' W. on a true line bet. secs. 17 and 20.
          Over rolling land, through scattering timber and under-
               growth.
          Set an iron post 3 ft. long, 1 in. in dism., 26 ins. in
39.92½
               the ground for \frac{1}{4} sec. cor. with brass cap mkd. \frac{15}{4} \frac{17}{5} \frac{20}{20}
               dig pits 18 X 18 X12 ins. E. and W. of post, 3 ft. do
               dist. and raise a mound of earth 3\frac{1}{2} ft. base, 1\frac{1}{2}ft.
               high N. of cor.
          Wash, 40 lks. wide, course, SE. Cor. of secs. 17, 18, 19 and 20.
65.75
79.85
```

22 Subdivision of T.3 N. R.5 W. Chains Land, gently rolling. Soil, rocky 3rd rate. Timber, scattering palo verde. Undergrowth, greasewood, sagebrush and cacti. West on a random line bet. secs. 18 and 19. Set temp. 1 sec. cor.
Intersect W. bdy. of tp. 9 lks. S. of cor. of secs. 40.00. 76.45 13, 18, 19 and 24, as described in book "B"." S. 89° 56' E. on a true line bet. secs. 18 and 19. Over gently rolling land, through scattering timberand undergrowth. Set an iron post 3 ft. long, 1 in. in dism., 26 ins. in 36.45 the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd. $\frac{18}{45}$ 19 1915 and raise a mound of stone, 2 ft. base, 12 ft. high N. of cor. Cor. of secs. 1%, 18, 19 and 20. Land, gently rolling. SoBl, rocky 3rd and 4th rates. 76.45 Timber, scattering palo verde. Undergrowth, greasewood and cat claw. N. 0° 3' W. bet. secs. 17 and 18; Over rolling land, through timber and undergrowth.
S. bank of wash, 2 ft. deep, course, SE.
N. bank of same wash, course, SE.
Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in 13.60 15.00 40 .00 the ground for & sec. cor. with brass cap mkd. S 18:S 17 dig pits 18 X 18 X 12 ins. N. and S. of cor. 3 ft. dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor. Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in 80.00 the ground for cor. of secs. 7, 8, 17 and 18, with brass cap mkd. 1:3 N R 5 W S 7:S 8 S18:S 17 1915 dig pits 18 X 18 X 12 ins. in each sec. 5½ ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high W. of cor. Land, gently rolling. Soil, rocky, 3rd and 4th rates. Timber, scattering palo verde and cat claw. Undergrowth, greasewood and cacti. East on a random line bet. secs. 8 and 17.
Set temp; sec. cor.
Intersect N. and S. line 21 lks. N. of cor. of secs. 40 .00 79.96 8, 9, 16 and 17. Thence N. 89° 51' W. on a true line bet. secs. 8 and 17. Over rolling land, through scattering timber and undergrowth. Wash, 100 lks. wide, 4 ft. deep, course, S. 10° E. Set an iron post 3 ft. long, lin. in diam., 26 ins. in 3.70 39.98 the ground for & sec. cor. with brass cap mkd. 15 8 4 S 17

```
Subdivision of T 3 N. R.5 W.
Chains
                and raise a mound of stone, 2 ft. base, 12 ft. high
                N. of cor.
           Cor. of secs. 7, 8, 17 and 18.
79.96
           Land, rolling.
           Soil, rocky, 3rd rate.. Timber, palo werde.
          Undergrowth, greasewood, pagebrush and cat claw.
          West on a random line bet. secs. 7 and 18.
          Set temp; \(\frac{1}{4}\) sec. cor.

Intersect W. bdy. of Tp. 3 lks. S. of cor. of secs.
40.00
76.39
                7, 12, 13 and 18, as described in book "B"!"
          Thence
           S. 89° 59' E. on a true line bet. secs. 7 and 18.
          Over rolling land, through scattering timber and under-
                growth.
          Road, brs. NW. and SE. Wash, 10 lks. wide, 2 ft. deep, course, SE. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
 8.40
23.20
36.39
                the ground for \frac{1}{4} sec. cor. with brass cap mkd.
                                  1915
                dig pits 18 X 18 X 12 ins. E. and W. of post, 3 ft.
               dist. and raise a mound of earth 3\frac{1}{2} ft. base, 1\frac{1}{2} ft. high N. of cor.
          Cor. of secs. 7, 8, 17 and 18.
76.39
          Land, rolling.
          Soil, rocky, 3rd and 4th rates. Timber, palo verde and cat claw.
          Undergrowth, greasewood, ocotillos and cacti.
          N. 0° 3' W. bet. secs. 7 and 8.
          Over rolling land, through scattering timber and under-
               growth.
          Wash, 40 lks. wide, 10 ft. deep, course, SE. Wash, 193 lks.wide, 15 ft. deep, course, SE.
12.20
          Wash, 193 lks.wide, 15 Asc. from wash, 15 ft.
19.75
          Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
40.00
                the ground for \frac{1}{4} sec. cor. with brass cap mkd.
                                  s 7 :s 8
                                     1915
               dig pits 18 X 18 X 12 ins. N. and S. of post, 3 ft. dist. and raise a mound of earth 3\frac{1}{2} ft. base, 1\frac{1}{2} ft.
               high W. of cor.
          Wash, 25 lks. wide, 2 ft. deep, course, SE.
51.40
71.49
          Dim road, brs. NW. and SE.
          Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 5, 6, 7 and 8, with
80.00
                brass cap mkd.
                                   T 3 N R 5 W
                                    S 7 :S 8
                                      1915
               dig pits 18 X 18 X 12 ins. in each sec. 5\frac{1}{2} ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high
               W. of cor.
          Land, rolling.
          Soil, stony, 3rd and 4th rates. Timber, palo verde and cat claw.
          Undergrowth, greasewood, ocotillos and cacti.
```

24	Subdivision of T.3 N., R.5 W.
Chains	East on a random line bet. secs. 5 and 8.
40.00	Set temp. ½ sec. cor.
80.09	Intersect N. and S. line, 25 lks. N. of cor. of secs.
	4, 5, 8 and 9.
	Thence
	N. 89° 49' W. on a true line bet. secs. 5, and 8.
	Over rolling land, through scattering timber and under- growth.
22.10	Wash, course, SE.
27.10	Wash, course, SE.
40.04	Set an iron post 3 ft. long, 1 in. in diam., 26 ins.in
	the ground for 4 sec. cor. with brass cap mkd.
	1 <u>S</u> 5 4S 8
	1915
	dig pits 18 X 18 X 12 ins. E. and W.of post, 3 ft.
	dist. and raise a mound of earth 3 ft. base, 1 ft.
	high N. of cor.
56.09	Wash, 4 chs. wide, course, SE.
65.00 80.09	Wash, course, SE. Cor. of secs. 5, 6, 7 and 8.
00.09	Land, gently rolling.
	Soil, rocky, 3rd rate.
	Timber, palo verde and cat claw.
	Undergrowth, greasewood, ocotillos and cacti.
,	West on a random line pet. secs. 6 and 7.
40.00	Set temp. 4 sec. cor.
76.24	Intersect W. bdy. of Tp. 7 lks. N. of cor. of secs. 1,
	6, 7 and 12, and described in book "B.".
	Thence N. 89° 57' E. on a true line bet. secs. 6 and 7.
	Over rolling land, through scattering timber and under-
*	growth.
33.34	Dim road, brs. NW. and SE.
36 .24	Set an iron post 3 ft. long, 1 in. in dim., 26 ins. in
	the ground for \frac{1}{4} sec. cor. with brass cap mkd.
	1 S 6 7 7 7 1
	s 7
	1,915
	dig pits 18 X 18 X 12 ins. N. and S. of post, 3 ft.
	dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N. of cor.
47.24	Wash, 25 lks. wide, 2 ft. deep, course, SE.
76.24	Cor. of secs. 5, 6, 7 and 8.
	Land, rolling.
	Soil, rocky, 3rd rate.
	Timber scattering palo verde. Undergrowth, greasewood, cat claw, and occtillos.
	ondergrown, greasewood, car craw, and occurros.
40.00	N. 0° 3' W. onta random line bet. secs. 5 and 6.
40.00	Set temp. 2 sec. cor. Intersect N. bdy. of Tp. 4 lks. E. of cor. of secs. 5,
19.00	6. 31 and 32, described in book "B"."
	Thence
	S. 0° 5' E. on a true line bet. secs. 5 and 6.
	Over rolling land, through scattering timber and under-
70 05	growth. Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in
39.85	the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	4
	S 6:S 5
	dig pits 18 X 18 X 12 ins. N. and S. of post, 3 ft.
	dist. and raise a mound of earth 3½ ft. base, 1½ ft.
	high W. of cor.

Chains
69.25 Wash, course, SE.
69.55 Wash, 6 ft. deep, course, SE.
79.85 Cor. of secs. 5 6, 7 and 8.
Land, rolling.
Soil, 3rd rate.
Timber, palo verde and cat claw.
Undergrowth, greasewood and cacti.

GENERAL DESCRIPTION

Subdivision of T.3 N.R.5 W.

This township contains mountainous and rolling land. The surface ranges from rough along the southern part to rolling and level in the northern part.

The soil varies from rocky, 4th rate in the mountainous regions to sandy 2nd rate in the level regions.

The vegetation consists of palo verde, cat claw, iron wood, ocotillos, mesquite, cactus, greasewood and sagebrush. There are no settlers.

No water has been developed.

--000--

Subdivision of T.3 N

DATE DIAGRAM

;	5/12-15	5/12-15	5/12-15	5/12-15	5/12-15	5/11-15	
5/13-15	6 1/8	5 /2/7 - 15	4 4 12 /2 4 12 /2	3 12-15	5/10-15	5/11-15	5/11-15
5/3-15	7 1/2/7-65	10/7/2	0 5/12-15	5/8-15	11 0//5	12 5/11-15	5/11-15 West
5/13-15	18 97	17 /2	16 -12	15 -15	5/10-15	13 5/10-15	5/11-15 Meridian
5/13-15	19 9	0 0 0/6-/5	21 8/- 5/6-15	2/2/5	23 - 0/5	2 4 5/10-15	5/10-15 ruide
5/13.15	30 30 12/6-151	99 - 9/5 12/5 - 85	28 5/4-15	27 - L/s 5/6-15	26 -85	25 5/7-15	5/10-15 -irst G
5/13-15	31 SY - 9/21 5/1-15	32 5/1-15 5/2-15	33, 1 5/1-15 S	. 34 . 5/1-15	35 - 1/5 4/29-15	36 4/29·15	5/7-15

Lines dated in black were surveyed by Woodbury Abbey,

U. S. Surveyor.

Lines dated in red were surveyed by R. J. Gill.

U. S. Transitman.

Lines dated in green were surveyed by H. D. Voigt.

U. S. Transitman.

CERTIFICATES

FINAL-OATH OF UNITED STATES SURVEYOR. AND UNITED STATES TRANSITMAN,

3*~	See Book "C."
I,	, U. S. Surveyor, do solemnly swear that, in pursuanc
of special instru	uctions received from the U.S. Surveyor General for
bearing date of	theday of, 191 , I have well, faithfully, and truly
	oper person, and in strict conformity with said instructions, the Manual of Surveying
	nd the laws of the United States, surveyed all those parts or portions of
`	
	of the
	Meridian, in the State of, which are represented in
the foregoing fi	eld notes as having been executed by me, and under my direction; and I do further
	that all the corners of said survey have been established and perpetuated in strict accord
	anual of Surveying Instructions, and the special written instructions of the U.S. Surveyor
	and in the specific manner described in the field notes, and that
tne toregoing ar	re the original field notes of such survey.
	U. S. Surveyor.
	U. B. Burveyor.
Subscribed by s	aid, and sworn to before me)
this	day of 191
	,
/	
SEAL	

	APPROVAL.
	OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
	Phoenix, Arizona, JUL 20 1918,
The foregoi	ing field notes of the survey of
,	Subdivision Lines
	- -
	TOWNSHIP 3 NORTH, RANGE 5 WEST,
of the G	ila and Salt River Base and Meridian, in the State of Arizon
executed by W	oodbury Abbey, U. S. Surveyor and Roy J. Gill, U.S. Transitm
under his specia	l instructions dated Dec. 12, 1914, for Group 39, Arizona, 191, having been
	ned, and the necessary corrections and explanations made, the said field notes, and the
	scribe, are nereby approved.
surveys they des	scribe, are hereby approved.
	U. S. Surveyor General.
surveys they des	Many Stored