.

BOOK 3102

JAN 5 - 1918

1-66-1918

FIELD NOTES

OF THE SURVEY OF THE

Completion of the
EAST BOUNDARY
and
SUBDIVISION LINES
and
RETRACEMENT OF PART OF THE SUBDIVISION LINES &
RESURVEY OF PART OF THE SUBDIVISION LINES OF
TOWNSHIP 27 NORTH, RANGE 3 EAST,
Of the Gila and Salt River Base and Meridian,
In the State ofArizona.
EXECUTED BY
Thomas B. Matthews, U. S. Surveyor,
and
William L. Nash, U. S. Transitman,
In the capacity of U.S. Surveyor, under instructions dated March 8, , 1915
issued by the United States Surveyor General to govern surveys included i
Group No. 55, which were approved by the Commissioner of the General Lan
Office, December 14, 1915.
Retracement.
Resurvey & Survey commenced July 19, , 1916.
Retracement, Resurvey & Survey completed July 29, , 1916.
. 1. 1. Antronomá

Executed under Assignment Instructions dated Apr. 13 & June 26, 1916. N

3102

Book "I"

Group 55 - - - Arizona.

BOOK 3102

INDEX DIAGRAM.

			Re XX 90				30 31 32 X 6	~//V			2702 20 2702 20	9 0
		б			6		7	1220	//////		7777	
	7	34	8	27	9	2	10	18	3 11	18	12	4
	33		. 33		27		22		17		12	
	18	34	17	26	16	22		17	14	12	13	4
_	32		31		T. 27	N-	R.3 E	Ξ.	16		11	
	19	31	20	25	21	20		16) 23	1	24	3
	30		30		25		20		15		10	
	30	29	29	24	28	19	27	15	26	10	25	3
	29		28		24		19		14		9	
	31	28	32	23	33	18	34		,) 35	g	36	2
				;								

•	Lines surveyed under this group.	
	Lines resurveyed or cretraced under this	group.
	Accepted surveys.	

////////////////////// Areas surveyed as per accepted plats on file.

1

survey of Completion of East Boundary of T. 27 N. Chains.

Retracements, resurveys and surveys hereinafter described; a, executed on dates shown on diagram onpage 35 hereof, by Thomas B.Matthews, U.S. Surveyor, and William L. Nash, U.S.
Transitman, using Buff and Buff transit No. 10124, and
Young and Sons light mountain transit No. 8535, respectively, described in Book "A."

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.,
which is a limestone, 12x12x12 ins. above ground, firmly

set marked and witnessed, as described by the surveyor

general,
South on a random line, along the E. ody. of the Tp., setting temp. \(\frac{1}{4} \) sec. and sec. cors. at intervals of 40.00 chs.; and at 379.70 chs., intersect the N. bdy. of sec. 6, T. 26 N., R. 4 E., 6.52 chs. N.89° 57' E. of the cor. of Ts. 26 N., Rs. 3 and 4 E., which is an iron post, described in Book "H".

At the point of intersection, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Ts. 27 N., Rs. 3 and 4 E., marked on brass cap

T27N R3E R4E S36 S31 SÓ T26N R4E 1916

And raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Thence

North on a true line, bet. secs. 31 and 36. Over gently rolling land, through scattering undergrowth.

Enter scattering timber.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 40.00

1836 | 831

From which A pinion, 14 ins. diam., brs. S.37½° E., 68 lks. dist., marked $\frac{1}{4}$ S31 BT. A pinion, 10 ins. diam., brs. N.45° W., 25 lks. dist., marked 4836 BT.

Rim rock, brs. E. and W. Desc. 40 ft. to 64.10

74.00 Draw, course W.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked on 80.00

> T27N R3E R4E S25 S30

From which A pinion, 14 ins. diam., brs. N.74° E.,218 lks. dist., marked T27N R4E S30 BT.

A pinion, 16 ins. diam., brs. S.79½° E., 232 lks. dist., marked T27N R4E S31 BT.

A pinion, 10 ins. diam., brs. S.58½° W., 88 lks. dist., marked T27N R3E S36 BT. A pinion, 10 ins. diam., brs. N.143° W., 124 lks. dist., marked T27N R3E S25 BT.

Land, rolling and gently rolling.

Soil, thin and rocky.

Timber, scrub cedar and pinion. Undergrowth, sagebrush and holly brush. Fair grass.

Survey of Completion of East Boundary of T. 27 N..

Chains.

North on a true line, bet. secs. 25 and 30. Over rolling land, through scattering timber and undergrowth.

Asc. 85 ft. to

Rim, brs. E. and W. Thence over gently rolling land.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor, marked on brass cap 10.30 40.00

> 1825 S30 1916

From which A pinion, 10 ins. diam., brs. $S.16\frac{1}{2}$ ° E., 93 lks. dist., marked 4830 BT. A pinion, 10 ins. diam., brs. N.22½° W., 10 lks. dist., marked 4S25 BT.

45.00

Desc. 35 ft. to
Draw, course W. Asc. 65 ft. to 50.00

62.31 65.00 69.84

Spur, slopes NW. Desc. 20 ft. to
Asc. 35 ft. to
Rim of mesa, brs. NW. and SE.
Rim of mesa, brs. NE. and SW. Desc. 55 ft. to
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
ground, for cor. of secs. 19, 24, 25 and 30, marked on 74.84 brass cap

> T27N R3E R4E S24 S19 S25 S30 1916

From which A pinion, 12 ins. diam., brs. $N.59\frac{1}{2}$ ° E., 87 lks. dist., marked T27N R4E S19 BT. 12 ins. diam., brs. S.2° E., 103 lks. dist., A pinion, marked T27N R4E S30 BT. A pinion, 10 ins. diam., brs. S.24° W., 82 lks. dist., marked 27N R3E S25 BT.
A pinion, 8 ins. diam., brs. N.49½° W., 20 lks. dist., marked T27N R3E S24 BT. Land, rolling and gently rolling. Soil, thin and rocky. Soil, scrub cedar end pinion. Undergrowth, holly brush.

North on a true line, bet. secs. 19 and 24. Over gently rolling land, through scattering timber and undergrowth.

5.00 Draw, course NE.

Thin grass.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor, marked on brass cap 40.00

> 324 S19 1916

From which A pinion, 14 ins. dism., brs. S.38° E., 97 lks. dist.. marked 4519 BT. A pinion, 18 ins. diam., brs. N.22° W., 110 lks. dist., marked $\frac{1}{4}$ \$24 BT.

Road, brs. NE. and SW. 52.40

75.00 Braw, course SE.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, marked on brass cap

S۱		Completion of East Boundary of T. 27 N. R. 3 E.
	Chains.	T27N R3E R4E S13 S18
	·	1916
		From which A pinion, 16 ins. diam., brs. N.23%° E., 51 lks. dist., marked T27N R4E S18 BT. A pinion, 18 ins. diam., brs. S.45° E., 85 lks. dist., marked T27N R4E S19 BT. A pinion, 10 ins. diam., brs. S.5 W., 157 lks. dist., marked T27N R3E S24 BT. A pinion, 12 ins. diam., brs. N.14%° W., 75 lks. dist., marked T27N R3E S13 BT. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, cedar and pinion. Undergrowth, sagebrush, 2 to 3 ft. high, and broom weed, 1 ft. high. Fair grass.
	40.00	North on a true line, bet. secs. 13 and 18. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	40.00	ground, for 2 sec. cor., marked on brass cap
		1916
,		From which A pinion, 10 ins. diam., brs. S.33° E., 43 lks. dist., marked \(\frac{1}{4}\)S18 BT.
44.	80.00	A pinion, 10 ins. diam., brs. N.523° W., 167 lks. dist., marked \$\frac{1}{4}\$S13 BT. Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, marked on brass cap T27N
		R3E R4E S12 S 7 S13 S18 1916
		From which A pinion, 14 ins. diam., brs. N.13° E., 366 lks. dist., marked T27N R4E S7 BT. A pinion, 12 ins. diam., brs. S.60° E., 176 lks. dist., marked T27N R4E S18 BT. A pinion, 8 ins. diam., brs. S.9½° W., 278 lks. dist., marked T27N R3E S13 BT. A pinion, 12 ins. diam., brs. N.17° W., 481 lks. dist., marked T27N R3E S12 BT. Land. gently rolling.
		Soil, coarse texture, 20 ins. deep. Timber, pinion and cedar. Undergrowth, sagebrush and broom weed, 1 ft. high. Fair grass.
	39.15	North bet. secs. 7 and 12. Over gently rolling land, through scattering timber and undergrowth. Draw, course NE.
	ノフ・エフ	Draw, Course will.

Survey of completion of East bdy.of T. 27 N., R. 3 E.

Chains.

40.00 Set an iron post, 3 ft.long, 1 in. in diam., 26 ins. in the ground, for 4 sec.cor., marked on brass cap,

1512 S 7 1916

from which,

A pinon, 12 ins. in diam., brs.N.27°E., 41 lks.

dist., marked 4 S 7 B T.

A pinon, 14 ins. in diam., brs.N.754°W., 172 lks.

dist., marked 4 S 12 B T.

79.70 The original cor. of secs.1, 6, 7 and 12, hereinbefore described.

Land, gently rolling. Soil, coarse texture, 26 ins. deep.

Timber, cedar and pinon.
Undergrowth, sage brush and holly brush, 1 to 4 ft.high.

Fair grass.

```
Retracement & resurvey of part of Subdivision lines of T.27N.R.3E
Chains.
                                                   RETRACEMENT.
            From the original 2 sec.cor. of secs. 6 and 7, which is a
                  limestone, 8x12x10 ins. above ground, firmly set, marked
 limestone, 8x12x10 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, $.89° 23'E., on a true line, bet. secs. 6 and 7. (E.½).

Over rolling land, thru.scattering timber and undergrowth.

3.00 Draw, course SE.

6.00 Draw, 2.00 chs.wide, course SW.

15.00 Enter heavy timber, brs. N. and S.

Intersect the original com. of secs. 5, 6, 7 and 8, which is a limestone, 14x12x12 ins. above ground, firmly set, marked and witnessed, as described by the surveyor general
                  general.
             Land, rollimg.
             Soil, loose, yellow, rocky loam, over limestone formation.
             Timber, pinon and juniper.
Undergrowth, sage brush and squawbbrush.
             Fair grass.
             S.89° 23' E., on a true line, bet. secs. 5 and 8. Over rolling land, thru. heavy timber and scattering
                  undergrowth.
  20.00 Draw, 2 chs. wide, course S.
25.00 Leave heavy enter scattering timber.
30.00 Draw, 1 ch. wide, course S.
40.22 Intersect the original 4 sec.cor., which is a limestone,
                  8x12x12 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Now
                  refers to sec.5 only.
             Thence, s.89° 32' E., on a true line, bet. secs.5 and 8. (E.\frac{1}{2}). Over rolling land.
  2.00 Draw, 2 chs.wide, course SW.
40.26 Intersect the original cor.of secs. 4, 5, 8 and 9, which
                   is a limestone, 10x12x3 ins. above ground, firmly set,
                   marked and witnessed, as described by the surveyor
                   general.
             Land, rolling.
Soil, loose, yellow, rocky loam, over limestone formation.
Timber, pinon, and juniper.
             Undergrowth, sage brush and squawbrush.
             Fair grass.
             S.89° 26' E., on a true line, bet. secs. 4 and 9. Over rolling land, thru. scattering timber and under-
                   growth.
     5.00 Enter heavy timber, brs.NE. and SW.
  42.02 Intersect the original 4 sec.cor., which is a pinon post, 4 ins. square, firmly set, marked and witnessed as described by the surveyor general. Remains common to
                   secs. 4 and 9.
              Thence.
                                                          RESURVEY.
              5.89^{\circ}31^{\circ}E, on a true line, bet. secs.4 and 9, (E.\frac{1}{2}).
              Over rolling land, draining SW.
   39.98 Intersect the original cor. of secs. 3, 4, 9 and 10, which is a pinon post, 4 ins. square, firmly set, marked and witnessed, as described by the surveyor general.
```

I destroy this cor., and in its place,

Retracement & Resur. of part of Subdivision lines of T. 27 N. R. 3 E. | Chains.

Set an iron post 3 ft.long, 2 ins. in diam., 26 ins. in the ground, for reestablished cor. of secs. 3, 4,9 and 10, marked on brass cap,

T27N R 3E S 4 S 3

The four original bearing trees were retained without alteration.

Land, rolling.
Soil, loose, rocky loam, over limestone formation.
Timber, pinon and juniper.
Undergrowth, sage brush, squaw brush and short weeds.

Fair grass.

S.89° 30' E., on a true line, bet. secs. 3 and 10. Over rolling land, thru heavy timber and undergrowth. 40.20 Intersect the original 2 sec.cor., which is a pinon post, 4 ins.square, firmly set, marked and witnessed, as described by the surveyor general. I destroy this cor., and in its place,

Set an iron post, 3 ft.long, 1 in. in diam. 26 ins. in
the ground, for reestablished \(\frac{1}{4}\) sec.cor.; of secs. 3 and
10, marked on brass cap,

> **S10** 1916

The two original bearing trees were retained without alteration.

Thence, $8.89^{\circ}33^{\circ}E$, on a true line, bet. secs. 3 and 10 (E. $\frac{1}{2}$). Over rolling land, draining SW.

15.00 Draw, 3 chs.wide, course SW.

40.22 Intersect the original cor. of secs.2,3,10 and 11, which is a pinon post, 4 ins, square, firmly set, marked and witnessed as described by the surveyor general, with the exception that the bearing tree in sec. 3 has been destroyed.

Mark a new tree as follows:

A juniper, 8 ins. in diam., brs.N.502° W., 123 lks.dist., marked T 27 N R 3 E S 3 B T.

Land, rolling. Soil, loose, yellow loam. Timber, pinon, and juniper. Undergrowth, sage brush and squaw brush, and broomweed, 6 to 8 ins.high.

RETRACEMENT.

From the original cor of secs. 1, 2, 11 and 12, which is a limestone, 6x18x6 ins. above ground, firmly set, marked and witnessed as described by the surveyor general,

S.89°19'E., on a true line, bet. secs.1 and 12.

Over gently rolling land, thru.scattering timber.

39.71 Intersect the original 1 sec.cor., which is a pinon post,
4 ins. square, 18 ins. above ground, firmly set, marked
and witnessed, as described by the surveyor general. Now refers to sec. 1 only.

S.89°22'E., on a true line, bet. secs.1 and 12 (E. $\frac{1}{2}$).

8. Retracement & Resur. of part of Subdivision lines of T.27N., R3E. Chains.

Over rolling land, draining N.

40.03 Intersect the original cor. of secs.1,6,7 and 12 on E.bdy.

of Tp., which is a limestone, hereinbefore described.

Land, gently rolling.

Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinon. Fair grass.

Boundaries of that part of T.27 N., R.3 E., subdivided under this group.

Latitudes, departures, and closing errors.

Line designated,	True bearing.	Dist.	Latitu	ides.	Departi	ires.
-			N.	S.	E.	W.
South boundary	s.89°57' w., N.89°59'W.	6.52 471.79	.14	.01		6.52 471.79
West boundary,	North,	402.09	402.09	2		
Subdivisional boundary,	5.89°46'E. 5.89°23'E. 5.89°32'E. 5.89°31'E. 5.89°33'E. 5.89°41'E. 5.89°41'E. 5.89°22'E.	37.66 80.06 40.26 40.02 39.98 40.20 40.22 80.00 39.71 40.03		.156.30 .4352 .447.44	40.26 40.02 39.98 40.20 40.22 80.00 39.71	
East boundary,	South,	399.70		399.70		
Convergency,			100	C	•43	120 79
Totals,		;	402.23	403.81	478,57 478.31	478.31
	Error in lat			1.58	0.26	

Chains.

Knowing from recent and repeated tests of our instruments on a meridian determined by observations on Polaris at elongation, that they are in adjustment, we proceed to the survey of the completion of the subdivision of

T.27 N., R.3 E.

From the cor. of secs.35 and 36, on the S. bdy. of the Tp., which is an iron post, described in Book "H", N.0° 1' W., bet. secs. 35 and 36.

Over gently rolling land, through scattering timber and

undergrowth.

20.00

Draw, 3 chs. wide, course NE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 40.00 ground, for 4 sec. cor, marked on brass cap

From which A pinion, 5 ins. diam., brs. N.87 $\frac{1}{4}$ ° E., 104 lks. dist., marked $\frac{1}{4}$ S36 BT.

A pinion, 8 ins. diam., brs. N.33° W., 231 lks. dist., marked 4\$35 BT.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on 26 ins. in the brass cap

T27N R3E S26 S25

From which

A pinion, 10 ins. diam., brs. N.19° E., 42 lks. dist., marked T27N R3E S25 BT.

12 ins. diam., brs. S 34° E., 55 lks. dist., A pinion,

marked T27N R3E S36 BT. A pinion, 8 ins. diam., brs. S.44° W., 97 lks. dist.,

marked T27N R3E S35 BT. A pinion, 9 this. diam., brs. N.30 $\frac{1}{2}$ ° W.,147 lks. dist., marked T27N R3E S26 BT.

Land, gently rolling.

Soil, coarse texture, 26 ins. deep.

Timber, scrub cedar and pinion.

Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 6 ins. high.

Fair grass.

40.00

S.89° 59' E., on a random line, bet. secs. 25 and 36. Set temp. \(\frac{1}{4}\) sec. cor.

Intersect E. bdy. of Tp., 7 lks. S. of the cor. of secs.

25, 30, 31 and 36, which is an iron post, hereinbefore 79.89 described.

Thence

S.89° 58' W., on a true line, bet. secs. 25 and 36. Over gently rolling land, through scattering timber and undergrowth.

8.30 Draw, 2 chs. wide, course NW.
39.94 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap

From which A pinion, 10 ins. diam., brs. N.34 $\frac{1}{4}$ ° W., 52 lks. dist., marked $\frac{1}{4}$ S25 BT. A pinion, 10 ins. diam., brs. S. $42\frac{1}{2}$ ° W., 138 lks. dist.,

Completion of Subdivision of T. 27 N., R. 3 E. 10. chains. marked $\frac{1}{4}$ S36 BT. The cor. of secs. 25, 26, 35 and 36. 79.89 Land, gently rolling. Soil, coarse texture, 26 ins. in depth. Timber, cedar and pinion. Undergrowth, sagebrush, and buck brush, 1 to 2 ft. high, and broom weed, 6 ins. high. Fair grass. N.0° 1' W., bet. secs. 25 and 26. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 40.00 4\$26 S25 1916 From which A pinion, 10 ins. diam., brs. $N.46\frac{1}{4}$ ° E., 26 lks. dist.. marked \(\frac{1}{4}\)S25 BT.

A pinion, 7 ins. diam., brs. N.12\(\frac{3}{4}\)° W., 69 lks. dist., marked \(\frac{1}{4}\)S26 BT. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, in a mound of stone, for cor. of secs. 23, 24, 25 and 26, marked on brass cap 80.00 T27N R3E S23 S24 S26 S25 1916 Brom Which A pinion, 12 ins. diam., brs. $N.51\frac{1}{2}$ ° E., 49 lks.dist., marked T27N "3E S24 BT. A pinion, 8 ins. diam., brs. $S.16\frac{1}{2}$ ° E., 188 lks. dist, marked T27N R3E S25 BT. A pinion, 16 ins. diam., brs. S.483° W., 76 lks. dist. marked T27N R3E S26 BT. A pinion, 12 ins. diam., brs. N.3° W., 30 lks. dist., marked T27N R3E S23 BT. Land, gently rolling. Soil, coarse texture, 12 to 26 ins. deep. Simber, cedar and pinion. Undergrowth, sagebrush and holly brush, 1 to 4 ft. high, and broom weed, 6 ins. high. Fair grass. N.89° 58' E., on a random line, bet. secs. 24 and 25. Set temp. 4 sec. cor.
Intersect E. bdy. of Tp., 30 lks. N. of the cor. of secs. 40.00 19, 24, 25 and 30, which is an iron post, hereinbefore described. Thence N.89° 49 W., on a true line, bet. secs. 24 and 25. Over gently rolling land, through scattering timber and undergrowth. 5.25 Draw, course NE. 40.11 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 2 sec. cor., marked on brass cap

Completion of Subdivision of T. 27 N. K. 3 E Chains. From which A pinion, 8 ins. diam., brs. N.69% E., 49 lks. dist., marked $\frac{1}{4}$ S24 B7. A pinion, 16 ins. diam., brs. $S.52\frac{1}{4}$ ° E., 59 lks. dist. marked 4\$25 BT. The cor. of secs. 23, 24, 25 and 26. 80.23 Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass. N.0° 1' W., bet. secs. 23 and 24. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the 40.00 ground, in a mound of stone, for 4 sec. cor., marked on brass cap 1523 S24 1916 From which A pinion, 12 ins. diam., brs. N.8 $\frac{1}{5}$ ° E., 37 lks. dist., marked $\frac{1}{4}$ \$24 BT. A pinion, 20 ins. diam., brs. S.70° W., 43 lks. dist., marked $\frac{1}{4}$ \$23 BT. Road, brs. E. and W. 44.23 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap T27N R3E S14 S13 S23 S24 1916 From which A pinion, 10 ins. diam., brs. N.24° E., 46 lks. dist. marked T27N R3E S13 BT. A pinion, 22 ins. diam., brs. $5.64\frac{1}{4}$ ° E., 52 lks.dist., marked T27N R3E S24 BT.
A pinion, 8 ins. diam., brs. S.39° W., 4 lks. dist., marked T27N R3E S23 BT. A pinion, 12 ins. diam., brs. N.3330 W., 59 lks. dist., marked T27N R3E S14 BT. Land, gently rolling.
Soil, coarse texture, 10 to 26 ins. deep.
Timber, cedar and pinion. Thin grass. Undergrowth, holly brush.

40.00 80.18 S.89° 49' E., on a random line, bet. secs. 13 and 24. Set temp. \(\frac{1}{4}\) sec. cor.
Intersect E. bdy. of Tp., 23 lks. S. of the cor. of s

23 1ks. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, hereinbefore described.

Thence N.89° 59' W., on a true line, bet. secs. 13 and 24. Over gently rolling land, through scattering timber and undergrowth.

80.12

described.

Completion of Subdivision of T. 27 N., R. 3 E. 12. hains. 4.20 Draw, course SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 40.09 ground, for $\frac{1}{4}$ sec. cor., marked on brass cap From which A pinion, 14 ins. diam., brs. N.42 $\frac{1}{2}$ ° W., 92 lks. dist. marked $\frac{1}{4}$ S13 BT. A pinion, 10 ins. diam., brs. $5.66\frac{1}{2}$ ° W., 42 lks. dist. marked 4S24 BT. The cor. of secs. 13, 14, 23 and 24. 80.18 Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, pinion and cedar. Undergrowth, sagebrush, I to 3 ft. high. Thin grass. N.0° 1' W., bet. secs. 13 and 14. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap 40.00 314 S13 1916 From which A pinion, 14 ins. diam., brs. N.66\frac{1}{2}\circ E., 83 lks. dist. marked $\frac{1}{4}$ \$13 BT. A pinion, 14 ins. diam., brs. N.21 $\frac{1}{2}$ ° W., 132 lks. dist., marked $\frac{1}{4}$ S14 BT. 60.00 Draw, course SW. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the 80.00 ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap T27N R3E S11|S12 S14 S13 1916 From which A pinion, 14 ins. diam., brs. N.124° E., 54 lks. dist. marked T27N R3E S12 BT. A pinion, 16 ins. diam., brs. S.882° E., 82 lks. dist. marked T27N R3E S13 BT. 10 ins. diam., brs. S.58° W., 110 lks. dist. A pinion, marked T27N R3E S14 BT. 10 ins. diam., brs. N.65% W., 117 lks. dist., A pinion, marked T27N R3E S11 BT. Land, gently rolling. Soil, coarse texture, 26 ins. in depth. Timber, cedar and pinion. Undergrowth, sagebrush and broom weed, 1 ft. high. Fair grass. S.89° 59' E., on a random line, bet. secs. 12 and 13.
Set temp. 1/4 sec. cor.
Intersect E. bdy. of Tp., 19 lks. S. of the cor. of secs.
7, 12, 13 and 18, which is an iron post, hereinbefore 40.00

Completion of Subdivision of T. 27 N., R. 3.E.

Chains.

Thence S.89° 53' W., on a true line, bet. secs. 12 and 13. Over gently rolling land, through scattering timber and

undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap

> 13 13 1916

From which

A pinion, 10 ins. diam., brs. $N.71\frac{1}{2}$ ° W., 60 lks. dist.

marked \$\frac{1}{4}\$12 BT.

A pinion, 10 ins. diam., brs. S.43½° E., 35 lks. dist.,

marked \$13 BT.
The cor. of secs. 11, 12, 13 and 14.

Land, gently rolling.

Soil, coarse texture, 26 ins. deep. Undergrowth, sagebrush.

Timber, cedar and pinion.

Thin grass.

N.O° l' W., on a random line, bet. secs. 11 and 12. Set temp. 2 sec. cor.

40.00

80.58 Intersect R. and W. line, 26 lks. W.of original cor. of secs. 1, 2, 11 and 12, which is a limestone, hereinbefore described.

Thence

S.0° 10' W., on a true line, bet. secs. 11 and 12. Over gently rolling land, through ...dense...; timber and

undergrowth.

40,58 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap

> 1511 S12 1916

From which A pinion, 8 ins. diam., brs. $8/70^{\frac{1}{2}}$ ° E., 35 lks. dist. marked 4S12 BT.

A pinion, 10 ins. diam., brs. N.74 $\frac{1}{4}$ ° W., 65 lks. dist., marked 4S11 BT.

50.60

0.60 Small, shallow draw, course W. 80.58 The cor. of secs. 11, 12, 13 and 14. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, broom weed, 1 ft. high. Fair grass.

> From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is an iron post, described in Book "H", N.O° 1 ' W., bet. secs. 34 and 35.
> Over rolling land, through heavy timber and scattering undergrowth.

Draw, 1 ch. wide, course NW. 6.00

29.90 Road, brs. NW. and SE.

37.50

Draw, 1 ch. wide, course Sw.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1sec. cor., marked on brass cap 40.00

	14.	Completion of Subdivision of T. 27 N., R. 3 E.
ľ	chains.	₹834 8 35
		1916
	72.00 75.00 80.00	From which A juniper, 14 ins. diam., brs. N.31° E., 46 lks. dist. marked \$\frac{1}{4}\$S35 BT. A pinion, 14 ins. diam., brs. N.87\frac{1}{4}° W., 60 lks. dist. marked \$\frac{1}{4}\$S34 BT. Leave heavy, enter scattering timeer, brs. E. and W. Draw, 2 chs. wide, course W. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on brass cap \$\frac{T27N R3E}{524 S35}\$
	•	1916
		From which A pinion, 10 ins. diam., brs. N.29\(20 \) E., 320 lks. dist., marked T27N R3E S26 BT. A pinion, 10 ins. diam., brs. S41° W., 247 lks. dist., marked T27N R3E S34 BT. A pinion, 20 ins. diam., brs. N.42° W., 228 lks. dist. marked T27N R3E S27 BT. No other trees within limits. Dig a pit, 18 X 18 X 12 ins., SE. of post, 5\(\frac{1}{2} \) ft. dist. Land, rolling. Soil, loose, yellow, gravelly loam. Timber, pinion and juniper. Undergrowth, sagebrush. Fair grass.
	-	
	40.00 80.10	S.89° 59' E., on a random line, bet. secs. 26 and 35. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 17 lks. N. of the cor. of secs. 25, 26, 35 and 36. Thence
	19.10 40.05	N.89° 52' W., on a true line, bet. secs. 26 and 35. Over rolling land, through heavy timber and scattering undergrowth. Draw, 1 ch. wide, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
	·	½s26 \$35 1916
•	40.50 47.60 75.40 80.10	From which A juniper, 10 ins. diam., brs. N.2½° W., 85 lks. dist. marked ½\$26 BT. A pinion, 14 ins. diam., brs. S.2½° E., 38 lks. dist., marked ½\$35 BT. Leave heavy, enter scattering timber, brs. N. and S. Draw, 1 ch. wide, course SW. Draw, 50 lks. wide, course S. The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, loose, yellow, gravelly loam, over limestone formation. Timber, pinion and juniper. Undergrowth, sagebrush, and broom weed, 1 ft. high. Fair grass.

Board sing

Completion of Subdivision of T. 27 N.

Chains.

N.O° 1' W., bet. secs. 26 and 27. Over rolling land, through scattering timber and undergrowth.

24.00

34.00

Draw, 2 chs. wide, course SW.
Enter heavy timber, brs. SE. and SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 40.00

> \$27 S26 1916

From which A pinion, 10 ins. diam., brs. N.79 $\frac{3}{4}$ ° E., 39 lks. dist., marked 4526 BT. A pinion, 8 ins. diam., brs. N.55 $\frac{1}{4}$ ° W., 14 lks. dist., marked $\frac{1}{4}$ S27 BT.

Leave heavy, enter scattering timber, brs. NE. and SW. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in. the ground, for cor. of secs. 22, 23, 26 and 27, marked 65.00 80.00 on brass cap

T37N R3E S22 | S23 527 | 526 1916

From which A pinion, 8 ins. dism., brs. $N.10^{\frac{1}{4}}$ ° E., 343 lks. dist., marked T27N RJE S23 BT. A pinion, 12 ins. diam., brs. S.40% E., 306 lks. dist., marked T27N R3E S26 BT.
A pinion, 12 ins. diam., brs. S.2% W., 366 lks. dist., marked T27N R3E S27 BT. No. other trees within limits. Dig a pit, 18 X 18 X 12 ins., NW. of post, 5 ft. dist. Land, gently rolling.
Soil, loose, yellow loam, over limestone formation. Timber, pinion and juniper. Undergrowth, sagebrush, squawbrush, and broom weed. 6 to 12 ins. high. Thin grass.

S.89° 52' E., on a random line, bet. secs. 23 and 26. 40.00

Set temp. 4 sec. cor. 79.78 Intersect N. and S. line, 6 lks. N. of the cor. of secs. 23, 24, 25 and 26.

Thence N.89° 49' W., on a true line, bet. secs. 23 and 26. Over gently rolling land, through scattering undergrowth and heavy timber.

9.80 34.80

Leave heavy, enter scattering timber, brs. NE. and SW. Leave scattering enter heavy timber, brs. NW. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 39.89 ground, for 4 sec. cor., marked on brass cap

From which A pinion, 24 ins. diam., brs. N.57° E., 19 lks. dist., marked 4S23 BT.
A pinion, 10 ins. diam., brs. S.42° W., 347 lks. dist.,

Leave heavy, enter scattering timber, brs. NE. and SW. The cor. of secs. 22, 23, 26 and 27. Land, gently rolling.

Soil, loose, yellow, rocky loam.

16		Completion of Subdiviston of T. 27 N., R. 3 E.
	Chains.	Timber, pinion and juniper. Undergrowth, sagebrush, squawbrush, and scattering broom weed, 1 ft. high. Fair grass.
		N.0° 1' W., bet. secs. 22 and 23. Over rolling land, through scattering timber and under-
	11.00 28.80	growth. Enter heavy timber, brs. SE. and SW. Road, brs. NE. and SW.
	38.00 40.00	
		1 \$22 S23
	,	1916
		From which A pinion, 12 ins. diam., brs. S.63° E., 198 lks. dist., marked 4823 BT.
	45 00	A pinion, 26 ins. diam., brs. S.35° W., 290 lks. dist., marked \$222 BT.
	47.00 58.00	Enter heavy timber brs. E. and W. Draw, 1 ch. wide, course SW. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the
	80.00	ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap
		T27N R3E S15 S14
		\$22 \$23 1916
		From which
		A pinion, 7 ins. diam., brs. N.53% E., 11 lks. dist., marked T27N R3E S14 BT. A pinion, 8 ins. diam., brs. S.14% E., 88 lks. dist.,
		marked T27N R3E S23 BT. A pinion, 12 ins. diam., brs. S.112° W., 135 lks. dist.,
	• .	marked T27N R3E S22 BT. A pinion, 10 ins. diam., brs. N.412° W., 48 lks. dist., marked T27N R3E S15 BT.
		Land, rolling. Soil, loose, yellow, rocky loam.
		Timber, pinion and juniper. Undergrowth, sagebrush, squawbrush, and scattering broom- weed, 1 ft. high. Fair grass.
	-	
	40.00 80.00	S.89° 49' E., on a random line, bet. secs. 14 and 23. Set temp. 2 sec. cor. Intersect N. and S. line, 14 lks. N. of the cor. of secs.
		13, 14, 23 and 24.
	10.00	N.89° 43' W., on a true line, bet. secs. 14 and 23. Over gently rolling land, through heavy timber and scattering undergrowth.
	10.00 22.00 40.00	Draw, 3 chs. wide, course SW. Draw, 1 ch. wide, course S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		1/4 S23 1916

BCCY 2102

```
Completion of Subdivision of T. 27 N.
                                                            R. 3 E.
Chains.
            From which
            A pinion, 12 ins. diam., brs. N.29\frac{1}{2}° E., 28 lks. dist.
            marked \frac{1}{4}S14 3T.
            A pinion, 24 ins. diam., brs. S.28\frac{1}{4}° E., 107 lks. dist.,
            marked \frac{1}{4}S23 BT.
51.00
         Draw, course S.
80.00
         The cor. of secs. 14, 15, 22 and 23.
         Land, gently rolling.
        Soil, loose, yellow, gravelly loam, over limestone formation. Timber, pinion and juniper.
         Undergrowth, sagebrush, squawbrush.
         Fair grass.
```

N.0° 1' W., bet. secs. 14 and 15. Over gently rolling land, through heavy timber and scattering undergrowth.

11.00

Draw, 1 ch. wide, course W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor, marked on brass cap 40.00

1/4 S15 S14

From which A pinion, 8 ins. diam., brs. N.49° E., 26 lks. dist., marked \$\frac{1}{4}\$S14 BT.
A pinion, 8 ins. diam., brs. S.42° W., 42 lks. dist., merked 4S15 BT.

45.50 80.00

Draw, 1 ch. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on brasss cap

T27N R3E sio síi S15 | S14 1916

From which A pinion, 10 ins. diam., brs. N.133° E., 35 lks. dist. marked T27N R3E S11 BT. 16 ins. diam., brs. S.57° E., 140 lks. dist. A pinion, marked T27N R3E S14 BT. A pinion, 14 ins. diam., brs. S.4530 W., 48 lks. dist. marked T27N R3E S15 BT. A pinion, 14 ins. diam., brs. N.72° W., 92 lks. dist., marked T27N R3E S10 BT. Land, gently rolling. Soil, loose, yellow, loam, over limestone formation. Timber, pinion and juniper. Undergrowth, sagebrush and squawbrush. Fair grass.

S.89° 43' E., on a random line, bet. secs. 11 and 14. 40.00 Set temp. $\frac{1}{4}$ sec. cor. 80.09 Intersect N. and S. line, 7 lks. N. of the cor. of secs. 11, 12, 13 and 14. Thence N.89° 40' W., on a true line, bet. secs. 11 and 14. Over gently rolling land, through scattering timber and undergrowth.

40.042 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap

8.	·	Completion of Subdivision of T. 27 N. R. 3 E.
Ī	Chains	
		¹ / ₄ S11
	,	1916
		1910
		From which
		A pinion, 14 ins. diam., brs. N.194° E., 86 lks. dist.
		marked 4S11 BT.
		A cedar, 8 ins. diam., brs. S.31\frac{3}{4}\circ \text{W., 5 lks. dist.,}
.		marked \$14 dT.
	50.00	Small draw, course NW.
	80.09	The cor. of secs. 10, 11, 14 and 15.
		Land, gently rolling.
		Soil, coarse texture, 26 ins. deep. Timber, dense cedar and pinion.
		Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 1
		ft. high.
		Fair grass.
.		
-		
		N.O° 1' W., on a random line, bet. secs. 10 and 11.
	40.00	Set temp. \(\frac{1}{4}\) sec. cor.
	80.30	Intersect E. and . Wyline, 49 lks, W. of the reestablished cory
	,	of secs12,3;10&11, which is a pinion post, hereinbefore
		descriped.
		Thence
		S.0° 20' W., on a true line, bet. secs. 10 and 11. Over gently rolling land, through heavy timber and scatter-
		ing undergrowth.
	40.30	Set an iron post, 3 ft. long, 1 in. diam., 26 ins in the
	4,5 0) 0	ground, for a sec. cor., marked on brass cap
1		<u> </u>
		1916
		1910
		From which
	,	A pinion, 24 ins. diam., brs. N.132° E., 66 lks. dist.
		marked \(\frac{1}{4}\)S11 3T.
-		A pinion, 29 ins. diam., brs. N.29° W., 60 lks. dist.,
	43.00	marked 4S10 BT.
	41.00	Draw, 3 chs. wide, course W. Draw, 2 chs. wide, course NW.
	80.30	The cor. of secs. 10, 11, 14 and 15.
1	.00.70	Land, gently rolling.
	,	Soil, loose, yellow loam, over limestone formation.
		Timber, pinion and juniper.
	•	Undergrowth, sagebrush and squawbrush.
		Fair grass.
1	•	
	-	
	•	
		From the cor. of secs. 33 and 34, on the S. bdy. of the
		Tp., which is an iron post, described in Book "H", N.O° 2' W., bet. secs. 33 and 34.
		Over rolling land, through heavy timber and scattering
		undergrowth.
	20.00	Draw 1 chs. wide. course W.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
		ground, for 4 sec. cor, marked on brass cap
		1827 821
		4877 874
		1916
		From which
		A pinion, 12 ins. diam., brs. S.88° E., 55 lks. dist.,
		marked $\frac{1}{2}$ S34 BT. A pinion, 12 ins. diam., brs. N.67 $\frac{1}{2}$ ° W., 105 lks. dist.,
		w biurou' is ing. diam. org. M. ols M. to) irg. disc.

```
Completion of Subdivision of T. 27 N.
Chains.
                marked $333 BT.
            Leave heavy timber, enter scattering timber, brs. NE. and
 55.00
           Draw, 3 chs. wide, course W. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on
 63.00
 80.00
                brass cap
                                           T27N ~3E
S28 S27
S33 S34
1916
                From which
                A pinion, 6 ins. diam., brs. N.64\frac{1}{2}° E., 108 lks. dist., marked T27N R3E S27 BT.
A pinion, 12 ins. diam., brs. S.4\frac{1}{2}° E., 43 lks. dist.,
                marked T27N R3E S34 BT.
A pinion, 12 ins. diam., brs. S.413° W., 314 lks. dist.,
               marked T27N R3E S33 BT.
A pinion, 10 ins. diam., brs. N.664 W., 168 lks. dist., marked T27N R3E S28 BT.
           Land, rolling.
          Soil, loose, yellow, rocky loam. Timber, pinion and juniper.
           Undergrowth, sagebrushand squawbrush.
          Fair grass.
         S.89° 59' E., on a random line, bet. secs. 27 and 34. Set temp. 1 sec. cor.
40.00
79.90 Intersect the corner of secs. 26, 27, 34 and 35....
           Thence
           N.89° 59' W., on a true line, bet. secs. 27 and 34. Over rolling land, through scattering timber and under-
               growth.
          Draw, 3 chs. wide, course SW.
Draw, 50 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
25.90
38.90
39 • 95
               From which
               marked \frac{1}{4}S27 BT.

A juniper, 12 ins. diam., brs. S.653° W., 41 lks. dist., marked \frac{1}{4}S34 BT.
54.85 79.90
          Road, brs. NW. and SE.
          The cor. of secs. 27, 28, 33 and 34.
         Land, rolling.
Soil, loose, yellow loam, over limestone formation.
          Timber, pinion and juniper.
          Undergrowth, sagebrush and squawbrush, and broom weed, 6 ins. to 18 high.
          Fair grass.
          N.O° 2' W., bet. secs. 27 and 28.
          Over rolling land, through scattering timber and under-
               growth.
12.00
          Draw, 2 chs. wide, course W. Road, brs. NW. and SE.
30.10
40.00
          Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
               ground, for \frac{1}{4} sec. cor., marked on brass cap
```

20.		Completion of Subdivision of T. 27 N., R. 3 E.
	Chains.	½S28 S27
		1916
		From which A pinion, 12 ins. diam., brs. N.69° E., 87 lks. dist., marked \(\frac{1}{4}\)S27 BT. A pinion, 12 ins. diam., brs. N.24\(\frac{3}{4}\)° W., 30 lks. dist., marked \(\frac{1}{4}\)S28 BT.
	50.00 64.00 80.00	Enter heavy timber, brs. NE. and W. Draw, 2 chs. wide, course W. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 21, 22, 27 and 28, marked on brass cap
		T27N R3E S21 S22 S28 S27 1916
		From which A pinion, 8 ins. diam., brs. N.833° E., 88 lks. dist., marked T27N R3E S22 BT. A pinion, 12 ins. diam., brs. S.653° E., 78 lks. dist., marked T27N R3E S27 BT. A pinion, 14 ins. diam., brs. S.13½° W., 136 lks. dist., marked T27N R3E S28 BT. A pinion, 8 ins. diam., brs. N.34° W., 120 lks. dist., marked T27N R3E S21 BT.
		Land, rolling. Soil, loose, yellow loam, over limestone formation. Timber, pinion and juniper. Undergrowth, sagebrush and squawbrush, and broom weed, 6 to 18 ins. high. Fair grass.
	40.00 79.96	S.89° 59' E., on a random line, bet. secs. 22 and 27. Set temp. ½ sec. cor. Intersect N. and S. line, 2 lks. S. of the cor. of secs. 22, 23, 26 and 27. Thence West on a true line, bet. secs. 22 and 27.
	1 9. 95 39 . 98	Over rolling land, through scattering timber and undergrowth.
·		\$22 \$27 1916 From which
	79.96	A pinion, 18 ins. diam., brs. N.43° E., 242 lks. dist. marked \(\frac{1}{4}\)S22 BT. A pinion, 12 ins. diam., brs. S.16\(\frac{3}{4}\)° W., 150 lks. dist., marked \(\frac{1}{4}\)S27 BT. The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, loose, yellowloam. Timber, pinion and juniper.
	79.96	marked \(\frac{1}{4}\) \(\text{S22 BT.} \\ A pinion, 12 ins. diam., brs. \(\text{S.163° W.}, \) 150 lks. dist., marked \(\frac{1}{4}\) \(\text{S27 BT.} \) The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, loose, yellowloam.

```
Completion of Subdivision of T. 27 N., R. 3 E.
                                                                                                   21.
Chains.
            Over rolling land, through heavy timber, and scattering
                undergrowth.
 10.00
           Draw, 1 ch. wide, course SW. Road in draw, brs. NE. and SW.
           Draw, 2 chs. wide, course SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor, marked on brass cap
 34.00
 40.00
                                            1/4 S21 | S22
                                                 1916
                A juniper, 6 ins. diam., brs. N.59^{3}° E., 69 lks. dist., marked \frac{1}{4}S22 BT. A juniper, 8 ins. diam., brs. N.42° W., 170 lks. dist.,
           marked \frac{1}{4}S21 BT.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on
 80.00
                brass cap
                                            T27N R3E
S16|S15
                                              S21 | S22
                                                 1916
                From which
                A juniper, 8 ins. diam., brs. N.70\frac{1}{2}° E., 78 lks. dist.,
                marked T27N R3E S15 BT.
A pinion, 8 ins. diam., brs. S.38% E., 75 lks. dist., marked T27N R3E S22 BT.
                A pinion, 16 ins. diam., brs. S.10\frac{1}{4}^{\circ} W., 90 lks. dist., marked T27N R3E S21 BT.
                A pinion, 8 ins. diam., brs. N.40\frac{1}{2}° W., 71 lks. dist., marked T27N R3E S16 BT.
           Land, rolling.
Soil, loose, yellow loam.
           Timber, pinion and juniper.
           Undergrowth, sagebrush and squawbrush and broom weed. 6
                to 12 ins. high.
           Fair grass.
           East on a random line, bet. secs. 15 and 22
40.00
           Set temp. 4 sec. cor.
79.98
           Intersect M. and S. line, 12 lks. S. of the cor. of secs.
               14, 15, 22 and 23.
           ^{\mathrm{T}}hence
           S.89° 55' W., on a true line, bet. secs. 15 and 22. Over gently rolling land, through heavy timber and scatter -
               ing undergrowth.
           Draw, 2 chs. wide, course SW.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
 9.00
39.99
                                            1916
               From which
                A pinion, 8 ins. diam., brs. N.19° E., 39 lks. dist,
               marked \frac{1}{4}$15 BT. A pinion, 8 ins. diam., brs. 8.12\frac{1}{2}° W., 60 lks. dist.,
          A pinion, 8 ins. diam., brs. S.12 marked 2522 BT.
The cor. of secs. 15, 16, 21 and 22.
79.98
          Land, gently rolling.
Soil, loose, yellow loam, over limestone formation.
Timber, pinion and juniper.
           Undergrowth, sagebrush, squawbrush and broom weed, 1 ft.
               high.
           Fair grass.
```

152

Completion of Subdivision of T. 27 N., R. 3 E 22. Chains. N.0° 2' W., bet. secs. 15 and 16. Over gently rolling land, through heavy timber and scattering undergrowth. Draw, 1 ch. wide, course W.
Draw, 2 chs. wide, course SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 2 sec. cor, marked on brass cap 2.00 12.00 40.00 4\$16 | \$15 1916 From which A pinion, 10 ins. diam., ors. N.50 $\frac{1}{4}$ ° E., 21 lks. dist. marked \(\frac{1}{4}\)S15 BT.

A pinion, \(\frac{1}{2}\) ins. diam., brs. S.62\(\frac{3}{2}\)° W., 48 lks. dist. marked $\frac{1}{4}$ S16 BT. Leave heavy, enter scattering timber, brs. NW. and SE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on 78.00 80.00 brass cap T27N R3E S 9 S10 S16 S15 1916 From which A pinion, 10 ins. diam., brs. N.65° E., 407 lks. dist. marked T27N $^{\rm R}3\rm E$ S10 BT. A pinion, 8 ins. diam., brs. S.53° E., 105 lks. dist., marked T27N R3E S15 BT. A pinion, 8 ins. diam., brs. $8.64\frac{1}{4}$ ° W., 133 lks. dist. marked T27N R3E S16 BT. A pinion, 12 ins. diam marked T27N R3E S9 BT. 12 ins. diam., brs. N.88° W., 190 lks. dist. Land, gently rolling. Soil, loose, yellow loam. Timber, pinion and juniper. Undergrowth, sagebrushand squawbrush. Fair grass. N.89° 55' E., on a random line, bet. secs. 10 and 15. Set temp. \(\frac{1}{4}\) sec. cor. 40.00 Intersect N. and S. line, 9 lks. N. of the cor. of secs. 79.96 10, 11, 14 and 15. S.89° 59' W., on a true line, bet. secs. 10 and 15. Over gently rolling land, through heavy timber and scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 39.98 \$15 1916 From which A pinion, 10 ins. diam., brs. N.60° E., 48 lks. dist., marked 1810 BT. 6 ins. diam., brs. $8.30\frac{1}{2}$ ° E., 65 lks. dist. A pinion, marked 4S15 BT. Leave heavy, enter scattering timber, brs. NW. and S. The cor. of secs. 9, 10, 15 and 16. 69.95 79.96 Land, gently rolling.
Soil, loose, yellow loam.
Timber, pinion and juniper. Undergrowth, sagebrush and squawbrush, and broom weed, 1 ft. high.

```
Completion of Subdivision of T. 27 N. A. 3 E.
Chains.
             Fair grass.
             N.0° 2' W., on a random line, bet. secs. 9 and 10, Set temp. \frac{1}{4} sec. cor.
 40.00
             Intersect E.& W. line, 2 lks.W. of reestablished cor.of secs. 3, 4, 9 and 10, which is an iron post, hereinbefore
 80.90
                  described.
             Thence
             S.0° 1' E., bet. secs. 9 and 10.
             Over gently rolling land, through heavy timber and scatter-
                  ing undergrowth.
            Draw, 1 ch. wide, course SW.
Leave heavy, enter scattering timber, brs. E. and W.
Draw, 2 chs. wide, course W.
 11.90
 20.90
 28.90
            Draw, 1 ch. wide, course NW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor, marked on brass cap
 34.90
 40.90
                                               \frac{1}{4}S 9 S 10
                 From which
                 A pinion, 14 ins. diam., brs. S.202° E., 308 lks. dist.
                 marked 4S10 BT.
                 A pinion, 6 ins. diam., brs. S.3° W., 177 lks. dist.,
                 marked 4S9 BT.
            Enter heavy timber, brs. E. and W. Leave heavy, enter scattering timber, brs. NE. and SW.
 42.90
70.90
73.90
80.90
            Draw, 1 ch. wide, course SW. The cor. of secs. 9, 10, 15 and 16.
            Land, gently rolling.
Soil, loose, yellow loam.
Timber, pinion and juniper.
            Undergrowth, sagebrush and squawbrush, and broom weed, 12
                 ins high.
            Fair grass.
            From the cor. of secs. 32 and 33, on the S. bdy.of the Tp., which is an iron post, described in Book "H", N.O° 3' W., bet. secs. 32 and 33.

Over gently rolling land, through scattering timber and
                 undergrowth.
           Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for \frac{1}{4} sec. cor., marked on
40.00
                 brass cap
                                               <del>1</del>832 833
                                                    1916
                 From which
                 A pinion, 10 ins. diam., brs. 8.87\frac{1}{4}° E., 237 lks. dist., marked \frac{1}{4}833 BT.
A pinion, 12 ins. diam., brs. 8.25\frac{1}{4}° W., 284 lks. dist., marked \frac{1}{4}852 BT.
51.50
            S. end of dry reservoir dam, brs. NE.
55.00
77.00
           Wide draw, course NW. Wide draw, course SW.
80.00
            Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on
                 brass cap
                                               T27N R35 S29 S28
```

24.		Completion of Subdivision of T. 27 N., R. 3 E.
	Chains.	
		From which A pinion, 10 ins. diam., brs. N.28° E., 305 lks. dist., marked T27N R3E S28 BT. A pinion, 12 ins. diam., brs. 8. 54½° E., 11 lks. dist., marked T27N R3E S33 BT. A pinion, 12 ins. diam., brs. S.22° W., 147 lks. dist.
•		marked T27N R3E S32 BT. A pinion, 12 ins. diam., brs. N.21½° W., 488 lks. dist., marked T27N R3E S29 BT. Land, gently rolling. Soil, coarse texture, 18 to 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush and holly brush, 1 to 4 ft. high. Fair grass.
	· <u></u>	
	4 0.00 80.04	S.89° 59! E., on a random line, bet. secs. 28 and 33. Set temp. ½ sec. cor. Intersect N. and S. line, 5 lks. N. of the cor. of secs. 27, 28, 33 and 34. Thence
		N.89° 57' W., on a true line, bet. secs. 28 and 33. Over gently rolling land, through scattering timber and undergrowth.
•	40.02	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1 528 \$33
		1916
	69.00 80.04	From which A pinion, 12 ins. diam., brs. N.44½° E., 40 lks. dist., marked ½\$28 BT. A pinion, 12 ins. diam., brs. \$5.50½° E., 30 lks. dist., marked ½\$33 BT. Wide draw, course SW. The cor. of secs. 28, 29, 32 and 33. Land, gently rolling. Soil, coarse texture, 18 to 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass.
	25.00 40.00	N.0° 3' W., bet. secs. 28 and 29. Over gently rolling land, through scattering timber and undergrowth. Leave scattering timber. Set an iron post, 3 ft. long, l in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1916
	47.20 62.00 80.00	And dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist. Shallow draw, course SW. Also dry ditch, 15 lks. wide, I ft. deep, course SW. Enter scattering timber. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, marked on brass cap T27N R3E SS20 S21 S29 S28 1916

DOOK 3102

		LUCK 31 Completion of Subdivision of E. 27 N. R. 3 E. 25.
	Chains.	
		From which A pinion, 8 ins. diam., brs. N.49° E., 421 lks. dist., marked T27N R3E S21 BT. A pinion, 12 ins. diam., brs. S·1° E., 209 lks. dist., marked T27N R3E S28 BT. A pinion, 10 ins. diam., brs. S·38½° W., 269 lks. dist., marked T27N R3E S29 BT. No other trees within limits. Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass.
	40.00 79.95 25.95 39.97 2	S.89° 57' E., on a random line, bet. secs. 21 and 28. Set temp. 4 sec. cor. Intersect the corner of secs. 21, 22, 27 and 28. Thence, N.89° 57' W., on a true line, bet. secs. 21 and 28. Over gently rolling land, through scattering timber and undergrowth. Draw, course SW. Road, brs. NE. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		<u>1</u> 821
		\$28 1916
	51.95 59.75 63.15 79.95	From which A pinion, 10 ins. diam., brs. N.31° W., 146 lks. dist., marked \(\frac{1}{4}S21 \) BT. A pinion, 10 ins. diam., brs. S.36\(\frac{1}{6}\) E., 80 lks. dist., marked \(\frac{1}{4}S28 \) BT. Draw, course SW. From this point, cement cistern brs. S. 3.50 chs. dist. Road, brs. NW. and SE. Draw, course NW. Road, brs. NW. and SE. The cor. of secs. 20, 21, 28 and 29. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, ceder and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass.
	1.00 1.50 16.90 26.70 40.00	N.0° 3' W., bet. secs. 20 and 21. Over gently rolling land, through scattering timber and undergrowth. Wide draw, course W. Road, brs. NW. and SE. Road, brs. NW. and SE. Wide draw, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
,		
	·	1916
THE RESERVE THE PERSON NAMED IN THE PERSON NAM		From which A pinion, 15 ins. diam., brs. $S.19\frac{1}{2}^{\circ}$ E., 113 lks. dist., marked $\frac{1}{4}S21$ BT.

26		Completion of Subdivision of T. 27 N., R. 3 E.
	80.00	A pinion, 14 ins. diam., brs. S.153° W., 287 lks. dist., marked \$200 BT. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on
٠,		T27N R3E S17 S16 S20 S21 1916
		And raise a mound of stone, 3 ft.base, 3 ft. high, W. of cor. Land, gently rolling Soil, coarse texture, 26 ins. deep. Timber, a few scattering cedar and pinion trees. Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 1 ft. high. Fair grass.
	40.00 80.00	S.89° 57' E., on a random line, bet. secs. 16 and 21. Set temp. 4 sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs. 15, 16, 21 and 22. hence
-	17.00 35.50 4 0.00	N.89° 59' W., on a true line, bet. secs. 16 and 21. Over gently rolling land, through scattering timber and undergrowth. Wide, shallow draw, course SW. Shallow draw, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
•	-	$\frac{\frac{1}{4}S16}{S21}$ 1916 From which A pinion, 10 ins. diam., brs. N.27\frac{1}{2}\circ E., 33 lks. dist.
	50.00 80.00	marked \(\frac{1}{4}\) S16 BT. A pinion, 12 ins. diam., brs. S.77\(\frac{3}{4}\) W., 48 lks. dist. marked \(\frac{1}{4}\) S21 BT. Leave scattering timber. The cor. of secs. 16, 17, 20 and 21. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 1 ft. high. Fair grass.
	18.10 40.00	N.0° 3' W., bet. secs. 16 and 17. Over gently rolling land, through scattering undergrowth. Enter scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		1916 From which A pinion, 10 ins. diam., brs. S.69° E., 88 lks. dist., marked 4816 BT. A pinion, 10 ins. diam., brs. S.37½° W., 163 lks. dist., marked 4817 BT.

```
Completion of Subdivision of T. 27 N., R. 3 E.
                                                                                     27.
Chains.
 64.00
          Draw, course NW.
72.50
80.00
          Small draw, course SW.
          Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on
              brass cap
                                     T27N R3E
S 8 S 9
                                       $17 S16
                                          1916
              From which
              A pinion, 10 ins. diam., brs. N.36\frac{1}{2}° E., 186 lks. dist.
              marked T27N R3E $9 BT.
                           12 ins. diam., brs. 5.31\frac{1}{4}° E., 168 lks. dist.,
              marked T27N R3E S16 BT.
              A pinion, 10 ins. diam., brs. S.33° W., 182 lks. dist.,
              marked T27N R3E S17 BT.
          A pinion, 14 ins. diam., brs. N.15% W., 127 lks. dist., merked T27N R3E S8 BT.
Land, gently rolling.
          Soil, coarse texture, 26 ins. deep.
          Timber, scrub cedar and pinion.
          Undergrowth, sagebrush and hollybrush, 1 to 4 ft. high.
          Fair grass.
         S.89° 59' E., on a random line, bet secs. 9 and 16. Set temp. ½ sec. cor.
Intersect N. and S. line, 11 lks. S. of the cor. of secs.
 40.00
80.00
             9, 10, 15 and 16.
          Thence
          S.89° 56' W., on a true line, bet. seas. 9 and 16.
          Over gently rolling land, through scattering timber and
              undergrowth.
40.00
         Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
              ground, for 3 sec. cor., marked on brass cap
                                     15 9
516
              From which
              A pinion, 10 ins. diam., brs. N.23\frac{1}{2}° E., 98 lks. dist.,
             marked \frac{1}{4}S9 BT. A pinion, 12 ins. diam., brs. S·16\frac{3}{4}° W., 125 lks. dist.,
              marked \frac{1}{4}$16 BT.
45.00
         Small draw, course SW.
  2.00 Wide draw, course SW. 80.00 The cor. of secs. 8, 9, 16 and 17.
72.00
         Land, gently rolling.
Soil, coarse texture, 26 ins. deep.
Undergrowth, sagebrush, 1 to 3 ft. high.
         Timber, scrub cedar and pinion.
         N.0° 3' W., on a random line, bet. secs. 8 and 9. Set temp. 3 sec. cor.
Intersect E.and W.line,6 1ks.E.of original cor.of secs.
40.00
81.57
             4,5,8 and 9, which is a limestonemhere inbefore described.
         S.0° 6' E., on a true line, bet. secs. 8 and 9. Over gently rolling land, through scattering timber and
            .undergrowth.
41.57
         Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
             ground, for 1 sec. cor., marked on brass cap
```

.28	•	Completion of Subdivision of T. 27 N., R. 3 E.
	Chains.	14S 8 S 9
		1916
		From which A pinion, 10 ins. diam., brs. N.38° E., 115 lks. dist.
	53.35 81.57	marked ½\$9 BT. A pinion, 16 ins. diam., brs. N.43° W., 132 lks. dist.
		marked 388 BT.
-		Draw, 5 chs. wide, 15 ft. deep, course W. The cor. of secs. 8, 9, 16 and 17.
		Land, gently rolling. Soil, coarse texture, 26 ins. deep.
		Timber, scrub cedar and pinion.
		Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass.
	` -	
		From the cor. of secs. 31 and 32, on the S. bdy. of the
		Tp., which is an iron post, described in Book "H", N.0° 3' W., bet. secs. 31 and 32.
		Over gently rolling land, through scattering timber and
	28.00	Undergrowth. Draw, course W.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor, marked on brass cap
		1916
		1916
		From which A pinion, 8 ins. diam., brs. S.84½° E., 298 lks. dist.
	80.00	marked $\frac{1}{4}$ S32 BT. A oedar, 16 ins. diam., brs. N.57 $\frac{1}{2}$ ° W., 255 lks. dist.
		marked 7851 BT.
		Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for cor. of secs. 29, 30, 31 and 32, marked on
		brass cap T27N R3E
		\$30\\$29
		\$31 \$32 1916
		From which
•		A pinion, 14 ins. diam., brs. N.254° E., 21 lks. dist. marked T27N R3B S29 BT.
		A pinion, 15 ins. diam., brs. S.71 $\frac{1}{2}$ ° E., 157 lks. dist.
		marked T27N R3E S32 BT. A pinion, 15 ins. diam., brs. S.80° W., 49 lks. dist.,
		marked T27N R3E S31 BT. A pinion, 12 ins. diam., brs. N.76 $\frac{1}{4}$ ° W., 140 lks. dist.
		marked T27N R3E S30 BT.
		Land, gently rolling. Soil, coarse texture, 26 ins. deep.
		Timber, cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 1
		ft. high. Fair grass.
		Tall glass.
		S.89° 59' E., on a random line, bet. secs. 29 and 32.
	40.00	Set temp. 4 sec. cor.
	80.00	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 28, 29, 32 and 33.
	and the second s	Thence West on a true line, bet. secs. 29 and 32.

Completion of Subdivision of T. 27 N. R. 3 E. 29 Chains. Over gently rolling land, through scattering timber and undergrowth. Draw, course Nw. Draw, course SW. 21.00 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap And dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. 55.00 80.00 Shallow draw, course NW. The cor. of secs. 29, 30, 31 and 32. Land, gently rolling.
Soil, coarse texture, 26 ins. deep. Timber, a few scattering cedar and pinion trees. Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed. 1 ft. high. Fair grass. N.89° 59' W., on a random line, bet. secs. 30 and 31. Set temp. 4 sec. cor. 40.00 78.26 Intersect W. bdy. of Tp., 5 lks. N. of the cor. of secs. 25, 30, 31 and 30, which is an iron post, described in Book "G". N.89° 59' E., on a true line, bet: secs. 30 and 31. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 38:26 From which A cedar, 8 ins. diam., brs. N.50 $\frac{1}{2}$ ° E., 58 lks. dist., marked $\frac{1}{2}$ S30 BT. A pinion, 12 ins. diam., brs. S.20% E., 295 lks. dist., marked $\frac{1}{4}$ S31 BT. The cor. of secs. 29, 30, 31 and 36. 78.26 Land, gently rolling.
Soil, coarse texture, 26 ins. deep. Timber, cedar and pinion. Undergrowth, sagebrush and holly brush, 1 to 5 ft. high. Fair grass. N.0° 3' W., bet. secs. 29 and 30. Over gently rolling land, through scattering timber and undergrowth. 5.00 Shallow draw, course W. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 1530 S29 1916 From which

A pinion, 10 ins. diam., brs. S.29° E., 72 lks. dist.,

A pinion, 6 ins. diam., brs. N.4° W., 132 lks. dist.,

marked 4529 BT.

```
Chains.
               marked \frac{1}{4}S30 BT.
          Wire fence, brs. NE. and SW. Wide draw, course SW. Dry reservoir 10 chs. down draw. Wire fence, brs. NW. and SE.
 62.70
 63.70
 65.08
75.50
76.63
          Ditch, 18 lks. wide, 18 ins. deep, course SW. Road, brs. NE. and SW.
 80.06
          Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on
               brass cap
                                        T27N R3E
                                          S19 | S20
                                          830 S29
                                            1916
               From which
               A pinion, 12 ins. diam., brs. N.71\frac{1}{2}° E., 125 lks. dist.
               marked T27N R3E S20 BT.
               A pinion, 8 ins. diam., brs. S.88° W., 317 lks. dist., marked T27N R3E S30 BT.
           No other trees within limits.
                                                     Raise a mound of stone, 3
           ft. base, 3 ft. high, W. of cor. Land, rolling and gently rolling. Soil, coarse texture, 26 ins. deep.
           Timber, scrub cedar and pinion.
           Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 1
               ft. high.
           Fair grass.
           East on a random line, bet. secs. 20 and 29.
           Set temp. 1 sec. cor. Intersect. the corner of sections 20, 21, 28 and 29.
 40.00
 79 • 97
           †hence
           West on a true line, bet. secs. 20 and 29. Over gently rolling land, through scattering timber and
              undergrowth.
 39.982 Set an iron post, 5 ft. long, 1 in. diam., 26 ins. in the ground, for 2 sec. cor., marked on brass cap
                                        <u></u>$20
$29
               From which
                             12 ins. diam., brs. N.63\frac{1}{2}\circ E., 310 lks. dist.,
               A pinion,
               marked \frac{1}{4}S20 BT.
               A pinion, 12 ins. diam., brs. S.6310 E., 66 lks. dist.
           marked 4$29 BT.

Road, brs. NE. and NW.

Ditch, in bottom of draw, course NW. from NE.

Ditch, 18 lks. wide, 18 ins. deep, course SW.
 41.45
43.85
71.15
71.85
           Road, brs. NE. and SW.
 79.97.
           The cor. of secs. 19, 20, 29 and 30.
           Land, gently rolling. Soil, coarse texture, 26 ins. deep.
           Timber, a few scattering cedar and pinion trees.
           Undergrowth, sagebrush, 1 to 4 ft. high, and broom weed, 1
               ft. high.
           Fair grass.
           S.89° 59' W., on a random line, bet. secs. 19 and 30.
 40.00
           Set temp. \frac{1}{4} sec. cor.
           Intersect W. bdy. of Tp., 14 lks. S. of the cor. of secs.
               19, 24, 25 and 30, which is an iron post, described in Book "G".
 78.36
```

Completion of Subdivision of T. 27 N. R. 3 E. Chains. Thence S.89° 55' E., on a true line, bet. secs. 19 and 30. Over gently rolling land, through scattering timber and undergrowth. Leave scattering timber, brs. NW. and SE.

Set an iron post, 3 ft. long, lin. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 18.35 38.36 \$30 1916 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. 78.36 The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, loose, yellow clay and loam. Timber, scattering cedar and pinion. Undergrowth, sagebrush, and broom weed, 1 ft. high. N.0° 3' W., bet. secs. 19 and 20. Over gently rolling land, through scattering timber and undergrowth. 24.00 Draw, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 40.00 1319 S20 1916 From which A cedar, 6 ins. diam., brs. $N.9\frac{1}{2}$ ° E., 205 lks. dist., marked $\frac{1}{4}S20$ BT. A pinion, 10 ins. diam., brs. N.53° W., 535 lks. dist., marked 4819 BT. 40.50 59.50 64.80 Wide, shallow draw, course W. Small draw, course SW. Road, brs. NW. and SE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on 80.00 brass cap T27N R3E S18 S17 S19 | S20 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, a few scattering scrub cedar and pinion trees. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass. East on a random line, bet. secs. 17 and 20. 40.00 Set temp. 4 sec. cor. 79.84 Intersect N. and S. line, 15 lks. N. of the cor. of secs. 10, 17, 20 and 21. Thence N.89° 54' W., on a true line, bet. secs. 17 and 20. Over gently rolling land, through scattering undergrowth. 20.00 Enter scattering timber, brs. NE. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 39.92

ground, for 2 sec. cor., marked on brass cap

52.	Completion of Subdivision of T. 27 N. B. 3 E.
Chains.	½S17 S20 1916
54.00 60.00 79.84	From which A pinion, 12 ins. diam., brs. N.59½° E., 40 lks. dist., marked ½S17 BT. A pinion, 10 ins. diam., brs. S.45½° E., 93 lks. dist., marked ½S20 BT. Draw, course SW. Leave scattering timber, brs. N. and S. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass.
40.00 78.28	N.89° 55' W., on a random line, bet. secs. 18 and 19. Set temp. ½ sec. cor. Intersect W. bdy. of Tp., 5 lks. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in Book "G".
	Thence S.89° 53' E., on a true line, bet. secs. 18 and 19. Over gently rolling land, through scattering timber and undergrowth.
38 .2 8	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
	1518 519 1916
54.15 78.28	And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. Road, brs. W. and SE. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling.land, Soil, coarse texture, 26 ins deep. Timber, a few scattering scrub cedar and pinion trees. Undergrowth, sagebrush and holly brush, 1 to 5 ft. high. Fair grass.
29.00 40.00	N.0° 3' W., bet. secs. 17 and 18. Over gently rolling land, through scattering undergrowth. Wide draw, course W. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
	½S18 S17
	1916
53.00 61.00 80.00	And raise a mound of stone, 2 ft. base, 21 ft. high, W. of cor. Wide, shallow draw, course SW. Enter scattering timber. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap
	T27N R3E S 7 S 8 S18 S17 1916

33.

Completion of Subdivision of T. 27 N., R. 3 E. Chains. From which A pinion, 8 ins. diam., brs. N.75% E., 173 lks. dist., marked T27N R3E S8 BT. 12 ins. diam., brs. S.544° E., 117 lks. dis., A pinion, marked T27N A3E S17 BT. 8 ins. diam., brs. S.64° W., 95 lks. dist., A pinion, marked T27N R3E S18 BT. A pinion, 11 ins. diam., brs. $N.3\frac{1}{2}^{\circ}$ W., 100 lks. dist., marked T27N R3E S7 BT. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high, and broom weed, 1 ft. high. Fair grass. S.89° 54' E., on a random line, bet. secs. 8 and 17. Set temp. 2 sec. cor. 40.00 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 79.98 8, 9, 16 and 17. Thence N.89° 57' W., on a true line, bet. secs. 8 and 17. Over gently rolling land, through scattering timber and undergrowth. 20.00 Draw, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap 39.99 1916 From which A pinion, 10 ins. diam., brs. N.58½° E., 210 lks. dist., marked $\frac{1}{4}$ S8 BT. A pinion, 8 ins. diam., brs. S.73° E., 415 lks. dist., marked \$\frac{1}{2}\$17 BT. 50.00 79.98 Small draw, course SW. The cor. of secs. 7, 8, 17 and 18. Land, gently rolling.
Soil, coarse texture, 26 ins. deep. Timber, scattering scrub cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass. N.89° 53! W., on a random line, bet. secs. 7 and 18. Set temp. ½ sec. cor.
Intersect W. bdy. of Tp., 2 lks. S. of the cor. of secs.
7, 12, 13 and 18, which is an iron post, described in 40.00 78.05 Book "G".. Thence S.89° 52' E., on a true line, bet. secs. 7 and 18. Over gently rolling land, through scattering timber and undergrowth. 38.0**5**

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap

¹/₄S 7 S18

From which A pinion, 12 ins. diam., brs. N.84° E., 224 lks. dist., marked $\frac{1}{4}$ S7 BT. A pinion, 8 ins. diam., brs. $5.54\frac{1}{2}$ ° E., 159 lks. dist.,

34.

•		Completion of Subdivision of T. 27 N., R. 3 E.
	65.05 78.05	marked \$\frac{1}{2}\$\$18 BT. Shallow draw, course SW. The cor. of secs. 7, 8, 17 and 18. "and, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering scrub cedar and pinion. Undergrowth, sagebrush, 1 to 4 ft. high. Fair grass.
	40.00 82.10	N.0° 3' W., on a random line, bet. secs. 7 and 8. Set temp. 1 sec. cor. Intersect E. and W.line, 44 lks.E. of original corcof secs. 5, 6, 7 and 8, which is a limestone, bereinbefore described. Thence
	2 9.10 42.10	S.0° 21' E., on a true line, bet. secs. 7 and 8. Over gently rolling land, through scattering timber and undergrowth. Wide draw, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 48 7 8 8
	48.10 82.10	From which A pinion 14 ins. diam., brs. N.65% E., 160 lks. dist. marked 458 BT. A pinion, 12 ins. diam., brs. N.15% W., 283 lks. dist., marked 457 BT. Wide draw, course NW. The cor. of secs. 7, 8, 17 and 18. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering scrub cedar and pinion. Undergrowth, sagebrush, 1 to 3 ft. high. Fair grass.

General Description.

This township consists of gently rolling and rolling land, covered with a scattering growth of sagebrush, squawbrush and broom weed undergrowth, and cedar, pinion and juniper timber. The soil is a loose, rocky loam, of coarse texture, 10 to 26 ins. in depth.

There are no settlers. Several earth dams have been constructed in draws, for the impounding of flood waters.

35

Diagram showing the respective surveys executed by Thomas B. Matthews, U.S.S., and William L. Nash, U.S.T., under instructions for Group No. 55, Arizona.

Book "I"

BOCK 8102

Township 27 North, Range 3 East.

	6	5 .	4	3.	2	. 1
					*	
1	7-20-16	7-20-16	7-20-16 7-21-16	7-21-16		7-20-16
			• • • • • • • • • • • • • • • • • • •	ပ္	و	ي ا
31-7	7 8	8 8 8	9-62	7.25-16	11 26-1	12
6-27-16	7-2	2-2	7	~	7.	7
	7-29-16	7-29-16	7-28-16	7-29-16	7-25-16	7-25-16
	•		•			
6-27-16	. 81 29-16	. 17 %	آن 28-16	15 2 15 2	91-42	13 -50-16
2-2	-1 8	17 82	ē 5	ū 7-2	7.2	<u>5</u>
٧	7-28-16	7-29-16	7-26-16	7-28-16	7-24-16	7-24-16
		¹				
ত্	91	91	ভূ	22 24-16	, 23 %	24
6-27-16	19 28-16	. 20 %	21 21	22 %	/ 23	24 6
ف		- 07.16	7 00 115	7.26.16	7-24-16	7-21-16
	7-28-16	7-27-16	7-26-16	7-26-16	7-24 10	7-21-16
و	v	و	. <u>v</u>	91	ص	<u> </u>
6-27-16	30 27-16	29 🛪	28 8	27 27	26 26 21-12	25
9		,	, , ,	• 1	.7	· 7
	7-27-16	7-27-16	7-26-16	7-26-16	7-22-16	7-21-16
_						٥
J-16	31 \frac{72}{91-\frac{72}{12}}	32 %	33 %	34 -22-2	35 35	36 2
6-27-16	7.2	7.2	22 . %	7.2	7-2	N.
-						
Mr. or	7-8-16	7-8-16	7-8-16	7-8-16	7-8-16	7-8-16

Blue lines indicate surveys by Thomas B. Matthews, U.S.S. on the various dates shown.

Red. lines indicate surveys by William L.Nash, U.S.T., on the various dates shown.

Green lines indicate surveys by Deane J. Wolff. U.S.T. on the various dates shown.

CERTIFICATES OF U. S. SURVEYOR AND U. S. TRANSITMAN.

We, Thomas B. Matthews, and William L. Nash, U. S. Surveyor and U.S. Transitman, respectively, hereby certify on honor that, in pursuance of special instructions received from the U.S. Surveyor General for Arizona for Group No.55, Arizona, bearing date of the 8th day of March, 1915, we have well, faithfully, and truly, in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the East boundary and the Subdivision lines, and resurveyed all those parts or portions of the Subdivision lines, and resurveyed all those parts or portions of the Subdivision lines of TOWNSHIP 27 NORTH, RANGE 3 EAST.

of the Gila and Salt River Base and Mefidian, in the State of Arizona, which are represented in the Loregoing field notes, and by the diagram on the reverse hereof, as having been executed by us, and under our direction; and we do further certify on honor that all the corners of said Sanzya, retractments and resurveys have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S. Surveyor General Loft Arizona for Group No.55, and in the specific manner described in our respective field notes, and that the foregoing are the original field notes of such surveys retracements and resurveys.

Thomas B. Matthew William 2 had U. S. Transitman.

APPROVAL.

OFFICE OF THE UNITED STATES SURVEYOR GENERAL.

Phoenix, Arizona, CEP 28 1918.

The foregoing field notes of the Survey of the completion of the East Boundary and the Subdivision lines, Retracement of part of the Subdivision lines, and resurvey of part of the Subdivision lines of

TOWNSHIP 27 NORTH, RANGE 3 EAST.

of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by Thomas B. Matthews, U. S. Surveyor, and William L. Nash, U.S. Transitman, under special instructions dated March 8,1915, for Group 55, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys, methodements and resurveys they describe are hereby approved.

I certify that the foregoing transcript of the field notes of the above-described surveys and retracements in Book-"I" of Group 55, has been correctly copied from the criginal notes on file in this office.

U.S. Surveyor Concret of Arizona.