Book "J"

JAN 5 - 1918

BOOK 3103

FLUG 1913

FIELD NOTES

OF THE SURVEY OF THE

	NORTH BOUNDARY
	a nđ
***************************************	SUBDIVISION LINES
***************************************	o f
	TOWNSHIP 26 NORTH, RANGE 4 EAST.
	·
	·
·	
In the Sta	te ofArizona.
	EXECUTED BY
•	Thomas B. Matthews, U. S. Surveyor,
······································	and
••••••	William L. Nash, U. S. Transitman,
In the cap	acity of U.S. Surveyor, under instructions dated March 8, , 1915
issued by	the United States Surveyor General to govern surveys included in
$Group \mathcal{N}o.$	55, which were approved by the Commissioner of the General Land
	December 14. , 1915.
	Survey commenced August 1, 1916
•	Survey completed August 17, 1916.
	, 1910.

Executed under Assignment Instructions dated Apr. 13 & June 26, 1916.

.

N

3103

Book "J"

Group 55 - - - Arizona.

BOOK 3103

INDEX DIAGRAM.

	1.44 2.47	, • !	i b		L		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			1		
	2		3		3		4		5		Т	
<u>.</u>	 6	8	5	18	4	1	3	4 4	2	3 0	1	
	8		iĄ		19	·	25		31		31	L
***	7	9	8	ı	9	1) 10	25	11	31	12	
	9		14		20		26		32		32	
].				
	- 18	10		1		2		26	14	38	13	
_	10		16		1. 40	/ Y]	R.4E.	•	/34		34	L
:	19]	O 20	16	-) 21	2	22	2 7	23	34	24	
	11		16		22		2 8		35		36	
***	80		.1 29	1	7 28	2	27	28	26	36	25	
	12		17		23		29		37		37	L
ا مستند من حود و ا	31	13	32	18	88	2.	34	2 9	35	37	36	

Lines	surveyed	und er	this	group.
Accep	ted surve	78 .		

Areas surveyed as per accepted plats on file.

Survey of North Boundary of T. 26 N. Chains.

Surveys the reinafter described leavecuted suon dates shown to be on diagram on page 39 here of by Thomas Bt Matthews, U. -S. Sirve for and William Lonash, U. ds. Transitman, . -using Buff and Buff light mountain transit No. 20124, and Young and Sons light mountain transit No. 2535 prespective—

Totalgorial sons light mountains transit words of the strong described ind Book "B." strong. The strong the strong strong

West on a random line, along the N. bdy. of T. 26 N., R. 4 E., setting temporary \(\frac{1}{4} \) sec. and sec. cors. for the areas N. of line at intervals of 40.00 chs. from the cor. of Ts. 27 N., Rs. 4 and 5 E.; and at 482.97 chs. from the cor. of Ts. 26 N., Rs. 4 and 5 E., fall 46 lks. N. of the cor. of Ts. 26 N., Rs. 3 and 4 E., which is an iron post, described in Book "H". The falling answers to a correction of0° 3', or 7 lks. S. per mile, counting from the NE. cor. of the Tp. therefore

N.89° 57' E., on a true line, along the N. bdy. of sec. 6, T. 26 N., R. 4 E.

Over level land, through scattering undergrowth.

The cor. of Ts. 27 N., Rs. 3 and 4 E., which is an iron post, described in Book "I".

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor. \(\rho \) f sec. \(6 \), marked on brass cap, 40.00

15 6 1916

Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.

(40.17 chs. from the cor. of Ts. 27 N., Rs. 3 and 4 E.) Set an iron post, 3 ft. long, 1 in. diam. 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 31, marked on brass cap, 46.69

1831

1916

And dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.

66.50 80.00

Enter heavy timber, brs. N. and S.
Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 5 and 6, T. 26 N., R. 4 E., marked on brass cap

T27N R4E S31 S 6 S 5 T26N R4E

From which A pinion, 12 ins. diam., brs. S.8° E., 208 lks. dist. marked T26N R4E S5 BT. A pinion, 14 ins. diam., brs. S.65° W., 45 lks. dist., marked T26N R4E S6 BT.

Land, level. Soil, loose, yellow loam, over malpais formation. Timber, juniper and pinion. Undergrowth, sagebrush and broom weed, 1 ft. high.

Fair grass.

Survey Chains. North Boundary of T. 26 N. R. 4 E. of

N.89° 57' E., on a true line, along the N. bdy. of sec. 5., 7. 26 N., R. 4 E.

Over gently rolling land, through heavy timber and scatter-

6.69

ing undergrowth.

(80.17 chs. from the cor. of Ts. 27 N., Rs. 3 and 4 E.)

Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 31 and 32, T. 27 N., R. 4 E., marked on brass cap

> T27N | R4E T26N Ŕ4E 1916

From which.

26.70 40.00

46.69

A pinion, 16 ins. diam., brs. $N.58\frac{1}{2}$ ° E., 35 lks. dist. marked T27N R4E S32 BT.

Apinion, 10 ins. diam., brs. N.592° M., 186 lks. dist., marked T27N R4E S31 BT.

Leave, heavy, enter scattering timber, brs. NW. and S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor.of sec.5, marked on brass cap,

From which

A juniper, 8 ins. diam., brs. S.79° E., 213 lks. dist., marked $\frac{1}{2}$ S5°BT.

A pinion, 16 ins diam., brs. S.9 $\frac{1}{2}$ ° W., 219 lks. dist.,

diam., brs. S.9½° W., 219 lks. dist. marked 4S5 BT.

(40.00 chs. from the cor. of secs. 31 and 32, T. 27 N.,

R. 4 E.)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., of sec. 32, marked on brass cap,

ՀՏ32

1916

And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of secs. 4 and 5, T. 26 N., R. 4 E., marked on brass cap

> T27N R4E S 5 S 4 T26N R4E -1916

From which

A pinion, 12 ins. diam., brs. $8.64\frac{1}{2}$ ° E., 217 lks. dist., marked T26N R4E S4 BT.

A pinion, 14 ins. diam., brs. $8.66\frac{1}{2}$ ° W., 76 lks. dist.

marked T26N R4E S5 BT.

Land, gently rolling.
Soil, loose, yellow loam, over malpais formation.

Timber, pinion and juniper.

Undergrowth, sagebrush and broom weed, 1 ft. high. Fair grass.

N.89° 57' E., on a true line, along the N. bdy. of sec. 4, T. 20 N., R. 4 E. Over gently rolling land, through heavy timber and scattering undergrowth.

BOCK 3103

6.69

4 E.)

Survey of North Boundary of T. 26 N., R. 4 E. Chains (80.00 chs. from the cor. of secs. 31 and 32, T. 27 N., R 6.69 4 E.) Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of secs. 32 and 33, T. 27 N., R. 4 E. marked on brass cap T27N R4E 332 S33 S 4 T26N R4E 1916 From which A pinion, 10 ins. diam., brs. N.35½° E., 189 lks. dist. marked T27N R4E S33 BT.

A juniper, 20 ins. diam., brs. N.11½° W., 206 lks. dist., marked T27N R4E S32 BT.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor.of sec.4, msrked on brass cap, 40.00 And raise a mound of stone, 3 ft. base, 3 ft. high, S. of cor. (40.00 chs. from the cor. of secs. 32 and 33, T. 27 N., R 46.69 4 E.) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor.of sec. 33; marked on brass cap 3S33 **1**916 From which. A juniper. 10 ins diam., brs. $N.16\frac{3}{4}$ ° E.,152 lks. dist., marked \$333 BT.
A juniper, 16 ins. diam., brs. N.18° W., 230 lks. dist., marked \$\frac{1}{4}\$S33 BT. Draw, 1 ch. wide, course N. Draw, 1 ch. wide, course N. 51.70 72.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 3 and 4, T. 26 N., R. 4 E., marked on brass cap 80.00 T20N R4E \$33 \$4\$3 T26N R4E 1916 From which A juniper, 10 ins. diam., brs. S.147° E., 71 lks. dist., marked T26N R4E S3 BT. 14 ins. diam., brs. $8.63\frac{1}{2}$ W., 89 lks. dist. A pinion, 14 ins. diam marked T26N R4E S4 BT. Land, gently rolling.
Soil, loose, yellow loam, over malpais formation. Timber, pinion and juniper. Undergrowth, sagebrush and broom weed, 1 ft. high. Fair grass. N.89° 57' E., on a true line, along the N. bdy. of sec. 3 T. 26 N., R. 4 E. Over ~ rolling land, through scattering timber and undergrowth. Desc. 160 ft.

(80.00 chs. from the cor. of secs. 32 and 33, T. 27 N., R.

```
Survey of North Boundary of T. 26 N. R.
Chains.
           Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of secs. 33 and 34, T. 27 N., R. 4 E.,
                marked on brass cap
                                           T27N R4E
                                             S33 | S34
                                           T26n R4E
                                                1916
                From which
              A pinion, 10 ins. diam., brs. N.614° E., 111 lks. dist.
               marked T27N R4E S34 BT.
               A cedar, 24 ins. diam., brs. N.144° W., 228 lks. dist., marked T27N R4E S33 BT.
13.05
           Leave scattering timber.
22.95
           Foot of descent; thence over gently rolling land.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor.\( \text{qf} \) sec. 3, marked on brass cap.
 40.00
               Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
               dist.
           (40.00 chs. from the cor. of secs. 33 and 34, T. 27 N., R.
46.69
               4 E.)
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor. of sec. 34, marked on brass cap,
                                                                           26 ins. in the
                                          <u></u>
$34
                                          1916
               And raise a mound of stone, 3 ft. base, 3 ft. high. N.
               of cor.
           Road, brs. NW. and SE.
Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 2 and 3, T. 26 N., R. 4 E.;
72.45
80.00
               marked on brass cap
                                          T27N R4E
                                               S34
                                           S 3 S 2
T26N R4E
                                               1916
               And raise a mound of stone, 3 ft. base, 3 ft. high, S.
           Land, rolling and gently rolling.
           Soil, coarse texture, 26 ins. deep.
           Timber, cedar and pinion.
           Undergrowth, sagebrush, 1 to 2 ft. high, and broom weed, 1
               ft. high.
           Fair grass.
          N.89° 57' E., on a true line, along the N. bdy. of secs. 2, T. 26 N., R. 4 E. Over level land, (80.00 chs. from the cor. of secs. 33 and 34, T. 27 N., R.
 6.69
               4 E.)
          Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 34 and 35, T. 27 N., R. 4 E., marked on brass cap
```

6.

•	Survey	ofNorth Boundary of T. 26 N., R. 4 E.
	chains.	T27N R4E S34 S35 S 2
		T26N R4E 1916
		And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
	28.95 34.45 40.00	Road, brs. NE. and SW. Ditch, 12 lks. wide, 1 ft. deep, course NE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor. of sec. 2, marked on brass cap,
	-	₹ S 2 1916
		And raise a mound of stone, $2\frac{1}{5}$ ft. base, 2 ft. high, N. of cor.
	46.69	(40.00 chs. from the cor. of secs. 34 and 35, T. 27 N., R. 4 E.)
	·	Set an iron post, 3 ft. long, 1 in. diam. 26 ins. in the ground, for \(\frac{1}{2} \) sec. cor. of sec. 35, marked on brass cap.
		1 835
		1916
	59 .2 5 80 . 00	And raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, North of cor. Road, brs. NE. and SW. Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 1 and 2, T. 20 N., R. 4 R.,
		marked on brass cap
		T27N R4E S35 S 2 \$ 1
	,	T26N R4E 1916
		And raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S of cor.
	· .	Land, level. Soil, coarse texture, 26 ins. deep. No timber or undergrowth.
		Broom weed, 1 ft. high. Fair grass.
1	6.69	N.89° 57' E., on a true line, along the N. bdy. of sec. 1. T. 26 N., R. 4 E. Over gently rolling land, (80.00 chs. from the cor. of secs. 34 and 35, T. 27 N., R. 4 E.)
		Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of secs. 35 and 36, T. 27 N., R. 4 E. marked on brass cap
	, v	T27N (R4E
		т26N R4E 1916
		And raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N of cor.
	-	

Surv	vey of North Boundary of T. 26 N. R. 4 E. 7.
22.95 37.95 40.00	Enter scattering timber. Leave scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor.of sec.1, marked on brass cap,
	∓s.1 1916
	From which A cedar, 16 ins. diam., brs. S.31½° E., 314 lks. dist., marked ½S1 BT.
4 6.69	A cedar, 14 ins. diam., brs. S.34° W., 215 lks. dist., marked 4S1 BT. (40.00 chs. from the cor. of secs. 35 and 36, T. 27 N., R. # E.)
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., of sec. 36, marked on brass cap,
	±336 1916
,	From which A cedar, 10 ins. diam., brs. N.56° E., 300 lks. dist., marked 4536 BT. A cedar, 8 ins. diam., brs. N.7° E., 183 lks. dist.,
82.97	marked 4836 BT. The cor. of Ts. 26 N., Rs. 4 and 5 E. Land, gently rolling.
	Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Broom wead, 1 ft. high. Fair grass.
	rair grass.

Boundaries of T. 26 N., R. 4 E.

	L	atitud	les, Dep	artures	and Clo	sing En	rors.	
					Latit	udes.	Depar	tures.
Line d	esignated.	True	bearing	Dist.	N.	S.	E .	W.
				chs.	chs.	chs.	chs.	chs.
	Boundary.	We	est.	483.85	,			483.85
	oundary.		rth.	483.16	483.16			
North	Boundary.		'57'E.	482.97	46.		482.97	
East B	oundary.		outh. 8'W.	480.00		480;00		.01
Conver		J. U	<u> </u>	J•±4		7.14	•52	.01
							<u> </u>	
Totals					483.58	483.14	483.49	483.86
•		•			483.14			483.49
Error	in latitud				0.44			1
Error .	in departu	re.		,			₹. . v-	0.37

Survey of Subdivision of T. 26 N., R. 4 E 8. Chains. From the cor. of secs. 5 and 6, on the N. bdy. of the Tp., which is an iron post, hereinbefore described, S.O° 1' W., bet. secs. 5 and 6. Over gently rolling land, through scattering timber and undergrowth. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor, marked on brass cap ₹s 6 s 5 ,1916 From which A pinion, 12 ins. diam., brs. N.1° E., 249 lks. dist., marked \$\frac{1}{4}\$5 BT. 12 ins. diam., brs. N.33° W., 172 lks. dist., A cedar, 12 in marked $\frac{1}{4}$ 86 BT. 56.00 Top of lowering brs. NE. and SW. 60.00 Leave scattering timber. Wide, shallow draw, course SW.
Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 5, 6, 7 68.00 80.00 and 8, marked on brass cap T26N R4E S 6 S 5 S 7 S 8 From which A pinion, 18 ins. diam., brs. $S.31\frac{1}{4}$ ° E., 195 lks. dist. marked T26N R4E S8 BT. A pinion, 12 ins. diam., brs. S.22 $\frac{1}{2}$ ° W., 151 lks. dist marked T26N R4E S7 BT. Raise a mound of stone, 3 No other trees within limits. ft. base, 3 ft. high, W. of cor. Land, gently rolling.
Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, 2 ft. high, and broom weed, 1 ft. high. Fair grass. S.89° 57' W., on a random line, bet. secs. 6 and 7.
Set temp. \(\frac{1}{4} \) sec. cor.
Intersect W. bdy. of Tp., 14 lks. N. of the cor. of secs.
1, 6, 7 and 12, which is an iron post, described in
Book "H". 40.00 80.00 Thence N.89° 51' E., on a true line, bet. secs. 6 and 7. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 40.00 A pinion, 12 ins. diam., brs. $N.10\frac{1}{2}^{\circ}$ E., 64 lks. dist. marked $\frac{1}{4}$ 56 BT. A pinion, 10 ins. diam., brs. S.3½° E., 25 lks. dist., marked $\frac{1}{4}$ S7 BT. Leave scrub timber. 51.00 **54.10** 80.00 Wide, shallow draw, course SW. The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.

Subdivision of T. 26 N. R. 4 E Chains. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, 2 ft. high, and broom weed, 1 ft. high. Fair grass. S.0° 1' W., bet. secs. 7 and 8. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor, marked on brass cap 40.00 $\frac{1}{4}$ S 7 S 8 1916 From which A pinion, 12 ins. diam., brs. $S.18\frac{1}{4}$ ° E., 111 lks. dist., marked $\frac{1}{4}S8$ BT. A pinion, 18 ins. diam., brs. S.8° W., 136 lks. dist., marked $\frac{1}{4}$ S7 BT. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in t ground, for cor. of secs. 7, 8, 17 and 18, marked on 80.00 26 ins. in the brass cap T26N R4E And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, gently rolling.
Soil, coarse texture, 26 ins. deep.
Timber, a few scattering scrub cedar and pinion trees. Undergrowth, sagebrush, 2 ft. high, and broom weed, 1 ft. high. Fair grass. S.89° 51' W., on a random line, bet. secs. 7 and 18. Set temp. $\frac{1}{4}$ sec. cor. 40.00 Intersect W. bdy. of Tp., 2 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, described in 79.83 Book "H". hence N.89° 50' E., on a true line, bet. secs. 7 and 18. Over gently rolling land, through very scattering timber and undergrowth. Rocky draw, course NW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4sec. cor., marked on brass cap 21.35 39.915 And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. 7.65 Road, brs. NW. and SE. 79.83 The cor. of secs. 7, 8, 17 and 18. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, a few scattering scrub cedar and pinion trees. Undergrowth, sagebrush and Brigham brush, 2 ft. high. Good grass.

10.		Subdivision of T. 26 N., R. 4 E.
	Chains.	9 00 71 W hot 2000 17 and 30
	2.50 40.00	S.0° 1' W., bet. secs. 17 and 18. Over gently rolling land, through scattering undergrowth. Road, brs. NW. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor, marked on brass cap
		1916
	80.00	And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on brass cap T26N R4E S18 S17
		S19 S20 1916 And raise a mound of stone, 2 to base, 2 ft. high, W. of cor.
		Eand, gently rolling. Soil, coarse texture, 26 ins. deep. No timber. Undergrowth, sagebrush, 2 to 3 ft. high, and broom weed, ft. high.
		Good grass.
	40.00	S.89° 50' W., on a random line, bet. secs. 18 and 19. Set temp. 4 sec. cor. Intersect W. bdy. of Tp., at the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in Book "H". Thence
	27.25	N.89° 50' E., on a true line, bet. secs. 18 and 19. Over gently rolling land, through scattering timber and undergrowth. Small draw, course Sw.
	37.25 39.87 2	Leave scattering timber. Set an iron post, 5 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for \(\frac{1}{2} \) sec. cor., marked on brass cap \[\frac{1}{2} \) S18 \[\frac{1}{2} \) S19
		S19 1916 From which A cedar, 12 ins. diam., brs. N.61° W., 284 lks. dist.,
	79 • 75	marked \(\frac{1}{4}\)S18 BT. A cedar, 8 ins. diam., brs. S.63\(\frac{1}{2}\)° W., 218 lks. dist., marked \(\frac{1}{4}\)S19 BT. The cor. of secs. 17, 18, 19 and 20. "and, gently rolling. Soil, coarse texture, 22 ins. deep.
		Timber, a few scattering scrub cedar and pinion trees. Undergrowth, sagebrush, 2 to 3 ft. high, and broom weed, 1 ft. high. Fair grass.
	40.00	S.0° l' W., bet. secs. 19 and 20. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{2} \) sec. cor., marked on brass cap

Subdivision of T. 26 N. R. 4 E. 11 Chains. - 1819 | 820 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. 56.15 Road, brs. NE. and SW. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap T26N R4E S19 S20 **830 | 82**9 1916 From which A pinion, 10 ins. diam., brs. N.63° E., 276 lks. dist. marked T26N R4E S20 BT. A pinion, 10 ins. diam., brs. $S.45\frac{1}{2}$ ° E., 461 lks. dist., marked T26N R4E S29 BT. A cedar, 10 ins. diam., brs. S.574° W., 400 lks. dist., marked T26N R4E S30 BT. A pinion, 12 ins. diam., brs. $N.15\frac{1}{4}$ ° W., 331 lks. dist., marked T26N R4E S19 BT. Land, gently rolling.
Soil, coarse texture, 26 ins. deep. Timber, a few scattering scrub cedar and pinion trees. Undergrowth, sagebrush, 2 ft. high, and broom weed, 1 ft. high. Fair grass. S.89° 50' W., on a random line, bet. secs. 19 and 30. 40.00 Set temp. $\frac{1}{4}$ sec. cor. 79.88 Intersect W. bdy. of Tp., 5 lks. S. of the cor. of secs. 25 and 30, which is an iron post, described in 19, 24, Book "H". hence N.89° 52' E., on a true line, bet. secs. 19 and 30. Over rolling land, through scattering timber and undergrowth: Asc. 75 ft. 11.90 brs. NW. and SE., in bottom of wide draw, course NW. Road, Rim of mesa, brs. NW. and SE. Thence over gently rolling 17.60 land. 17.90 From this point, reservoir, brs. S.10° E. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 39.94 1916 And dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. 79.88

The cor. of secs. 19, 20, 29 and 30. Land, rolling and gently rolling. Soil, coarse texture, 26 ins. deep. Timber, a few scrub cedar and pinion trees.

Undergrowth, sagebrush, 2 ft. high. Fair grass.

S.0° 1' W., bet. secs. 29 and 30. Over gently rolling land, through scattering timber and undergrowth.

1	.2.	Subdivision of T. 26 N., R. 4 E.
	Chains. 40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor, marked on brass cap
		1 \$30 \$2 9
		1916
		And dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, marked on brass cap
		T26N R4E S30 S29
		331 832 1916
,	•	From which
		A pinion, 12 ins. diam., brs. $N.73\frac{1}{2}$ ° E., 237 lks. dist. marked T26N R4E S29 BT.
		A pinion, 9 ins. diam., brs. $5.66\frac{1}{2}$ ° E., 240 lks. dist., marked T26N R4E S32 BT.
	-	A pinion, 12 ins. diam., brs. S.892° W., 318 lks. dist. marked T26N R4E S31 BT.
	,	A pinion, 10 ins. diam., brs. N.83° W., 681 lks. dist., marked T26N R4E S30 BT.
		Land, gently rolling. Soil, coarse texture, 26 ins. deep.
		Timber, a few scattering cédar and pinion trees. Undergrowth, sagebrush, 2 ft. high, and broom weed, 1 ft.
		high. Fair grass.
		S.89° 52' W., on a random line, bet. secs. 30 and 31.
	40.00 80.00	Set temp. \(\frac{1}{2}\) sec. cor. Intersect W. bdy. of Tp. 9 lks. N. of the cor. of secs.
		25, 30, 31 and 36, which is an iron post, described in Book "H". Thence
		N.89° 48' E., on a true line, bet. secs. 30 and 31. Over gently rolling land, through scattering timber and undergrowth.
	32.10 40.00	Dim road, brs. N. and S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	1	ground, for 4 sec. cor., marked on brass cap
	•	1 S 3 O S 3 I
		1916
		From which A pinion, 24 ins. diam., brs. N.71° W., 336 lks. dist.,
		marked 4830 BT. A pinion, 10 ins. diam., brs. S.73° W., 178 lks. dist., marked 4831 BT.
	40.35	Junction of two washes, 15 lks. wide, 4 ft. deep, one, from SE. and one from SW., course NW.
	40.90	Road, brs. NW. and SE.
	55.00 80.00	Rim of mesa, brs. NW. and SE. The cor. of secs. 29, 30, 31 and 36. Land, gently rolling.
	a a a a a a a a a a a a a a a a a a a	Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion.
		Undergrowth, sagebrush, 2 ft. high. Good grass.
	200	

	Subdivision of T. 26 N. R. 4 E. 13.
Chains.	S.0° 1' W., on a random line, bet. secs. 31 and 32. Set temp. ½ sec. cor.
40.00 83.39	Set temp. 2 sec. cor. Intersect S. bdy. of Tp., 7 lks. E. of original cor.of secs.
	5, b, 31 and 32, which is a malpais stone, 8 x 12 x b;
	ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.
	N.0° 4' E., on a true line, bet. secs. 31 and 32.
	Over gently rolling land, through scattering timber and
43.39	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	ground, for 4 sec. cor., marked on brass cap
	1916
	1916
	From which
	A pinion, 16 ins. diam., brs. $S.17\frac{1}{2}$ ° E., 310 lks. dist. marked $\frac{1}{4}S32$ BT.
	A pinion, 8 ins. diam., brs. N.84° W., 250 lks. dist.
47.05	marked 4831 BT. Ditch, 9 lks. wide, 2 ft. deep, course NW., inbottom of
47.50	Wide draw, course NW. Road, brs. NW. and SE.
63.40 83.39	Rim of mesa, brs. E. and W.
03.59	The cor. of secs. 29, 30, 31 and 32. Land, gently rolling.
	Soil, coarse texture, 26 ins. deep. Timber, scattering cedar and pinion.
	Undergrowth, sagebrush and Brigham brush, 2 ft. high, and broom weed. 1 ft. high.
	Good grass.
	From the cor. of secs. 4 and 5, on the N. bdy. of the
	Tp., which is an iron post, hereinbefore described, S.O° 1' W., bet. secs. 4 and 5.
40.00	Over rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam. 26 ins. in the
	ground, for ½ sec. cor., marked on brass cap
	글S 5 S 4
	4 s 5 s 4
	From which
	A juniper, 14 ins. diam., brs. $S.17\frac{1}{2}$ ° E., 265 lks. dist.,
,	marked 4S4 BT. A pinion, 16 ins. diam., brs. S.6° W., 268 lks. dist.,
80.00	marked 485 BT. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the
	ground, for cor. of secs. 4, 5, 8 and 9, marked on brass cap
	T26N R4E
	S 5 S 4 S 8 S 9
	1916
	From which A pinion, 8 ins. diam., brs. N.50° E., 63 lks. dist.,
	marked T26N R4E S4 BT.
	A juniper, 36 ins. diam., brs. S.324° E., 110 lks. dist., marked T26N R4E S9 BT.
	A pinion, 8 ins. diam., brs. S.303° W., 240 lks. dist., marked T26N R4E S8 BT.
	A pinion, 12 ins. diam., brs. N.23\frac{1}{2}\circ \textbf{W}. 150 lks. dist.
	marked T26N R4E S5 BT. Land, rolling.

Land, rolling.
Soil, loose, yellow rocky loam, over malpais formation.

14		Subdivision of T. 26 N. R. 4 E.	
	Chains.	Timber, pinion and juniper. Undergrowth, scattering sagebrush, squawbrush and broom weed, 1 ft. high. Fair grass.	
			_
	40.00 80.20	S.89° 57' W., on a random line, bet. secs. 5 and 8. Set temp. \(\frac{1}{4}\) sec. cor. Intersect the corner of sections . 5, 6, 7 and 8.,	
	40.10	Thence N.89° 57' E., on a true line, bet. secs. 5 and 8. Over rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the	
	40.20	ground, for 4 sec. cor., marked on brass cap	
		1916	
	,	And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.	
	41.00	Enter scattering timber, brs. NE. and SW. The cor. of secs. 4, 5, 8 and 9. and, rolling.	
		Soil, loose, yellow, rocky loam, over malpais formation. Timber, pinion and juniper. Undergrowth, broom weed, 1 ft. high. Fair grass.	
			_
	d va	S.0° 1' W., bet. secs. 8 and 9. Over rolling land, through scattering timber and under-	
	40.00	growth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4sec. cor., marked on prass cap	
		1/4 S 8 S 9	
		1916	
		And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.	
	40.50 65.00	Draw, 50 lks. wide, course NW. Mountain brs. E. 25 chs. dist.	
	86.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on brass cap	
•	,	T26N R4E S 8 S 9 S17 S16 1916	
		And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, rolling.	
		Soil, loose, rocky loam, over malpais formation. Timber, scattering pinion and juniper. Undergrowth, sagebrush and squawbrush, and broom weed, l	
		ft. high. Fair grass.	
			L
•		S.89° 57' W., on a random line, bet. secs. 8 and 17.	
		- 19 91, III & I amount I I I 10	

```
BOOK
                                                                                  3103
                 Subdivision of T. 26 N. R. 4 E.
Chains.
 40.00
          Set temp. 1 sec. cor. Intersect N. and S. line, 19 lks. N. of the cor. of secs.
 80.20
              7, 8, 17 and 18.
          Thence
          N.89° 49' E., on a true line, bet. secs. 8 and 17. Over rolling land, through scattering timber and under-
              growth.
  40.10 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
             ground, for 4 sec. cor. marked on brass cap
              From which
             A pinion, 12 ins. diam., brs. N.49½° E., 75 lks. dist., marked 488 BT.
             A juniper, 8 ins. diam., brs. S.59° E., 91 lks. dast.,
             marked 4S17 BT.
80.20
         The cor. of secs. 8, 9, 16 and 17.
         Land. rolling.
Soil, loose, yellow loam, over malpais formation.
Timber, pinion and juniper.
         Undergrowth, sagebrush and squawbrush, and broomweed, 10
             to 12 ins. high.
         Fair grass.
         S.0°1' W., bet. secs. 16 and 17.
         Over rolling land, through scattering timber and under-
         Set an iron post, 3 ft. long, lin. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
40.00
                                     1317 S16
                                         1916
             From which
             A juniper, 10 ins. diam., brs. S.67° E., 125 lks. dist., marked \frac{1}{4}S16 BT.
             A pinion, 12 ins. diam., brs. S.40° W., 200 lks. dist. marked $17 BT.
60.00
         Leave scattering timber, brs. SE. and W.
         Road, brs. NW. and SE. Road, brs. NE. and SW.
61000
74.80
         Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on
00.08
             brass ca p
                                     T26N R4E
                                      s 17 s16
                                      520 521
                                         1916
             From which
         A juniper, 14 ins. diam., brs. N.37° W., 168 lks. dist., marked T26N R4E S17 BT.

No other trees within limits. Raise a mound of stone, 3
             ft. base, 3 ft. high, W. of cor.
         and, rolling.
         Soil, loose, yellow laam, over malpais formation. Timber, pinion and juniper.
         Undergrowth, sagebrush, and broom weed, 1 ft. high.
```

Fair grass.

16.		Subdivision of T. 26 N. R. 4 E.
	Chains.	S.89° 49' W., on a random line, bet. secs. 17 and 20.
	40.00 80.25	Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 2 lks. N. of the cor. of secs. 17, 18, 19 and 20.
		Thence N.89° 48' E., on a true line, bet. secs. 17 and 20. Over rolling land, through scattering undergrowth and timber.
	40.12 1	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec.cor., marked on brass cap
·		1517 520 1916
	74.25 80.25	And raise a mound of stone, 2 ft. base, 12 ft. high, N. of cor. Road, brs. NE. and SW. The cor. of secs. 16, 17, 20 and 21. Land, rolling. Soil, loose, yellow loam, over malpais formation. Timber, a few scattering juniper and pinion trees. Undergrowth, scattering sagebrush. Fair grass.
	_	
	20.00 40.00	S.0° 1' W., bet. secs. 20 and 21. Over gently rolling land, through scattering undergrowth. Enter scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, for 4 sec. cor., marked on brass cap \$\frac{1}{4}\$\$20 \$\frac{1}{8}\$\$21
		1916
	80.00	From which A pinion, 10 ins. diam., brs. S.10% E., 197 lks. dist., marked \(\frac{1}{4}\)S21 BT. A pinion, 10 ins. diam., brs. N.37% W., 74 lks. dist., marked \(\frac{1}{4}\)S20 BT. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, marked on brass cap
:		T26N R4E S20 S21 . S29 S28 1916
		From which A pinion, 8 ins. diam., brs. N.69\frac{1}{2}\circ E., 141 lks. dist., marked T26N R4E S21 BT. A cedar, 10 ins. diam., brs. S.69\circ E., 95 lks. dist., marked T26N R4E S28 BT. A pinion, 12 ins. diam., brs. S.6\frac{1}{2}\circ W., 68 lks. dist., marked T26N R4E S29 BT.
		A pinion, 12 ins. diam., brs. N.85° W., 109 lks. dist, marked T26N R4E S20 BT. Land, rolling and gently rolling. Soil, coarse and rocky texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush and holly brush, 2 to 4 ft. high. Good grass.
	40.00	S.89° 48' W., on a random line, bet. secs. 20 and 29. Set temp. $\frac{1}{4}$ sec. cor.

		FOOK 3103
		Subdivision of T. 26 N. A. 4 E. 17.
	Chains.	4 19
	80.17	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 19, 20, 29 and 30.
		N.89° 47' E., on a true line, bet. secs. 20 and 29. Over gently rolling land, through scattering timber and undergrowth.
	40.08½	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass capp
		1916
		From which A pinion, 12 ins. diam., brs. N.12° W., 284 lks. dist.
		marked $\frac{1}{4}$ S20 BT. A pinion, 10 ins. diam., brs. S.9 $\frac{1}{2}$ ° W., 150 lks. dist.
	80.17	marked \(\frac{1}{2}\)S29 BT. The cor. of secs. 20, 21, 28 and 29.
		Land, gently rolling. Soil, coarse texture, 26 ins. deep. Undergrowth, scattering sagebrush, 2 ft.high.
		Timber, a few scattering cedar and pinion trees. Fair grass.
		rail glads.
		S.0° 1' W., bet. secs. 28 and 29. Over gently rolling land, through scattering timber and
		undergrowth.
	40.00	Set an iron post, 3 ft. long, I in. diam. 26 ins. in the
	•	ground, for ½ sec. cor., marked on brass cap
		1 S 29 S 28
		1916
		From which A pinion, 10 ins. diam., brs. S.15½° E., 145 lks. dist.,
		marked $\frac{1}{4}$ S28 BT. A cedar, 10 ins. diam., brs. S.31 $\frac{1}{2}$ ° W., 76 lks. dist.,
	80.00	marked $\frac{1}{4}$ S29 BT. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
		ground, for cor. of secs. 28, 29, 32 and 33, marked on brass cap
		T26N R4E 82 9 52 8
		\$32 \$33 1916
		From which
		A pinion, 9 ins. diam., brs. N.23½° E., 127 lks. dist., marked T26N R4E S28 BT.
-		pinion, 10 ins. diam., brs. S.1° E., 144 lks. dist., marked T26N R4E S33 BT.
		A pinion, 14 ins. diam., brs. $S.14\frac{1}{4}^{\circ}$ W., 128 lks. dist., marked T26N R4E S32 BT.
		A pinion, 12 ins. diam., brs. N.7830 W., 81 lks. dist., marked T26N R4E S29 BT.
		Land, gently rolling. Soil, coarse and rocky texture.
		Timber, scrub cedar and pinion. Undergrowth, scattering holly and sagebrush, 2 to 8 ft. high.
		Good grass.
		G ROS 471 W on a mandam line hat green 20 and 20
		S.89° 47' W., on a random line, bet. secs. 29 and 32. Set temp. \(\frac{1}{4}\) sec. cor.
		Additional Control of the Control of

.18.	*	Subdivision of T. 26 N., R. 4 E.
	Sheins. 80.26	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 29, 30, 31 and 32. Thence N.89° 45' E., on a true line, bet. secs. 29 and 32.
	40.13	Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap
		1329 532 1916
		From which A pinion, 14 ins. diam., brs. N.17° W., 178 lks. dist., marked \(\frac{1}{4}\)S29 BT. A pinion, 10 ins. diam., brs. S.38° E., 478 lks. dist.
	80.26	marked \(\frac{1}{4}\) \$32 BT. The cor. of secs. 28, 29, 32 and 33. And, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush, 2 ft. high. Good grass.
	40.00 83.58	S.0° 1' W., on a random line, bet. secs. 32 and 33. Set temp. \(\frac{1}{2}\) sec. cor. Intersect S. bdy. of Tp., 38 lks. H.of original corf. of secs. 4, 5, 32 and 33, which is a sandstone, 10 X 14 X 4 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General. Thence
·	1:0.00 27.30	N.0° 17 'E., on a true line, bet. secs. 32 and 33. Over gently rolling land, through scattering timber and undergrowth. Ditch, 10 lks. wide, 3 ft. deep, course NW. Ditch, 8 lks. wide, 1 ft. deep, in bottom of wide draw,
	27.50	course NW. Road, brs. NW. and SE. Rim of mesa, brs. E. and W. Leave scattering timber. Set an iron post, 3 ft. long, l in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor, marked on brass cap
		1916
	78.58 83.58	And raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. Enter scattering timber. The cor. of secs. 28, 29, 32 and 33. Land, gently rolling.
	•	Soil, coarse texture, rocky, 26 ins. deep. Timber, scrub cedar and pinion on S. end. Undergrowth, sagebrush, 2 ft. high. Good grass.
	•	From the cor. of secs. 3 and 4, on the N. bdy. of the Tp.
		which is an iron post, hereinbefore described, S.O° 2' W., bet. secs. 3 and 4. Over mountainous land, through scattering timber and undergrowth. Asc. 260 ft. to
,	9.15 2 9.00	Top of mountain; desc. 230 ft. to Draw, 50 lks. wide, course SE. Thence over gently rolling land.

	BOOK 3103
	Subdivision of T. 26 N., R. 4 E. 19.
Chains. 40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
	1916
80.00	From which A juniper, 8 ins. diam., brs. S.74½° E., 146 lks. dist., marked ¼S3 BT. A pinion, 8 ins. diam., brs. S.40½° W., 129 lks. dist., marked ¼S4 BT. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on brass cap T26N R4E S 4 S 3 S 9 S10 1916
	From which A juniper, 8 ins. diam., brs. 5.823° W., 258 lks. dist., marked T26N R4E S9 BT. A juniper, 14 ins. diam., brs. N.4° W., 84 lks. dist., marked T26N R4E S4 BT. No other trees within limits. Dig pits, 18 X 18 X 12 ins.,
	NE. and SE. of post, 5½ ft. dist. Land, mountainous and rolling. Soil, loose, yellow loam, over malpais formation. Undergrowth, sagebrush and squawbrush. Timber, pinion and juniper.
-	
40.00	S.89° 57' W., on a random line, bet. secs. 4 and 9. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 14 lks. S. of the cor. of secs. 4, 5, 8 and 9. Thence
	S.89° 57' E., on a true line, bet. secs. 4 and 9. Over rolling land, through scattering timber and undergrowth.
15.8 0 19.80 39.90	Draw, 1 ch. wide, course SW. Leave scattering timber, brs. N. and S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
	1916
49.80 59.80 77.00 79.80	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. Enter scattering timber, brs. NW. and SE. Draw, 1 ch. wide, course SW. Dim road, brs. NW. and SE. The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, loose, yellow, gravelly loam, over malpais formation. Timber, pinion and juniper.
	Undergrowth, sagebrush and squambrush, and broom weed, 1 ft. high. Fair grass.
	S.0° 2' W., bet. secs. 9 and 10. Over rolling land, through scattering timber and undergrowth.

20. Subdivision of T. 26 N., R. 4 E. Chains. 3.00 7.00 Leave scattering timber. Thence across valley, course SE Road, brs. NW. and SE. Leave valley, course SE. 30.00 Enter scattering timber, brs. W and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor, marked on brass cap 40.00 글S 9 S10 1916 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on 80.00 brass cap T26N R4E s 9 sio si6 si5 1916 From which A cedar, 10 ins. diam., brs. $N.13\frac{1}{2}$ ° E., 240 lks. dist. marked T26N R4E S10 BT. 10 ins. diam., brs. S.41 $\frac{1}{2}$ ° W., 240 lks; dist. A pinion, marked T26N R4E S16 BT. A cedar, 36 ins. diam., brs. N.12° W., 228 lks. dist. marked T26N R4E S9 BT. No other trees within limits. Dig a pit, 18 X 18 X 12 ins., SE. of post, 5 ft. dist. Land, rolling. Soil, rocky; 3rd rate; malpais formation. Timber, pinion and cedar. Undergrowth, sagebrush, rabbit brush and broom weed. Fair grass. N.89° 57' W., on a random line, bet. secs. 9 and 16. 40.00 Set temp. \(\frac{1}{4}\) sec. cor. Intersect. N. and S. line, 5 lks. S. of the cor. of secs. 79.84 8, 9, 16 and 17. Thence S.89° 55' E., on a true line, bet. secs. 9 and 16. Over gently rolling land, through scattering timber and undergrowth. Asc. 120 ft. to 29.85 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 39.92 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
Desc. 170 ft. to
Foot of descent; thence over rolling land. 64.85 The cor. of secs. 9, 10, 15 and 16. Land, rolling and mountainous. 79.84 Soil, rocky; 3rd and 4th rates. Timber, pinion and cedar. Undergrowth, rabbit brush, segebrush and broom weed. Fair grass. S.0° 2' W., bet. secs. 15 and 16. Over rolling land, through scattering timber and undergrowth.

```
Subdivision of T. 26 N., R. 4 E.
                                                                                        21.
Chains
           Leave timber, brs. SW. and SE. Thence over level land. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
 10.00
 40.00
                                          1516 S15
                                               1916
                And dig pits, 18 X 18 X 12 ins., N. and S. of post, 3
                ft. dist.
 72.00
           Leave flat, and enter timber, brs. NE. and SW.
 80.00
           Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on
                brass cap
                                          T26N R4E
                                            s16 s15
                                            321 322
                                               1916
               From which
               A cedar, 8 ins. diam., b marked T26N R4B S15 bT.
                                                 brs. N.4\frac{1}{2}° E., 148 lks. dist.
               A cedar, 10 ins. diam., brs. S.46\frac{1}{2}° E., 95 lks. dist., marked T26N R4E S22 BT.
               A pinion, 10 ins. diam. marked T26 R4E S21 BT.
                             10 ins. diam., brs. S.32° W., 133 lks. dist.,
           A cedar, 10 ins. diam., brs. N.88% W., 146 lks. dist., marked T26N R4 E S16 BT.
Land, rolling and level.
           Soil, 2nd rate; malpais formation.
           Timber, cedar and pinion.
           Undergrowth, rabbit brush, sagebrush and broom weed.
           Gramma grass.
           N.89° 55' W., on a random line, bet. secs. 16 and 21. Set temp. \frac{1}{4} sec. cor.
 40.00
           Intersect N. and S. line, ll lks. S. of the cor. of secs.
 79.96
           16, 17, 20 and 21. Thence 3.899 50' E., on a true line, bet. secs. 16 and 21.
           Over level land, through scattering undergrowth. Enter scattering timber, brs. NE. and SW. Thence over
 32.95
               rolling land.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
 39.98
                                          <sup>1</sup>/<sub>4</sub>S16
S21
               From which
               A cedar, 7 ins. diam., brs. N.81° W., 217 lks. dist., marked \frac{1}{4}S16~\mathrm{BT}.
               A pinion, 8 ins. diam., brs. S.26° E., 207 lks. dist..
          marked \frac{1}{4}Š21 BT.
Road, brs. NW. and SE.
63.45
79.96
          The cor. of secs. 15, 16, 21 and 22. Land, rolling and level.
Soil, 2nd rate; malpais formation.
           fimber, pinion and cedar.
          Undergrowth, rabbit brush, sagebrush and broom weed.
          Good gramma grass.
```

S.0° 2' W., bet. secs. 21 and 22. Over rolling land, through scattering timber and undergrowth. Road, brs. NW. and SE. Asc. 55 ft. to 12.20

22.		Subdivision of T. 26 N., R. 4 E.
	Chains. 40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for \$\frac{1}{4}\$ sec. cor., marked on brass cap \$\frac{1}{2}\$S21 S22
		1916
		From which A pinion, 20 ins. diam., brs. N.86° E., 246 lks. dist. marked \(\frac{1}{4}\)S22 BT. A pinion, 10 ins. diam., brs. S.81\(\frac{1}{4}\)° W., 49 lks. dist. marked \(\frac{1}{4}\)S21 \(\frac{1}{4}\)T.
	47.00 72.00 80.00	Desc. to Draw, 1 ch. wide, course NE. Asc. 115 ft. to Spur, slopes W. Desc. 30 ft. to Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on brass cap
		T26N R4E S21 S22 S28 S27 1916
		From which A cedar, 8 ins. diam., brs. N.42° E., 185 lks. dist., marked T26N R4E S22 BT. A cedar, 8 ins. diam., brs. S.8½° W., 47 lks. dist., marked T26N R4E S28 BT. No other trees within limits. Dig pits, 18 X 18 X 12 ins. SE. and NW. of post, 5½ ft. dist. Land, rolling and broken. Soil, 2md and 3 rd rate, over malpais formation. Timber, pinion and cedar.
	-	Undergrowth, sagebrush, rabbit brush and broom weed. Fair gramma grass.
	40.00 80.20	N.89° 50' W., on a random line, bet. secs. 21 and 28. Set temp. ½ sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs. 20, 21, 28 and 29.
		S.89° 48' E., on a true line, bet. secs. 21 and 28. Over rolling land, through scattering timber and under-
	40.10	growth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground. for \(\frac{1}{4}\) sec. cor., marked on brass cap
		½S ₂₁ \$28 1916
		From which A pinion, 10 ins. diam., brs. N.20° E., 52 lks. dist., marked \(\frac{1}{4}\)S21 BT. A cedar, 20 ins. diam., brs. S.21\(\frac{1}{5}\)° W., 115 lks. dist. marked \(\frac{1}{4}\)S28 BT.
	63.20 75.20 80.20	Draw, 1 ch. wide, course SE. Asc. 70 ft. to Thence over gently rolling land.
	Source at a few control	Timber, pinion and cedar. Undergrowth, rabbit brush, sagebrush and broom weed. Fair gramma grass.

```
Subdivision of T
Chains.
          S.0° 2' W., bet. secs. 27 and 28.
          Over rolling land, through scattering timber and under-
          Draw, 2 chs. wide, course SW. Asc. 45 ft. to
Thence over gently rolling land.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
  7.00
 15.00
 40.00
                                      1528 S27
                                           1916
              From which
             A cedar, 12 ins. diam., brs. N.81° E., 72 lks. dist., marked \frac{1}{4}S27 BT.
              A pinion, 14 ins. diam., brs. N.\frac{1}{2}° W., 112 lks. dist.
              marked $328 BT.
          Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on
80.00
              brass can
                                      T26N R4E
                                       S28 S27
             From which
             A pinion, 12 ins. diam., brs. N.20° E., 50 lks. dist., marked T26N R4E S27 BT.
             A pinion, 10 ins. diam., brs. S.53° E., 118 lks. dist., marked T26N R4E S34 BT.
             A pinion, 12 ins. diam., brs. S.5\frac{1}{4}° W., 35 lks. dist., marked T26N R4E S33 BT.
             A pinion, 12 ins. diam., brs. N.71° W., 46 lks. dist., marked T26N R4E S28 BT.
         Land, rolling and gently rolling.
          Soil, 2nd rate; malpais formation.
          Timber, cedar and pinion.
          Undergrowth, sagebrush, broom weed and rabbit brush.
         Fair grass.
         N.89° 48' W., on a random line, bet. secs. 28 and 33.
         Set temp. 4 sec. cor.
40.00
79.86
         Intersect N. and S. line, 5 lks. N. of the cor. of secs.
             28, 29, 32 and 33.
         Thence
         S.89° 50' E., on a true line, bet. secs. 28 and 33.
         Over rolling land, through scattering timber and under-
             growth.
         Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, for \frac{1}{4} sec. cor., marked on
39.93
             brass cap
             From which
```

79.86

A pinion, 12 ins. diam., brs. N. $77\frac{3}{4}$ ° W., 102 lks. dist., marked $\frac{1}{4}$ S28 BT. A pinion, 14 ins. diam., brs. South 41 lks. dist.,

marked $\frac{1}{4}$ \$33 BT. The cor. of secs. 27, 28, 33 and 34.

Land, rolling. Soil, 2nd rate, over malpais formation. Timber, cedar and pinion. Undergrowth, sagebrush, rabbit brush and broom weed. Good grass.

Subdivision of T. 26 N., R. 4 E. 24. S.0° 2' W., on a random line, bet. secs. 33 and 34.

Set temp. ½ sec. cor.

Intersect S. bdy. of Tp., 9 lks. E. of original cor.of secs.

3, 4, 33 and 34, which is a malpais stone, 8 % 7 % 3 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.

Thence chains. 40;00 83.21 N.0° 6' E., bet. secs. 33 and 34. Over gently rolling land, through scattering undergrowth. Road, brs. E. and W. Road, brs. NE. and SW. Enter scattering timber. 0.30 0.75 36.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the 43.21 ground, in a mound of stone, for \(\frac{1}{4} \) sec. cor., marked on brass cap ₹**S**33 S34 1916 From which A cedar, 10 ins. diam., brs. S.79 $\frac{1}{4}$ ° E., 53 lks. dist., marked $\frac{1}{4}$ S34 BT. A pinion, 10 ins. diam., brs. S.32° W., 108 lks. dist. marked \$833 BT.
The cor. of secs. 27, 28, 33 and 34. 83.21 Land, gently rolling. Soil, coarse texture, rocky, 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush, 2 ft. high. Good grass. From the cor. of secs. 2 and 3, on the N. bdy. of the Tp. which is an iron post, hereinbefore described. S.0° 3' W., bet. secs. 2 and 3. Over gently rolling land, through scattering undergrowth. Road, brs. NW. and SE. Enter scattering timber. 20.00 32.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor, marked on orass cap 40.00 글S 3 S 2 1916 From which A pinion, 18 ins. diam., brs. N.58° E., 61 lks. dist., marked \$32 BT. A pinion, 10 ins. diam., brs. N.82° W., 59 lks. dist., marked \$33 BT.

Leave scattering timber. 56.50 68.60 Road, brs. NE. and SW. Dry ditch, 3 lks. wide, 8 ins. deep, course NE. Set an iron post, 3 ft. long, 2 ins. dism., 26 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, marked on 70.78 80.00 brass cap T26N R4E S 3 S 2 S10 S11 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, rolling and gently rolling. Soil, coarse and rocky texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush and Brigham brush, 2 ft. high, and

BOOK 3103 Subdivision of T. 26 N., R. 4 E. Chains. broom weed, 1 ft. high. Good grass. S.89° 57' W., on a random line, bet. secs. 3 and 10. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 33 lks. N. of the cor. of secs. 40.00 80.04 3, 4, 9 and 10. Thence N.89° 43' E., on a true line, bet. secs. 3 and 10. Over gently rolling land, through scattering timber and undergrowth. 40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap From which A pinion, 10 ins. diam., brs. N.27° E., 129 lks. dist., marked \$33 BT. 10 ins. diam., brs. $5.26\frac{1}{2}$ ° E., 41 lks. dist. A pinion, marked 3510 BT. 58.05 Leave scattering timber. Road, brs. NE. and SW. The cor. of secs. 2, 3, 10 and 11. Land, gently rolling. Soil, coarse and rocky texture, 26 ins. deep. Timber, scattering scrub cedar and pinion. Undergrowth, sagebrush and Brigham brush, and broom weed, 1 ft. high. Good grass. S.0° 3' W., bet. secs.10 and 11.

Over level land, through scattering undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor, marked on brass cap 40.00 2510 S11 1916 From which A cedar, 10 ins. diam., brs. N.73½° E., 291 lks. dist., marked $\frac{1}{4}$ S11 BT. A cedar, 18 ins. diam., brs. S.74½° W., 185 lks. dist., A cedar, 18 insmarked $\frac{1}{4}$ S10 BT. Enter scattering timber.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on 70.00 80.00 brass cap T26N R4E S10 | S11 S15 | S14 1916 From which A pinion, 10 ins. diam., brs. N.70 $\frac{1}{2}$ ° E., 470 lks. dist.,

marked T26N R4E S11 BT. A cedar, 10 ins. diam., brs. $S.12\frac{1}{4}^{\circ}$ E., 13 lks. dist., marked T26N R4E S14 BT. A pinion, 12 ins. diam., brs. $S.19\frac{1}{2}^{\circ}$ W., 56 lks. dist., marked T26N R4E S15 BT. A pinion, 12 ins. diam., brs. $N.34\frac{1}{4}$ ° W., 176 lks. dist., marked T26N R4E S10 BT.

26	the state of the s	Subdivision of T. 26 N. R. 4 E.
	Chains.	Land, level. Soil, coarse texture, 26 ins. deep. Timber, scattering scrub cedar and pinion.
		Undergrowth, sagebrush and Brigham brush, 2 ft. high, and broom weed, 1 ft. high. Good grass.
	40.00 79.82	S.89° 43' W., on a random line, bet. secs. 10 and 15. Set temp. ½ sec. cor. Intersect N. and S. line, 7 lks. S. of the cor. of secs. 9, 10, 11 and 14.
	39.91	Thence N.89° 46' E., on a true line, bet. secs. 10 and 15. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1916
	40.80 52.15 74.80 79.82	From which A pinion, 16 ins. diam., brs. N.1½° E., 233 lks. dist. marked ½\$10 BT. A pinion, 20 ins. diam., brs. \$5.60½° W., 261 lks. dist. marked ½\$15 BT. Leave scattering timber. Road, brs. NE. and SW. Enter scattering timber. The cor. of secs. 10, 11, 14 and 15. Land, gently rolling. Soil, coarse texture, 26 ins. deep. ———————————————————————————————————
	40.00	S.0° 3' W., bet. secs. 14 and 15. Over gently rolling land, through scattering timber and undergrowth.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1916
-		From which A cedar, 12 ins. diam., brs. N.82% E., 183 lks. dist., marked %S14 BT. A cedar, 8 ins. diam., brs. N.68° W., 435 lks. dist.,
	69.35 80.00	marked \(\frac{1}{4}\)S15 BT. Road, brs. NW. and SE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap
		T26N R4E S15 S14 S22 S23 1916
		From which A cedar, 30 ins. diam., brs. N.57° E., 260 lks. dist., marked T26N R4E S14 BT.

```
Subdivision of T. 26 N. H. 4 E.
                                                                                       27.
Chains.
                            12 ins. diam., brs. 5.66\frac{1}{8}° E., 146 lks. dist.
                A cedar
               marked T26N R4E S23 BT.
               A cedar, 10 ins. diam., brs. S.88% W., 32 lks. dist., marked T26N R4E S22 BT.
A cedar, 22 ins. diam., brs. N.27% W., 203 lks. dist., marked T26N R4E S15 BT.
           Land, gently rolling.
           Soil, coarse texture, 26 ins. deep.
           pimber, a few scattering scrub cedar and pinion trees.
           Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high,
               and broom weed, 1 ft. high.
           Good grass.
           S.89° 46' W., on a random line, bet. secs. 15 and 22.
           Set temp. 4 sec. cor. Intersect N. and S. line, 5 lks. N. of the cor. of secs.
40.00
79.81
               15, 16, 21 and 22.
N.89° 44' E., on a true line, bet. secs. 15 and 22.

Over rolling land, through scattering timber and undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
                                         ½S15
               From which
               A pinion, 12 ins. diam., brs. N.76\frac{1}{4}° W., 285 lks. dist.
               marked $\frac{1}{4}$S15 BT.

A cedar, 10 ins. diam., brs. S.81° E., 243 lks. dist.,
               A cedar, 10 ins marked \frac{1}{4}S22 BT.
40.15
           Wide, shallow draw, course N.
79.81
          The cor. of secs. 14, 15, 22 and 23.
          Land, rolling.
Soil, coarse texture, 26 ins. deep.
          Timber, scattering scrub cedar and pinion.
          Undergrowth, scattering sagebrush, holly brush and Brigham-
               brush, and broom weed, 1 ft. high.
          Good grass.
          S.0° 3' W., bet. secs. 22 and 23.
          Over rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
                                         1522 S23
                                              1916
              From which
              A pinion, 10 ins. diam., brs. S.43° E., 21 lks. dist., marked \(\frac{1}{4}\)S23 BT.
              A pinion, 12 ins. diam., brs. N.64\frac{1}{2}° W., 19 lks. dist., marked \frac{1}{4}S22 BT.
          Set am iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on
80.00
              brass cap
                                         T26N RAE
                                           S22 | S23
                                           $27 $26
1916
```

A pinion, 10 ins. diam., brs. $N.29\frac{1}{2}$ ° E., 232 lks. dist.,

From which

28.		Subdivision of T. 26 N., R. 4 E.
	Chains.	marked T26N R4E S23 BT. A pinion, 20 ins. diam., brs. S.63½° E., 63 lks. dist., marked T26N R4E S26 BT. A cedar, 10 ins. diam., brs. S.48½° W.,21 lks. dist., marked T26N R4E S27 BT. A pinion, 14 ins. diam., brs. N.5° W., 260 lks. dist., marked T26N R4E S22 BT. Land, rolling. Soil, coarse and rocky, 26 ins. deep. Timber, scrub cedar and pinion.t Undergrowth, sagebrush, 2 ft. high, and broom weed, 1 ft. high. Good grass.
	40.00 79.81 2.10 6.15 12.30 24.80 29.80 39.90	S.89° 44' W., on a random line, bet. secs. 22 and 27. Set temp. ½ sec. cor. Intersect N. and S., 5 lks. N. of the cor. of secs. 21, 22, 27 and 28. Thence N.89° 42' E., on a true line, bet. secs. 22 and 27. Over mountainous land, through scattering undergrowth. Asc. to Small spur, slopes SW. 5 chs. Desc. 50 ft. to Draw, course SW. Asc. 60 ft. to Ridge, brs. N. 10 chs. and S. 7 chs. Desc. 180 ft. to Foot of descent; thence over gently rolling land. Enter scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
		1522 527 1916
	68.30 79.81	From which A cedar, 18 ins. diam., brs. N.84° W., 216 lks. dist., marked 4522 BT. A pinion, 12 ins. diam., brs. S.314° W., 292 lks. dist., marked 4527 BT. Road, brs. 4W. and SE. The cor. of secs. 22, 23, 26 and 27. Land, rolling and mountainous. Soil, coarse and rocky, 26 ins. deep. Timber, scattering scrub cedar and pinion. Undergrowth, scattering sagebrush and bruck brush, 2 ft. high, and broom weed, 1 ft. high. Good grass.
	25.00 25.14 26.10 38.25 40.00	S.0° 3' W., bet. secs. 26 and 27. Over gently rolling land, through scattering timber and undergrowth. Leave timber. Road, brs. NW. and SE. Ditch, 10 lks. wide, 10 ins. deep, course SE. Wire fence, brs. NE. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 4827 826 1916 From which
		A cedar, 20 ins. diam., brs. S.24° E., 273 lks. dist., marked 4S26 BT.

```
Subdivision of T. 26 N., R. 4 E.
Chains.
              A pinion, 10 ins. diam., brs. S.62 w., 188 lks. dist.,
              marked 4827 BT.
          Enter scattering timber. Wire fence, brs. E. and W.
 42.00
 79.35
80.00
          Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on
              brass cap
                                     T26N R4E
S27 S26
S34 S35
1916
              From which
                          14 ins. diam., brs. N.78\frac{1}{2}° E., 110 lks. dist.,
              A pinion,
              marked T26N R4E S26 BT.
              A pinion, 12 ins. diam., brs. S.804° E., 230 lks. dist.,
             marked T26N R4E S35 BT.
A pinion, 12 ins. diam., brs. S.39° W., 180 lks. dist., marked T26N R4E S34 BT.
              A pinion, 10 ins. diam., brs. N.13° W., 260 lks. dist.,
             marked T26N R4E S27 BT.
         Land, gently rolling.
Soil, coarse texture, 20 ins. deep.
         Timber, scrub cedar and pinion.
          Undergrowth, scattering sagebrush and Brigham brush, 2 ft.
             high, and broom weed, 1 ft. high.
         Good grass.
         S.89° 42' W., on a random line, bet. secs. 27 and 34. Set temp. 2 sec. cor. Intersect N. and S. line, 11 lks. S. of the cor. of secs.
40.00
79.82
             27, 28, 33 and 34.
         Thence
         N.89° 47' E., on a true line, bet. secs. 27 and 34.
         Over gently rolling land, through scattering timber and
             undergrowth.
39.91
         Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
             ground, for ½ sec. cor., marked on brass cap
             From which
             A pinion, 12 ins. diam., brs. N.86° W., 430 lks. dist., marked \frac{1}{4}S27 3T.
             A pinion, 14 ins. diam., brs. 8.76\frac{1}{4}° W., 318 lks. dist.,
             marked 4534 BT.
         From this cor., dry lake bed brs. S. 10 chs. dist.
         Wide draw, course SW. The cor. of secs. 26, 27, 34 and 35.
49.70 79.82
         Land, gently rolling.
         Soil, coarse and rocky texture, 26 ins. deep.
         Timber, scrub cedar and pinion.
         Undergrowth, sagebrush, 2 ft. high.
         Good grass.
         S.0° 3' W., on a random line, bet. secs. 34 and 35. Set temp. 2 sec. cor.
40.00
         Intersect S. bdy. of Tp., 9 lks.E. of original cor. of secs. 2, 3, 34 and 35, which is a malpais stone, 8 x 8 x 5 ins. above ground, firmly set, marked and witnessed as
83.31
            described by the Surveyor-General.
        Thence
        N.O° 7' E., on a true line, bet. secs. 34 and 35.
```

Subdivision of T. 26 N., R. 4 E. 30 chains. Over gently rolling land, through scattering undergrowth. 18.30 28.30 43.31 Dim road, brs. NE. and SW. Enter scattering timber, brs. NE. and SN.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \$\frac{1}{4}\$ sec. core, marked on brass cap 1834 835 1916 From which 6 diam., brs. N.34° E., 119 lks. dist., A pinion, marked 4835 BT. A cedar, 6 diam., brs. N.7° W., 106 lks. dist., A cedar, 6 d marked 4534 BT. Leave scattering timber, brs. NE. and W. **49.31** 64.00 Road, brs. NE. and SW. The cor. of secs. 26, 27, 34 and 35. 83;31 Land, gently rolling.
Soil, loose, yellow, rocky loam, over malpais formation.
Timber, pinion and juniper. Undergrowth, scattering broom weed. Fair grass. From the cor. of secs. 1 and 2, on the N. bdy. of the Tp., which is an iron post, hereinbefore described,

S.O° 3' W., bet. secs. 1 and 2.

Over gently rolling land, through scattering undergrowth.

Enter scattering timber, brs. NE. and SW.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 25.00 40.00 4S 2 S 1 1916 From which A cedar, 8 ins. diam., brs. N.842° E., lll lks. dist., marked 4Sl BT. A cedar, 8 ins. diam., brs. N.60½° W., 415 lks. dist., marked $\frac{1}{4}$ S2 BT. Enter heavy timber, brs. NE. and SW. 65.00 Leave heavy, enter scattering timber, brs. NE. and SW. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, marked on 75.00 80.00 brass cap T26N R4E S 2 S 1 S11 S12 1916 From which A ceder, 10 ins. diam., brs. N.554° E., 282 lks. dist. marked T26N R4E S1 BT.
A cedar, 6 ins. diam., brs. S.22½° E., 210 lks. dist..
marked T26N R4E S12 BT. A cedar, 10 ins. diam., brs. S.69½° W., 150 lks. dist. marked T26N R4E S11 BT. A cedar, 10 ins. diam., brs. N.65½° W., 76 lks. dist., marked T36N R4E S2 BT. Land, gently rolling. Soil, rocky, 2nd and 3rd rate. Timber pinion and cedar.

Undergrowth, sagebrush, rabbit brush, and broom weed.

BOOK 3103

Subdivision of T. 26 N. R. 4 E. Chains. S.89° 57' W., on a random line, bet. secs. 2 and 11. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 23 lks. S. of the cor. of secs. 2, 40.00 80.14 3, 10 and 11. Thence S.89° 53' E., on a true line, bet. secs. 2 and 11. Over gently rolling land, through scattering timber and undergrowth. 2055 Road, brs. NW. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for a sec. cor., marked on brass cap 40.07 $\frac{1}{4}$ S 2 1916 From which A cedar, 6 ins. diam., brs. N.263° E., 320 lks. dist., marked $\frac{1}{4}$ S2 BT. A cedar, 10 ins. diam., brs. S.403° E., 166 lks. dist., marked 2511 BT.
The cor. of secs. 1, 2, 11 and 12. 80.14 Land, gently rolling. Soil, rocky, 2nd rate. Timber, pinion and cedar. Undergrowth, rabbit brush, sagebrush and broom weed. Good grass. N.89° 57' E., on a random line, bet. secs. 1 and 12. Intersect E. bdy. of Tp., 2 lks. S. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, described in Book "B." 40.00 Set temp. 1 sec. cor. 83.00 Thence S.89° 56' W., on a true line, bet. secs. 1 and 12. Over gently rolling land, through scattering undergrowth. Enter scattering timber, brs. NE. and SW. Leave scattering timber, brs. NE. and SW. Set an iron post, 5 ft. long, 1 in. diam., 26 ins. in the 13.00 23.00 43.00 ground, for 4sec. cor., marked on brass cap 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
Enter heavy timber, brs. NE. and SW.
Leave heavy, enter scattering timber, brs. NE. and SW.
The cor. of secs. 1, 2, 11 and 12. 49.00 73.00 83.00 Land, gently rolling.
Soil, rocky, 2nd rate; limestone formation.
Limber, cedar and pinion. Undergrowth, rabbit brush, sagebrush and broom weed. Fair grass. $S \cdot 0^{\circ} 3' \text{ W., bet. secs. } 11 \text{ and } 12.$ Over rolling land, through scattering timber and undergrowth. Leave rolling land. Asc. 40 5 ft. to
Top of butte. Desc. 355 ft.
Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the 15.00 38.00 40.00 ground, in a mound of stone, for 4 sec. cor., marked on brass cap 1511 S12 1916

```
Subdivision of T. 26 N. R. 4 E.
Chains.
                And raise a mound of stone, 2 ft. base, 12 ft. high, W
                of cor.
           Foot of descent; draw, 3 chs. wide, course SE. Road in draw, brs. NW. and SE. Thence over gently rolling land. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on
 68.60
 80.00
                brass cap
                                           T26N R4E
                                            S11 S12
                                             S14 | S13
                                               1916
                From which
                A pinion, 20 ins. diam., brs. N.8° E., 120 lks. dist., marked T26N R4E S12 BT.
                A cedar, 14 ins. diam., brs. S.33\frac{1}{2}° E., 128 lks. dist. marked T26N R4E S13 BT. A cedar, 8 ins. diam., brs. S.43° W., 68 lks. dist.,
                marked T26N R4E S14 BT.
                A cedar, 8 ins. diam., brs. N.413° W., 100 lks. dist., marked T26N R4E S11 BT.
           Land, gently rolling and mountainous. Soil, rocky, 2nd and 3rd rate.
            Timber, pinion and cedar.
            Undergrowth, rabbit brush, sagebrush and broom weed.
            Good grass.
            N.89° 53' W., on a random line, bet. secs.11 and 14.
           Set temp. 1 sec. cor. Intersect N. and S. line, 37 lks. N. of the cor. of secs.
 40.00
 80.42
               10, 11, 14 and 15.
            Thence
            N.89° 51' E., on a true line, bet. secs. 11 and 14.
            Over gently rolling land, through scattering timber and
                undergrowth.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
 40.21
                                            1916
                From which
                A cedar, 6 ins. diam., brs. N.31\frac{1}{4}° W., 94 lks. dist., marked \frac{1}{4}S11 BT.
                A cedar, 8 ins. diam., brs. S.42\frac{1}{2}° E., 38 lks. dist., marked \frac{1}{4}S14 BT.
           Draw, 2 chs. wide, course NW.
Draw, 1 ch. wide, course N.
Draw, 1 ch. wide, course N.
The cor. of secs. 11, 12, 13 and 14.
 64.40
 74.40
  76.40
 80.42
            Land, gently rolling.
Soil, rocky, 2nd rate; malpais formation.
            Timber, cedar and pinion.
            Undergrowth, rabbit brush, sagebrush and broom weed.
            Good gramma grass.
            N.89° 56' E., on a random line, bet. secs. 12 and 13. Set temp. \frac{1}{4} sec. cor.
           Intersect E. bdy. of Tp., 5 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, described in Book ""B."
 40.00
 83.10
            5.89^{\circ} 58' W., on a true line, bet. secs. 12 and 13.
            Over mountainous land, through scattering timber.
```

```
EOOK 3103
                       Subdivision of T. 26 N. n. 4 E.
            Asc. 125 ft. to
           Ridge, brs. NW. and SE. Desc. 165 ft., through heavy timber. Foot of descent, thence over gently rolling land. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap
   8.10
 33.10
 43.10
                                            1S12
                                            1916
                From which
                A pinion, 10 ins. diam., brs. N.2\frac{1}{2}° W., 155 lks. dist.,
                marked $12 BT. A pinion, 8 ins. diam., brs. S.424° E., 86 lks. dist., marked $13 T.
58.10
           Leave heavy, enter scattering timber, brs. E. and W.
61.10
           Draw, 1 ch. wide, course NW. Road, brs. NW. and SE.
66.90
           The cor. of secs. 11, 12, 13 and 14. Land, gently rolling and mountainous. Soil, rocky, 2nd and 3rd rate.
83.10
           Timber, pinion and cedar.
           Undergrowth, rabbit brush, sagebrush, broom weed.
           Good grass.
           S.0° 3' W., bet. secs. 13 and 14.
           Over rolling land, through scattering timber and undergrowth.
10.00
           Asc. 105 ft.
           Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
40.00
                                           글S14 S13
                                                1916
               From which
               A pinion, 10 ins. diam., brs. N.27% E., 195 lks. dist.,
               marked \frac{1}{4}S13 BT.
               A pinion, 10 ins. diam., brs. S.134° W., 370 lks. dist.
               marked $\frac{1}{4}$14 3T.
          Spur, slopes NW. Desc. 100 ft. to
Set an ironpost, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 13, 14, 23 and 24, marked on
55.00
86.00
               brass cap
                                           T26N R4E
                                            S14 | S13
S23 | S24
                                                1916
               From which
               A pinion, 18 ins. diam., brs. N.58° E., 331 lks. dist.,
               marked T26N R4E S13 BT.
              A pinion, 18 ins. diam., brs. S.18° E., 374 lks. dist., marked T26N R4E S24 BT.
A cedar, 20 ins. diam., brs. S.623° W., 154 lks. dist., marked T26N R4E S23 BT.
              A pinion, 12 ins. diam., brs. N.69° W., 483 lks. dist., marked T26N R4E S14 BT.
          Land, rolling and mountainous. Soil, rocky, 2nd and 3rd rate.
```

Undergrowth, rabbit brush, sagebrush and broom weed.

Timber, pinion and cedar.

Good gramma grass.

BOOK 3103

Subdivision of T. 26 N. R. 4 E. Chains. S.89° 51' W., on a random line, bet. secs. 14 and 23. Set temp. 4 sec. cor. Intersect N. and S. line, 9 lks. N. of the cor. of secs. 40.00 80.40 14, 15, 22 and 23. Thence N.89° 47' E., on a true line, bet. secs. 14 and 23. Over gently rolling land, through scattering undergrowth. Road, brs. NW. and SE. **6.2**0 20.00 Enter scattering timber. Ditch, 15 lks. wide, 1 ft. deep, course SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 22.60 40.20 From which A pinion, 12 ins. diam., brs. N.21° W., 125 lks. dist. A pinion, 11 ins. diam., brs. S.7° E., 249 lks. dist., marked \$\frac{1}{4}\$S23 BT. The cor. of secs. 13, 14, 23 and 24. 80.40 Land, gently rolling. Soil, coarse and rocky, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, scattering sagebrush, 2 ft. high, and broom weed. 1 ft. high. Good grass. N.89° 58' E., on a random line, bet. secs. 13 and 24. Set temp. ½ sec. cor.

Intersect E. bdy. of Tp., 5 lks. S. of the cor. of secs.

13, 18, 19 and 24, which is an iron post, described in 40.00 83.30 Book "B" Thence S.89° 56' W., on a true line, bet. secs. 13 and 24. Over gently rolling land, through scattering timber and undergrowth. Old road, brs. NW. and SE. 1.60 Road, brs. NW. and SE. 21.65 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 43.30 ground, for 4 sec. cor., marked on brass cap From which A pinion, 8 ins. diam., brs. N.87 $\frac{1}{2}$ ° W., 51 lks. dist., marked 4813 BT.
A cedar, 10 ins. diam., brs. S.14° W., 55 lks. dist., A cedar, 10 ins. marked 4824 BT. 64.70 Rim of mesa, brs. NE. and SW. Shallow draw, course S. 80.30 The cor. of secs. 13, 14, 23 and 24. Land, gently rolling.
Soil, coarse and rocky texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, holly brush and Brigham brush, 2 to 3 ft. high, and broom weed, 1 ft. high. Good grass. S.0° 3' W., bet. secs. 23 and 24. Over gently rolling land, through scattering timber and

undergrowth.

Subdivision of T. 26 N. R. A E. hains. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 40.00 ₹823 S24 From which A cedar, 36 ins. diam., brs. N.54° E., 230 lks. dist., marked 4824 BT.
A pinion, 18 ins. diam., brs. N.894° W., 250 lks. dist., marked 4823 BT. 60.00 Leave timber, brs. E. and W. Enter heavy timber, brs. E. and W.
Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, in a mound of stone, for cor. of secs. 233, 24, 25 and 26, marked on brass cap 71.00 80.00 T26N R4E S23 S24 S26 S25 1916 From which A pinion, 12 ins. diam., brs. N.45 $\frac{1}{2}$ ° E., 60 lks. dist., marked T26N R4E S24 BT. A pinion, 10 ins. diam., brs. S.371° E., 49 lks. dist., marked T26N R4E S25 BT. A cedar, 10 ins. diam., brs. S.74 $\frac{2}{2}$ ° W., 19 lks. dist., marked T26N R4E S26 BT. A cedar, 30 ins. diam., brs. N.5330 W., 54 lks. dist., marked T26N R4E S23 BT. Land, gently rolling. Soil, gravelly, 2nd rate; limestone formation. Timber, pinion and cedar. Undergrowth, rabbit brush, broom weed and sagebrush. Fair grass. S.89° 47' W., on a random line, bet. secs. 23 and 26. Set temp. $\frac{1}{4}$ sec. cor. 40.00 80.16 Intersect hecor. of secs. 22, 23, 26 and 27. hence N.89° 47' E., on a true line, bet. secs. 23 and 26. Over rolling land, through scattering timber and undergrowth. 20.16 Rim, brs. NE. and SW. 24.15 Leave scattering timber. 27.55 28.10 Road, brs. NE. and SW. Ditch, 10 lks. wide, 1 ft. deep, course SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap 40.08 1823 826 1916 And raise a mound of stone, 3 ft. base, 3 ft. high. N. of cor. 65.16 Enter scattering timber.

The cor. of secs. 23, 24, 25 and 26. Land, rolling. Soil, coarse and rocky, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, and Brigham brush, 2 to 3 ft. high. and broom weed, 1 ft. high. Good grass.

ිර.16

٠**٠**('

BOOK 3103

```
36.
                        Subdivision of T. 26 N. R. 4 E.
    chains.
               N.89° 56' E., on a random line, bet. secs. 24 and 25.
               Set temp. \frac{1}{4} sec. cor.
Intersect E. bdy. of Tp., 11 lks. S. of the cor. of secs.
     40.00
     83.41
                   19, 24, 25 and 30, which is an iron post, described in
                   Book "B."
               Thence
               S.89° 51' W., on a true line, bet. secs. 24 and 25.
               Over gently rolling land, through scattering timber and
                   undergrowth.
               Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
     43.41
                   From which
                   A cedar, 10 ins. diam., brs. N.30° W., 269 lks. dist., marked \frac{1}{4}S24 BT.
                   A pimion, 10 ins. diam., brs. S.74° E., 515 lks. dist.
                   marked \frac{1}{4}$25 BT.
               Ditch, 10 lks. wide, 1 ft. deep, course S. The cor. of secs. 23, 24, 25 and 26.
     49.87
83.41
               Land, gently rolling.
Soil, coarse textume 26 ins. deep.
               Timber, scrub cedar and pinion.
               Undergrowth, magebrush and Brigham brush, and broom weed, ft. high.
               Good grass.
               S.0° 3' W., bet. secs. 25 and 26. Over gently rolling land, through heavy timber and scatter-
                   ing undergrowth.
              Leave timber, brs. E. and W. Chimney on House, brs. S.672° W. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
      9.00
      11.51
     40.00
                  ground, for 4 sec. cor, marked on brass cap
                                             ₹S26 S25
                                                 1916
                   Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
                   dist.
              Road, brs. E. and W.
Enter heavy timber, brs. E. and W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on
     56.00
     75.00
80.00
                   brass cap
                                             T26N R4E
                                              $26 | $2°
                                              835 | 836
                   From which
                  A pinion, 12 ins diam., brs. N.69½° E., 265 lks. dismarked T26N 4E S25 BT.
A pinion, 8 ins. diam., brs. S.41° E., 35 lks. dist., marked T26N R4E S36 BT.
                                           diam., brs. N.69\frac{1}{5}° E., 265 lks. dist.,
                   A pinion.
                                 30 ins. diam., brs. S.48\frac{1}{4}° W., 132 lks. dist.,
                   marked T26N R4E S35 BT.
                   A cedar, 8 ins. diam., brs. N.613° W., 180 lks. dist., marked T26N R4E S26 BT.
              Land, gently rolling, Soil, 2nd rate.
               Timber, pinion and cedar.
               Undergrowth, rabbit brush, sagebrush, and broom weed.
```

BOOK 3108

		Subdivision of T. 26 N. R. 4 E. 37.
=	Chains.	Good grass.
	,	
	40.00 80.04	S.89° 47' W., on a random line, bet. secs. 26 and 35. Set temp. 4 sec. cor. Intersect N. and S. line, 26 ks. S. of the cor. of secs. 26, 27; 34 and 35. Thence N.89° 58' E., on a true line, bet. secs. 26 and 35.
	9.00 9.70 40.00 40.02	Over gently rolling land, through scattering timber and undergrowth. Leave timber, brs. N. and S. Road, brs. N. and S. Dry lake bed, 10 chs. wide, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 2 sec. cor., marked on brass cap
		1526 535 1916
	The supporting way	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
	51.55 71.05 80.04	From this point, Chimney on Ranch House brs. N.29° 44' W., Enter heavy timber, brs. E. and W. The cor. of secs. 25, 26, 35 and 36. Land, gently rolling. Soil, 2nd rate, over malpais subsoil. Timber, pinion and cedar.
		Undergrowth, rabbit brush, sagebrush, and broom weed. Good grass.
	40.00 83.46	N.89° 51' E., on a random line, bet. secs. 25 and 36. Set temp. \(\frac{1}{4}\) sec. cor. Intersect E. bdy. of Tp., 14 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in Book "B."
	43•46	Thence S.89° 57' W., on a true line, bet. secs. 25 and 36. Over gently rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, l in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		±325 ■ 336 1916
	77•45 83•46	And dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. Enter heavy timber. The cor. of secs. 25, 26, 35 and 36. Land, gently rolling. Soil, 2nd rate; malpais formation. Timber, cedar and pinion. Undergrowth, rabbit brush, sagebrush and broom weed. Gramma grass.
	40.00 83.20	S.0° 3' W., on a random line, bet. secs. 35 and 36. Set temp. 4 sec. cor. Intersect S. bdy. of Tp., 24 lks. Elof original cor. of secs. 1, 2, 35 and 36, which is malpais stone, 8 X 10 X 8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor-General.

BOOK_ \$103

38. Subdivision of T. 26 N., R. 4 E.

Chains. Thence N.0° 13' E., on a true line, bet. secs. 35 and 36.
Over gently rolling land, through heavy timber and scattering undergrowth. 13.20 33.20 43.20 Leave timber, brs. E. and W. Draw, 5 chs. wide, course NW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor, marked on brass cap 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
Enter scattering timber, brs. E. and W.
Leave scattering, enter heavy timber, brs. E. and W.
The cor. of secs. 25, 26, 35 and 36. 62.20 78.20 83.20 Land, gently rolling.
Soil, 2nd rate, malpais formation. Timber, pinion and cedar. Undergrowth, rabbit brush, sagebrush and broom weed. Fair gramma grass.

General Description.

This township consists of gently rolling and rolling land, broken by several buttes. It is covered with a scattering growth of sagebrush, squawbrush and broom weed undergrowth, and cedar, pinion and juniper timber. The soil is a loose, rocky loam, of coarse texture, 10 to 26 ins. in depth.

There is one ranch house in sec. 26. Several earth dams have been constructed in draws, for the impounding

of flood waters.

. i equi.

Diagram showing the respective surveys executed by Thomas B. Matthews, U.S.S., and William L. Nash, U.S.T., under instructions for Group No.55, SOOK 3103

Book "J"
Township 26 North, Range 4 East.

,	8-1-16	8-1-16	8-1-16	8-1-16	8-1-16	8-1-16	
7-8-16	6 ±	1. *.	,	O.	2 2 91-8	5-23-16	
7.10-16,7-8-16	8-11-16 	8 -1-	8-12-16 9 4- 8-14-16		8-16-16 91-91-8	8-16-16 91-52-52 8-16-16	
7-10-16		H 18 8 18 18 18 18 18 18 18 18 18 18 18 1			14 - 1-60 8-17-16	9]- 27 - 22 8-17-16	
91-01-2	19 - 14-16	20 ½ 8-15-16	2! <u>9</u> :5:-8 8-15-16	91-91-8 8-16-16	25 27-16	91-27-9 24	
7-8-16	30 7	31-29 29-9-9	28 28-16-16	9 27 - કે કે	8-17-16 91-11-8	. ")	
7-7-16, 7-8-16	8- 15-16 21 <u>15</u>	8-15-16 32 <u>4</u>	8-15-16 9-1-1-16	8-17-16 <u>9</u> 34 <u>0</u>	8-17-16 99 35 -21-8	8-17-16 91-22-5	

Blue lines indicate surveys by Thomas B. Matthews, U.S.S. on the various dates shown.

on the various dates shown.

and the control of t The control of the control of

Green lines indicate surveys by Deane J. Wolff, U.S.T.

40

CERTIFICATES OF U. S. SURVEYOR AND U. S. TRANSITMAN.

BOCK 3103

We, Thomas B. Matthews and William L. Nash, U.S. Surveyor, and U.S. Transitman, respectively, hereby certify on honor that, in pursuance of special instructions received from the U.S. Surveyor General for Arizona for Group No.55, Atizona, bearing date of the 8th day of March, 1915, we have well, faithfully, and truly, in our own proper persons, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the North boundary, and the Subdivision lines of

TOWNSHIP 26 NORTH, RANGE 4 EAST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes, and by the diagram on the reverse hereof, as having been executed by us, and under our direction; and we do further certify on honor that all the corners of said psurvey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S.Surveyor General for Arizona for Group No.55, and in the specific manner described in our respective field notes, and that the foregoing are the original field notes of such surveys.

Thomas B. Matthews __

William & had U. S. Transitman.

APPROVAL

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona,

SEP 28 1918.

The foregoing field notes of the Survey of the North boundary and the Subdivision lines of

TOWNSHIP 26 NORTH, RANGE 4 EAST.

of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by Thomas B. Matthews, U. S. Surveyor, and William L.Nash, U.S. Transitman, under special instructions, dated March 8, 1915 for Group 55, Arizona, having been critically examined, and the necessary corrections and explanations made, and the said field notes, and the surveys they describe are hereby approved.

U.S. Surveyor General of Arizona.

I certify that the foregoing transcript of the field notes of the above-described surveys in Book "J" of Group 55, has been correctly copied from the original notes on file in this office.

U.S. Surveyor Coneral of Arizons.