BOOK 8104

JAN 5 - 1918

FLD.6-1918

FIELD NOTES

RE-OF THEASURVEY OF PART

		•				
•			of	·		
		O.T.	IDDINIGIAN I	r T T T T T T T T T T T T T T T T T T T	1	
·			IBDIVISION 1			
,	· 		and SURVEY	of	·	
	<u>C</u>	COMPLETION	OF SUBDIVIS	SION LINES	S OF	
					<u>-</u>	
		TOWNSHIP	27 NORTH, I	RANGE / EAS	3.T	
				·		

		·			·	
					·	
	Of the	Sila and S	alt River Be	Ase and	Meridian,	
In the State			alt River Ba	ase and	M e ridian,	
In the State			Arizona.	·	Meridian,	
In the State			· · · · · · · · · · · · · · · · · · ·	·	M e ridian,	
In the State	e of	E	Arizona. XECUTED) BY	Meridian,	
	e of	E Thomas B. L	Arizona. XECUTED	D BY	/ or ,	
	e of	E Thomas B. L	Arizona. XECUTED Matthews, U	D BY	/ or •	
	e of	Enomas B. L	Arizona. XECUTEE Matthews, U and Nash, U. S	D BY . S. Surve	or,	
	e of	Enomas B. L	Arizona. XECUTEE Matthews, U and Nash, U. S	D BY . S. Surve	/ or •	
In the capa	e of	Enomas B. L. William L. S. Surveyor	Arizona. XECUTEE Matthews, U and Nash, U. S , under instr	D BY . S. Surve; . Transitms	or,	,, 191
In the capa	the United	Enomas B. 1 William L. S. Surveyor d States Si	Arizona. XECUTEE Matthews, U and Nash, U. S , under instruction	D BY S. Survey Transitms Fuctions dates ral to gove	or, an, d March 8	included
issued by Group No.	e of	Enomas B. 1 William L. S. Surveyor d States Si	Arizona. EXECUTED Atthews, U and Nash, U. S , under instruction urveyor General approved by t	D BY S. Survey Transitms Fuctions dates ral to gove	or, an, d March 8 rn surveys	included
issued by Group No.	e of	Enomas B. 1 William L. S. Surveyor d States Si which were	Arizona. EXECUTED Atthews, U and Nash, U. S , under instruction urveyor General approved by t	D BY S. Survey Transitms Fuctions dates ral to gove	or, an, d March 8 rn surveys	included
issued by Group No.	e of	Enomas B. 1 William L. S. Surveyor d States Si which were	Arizona. EXECUTED Atthews, U and Nash, U. S , under instruction urveyor General approved by t	D BY S. Survey Transitms Fuctions dates ral to gove	or, an, d March 8 rn surveys	included
issued by Group No. Office, Dec	e of	Thomas B. 1 Nilliam L. S. Surveyor d States Si which were , 19	Arizona. EXECUTED Atthews, U and Nash, U. S , under instruction urveyor General approved by t	. S. Survey . Transitms ructions dates ral to gove	or, d March 8 rn surveys coner of the G	included

 χ_{\prime}

3/04
Book "K"
Group 55 - - - Arizona.

BOOK 3104

INDEX DIAGRAM.

,,,,	.		IN L	ノニ	XI	וכ	AC	яK	AIV	I .	ı	N/II.
	Minne	im	.++++	+444	4447444	1144		(1441)	+++++	+++*	//// <i>/</i> ///////////////////////////////	
										<i> }</i>		
						NA PA						
7-7-		7777	77777	777		7777	777.27.7	77/73	77777	777		<i>777.</i>
	7	29	8	2	9 1	.9	10	14	11	1	12	
	29		29		22		18		14		10	
					,							
	18	2Β	17	2 7		.8 ,	15) <i>A F</i>	14	14	1	13	
_	28		27	- ' -	27N	1/	.4 C	-	13	_	9	
	19	25	20	2	21	17	22	13	20	9		
		T	•	1		1		1	23	٦	24	
_	26		25	+	20	1	16_		12		8	
	30	25	29	20	28	1 6	27	12	26	8	25	
	24		21		19		15		ı i		7	
	81	23	32	19	88	1 5	34	中	35	7	36	
		نــــــــــــــــــــــــــــــــــــــ										
	* • :	F		į.		F		ŧ		ļ		

Lines surveyed under this group.

_____ Lines resurveyed under this group.

Accepted surveys.

"//////////////////// Areas surveyed, as per accepted plats on file.

BOOK 3104 T 27 N R.S. E.

Sec. 2. anisted with mecassing finish limits.

Sec. 2. anisted with mecassing finish limits.

T 27 N R.A. E.

Without as propertinged.

Without as propertinged.

Resurvey of part of Subdivision lines of Township 27 N. R.A

Chains.

Resurveys and surveys hereinafter described, executed on dates shown on diagram on page 31 hereof, by Thomas B. Matthews, U.S. Surveyor, and William L. Nash, U.S. Transit-man, using Buffland Bufflight mountain transit No. 10124 and Young and Sons Light mountain transit No. 8535, respectively, rescribed in Book "A."

Resurvey of South Boundary of sec.6.

From the original cor. of secs.1,6,7 and 12, on the W.bdy. of the Tp., which is a limestone,12x12x12 ins.above

ground, firmly set, marked and witnessed as described by the surveyor general,

N.89°37'E., on a true line, on S. bdy.of sec.6.

Over rolling land, thru.scattering timber and undergrowth,

Joseph Sec. or ., which is a limestone 16x12x6 ins. above ground. loosely set, marked and witnessed as described by the surveyor general. Now refers to sec. 7 only.

Thence,
N.88°16'E., on a true line, on S.bdy.of sec.6 (E.½).
(39.86 chs.from the original cor.of secs.1,6,7 and 12,on the W.bdy.of the Tp.),
Set an iron post, 3 ft.long, 1'in. in diam., 24 ins. in the ground, for reestablished 2 sec.cor.of sec.6,marked

on orass cap,

₹S 6 1916

from which,

A pinon, 12 ins. in diam., brs. S. 23½°E., 96 lks. dist., marked ½ S6 B T.

A pinon, 10 ins. in diam., brs. S. 6¾ 0w., 52 lks. dist., marked ½ S6 BT.

29.50 Shallow draw, course SW.
40.52 Intersect the original cor.of secs. 5,6,7 and 8, which is a limestone,8x10x10 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Change this cor. to refer to secs. 5 and 6 only, by changing the markings on the bearing tree in what was originally sec. 8 to read as follows: T27N R4E S7 BT.

Land, rolling. Soil, coarse texture, 26 ins. deep.

Timber, scrub cedar and pinon. Undergrowth, hollybrush and sage brush, 1 to 4 ft.high. Fair grass.

Resurvey of South boundary of sec.5.

From the reestablished cor.of secs. 5 and 6,
N.89°56'E., on a true line on S. bdy.of sec.5.
Over rolling land, thru.scattering timber and undergrowth.
(79.88 chs.--79.86 chs.easting--from the original cor.of
secs.1,6,7 and 12, on the W. bdy.of the Tp.),
Set an iron post, 3 ft.long. 2 ins. in diam., 24 ins. in
the ground, for reestablished cor.of secs.7 and 8, marked on brass cap,

from which,

A pinon, 14 ins. in diam., brs.S.9°E., 27 lks. dist., marked T27N R4E S8BT.

BOOK 3104

Resurvey of part of the Subdivision lines of T.27 N.R. Z.E. Chains. A pinon, 16 ins. in diam., brs.S.35°W.,23 lks. dist., marked T27N R4E S7BT. 35.00 Ascend 35 ft.to 40.39 Intersect the original $\frac{1}{4}$ sec.cor., which is a malpais stone, 12x12x10 ins.above ground, loosely set, marked and witnessed, as described by the surveyor general. Now refers to sec.5 only/ Thence, s.89°51'E. on a true line, on S.bdy. of sec. 5 (E. $\frac{1}{2}$). Ascend 30 ft.to 2.07 (40.00 chs.from the reestablished cor.of secs.6 and 7), Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground, in a mound of stone, for reestablished ½ sec.cor.of sec.8, marked on brass cap, **₹8** 8 1916 from which. A pinon, 12 ins. in diam., brs. S. 84°E., 49 lks. dist., marked ½ S 8BT.

A pinon, 14 ins. in diam., brs. S. 884°W., 113 lks. dist., marked 288 BT. Descend 45 ft.to 10.00 Thence over level land. 20.00 Draw, course NW.
26.00 Small reservoir, brs.S. 4 chs.dist.
39.63 Road brs.NW. and SE.
40.32 Intersect the original cor.of secs.4, 5, 8 and 9, which is a limestone, 12x10x4 ins. above ground, firmly set, marked and witnessed, as described by the surveyor general. Now refers to secs.4 and 5 only. Land, level, rolling and broken. Soil, thin and rocky. Timber, cedar and pinon. Undergrowth, sage brush and Brigham brush, and broom weed. 1 ft. high. Fair grass. Resurvey of the South bdy.of sec.4. From the cor.of secs. 4 and 5, N.89°27'E., on a true line, on S. bdy.of sac.4. Over rolling, burnt over land, thru. scattering undergrowth. 1.75 (80.00 chs.from the reestablished cor.of secs. 7 and 8), Set an iron post, 3 ft.long, 2 ins. in diam., 20 ins. in a mound of stone, for reestablished cor.of secs. 8 and 9 marked on brass cap, T27N R4E \$ 4 \$ 8(\$ 9 1916 and raise a mound of stone, 3 ft. base, 3 ft. high, S. of Draw, 1 ch. wide, course SW.

32.45 Road brs.N.and S.

40.60 Intersect the original a sec.cor., which is a limestone,

5x12x4 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Now refers to sec.4 only. Thence,
N.89°36'E., on a true line, on S. bdy. of sec.4 (E.1/2).
(40.00 chs.from the reestablished cor. of secs.8 and 9),
Set an iron post, 3 ft.long, 1 in. in diam., 26 ins. in
the ground, for reestablished 1 sec.cor., marked on

brass cap,

Resurvey of part of the Subdivision lines of T.27 N.R. Chains.

₹S 9 1916

and raise a mound of stone, 2 ft.base, 12 ft. high, S. of

32.15 Draw, 10 chs.wide, course SW.

40.21 Intersect the original cor. of secs. 3,4,9 and 10, which is a limestone, 6x13x5 ins.above ground, firmly set, marked and witnessed, as described by the surveyor general. Now refers to secs. 3 and 4 only Land, rolling.

Soil, loose darkloam, over limestone and malpais formations

Undergrowth, sage brush and broom weed, lft. high. Fair grass.

Resurvey of the South bdy. of sec. 3.

From the cor.of secs.3 and 4. N.89°42'E., on a true line, on S bdy. of sec.3. Over rolling, burnt over land, thru scattering undergrowth. (80.00 chs.from the reestablished cor.of secs. 8 and 9), set an iron post, 3 ft.long, 2 ins. in diam., 24 ins. in the ground, for reestablished cor.of secs. 9 and 10, marked on brass cap,

T27N R4E S 3 S 9|S10 1916

and raise a mound of stone, 3 ft. base, 3 ft. high, S.

of cor.

20.95
Draw, 3 chs.wide, course S.

40.11 Intersect the original 4 sec.cor., which is a limestone, 4x10x7 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Now refers to sec.3 only.

Thence,
N.89°52' E., on a true line, on S. bdy. of sec. 3, (E.½).
(40.00 chs. from the reestablished cor. of secs. 9 and 10).
Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for reestablished ½ sec.cor.ofmsec.10 markeds 0.83 omphrass cap,

> -3510 1916

dig pits, 18x18x12 ins., E and W. of post, 3 ft. dist.

40.16 Intersect the original cor. of secs. 2, 3, 10 and 11, which is a sandstonem18x16x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I destroy the bearing trees S. of line, as this cor.refers to secs. 2 and 3 only.

Land, rolling. Soil, loose, dark, rocky loam, over limestone formation. No timber.

Undergrowth, scattering sage brush and broom weed, 1 ft. high.

Fair grass.

Resurvey of the South bdy.of sec. 2.

From the cor.of secs. 2 and 3. N. 89° 42' E., on a true line, on S. bdy. of sec. 2.

Resurvey of part of South bdy of Townshin Chains Over rolling, burnt over land, thru.scattering undergrowth. (80.00 chs.from the reestablished cor.of secs. 9 and 10), Set an iron post, 3 ft.long, 2 ins. in diam., 24 ins. in the ground, for reestablished cor.of secs. 10 and 11, 0.67 marked on brass cap, T27N R4 E \$10[\$11 1916 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, \forall . of cor. 5.67 Draw, 4 chs.wide, course N.
14.65 Draw, 2 chs.wide, course N.
40.14 Intersect the original 4 sec.cor., which is a limestone, 5x14x10 ins., above ground, firmly set, marked and witnessed, as described by the surveyor general. Now refers to sec. 2 only. Thence,
N.39°47' E., on a true line, on S. bdy. of sec.2 (E.½).
(40.00 chs.from the reestablished cor.of secs.10 and 11),
Set an iron post, 3 ft.long, 1 in. in diam., 26 ins. in
the ground, for reestablished ½ sec.cor., of sec.11, marked on orass cap, and dig pits, 18x18x12 ins., E and W. of post, 3 ft. dist. 25.50 Enter scattering timber. 40.14 Intersect the original cor. of secs. 1, 2, 11 and 12, which is a limestone, 6x16x10 ins., above ground, firmly set, marked and witnessed, as described by the surveyorgeneral. I destroy the bearing trees S.of line, as this cor. now refers to secs. 1 and 2 only. Land, rolling. Soilploose, yellow, gravelly loam, over limestone and sandstone formations. Timber, pinon and juniper. Undergrowth, broom weed, 1 ft. high. Fair grass. Resurvey of South bdy.of sec. 1. From the cor.of secs. 1 and 2,
N.89° 49' E., on a true line, on S bdy.of sec. 1/
Over rolling land, thru. scattering timber and undergrowth.
(80.00 chs.from the reestablished cor.of secs. 10 and 11),
Set an iron post 3 ft.long, 2 ins. indiam.,12 ins. in the
ground, in a mound of stone, for reestablished cor.of
secs. 11 and 12 marked on brace car secs.11 and 12, marked on brass cap, T27N R4E s 1 S11 S12 1916 and raise a mound of stone, 3 ft.base, 3 ft.high, S.of cor. 5.00 Draw, 1 chain wide, course NE. 25.00 Draw, 2 chs.wide, course NE. 40.18 Intersect the original sec.cor., which is a limestone, 2x18x13 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Now re-

fers to sec.1 only.

Resurvey of part of the Subdivision lines of T.27 N.R.4 E.

Chains

Thence,
N.39° 56' E., on a true line on s. bdy.of sec.1 (E.½).
(40.00 chs. from the oregitab.cor.of secs. 11 and 12),
Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
the ground, for reestablished sec.cor., of sec.12, marked on brass cap.

2512
1916

dig pits, 18x18x12 ins. E.and W.of post, 3 ft. dist.
11.80 Leave scattering timber, enter heavy timber, brs. NW. and
SE.
Draw, 1 chain wide, course SW.
Intersect the original cor.of secs.1,6,7 and 12 on the E.
bdy.of the Tp., which is a limestone, 14x10x9 ins. above
ground, firmly set, marked and witnessed, as described
by the surveyor general.
Land, rolling.
Soil, loose, yellow loam.
Timber, pinon and juniper.
Undergrowth, broom weed, 1 ft. high.
Fair grass.

```
of Completion of Subdivision of T. 27 N. R. 4 E
Chains.
                                           rvoy as extraced the overrist will Built and their light standard the court No. 10,124, and from the Constitution of the modern of the court of the 
                                   Pauvoy es Larmeed
                                             នល់ក្រុម ប្រជាពលរបស់ ប្រជាពលរបស់ ប្រជាពលរបស់ ប្រជាពលរបស់ ប្រាជាពលរបស់ ប្រជាពលរបស់ ប្រជាពលរបស់ ប្រជាពលរបស់ ប្រជ
ទៅក្រុម ប្រជាពលរបស់ ប្រ
                                 I common from the cor. of secs. 35 and 36, on the S. bdy.
                                            of the Tp., which is an iron post, described in Book
                                             "ປຸ" .
                                Thence
                              N.0° 1' W., bet. secs. 35 and 36.

Over gently rolling land, through scattering undergrowth.

Dry ditch, 10 lks. wide, 18 ins. deep, course NW.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
     37.00
     40.00
                                                                                                                  ₽835| 836
                                                                                                                              1916
                                           And raise a mound of stone, 2 ft. base, 2 ft. high. W.
                                           of cor.
    76.80
80.00
                               Road, brs. NE. and SW.
                               Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on
                                           brass cap
                                                                                                               T27N R4E

$26 | $25

$35 | $36

1916
                                          And raise a mound of stone, 3 ft. base, 3 ft. high, W.
                                          of cor.
                              Land, gently rolling. Soil, coarse texture, 20 ins. deep.
                               No timber.
                               Undergrowth, broom weed, 1 ft. high.
                               Fair grass.
                              N.89° 57' E., on a random line, bet. secs. 25 and 36. Set temp. ½ sec. cor. Intersect E. bdy. of Tp., 11 lks. S. of the cor. of s
    40.00
   80.03
                                                                                                                                11 lks. S. of the cor. of secs.
                                          25, 30, 31 and 36, which is an iron post, described in Book "D".
                               Thence
                             S.89° 52' W., on a true line, bet. secs. 25 and 36. Over gently rolling land, through scattering timber and
                                          undergrowth.
  40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
                                         From which
                                         A cedar, 14 ins. diam., brs. N.30\frac{1}{2}° W., 96 lks. dist., marked \frac{1}{4}S25 BT. A cedar, 20 ins. diam., brs. S.19\frac{1}{4}° E., 69 lks. dist.,
                                         A cedar, 20 ins marked 4836 BT.
  77.00 Road, brs. NE. and Sw. 80.03 The cor. of secs. 25, 26, 35 and 36.
                             Land, gently rolling.
Soil, coarse texture, 26 ins. deep.
                              Timber, a few scrub cedar and pinion trees.
                             Undergrowth, scattering sagebrush, 1 to 3 ft. high, and
                                         broom weed, 1 ft. high.
```

Chains.	
	Fair grass.
_	
	N.0° 1' W., bet. secs. 25 and 26.
	Over level land, through scattering undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground. for \(\frac{1}{4}\) sec. cor. marked on brass cap
	<u></u> 4\$26 \$2 5
	1916
<i>į</i> .	Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
80.00	dist. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in th
00.00	ground, for cor. of secs. 23, 24, 25 and 26, marked on
	brass cap T27N R4E
	S23 S24
- · · · · ·	\$26 \$ 2 5 1916
	And raise a mound of stone, 3 ft.base, 3 ft. high, W.
	of cor.
	Land, level. Soil. coarse texture, 26 ins. deep.
	No timber.
	Undergrowth, broom weed, 1 ft. high. Fair grass.
	T 900 FOLD as a mandam line hat good 24 and 25
40.00	N.89° 52' E., on a random line, bet. secs. 24 and 25. Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect E. pdy. of Tp., 5 lks. S. of the cor. of secs.
	24, 25 and 30, which is an iron post, described in Boo
	Thence
	S.89° 50' W., on a true line, bet. secs. 24 and 25. Over gently rolling land, through scattering timber and
24.00	undergrowth.
24.00 30.00	Leave scattering timber. Wide draw, course NE.
36.85	Enter scattering timber.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 26 inthe in the ground, for $\frac{1}{2}$ sec. cor., marked on brass cap
	½S24 S25
ere i i	1916
	From which
	A pinion, 12 ins. diam., brs. $N.7\frac{1}{2}$ ° E., 28 lks. dist., marked $\frac{1}{2}S24$ BT.
	A pinion, 8 ins. diam., brs. S.ll2 W., 93 lks. dist.
47.85	marked \(\frac{1}{4}S25 \) BT. Leave scattering timber.
80.08	The cor. of secs. 23, 24, 25 and 20.
. :	Land, gently rolling. Soil, coarse texture, 26 ins. deep.
	Timber, scrub cedar and pinion.
	Undergrowth, sagebrush and Brigham brush, 1 to 3 ft. high and broom weed, 1 ft. high.
	Fair grass.
İ	

```
Completion of Subdivision of T. 27 N., R. 4 E.
Chains.
           N.0° 1' W., bet. secs. 23 and 24.
           Ovev gently rolling land, through scattering timber and
              undergrowth.
          Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor, marked on brass cap
 40.00
                                        글S23 S24
                                            1916
              From which
          A cedar, 8 ins. diam., brs. S.40½° E., 214 lks. dist., marked $24 BT.

A cedar, 16 ins. diam., brs. S.37³° W., 46 lks. dist., marked $23 BT.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap
80.00
              brass cap
                                        T27N R4E
S14 S13
S23 S24
                                            1916
              From which
              A pinion, 8 ihs. diam., brs. N.70° E., 134 lks. dist., marked T27N R4E S13 BT.
              A pinion.
                           12 ins. diam., brs. 8.39° E., 235 lks. dist.
              marked T27N R4E S24 BT.
              A pinion, 10 ins. diam., brs. S.78° W., 132 lks. dist., marked T27N R4E S23 BT.
              A pinion, 10 ins. diam., brs. N.72\frac{1}{2}° W., 34 lks. dist.,
              marked T27N R4E S14 BT.
          Land, gently rolling.
Soil, coarse texture, 26 ins. deep.
          Timber, a few scrub cedar trees.
          Undergrowth, Brigham brush, 1 to 2 ft. high, and broom
              weed, 1 ft. high.
          Fair grass.
          N.89° 50' E., on a random line, bet. secs. 13 and 24. Set temp. 2 sec. cor. Intersect E. bdy. of Tp., 2 lks. N. of the cor. of se
40.00
79.90
                                             , 2 lks. N. of the cor. of secs.
              13, 18, 19 and 24, which is an iron post, described in
              Book "D'"
          Thence
          S.89° 51' W., on a true line, bet. secs. 13 and 24.
          Over gently rolling land, through scattering timber and
             undergrowth.
         Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
39.95
                                       1916
              From which
              A pinion, 16 ins. diam., brs. N.85\frac{1}{2}° W., 240 lks. dist.,
              marked \frac{1}{4}S13.37.
              A pinion, 12 ins. diam., brs. S.76\frac{1}{2}° W., 175 lks. dist.,
          marked \frac{1}{4}S24 BT.
The cor. of secs. 13, 14, 23 and 24.
79.90
          Land, gently rolling.
          Soil, coarse texture, 26 ins. deep.
          Timber, scattering scrub cedar and pinion.
Undergrowth, sagebrush and Brigham brush, 1 to 3 ft. high,
              and broom weed, 1 ft. high.
          Fair grass.
```

10.		etion of Subdivision of T. 27 N., R. 4 E.
	20.00 40;00	N.0° 1' W., bet. secs. 13 and 14. Over gently rolling land, through scattering timber and undergrowth. Leave scrub timber. Set an iron post, 3 ft. long, lin. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1916
	80.00	And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, marked on brass cap T27N R4E S11 S12 S14 S13 1916
		From which A cedar, 8 ins. diam., brs. N.43° W., 214 lks. dist., marked T27N R4E S11 BW. No other trees within limits. Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, Brigham brush, 2 ft. high, and broom weed, 1 ft. high. Fair grass.
	40.00 79.89	N.89° 51' E., on a random line, bet. secs. 12 and 13. Set temp. ½ sec. cor. Intersect E. bdy. of Tp., 21 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, described in Book "D." Thence West on a true line, bet. secs. 12 and 13. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for ½ sec. cor. marked on brass can
	69.90 79.89	ground, for \$\frac{1}{4}\$ sec. cor., marked on brass cap \$\frac{1}{4}\$S12 \$\frac{1}{8}\$13 \$\frac{1}{9}\$16 From which A cedar, \$\frac{1}{3}6\$ ins. diam., brs. N.12\frac{1}{2}° E., 277 lks. dist. marked \$\frac{1}{4}\$S12 BT. A pinion, \$10\$ ins. diam., brs. S.72° W., 362 lks. dist. marked \$\frac{1}{4}\$S13 BT. Leave scattering timber. The cor. of secs. \$11\$, \$12\$, \$13\$ and \$14\$. Land, gently rolling. Soil, coarse texture, \$26\$ ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush and Brigham brush, \$1\$ to \$3\$ ft. high, and broom weed, \$1\$ ft. high. Fair grass.
	40.00	N.O° 1' W., on a random line, bet. secs. 11 and 12. Set temp. 2 sec. cor.

		Completion of Subdivision of T. 27 N., R. 4 E.
	Chains. 80.92	Intersect S. bdy. of sec. 1, 14 lks.W.of reestab.cor. of secs. 11 and 12, which is an iron post, hereinbefore described.
į	20 . 90 40 . 92	Thence S.0° 5' W., on a true line, bet. secs. 11 and 12. Over gently rolling land, through scattering timber and undergrowth. Draw, 2 chs. wide, course NE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	40.74	ground, for 4 sec. cor., marked on brass cap
		1916
	80.92	From which A pinion, 20 ins. diam., brs. $5.84\frac{1}{2}$ ° E., 120 lks. dist., marked $\frac{1}{2}$ S12 BT. A pinion, 10 ins. diam., brs. N.653° W., 64 lks. dist., marked $\frac{1}{4}$ S11 BT. The cor. of secs. 11, 12, 13 and 14.
		Land, gently rolling. Soil, loose, yellow loam, over sandstone and limestone formations. Timber, pinion and juniper. Undergrowth, broom weed, 1 to 2 ft. high, and scattering
		sagebrush. Fair grass.
	40.00	From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is an iron post, described in Book "J," N.O° 1' W., bet. secs. 34 and 35. Over gently rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1916
		And raise a mound of stone, 3 ft. base, 3 ft. high, W.
	56.00 80.00	of cor. Draw, 2 chs. wide, course SE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on brass cap
		T27N R4E S27 S26 S34 S35 1916
		And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, gently rolling. Soil, loose, yellow, gravelly loam, over malpais formation. No timber. Undergrowth, broom weed, 1 ft. high. Fair grass.
	40.00 80.10	N.89° 57' E., on a random line, bet. secs. 26 and 35. Set temp. \frac{1}{4} \text{ sec. cor.} Intersect N. and S. line, 2 lks. N. of the cor. of secs. 25, 26, 35 and 36. hence S.89° 58' W., on a true line, bet. secs. 26 and 35.

		Completion of Subdivision of T. 27 N. R. 4 E.
	30.10 40.05	Over gently rolling land, through scattering undergrowth. From this point, dirt reservoir brs. S. 20 chs. dist. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		\frac{1}{4}\$26 \frac{3}{5} 1916
	/ s	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
	80.10	The cor. of secs. 26, 27, 34 and 35. Land, gently rolling.
		Soil, loose, yellow, gravelly clay and loam. No timber. Undergrowth, broom weed, 6 ins. to 12 ins. high.
3		
	40.00	N.O° 1' W., bet. secs. 26 and 27. Over gently rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor, marked on brass cap
		₹ S27 S26
		1916 And raise a mound of stone, 3 ft.base, 3 ft. high, W.
	45.00 80.00	of cor. Draw, 3 chs. wide, course SE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap
		T27N R4E . S22 S23 S27 S26 1916
		And raise a mound of stone, 3 ft.base, 3 ft. high, W. of cor. Land, gently rolling. Soil, loose, yellow loam, over malpais formation. No timber.
		Undergrowth, broom weed, 6 to 12 ins. high. Fair grass.
	40.00 79.98	N.89° 58' E., on a random line, bet. secs. 23 and 26. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 2 lks. N. of the cor. of secs. 23, 24, 25 and 26.
	39. 99	Thence S.89° 59' W., on a true line, bet. secs. 23 and 26. Over gently rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap
		1916
	75.00 79.98	And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. Draw, course SE. The cor. of secs. 22, 23, 26 and 27. Land, gently rolling. Soil, loose, yellow, gravelly loam. No timber.

		Completion of Subdivision of T. 28 N. R. 4 E. 13.
	Chains.	Undergrowth, scattering sagebrush, and broom weed, 6 to 12 ins. high.
	-	
	5.00 40.00	N.0° l' W., bet. secs. 22 and 23. Over gently rolling land, through scattering undergrowth. Draw, course SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap
		1 S22 S23
		1916
		And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
	55.00 55.50 80.00	Draw, 2 chs. wide, course NE. Enter scattering timber, brs. NE. and SW. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, marked on brass cap
		T27N R4E S15 S14 S22 S23 1916
		From which A pinion, 12 ins. diam., brs. N.73° E., 193 lks. dist., marked T27N R4E S14 BT. A pinion, 6 ins. diam., brs. S.32½° E., 58 lks. dist., marked T27N R4E S23 BT. A pinion, 6 ins. diam., brs. S.4° W., 158 lks. dist., marked T27N R4E S22 BT. A pinion, 14 ins. diam., brs. N.83½° W., 122 lks. dist.,
		marked T27N R4E S15 3T. Land, gently rolling. Soil, loose, yellow, gravelly loam, over malpais formation. Timber, pinion and juniper. Undergrowth, broom weed, 1 ft. high, Fair grass.
	40.00 7 9.98	N.89° 59' E., on a random line, bet. secs. 14 and 23. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 17 lks. S. of the cor. of secs. 13, 14, 23 and 24. Thence
	5.00 39.99	S.89° 52' W., on a true line, bet. secs. 14 and 23. Over gently rolling land, through scattering timber and undergrowth. Leave scattering timber, brs. N. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
		½S14 S23 1916
	60.00 79.98	And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. Enter scattering timber, brs. N. and SW. The cor. of secs. 14, 15, 22 and 23. Land, gently rolling. Soil, loose, yellow loam. Timber, pinion and juniper. Undergrowth, broom weed, 1 ft. high. Fair grass.
١	ļ	

4.		Completion of Subdivision of T. 27 N., R. 4 E.
	15.00 40.00	N.0° 1' W., bet. secs. 14 and 15. Over rolling land, through scattering timber and undergrowth. Leave scattering timber, brs. NW. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	40.00	ground, for ½ sec. cor, marked on brass cap 4815 814
		1916
	80.00	Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on brass cap
		T27N R4E S10 S11 S15 S14 1916
		And dig pits, 18 X 18 X 12 ins., in each sec., 5½ ft. dist. Land, gently rolling. Soil, loose, yellow, sandy clay and loam. Timber, pinion and juniper. Undergrowth, broom weed, 1 to 2 ft. high. Fair grass.
_	40.00 80.00	N.89° 52' E., on a random line, bet. secs. 11 and 14. Set temp. ½ sec. cor. Intersect N. and S. line, 7 lks. N. of the cor. of secs. 11, 12, 13 and 14. Thence S.89° 55' W., on a true line, bet. secs. 11 and 14.
•	30.00 33.00 40.00	Over gently rolling land, through scattering timber and undergrowth. Leave scattering, enter heavy timber, brs. NW. and SE. Draw, 2 chs. wide, course NE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
	65.00 80.00	From which A pinion, 10 ins. diam., brs. N.23½° E., 69 lks. dist., marked ½Sl1 BT. A pinion, 10 ins. diam., brs. S.11½° E., 119 lks. dist., marked ½Sl4 BT. Leave timber, brs. N. and SE. The cor. of secs. 10, 11, 14 and 15. Land, gently rolling. Soil, loose, yellow, loam, over limestone and sandstone formations. Timber, pinion and juniper. Undergrowth, broom weed, 6 to 24 ins. high. Fair grass.
	4 0.00 80.81	N.0° 1' W., on a random line, bet. secs. 10 and 11. Set temp. 2 sec. cor. Intersect R.andyW.line,17 lks.W.of reestablished cor.of secs. 10 and 11, which is an iron post, hereinbefore described.

```
Completion of Subdivision of T. 27 N., R. 4 E.
           S.0° 6' W., on a true line, bet. secs. 10 and 11. Over rolling, burnt over land, through scattering under-
               growth.
          Draw, 2 chs. wide, course NW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor, marked on brass cap
  8.80
40.81
                                          2510 S11
               And dig pits, 18 X 18 X 12 ins., N. and S. of post, 3
               ft. dist.
80.81
           The cor. of secs. 10, 11, 14 and 15.
          Land, rolling.
Soil, loose, yellow loam, over sandstone formation.
          Timber, a few scattering pinion and juniper trees. Undergrowth, broom weed, 1 to 2 ft. high.
          Fair grass.
          From the cor. of secs. 33 and 34, on the S. bdv. of the Tp.,
          which is an iron post, described in Book "J," N.O° 2' W., bet. secs. 33 and 34.
          Over rolling land, through scattering timber and under-
              growth.
          Desc. 65 ft. to
 5.00
          Shallow draw, course E. Asc. gradually to
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for \( \frac{1}{4} \) sec. cor, marked on brass cap
24.90
40.00
                                         1533 S34
                                              1916
              And raise a mound of stone, 3 ft. base, 3 ft. high, W.
          Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on
80.00
               brass cap
                                         T27N R4E
S28 S27
                                           S33 S34
                                              1916
              And raise a mound of stone, 3 ft. base, 3 ft. high, 4.
              of cor.
          Land, rolling.
          Soil, coarse texture, 26 ins. deep.
Timber, a few scrub cedar and pinion.trees.
          Undergrowth, sagebrush and Brigham brush, 2 ft. high, and
               broom weed, 1 ft. high.
          Fair grass.
          N.89° 57' E., on a random line, bet. secs. 27 and 34.
          Set temp. ½ sec. cor.

Intersect N. and S. line, 5 lks. S. of the cor. of secs.

26, 27, 34 and 35.
40.00
80.20
          S.89° 55' W., on a true line, bet. secs. 27 and 34. Over slightly rolling land, through scattering undergrowth. Low rim, brs. HW. and SE.
19.60
21.90
          Wide draw, course SE.
          Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., marked on brass cap
40.10
```

Completion of Subdivision of T. 27 N. Chains. <u>‡</u>S27 1916 And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. Road, brs. NW. and SE. 42.25 80.20 The cor. of secs. 27, 28, 33 and 34. Land, slightly rolling. Soil, coarse texture, 26 ins. deep. No timber. Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high. and broom weed, 1 ft. high. Fair grass. $N.0^{\circ}$ 2' W., bet. secs. 27 and 28. Over slightly rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor, marked on brass can 40.00 ±\$28 | **\$2**7 From which A pinion, 10 ins. diam., brs. N.19° E., 210 lks. dist. marked \$\$27 BT. No other trees within limits. Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. 70.00 Enter scattering timber. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on 80.00 brass cap T27N R4E S21 S22 S28 | S27 1916 From which A pinion, 12 ins. diam., brs. $\mathbb{N}.60\frac{1}{4}$ ° E., 36 lks. dist. marked T27N R4E S22 BT. A pinion, 10 ins. diam., brs. $8.59\frac{3}{4}$ ° E., 86 lks. dist. marked T27N R4E S27 BT. 9 ins. diam., brs. S.42° W., 25 lks. dist., A pinion. marked T27N R4E S28 BT.

A cedar, 8 ins. dism., brs. N.85° W., 55 lks. dist., marked T27N R4E S21 BT. Land, slightly rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering cedar and pinion timber. Undergrowth, broom weed, 1 ft. high. Fair grass. N.89° 55' E., on a random line, bet. secs. 22 and 27. 40.00 Set temp. - sec. cor. ਰੋਹ.17 Intersect N. and S. line, 14 lks. N. of the cor. of secs. 22, 23, 26 and 27. Thence N.89° 59' W., on a true line, bet. secs. 22 and 27. Over gently rolling land, through scattering undergrowth.

40.08 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 1S22

1916

		Completion of Subdivision of T. 27 N. R. A. T
	Chains.	Completion of Subdivision of T. 27 N. R. 4 E. 17
	62.40	And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. Road, brs. NW. and SE.
	68.15	Enter scattering timber.
	80.17	The cor. of secs. 21, 22, 27 and 28. Land, slightly rolling.
		Soil, coarse texture, 26 ins. deep.
		Timber, scattering scrub cedar and pinion. Undergrowth, broom weed, 1 ft. high.
		Fair grass.
	·	
		N.O° 2' W., bet. secs. 21 and 22. Over rolling land, through scattering timber and undergrowth.
	40.00	Set an iron most, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on orass cap
		₹ S21 S22
		1916
		From which
		A pinion, 10 ins. diam., brs. N.50 $\frac{1}{2}$ ° E., 53 lks. dist., marked $\frac{1}{4}$ S22 BT.
		A pinion, 16 ins. diam., brs. West, 31 lks. dist., marked \(\frac{1}{4} \)S21 BT.
	47.00 80.00	Road, brs. NW. and SE.
	00.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on
		brass cap T27N R4E
		B 16 S15
		\$21 \$22 1916
		From which
		A cedar, 10 ins. diam., brs. S.38 $\frac{1}{2}$ ° E., 276 lks. dist., marked T27N R4E S22 BT.
		No other trees within limits. Raise a mound of stone, 3
		ft. base, 3 ft. high, W. of cor. Land, rolling.
		Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion.
.		Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high,
		and broom weed, 1 ft. high. Fair grass.
	. 🖠	
1		S.89° 59' E., on a random line, bet. secs. 15 and 22.
	40.00 [80.05	Set temp. sec. cor. Intersect N. and S. line, 13 ks. S. of the cor. of secs.
	00.05	14, 15, 22 and 23.
		Thence S.89° 55' W., on a true line, bet. secs. 15 and 22.
		Over gently rolling land, through scattering timber and
	40.02½	undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		1/4 S15 S22
		\$22 1916
		From which
		A pinion, 12 ins. diam., brs. N.56° W., 80 lks. dist.,
		marked 4S15 BT.
- 6		

18.		Completion of Subdivision of T. 27 N. R. 4 E.
	80.05	A pinion, 12 ins. diam., brs. S.14° E., 480 lks. dist., marked \(\frac{1}{4}\)S22 BT. The cor. of secs. 15, 16, 21 and 22. Land, slightly rolling. Soil, coarse texture, 26 ins. deep. Timber, a few scrub cedar and pinion trees. Undergrowth, broom weed, 8 ins. high. Fair grass.
		N.0° 2' W., bet. secs. 15 and 16. Over rolling, burnt over land, through scattering under-
	40.00	growth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap
•		1916 1916
	80.00	And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
•	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on brass cap T27N R4E
		\$ 9 \$10 \$16 \$15 1916
	·	And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
		Land, rolling. Soil, loose, yellow loam. Timber, a few burnt pinion and juniper trees. Undergrowth, broom weed, l ft. high. Fair grass.
	,	
	40.00 80.06	N.89° 55' E., on a random line, bet. secs. 10 and 15. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 2 lks. N. of the cor. of secs. 10, 11, 14 and 15.
		Thence S.89° 56' W., on a true line, bet. secs. 10 and 15. Over gently rolling land, through scattering timber and undergrowth.
	40.03	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
		1/4 S10 S15 1916
	EE 00	And dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
	55.00 80.06	Draw, 5 chs. wide, course NW. The cor. of secs. 9, 10, 15 and 16. Land, gently rolling. Soil, dark, loose, yellow loam. Timber, a few scattering pinion and juniper trees. Undergrowth, broom weed, 1 ft. high. Fair grass.

```
Completion of Subdivision of T. 27 N., R. 4 E.
Chains.
           N.0° 2' W., on a random line, bet. secs. 9 and 10. Set temp. 1 sec. cor. Intersect the reestablished cor. of secs. 9 and 10,
 40.00
 80.70
                which is an iron post, hereinbefore described.
           Thence
           S.0° 2' E., on a true line, bet. secs. 9 and 10. Over rolling, burnt over land, through scattering under-
               growth.
           Draw, 5 chs. wide, course SW.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, for \( \frac{1}{4} \) sec. cor., marked on
 25.70 40.70
                brass cap
                                           18 9 S10
                                               1916
                And dig pits, 18 X 18 X 12 ins., N. and S. of post, 3
                ft. dist.
 80.70
           The cor. of secs. 9, 10, 15 and 16.
           Land, rolling.
Soil, loose, red, rocky loam, over limestone formation.
Timber, burned off.
           Undergrowth, scattering sagebrush, squawbrush and bruck
               brush.
           Fair grass.
           From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., which is an iron post, described in Book "J", N.O° 3' W., bet. secs. 32 and 33.
           Over rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 40.00
               ground, for ½ sec. cor, marked on brass cap
                                          ₹$32 |$33
                                               1916
                And raise a mound of stone, 3 ft. base, 3 ft. high, W.
               of cor.
           Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on
 80.00
                brass cap
                                          T27N R4E
S29 | S28
                                            S32 | S33
               From which
                A pinion, 24 ins. diam., brs. N.59\frac{1}{2}° E., 178 lks. dist.,
                marked T27N R4E S28 BT.
               A pinion, 10 ins. diam., brs. S.36° E., 465 lks. dist., marked T27N R4E S33 BT.
A pinion, 10 ins. diam., brs. S.173° W.,109 lks. dist.,
                marked T27N R4E S32 BT.
               A pinion, 10 ins. diam., brs. N.34° W., 260 lks. dist., marked T27N R4E S29 BT.
           Land, rolling and gently rolling.
Soil, loose, yellow loam, over malpais formation.
           Timber, pinion and juniper.
           Undergrowth, broom weed, 1 ft. high; and scattering sage
                brush.
           Fair grass.
           N.89° 57' E., on a random line, bet. secs. 28 and 33.
 40.00
           Set temp. \frac{1}{2} sec. cor.
```

	·•	
20.		Completion of Subdivision of T. 27 N., R. 4 E.
	Chains. 79.82	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 27, 28, 33 and 34.
•	39 . 91	S.89° 58' W., on a true line, bet. secs. 28 and 33. Over gently rolling land, through scattering undergrowth. Set an iron post, 3 ft. long, l in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
	,	½\$28 \$33 1916
•		And raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
•	60.80 79.82	Enter scattering timber, brs. N. and S. The cor. of secs. 28, 29, 32 and 33. Land, gently rolling. Soil, loose, yellow loam, over malpais formation. Timber, pinion and juniper.
		Undergrowth, broom weed, 1 ft. high. Fair grass.
	11.00 40.00	N.0° 3' W., bet. secs. 28 and 29. Over rolling land, through scattering timber and undergrowth. Enter heavy timber, brs. E. and W. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \$\frac{1}{4}\$ sec. cor, marked on brass cap
		½ S2 9 S2 8
•		1916
	72.00 75.00 80.00	From which A pinion, 7 ins. diam., brs. S.663° E., 64 lks. dist., marked \$\frac{1}{4}\$S28 BT. A pinion, 30 ins. diam., brs. N.73\frac{1}{4}° W., 34 lks. dist., marked \$\frac{1}{4}\$S29 BT. Leave heavy timber, brs. NE. and SW. Draw, 1 ch. wide, course NE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, marked on brass cap
•		T27N R4E S20 S21 S29 S28 1916
		And raise a mound of stone, 3 ft. base, 3 ft. high, W. W. of cor. Land, gently rolling and. Soil, loose, yellow loam. Timber, pinion and juniper. Undergrowth, scattering sagebrush, and broom weed, 1 ft. high. Fair grass.
		- W D- W
	40.00 80.00	N.89° 58' E., on a random line, bet. secs. 21 and 28. Set temp. ? sec. cor. Intersect the corner of secs. 21, 22, 27 and 28.
		Thence S.89° 58' W., on a true line, bet. secs. 21 and 28. Over rolling land, through scattering timber and under-
	30.00	growth. From this point, mountain brs. N. 10 chs. dist. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

Completion of Subdivision of Tre 27 N., R. 4 E. Chains. ground, for ½ sec. cor., marked on brass cap <u></u>3821 \$28 1916 From which A pinion, 10 ins. diam., brs. N.25½° W., 153 lks. dist., marked ½S21 BT.
A pinion, 8 ins. diam., brs. S.3½° W., 33 lks. dist., marked ½ S28 BT. 61.00 Draw, 1 ch. wide, course NW. Leave scattering timber, brs. NE. and SW. 74.00 75.00 Draw, 1 ch. wide, course NE. The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, loose, rocky loam, over malpais formation. Timber, pinion and juniper. Undergrowth, broom weed, 1 ft. high. Fair grass. N.0° 3' W., bet. secs. 20 and 21. Over rolling land, through scattering undergrowth. 10.00 Enter scattering timber, brs. E. and W. Draw, 3 chs. wide, course NW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap 20.00 40.00 1520 S21 1916 From which 6 ins. diam., brs. S.87 $\frac{1}{5}$ ° E., 78 lks. dist. A juniper, marked 4S21 BT. A juniper, 6 ins. diam., brs. S.89½° W., 37 lks. dist. marked 4S20 BT. Draw, 2 chs. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on 44.00 80.00 brass cap T27N R4E S17 S16 S20 S21 1916 And raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, gently rolling. Soil, loose, rocky loam, over malpais formation. Timber, a few scattering juniper and pinion trees. Undergrowth, broom weed, 6 to 12 ins. high. Fair grass. N.89° 58' E., on a random line, bet. secs. 16 and 21. Set temp. 4 sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs. 40.00 80.17 15, 16, 21 and 22. S.89° 56' W., on a true line, bet. secs. 16 and 21. Over gently rolling land, through scattering timber and undergrowth. 16.10 Road, brs. NW. and SE. 29.00 Ditch, 10 lks. wide, 1 ft. deep, course $\frac{1}{10}$. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

BOOK 3104

```
22
              Completion of Subdivision of T.
   Chains.
                ground, for \frac{1}{4} sec. cor., marked on brass cap
                                       1<sub>4</sub>S16
                                         S21
                                        1916
                From which
                A ceder, 14 ins. diam., brs. N.7\frac{3}{4}° E., 244 lks. dist.,
                marked 4816 BT.
                A cedar, 10 ins. diam., brs. S.554° E., 262 lks. dist., marked 4821 BT.
            Road, brs. NW. and SE. Road, brs. NW. and SE.
    46.63
   61.15
    79.10
            Road, brs. N. and S.
   86.17
            The cor. of secs. 16, 17, 20 and 21.
            Land, gently rolling. Soil, coarse texture, 26 ins. deep.
            Timber, a few scattering cedar and pinion trees.
             Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high,
                and broom weed, 1 ft. high.
             Fair grass.
             N.0° 3' W., bet. secs. 16 and 17. Over gently rolling, burnt over land, through scattering
                undergrowth.
    11.00
             Road, brs. NE. and SW.
    14.20
             Wire fence, brs. NE. and SW.
            S. end of dirt reservoir, extends N. N. end of reservoir.
    19.10
    24.10
            Four wire fence, brs. NE. and SW.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor, marked on brass cap
    26.00
    40.00
                                        <del>2</del>817|816
                                            1916
                 And dig pits, 18 X 18 X 12 ins., N. and S. of post, 3
                 ft. dist.
             From this point, hill brs. W. 10 chs. dist.
    50.00
             Draw, 1 ch. wide, course NE.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, marked on
     5.00
    80.00
                 brass cap
                                        T27N R4E
S 8 S 9
S17 S16
                                            1916
                And dig pits, 18 \times 18 \times 12 ins., in each sec., 5\frac{1}{5} ft.
                 dist.
             Land, gently rolling.
                    loose, gravelly yellow loam.
             No timber.
             Undergrowth, scattering sagebrush, and broom weed, 1 ft.
                 high.
             Fair grass.
             N.89° 56' E., on a random line, bet. secs. 9 and 16.
             Set temp. \frac{1}{4} sec. cor.
    40.00
             Intersect N. and S. line, 32 lks. S. of the cor. of secs.
    80.16
                 9, 10, 15 and 16.
             Thence
             $.89° 55° W., on a true line, bet. secs. 9 and 16.
             Over rolling land, through scattering undergrowth.
    37.15
             Road, brs. NW. and SE.
```

		EOOK	3
		Completion of Subdivision of T. 27 N., R. 4 E. 23.	
	chains. 40.08	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap	
		½S 9 316 1916	
	63.65 75.15 80.16	And dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. Road, brs. N. and S. Draw, 1 ch. wide, course NE. The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, loose, yellow loam. No timber. Undergrowth, broom weed, 1 ft. high. Fair grass.	
•	40.00 80.62	N.0° 3' W., on a random line, bet. secs. 8 and 9. Set temp. \(\frac{1}{4} \) sec. cor. Intersect. E. and W. line, 27. lks. W. of reestablished cor. of secs. 8 and 9, which is an iron post, hereinbefore described. Thence	
	0.40 15.10 39.60 40.62	S.0° 9' W., bet. secs. 8 and 9. Over rolling land, through scattering timber and undergrowth. Road, brs. NW. and SE. Draw, 4 chs. wide, course NW. Draw, 1 chs.wide, course NE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \$\frac{1}{2}\$ sec. cor , marked on brass cap	
	55.60 60.10 64.60 80.62	1916 And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Draw, 1 ch. wide, course E. Draw, 50 lks. wide, course E. Asc. to Spur, slopes E. from hill 10 chs. W. Desc. gradually to The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, loose, gravelly loam. Timber, a few pinion and juniper trees. Undergrowth, sagebrush and broom weed, 1 ft. high. Fair grass.	
	40.00	From the cor. of secs. 31 and 32, on the S.bdy. of the Tp. which is an iron post, described in Book "J", N.O° 3' W., bet. secs. 31 and 32. Over gently rolling land, through scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap \[\frac{1}{4}\S31 \] S32 \[\frac{1}{4}\S31 \] S32	
		From which A pinion, 12 ins. diam., brs. $N.63\frac{1}{4}$ ° E., 27 lks. dist., marked $\frac{1}{4}$ S32 BT.	

24.	Completion of Subdivision of The 27 N. R. 4 E.
Chains.	A pinion, 12 ins. diam., brs. N.55° W., 19 lks. dist., marked 1831 BT. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the
	ground, for cor. of secs. 29, 30, 31 and 32, marked on brass cap T27N R4E S30 S29 S31 S32
·	1916 From which A pinion, 10 ins. diam., brs. N.494° E., 108 lks. dist.,
	marked T27N R4E S29 BT. A pinion, 12 ins. diam., brs. S.894° E., 120 lks. dist., marked T27N R4E S32 BT. A pinion, 10 ins. diam., brs. S.432° W., 61 lks. dist.
	marked T27N R4E S31 BT. A pinion, 12 ins. diam., brs. N.88½° W., 334 lks. dist., marked T27N R4E S30 BT. Land, gently rolling.
7	Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high, and broom weed, 1 ft. high. Fair grass.
•	3
40.00 80.00	N.89° 57' E., on a random line, bet. secs. 29 and 32. Set temp. ½ sec. cor. Intersect N. and S. line, 2 lks. N. of the cor. of secs. 28, 29, 32 and 33.
	Thence S.89° 58' W., on a true line, bet. secs. 29 and 32. Over gently rolling land, through scattering timber and undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
	\$329 \$32 1916
	From which A pinion, 20 ins. diam., brs. N.28\frac{1}{4}\circ W., 150 lks. dist., marked \frac{1}{4}\$S29 BT. A pinion, 30 ins. diam., brs. S.23\frac{3}{4}\circ W., 220 lks. dist., marked \frac{1}{4}\$S32 BT.
41.00 50.00 80.00	Enter heavy timber, brs. NE. and SW. Leave heavy, enter scattering timber, brs. NW. and SE. The cor. of secs. 29, 30, 31 and 32. Land, gently rolling.
	Soil, loose, yellow loam. Timber, pinion and juniper. Undergrowth, a few scattering sagebrushes; and broom weed, 1 ft. high.
	Fair grass.
40.00 80.07	S.89° 57' W., on a random line, bet. secs. 30 and 31. Set temp. \(\frac{1}{4}\) sec. cor. Intersect W. bdy. of Tp., 9 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, described in
	Book "I". Thence N.89° 53' E., on a true line, bet. secs. 30 and 31. Over rolling land, through scattering timber and undergrowth.

	Completion of Subdivision of T. 27 N., R. 4 E. 25.
Chains. 7.10 15.05	Asc. 55 ft. to Rim of mesa, brs. NW. and SE. Thence over gently rolling land.
33.05 40.07	Leave scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap
	\$30 \$31 1916
52.55 80.07	From which A cedar, 10 ins. diam., brs. N.83½° W., 407 lks. dist. marked ¼530 3T. A cedar, 12 ins. diam., brs. S.50½° W., 3 81 lks. dist., marked ¼531 BT. Enter scattering timber. The cor. of secs. 29, 30, 31 and 32. Land, rolling and gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high and broom weed, 1 ft. high. Fair grass.
35.00 40.00	N.0° 3' W., bet. secs. 29 and 30. Over level land, through scattering undergrowth. Enter scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
	1916
80.00	From which A cedar, 24 ins. diam., brs. S.64° E., 70 lks. dist., marked 4529 BT. A pinion, 12 ins. diam., brs. S.80° W., 235 lks. dist., marked 4530 BT. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap T27N R4E S19 S20 S30 S29 1916
	From which A pinion, 14 ins. diam., brs. N.21° E., 237 lks. dist., marked T27N R4E S20 BT. A cedar, 12 ins. diam., brs. S.74½° E., 74 lks. dist., marked T27N R4E S29 BT. A pinion, 12 ins. diam., brs. S.61° W., 104 lks. dist., marked T27N R4E S30 BT. A pinion, 14 ins. diam., brs. N.44° W., 143 lks. dist., marked T27N R4E S19 BT. Land, level. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush and Brighem brush, 1 to 2 ft. high, and broom weed, 1 ft. high. Fair grass.
	N.89° 58' E., on a random line, bet. secs. 20 and 29.

2 6		Completion of Subdivision of T. 27 N. R. 4 E.
	40.00 80.00	Set temp. \(\frac{1}{4}\) sec. cor. Intersect M. and S. line, 2 lks. N. of the cor. of secs. 20, 21, 28 and 29.
	3 6. 00 40 . 00	Thence S.89° 59' W., on a true line, bet. secs. 20 and 29. Over gently rolling land, through scattering undergrowth. Enter scattering timber, brs. NW. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		1916
	58.00 61.00 80.00	From which A pinion, 12 ins. diam., brs. N.27° W., 232 lks. dist., marked \$\frac{1}{4}\$S20 BT. A pinion, 16 ins. diam., brs. \$\S.60\frac{1}{2}\$° W., 80 lks. dist., marked \$\frac{1}{4}\$S29 BT. Draw, 1 ch.wide, course NW. Enter heavy timber, brs. N. and S. The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, loose, rocky loam, over malpais formation. Timber, pinion and juniper.
		Undergrowth, scattering sagebrush, and broom weed, 6 to 12 ins. high. Fair grass.
	40.00 80.00	S. 89° 53' W., on a random line, bet. secs. 19 and 30. Set temp. ½ sec. cor. Intersect 7. bdy. of Tp., 5 lks. N. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, described in Book "I". Thence
	5.00 15.00	N.89° 51' E., on a true line, bet. secs. 19 and 30. Over gently rolling land, through scattering timber and undergrowth. Asc. 50 ft. to Rim of mesa, brs. I. and S. Thence over gently rolling
	40.00	land. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
		\$\frac{1}{4}\$19 \$30 1916
	49.00 58.00 80.00	From which A pinion, 8 ins. diam., brs. N.25° E., 25 lks. dist., marked 2819 BT. A pinion, 12 ins. diam., brs. S.853° W., 93 lks. dist., marked 4830 BT. Leave scrub timber. Enter scrub timber. The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush and Brigham brush, 2 ft. high, and broom weed, 1 ft. high. Fair grass.
		N.0° 3' W., bet. secs. 19 and 20. Over gently rolling land, through scattering timber and undergrowth.

	Completion of Subdivision of T. 27 N., R. 4 E. 27.
Chains 40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 2 sec. cor., marked on brass cap
	1916
48.50 73.80 80.00	
	T27N R4E
	From which A pinion, 16 ins. diam., brs. N.77° E., 256 lks. dist., marked T27N R4E S17 BT. A pinion, 12 ins. diam., brs. S.47½° E., 78 lks. dist., marked T27N R4E S20 BT. A cedar, 10 ins. diam., brs. S.16½° W., 75 lks. dist., marked T27N R4E S19 BT. A cedar, 12 ins. diam., brs. N.66° W., 295 lks. dist., marked T27N R4E S18 BT. Land, gently rolling. Soil, coarse texture, rocky, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, sagebrush, Brigham orush and holly brush, 1 to 4 ft. high, and broom weed, 1 ft. high. Fair grass.
40.00 79.78	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 16, 17, 20 and 21.
24.00 39.89	
	1916
75.00 76.00 79.78	Edge of mesa, brs. NW. and SE. Desc. 30 ft. to

28.		Completion of Subdivision of T. 27 N., R. 4 E.
	40.00 79.90	S.89° 51' W., on a random line, bet. secs. 18 and 19. Set temp. \(\frac{1}{4} \) sec. cor. Intersect W. bdy. of Tp., 2 lks. S. of the cor. of secs. 13, 18, 19 and 24, which is an iron post, described in Book "I".
	9.90 3 9.90	Thence N.89° 52' E., on a true line, bet. secs. 18 and 19. Over gently rolling land, through scattering timber and undergrowth. Shallow draw, course S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
		1518 1916
	79.90	From which A pinion, 10 ins. diam., brs. N.5° E., 95 lks. dist., marked \$\frac{1}{2}\$18 BT. A pinion, 10 ins. diam., brs. S.33° E., 145 lks. dist., marked \$\frac{1}{4}\$\$19 BT. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering cedar and pinion. Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high, and broom weed, 1 ft. high. Fair grass.
	8.00 40.00	N.0° 3' W., bet. secs. 17 and 18. Over gently rolling land, through scattering timber and undergrowth. Rim of mesa, brs. N.W. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
		1916
	80.00	And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap T27N R4E S7 \$ 8 S18 \$17 1916
		From which A pinion, 12 ins. diam., brs. N.64½° E., 373 lks. dist., marked T27N R4E S8 BT. A cedar, 12 ins. diam., brs. S.9° E., 296 lks. dist., marked T27N R4E S17 BT. A pinion, 12 ins. diam., brs. S.74½° W.,181 lks. dist. marked T27N R4E S18 BT. A pinion, 10 ins. diam., brs. N.62½° W., 248 lks. dist. marked T27N R4E S7 BT. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scattering scrub cedar and pinion. Undergrowth, sagebrush and holly brush, 1 to 3 ft. high. Fair grass.
].		

	POOK 3107
	Completion of Subdivision of T. 27 N., R. 4 E. 29.
40;00 79.68	N.89° 58' E., on a random line, bet. secs. 8 and 17. Set temp. 4 sec. cor. Intersect N. and S. line, 9 lks. S. of the cor. of secs. 8, 9, 16 and 17.
7.00 39.84	Thence S.89° 54' W., on a true line, bet. secs. 8 and 17. Over rolling land, through scattering undergrowth. Enter scattering timber, brs. NE. and SW. Set an iron post, 3 ft, long, l in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
•	½S 8 S17 1916
79.68	From which A pinion, 8 ins. diam., brs. N.183° E., 396 lks. dist., marked \(\frac{1}{4} \)S8 BT. A pinion, 12 ins. diam., brs. S.33° W.,170 lks. dist., marked \(\frac{1}{2} \)S17 BT. The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, loose, dark, yellow loam. Timber, pinion and juniper.
	Undergrowth, scattering sagebrush, squawbrush, and broom weed, 1 ft. high. Fair grass.
40.00 79.95	S.89° 52' W., on a random line, bet. secs. 7 and 18. Set temp. ½ sec. cor. Intersect W. bdy. of Tp., ll lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, described in Book "I".
21.95 39.95	Thence N.89° 47' E., on a true line, bet. secs. 7 and 18. Over gently rolling land, through scattering timber and undergrowth. Rim of mesa, brs. N. and S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap
	1916
7 9•95	From which A pinion, 12 ins. diam., brs. N.32° E., 43 lks. dist., marked \(\frac{1}{4}\)\$7 BT. A pinion, 10 ins. diam., brs. S.50\(\frac{1}{6}\)° W., 82 lks. dist. marked \(\frac{1}{4}\)\$18 BT. The cor. of secs. 7, 8, 17 and 18. Land, gently rolling.
	Soil, coarse texture, 26 ins. deep. Wimber, scrub cedar and pinion. Undergrowth, sagebrush and Brigham brush, 1 to 2 ft. high. Fair grass.
4 0.00 80.70	N.0° 3' W., on a random line, bet. secs. 7 and 8. Set temp. ½ sec. cor. Intersect E. and W. line 2 lks.E.2f reestablished cor. of secs. 7 and 8, which is an iron post, hereinbefore described. Thence S.0° 4' E., on a true line, bet. secs. 7 and 8. Over gently rolling land, through scattering timber and undergrowth.

<u> 30</u> .

_	•	Completion of Subdivision of T. 27 N. R. A E.							
	Chains. 40.70	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap							
		4s 7 s 8							
	42.70 80.70	From which A pinion, 17 ins. diam., brs. N.11° E., 66 lks. dist., marked 488 BT. A pinion, 14 ins. diam., ors. N.72½° W., 62 lks. dist., marked 487 BT. Rim of mesa, brs. E. and W. The cor. of secs. 7. 8, 17 and 18. Land, gently rolling. Soil, coarse texture, 26 ins. deep. Timber, scrub cedar and pinion. Undergrowth, broom weed, 1 ft. high. Fair grass.							

Boundaries of that portion of T.27 N., R.44 Elsubdivided under to Latitudes, departures and closing errors

	Lat	itudes, depart		closing errors.			
				Latitudes			rtures.
Line d	esignated.	True bearing.		N.	S. 🥖		W.
	e a less entre les	r te Auntaba	chs.	chs.	chs*	chs.	chs.
South	Boundary.	N.89°51'W.	3.72	.01			3.72
	· · · · · · · · · · · · · · · · · · ·	s.89°57'W.	476.45		.41		476.45
West 3	pundary.	North.	399.70	399.70			
	Junuary.	1,01 011.	733.10	757.10			
	sionals.	N.89°37'E. N.89°56'E. N.89°51!E. N.89°51!E. N.89°42'E. N.89°42'E. N.89°42'E. N.89°47'E. N.89°46'E. N.89°46'E.	36.90 40.52 40.39 40.32 40.60 40.21 40.16 40.14 40.18 40.21	.25 1.23 .05 .39 .28 .21 .09 .15 .13	.11	36.90 40.50 40.39 40.60 40.21 40.11 40.16 40.14 40.18 40.21	
East B	oundary.	South.	401.18		401.18		
Conver	gency.					•43	
Totals			402.75	401.70	4 80 .29	480.17	
				401.70		480.17	
Error	Error in latitude.						
Error	n departu	re.				0.12	0.10

General Description.

This township consists of gently rolling and rolling land, covered with a scattering growth of sagebrush, squavbrush and broom weed undergrowth, and cedar, pinion and juniper timber. The soil is a loose, rocky loam, of coarse texture, 10 to 26 ins. in depth.

There are no settlers. Several earth dams have been

There are no settlers. Several earth dams have been constructed in draws, for the impounding of flood waters.

Diagram showing the respective surveys executed by Thomas B.Matthews, U.S.S., and William L. Nash, U.S.T., under instructions for Group No.55, Arizona.

Book "K"
Township 27 North, Range 4 East.

	_ 6	, 5 ,, ,		3	2	1	
	8-7-16	8-7-16	8-8-16	8-8-16	8-8-16	8-8-16	
7-20-16		8 K 8-7-16	9 - 2- - 6 8-7-16	10 4 8-4-16	8-4-16 11 -4-8 91-4-16	12 9 12 - 18 9 18-3-16	(
7-20-16	18 -7-16	17 - 29 17 - 28 8-7-16	91-2-8 16 -2-8 8-4-16	. 15 -4-8	14 14 8-4-16	13 E	
	9- /- id		8-4-(6	8-4-16	8-4-16	8-3-16	,
7-19-16	- 19 <u>4</u>	20 20 91-3-8	51 4- 8-4- 9-4-	22 kg	25 £	91-0e-9 24	
4	8-5-16	8-5-16	8-5-16	8-4-16	8-3-16	8-3-16	
7-19-16	- 30 91-5-8 - 2-1-10		58 -4-8	27 ½	26 -2-8	91-0g-9	
	8-5-16	8-5-16	8-5-16	8-4-16	8-3-16	8-2-16	
7-19-16	, 31 9:5-8 8-5-1	32 <u>3</u> -3-8	22 4-8 31-4-8	, <u>9</u> 34 k,	35 સ્	36 5-30-6	
	8-1-16	8-1-16	8-1-16	8-1-16	8-1-18	8-1-16	5-22-1 6

Blue lines indicate surveys by Thomas B. Matthews, U.S.S., on the various dates shown.

CReed lines indicate surveys by William L.Nash,
U.S.T., on the various dates shown.

32

CERTIFICATES OF U. S. SURVEYOR AND U. S. TRANSITMAN.

We, Thomas B. Matthews and William L. Nash, U. S. SUrveyor and U.S. Transitman, respectively, hereby certify on honor that, in pursuance of special instructions received from the U.S. Surveyor General for Arizona for Group No.55, Arizona, bearing date of the 8th day of March, 1915, we have well, faithfully, and truly, in our own proper persons and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, resurveyed all those parts or portions of the Subdivision lines, and surveyed all those parts or portions of the Subdivision lines of

TOWNSHIP 27 NORTH, RANGE 4 EAST,

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes, and by the diagram on the reverse hereof, as having been executed by us, and under our direction; and we do further certify on honr that all the corners of said resurvey and survey have been reestablished or established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions for the U.S. Surveyor General of Arizona for Group No. 55, and in the specific manner described in our respective field notes, and that the foregoing are the original field notes of such resurveys and surveys.

Thomas B. Matheur Weliam & hack U. S. Surveyor. U.S. Transitman.

APPROVAL

OFFICE OF THE UNITED STATES SURVEYOR GENERAL,

Phoenix, Arizona,

SEP 28 1918.

The foregoing field notes of the Resurvey of part of the Subdivision lines, and survey of the completion of the Subdivision lines of

TOWNSHIP 27 NORTH, RANGE 4 EAST

of the Gila and Salt River Base and Meridian, in the State of Arizona, executed by Thomas B. Matthews, U. S. Surveyor, and William L.Nash, U.S. Transitman, under special instructions, dated March 8, 1915, for Group 55, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the resurveys and surveys they describe, are hereby approved.

I sertify that the foregoing transcript of the field notes of the above-described resurveys and surveys in Book "E," of Group 55, has been sorrectly copied from the ofiginal notes on file in this office.

U.S.Surveyor Coneral of Arizona.