Book"G" 4-679

BOOK > 3161

FIELD NOTES

RE-OF THE SURVEY OF THE

North boundary of Township 22 North, Range 3 West, and
West boundary of Township 23 North, Range 2 West,
and SURVEY of
Subdivision lines of Township 23 North, Range 3 West.
Of the Gila and Salt River Base and Meridian,
In the State ofArizona.
EXECUTED BY
Fred Mensch,
In the capacity of U.S. Surveyor, under instructions dated October 5,, 1915
issued by the United States Surveyor General to govern surveys included in
Group No. 62 , which were approved by the Commissioner of the General Land
Office, November 3, 1915.
Survey Commenced April 18, , 1916.
Survey Completed May 6, , 1916.

3/6/ Book "G"

Group 62 - - - Arizona.

BOOK 3161

		. [N	ЭE	EX			àR	ΑŅ	1.		,	
	Towns	ship	2 <u>3</u>	Nor	t h,		Range	ا 3	West	; <u>,</u>		·	
	6 /	46	5	38	4	32	8	25	2	20	1	1	
	4 6		45		37		31		25		20		
	7	44	8	35	9	3 0	10	25	11	19	12	o l	
	44	_	43		36	_	30		24		19		
	18	43	17	35	16	19	15	24	14	18	13	<u>8</u>	
	42	-	42		35		29	-	23		17		·
	19	4	, 20	34	21	8	22	3	23	17	24	_7	
	40	_	40		34		28_		22		16		
	30	3 9	29	33	28	7	27	22	26	15	25	6	_
	14	ļ	14		13	_	13		12		11		
	81	3 8	32	3 2	33	26	34	21	35	15	36	5-	
. The second second	1		2		2		3		4		4	151	
and growing the second	•	,		1								- 151	

	Surveyed under this groupnotes in this book. 3/6/
	Resurveyed under this groupnotes in this book.3/6/
	Surveyed under this groupnotes in Book F. 3/60
· · · · · · · · · · · · · · · · · · ·	Resurveyed under this groupnotes in Book F.3/60
	Surveyed under current Group 52.
<u> </u>	Resurveyed under current Group 52.

Previously accepted surveys.

Resurvey of N. Bdy., T. 22 N., R. 3 W., Resurvey of W. Bdy., T. 23 N., R. 2 W., and Subdivision of T. 23 N., R. 3 W.

Chains

Work executed by Fred Mensch, U. S. Surveyor on dates shown on diagram on page 49 of this book. The instrument used is described, with record of approval by the Assistant Supervisor of Surveys, field tests, and method of maintaining adjustments, in Books A, D, and F.

The magnetic variation is 15°15'E.

Resurvey of N. Bdy., T. 22 N., R. 3 W.

From the reestablished cor. of Ts. 22 and 23 N., Rs. 3 and 4 W., described in book F;

 $N.87^{\circ}14^{\circ}E.$, on N. bdy. of sec. 6, descending gradual E. slope, through dense timber and undergrowth.

6.92 Wash, course S. Asc. gradually, on W. slope.

25.00 Thence over flat-topped mesa. 39.99

The old 2 sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as ½ sec. cor. of sec. 6 only, as follows:
With original stone, set an iron post, 3 ft. long, 1 in.
diam., 26 ins. in the ground, with brass cap, marked

1 S6

1916

from which

A juniper, 8 ins. diam., bears S.43°W., 64 lks. dist., marked \$\frac{1}{4}\$ S6 BT.

A juniper, 6 ins. diam., bears S.14°15'E., 106 lks. dist., marked \$\frac{1}{4}\$ S6 BT.

Thence S.88°37'E., on N. bdy. of E. half of sec. 6. Desc. 90 ft., on E. slope.
Wash, course S. Asc. 35 ft., on W. slope.
Fence bears N.60°W. and S.60°E.

15.00

32.20

34.20

35.95 38.80 Road bears S. to Ash Fork and N.

Fence bears N. and S. 40.05

The old cor. of secs. 5, 6, 31 and 32, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as cor. of secs. 5 and 6 only, as follows:

With original stone, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 5 and 6, with brass cap, marked

S6 S5 T22N R 3W

1916

A juniper, 9 ins. diam., bears S. 4°E., 29 lks. dist., marked T. 22 N R 3 W S 5 B T.

A juniper, 9 ins. diam., bears S. 85°W., 18 lks. dist., marked T 22 N R 3 W S 6 B T.

rolling and broken.

Soil, malpais and sandstone formations; 2nd to 4th rate. Timber, juniper.

Undergrowth, greasewood, juniper and rabbit brush.

220 BOOK 3161

Resurvey of N. Bdy. T. 22 N. R. 3 W. Chains S.88°34'E., on N. bdy. of sec. 5, ascending on rocky W.slope, through dense timber and undergrowth; 7 lks. S. of wire fence running E. and W. Thence over flat-topped mesa. 12.50 39.75 The old \frac{1}{2} sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. as 2 sec. cor. of sec. 5 only, as follows:
With original stone, set an iron post, 3 ft. long, 1 in.
diam., 26 ins. in the ground, with brass cap, marked 1 S 5 1916 I replace old bearing trees as follows: A juniper, 12 ins. diam., bears S.4°W., 48 lks. dist., marked \(\frac{1}{4} \) S5 BT.

A juniper, 14 ins. diam., bears S.15°E., 42 lks. dist., marked \(\frac{1}{4} \) S5 BT. Thence N.85°45'E., on N. bdy. of E. half of sec. 5. Desc. 300 ft., on rocky SE. slope, through thinner growth 16.00 of timber. The old cor. of secs. 4, 5, 32 and 33, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as cor. of secs. 4 and 5 only, 40.02 as follows: With original stone, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked S5 S4 T22N R 3W 1916 from which A juniper, 10 ins. diam., bears S.57°E., 55 lks. dist., marked T22N R3W S4 BT.
A juniper, 8 ins. diam., bears S.33°W., 44 lks. dist., marked T22N R3W S5 BT. Land, rolling and broken. Soil, sandstone, formation; 3rd and 4th rate. Timber, juniper. Undergrowth, cactus, juniper, and rabbit brush. S.89°58'E., on N. bdy. of sec. 4, descending rocky E. slope, through timber and undergrowth. Wash, 35 lks. wide, 1 ft. deep, course SE., 140 ft. below sec. cor. Asc. SW. slope. 17.95 Thence along S. slope. 30.00 The old ½ sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. as ½ sec. cor. of sec. 4 only, as follows: With original stone, set an iron post, 3 ft. long, 1 in. 40.08 diam., 26 ins.in the ground, with brass cap, marked 1 S4 1916 from which A juniper, 4 ins. diam., bears S.6°E., 145 lks. dist., marked ½ S4 BT. A juniper, 10 ins. diam., bears S.28°W., 181 lks. dist., marked 4 S4 BT. S.89 21 E., on N. bdy. of E. half of sec. 4. Fence bears NE. and SW. 1.10

Desc. steep rocky E. slope. Enter small valley.

6.00

Resurvey of N. Bdy.. Chains Wash, 50 lks. wide, 4 ft. deep, course S.10°E. Asc. rocky W. slope. 19.70 22.50 34.28 Fence bears N.60°W. and S. The old cor. of secs. 3, 4, 33 and 34, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. as cor. of secs. 3 and 4 only, as follows: 40.58 With original stone, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked S4 S3 T22N R 3W 1916 from which
A juniper, 8 ins. diam., bears S.1°30'W., 91 lks. dist.,
marked T22N R3W S4 BT. A juniper, 16 ins. diam., bears S.34°E., 44 lks. dist., marked T22N R3W S3 BT. rolling and broken. Soil, sandstone formation; 3rd and 4th rate. Timber, juniper. Undergrowth, cactus, rabbit brush and greasewood. S.89°48'E., on N. bdy. of sec. 3, ascending gradual W. slope, through timber and undergrowth. 3.00 Desc. rocky NE. slope. 12.00 Thence on more gradual slope. Wash, 20 lks. wide, 3 ft. deep, course SE. Asc. SW. slope, 32.20 over low rolling hills. The old 2 sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. 40.44 as $\frac{1}{4}$ sec. cor. of sec. 3 only, as follows: With original stone, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap, marked 1 S3 1916 from which A juniper, 12 ins. diam., bears S.74°W., 42 lks. dist., marked \$\frac{1}{4}\$ S3 BT.

A juniper, 8 ins. diam., bears S.18\frac{1}{2}°E., 110 lks. dist., marked \$\frac{1}{4}\$ S3 BT. Thence N.89°48'E., on N. bdy. of E. half of sec. 3. Road bears NE. and SW. 19.95 31.55 40.34 Wash, 30 lks. wide, 1 ft. deep, course SE.

The old cor. of secs. 2, 3, 34 and 35, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as cor. of secs. 2 and 3 only, as follows:
With original stone, set an iron post, 3 ft. long, 3 ins.
diam., 24 ins. in the ground, with brass cap, marked S3 S2 T22N R 3W 1916 from which A juniper, 4 ins. diam., bears S.21°E., 12 lks. dist., marked T22N R3W S2 BT.
A juniper, 8 ins. diam., bears S.20°W., 190 lks. dist.,

marked T22N R3W S3 BT.

222

Chains Land, rolling and broken. Soil, sandstone formation; 3rd and 4th rate. Timber, juniper. Undergrowth, juniper, greasewood and rabbit brush. $N.87^{\circ}28$ 'E., on N. bdy. of sec. 2, over low rolling hills, through scattering timber and undergrowth. The old 4 sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. 40.31 as $\frac{1}{4}$ sec. cor. of sec. 2 only, as follows: With original stone, set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, with brass cap, marked 1 S 2 1916 from which A juniper, 12 ins. diam., bears S.2½°E., 223 lks. dist., marked $\frac{1}{4}$ S2 BT.

A juniper, 10 ins. diam., bears S.4 $\frac{1}{4}$ °W., 267 lks. dist., marked $\frac{1}{4}$ S2 BT. Thence S.85°02'E., on E. half of N. bdy. of sec. 2.
The old cor. of secs. 1, 2, 35 and 36, which is a stone, marked and witnessed as described by the Surveyor Gen-42.96 I reestablish cor. as cor. of secs. 1 and 2 only, eral. as follows: With original stone, set an iron post, 3 ft.long, 3 ins. diam., 18 ins. in the ground, surrounded by a mound of stone, with brass cap, marked S2 S1 T22N R3W 1916 from which A juniper, 18 ins. diam., bears S.53°W., 159 lks. dist., marked T22N-R3W S2 BT. A juniper, 18 ins. diam., bears S.21°E., 11 lks. dist., marked T22N R3W S1 BT. Land, rolling.
Soil, sandstone formation; 3rd and 4th rate. Timber, juniper. Undergrowth, greasewood, cactus and rabbit brush. S.85°35'E., on N. bdy. of sec. 1, over rolling mesa, through scattering timber and undergrowth. 15.00 Asc. gradual W. slope. Ridge bears E. and W., 6 chs. N. of line. 40.00 The old \(\frac{1}{4} \) sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. 40.20 as \(\frac{1}{4}\) sec. cor. of sec. 1 only, as follows:

With original stone, set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, with brass cap, marked

경 Sl

Resurvey of N. Bdy. T. Chains A juniper, 28 ins. diam., bears S.10% W., 76 lks. dist., marked % S1 BT. A juniper, 20 ins. diam., bears S.10°E., 134 lks. dist., marked \(\frac{1}{4} \) Sl BT. Thence S.87°21'E., on N. bdy. of E. half of sec. 1. Thence along E. and W. ridge. 5.00 26.18 Fence bears N.70°W. and S.70°E. Fence bears N.15°E. and S.15°W. The old cor. of Ts. 22 and 23 N., Rs. 2 and 3 W., which 38.08 40.22 is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as follows: With original stone, set an iron post, 3 ft long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked T23N R3W R2W S36 S31 S1 S6 732N from which A juniper, 6 ins. diam., bears N.55°E.,176 lks. dist., marked T23N R2W S31 BT. A juniper, 5 ins. diam., bears S.75°E., 8 lks. dist., marked T22N R2W S6 BT. A juniper, 24 ins. diam., bears S.6½°W., 301 lks. dist., marked T22N R3W S1 HT.
A juniper, 8 ins. diam., bears N.24°W., 109 lks. dist., marked T23N R3W S36 BT. Land, rolling. Soil, malpais formation; 3rd and 4th rate. Timber, juniper. Undergrowth, juniper and greasewood. Resurvey of W. Bdy., T. 23 N., R. 2 W. From the reestablished cor. of Ts. 22 and 23 N., Rs. 2 and 3 W., hereinbefore described; N.1°11'W., on W. bdy. of sec. 31, over rolling land, through dense timber and undergrowth. Desc. rocky N. slope. 2.50 15.00 16.40 Ft. of slope. Fence bears N.10°E. and S.10°W. Leave timber, bearing N.70°E. and S.70°W. Thence over rolling prairie. Reestablish missing $\frac{1}{4}$ sec. cor. as $\frac{1}{4}$ sec. cor. of sec. 31 44.55 only, as follows: Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, with brass cap, marked 1831 1916 and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high. E. of cor. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor. of sec. 36, with brass cap, 49.09 marked

Chains 1836 1916 from which A juniper, 24 ins. diam., bears N.8°W., 177 lks. dist., marked $\frac{1}{4}$ S36 BT. No other bearing tree available. Raise a stone, 2 ft. base, 1½ ft. high, W. of cor. Enter timber, bearing NE. and SW. Raise a mound of 50.40 78.65 83.50 89.10 Desc. rocky N. slope. Wash, 60 lks. wide, water in holes, course S.70°E. The old cor. of secs. 25, 30, 31 and 36, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as follows:
With original stone, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked T23N R 3W R 2W S25 S30 s36 S31 1916 from which A juniper, 24 ins. diam., bears S.89°E., 291 lks. dist., marked T23N R2W S31 BT.

A juniper, 18 ins. diam., bears N.71°45'E., 343 lks. dist., marked T23N R2W S30 BT. A juniper, 20 ins. diam., bears N.26°W., 242 lks. dist., marked T23N R3W S25 BT. No other bearing tree available. Dig pits, 18x18x12 ins., in each sec., $5\frac{1}{8}$ ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, malpais formation; 2nd and 4th rate. Timber, juniper. Undergrowth, same. N.2000 W., on W. bdy. of sec. 30, ascending on gradual SW. slope, through scattered timber and undergrowth. 7.10 21.00 Road bears SE. to Ash Fork and NW. Enter dense timber, bearing NW. and SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of sec. 25, with brass cap, 40.02 marked 1916 from which A juniper, 16 ins. diam., bears S.71°W., 3 lks. dist., marked ½ S25 BT.

A juniper, 10 ins. diam., bears N.51°W., 57 lks. dist., marked ½ S25 BT. The old $\frac{1}{4}$ sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. 40.35 as $\frac{1}{4}$ sec. cor. of sec. 30 only, as follows: With original stone, set an iron post, 3 ft.long, 1 in. diam., 26 ins.in the ground, with brass cap, marked 1830 1916 from which A juniper, 6 ins. diam., bears S.182°E., 57 lks. dist., marked 4 S30 BT.

	Resurvey of W. Bdy., T. 23 N., R. 2 W. 7
Chains	
	A juniper, 24 ins. diam., bears N.49°E., 24 lks. dist., marked \(\frac{1}{4}\) S30 BT.
4.50	Thence N.3°04'E., on W. bdy. of N. half of sec. 30. Wash, 60 lks. wide, 6 ft. deep, course W. Thence along gradual W. slope. Wash, course SW.
37 · 85 39 · 73	Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 24 and 25, with brass cap, marked
	T23N
	S24 S25 R3W
	1916 from which
	A juniper, 10 ins. diam., bears N.54°W., 33 lks. dist., marked T23N R3W S24 BT.
	A juniper, 10 ins. diam., bears S.66°W., 107 lks. dist., marked T23N R3W S25 BT.
40.29	The old cor. of secs. 19, 24, 25 and 30, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as cor. of secs. 19 and
	30 only, as follows: With original stone, set an iron post, 3 ft.long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked
	T23N
	S19 S30
	RŹW
	1916
	from which A juniper, 10 ins. diam., bears S.26°E., 67 lks. dist., marked T23N R2W S30 BT.
	A juniper, 24 ins. diam., bears N.74°E., 148 lks. dist., marked T23N R2W S19 BT.
	Land, rolling. Soil, malpais formation; 2nd and 4th rate. Timber, juniper.
,	Undergrowth, same.
	N 00241W on W have of con 30
	N.O°24'W., on W. bdy. of sec. 19, over bottom of valley, through dense timber and undergrowth.
3.19 13.44	Wash, water in holes, course SE. Thence over broken W. slope.
30.54	Wash, 10 lks. wide, course W.
37.00 37.50	Asc. over rock ledge. Thence over rolling mesa.
39 • 44	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{2} \) sec. cor. of sec. 24, with brass cap,
	marked $\frac{1}{4}$ S24
	1916
	from which A juniper, 16 ins. diam., bears N.41°W., 33 lks. dist.,
	marked ½ S24 BT. A juniper, 16 ins. diam., bears S.45°W., 74 lks. dist., marked ½ S24 BT.
40.08	The old $\frac{1}{4}$ sec. cor., which is a stone, marked and witnessed
	as described by the Surveyor General. I reestablish

		Resurvey of W. Bdv. T. 23 N. R. 3 W.
	Chains	
		cor. as \(\frac{1}{4}\) sec.cor. of sec. 19 only, as follows: With original stone, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap, marked
		4 \$19
		from which
Andrew Company of the		from which A juniper, 6 ins. diam., bears N.72°45'E., 66 lks. dist., marked \(\frac{1}{4}\) S19 BT.
William Company of the Company of th		A juniper, 16 ins. diam., bears S.77½°E., 62 lks. dist., marked ½ S19 BT.
İ	25.56	Thence N.2°03'E., on W. bdy. of N. half of sec. 19. Gulch, 70 lks. wide, 20 ft. deep, course W.
	39.38	Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of secs. 13 and 24, with brass cap.
		marked T23N
		S13 S24
		R3W
-		1916
		from which A juniper, 24 ins. diam., bears N.77°W., 121 lks. dist.,
		marked T23N R3W S13 BT.
		A juniper, 24 ins. diam., bears S.36°W., 50 lks. dist., marked T23N R3W S24 BT.
	40.32	The old cor. of secs. 13, 18, 19 and 24, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. as cor. of secs. 18 and 19 only, as follows:
-	÷.	With original stone, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, with brass cap, marked
Ì		T23N
	·	$\frac{\$18}{\$19}$
		R2W
-		1916 from which
-		A juniper, 20 ins. diam., bears N.69°E 30 lks. dist.
		marked T23N R2W S18 BT. A juniper, 10 ins. diam., bears S.68°E., 15 lks. dist., marked T23N R2W S19 BT.
		Land, rolling, and broken.
		Soil, malpais formation; 4th rate. Timber, juniper.
-		Undergrowth, same.
-		
-		
		N.0°31'E., on W. bdy. of sec. 18, descending on steep, rocky N. slope, through dense timber
	6.70	and undergrowth. Wash, 15 lks. wide, 12 ft. deep, course Nr. Thence over
	•	rolling W. slope.
-	99. 50	Small reservoir, built in wash, 150 lks. wide, 3 ft. deep, course S.70°W.
The state of the s	30.90 39.06	Road bears N.70°W, and S. 70°E. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor. of sec. 13, with brass cap.
	. !	marked
-		\$13 307€
		1916

Chains	Resurvey of W. Bdy., T. 23 N., R. 2 W.	
	from which A juniper, 20 ins diam., bears N.59°W., 32 lks. dist., marked ½ S13 BT. A juniper, 20 ins. diam., bears S. 67½° W., 99 lks. dist., marked ½ S 13 B T.	
40.25	The old 4 sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor as 4 sec. cor. of sec. 18 only, as follows: With original stone, set an iron post, 3 ft. long, 1 in.div. 26 ins. in the ground, with brass cap, marked	•
	<u></u>	
-	1916	
	from which A juniper, 24 ins. diam., bears S.37°E., 07 lks. dist., marked \(\frac{1}{4} \) S18 BT. A juniper, 8 ins. diam., bears N.83\(\frac{1}{2} \) °E., 67 lks. dist.,	
	marked 4 S18 BT.	
. 9.80 22.80	Thence N.0°49'E., on W. bdy. of N. half of sec. 18. Asc. SE. slope. Thence over rolling E. slope. Proch force bears E. and W.	
31.40 38.81	Brush fence bears E. and W. Set an iron post, 3 ft. long, 3 ins.diam., 24 ins. in the ground, for cor. of secs. 12 and 13, with brass cap, marked	
*.	T23N S12	
ं √ं 9 9°	S13 R3W	
	19 16	
	from which A juniper, 16 ins. diam., bears N.68°W,, 23 lks. dist., marked T23N R3W S12 BT. A juniper, 16 ins. diam., bears S.76°W., 44 lks. dist.,	
	marked T23N R3W S13 BT.	
40.24	The old cor. of secs. 7, 12, 13 and 18, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as cor. of secs. 7 and 18 only, as follows:	
	With original stone, set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground, with brass cap, marked	. •
	T23N S7	
	1916 from which A juniper, 16 ins. diam., bears N.38°E., 30 lks. dist., marked T23N R2W S7 bT. A juniper, 14 ins. diam., bears S.82½°E., 102 lks. dist., marked T23N R2W S18 BT.	,
	Land, rolling. Soil, malpais formation; 2nd and 3rd rate. Timber, juniper. Undergrowth, juniper and greasewood.	
38 - 5 8	N.1°28'E., on W. bdy. of sec. 7, over rolling land, through dense timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4} \) sec.cor. of sec. 12, with brass cap, marked	

10 Bdvcha ins ₹S12 1916 from which. A juniper, 8 ins. diam., bears S.49°W., 58 lks. dist., marked ½ Sl2 BT.

A juniper, 8 ins. diam., bears N.70°W., 68 lks. dist., marked ½ Sl2 BT. 40.15 The old 2 sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as a sec. cor. of sec. 7 only, as follows: With original stone, set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, with brass cap, marked 187 from which A juniper, 10 ins. diam., bears N.47°E., 82 lks. dist., marked \$\frac{1}{4}\$ S7 BT.

A juniper, 8 ins. diam., bears S.17°E., 43 lks. dist., marked \$\frac{1}{4}\$ S7 BT. Thence N.1°34'E., on W. bdy. of N. half of sec. 7. Brush fence bears E. and W. 10.00 Wash, 110 lks. wide, course S.60°E.; water in holes.
Road bears N.70°W. to Seligman and S.70°E. to Ash Fork.
Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, for the core. 32.72 33.82 38.44 of secs. 1 and 12, with brass cap, marked 1916 from which A juniper, 14 ins. diam., bears N.782°W., 45 lks. dist., marked T23N R3W Sl BT.

A juniper, 24 ins. diam., bears S.35°W., 90 lks. dist., marked T23N R3W Sl2 BT. 40.53 The old cor. of secs. 1, 6, 7 and 12, which is a stone, marked and witnessed as described by the Surveyor General. I reestablish this cor. as cor. of secs. 6 and 7 only, as follows: With original stone, set an iron post, 3 ft. long, 3 ins. diam., 18 ins. in the ground, surrounded by a mound of stone, with brass cap, marked T23N **S**6. **S7** R2W 1916 from which A juniper, 30 ins.diam., bears S.12 E., 117 lks. dist., marked T23N R2W S7 BT. A juniper, 20 ins. diam., bears N.76% E., 43 lks. dist., marked T23N R2W S6 BT. Land, rolling.
Soil, malpais and sandstone formations; 3rd rate. Timber, juniper.

Undergrowth, juniper and greasewood.

Resurvey of W. Bdy. T. Chains N.0°39'E., on W. bdy. of sec. 6, over rolling land, through dense undergrowth and timber. Enter wash, course SE.; thence up bed of same. 4.00 Leave same, course S.; comes from N.20°E. Same wash, 25 lks. wide, course SE. Asc. rocky SW. slope. 5.10 **21.90** Thence over low, rolling mesa.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor. of sec. 1, with brass cap, 28.90 37.91 marked 181 1916 from which A juniper, 8 ins. diam., bears N.6°W., 43 lks. dist., marked $\frac{1}{4}$ Sl bT. A juniper, 24 ins. diam., bears S.46 $\frac{1}{4}$ °W., 282 lks. dist., marked $\frac{1}{4}$ Sl BT. 40.26 The old $\frac{1}{4}$ sec. cor., which is a stone, marked and witnessed as described by the Surveyor General. I reestablish cor. as \(\frac{1}{4} \) sec. cor. of sec. 6 only, as follows;
With original stone, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, marked on brass cap, 1356 1916 from which A juniper, 30 ins marked \$ 56 BT. 30 ins. diam., bears S.59°E., 110 lks. dist., A juniper, 18 ins. diam., bears N.21°E.,177 lks. dist., marked ½ S6 BB. Thence N.1°51'E., on W. bdy. of N. half of sec. 6. The cor. of Ts. 23 and 24 N., Rs. 2 and 3 W., which is 40.33 a 3 in. iron post, properly marked and set alongside of old stone cor., witnessed by 4 bearing trees, as reestablished under current group No. 52. Land, rolling. Soil, malpais formation; 3nd rate. Timber, juniper. Undergrowth, juniper and cactus. Subdivision of T. 23 N., R. 3 W. Sectional Correction Line. From the cor. of secs. 25 and 36, on E. bdy. of Tp., hereinbefore described; West, on sectional correction line, bet. secs. 25 and 36, over valley land, through scattering timber and undergrowth. Fence bears S.20°E. and N.20°W. to NE. cor., 15 lks. dist. .23 6.35 Wash, course SE. Asc. NE. slope.
Summit of ascent. Thence over mesa, malpais formation.
Draw, course NE. Asc. E. slope. 18.30 Thence over rolling land.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 25.00 40.00 ground, for \frac{1}{4} sec. cor., with brass cap, marked

> 1 S25 2 S36 1916

```
of T.
                             Subdivision
Chains
             from which
            A juniper, 18 ins. diam., bears N.32°W., 48 lks. dist., marked ½ S25 BT.
            A juniper, 5 ins. diam., bears S.65% W., 160 Iks. dist., marked $ 336 BT.
          Wire fence bears N.20°E. and S.20°W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with
79.54
            brass cap, marked
                                          T23N R 3W
S26 S25
                                            S35 S36
                                             1916
             from which
            A juniper, 14 ins. diam., bears S.11°E., 50 lks. dist., marked T23N R3W S36 BT.
            A juniper, 18 ins. diam., bears S.10°W., 138 lks. dist.,
               marked T23N R3W S35 BT.
            A juniper, 14 ins.diam., bears N.51°W., 67 lks. dist., marked T23N R3W S26 BT.
A juniper, 16 ins. diam., bears N.26½°E., 214 lks. dist.,
               marked 123N R3W S25 BT.
         Land, rolling.
Soil, malpais formation; 2nd to 4th rate.
            Timber, juniper.
            Undergrowth, juniper and rabbit brush.
         West, on sectional correction line, bet. secs. 26 and 35, over rolling land, through dense timber and undergrowth. Spur, slopes NE., 10 chs.

Desc. gradual NW. slope.
15.00
17.50
40.00
          Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
            ground, for \frac{1}{4} sec. cor., with brass cap, marked
                                             $26
$35
1916
            from which
            A juniper, 6 ins. marked $25 BT.
                            6 ins. diam., bears N.21°W., 78 lks. dist.,
            A juniper, 10 ins. diam., bears S.21°W., 72 lks. dist., marked \( \frac{1}{4} \) S35 bT.
69.60
          Wash, 10 lks. wide, 1 ft. deep, course S.40°E.
                                                                              Asc. on
             gradual SE. slope.
          Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass
80.00
            cap, marked
                                          T23N R 3W
S27 S26
                                            S34 S35
                                             1916
            from which
            A juniper, 8 ins. diam., bears N.43°E., 26 lks. dist.,
            marked T23N R3W S26 bT. A juniper, 36 ins. diam., bears S.40°E., 61 lks. dist.,
               marked T23N R3W S35 BT.
            A juniper, 7 ins. diam., bears S.54°W., 55 lks. dist., marked T23N R3W SS4 BT.
            A juniper, 10 ins. diam., bears N.272°W., 60 lks. dist.,
               marked T23N R3W S27 BT.
         Land, rolling.
Soil, malpais formation; 2nd rate.
```

Timber, juniper.

Undergrowth, juniper and cactus.

	Subdivision of T. 23 N. R. 3 W. 13
Chains	
38. 08	West, on sectional correction line, bet. secs. 27 and 34, over rolling land, through timber and undergrowth. Rocky wash, 15 lks. wide, course SE. Thence over rolling
40.00	S. slope. Set an iron post, 3 ft.long, 1 in. diam., 25 ins. in the
	ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
	\$27 \$34
	1916
	from which A juniper, 4 ins. diam., bears N.2½°E., 59 lks. dist.,
	marked ½ S27 BT. A juniper, 18 ins.diam., bears South, 66 lks. dist.,
63.15	marked \(\frac{1}{4} \) S34 BT. Wash, 10 lks. wide, course SE.
75.60 80.00	Wash, 20 lks. wide, 2 ft. deep, course S. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass
	cap, marked
	T23N R 3W S28 S27
	\$33 S34
	1916 from which
	A juniper, 10 ins. diam., bears N.37°E., 21 lks. dist., marked T23N R3W S27 BT.
	A juniper, 8 ins. diam., bears S.62 to E., 65 lks. dist.
	marked T23N R3W S34 BT. A juniper, 16 ins. diam., bears S.60°W, 8 lks. dist.,
	marked T23N R3W S33 bT. A juniper, 14 ins. diam., bears N.71°W., 36 lks. dist., marked T23N R3W S28 BT.
	Land, rolling.
	Soil, sandstone formation; 2nd rate. Timber, juniper.
	Undergrowth, juniper and cactus.
	West, on sectional correction line, bet. secs. 28 and 33, ascending on gradual SE. slope, through dense timber and undergrowth.
6.00 1 3.95	Spur, slopes S.20°E. Desc. on SW. slope. Rocky wash, 25 lks. wide, 3 ft. deep, course S.10°W.
19.35	Asc. SE. slope. Wash, 20 lks. wide, 2 ft. deep, course S.20°E.
34.20	Leave timber, bearing N. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	ground, for 2 sec. cor., with brass cap, marked
	S28
	\$33 1916
45.00	and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
47.00	Spur, slopes S.10°E. Desc. steep SW. slope, 260 ft. Wash, 100 lks. wide, 3 ft. deep, course S.10°E. Asc. SE. slope.
68.00 80.00	Fence bears N.10°W. and S.10°E.
00 • 00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, with brass cap, marked

Chains T23N|R 3W S29 S28 S32 S33 1916 and raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Land, rolling and broken. Soil, 2nd to 4th rate, Timber, juniper. Undergrowth, juniper and cactus. West, on sectional correction line, bet. secs. 29 and 32, ascending on steep SE. slope, through scattering undergrowth, and timber. 8.00 Thence along broken S. slope. Draw, course S.30°E. Asc. NE. slope.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., with brass cap, marked 24.70 40.00 from which A juniper, 14 ins. marked 4 832 BT. 14 ins. diam., bears S.25°E., 63 lks. dist. A juniper, 5 ins.diam., bears N.14°E., 20 lks.dist., marked \(\frac{1}{4} \) S29 BT.

Spur, slopes N.20°E., 10 chs. \(\frac{1}{2} \) Sec. NW. slope.

Draw, course NE. Asc. steep E. slope.

Spur, slopes N., 25 chs.

Desc. W. slope. 45.00 52.33 66.30 67.85 76.40 Wash, 15 lks. wide, course N.20°W. Thence over rolling mesa. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins in the ground, for cor. of secs. 29, 30, 31 and 32, with brass 80.00 cap, marked T23N R 3W S30 S29 S31 S32 1916 from which A juniper, 20 ins. diam., bears N.86°E., 63 lks. dist., marked T23N R3W S29 BT. A juniper, 20 ins. diam., bears S.84°E., 61 lks. dist., marked T23N R3W S32 BT. A juniper, 10 ins. diam., bears S.62°30'W., 59 lks. dist., marked T23N R3W S31 BT. A juniper, 10 ins. diam., bears N.32°W., 77 lks. dist., marked T23N R3W S30 BT. nd, rolling and broken. Soil, sandstone formation; 3rd rate. Timber, juniper. Undergrowth, juniper and cactus. West, on sectional correction line, bet. secs. 30 and 31, over rolling mesa, through dense timber and jundergrowth.

Desc. gradually, on NW. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

ground, for \frac{1}{4} sec. cor., with brass cap, marked

Fence bears N. and S.

1.24

28.00 40.00

	Subdivision of T. 23 N. R. 3 W. 15
Chains	1 S30
	\$31
	1916 from which
	A juniper, 12 ins. diam., bears N.52°E., 80 lks. dist., marked ½ S30 BT.
	A juniper, 30 ins. diam., bears S.60°W., 75 lks. dist., marked \(\frac{1}{4} \) S31 BT.
54.76	Road bears NW. to Albright's ranch, and SE. to Ash Fork.
60.00 82.09	Desc. rocky W. slape. Intersect E. bdy. of T. 23 N., R. 4 W., 468 lks. N. of the cor. of secs. 25 and 36, described in book R.
* · · · · · · · · · · · · · · · · · · ·	At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 30 and 31, with brass cap, marked
	T23N T23N
	$\begin{array}{c} \text{S25} \\ \hline \text{S31} \end{array}$
	R4W R3W
	1916 from which
	A juniper, 30 ins. diam., bears S.31°E., 33 lks. dist., marked T23N R3W S31 BT.
	A juniper, 4 ins. diam., bears N.36°E., 66 lks. dist., marked T23N R3W S30 BT.
	Land, rolling and broken. Soil, sandstone formation; 3rd rate.
•	Timber, juniper. Undergrowth, juniper, cactus and scrub oak.
	ondors own, Jumpor, Cabous and Solub Can.
	South an gootional quide manidian hat good 75 and 76
0.00	South, on sectional guide meridian, bet. secs. 35 and 36, over rolling land, through dense timber and undergrowth.
2.80 5.60	Fence bears N.10°E. and S.10°W. Wash, 6 lks. wide, 1 ft. deep, course E. Asc. gradually.
18.30 20.50	Ridge bears N.70°W. and S.70°E. Desc. S. slope. Ft. of slope. Asc. NE. slope.
38•40	Summit of ascent. Desc. SE. slope, through scattering timber.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, for 4 sec. cor., with brass cap, marked
	\$35 S36
•	
•	1916 from which
	A juniper, 10 ins. diam., bears N.2°W., 170 lks. dist., marked 2 835 BT.
	A juniper, 12 ins. diam., bears N.53"45'E., 287 lks. dist.,
65.00	marked 4 S36 BT. Ft. of slope.
66.30 84.11	Fence bears N.70°W. and S.70°E. Intersect N. bdy. of T. 22 N., R. 3 W., 169 lks. N.85°02'W.
	of the reestablished cor. of secs. A and 2, hereinbefore described. At point of intersection,
	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 35 and 36, with brass cap, marked
	T23N R 3W
	\$35 \$36 \$ 2
	T22N R 3W

234

```
16
                            Subdivision of T. 23 N. R.
     Cha ins
                 from which
                 A juniper, 6 ins. diam., bears N.13°E., 52 lks. dist., marked T23N R3W S36 BT.
                 No other bearing tree available. Raise a mound of stone.
                 2 ft. base, l^{\frac{1}{2}} ft. high, N. of cor.
                 nd, rolling.
Soil, sandstone and malpais formations; 3rd and 4th rate.
              Land.
                 Timber, juniper.
                 Undergrowth, juniper and cactus.
              North, on sectional guide meridian, bet. secs. 25 and 26,
                 over low, rolling mesa, through scattering timber and
                 undergrowth.
              Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked
     40.00
                                              S26 | S25
                                                1916
                 from which
                A juniper, 1% ins. diam., bears S.5°E., 55 lks. dist., marked \( \frac{1}{4} \) S25 BT.

A juniper, 8 ins. diam., bears N.54\( \frac{1}{6} \) W., 119 lks. dist., marked \( \frac{1}{4} \) S26 BT.
     47.50
63.35
79.20
80.00
              Desc. gradual N. slope.
              Wash, 15 lks. wide, 1 ft. deep, course E. Road bears NE. and SW.
              Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass
                 cap, marked
                                             T23N|R 3W
                                              S23 S24
                                              S26 | S25
                                               1916
                 from which
                A juniper, 18 ins. diam., bears N.562°E., 114 lks. dist.,
                marked T23N R3W S24 BT.
A juniper, 24 ins. diam., bears S.9½°E., 248 lks. dist.,
                   marked T23N R3W S25 BT.
                A juniper, 20 ins. diam., bears S.81°W., 290 lks. dist., marked T23N R3W S26 BT.
                A juniper, 18 ins. diam., bears N.70°W., 303 lks. dist.,
                   marked T23N R3W S23 BT.
                    rolling mesa.
                Soil, malpais and sandstone formation; 3rd and 4th rate,
                Timber, juniper.
                Undergrowth, same.
              East, on a random line, bet. secs. 24 and 25.
             Set temp. \(\frac{1}{4}\) sec. cor.

Intersect \(\text{E}\). bdy. of Tp. 5 lks. S. of the cor. of secs.

24 and 25, hereinbefore described.
    40.00
    80.80
             Thence S.89°58'W., on a true line, bet. secs. 24 and 25,
                over gently rolling mesa, through scattering timber and
                undergrowth.
             Road bears N.10°W. to Pitt's ranch, and S.10°E. to Ash Fork.
    10.30
             Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
    40.80
                ground, for 4 sec. cor., with brass cap, marked
                                                 S24
```

S25 1916

```
Subdivision of T.
 Chains
               from which
               A juniper, 8 ins. diam., bears S.7°W., 19 lks. dist., marked ½ S25 BT.

A juniper, 6 ins. diam., bears N.26°W., 9 lks. dist., marked ½ S24 BT.
 49.80
75.80
80.80
            Wash, course S.10°E.
                                             Asc. gradual SE. slope.
            Summit of slope.
            The cor. of secs. 23, 24, 25 and 26.
               Land, gently rolling mesa.
               Soil, sandstone formation: 2nd rate.
               Timber and undergrowth, juniper.
            North, on sectional guide meridian, bet. secs. 23 and 24,
               ascending on gradual SE. slope, through scattering tim-
               ber and undergrowth.
 37.00
            Spur, slopes E. Desc. NE. slope.
            Set an iron post, 3 ft. long, 1 in. diam., 26 ins.in the
 40.00
               ground, for \frac{1}{4} sec. cor., with brass cap, marked
                                                  S23 S24
                                                   1916
               from which
           A juniper, 16 ins. diam., bears S.81°W., 67 lks. dist., marked $\frac{1}{4}$ S23 BT.

A juniper, 22 ins. diam., bears S.70\frac{1}{4}°E., 186 lks. dist., marked $\frac{1}{4}$ S24 BT.

Wash, 20 lks. wide, 1 ft. deep, course N.80°E.

Spur, slopes E., 20 chs.

Wash 20 lks. wide, 1 ft. doop, course SE.
54.08
68.00
           Wash, 20 lks. wide, 1 ft. deep, course SE.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass
$6.25
80.06
               cap, marked
                                                T23N R 3W
S14 S13
                                                 S23 S24
                                                   1916
              from which
              A juniper, 9 ins. diam., bears N.85°E., 199 lks. dist., marked T23N R3W S13 BT.

A juniper, 9 ins. diam., bears S.74½°E., 173 lks. dist. marked T23N R3W S24 BT.
              A juniper, 12 ins. diam., bears S.49½°W., 149 lks. dist, marked T23N R3W S23 BT.

A juniper, 7 ins. diam., bears N.54°W., 80 lks. dist., marked T23N R3W S14 BT.
           Land, rolling.
              Soil, malpais and sandstone formations; 2nd to 4th rate
              Timber, juniper.
              Undergrowth, juniper and greasewood.
          East, on a random line, bet. secs. 13 and 24. Set temp. \frac{1}{4} sec. cor.
40.00
           Intersect E. bdy. of Tp. 14 lks. N. of the cor. of secs.
              13 and 24, hereinbefore described.
           Thence N.89°54'W., on a true line, bet. secs. 13 and 24,
              over rolling land, through scattering timber and under-
              growth.
```

Desc. 70 ft., on NW. slope.

3	<u> </u>	Subdivision of T. 23 N. R. 3 W.
A PARTY AND THE PROPERTY OF TH	9.85 13.86 17.06 20.86 23.55 25.76 41.86	Ft. of slope. Road bears N.20°E. to Seligman and S.20°W. to Ash Fork. Fence bears NE. and SW. Reservoir, 200 lks. long, 40 lks. wide, 3 ft. deep, containing good water; built in bed of wash, course SE. Wm. Pitt's house bears S., 350 lks. dist., Wm. Pitt's barn bears S., 150 lks. dist. Set an iron post, 3 ft.long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
AND THE PROPERTY OF THE PROPER	75•43 81•86	S13 S24 1916 from which A juniper, 5 ins. diam., bears N.19°E., 92 lks. dist., marked \(\frac{1}{4} \) S13 BT. A juniper, 10 ins. diam., bears S.30°E., 33 lks. dist., marked \(\frac{1}{4} \) S24 BT. Fence bears N. and S. The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, sandstone and malpais formations; 2nd to 4th rate. Timber and undergrowth, juniper.
AND	40.00	North, on sectional guide meridian, bet. secs. 13 and 14, over rolling land, through dense timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked \(\frac{1}{4} \) S14 S13 \(\frac{1}{4} \) from which
AND THE RESIDENCE OF MANAGEMENT AND ADDRESS AND ADDRES	45.00 71.00 80.00	A juniper, 8 ins. diam., bears S.32°W., 93 lks. dist., marked \$\frac{1}{4}\$ S14 BT. A juniper, 10 ins. diam., bears N.88\frac{1}{2}°E., 121 lks. dist. marked \$\frac{1}{4}\$ S13 BT. Asc. gradually, on S. slope, 130 ft. Spur, slopes E. Desc. gradually, on NE. slope. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap, marked \$\frac{T23N}{S11} \frac{R}{S12}\$ \text{S11} \frac{S12}{S14}\$
n - arrage y many ang mangan and a ray y managan and a surject to the surject of		from which A juniper, 5 ins. diam., bears N.4½°E., 70 lks. dist., marked T23N R3W S12 BT. A juniper, 6 ins. diam., bears S.38°E., 35 lks. dist., marked T23N R3W S13 BT. A juniper, 12 ins. diam., bears S.35°45'W., 133 lks. dist., marked T23N R3W S14 BT. A juniper, 10 ins. diam., bears N.77°45'W., 142 lks. dist., marked T23N R3W S11 BT. Land, rolling.
Annual Control of the		Soil, sandstone formation; 3rd rate. Timber, juniper. Undergrowth, juniper and greasewood.

		Subdivision of T. 23 N., R. 3 W. 19
	Chains	
	40.00 82.86	East, on a random line, bet. secs. 12 and 13. Set temp. \(\frac{1}{4}\) sec. cor. Intersect \(\text{E}\). bdy. of Tp., 8 lks. S. of the cor. of secs. 12 and 13, hereinbefore described.
	6.85 19.75 34.96 42.86	Thence S.89°57'W., on a true line, bet. secs. 12 and 13, over rolling land, through dense timber and undergrowth. Asc. steep NE. slope. Summit of ascent. Thence along S. slope. Wash, course SE.; 5 lks. wide, 6 ins. deep. Brush fence bears NW. and SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
	•	\$12 \$13
•		from which A juniper, 10 ins. diam., bears S.12°E., 42 lks. dist., marked ½ S13 BT. A juniper, 10 ins. diam., bears N.1°E., 39 lks. dist., marked ½ S12 BT.
	51 • 35 52 • 86 72 • 86	Spur, slopes S. Desc. gradual W. slope. Ft. of slope. Asc. gradual E. slope. Summit of ascent. Thence on gentle NE. slope. The cor. of secs. 11, 12, 13 and 14.
	•	Land, rolling. Soil, sandstone formation; 2nd and 3rd rate. Timber and undergrowth, juniper.
	·	
	15.00 27.90 40.00	North, on sectional correction line, bet. secs. 11 and 12, over gradual NE. slope, through dense timber and undergrowth. Desc. gradual N. slope. Draw, course N.60°E. Asc. gradual S.slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor; with brass cap, marked
		S11 S12
	47.50 72.40 80.00	from which A juniper, 7 ins. diam., bears S.4½°W., 34 lks. dist., marked ¼ Sll bT. A juniper, 6 ins. diam., bears S.70°E., 25 lks. dist., marked ¼ Sl2 BT. Ridge bears E. and W. Desc. gradual N. slope. Thence on NW. slope. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap, marked
		T23N R 3W S2 S1 S11 S12
		from which A juniper, 14 ins. diam., bears N.114°E., 21°R lks. dist., marked T23N R3W S1 BT. A juniper, 12 ins.diam., bears S.59°E., 53 lks. dist., marked T23N R3W S12 BT. A juniper, 16 ins. diam., bears S.39°45'W., 163 lks. dist., marked T23N R3W S11 BT. A juniper, 14 ins. diam., bears N.64°W., 44 lks.dist., marked T23N R3W S2 BT.
	1 - 11	

O Chains	Subdivision of T. 23 N., R. 3 W.
CHAIN	Land, rolling. Soil, sandstone formation; 3rd rate. Timber, juniper. Undergrowth, same.
1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
40.00 85.05	
13.25 27.55 45.05	Wash, 200 lks. wide, 3 ft. deep, course SE. Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4} \) sec.cor., with brass cap, marked
e e e	1 S 1 S12
	1916 from which A juniper, 8 ins. diam., bears N.22°E., 18 lks. dist., marked \$\frac{1}{4} \text{SI BT.} A juniper, 12 ins. diam., bears S.45\frac{1}{2}\cdot E., 75 lks. dist., marked \$\frac{1}{4} \text{S12 BT.}
52.55 53.45 63.55 70.05	Desc. over rock ledge 20 ft. high. Wash, 150 lks. wide, 3 ft. deep, course N.60°E. Wash, 150 lks. wide, 3 ft. deep, course SE, same wash. Rocky wash, 6 lks. wide, 6 ins. deep, course N.20°E. Asc. NE. slope.
79.05 80.85 85.05	Top of slope. Spur, slopes N. The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, sandstone formation; 3rd rate. Timber and undergrowth, juniper.
4.20 31.05 34.25 36.20 40.00	North, on sectional correction line, bet. secs. 1 and 2, descending gradual Nw. slope, through dense timber and undergrowth. Wash, 20 lks. wide, course NE. Road bears Nw. to Seligman and SE. to Ash Fork. Wash, 100 lks. wide, 2 ft. deep, course SE. Asc. rocky Sw. slope. Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
	S2 S1
	1916 from which
52.60 64.00	A juniper, 6 ins. diam., bears N.36°W., 95 lks. dist., marked ½ S2 BT. A juniper, 10 ins. diam., bears S.14°E., 83 lks. dist., marked ½ S1 BT. Brush fence bears NE. and SW. Top of rocky slope, 150 ft. above 36.20 ch. pt. Thence over rolling mesa.
71.35 77.50 82.43	Brush fence bears NW. and SE. Road bears NW. and SE. Intersect S. Edy. of T. 24 N., R. 3 W. 690 lks. W. of the cor. of secs. 1, 2, 35 and 36. I change this cor. and the 4 sec. cors. on the S. bdrs. of secs. 35 and 36,

all of which are iron posts with brass caps, marked and witnessed as described by the Surveyor General, to cors. pertaining solely to the area N. of the Tp. line, by effacing the marks on brass caps and bearing trees

relating to the area S. of same.

From the \$\frac{1}{4}\$ sec. cor. of sec. 35, a cedar, 12 ins. diam., bears N.57\frac{1}{2}°E., 54 lks. dist., which I mark \$\frac{1}{4}\$ S35 bT.

At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in a mound of stone, for closing cor. of secs. 1 and 2, with brass cap, marked

> T24N R3W S35 S2 S1 T23N R3W 1916

from which

A Pinyon, 6 ins. diam., bears S.354°W., 52 lks. dist., marked T23N R3W S2 BT.

A juniper, 16 ins. diam., bears S.33°E., 52 lks. dist., marked T23N R3W S1 BT.

Land, rolling.
Soil, sandstone formation and malpais; 2nd and 4th rate. Timber, juniper and pinyon. Undergrowth, juniper and rabbit brush.

S.0001 E.on a true line, bet. secs. 34 and 35, over gradual SE. slope, through medium growth of timber

40.00

and underbrush. Set an iron post, 3 ft.long, 1 in. diam., 26 ins.in the ground, for 4 sec. cor., with brass cap, marked

> S34 S35 1916

from which

A juniper, 36 ins. diam., bears N.34°W., 184 lks. dist., marked \(\frac{1}{4} \) S34 BT.

A juniper, 36 ins. diam., bears S.80°E., 141 lks. dist., marked 4 S35 pT.

Ridge, malpais formation, bears E. and W.
Intersect N. bdy. of T. 22 N., R. 3 W., 135 lks. N.85°28'E. of
cor. of secs. 2 and 3, reestablished as hereinbefore described.

At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 34 and 35, with brass cap, marked

C | C | T 23N | R 3W S34 | S35 T22N R 3W

1916

from which A juniper, 14 ins. diam., bears N.27°W., 38 lks. dist., marked T23N R3W S34 BT.

A juniper, 8 ins. diam., bears N.67°E., 157 lks. dist., marked T23N R3W S35 BT.

Land, rolling.

Soil, malpais formation; 2nd and 3rd rate. Timber, juniper.

Undergrowth, juniper and cactus.

) =		Subdivision of T. 23 N., R. 3 W.
	Chains	N.0°01'W., bet. secs. 26 and 27, ascending on SE. slope, through dense timber and under-
	17.50 35.00 40.00	growth. Slope becomes steeper. Thence along E. slope. Set an iron post, 3 ft.long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
		s27 s26
		1916
		from which A juniper, 5 ins. diam., bears N.11°E., 40 lks. dist., marked 4 S26 BT.
		A juniper, 6 ins. diam., bears S.41°W., 124 lks. dist., marked 4 S27 BT.
	47.60 64.03	Desc. on N. slope, 90 ft. Wash, 15 lks. wide, 2 ft. deep, course N.70°E. Asc. 100
	80.00	ft., on SE. slope. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass
		cap, marked T23N R 3W S22 S23
		S27 S26
		1916 from which
		A juniper, 24 ins. diam., bears N.75°E., 103 lks. dist., marked T23N R3W S23 BT. A juniper, 18 ins. diam., bears N.19½°W., 187 lks. dist.,
		marked T23N R3W S22 BT. A juniper, 8 ins. diam., bears S.56°W., 94 lks. dist.,
		marked T23N R3W S27 BT. A juniper, 8 ins. diam., bears S.64°E., 42 lks. dist., marked T23N R3W S26 BT.
		Land, rolling. Soil, sandstone formation; 2nd rate. Timber, juniper. Undergrowth, juniper and cactus.
-		East, on a random line, bet. secs. 23 and 26.
٠	40.00 79.94	Set temp. \(\frac{1}{4}\) sec. cor.
	39•97	Thence S.89°58'W., on a true line, bet. secs. 23 and 26, over rolling land, through timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
		\$23 4 \$26
		1916 from which A juniper, 18 ins. diam., bears N.6°E., 165 lks. dist.,
	79•94	marked ½ S23 BT. A juniper, 40 ins. diam., bears N.6°E., 165 iks. dist., marked ½ S26 BT. The cor. of secs. 22, 23, 26 and 27.
	10.74	Land, rolling. Soil, sandstone formation; 3rd rate.
		Timber, juniper. Undergrowth, juniper and cactum.
	,	

	Subdivision of T. 23 N. R. 3 W. 23
Chains	
10.50 40.00	N.0°01'W., bet. secs. 22 and 23, ever rolling land, through timber and undergrowth. Asc. 65 ft. Spur, slopes N.70°E. Desc. gradually, on NE. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked \$22 \S23
42.52 43.75 48.00 80.00	from which A juniper, 14 ins. diam., bears N.80°E., 51 lks. dist., marked \$\frac{1}{4}\$ \$23 BT. A juniper, 6 ins. diam., bears N.81°W., 75 lks. dist., marked \$\frac{1}{4}\$ \$22 BT. Old road bears N.70°W., and S.70°E. Wash, 25 lks. wide, course S.70°E. Asc. SW. slope. Spur, slopes W., 10 chs. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap, marked
	T23N R 3W S15 S14 S22 S23
	1916 from which A juniper, 12 ins. diam., bears N.48°E., 59 lks. dist., marked T23N R3W S14 BT. A juniper, 8 ins. diam., bears S.21½°E., 72 lks. dist., marked T23N R3W S23 BT. A juniper, 10 ins. diam., bears S.50°W., 151 lks. dist., marked T23N R3W S22 BT. A juniper, 12 ins. diam., bears N.11°W., 83 lks. dist., marked T23N R3W S15 BT.
,	Land, rolling. Soil, sandstone formation; 3rd rate. Timber, juniper. Undergrowth, juniper and cactus.
40.00 79.98	East, on a random line, bet. secs. 14 and 23. Set temp. ½ sec. cor. Intersect N. and S. line 16 lks. S. of the cor. of secs. 13, 14, 23 and 24.
2.13 39.99	Thence S.89°53'W., on a true line, bet. secs. 14 and 23, over rolling land, through dense timber and undergrowth. Wash, 50 lks. wide, course SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked
	\$14 \$23 1916 from which
	A juniper, 24 ins. diam., bears N.27°W., 99 lks. dist.,
79.98	A juniper, 16 ins. diam., bears S.50°E., 39 lks. dist., marked 4 S23 BT. The cor. of secs. 14, 15, 22 and 23.
	Land, rolling. Soil, sandstone formation; 2nd rate. Timber, juniper. Undergrowth, juniper and cactus.

2	4	Subdivision of T. 23 N. R. 3 W.
	Chains	
	6.00 28.50 30.50 40.00	N.O°Ol'W., bet. secs. 14 and 15, over rolling E. slope, through dense timber and undergrowth. Asc. gradual SE. slope. Ridge bears NE. and SW., 100 ft. above ft. of slope. Desc. gradual N. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., with brass cap, marked
		S15 S14
		1916
	47:00 80:00	from which A juniper, 24 ins. diam., bears N.12°W., 85 lks. dist., marked ½ S15 BT. A juniper, 18 ins. diam., bears S.59°E., 88 lks. dist., marked ½ S14 BT. Thence over gently rolling mesa. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap, marked
		T23N R3W S10 S11 S15 S14
		from which A juniper, 20 ins. diam., bears S.53°E., 114 lks. dist., marked T23N R3W S14 BT. A juniper, 10 ins. diam., bears S.82°W., 204 lks. dist., marked T23N R3W S15 BT. A juniper, 20 ins. diam., bears N.57°W., 188 lks. dist., marked T23N R3W S10 BT. A juniper, 36 ins. diam., bears N.8°E., 300 lks. dist., marked T23N R3W S11 BT.
		Land, rolling. Soil, sandstone formation; 2nd rate. Timber, juniper. Undergrowth, juniper and cactus.
	40.00 79.80	N.89°53'E., on a random line, bet. secs. 11 and 14. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line 37 lks. N. of the cor. of secs. 11, 12, 13 and 14.
	12.80 39.90	Thence N.89°51'W., on a true line, bet. secs. 11 and 14, ascending gradually, on E. slope, through medium growth of timber and undergrowth. Top of slope. Thence over gently rolling mesa. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked
		sl1 Sl4 1916 from which A juniper, 9 ins. diam., bears 3.1°W., 23 lks. dist., marked ½ Sl4 BT. A juniper, 8 ins. diam., bears N.36°E., 14 lks. dist., marked ½ Sl1 BT.
	79.80	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, sandstone formation; 2nd rate.
		Timber, juniper. Undergrowth, juniper and cactus.

	Subdivision of T. 23 N. H. 3 W. 25
Chains	
15.30 40.00	N.0°Ol'W., bet. secs. 10 and 11, over rolling E. slope, through medium growth of timber and undergrowth. Wash, 15 lks. wide, 1 ft. deep, course E. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 3 sec. cor., with brass cap, marked
	sio sii
	1916
	from which A juniper, 20 ins. diam., bears N.62½°E., 62 lks. dist., marked ¼ Sll BT. A juniper, 5 ins. diam., bears N.22½°W., 61 lks. dist., marked ¼ Sl0 BT.
50.35	Rocky wash, 15 lks. wide, course N.80°E.
60.50 71.40 80.00	Desc. gradual N. slope. Wash, 15 lks. wide, course E. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, surrounded by a mound of stone, for cor. of secs. 2, 3, 10 and 11, with brass cap, marked
	T23N R 3W S3 S2 S10 S11
	from which A juniper, 12 ins. diam., bears S.40°E., 3 lks. dist., marked T23N R3W S11 BT.
	A juniper. 8 ins. diam., bears S.45°W., 52 lks. dist., marked T23N R3W S10 BT.
	A juniper, 8 ins. diam., bears N.87°W., 36 lks. dist:
	marked T23N R3W S3 BT. A juniper, 16 ins. diam., bears N.8°E., 29 lks. dist., marked T23N R3W S2 BT.
	Land, rolling. Soil, sandstone formation; 2nd rate. Timber, juniper. Undergrowth, juniper and cactus.
	Fact on a mandom line bet
40.00	East, on a random line, bet. secs. 2 and 11. Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect N. and S. line 8 lks. N. of the cor. of secs. 1, 2, 11 and 12.
3.90	Thence N.89°57'W., on a true line, bet. secs. 2 and 11, over rolling land, through medium growth of timber and underbrush. Wash, 15 lks. wide, course NE.
39 • 95	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked
	1 S 2
	* S11 1916
	from which
	A juniper, 18 ins. diam., bears N.4°W., 82 lks. dist., marked ½ S2 BT.
	A juniper, 18 ins diam., bears S.4°W., 85 lks. dist., marked 4 Sl1 BT.
	Wash, 20 lks. wide, course N.70°E. Thence on gradual E. slope.
79.90	The cor. of secs. 2, 3, 10 and 11.

Chains Land, rolling. Soil, sandstone formation; 2nd rate. Timber, juniper. Undergrowth, juniper and cactus. N.0°01'W., bet. secs. 2 and 3, over gradual SE. slope, through dense timber and undergrowth. 15.00 26.80 Desc. gradual N. slope. Wash, 10 lks. wide, course E. Asc. gradual S. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked 40.00 S3 | S2 1916 from which A juniper, 7 ins. diam., bears N.23°E., 32 lks. dist., marked \$ S2 BT. A juniper, 5 ins. diam., bears S.75°W., 29 lks. dist., marked \$\frac{1}{4}\$ S3 BT.

Spur, slopes E. 15 chs. 41.60 52.70 82.34 Thence over level mesa. Intersect S. bdy. of T. 24N., R. 3 W., 673 lks. W. of the cor. of secs. 2, 3, 34 and 35. I change this cor. and the ½ sec. cor. bet. secs. 3 and 34, both of which are iron posts with brass caps, marked and witnessed as described by the Surveyor General, to cors. pertaining solely to the area N. of Tp. line, by effacing the marks on brass caps and on bearing trees relating to the area S. of same. From the $\frac{1}{4}$ sec. cor., a cedar, 24 ins. diam., bears N.72°E., 121 lks. dist., which I mark $\frac{1}{4}$ S34 bT. At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap, marked T24N R 3W S34 S3 S2 T23N R 3W CIC 1916 from which A juniper, 18 ins. diam., bears S.12°W., 87 lks. dist. marked T23N R3W S3 BT. A juniper, 36 ins. diam., bears S.18°E., 210 lks. dist., marked T23^M R3W S2 BT. Land, rolling and level. Soil, limestone and sandstone formations; 3rd rate. Timber, juniper. Undergrowth, juniper and cactus. S.0°01'E., bet. secs. 33 and 34, descending on gradual S. slope, through medium growth of timber and underbrush. Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4}\) sec. cor., 40.00 with brass cap, marked

> \$33|\$34 1916

	Subdivision of T. 23 N. R. 3 W. 27
Chains	
43.50 56.00 59.00 82.27	from which A juniper, 12 ins. diam., bears N.21°W., 38 lks. dist., marked \$\frac{1}{4}\$ \$33 BT. A juniper, 10 ins. diam., bears N.86°E., 65 lks. dist., marked \$\frac{1}{4}\$ \$34 BT. Wash, 10 lks. wide, course E. Thence asc. gradually, on N. slope. Rocky spur, slopes E. Desc. gradual SE. slope. Intersect N. bdy. of T. 22 N., R. 3 W., 208 lks. S.89°48'E. of the reestablished cor. of secs. 3 and 4, hereinbefore described.
	At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 33 and 34, with brass cap, marked
	C C T23N R 3W S33 S34 S 3 T22N R 3W
	T22N Ŕ 3W
	1916 from which A juniper, 12 ins. diam., bears N.31°W., 25 lks. dist., marked T23N R3W S33 BT. A juniper, 7 ins. diam., bears N.16°E., 23 lks. dist., marked T23N R3W S34 BT.
	Land, rolling. Soil, sandstone formation; 3rd rate. Timber, juniper. Undergrowth, juniper and cactus.
29.50 34.00 40.00	N.0°Ol'W., bet. secs. 27 and 28, ascending on S. slope, through dense timber and undergrowth. Ridge bears E. and W., 315 ft. above sec.cor. Desc. gradual N. slope. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, for ½ sec. cor., with brass cap, marked
	G00 G07
*.	S28 S27
	from which A juniper, 8 ins. diam., bears S.37°W., 27 lks. dist., marked 4 S28 BT. A juniper, 10 ins. diam., bears N.7°E., 8 lks. dist., marked 4 S27 BT.
50.00 65.40 67.50 73.00 80.00	Asc. 115 ft., on S. slope. Ridge bears NE. and SW. Desc. steep NW. slope. Ft. of slope. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass
	cap, marked T23N R 3W
	S21 S22 S28 S 27
	1916
	from which A juniper, 24 ins. diam., bears N.30°E., 111 lks. dist.,

2	8	Subdivision of T. 23 N. R. 3 W.
	Chains	marked T23N R3W S22 BT. A juniper, 6 ins. diam., bears S.66°E., 59 lks. dist., marked T23N R3W S27 BT. A juniper, 10 ins. diam., bears S.3°W., 65 lks. dist., marked T23N R3W S28 BT. A juniper, 10 ins. diam., bears N.67°W., 23 lks. dist. marked T23N R3W S21 BT. Land, mountainous and rolling. Soil, sandstone and limestone formations; 3rd rate. Timber, juniper. Undergrowth, greasewood and juniper.
	40.00 80.10	East, on a random line, bet. secs. 22 and 27. Set temp. \(\frac{1}{4}\) sec.cor. Intersect N. and S. line 4 lks. S. of the cor. of secs. 22, 23, 26 and 27.
	18.60 29.80 40.05	Thence S.89°58'W., on a true line, bet. secs. 22 and 27, over rolling land, through dense timber and undergrowth. Asc. 100 ft., on SE. slope. Ridge bears NE. and SW. Desc. 65 ft., on W. slope. Rocky wash, 20 lks. wide, course N.20°E. Asc. E. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., with brass cap, marked
		S22
	59.10 76.10 80.10	S27 1916 from which A juniper, 14 ins. diam., bears N.70°E., 18 lks. dist., marked \(\frac{1}{4}\) S22 BT. A juniper, 5 ins. diam., bears S.35°E., 41 lks. dist., marked \(\frac{1}{4}\) S27 BT. Summit of ascent, 200 ft. above wash. Thence on very gradual E. slope. Desc. gradually, The cor. of secs. 21, 22, 27 and 28.
		Land, rolling and rolling mountainous. Soil, sandstone formation; 3rd rate. Timber, juniper. Undergrowth, juniper and cactus.
	10.00 25.00 40.00	N.0°01'W., bet. secs. 21 and 22, along W. slope, through dense timber and undergrowth. Along top of sour, sloping N. Desc. over end of same. Set an iron post, 3 ft. long, 1 in. diam., 26 ins inthe ground, for 4 sec.cor., with brass cap, marked
		S21 S22
	54.60 76.00 80.00	from which A juniper, 8 ins. diam., bears N.63°W., 17 lks. dist., marked \$\frac{1}{4}\$ S21 BT. A juniper, 8 ins. diam., bears S.70°E., 32 lks. dist., marked \$\frac{1}{4}\$ S22 BT. Rocky wash, 25 lks. wide, course NW., 145 ft. below 25 ch. pt. Thence over rolling W. slope. Timber becomes scattering. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15; 16, 21 and 22, with brass cap, marked

```
29
                          Subdivision of T.
Chains
                                            T23N R 3W
S16 S15
                                              S21 S22
                                               1916
             from which
             A juniper, 24 ins. diam., bears N.63°E., 199 lks. dist., marked T23N R3W S15 BT.
             A juniper, 30 ins. diam., bears S.74°E., 209 lks. dist., marked T23N R3W S22 BT.
             A juniper, 20 ins. diam., bears 5.25\frac{1}{8}°W., 373 lks. dist|.,
                marked T23N R3W S21 BT.
             No other bearing tree available. Raise a mound of stone,
             2 ft. base, l^{\frac{1}{2}} ft. high, W. of cor.
          Land, rolling.
             Soil, sandstone formation; 2nd rate.
             Timber, juniper.
             Undergrowth, juniper and cactus.
          East, on a random line, bet. secs. 15 and 22. Set temp. $\frac{1}{2}$ sec. cor. Intersect N. and S. line at the cor. of secs. 14, 15, 22
40.00
80.18
             and 23.
          Thence West, on a true line, bet. secs. 15 and 22,
          over rolling land, through dense timber and undergrowth Asc. 80 ft., on E. slope.

Spur, slopes S, 10 chs.
16.20
27.70
28.58
          Road bears NW. and SE.
          Wash, 15 lks. wide, course SE. Asc. NE. slope, gradually. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked
40.Ó9
             A juniper, 9 ins. diam., bears S.16°E., 37 lks. dist., marked ½ S22 BT.
          A juniper, 20 ins. diam., bears N.10°E., 4 lks. dist., marked \(\frac{1}{4}\) S15 BT.

Spur, slopes N., 10 chs.; 110 ft. above wash. Desc. 75
54.20
             ft., on NW. slope.
65.20
          Thence desc. on gradual W. slope.
          Leave dense timber, bearing N. and S.60°W. Thence through
70.40
          scattering growth of same. The cor. of secs. 15, 16, 21 and 22.
80.18
             Land, rolling.
             Soil, sandstone formation; 3rd rate.
             Timber, juniper.
             Undergrowth, juniper and cactus.
          N.0°01'W., bet. secs. 15 and 16, ascending on gradual S. slope, through scattering timber
             and undergrowth.
          Wash, 15 lks. wide, course S.30°W. Wash, 15 lks. wide, course E. Same wash, course S.20°W.
   .10
5.60
15.80
38.20
          Enter dense timber, bearing E. and W.
38.45
          Wash, 20 lks. wide, course S.30°W. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
40.00
             ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
```

3		Subdivision of T. 23 N., R. 3 W.
	Cha ins	<u>1</u> 4
		s16 s15
		1916
		from which A juniper, 16 ins. diam., bears S.29°E., 57 lks. dist.,
	·	marked 4 S15 BT. A juniper, 22 ins. diam., bears N.78°W., 47 lks. dist., marked 4 S16 BT.
-	46.73 66.00	Road bears N.30°W., and S.30°E., ascend gradually. Thence over flat mesa.
,	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap, marked
		T23N R 3W S 9 S 10 S 16 S 15
		1916
		from which A juniper, 8 ins. diam., bears N.39°E., 37 lks. dist.,
		marked T23N R3W S10 BT. A juniper, 24 ins. diam., bears S.36°E., 11 lks. dist.
		marked T23N R3W S15 BT. A juniper, 18 ins. diam., bears S.36°W., 18 lks. dist.,
		marked T23N R3W S16 BT. A juniper, 12 ins. diam., bears N.23°W., 41 lks. dist.,
		marked T23N R3W S9 BT.
		Land, rolling and level. Soil, sandstone formation; 2nd rate. Timber, juniper.
	·	Undergrowth, juniper and cactus.
	,	
	40.00 80.20	East, on a random line, bet. secs. 10 and 15. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line 22 lks. N. of the cor. of secs. 10, 11, 14 and 15.
		Thence N.89°51'W., on a true line, bet. secs. 10 and 15, over slightly rolling land, through dense timber and undergrowth.
	40.10	Set an iron post, 3 ft.long, 1 in. diam., 12 ins. in the ground, surrounded by a mound of stone, for $\frac{2}{4}$ sec. cor., with brass cap, marked
		\$10 4
		315 1916
		from which A juniper, 8 ins. diam., bears N.21°W., 8 lks. dist.,
	80.20	marked ½ S10 BT. A juniper, 20 ins. diam., bears S.38°E., 36 lks. dist., marked ½ S15 BT. The cor. of secs. 9, 10, 15 and 16.
-		Land, slightly rolling mesa.
		Soil, sandstone formation; 2nd rate. Timber, juniper. Undergrowth, juniper and cactus.
-		
	24 • 90 34 • 50	N.0°Ol'W., bet. secs. 9 and 10, over low mesa, through dense timber and undergrowth. Asc. rocky S. slope, 70 ft. Ridge bears N.70°E. and S.70°W.
	37.70	Desc. steep N. slope.

		Subdivision of T. 23 N. R. 3 W. 31
Ī	Cha ins	
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4} \) sec. cor., with brass cap, marked
	.*	S 9 S10
		from which A juniper, 6 ins. diam., bears S.44°E., 38 lks. dist., marked ½ S10 BT. A juniper, 10 ins. diam., bears S.72½ W., 57 lks. dist., marked ½ S9 BT.
	44.00 45.00 64.00 72.65 80.00	Asc. on SE. slope. Asc. on SE. slope. Ridge bears N.60°E. and S.60°W. Desc. 50 ft., on rocky N. slope. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap, marked
		T23N R 3W S4 S3 S 9 S10
	***	from which A juniper, 7 ins. diam., bears N.13°E., 13 lks. dist., marked T23N R3W S3 BT. A juniper, 7 ins. diam., bears S.12°E., 13 lks. dist., marked T23N R3W S10 BT. A juniper, 12 ins. diam., bears S.30°W., 17 lks. dist., marked T23N R3W S9 BT. A juniper, 7 ins. diam., bears N.42°W., 29 lks. dist., marked T23N R3W S4 BT.
		Land, rolling. Soil, limestone formation; 3rd rate. Timber, juniper. Undergrowth, juniper, greasewood and cactus.
	40.00 80.10	East, on a random line, bet. secs. 3 and 10. Set temp. \(\frac{1}{4} \) sec. cor. Intersect N. and S. line 18 lks. N. of the cor. of secs. 2, 3, 10 and 11.
	38 • 40 40 • 05	Thence N.89°52'W., on a true line, bet. secs. 3 and 10, over low mesa, through dense timber and undergrowth. Wash, 10 lks. wide, 6 ins. deep, course SE. Asc. E. slope. Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, surrounded by a mound of stone, for ½ sec. cor., with brass cap, marked
	46.10 73.00 80.10	S 3 S10 1916 from which A juniper, 20 ins. diam., bears N.20°E., 3° lks. dist., marked ½ S3 BT. A juniper, 1° ins. diam., bears S.65°W., 44 lks. dist., marked ½ S10 BT. Top of slope. Continue over low mesa. Desc. gradual W. slope. The cor. of secs. 3, 4, 9 and 10.
		Land, rolling. Soil, limestone formation; 2nd and 3rd rate. Timber, juniper. Undergrowth, juniper, greasewood and cactus.

```
32
                                          Subdivision of T. 23 N.
   Chains
                  N.0°01 W., bet. secs. 3 and 4, on rocky NW. slope, through dense timber and undergrowth.
                  Enter small valley.
Wash, 10 lks. wide, course NE.
Asc. gradual SE. slope.
     20.70
     25.05
28.70
     37.00
                   Spur, slopes NE. Thence over rolling E. slope.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
     40.00
                       ground, for 4 sec. cor., with brass cap, marked
                                                                    S4 S3
                                                                    1916
                       from which
                      A juniper, 6 ins. diam., bears S.38°W., 17 lks. dist., marked ½ S4 BT.
                  A juniper, 14 ins. diam., bears N.52°E., 110 lks. dist., marked ½ S3 BT.
Wash, 15 lks. wide, course NE.
     45.00
    64.50
71.40
                  Desc. gradually, on NE. slope. Wash, 8 lks. wide, course E.
                  Intersect S. bdy. of T. 24 N., R. 3 W., 688 lks. W. of the cor. of secs. 3, 4, 33 and 34. I change this cor. and the ½ sec. cor. bet. secs. 33 and 4, both of which are iron posts with brass caps, marked and witnessed ad described by the Surveyor General, to cors. pertaining solely to the area N. of the Tp. line, by effacing
     82.07
                      the marks on brass caps and on bearing trees relating
                      to the area S. of same.
                 From the \( \frac{1}{4} \) sec. cor., a cedar, 28 ins. diam., bears N.75°E., 68 lks. dist., marked \( \frac{1}{4} \) S33 BT.

At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, for closing cor. of secs. 3 and 4, with brass
                      cap, marked
                                                               T24N R 3W
                                                                     S33
                                                                   S4 | S3
                                                               T23N R 3W
                                                                   1916
                      from which
                     A juniper, 12 ins. diam., bears S.4½°E., 49 lks. dist., marked T23N R3W S3 BT.

A juniper, 18 ins. diam., bears S.14°W., 64 lks. dist.,
                          marked T23N R3W S4 BT.
                  Land, rolling.
                      Soil, limestone formation; 3rd rate.
                      Timber, juniper.
                      Undergrowth, juniper, greasewood and cactus.
                  S.0°02'E., on a true line, bet. secs. 32 and 33,
                 over mountainous land, through scattering undergrowth.

Desc. 50 ft., on rocky S. slope.

Wash, 25 lks. wide, 7 ins. deep, course E.

Enter timber, bearing S.70°W. and SE. Asc. on slope
      2.18
      4.80
                      inclining NNW.280 ft.
                 Spur, slopes NE., 20 chs.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins, in the ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
    38.00
    40.00
                                                                 S32 | S33
                                                                   1916
                      from which
```

```
Subdivision of T. 23 N. R.
 Chains
           A juniper, 20 ins. diam., bears S.66°W., 21 lks. dist., marked ½ S32 BT.

A juniper, 12 ins. diam., bears S.62°E., 36 lks. dist., marked ½ S33 BT.

Desc. 125 ft., on SE. slope.
44.50
65.70
70.00
            Rocky wash, course E. Asc. 20 ft., on NE. slope.
           Spur, slopes E., 25 chs. Desc. SE. slope. Rocky wash, 20 lks. wide, course E.
 78.00
               Fence bears NE. and SW. Thence asc. rocky N. slope.
            Intersect N. bdy. of Tp. 22 N., R. 3 W., 283 lks.
 81.72
               s.89°58'E. of the reestablished cor. of secs. 4 and 5,
               hereinbefore described.
            At point of intersection, set an iron post, 3 ft. long,
              2 ins. diam., 14 ins. in the ground, surrounded by a mound of stone, for closing cor. of secs. 32 and 33,
               with brass cap, marked
                                                       C C
                                                  T23N R 3W
S32 S33
                                                       S4
                                                  T22N R 3W
                                                     1916
              from which
              A juniper, 20 ins. diam., bears N.56°W., 102 lks. dist.,
              marked T23N R 3W S32 bT.

A juniper, 6 ins. diam., bears N.2°E., 50 lks. dist., marked T23N R3W S33 BT.
           Land, rolling and rolling mountainous.
              Soil, sandstone formation; 4th rate.
              Timber, juniper.
              Undergrowth, juniper, scrub oak and cactus.
           N.0^{\circ}02^{\dagger}W., bet. secs. 28 and 29,
              along rocky SE. slope, through scattering undergrowth.
           Thence along steep E. slope.
  3.00
                                                         Descend gradually.
           Enter timber, bearing E. and W. Ft. of slope. Thence over bottom of valley.
  4.65
24 • 40
25.15
27.45
37.30
40.00
           Fence bears S.20°E. and N.20°W.
           Wash, 100 lks. wide, 8 ins. deep, course E. Same wash, 50 lks. wide, 6 ins. deep, course S.60°W. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
              ground, for \frac{1}{4} sec. cor., with brass cap, marked
                                                  S29 S28
                                                   1916
              from which
              A juniper, 24 ins. diam., bears N.45°E., 198 lks. dist., marked 4 $28 BT.
          A juniper, 24 ins. diam., bears N.88½°W., 240 lks. dist., marked ½ S29 BT.

Wash, 30 lks. wide, 3 ft. deep, course S.70°E.

Wash, 25 lks. wide, 2 ft. deep, course E.

Set an iron post, 3 ft.long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass
61.70
63.85
80.00
              cap, marked
                                                T23N R 3W
S20 S21
                                                  S29 S28
                                                   1916
              from which
              A juniper, 28 ins. diam., bears N.78½°E., 182 lks. dist., marked T23N R3W S21 BT.
A juniper, 12 ins. diam., bears S.82½°E., 137 lks. dist.,
```

```
Subdivision of T. 23 N. R. 3 W
Chains
                 marked T23N R3W S28 BT.
              A juniper, 14 ins. diam., bears S.82°W., 196 lks. dist., marked T23N R3W S29 bT.
              A juniper, 20 ins. diam., bears N.68°W., 150 lks. dist.,
                 marked T23N R3W S20 BT.
           Land, mountainous and rolling.
Soil, sandstone formation; 2nd rate.
              Timber, juniper.
              Undergrowth, juniper and cactus.
           East, on a random line, bet. secs. 21 and 28.
40.00
           Set temp. \frac{1}{4} sec. cor.
           Intersect N. and S. line 5 lks. S. of the cor. of secs. 21, 22, 27 and 28.
80.12
           Thence S.89°58'W., on a true line, bet. secs. 21 and 28,
              over rolling land, through medium growth of timber and
              underbrush.
           Spur, slopes N.20°W., 15 chs. Desc.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap, marked
19.32
40.06
              A juniper, 8 ins. diam., bears N.2°15'E., 186 lks. dist., marked \( \frac{1}{4} \) S21 BT.
              from which
              A juniper, 6 ins. diam., bears S.36½°E., 52 lks. dist., marked \frac{1}{4} S28 BT.
41.47
           Wash, 50 lks. wide, 1 ft. deep, course NW.; 270 ft. below
              spur.
56.07
           Same wash, course S.
           Same wash, 25 lks. wide, 4 ft. deep, course NW. Same wash, 35 lks. wide, 2 ft. deep, course S. Wash, 30 lks. wide, 3 ft. deep, course SE. The cor. of secs. 20, 21, 28 and 29.
64.77
72.32
78.57
80.12
              Land, rolling and broken.
              Soil, sandstone formation; 3rd rate.
              Timber, juniper.
              Undergrowth, juniper and cactus.
              0°02'W., bet. secs. 20 and 21, over rolling land, through medium growth of timber and
           N.0°02'W.,
              undergrowth.
          Rocky wash, 15 lks. wide, 3\frac{1}{2} ft. deep, course S.30°E. Spur, slopes SE. Thence along E. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., with brass cap, marked
 6.00
20.00
40.00
                                                 S20 S21
                                                  1916
              from which
              A juniper, 14 ins. diam., bears S.80°E., 28 lks. dist., marked $\frac{1}{4}$ S21 BT.

A juniper, 24 ins. diam., bears N.72°W., 104 lks.dist., marked $\frac{1}{4}$ S20 bT.
          wash, 25 lks. wide, course SE. Same wash, course S.30°W. Same wash, course S.20°E.
44.30
50.60
52.70
56.85
           Same wash, course S.30°W.
           Same wash, course SE. Asc. 140 ft., on SW. slope.
58.65
```

```
Subdivision of T.
 Chains
          Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass
 80.00
             cap, marked
                                         T23N | R3W
                                          s17 s16
                                          S29 S28
                                           1916
             from which
            A juniper, 16 ins. diam., bears N.53°W., 40 lks. dist.,
               marked T23N R3W S17 BT.
            A juniper, 24 ins. diam., bears N.47°E., 54 lks. dist.,
               marked T23N R3W S16 BT.
            A juniper.
                          1º ins. diam., bears S.35°W., 42 lks. dist.,
            marked T23N R3W S29 bT.
A juniper, 30 ins. diam., bears S.87°E., 43 lks. dist., marked T23N R3W S28 BT.
          Land, rolling.
            Soil, 2nd and 3rd rate.
            Timber and undergrowth, juniper.
          East, on a random line, bet. secs. 16 and 21.
         Set temp. 2 sec. cor. Intersect N. and S. line 10 lks. S. of the cor. of secs.
40.00
80.04
            15, 16, 21 and 22.
          Thence S.89°56'W., on a true line, bet. secs. 16 and 21,
            over rolling land, through scattering timber and under-
            growth.
   .12
         Wash, 10 lks. wide, course SW.
27.65
         Wash, 15 lks. wide, course S.10°W. Thence on SE. slope. Set an iron post, 3 ft.long, 1 in. diam., 26 ins. in the
40.02
            ground, for 4 sec. cor., with brass cap, marked
                                             S21
                                            1916
            from which
            A juniper, 10 ins. diam., bears S.49°W., 19 lks. dist., marked ½ S21 BT.
            A juniper, 10 ins. diam., bears N.30°W., 17 lks. dist., marked \(\frac{1}{4}\) S16 BT.
56 • 34
         Top of gradual SE. slope.
57.54
65.24
67.84
77.64
80.04
         Spur, slopes S., 10 chs. Desc. rocky SW. slope. Enter dense timber, bearing N. and SE.
         Asc. gradual NE. slope.
         Spur, slopes SE., 20 chs. The cor. of secs. 16, 17, 20 and 21.
            Land, rolling and broken.
            Soil, sandstone formation; 2nd and 3rd rate.
            Timber, juniper.
            Undergrowth, juniper and cactus;
         N.0°02'W., bet. secs. 16 and 17,
            over broken land, through dense timber and undergrowth.
         Asc. rocky S. slope, 100 ft.
Summit of ascent. Thence over level mesa.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
10.00
18.00
40.00
                                         S17 | S16
```

1916

Desc. 95 ft., on N. slope. Ft. of slope. Thence over rolling mesa.

5.13

	Subdivision of T. 23 N., R 3 W. 37
Chains	
17.90	Wash, 60 lks. wide, course NW. Road, in wash, bears NW. and SE.
38.50 40.00	Desc. rocky N. slope. Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, surrounded by a mound of stone, for \$\frac{1}{4}\$ sec. cor., with brass cap, marked
	\$8 S9
	1916
	from which A juniper, 12 ins. diam., bears S.31 W., 35 lks. dist., marked 4 S8 BT. A juniper, 6 ins. diam., bears N.71°E., 20 lks. dist.,
41.30	marked $\frac{1}{4}$ S9 BT. Enter narrow valley, extending N. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
	ground, for cor. of secs. 4, 5, 8 and 9, with brass cap, marked
	T23N R 3W S5 S4 S8 S9
	1916 from which A juniper, 24 ins. diam., bears S.864°E., 296 lks. dist., marked T23N R3W S9 BT.
	A juniper, 8 ins. diam., bears N.83°45'E., 314 lks. dist., marked T23N R3W S4 BT.
	A juniper, 8 ins. diam., bears S.47°W., 183 lks. dist., marked T23N R3W S8 BT.
	A juniper, 8 ins. diam., bears N.75% W., 141 lks. dist., marked T23N R3W S5 BT.
	Land, mountainous and rolling. Soil, limestone formation; 2nd to 4th rate. Timber, juniper. Undergrowth, juniper, greasewood and cactus.
40.00	East, on a random line, bet. secs. 4 and 9. Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line 2 lks. S. of the cor. of secs. 3, 4, 9 and 10.
	Thence S.89°59'W., on a true line, bet. secs. 4 and 9, descending rocky W. slope, through dense timber and undergrowth.
2.70 18.40 23.10	Wash, 8 lks. wide, course N. Spur, slopes N., 5 chs. Desc. W. slope.
34.40	Wash, 10 lks. wide, course N.20°E. Asc. gradually, on NE. slope.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked
	$\frac{3}{4} \frac{\text{S 4}}{\text{S 9}}$
	\$ 9 1916
	from which A juniper, 6 ins. diam., bears N.25°W., 3 lks. dist., marked ½ S4 BT.
	A juniper, 8 ins. diam., bears S.20°E., 39 lks. dist., marked 4 S9 BT.
63.10 77.94 80.16	Ridge bears N. and S. Desc. 75 ft., on W. slope. Enter valley; drains N. The cor. of secs. 4, 5, 8 and 9.

38 Subdivision of T. N. Chains Land, rolling and broken. Soil, limestone formation; 3rd rate. Timber, juniper. Undergrowth, juniper, greasewood and cactus. $N.0^{\circ}02^{\dagger}W.$, bet. secs. 4 and 5, along bottom of valley, through scattering undergrowth. 17.00 18.10 Asc. rocky SW. slope. Enter timber. Top of slope. Thence over mesa.
Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, for 4 sec. cor., with brass cap, marked 20.00 40.00 1916 from which A juniper, 40 ins. diam., bears S.49°E., 40 lks. dist. marked 4 S4 BT.

A juniper, 20 ins. diam., bears S.88°W., 114 lks. dist., marked 4 S5 BT. Raise a mound of stone around post. Wash, 10 lks. wide, course NE. Enter valley, draining E. 42.00 52.00 61.00 Asc. rocky slope. 68.00 Top of slope. Thence over mesa. Intersect S. bdy. of T. 24 N., R. 3 W., 712 lks. W. of the cor. of secs. 4, 5, 32 and 33. I change this cor. and the 4 sec. cor. bet. secs. 5 and 32, both of which are iron posts with brass caps, properly marked and set, witnessed by bearing trees, established under current 82.03 group No. 52, to cors. pertaining solely to the area N. of Tp. line, by effacing the marks on brass caps and on bearing trees relating to the area S. of same. From the 4 sec. cor., a cedar, 8 ins. diam., bears N.772 E., which I mark 4 S32 BT. At point of intersection, set an iron post, 3 ft. long, 2 ins.diam., 24 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap, marked T24N R 3W S32 S5 S4 T23N R 3W 1916 from which A juniper, 20 ins. diam., bears S.66°E., 29 lks. dist., marked T23N R3W S4 BT.

A juniper, 20 ins. diam., bears S.45°W., 14 lks. dist., marked T23N R3W S5 BT. nd, rolling and broken.
Soil, limestone and malpais formations; 2nd to 4th rate. Land Timber, juniper. Undergrowth, juniper and cactus. S.0°03'E., on a true line, bet. secs. 31 and 32, over rolling mesa, through dense timber and undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked 40.00

	Subdivision of T. 23 N., R. 3 W. 39
Chains	4
	S31 S32
2	1916 from which
	A juniper, 18 ins. diam., bears S.43½°E.,72 lks. dist., marked ½ S32 BT.
66 40	A juniper, 14 ins. diam., bears S.65°W., 43 lks. dist., marked \$\frac{1}{4}\$ S31 BT.
66.40 72.77 83.69	Desc. steep S. slope, 45 ft. Ravine, course S.70°W. Thence along steep W. slope. Intersect N. bdy. of T. 22 N., R. 3 W., 217 lks. S.88°34'E. of the reestablished cor. of secs. 5 and 6, hereinbefore described.
	At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 31 and 32, with brass cap, marked
	T23N R 3W
	S 5 5
	T22N R 3W
	from which
	A juniper, 10 ins. diam., bears N.59°E., 92 lks. dist., marked T23N R3W S32 BT. A juniper, 10 ins. diam., bears N.59°W., 77 lks. dist.,
	marked T23N R3W S31 BT.
	Land, rolling and broken. Soil, sandstone formation; 3rd rate. Timber, juniper.
	Undergrowth, juniper and cactus.
8.10	N.0°03'W., bet. secs. 29 and 30, over rolling mesa, through dense timber and undergrowth. Wash, 15 lks. wide, course NW. Thence along rocky W. slope. Wash, 10 lks. wide, course W.
31.00 33.95	Reservoir, 15 chs. long, 5 chs. wide, bears W., 10 chs. dist. Fence bears E. and W. Leave timber.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap, marked $\frac{1}{4}$
,	S30 S29
	from which
	A juniper, 20 ins. diam., bears N.77°E., 86 lks. dist., marked \(\frac{1}{4}\) S29 BT.
	A Mexican currant, 7 ins. diam., bears N.16½°W., 90 lks. dist., marked ½ S30 BT. Desc. over NW. slope.
49.00	Fence bears E. and W. Wash, 30 lks. wide, course NE.
74.00	Spur, slopes SE. Set an iron post, 3 ft.long, 2 ins. diam., 6 ins. in the ground, surrounded by a mound of stone, for cor. of secs. 19, 20, 29 and 30, with brass cap, marked
	T23N R3W S19 S 2 O
	S30 S29
	1916

0	Subdivision of T. 23 N. R. 3 W.
Chain	and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, sandstone and malpais formations; 3rd rate. Timber, juniper. Undergrowth, juniper, scrub oak and cactus.
40.00 80.04	East, on a random line, bet. secs. 20 and 29. Set temp. ½ sec. cor. Intersect N. and S. line 2 lks. N. of the cor. of secs. 20, 21, 28 and 29.
7.20 19.60 35.12 40.02	Thence N.89°59'W., on a true line, bet. secs. 20 and 29, over rolling land, through timber and undergrowth, over small valley. Leave valley. Leave timber. Wash, 10 lks. wide, course S. Asc. rocky E. slope. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
	\$\frac{1}{4} \frac{\text{S20}}{\text{S29}}
•	1916 from which
52.05 62.15 77.02	A juniper, 6 ins. diam., bears N.37½°W., 150 lks. dist., marked ½ S20 BT. A juniper, 18 ins. diam., bears S.28½°E., 81 lks. dist., marked ½ S29 BT. Top of slope.
80.04	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling and broken. Soil, sandstone and limestone formations; 4th rate. Timber, juniper. Undergrowth, cactus and scrub oak.
17.23 19.72 33.70 40.00	Desc. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
,	ground, for 2 sec. cor., with brass cap, marked
	\$19 \$30
	from which
43.95 47.95 62.20 62.70	A juniper, 8 ins. diam., bears S.35°E., 10 lks. dist., marked \$\frac{1}{4}\$ S30 BT. A juniper, 10 ins. diam., bears N.12°W., 37 lks. dist., marked \$\frac{1}{2}\$ S19 BT. Enter small valley, draining S. Wash, course S. Road bears NW. to Albright's ranch and SE. to Ash Fork. Wash, course NW., 10 lks. wide. Asc.
81•86	Intersect E. bdy. of T. 23 N., R. & W., 479 lks. N. of the cor. of secs. 24 and 25, indescribed in Book F.

	Subdivision of T. 23 N. R. 3 W. Al	
Cha ins		
	At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 19 and 30, marked on brass cap,	
	T23N S24 R4W R3W	
	from which A juniper, 10 ins. diam., bears S.83°E., 55 lks. dist., marked T23N R 3W S30 BT. A juniper, 6 ins. diam., bears N.51°E., 33 lks. dist., marked T23N R3W S19 BT.	
	Land, rolling and broken. Soil, Sandstone and limestone formations; 2nd to 4th rate Timber, juniper. Undergrowth, catclaw, scrub oak and cactus.	9 •
	N.0°03'W., bet. secs. 19 and 20, over NE. slope, through underbrush and very scattering timber.	
1.86 16.47 32.80 39.40 40.00	Wash, 10 lks. wide, course SE. Asc. over S. slope. Top of ridge bears E. and W.; 250 ft. above sec. cor. Gulch, 240 lks. wide, course E. Wash, 10 lks. wide, course SE. Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4}\) sec.cor., with brass cap, marked	
	1/4	
	S19 S20	
	1916	
AF. (0	from which A juniper, 12 ins. diam., bears S.35°E., 68 lks. dist., marked \$\frac{1}{4}\$ S20 BT. A juniper, 10 ins. diam., bears S.76°W., 71 lks. dist., marked \$\frac{1}{4}\$ S19 BT. Asc. S. slope 94 ft.	
47.60	Top of slope. Head of draw 300 lks. wide, course SE.	
73.10 77.50	Enter valley from NE.; extends SW.	
80.60	Set an iron post, 3 ft. long, 2 ins: diam., 24 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, with brass cap, marked	
	T23N R 3W 518 S17	
	\$19 \$ 2 0 1916	
	from which A juniper, 28 ins. diam., bears N.11½ W., 262 lks. dist. marked T23N R3W S18 BT.	,
• * * * ±	No other bearing trees available. Raise a mound of stone 2 ft. base, $l\frac{1}{2}$ ft. high, W. of cor.	∍,
	Land, rolling mountainous and rolling. Soil, limestone and sandstone formations; 2nd to 4th rate	∍.
•	Timper, juniper. Undergrowth, catclaw, cactus and scrub oak.	

=	42	Subdivision of T. 23 N. R. 3 W.
	Chains	
	40.00	
	11.92 40.06	Thence S.89°57'W., on a true line, bet. secs. 17 and 20, over roughly rolling and broken land, through scattering timber and undergrowth. Desc. 75 ft. Gulch, 600 lks. wide, course S. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
		\$\frac{1}{4} \frac{\text{S17}}{\text{S20}} \\ \text{1916}
		from which A juniper, 8 ins. diam., bears S.73°W., 20 lks. dist., marked 4 S20 BT. A juniper 12 ins. diam. bears N.24°E. 70 lks. dist.
	41.54 53.93	marked 4 S17 BT. Desc. w slope, 200 ft. Wash, 20 lks. wide, course S. Asc. 50 ft., on steep
	63.05 78.10 80.12	slope. Summit of ascent. Thence over mesa. Desc. W. slope of mesa. The cor. of secs. 17, 18, 19 and 20.
		Land, roughly rolling and broken. Soil, limestone and sandstone formations; 2nd to 4th rate. Timber, juniper. Undergrowth, quinine brush, catclaw and cactus.
general a segmental designation of the second secon	6.00 7.50 40.00	West, on a true line, bet. secs. 18 and 19, over flat valley land, through scattering timber and undergrowth. Asc. gradually. Timber becomes less scattering. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked
		$\frac{1}{4} \frac{\text{S18}}{\text{S19}}$
		1916 from which A juniper, 1º ins. diam., bears S.60°W., 17 lks. dist.,
	44.95 52.90 61.55 64.70 69.84 81.40	marked ½ S19 BT. A juniper, 8 ins. diam., bears N.56°W., 38 lks. dist., marked ½ S18 BT. Road bears NE. and SW. Road bears N. and S. Draw, 200 lks. wide, course S. Draw, 190 lks. wide, course S. Asc. 165 ft., on rocky slope. Intersect E. bdy. of T. 23 N., R. 4 W., 515 lks. N. of the cor. of secs. 13 and 24, described in Book F.
		At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. din the ground, for closing cor. of secs. 18 and 19, with brass cap, marked
		T23N S13 T23N S18 CC S19 R3W
***************************************		from which

```
Subdivision of T. 23 N.
             A juniper, 12 ins. diam., bears S.47°E., 48 lks. dist.
               marked T23N R3W S19 BT.
             A juniper, 12 ins. diam., bears N.49°E., 65 lks. dist., marked T23N R3W S18 BT.
          Land, rolling, broken and flat.
Soil, gravelly loam; 2nd and 3rd rate.
             Timber, juniper.
             Undergrowth, cactus and Mexican currant.
          N.0^{\circ}03 W., bet. secs. 17 and 18,
          over open valley land, through scattering undergrowth. Asc. gradually, on rocky SW. slope. Thence along W. slope.
19.00
20.25
          Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, surrounded by a mound of stone, for \frac{1}{4} sec. cor.
40.0Ó
             with brass cap, marked
                                              S18 S17
                                                1916
             from which
             A juniper, 8 ins.diam., bears N.63°W., 60 lks. dist., marked 4 S18 BT.
             A juniper, 6 ins. diam., bears N.67°E., 75 lks. dist., marked 4 S17 BT.
          Wash, 6 lks. wide, course NW.
Draw, 290 lks. wide, course W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass
44.42
61.50
80.Ó0
             cap, marked
                                             T23N R 3W
S7 S8
                                              S18 S17
                                                1916
             from which
             A juniper, 14 ins. diam., bears S.87°E., 30 lks. dist., marked T23N R3W S17 BT.
             A juniper, 20 ins. diam., bears N.44°E., 30 lks. dist.,
             marked T23N R3W S8 BT.

A juniper, 20 ins. diam., bears S.73°W., 100 lks. dist.
marked T23N R3W S18 BT.

A juniper, 18 ins. diam., bears N.34°W., 235 lks. dist.
                marked T23N R3W S7 BT.
          Land, rolling.
             Soil, gravelly loam; 2nd to 4th rate.
             Timber, juniper.
             Undergrowth, cactus and catclaw.
          East, on a random line, bet. secs. 8 and 17.
          Set temp. \(\frac{1}{4}\) sec. cor.
Intersect N. and S. line 5 lks. N. of the cor.of secs.
40.00
80.16
             8, 9, 16 and 17.
          Thence N.89°58'W., on a true line, bet. secs. 8 and 17,
             over rocky slope, through scattering timber and under-
             growth.
          Wash, 10 lks. wide, course NW. Thence over rolling hills. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., with brass cap, marked
19.12
40.08
```

17	Subdivision of T. 23 N., R. 3 W.
Chains	
80.16	S 8 14 S17 1916 from which A juniper, 16 ins. diam., bears N.66°E., 12 lks. dist., marked 4 S8 BT. A juniper, 16 ins. diam., bears S.77°W., 14 lks. dist., marked 4 S17 BT. The cor: of secs. 7, 8, 17 and 18. Land, rolling. Soil, malpais and limestone formation; 2nd to 4th rate. Timber, juniper. Undergrowth, Mexican currant and cactus.
14.02 16.00 16.50 31.20 40.00	West, on a true line, bet. secs. 7 and 18, descending through scattering undergrowth, and very scattering timber. Road bears NE. and SW. Small valley, 100 ft. below sec. cor. Road bears N. and S. Enter timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., with brass cap, marked
	S 7
57•75 63•54 69•44 77•84 81•33	S18 1916 from which A juniper, 24 ins. diam., bears N.19°W., 86 lks. dist., marked \$\frac{1}{4}\$ S7 BT. A juniper, 24 ins. diam., bears S.63°E.,,67 lks. dist., marked \$\frac{1}{4}\$ S18 BT. Wash, 4 lks. wide, course NE. Road bears NE. and SW. Asc. 150 ft., on gradual slope. Summit of ascent. Intersect E. bdy. of T. 23 N., R. 4 W., 523 lks. N. of the cor. of secs. 12 and 13, described in Book F.
	At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 7 and 18, with brass cap, marked
	T23N S12 R4W R3W 1916 from which A juniper, 10 ins. diam., bears S. 21° E., 29 lks. dist., marked T23N R 3W S18 BT. A juniper, 16 ins. diam., bears N. 66° E., 42 lks. dist., marked T23N R3W S7 BT. Land, rolling and broken. Soil, limestone and malpais formation; 2nd to 4th rate. Timber, juniper. Undergrowth, catclaw, cactus and quinine brush.
6.00	N.0°03'W., bet. secs. 7 and 8, along W. slope, through scattering undergrowth. Draw, 105 lks. wide, course W. Desc. NE. slope.

	Subdivision of T. 23 N. R. 3 W. 45
Chains	
29.25 39.94 40.00	Enter valley. Road bears NE. and SW. Set an iron post, 3 ft.long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., marked on brass cap, \(\frac{1}{4} \)
•	\$7 S8
	1916
44.60 60.00	dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth, 3½ ft. base, ½ ft. high, W. of cor. Enter timber. Asc. 110 ft., on SE. slope.
76.00 80.00	Top of slope. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5, 6, 7 and 8, with brass cap, marked
	T23N R 3W S6 S5 S7 S8
	from which
	A juniper, 10 ins. diam., bears S.18°E., 52 lks. dist., marked T23N R3W S8 BT. A juniper, 9 ins. diam., bears N.35°E., 26 lks. dist.,
	marked T23N R3W S5 BT. A juniper, 10 ins. diam., bears N.19°W., 47 lks. dist., marked T23N R3W S6 BT.
	A juniper, 14 ins. diam., bears S.87°W., 16 lks. dist., marked T23N R3W S7 BT.
	Land, rolling. Soil, malpais formation; gravelly loam; 2nd to 4th rate. Timber, juniper. Undergrowth, rabbit brush, cactus and quinine brush.
40.00 79.94	East, on a random line, bet. secs. 5 and 8. Set temp. \(\frac{1}{4} \) sec. cor. Intersect N. and S. line 2 lks. S. of the cor. of secs. 4, 5, 8 and 9.
	Thence S.89°59'W., on a true line, bet. secs. 5 and 8, over rolling land, through scattering timber and undergrowth.
1.14 25.00 39.97	Road bears N. and S. Wash, 200 lks. wide, course N. Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4} \) sec. cor. with brass cap, marked
	$\frac{1}{4} \frac{s}{s} \frac{5}{s}$
	1916
	from which A juniper, 8 ins. diam., bears S.20°E., 67 lks. dist., marked \(\frac{1}{4} \) S8 BT.
47.00	A juniper, 6 ins. diam., bears N.27°E., 61 lks. dist., marked ½ S5 BT. Leave timber.
54.75 61.65	Wash, course N. Small valley draining NE. Enter timber, and asc. 150 ft., over NE. slope.
79 • 94	The cor. of secs. 5, 6, 7 and 8.
ţ	Land, rolling and broken. Soil, gravelly loam; 3rd rate. Timber, juniper. Undergrowth, cactus, catclaw and Mexican current.

	Subdivision of T. 23 N. R. 3 W.							
Chain								
17.40	West, on a true line, bet. secs. 6 and 7, over rocky mesa, through dense timber and undergrowth. Leave dense timber. Thence through scattering growth of							
40.00	same. Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, surrounded by a mound of stone, for \(\frac{1}{4}\) sec. cor., with brass cap, marked							
	S 6 S 7 1916							
	from which A juniper, 5 ins. diam., bears N.37½°W., 236 lks. dis marked ½ 86 BT.							
81.42	A juniper, 4 ins. diam., bears S.54% W., 65 lks. dist., marked \$ 87 BT. Intersect E. bdy. of T. 23 N., R. 4 W., 526 lks. N. of the cor. of secs. 1 and 12, described in Book F.							
	At the point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap, marked							
	T23N S 1 S6 CC R4W R3W							
	1916 and raise a mound of stone, 2 ft. base, $l_{2}^{\frac{1}{2}}$ ft. high, E. of cor.							
	Land, rolling mesa. Soil, rocky loam; malpais formation; 2nd to 4th rate. Timber, juniper. Undergrowth, rabbit brush.							
35.00 38.00 40.00	N.0°03'W., bet. secs. 5 and 6, over rocky mesa, through dense timber and undergrowth. Leave timber. Enter scattering timber. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap, marked							
	s6 s ₅							
	1916 from which A juniper, 12 ins. diam., bears S.89½°E., 77 lks. dist., marked ½ S5 BT. A juniper, 4 ins. diam., bears S.69½°W., 64 lks. dist., marked ½ S6 BT.							
47.00 49.75 52.80 82.03	Desc. into draw, 900 lks. wide, 35 ft. deep, course NE. Wash, in bottom of draw, 10 lks. wide, course NE. Enter dense timber.							
	Intersect S. bdy. of T. 24 N., R. 3 W., 695 lks. W. of the cor. of secs. 5, 6, 31 and 32. I change this cor. and the \(\frac{1}{4}\) sec. cor. bet. secs. 6 and 31, which are both iron posts, Properly marked, set and witnessed, established under current group No. 52, to cors. pertaining solely to the area N. of the Tp. line, by effacing the marks on brass caps and on bearing trees relating to the area S. of same.							
	At point of intersection, set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor.							

Chains

Subdivision of T.

of secs. 5 and 6, marked on brass cap

T24N R 3W S31 CC \$6 S5 T23N R 3W

1916

from which

A juniper, 18 ins. diam., bears S.70°E., 71 lks. dist., marked T23N R3W S5 BT.

No other bearing tree available. Raise a mound of stone,

2 ft. base, $l^{\frac{1}{2}}$ ft. high, S. of cor.

Land, rolling.

Soil, 2nd and 3rd rate.

Timber, juniper.
Undergrowth, cactus and rabbit brush.

Boundaries of T. 23 N., R. 3 W. Latitudes, Departures, and Closing Errors.

Line designa	ed True Course	Dist.	Latitudes		Departures	
			N.	S.	Ε.	W.
		chs.	chs.	chs,	chs.	chs.
South Boundar	N.87°21 W. N.85°35 W. N.85°02 W. S.87°28 W. S.89°48 W. N.89°58 W. N.89°58 W. S.85°45 W. N.88°37 W. N.88°37 W. S.87°14 W.	40.22 40.20 42.96 40.31 40.34 40.44 40.58 40.02 39.75 40.05 39.99	1.86 3.10 3.72 .14 .46 .02 1.00 .97	1.78 .14 2.97		40.18 40.08 42.80 40.27 40.34 40.44 40.58 40.08 39.91 39.74 40.04 39.94
West Boundary	North ,	487.12	4º7.12			711
North Bounda	y East	488.65			488.65	
East Boundary	S.1°51'W. S.0°39'W. S.1°34'W. S.1°28'W. S.0°49'W. S.0°31'W. S.0°24'E. S.3°04'W. S.2°E S.1°11'E.	40.33 40.26 40.53 40.15 40.24 40.25 40.32 40.08 40.29 40.35 89.10		40.31 40.26 40.52 40.14 40.24 40.25 40.30 40.08 40.23 40.33	.28 1.41 1.85	1.30 .45 1.11 1.03 .57 .36 1.44
Convergency					•52	
Totals			498.37	498.56	492.71	492.82
				498.37	492.71	492.71
Error in lati		3		.19		
4.45	Error in departure .11					

This township is rolling, generally rocky, sparsely timbered with scrub cedar, with many open draws comparatively free from rock.

It is fair grazing land, fairly well supplied with water, stored in "Tanks", both natural and artificial, and supports considerable numbers of horses, cattle and sheep.

Partridge creek runs through the eastern portion of the township and this creek and its tributaries supply all the visible water.

The soil in the draws and valleys is a sandy loam and would be productive if irrigated.

Wm. Pitts' ranch is situated in Sec. 24, supplied with good buildings, reservoir, pumping plant and substantial improvements.

Book "G"

49

Group 62----Arizona.

4-680

Township 23 North, Range 3 West.

DATE DIAGRAM.

							<u> </u>

		,					
	······································	Ø	d ,	· · · · · · · · · · · · · · · · · · ·	%		25-16
	6	5 0	4 5	3 - 13	5 25	1 -	208
	5-11-16	5-10-16	5-5-16	5-2-16	4-28-16	4-25-16	4
	<i>b</i>	· · · · · · · · · · · · · · · · · · ·	<i>\delta</i>	<i>"</i>	<i>Q</i>		H25-1
	7 \$	8 4	9 %	10 %	11 %	12	707-7
	5-10-16	5-9-16	5-4-16	5-2-16	4-28-16	4-24-16	30 4
	18 0	17 ¥	16 🐇	15 %	14 %	13	10821 EVEL
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	· · · · · · · · · · · · · · · · · · ·		A.	4		4.20 27.70
	5-9-16	5-9-16	5-4-16	5-1-16	4-28-16	4-24-16	200
	19 %	50 <i>†</i>	21 /	22 %	23 %	24	220
	5-8-16	5-8-16	5-3-16	5-1-16	4-27-16	4-22-16	4-2
		h	\ <u>a</u>	d	d		9/-1
	30 %	3 9 h	28	27	26 77	25 -	9 2
	5-6-16	5-6-16	4-29-16	4-29-16	4-27-16	4-27-16	4
	h	d,	9	þ	Ø		21-16
	31	32 5	33 0	34	35	3 6	#61
	4-12-16	4-18-16	4-18-16	4-18-16	4-18-16	4-18-16	4
<u></u>			RESULT	PYEYED			
-							62764

Surveys and resurveys executed on dates shown in red on above diagram, by Fred Mensch; U. S. Surveyor.

50

CERTIFICATE OF UNITED STATES SURVEYOR.

I,, U. S. Surveyor, hereby certify upon honor that, in pursuance
of special instructions received from the U.S. Surveyor General for Group 62, Arizona,
bearing date of the5th day of0ctober, 191 5, I have well, faithfully, and truly
in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, surveyed all those parts or portions of the subdivision lin
of Township 23 North, Range 3 West,
and RESURVEYED all those parts or portions of the
North boundary of Township 22 North, Range 3 West,
and the West boundary of Township 23 North, Range 2 West,
vai boundar and the Gila and Salt
River Base and Meridian, in the State of
tions, and the special written instructions of the U. S. Surveyor General for Group 62. Arizona
and in the specific manner described in the field notes, and that the foregoing are the original field notes of
such survey and resurvey [Seed Mencel U. S. Surveyor.
APPROVAL.
OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
Phoenix, Arizona October 16, 191 8
The foregoing field notes of the survey of the subdivision lines of
Township 23 North, Range 3 West,
and the RESURVEY of
the North boundary of Township 22 North, Range 3 West,
and the West boundary of Township 23 North, Range 2 West,
of the Gila and Salt River Base and Meridian, in the State of Arizona,
executed by Fred Mensch, U. S. Surveyor,
under his special instructions for Group 62, Arizona, dated Oct. 5, 1915, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved. and resurveys U. S. Surveyor General.
I certify that the foregoing transcript of the field notes of the above-described surveys in
, has been correctly copied from the original notes on file in this office.