# FIELD NOTES

**BOOK** 3350

OF THE SURVEY OF THE -- West and North boundaries, and Subdivision lines of TOWNSHIP 13 SOUTH, RANGE 6 WEST, Of the Gila and Salt River Base and Meridian, In the State of \_\_\_\_\_Arizona. EXECUTED BY W. H. Thorn, U. S. Surveyor, and Loyd E. Sechrist, U.S. Transitman, In the capacity of U.S. Surveyors
In the capacity of U.S. Surveyor , under Special Instructions dated July 12, , 1917, issued by the United States Surveyor General to govern surveys included in Group No.84. Arizona, , which were approved by the Commissioner of the General Land Office, July 25. , 1917, and Assignment Instructions dated Dec. 20. , 1917.

Survey commenced \_\_\_\_\_April 18, \_\_\_\_\_, 1918

Survey completed \_\_\_\_\_, 1918.

BOOK 3350

*3350* Book "H"

Group 84 - - Arizona.
Township 13 South, Range 6 West.

# INDEX DIAGRAM.

				1	t:		
	700.70. 6	.jp <b>.7</b>	7	, Runge	β	9	
	6 38	5	1 4 2		0 2	<b>5</b> 1	
	38	. 37	<b>31</b>	25	19	13	·
	7 3'	7 8 30		5 <sub>10</sub> :	•	3 <sub>12</sub> _	
	36	56	30	24	18	12	
4-	18 3	5 17 <b>2</b> 9	16 2	3 15	.8 14	2 13	
	35	35	7.135.	3 15 R.G.W.	17	12	
4-	19 3	20	8 21 2	2 <sub>22</sub> 1	5 <sub>23</sub> :	1 24 -	
. <b></b>	34	34	28	22	16	11	
3-	30 <b>3</b>	3 29	27 <sub>28</sub> 2	.1 <sub>27</sub>	15 <sub>26</sub> :	.0 <sub>25</sub> _	
	33	32	27	21	15	10	
×	81	2 82 2	5 88 8	0 84 1	4 <sub>35</sub> 9	36 -	
	* * * * * * * * * * * * * * * * * * * *						
,	· ·		• •				

Lines surveyed under this group.

---- Unsurveyed.

3350 Book "E"

Group 84---- Arizona.

Township 13 South, Range 6 West.

BOOK 3350

#### DATE DIAGRAM.

	4-23-18	4-23-18	4-23,-18	4-22-18	4-22-18	4-22-18
4-20-18	6 <b>3</b> <b>5-9-1</b> 8	5 5-9-18	4-30-18	3 3 4-29-18	2 25-18 4-25-18	<b>1</b> 4-25-18
18	7 0 0 0 1 4-30-18	8 <b>91</b> <b>4-3</b> 0~18	9 83 -4-30-18	10 -52-78 4-29-18	11 4-25-18	12 4-24-18
4.20.4	28 K 18 K 4-29-18	17 <b>87</b> 17 <b>87</b> 4-29-18	16 <b>27-18</b>	15 15	14 _4=24=18_	<b>13</b> 4-24-18
A. 20-18	81-62-4 4-29-18	20 27 4 - 29 - 18	21 23 _4=27=18_	22-18	2 <b>3</b> 2-2-18	<b>24</b> 4-20-18
4.90.10	30 1/2, 4 4-27-18	29 29 4-27-18	28 = 3 - 3 - 4=27=18	27	56 97-77-74	<b>25</b> 4-20-18
0 V V	<b>31</b> 81-81-4	32 4-27-18	<b>3</b> 33 <b>2</b>		35 5 81-02-4	36

Lines surveyed on dates shown in black on above diagram by William H. Thorn. U.S. Surveyor.

Lines surveyed on dates shown in red on above diagram by Loyd E. Sechrist, U.S. Transitman.

Survey of West bdy of Township 14 South Renge b West Chains Survey executed by Wm. H. Thorn, U. S. Surveyor and Loyd E. Sechrist, U. S. Transitman, on dates shown on page 1 hereof, using respectively Young and Sons light mountain transit No. 8592 and Buff solar transit No. 10125, each instrument being equipped with Smith solar attachment. For description of instruments, certificate of approval, and field tests of adjustments, see Book "C". From the cor. of Ts. 13 and 14 S., Rs. 6 and 7 W., described in Book "P" North bet. secs. 31 and 36. Over rolling land, through dense undergrowth. Pesc. 80 ft. Thence over level land. 9.90 Wash, course S 5°W.

Set an iron post, 3 ft. long, l in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap 24.90 40.00 **s**36 s31 And raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, marked on 80.00 R7W **n**6w S25 S30 3361**33**1 1918 From which A mesquite, 5 ins. diam., brs. S.48°W.,
68 lks. dist., marked T13S R7W S36 BT.
er trees within limits. Dig pits, 18 X 18 X 12 ins., No other trees within limits. in each sec.,  $5\frac{1}{2}$  ft. dist. Land, level and rolling. Soil, sandy and rocky adobe, 1st and 4th rate. No timber. Undergrowth, greasewood, mesquite, palo verde. Good growth of grass. North bet. secs. 25 and 30. Over level land, through dense undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap 40.00 From which A mesquite, 5 ins. diam., brs. N.87°W.,
131 lks. dist., marked 1825 BT.
No other trees within limits. Dig pits, 18 X 18 X 12 ins., No other trees within limits. Dig pits, 10 % 10 % 12 ins.

N. and S. of post, 3 ft. dist.

Wood road, brs. E. and W.

Wood road, brs. NE. and SW.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, marked on 45.00 66.80 80.00 24 ins. in the

76.50

Wash, 12 lks. wide, course S.70°E.

Survey of the West Boundary of T. 13 S., R. 6 W. Mains T135 R7W|R6W S24|S19 Dig pits, 18 X 18 X 12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist Land, level. Soil, sandy adobe, 1st rate. No timber. Undergrowth, mesquite and greasewood. Good growth of grass. North bet. secs. 19 and 24. Over level land, through dense undergrowth. Wood road, brs. E. and W. 6.20 Wash, 90 lks. wide, course S.70°W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 9.50 s24 s19 1918 From which A palo verde, 18 ins. diam., brs. S.40°E., 62 lks. dist., marked \$\frac{1}{2}\$S19 BT.

A mesquite, 8 ins. diam., brs. N.27°W., 214 lks. dist., marked \$\frac{1}{4}\$S24 BT.

Wash, 8 lks. wide, course SE..

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in th ground, for cor. of secs. 13, 18, 19 and 24, marked on 79.60 86.00 24 ins. in the brass cap **T13S** From which A mesquite, 7 ins. diam., brs.  $5.17\frac{1}{2}$ °E. 56 lks. dist., marked T13S R6W S19 BT. A mesquite, 6 ins. diam., brs.  $9.70^{\frac{1}{2}}$  W., 60 lks. dist., marked T13S R7W S24 BT.
No other trees within limits. Raise a mound of stone, 3
ft. base, 2 ft. high, W.of cor. Land, level. Soil, gravelly, 2nd rate. No timber. Undergrowth, mesquite, palo verde and greasewood. North bet. secs. 13 and 18.

Over level land, through dense undergrowth.

Wood road, brs. E. and W.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 9.80 40.00 \$13**|**\$18 Dig pits, 18 X 18 X 12 ins., N. andS. of post, 3 ft. dist. Wash, 12 lks. wide, course E. 59.00

Surveyyof the West Boundary of T. 13 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, marked on 24 ins. in the brass aap T13S R7W R6W And raise a mound of stone, 2 ft. base, 1 ft. high. W of cor. Land, level. Soil, gravelly and rocky, 2nd rate. No timber. Undergrowth, mesquite, palo verde, greasewood and rosin brush. North bet. secs. 7 and 12. Over gently rolling land, through dense undergrowth. Wash, 10 lks. wide, course E. Wash, 8 lks. wide, course S.75°E. Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the 21.99 27.00 40.00 ground, in a mound of stone, 2 ft. base, 1 ft. high. for  $\frac{1}{4}$  sec. cor., marked on brass cap S12|S 7 1918 From which A palo verde, 5 ins. diam., brs. N.80°E.,

138 lks. dist., marked \$57 BT.

A mesquite, 8 ins. diam., brs. N.85°W.,

103 lks. dist., marked \$12 BT.

Ravine, 75 lks. wide, 10 ft. deep, course S.70°E.

Wash, 8 lks. wide, course SE. Asc. very gradual
Desc. slightly 42.30 49.30 70.00 Asc. very gradually. Desc. slightly. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, marked on brass cap T138 R7W R6W S 1 | S6 S12 | S 7 1918 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. Land, gently rolling. Soil, gravelly and rocky, 3rd rate. No timber. Undergrowth, palo verde, ironwood, mesquite, greasewood, rosin brush and cactus. North bet. secs. 1 and 6.

Over rolling land, through dense undergrowth. Wash, 30 lks. wide, course W. Same wash, 30 lks. wide, course SE. Same wash, 25 lks. wide, course SW. 10.10 12.40 14.80 Asc. 105 ft. 34.11 40.00 Desc. 95 ft.

Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in a mound of stone, 4 ft. base, 3 ft. high, for f sec. cor., marked on brass cap

Survey of the West Boundary of T. 13 S., R. 6 W.

chains. ร 1 รีธ 6 And raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W of cor. Wash, 30 lks. wide, course W. Asc. 35 ft.

Desc. 30 ft.

Wash, 30 lks. wide, course SW. Asc. 25 ft.

Dim road, brs. NE. and SW. Desc.

Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base, 2½ ft. high, for cor. of Ts. 12 and 13 S., Rs. 6 and 7 W., marked on 63.78 67.52 74.01 77.52 brass cap T125 R7W R6W 836 831 1186 T13S 1918 And raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Land, rolling. Soil, gravelly and rocky, 3rd and 4th rates. No timber. Undergrowth, palo verde, ironwood, greasewood, rosin brush and cactus. Survey of the North Boundary of T. 13 S., R. 6 W. From the cor. of Ts. 12 and 13 S., Rs. 5 and 6 W., described in Book "G".
West on a random line, along the N. bdy. of T. 13 S., R. 6 W., setting temp. 1 sec. and sec. cors. at intervals of 40.00 chs.; and at 478.55 chs., intersect the cor. of Ts. 12 and 13 S., Rs. 6 and 7 W., hereinbefore described. Thence East on a true line, bet. secs. 6 and 31. Over rolling land, through dense undergrowth. 1.30 5.20 7.90 38.55 Wash, 20 lks. wide, 2 ft. deep, course SW.
Road, brs. NE. and SW.
Wash, 50 lks. wide, 10 ft. deep, course SW. Asc. 65 ft.
Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in a mound of stone, for \frac{1}{4} sec. cor., marked on brass cap 1 S 5 6 1918 And raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Desc. 30 ft. Asc. 40 ft. 40.15 45.10 Desc: 45 ft. Enter wash, course S.60°W., comes from E.

Leave wash, course S., from NE. Asc. 25 ft.

Set an iron post, 3 ft. long, 2 ins. diam. on bed rock, a mound of stone, for cor. of secs. 5, 6, 31 and 32, marked on brass can 56.85 68.45 78.55

marked on brass cap

BOOK 3350

```
chains.
                                       T128 R6W
S31 S32
S 6 S 5
                                            T135
                                            1918
              And raise a mound of stone, 2 ft. base, 12 ft. high. W
              of cor.
          Land, rolling.
          Soil, rocky, 4th rate.
          No timber.
          Undergrowth, greasewood, palo verde and cactus.
          East on a true line, bet. secs. 5 and 32.
          Over mountainous land, through dense undergrowth.
          Desc. gradually.
 8.70
          Wash, 30 lks. wide, 2 ft. deep, course SE. Asc. 45 ft. Thence over rolling land.
19.45
25.55
37.45
         Asc. 100 ft., over mountainous land.
Spur, slopes S. Desc. 70 ft.
Set an iron post, 3 ft. long, l in. diam., in a mound of
40.00
              stone, for \frac{1}{4} sec. cor., marked on brass cap
                                        1 S32
2 S 5
1918
              And raise a mound of stone, 3 ft. base, 2 ft. high, N.
              of cor.
          Wash, 10 lks. wide, 3 ft. deep, course S. Spur, slopes S.10°W. Desc. 245 ft.
43.45
52.95
61.20
                                                                     Asc. 185 ft.
          Foot of descent; thence over level land.
         Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 4, 5, 32 and 33, marked on
80.00
              brass cap
                                       T12S R6W
S3.2 S33
S 5 S 4
T13S
1918
              Dig pits, 18 X 18 X 12 ins., in each sec., 5\frac{1}{2} ft. dist
         Land, level, rolling and mountainous. Soil, rocky, 4th rate.
          No timber.
          Undergrowth, mesquite, cactus and palo verde.
          East on a true line, bet. secs. 4 and 33.
          Over rolling land, through dense undergrowth.
         Desc. 95 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
16.95
40.00
              ground, for 1 sec. cor., marked on brass cap
                                        333
S 4
1918
              Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
         dist.
Asc. 15 ft.
57.20
59.95
62.20
72.60
         Road, brs. N. and S.
Desc. 30 ft.
Asc. 25 ft.
Set an iron post, 3 ft. long, 2 ins. diam.,6 ins. in the ground, in a mound of stone, for cor. of secs. 3, 4, 33
80.00
             and 34, marked on brass cap
```

Survey of the R. 6 W. North Boundary of T. 13 S. chains. T12S R6W 833 834 1918 And raise a mound of stone, 2 ft. base,  $l_2^1$  ft. high, W of cor. Land, rolling. Soil, rocky, 4th rate. No timber. Undergrowth, greasewood, cactus and palo verde. East on a true line, bet. secs. 3 and 34. Over rolling land, through dense undergrowth. Asc. 10 ft. Desc. 30 ft. Asc. 15 ft. Desc. 15 ft. 1.15 5.00 10.00 Asc. 20 ft. 12.20 18.95 27.55 32.55 40.00 Desc. 25 ft. Desc. 110 ft. Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, for 1 sec. cor., marked on brass cap 1 S34 S 3 1918 And raise a mound of stone, 2 ft. base,  $l^{\frac{1}{2}}$  ft. high, N of cor. Continue gradual déscent. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 3, 34 and 35, marked on 80,00 And raise a mound of stone, 2 ft. base, 12 ft. high, W of cor. Land, rolling. Soil, rocky, 4th rate. No timber. Undergrowth, greasewood, palo verde and cactus. East on a true line, bet. secs. 2 and 35. Over rolling land, through dense undergrowth. Asc. 10 ft. Desc. 40 ft. 1.40 Road, brs. N. and S.
Wash, 20 lks. wide, 4 ft. deep, course N.
Road, brs. N.20°E. and S.20°W.
Wash, 35 lks. wide, 2 ft. deep, course N.20°E.
Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, for \( \frac{1}{4} \) sec. cor., marked on 12.00 22.60 31.90 36.60 40.00 brass cap And raise a mound of stone, 3 ft. base, 2 ft. high, N.

of cor.

Survey of the North Boundary of T. 13 S. R. 6 W. hains. Asc. 15 ft. Desc. 20 ft. Asc. 80 ft. 54.55 64.15 69.15 Desc. 10 ft. 77.30 Asc. 10 ft. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in a mound of stone, for cor. of secs. 1, 2, 35 and 36, marked on brass cap T125, R6W And raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W of cor. Land, rolling. Soil, rocky, 4th rate. No timber. Undergrowth, palo verde, greasewood and cactus. East on a true line, bet. secs. 1 and 36. Over rolling and mountainous land, through dense undergrowth. Desc. 25 ft. 5.35 18.30 Asc. 155 ft. Gulch, course N. Spur, slopes N. Desc. 160 ft. 29.40 Gulch, course NE. Asc. 30 ft. Spur, slopes N.20°E. Desc. 325 ft.
Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for ½ sec. cor., marked on brass cap 39.10 40.00 And raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Continue descent. The cor. of Ts. 12 and 15 S., Rs. 5 and 6  $\overline{w}$ . 80.00 Land, rolling and mountainous. Soil, rocky, 4th rate. No timber. Undergrowth, greasewood, palo verde and cactus. Survey of the Subdivision of T. 13 S., R. 6 W. From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of Tp., described in Book "F", N.O°1'W., bet. secs. 35 and 36. Over level land, through dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap 40.00 1918 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. Wash, 36 lks. wide, 2 ft. deep, course S.20°E.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked on 73.80 80.00 brass cap

Survey of the 10 Subdivision chains. T13S R6W S26 S25 S35 S36 Dig pits, 18 X 18 X 12 ins., in each sec.,  $5\frac{1}{2}$  ft. dist Land, level. Soil, sandy and gravelly clay, 2nd rate. No timber. Undergrowth, greasewood, mesquite and palo verde. East on a random line, bet. secs. 25 and 36. 40.00 Set temp. 1 sec. cor Intersect E. bdy. of Tp., 3 lks. S. of the cor. of secs. 25, 30, 31 and 36, described in Book "G". Thence S.89°59'W., on a true line, bet. secs. 25 and 36.

Over level land, through dense undergrowth.

Wash, 25 lks. wide, 3 ft. deep, course S.30°E.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap 19.75 40.08 1 S25 4 S36 1918 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. Wash, 20 lks. wide, 2 ft. deep, course S. Road, brs. NW. and SE. The cor. of secs. 25, 26, 35 and 36. Land, level. Soil, sandy and gravelly, 2nd and 3rd rates. No timber Undergrowth, greasewood, mesquite, palo verde and iron-N.0°1'W., bet. secs. 25 and 26. Over level land, through dense undergrowth. Wash, 30 lks. wide, 2 ft. deep, course SW.

Same wash, course S.10°E.

Same wash, course S.30°W.

Enter same wash, course S.10°E., from N.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, in shallow wash, for \( \frac{1}{4} \) sec. cor., marked on 24.80 29.90 38.50 40.00 brass cap s26 s25 1918 An ironwood, 12 ins. diam., brs. N.80°E., 7 lks. dist., marked \$255 BT.

A mesquite, 10 ins. diam., brs. S.19°W., 89 lks. dist., marked \$26 BT. 41.90 Leave wash, course S., from NE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, marked on 26 ins. in the brass cap T13S R6W S23 S24 S26 S25 1918

=		Subdivision of T. 13 S. R. 6 W.
	Chains	Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist.
		Land, level. Soil, gravelly and sandy clay, 2nd rate.
		No timber. Undergrowth, greasewood, mesquite, palo verde and iron-
		wood.
	40.00	East on a random line, bet. secs. 24 and 25. Set temp. \(\frac{1}{2}\) sec. cor.
	80.07	Intersect E. bdy. of Tp., 6 lks. S. of the cor. of secs.
		19, 24, 25 and 30, described in Book "G". Thence
		S.89°57'W., on a true line, bet. secs. 24 and 25. Over level and gently rolling land, through dense under-
	21.65	growth. Wash, 50 lks. wide, 7 ft. deep, course S.
	40.03 <del>2</del>	Wash, 50 lks. wide, 7 ft. deep, course S. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
		1 S24
	·	
		Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
	43.55 65.65	Road, brs. NW. and SE. Road, brs. N. and S.
	75.35 80.07	Wash, 40 lks. wide, 2 ft. deep, course S. The cor. of secs. 23, 24, 25 and 26.
	00.07	Land, level and gently rolling.
	. G	Soil, gravelly and rocky, 3rd rate. No timber.
		Undergrowth, greasewood, mesquite, palo verde and ironwood.
	· <u>-</u> -	
		N.0°1'W., bet. secs. 23 and 24.
	7 70	Over level land, through dense undergrowth.
	3.70 40.00	Wash, 20 lks. wide, 1 ft. deep, course SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
-		ground, for 4 sec. cor., marked on brass cap
		S23 S24
	•	1918
		Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft.
	E7 00	dist.
	53.60 63.60	Wash, 15 lks. wide, 1 ft. deep, course SE. Road, brs. NW. and SE.
	64.80 80.00	Wash, 50 lks. wide, 4 ft. deep, course SE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the
		ground, for cor. of secs. 13, 14, 23 and 24, marked on brass cap
		T13S R6W S14 S13
		1918
		Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist. Land, rolling.
		Soil, gravelly and rocky, 3rd rate. No timper.
		the state of the s

Survey of the Subdivision of T. 13 S., R. 6 W.

2	)	Subdivision of T. 13 S., R. 6 W.
	Chains.	Undergrowth, greasewood, mesquite, palo verde, ironwood and cactus.
	,	
	40.00 79.97	East on a random line, bet. secs. 13 and 24.  Set temp. ½ sec. cor.  Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs.  13, 18, 19 and 24, described in Book "G".
	39 • 9 8 <del>1</del>	ground, in a mound of stone, for \( \frac{1}{4} \) sec. \( \omega \) r., marked on brass cap
		1918
	,	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
	54·45 63·05 79·97	Wash, 20 lks. wide, 3 ft. deep, course S.20°E. Road, brs. NW. and SE. The cor. of secs. 13, 14, 23 and 24. Land, rolling.
		Soil, gravelly and rocky, 3rd rate. No timber.
		Undergrowth, greasewood, cactus, palo verde and ironwood.
	10.00	N.0°1'W., bet. secs. 13 and 14.  Over rolling and mountainous land, through dense undergrowth.  Road, brs. W. and SE.  Asc. 305 ft.  Desc. 260 ft.  Set an iron post, 3 ft. long, l in. diam., on bed rock, in a mound of stone, 4 ft. base, 3 ft. high, for ½ sec. cor., marked on brass cap
		S14 S13
	,	1918
	51.35 80.00	And raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  Wash, 18 lks. wide, course S.30°E. Asc. gradually, 65 ft. Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base, 2½ ft. high, for cor. of secs. 11, 12, 13 and 14, marked on brass cap
		T13S R6W S11 S12 S14 S13 1918
		And raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.  Land, rolling and mountainous.  Soil, gravelly and rocky, 2nd and 4th rate.  No timber.
		Undergrowth, palo verde, ironwood, mesquite, greasewood, rosin brush and cactus.
		East on a random line, bet. secs. 12 and 13.

```
Set temp. ½ sec. cor. Intersect E. bdy. of Tp., at the cor. of secs. 7, 12, 13 and 18, described in Book "G".
 40.00
80.12
          hence
          West on a true line, bet. secs. 12 and 13.
          Over mountainous land, through dense undergrowth,
          Asc. 115 ft.
  5.00
          Spur, slopes S.60°E. Desc. 135 ft. Asc. 490 ft.
25.40
          Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in a mound of stone, 4 ft. base, 3 ft. high, for \frac{1}{4} sec.
40.06
              cor., marked on brass cap
              And raise a mound of stone, 3 ft. base, 2 ft. high, N.
              of cor.
42.90
80.12
          Ridge, brs. N.10°E. and S.15°E. Desc. 605 ft.
         The cor. of secs. 11, 12, 13 and 14.
          Land, mountainous.
Soil, rocky, 4th rate, malpais formation.
          No timber.
          Undergrowth, palo verde, ironwood, rosin brush, greasewood
              and cactus.
         N.O°1'W., bet. secs. 11 and 12.
          Over rolling and mountainous land, through dense undergrowth.
         Asd. 115 ft.
34.96
40.00
         Desc. 30 ft.
         Set an iron post, 3 ft. long, l in. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base, 2½ ft. high,
              for \frac{1}{4} sec. cor., marked on brass cap
                                      S11 S12
                                         1918
              And raise a mound of stone, 3 ft. base, 2 ft. high, W.
              of cor.
         Ravine, 50 lks. wide, 10 ft. deep, course SW. Asc. 305 ft. Set an iron post, 3 ft. long, 2 ins. diam., on bedorock, in a mound of stone, 4 ft. base, 3 ft. high, for cor. of secs. 1, 2, 11 and 12, marked on brass cap
54.70
80.00
                                      T138 R6W
                                        S11 S12
                                          1918
             And raise a mound of stone, 3 ft. base, 2 ft. high, W.
             of cor.
             Land, rolling and mountainous.
         Soil, rocky, 4th rate.
         No timber.
         Undergrowth, greasewood, palo verde, ironwood and rosin
             brush.
         East on a random line, bet. secs. 1 and 12.
         Set temp. ½ sec. cor.
Intersect E. bdy. of Tp., 7 lks. N. of the cor. of secs.

1, 6, 7 and 12, described in Book "G".
40.00
79 •97
```

N.89°57'W., on a true line, bet. secs. 1 and 12.

```
Survey of the
                    Subdivision of T
chains.
           Over rolling and mountainous land, through dense under-
               growth.
          Asc. 735 ft. Set an iron post, 3 ft. long, 1 in. diam., in a mound of
 39.98<del>}</del>
               stone, for \frac{1}{4} sec. cor., marked on brass cap
                And raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high, N
                of cor.
           Ridge, brs. N.15°W. and S.15°E. Desc. 395 ft. The cor. of secs. 1, 2, 11 and 12.
 57.10
79.97
           Land, rolling and mountainous.
           Soil, rocky, 4th rate.
           No timber.
           Undergrowth, greasewood, cactus and palo verde.
           N.O.1.W., on a random line, ?bet. secs. 1 and 2.
           Set temp. \frac{1}{4} sec. cor.
 40.00
           Intersect N. bdy. of Tp., 9 lks. W. of the cor. of secs.
1, 2, 35 and 36, hereinbefore described.
 79.85
            Thence
           S.003 W.
                         on a true line, bet. secs. 1 and 2.
           Over rolling and mountainous land, through medium under-
               growth.
           Asc. 255 ft. along W.side of Black Mountain.
Set an iron post, 3 ft. long, 1 in. diam., in a mound of
 39.85
                stone, for 4 sec. cor., marked on brass cap.
                                           ន 2 នៃ 1
                And raise a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high, W.
           of cor.
Desc. 30 ft.
Asc. 90 ft.
 59.80
66.00
           Spur, slopes SW. Desc. 255 ft. The cor. of secs. 1, 2, 11 and 12.
 72.75
79.85
           Land, rolling and mountainous. Soil, rocky, 4th rate.
           No timber.
            Undergrowth, palo verde, greasewood and cactus.
           From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp., described in Book "F", N.O°l'W., bet. secs. 34 and 35.
            Over level land, through dense undergrowth.
           Wash, 12 lks. wide, 1 ft. deep, course S.10°E.

Same wash, 12 lks. wide, course S.5°W.

Same wash, 12 lks. wide, course S.10°E.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap
  10.00
 15.00
  34.50
  40.00
                                           834 S35
                                              1918
                From which
                      A mesquite, 20 ins. diam., brs. N.82½°W., 132 lks. dist., marked ±534 BT.
```

BOOK 3350

Survey of the Subdivision of Total S. R. 6 W 15 chains. No other trees within limits. Dig pits,  $18 \times 18 \times 12$  ins. N. and S. of post, 3 ft. dist.

Same wash, 8 lks. wide, course S.15°W.

Wash, 12 lks. wide, 1 ft. deep, course S.10°W.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked on 51.10 56.10 80.00 brass can T138 R6W S27 S26 From which A mesquite, 12 ins. diam., brs. S.61°W.,
141 lks. dist., marked T13S R6W S34 BT.
No other trees within limits. Dig pits, 18 X 12 ins. in each sec.,  $5\frac{1}{2}$  ft. dist. Land, level. Soil, sandy loam and adobe, 1st rate. No timber. Undergrowth, greasewood, mesquite, palo verde, rosin brush and ironwood. Poor growth of grass. East on a random line, bet. secs. 26 and 35. Set temp. 4 sec. cor. Intersect N. and S. line, at the cor. of secs. 25, 26, 35 40.00 79.94 and 36. Thence West on a true line, bet. secs. 26 and 35. Over level land, through dense undergrowth. Wash, 25 lks. wide, course S.10°E.
Wash, 16 lks. wide, course S.
Wash, 8 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap 2.24 12.75 32.15 39.97 1 S26 4 S35 1918 From which An ironwood, 16 ins diam., brs. N.75°W.,
150 lks. dist., marked 4826 BT. No other trees within limits. Dig pits, 18 X 18 X 12 ins. E. and W. of post, 3 ft. dist. Wash, 10 lks. wide, course S.
Wash, 12 lks. wide, course S.10°E.
Wood road, brs. N. and S.
Wash, 20 lks. wide, 1 ft. deep, course S.15°W.
The cor. of secs. 26, 27, 34 and 35. 52.45 **5**9 • 45 66 • 85 73 • 45 79 • 94 Land, level. Soil, sandy and gravelly loam and adobe, 1st and 2nd rates. No timber: Undergrowth, mesquite, palo verde, ironwood, greasewood and rosin brush. Poor growth of grass.

N.0°1'W., bet. secs. 26 and 27.

Over level land, through dense undergrowth.

S. end of mountain brs. E. 40 chs. dist.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass can 35:88

Survey of the of T. 6 w 16 Subdivision chains. s27 s26 1918 From which A palo verde, 8 ins. diam., brs. S.63°W.,
72 lks. dist., marked \(\frac{1}{2}\)S27 BT.
Road, brs. N.15°E. to Ajo and S. 15°W. to Sonoyta. 42.50 Wash, 12 lks. wide, course SW.
Road, brs. N.15°E. to Ajo and S.15°W. 65.40 76.85 Wash, 10 lks. wide, course S.15°W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on 78.30 80.00 brass cap T13S R6W S22 S23 S27 S26 1918 From which An ironwood, 8 ins. diam., brs. N.5½°E.,
90 lks. dist., marked T13S R6W S23 BT.
An ironwood, 10 ins. diam., brs. S.4½°E.,
96 lks. dist., marked T13S R6W S26 BT.
No other trees within limits. Dig pits, 18 X 18 X 12 ins. in each sec.,  $5\frac{1}{5}$  ft. dist. Land, level. Soil, sandy and gravelly adobe, 1st and 2nd rates. No timber. Undergrowth, mesquite, ironwood, palo verde and greasewood. East on a random line, bet. secs. 23 and 26. Set temp.  $\frac{1}{4}$  sec. cor. Intersect N. and S. line, 2 lks. N. of the cor. of secs. 79.84 23, 24, 25 and 26. Thence N.89°59 W., on a true line, bet. secs. 23 and 26. Over rolling and mountainous land, through dense undergrowth. Asc. 385 ft.
Wash, 8 lks. wide, course SE. Continue ascent.
Ridge, brs. N.10°E. and S. Desc. 365 ft.
Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in a mound of stone, 4 ft. base, 3 ft. high, for ‡ sec. cor., 10.00 35.30 39.92 marked on brass cap 523 4 326 1918 And raise a mound of stone, 2 ft. base, 1 ft. high, N Wash, 20 lks. wide, 2 ft. deep, course S. Thence level land. Road, brs. N. to Ajo and S.15°W. to Sonoyta. Road, brs. N.15°E. to Ajo and S.15°W. to Wash, 10 lks. wide, course S.10°W. The cor. of secs. 22, 23, 26 and 27. Land, level, rolling and mountainous. Soil, sandy and rocky adobe, 1st and 4th rates. No timber. of cor. 62.25 65.45 78.54 79.65 Undergrowth, mesquite, palo verde, ironwood and greasewood N.0011W., bet. secs. 22 and 23. Over level land, through dense undergrowth.

```
Survey of the
                    Subdivision of T. 13 S., R. 6 W.
18
chains
             N.0^{\circ}l^{\dagger}W., bet. secs. 14 and 15.
             Over level land, through dense undergrowth.
             Wash, 8 lks. wide, course SE.
Road, brs. NE. and SW.
Wash, 8 lks. wide, course SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for 4 sec. cor., marked on brass cap
   2.20
 30.75
38.00
 40.00
                                                 s15 s14
                  From which
                         An ironwood, 16 ins. diam., brs. S.1°E.,
                         150 lks. dist., marked $\frac{1}{4}$14 BT.

A mesquite, 7 ins. diam., brs. $.64°W.,

173 lks. dist., marked $\frac{1}{4}$15 BT.
 50.30
68.70
             Wash, 10 lks. wide, course E. Wood road, brs. NE. and SW.
             Wash, 8 lks. wide, course SE.
Wash, 6 lks. wide, course SE.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, marked on
 70.00
  76.50
 80.00
                  brass cap
                                                 T13S R6W
S10 S11
S15 S14
                  From which
                        An ironwood, 7 ins. diam., brs. N.64°E.,

143 lks. dist., marked T13S R6W S11 BT.

A palo verde, 10 ins. diam., brs. S.81½°W.,

130 lks. dist., marked T13S R6W S15 BT.

er trees within limits. Dig pits, 18 X 18 X 12 ins.
             No other trees within limits.
                  in each sec., 5\frac{1}{2} ft. dist.
             Land, level.
             Soil, sandy and gravelly laom, 2nd rate.
             No timber.
             Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush.
             East on a random line, bet. secs, 11 and 14.
             Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs.
 40.00.
 80.11
                  11, 12, 13 and 14.
             Thence
             S.89°58'W., on a true line, bet. secs. 11 and 14.
             Over level and gently rolling land, through dense under-
                  growth.
             Desc. 40 ft.
 20.10
             North end of mountain, 350 ft. high, brs. S. 1 ch. dist.
 20.80 Wash, 30 lks. wide, course SW.
Wash, 3 chs. wide, course S.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, 2 ft. high, ofor 4 sec. cor., marked on brass cap
                                                    1918
                  And raise a mound of stone, 3 ft. base, 2\frac{1}{2} ft. high, N.
                  of cor.
             Road, brs. NW. and S.20°E.
 52.60
57.40
64.10
             Road, brs. N. and S.
Wash, 60 lks. wide, 2 ft. deep, course S.
Road, brs. NE. and SW.
  69.10
             Wash, 12 lks. wide, course SE.
 69.85
```

. 19

```
80.11
             The cor. of secs. 10, 11, 14 and 15. Land, level and gently rolling.
              Soil, gravelly and rocky, 2nd and 3rd rates.
             No timber.
             Undergrowth, palo verde, ironwood, mesquite, greasewood.
                   rosin brush and cactus.
             N.0°1'W., bet. secs. 10 and 11.
             Over level and gently rolling land, through dense under-
                   growth.
4.50
17.40
             Wash, 16 lks. wide, course SE.
             Wash, 12 lks. wide, course SE.
Wash, 10 lks. wide, course SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
37·99
40·00
                                                  S10|S11
                                                        1918
                   From which
                          An ironwood, 6 ins. diam., brs. S.26°E.,
78 lks. dist., marked $\frac{1}{4}$$$$$Sl1 BT.

A palo verde, 8 ins. diam., brs. S.39\frac{1}{2}$$$\text{ow.},
89 lks. dist., marked $\frac{1}{4}$$$$$$$$$$$$$$$$$$$$$$$
            Wash, 8 lks. wide, course E.

Moad, brs. N.5°E. and S.15°W.

Wash, 10 lks. wide, course SE.

Bet an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 2, 33 10 and 11, marked on
58.39
78.19
78.59
80.00
                   brass cap
                                                   T13S R6W
S 3 S 2
S10 S11
                                                         1918
                  From Which
                         An ironwood, 12 ins. diam., brs. S.21°E.,
100 lks. dist., marked T13S R6W S11 BT.
An ironwood, 9 ins. diam., brs. N.39°W.,
61 lks. dist., marked T13S R6W S3 BT.
             No other trees within limits. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
             Land, level and gently rolling.
             Soil, gravelly and rocky, 3rd and 4th rates.
             No timber.
             Undergrowth, palo verde, ironwood, greasewood, rosin brush
                   and cactus.
             East on a random line, bet. secs. 2 and 11.
            Set temp. \frac{1}{4} sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs.
40.00
80.19
                  1, 2, 11 and 12. ·
             Thence
            S.89°58 W., on a true line, bet. secs. 2 and ll. Over mountainous land, through dense undergrowth.
            Asc. 100 ft.
3.85
35.70
3.85 Spur, slopes SW. Desc. 525 ft.
35.70 Wash, 30 lks. wide, course S.80°W. Continue descent.
40.09½ Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brase cap
```

Survey of the Subdivision of T. 13 20 S. R. 6 W chains. And raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
Road, brs. N.15°W. and S.
Wash, 35 lks. wide, course S. Asc. 30 ft. 61.90 62.80 72.30 80.19 Desc. The cor. of secs. 2, 3, 10 and 11. Land, rolling and mountainous. Soil, gravelly and rocky, 3rd and 4th rates. No timber. Undergrowth, palo verde, ironwood, mesquite, greasewood, rosin brush and cactus. N.O°l'W., on a random line, bet. secs. 2 and 3.
Set temp. ½ sec. cor.
Intersect N. bdy. of Tp., 9 lks. W. of the cor. of secs.
2, 3, 34 and 35, hereinbefore described. 40.00 79 • 97 Thence S.0°3'W., on a true line, bet. secs. 2 and 3. Over mountainous and rolling land, through dense undergrowth. Asc. 15 ft. Desc. 20 ft.
Wash, 12 lks. wide, course E. Thence over rolling land.
Wash, 8 lks. wide, course N.70°E. Asc. 15 ft.
Divide, brs. E. and W. Desc. 30 ft. 12.20 16.90 26.90 30.00 34.95 From this point, Locomotive Butte brs. W. about 20 chs. dist. Wash, 12 lks. wide, course E. Asc.
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, 2 ft. high, 39 • 70 39 • 9 7 for 1/4 sec. cor., marked on brass cap s 3 s 2 1918 And raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor Desc. 30 ft. Wash, 8 lks. Wide, course SE. Thence over gently rolling. 56.05 land. 69.60 Dim road, brs. E. and W. Wash, 16 lks. wide, course E. Asc. 20 ft. 71.20 72.60 Desc. 15 ft. The core of secs. 2, 3, 10 and 11. 79 •97 Land, rolling and mountainous. Soil, gravelly and rocky, 3rd and 4th rates. No timber. Undergrowth, palo verde, ironwood, greasewood, rosin brush and cactus. From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of Tp., described in Book "F", N.0°2'W., bet. secs. 33 and 34. Over level land, through dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 40.00 \$33 \$34 1918 From which A mesquite, 7 ins. diam., brs. N.3°W.,

89 lks. dist., marked 1833 BT.

21

Survey of the Subdivision of T. 13 S.. Chains. No other trees within limits. Dig pits,  $18 \times 18 \times 12$  ins. No other trees within limits. Big pits, 10 % 12 ins.

No and S. of post, 3 ft. dist.

Wash, 8 lks. wide, course S.10°E.

Same wash, 8 lks. wide, course S.10°W.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, marked on 57.60 60.00 80.00 brass cap T13S R6W S28 S27 From which A mesquite, 8 ins. diam., brs. N.37°E. 136 lks. dist., marked T13S R6W S27 BT. An ironwood, 12 ins. diam., brs. S.26½°E., 157 lks. dist., marked T13S R6W S34 BT. Dig pits, 18 X 18 X 12 ins., No other trees within limits. in each sec.,  $5\frac{1}{2}$  ft. dist. Land, level. Soil, sandy loam, and adobe, 1st rate. No timber. Undergrowth, mesquite, ironwood, greasewood. Poor growth of grass. East on a random line, bet. secs. 27 and 34. Set temp. 1 sec. cor. 40.00 80.00 Intersect N. and S. line, at the cor. of secs. 26, 27, 34 and 35. Thence West on a true line, bet. secs. 27 and 34. Over level land, through dense undergrowth.

Road, brs. N. to Ajo and S. to Sonoyta.

Wash, 10 lks. wide, 2 ft. deep, course S.

Draw, course S.

Road, brs. N.15°E. to Ajo and S.20°W.

Set an iron post, 3 ft. long, l in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap 4.20 20.00 32.00 **36.2**0 40.00 From which A mesquite, 8 ins. diam., brs. N.58°W., 77 lks. dist., marked \(\frac{1}{4}\)S27 BT. No other trees within limits. Dig pits, 18 imes 18 imes 12 ins. E. and W. of post, 3 ft. dist.
Wash, 10 lks. wide, 2 ft. deep, course S.
Wash, 6 lks. wide, course S. 45.00 56.70 Wash, 12 lks. wide, course S. The cor. of secs. 27, 28, 33 and 34. 74.05 80.00 Land, level. , sandy loam and adobe, 1st and 2nd rates. Soil, No timber. Undergrowth, greasewood, mesquite and palo verde. N.0°2'W., bet. secs. 27 and 28. Over level land, through dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \( \frac{1}{2} \) sec. cor., marked on brass cap 40.00 s28[ s27

1918

Survey of the Subdivision of T. 13 S. R. 6 W. 22 chains. A mesquite, 7 ins. diam., brs. N.87°E.,

28 lks. dist., marked ½ S27 BT.

A mesquite, 12 ins. diam., brs. N.88°W.,

24 lks. dist., marked ½ S28 BT.

Wash, 6 lks. wide, course S.15°E.

Wash, 6 lks. wide, course S.10°E.

Wash, 8 lks. wide, course S.10°E.

Road, brs. N.70°E. and SW 40.25. 55.80 62.10 78.60 Road, brs. N.70°E. and SW. Setan iron post, 3 ft: long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, marked on 80.00 brass cap T13S R6W S21 S22 S28 S27 . 1918 From which A palo verde, 16 ins. diam., brs. S.80°E.,
118 lks. dist., marked T13S R6W S27 BT.
No other trees within limits. Dig pits, 18 X 18 X 12 ins., in each sec., 5 ft. dist. Land, level. Soil, sandy adobe, 1st rate. No timber. Undergrowth, mesquite, palo verde, ironwood and greasewood. East on a random line, bet. secs. 22 and 27. Set temp. 4 sec. cor 40.00 Intersect N. and S. line, 3 lks. S. of the cor. of secs. 80.00 22, 23, 26 and 27. Thence S.89°59'W., on a true line, bet. secs. 22 and 27. Over level land, through dense undergrowth. Wash, 8 lks. wide, course S.15°W. 5.00 Draw, course S.
Wash, 10 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap 20.00 3**4.3**0, 40**.**00 \$22 4 \$27 1918 Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. Wash, 16 lks. wide, course S. Wash, 10 lks. wide, course S. Road, brs. N.70°E, and S.70°W. 48.00 68.80 75.80 80.00 The cor. of secs. 21, 22, 27 and 28. Land, level. Soil, sandy and gravelly loam and adobe, 1st and 2nd rates. No timber. Undergrowth, mesquite, palo verde, ironwood, greasewood and rosin brush. Fair growth of grass. N.0°2'W., bet. secs, 21 and 22. Over level land, through dense undergrowth. Wash, 8 lks. wide, course S.10°W.
Same wash, 8 lks. wide, course S.10°E.
Same wash, 8 lks. wide, course S.10°W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 16.70 20.00 37.30 40.00

23

Survey of the Subdivision of T. 13 S. R. 6 W chains. - 1918 From which An ironwood, 12 ins. diam., brs. S.45°E., 185 lks. dist., marked \$22 3T.

An ironwood, &finsk diam., brs. S.80°W., 162 lks. dist., marked  $\frac{1}{4}$ S21 BT. 54.00 67.40 80.00 Wash, 12 lks. wide, course S.15°W.
Road, ors. E. and W.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, marked on brass cap T13S R6W S16 S15 S21 S22 1918 From which A mesquite, 7 ins. diam., brs. S.502°E., 69 lks. dist., marked T13S R6W S22 BT. An ironwood, 8 ins. diam., brs. S.43½°W., 157 lks. dist., marked T13S R6W S21 BT. No other trees within limits. Dig pits, 18 X 18 X Dig pits, 18 x 18 x 12 ins. in each sec., 5\frac{1}{2} ft. dist. Land, level. Soil, sandy loam and adobe, 1st rate. No timber. Undergrowth, mesquite, palo verde, ironwood, greasewood and rosin brush. East on a random line, bet. secs. 15 and 22. Set temp. 🗦 sec. cor. 40.00 Intersect N. and S. line, at the cor. of secs. 14, 15, 22 80.00 and 23. Thence West on a true line, bet. secs. 15 and 22. Over level land, through dense undergrowth. Wash, 8 lks. wide, course S.15°E.
Road, brs. SW. and N.
Wash, 70 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap 11.00 14.65 26.40 40.00 From which An ironwood, 9 ins. diam., brs. N.20°W.,
133 lks. dist., marked 4815 BT.

A palo verde, 8 ins. diam., brs. S.1°W.,
21 lks. dist., marked 4822 BT. 55.40 73.70 78.50 Wash, 12 ins. wide, course S. Wash, 6 lks. wide, course S. Wood road, brs. N. and S. The cor. of secs. 15, 16, 21 and 22. 80.00 Land, level. Soil, sandy and gravelly loam, 1st and 4th rates. No timber. Undergrowth, mesquite, palo verde, ironwood, greasewood

 $N.0^{\circ}2^{\circ}W.$ , bet. secs. 15 and 16.

Over level land, through dense undergrowth.

Survey of the 24 Subdivision of T. 13 S., R. 6 W. MARIE AST Wood road, brs. NW. and S.20°E. Wood road, brs. SW. and N.10°W. Wood road, brs. NE. and SW. 2.30 9.20 15.45 30.90 Wash, 6 lks. wide, course S.20°W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \$\frac{1}{2}\sec.2\cor., marked on brass cap 40.00 s16 s15 1918 From which An ironwood, 12 ins. diam., brs. N.80°E., 175 lks. dist., marked 1815 BT.

A mesquite, 8 ins. diam., brs. S.5510W.,
87 lks. dist., marked 1816 BT. 59.40 76.19 Wash, 6 lks. wide, course 5.15°W. Wash, 6 lks. wide, course SW.
Wash, 8 lks. wide, course SW.
Same wash, 8 lks. wide, course SE.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked on 77.19 78.90 80.00 brass cap T13S R6W S 9 S10 **S16** | S15 1918 From which A palo verde, 12 ins. diam., brs. N.52°E., 116 lks. dist., marked T13S R6W S10 BT. No other trees within limits. Dig pits, 18 x 18 x 12 ins, in each sec.,  $5\frac{1}{2}$  ft. dist. Land, level and rolling. gravelly and rocky, 2nd and 3rd rates. Soil, No timber. Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush. East on a random line, bet. secs. 10 and 15. Set temp. 2 sec. cor. Intersect N. and S. line, 2 lks. N. of the cor. of secs. 40.00 80.12. 10, 11, 14 and 15. Thence N.89°59 W., on a true line, bet. secs. 10 and 15. Over rolling land, through dense undergrowth. Wash, 6 lks. wide, course SE. Asc. 25 ft. 2.95 12.65 Desc. 20 ft. Wash, 10 lks. wide, course S.15°E.
Wash, 25 lks. wide, course S.
Wash, 50 lks. wide, course S.15°E. Asc. 35 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap 16.95 39.65 40.06 From which A cat claw, 5 ins. diam., brs. N.54°E., 19 lks. dist., marked 2810 BT. An ironwood, 20 ins. diam., brs. S.60°E.,

55 lks. dist., marked \$\frac{1}{2}\$\$S15 3T.

Desc. 20 ft. 50.15 58.30 65.10 Wash, 10 lks. wide, course S. Asc. 20 ft. Desc. 30 ft. Wash, 6 lks. wide, course SW. Asc.

		BOCK 3350	
		Survey of the Subdivision of T. 13 S., R. 6 W.	25
	Chains. 80.12	The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, gravelly and rocky, 2nd and 3rd rates. No timber. Undergrowth, mesquite, palo verde, ironwood, cat claw, greasewood and rosin brush.	
	15.00 18.90 24.45 29.45 40.00	N.0°2'W., bet. secs. 9 and 10.  Over gently rolling land, through dense undergrowth.  Asc. 25 ft.  Desc.  Wash, 8 lks. wide, course SW. Asc. 55 ft.  Desc. 15 ft.  Asc. 45 ft.  Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in a mound of stone, 4 ft. base, 3 ft. high, for \$\frac{1}{2}\$ sec.	
		cor., marked on brass cap  S 9 slo	
	40.89 67.07 71.37 74.07 80.00	And raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  Desc. 60 ft.  Wash, 50 lks. wide, course SE.  Wash, 20 lks. wide, course S.10°E.  Wash, 10 lks. wide, course SE. Asc. 20 ft.  Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, marked on bracap	SS
•		T13S R6W S 4 S 3 S 9 S10 1918  Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist. Land, gently rolling. Soil, gravelly and rocky, 3rd and 4th rates.	
	_	No timber. Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush.	
	40.00 80.08	East on a random line, bet. secs. 3 and 10.  Set temp; \(\frac{1}{4}\) sec. cor.  Intersect N. and S. line, 5 lks. S. of the cor. of secs.  2, 3, 10 and 11.	
	23.30	Thence S.89°58'W., on a true line, bet. secs. 3 and 10. Over rolling land, through dense undergrowth. Desc. Wash, 10 lks. wide, course SE. Asc. 100 ft. Desc. 60 ft. Wash, 10 lks. wide, course SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap	
		$\frac{1}{4} \frac{S}{S10}$ $1918$ And raise a mound of stone, $2\frac{1}{8}$ ft. base, 2 ft. high, N.	
	49·45 52·40	of cor. Wash, 12 lks. wide, course S. Wash, 8 lks. wide, course Sw.	

Survey of the R. 6 W. Subdivision of 13 S. 26 Tha Tha . 72.20 Wash, 40 lks. wide, course S. Wash, 12 lks, wide, course SW. The cor. of secs. 3, 4, 9 and 10. 76.60 80.08 Land, rolling. Soil, gravelly and rocky, 3rd and 4th rates. No timber. Undergrowth, palo v and rosin brush. palo verde, mesquite, ironwood, greasewood N.0°2'W., on a random line, bet. secs. 3 and 4.
Set temp. \(\frac{1}{2}\) sec. cor.
Intersect N. bdy. of Tp., 9 kks. W. of the cor. of secs.
3, 4, 33 and 34, hereinbefore described. 40.00 80.01 Thence on a true line, bet. secs. 3 and 4. S.0°2 1W. Over rolling land, through dense undergrowth. Desc. 25 ft. 8.75 10.55 28.90 Wash, 25 lks. wide, course SE. Asc. 10 ft. Desc. 60 ft. Wash, 25 Wash, 10 lks. wide, course SE. Same wash, course S.15°W. Asc. 20 ft.
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, 2 ft. high, 33.20 40.01 for \frac{1}{4} sec. cor., marked on brass cap s 4 s 3 And raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. 52.00 62.20 Desc. 45 ft. Enter wash, course S., from NE.

Leave wash, 12 lks. wide, course S.5°E.

The cor. of secs. 3, 4, 9 and 10. 67.70 80.01 Land, rolling. Soil, gravelly and rocky, 3rd and 4th rates. No timber. Undergrowth, palo verde, mesquite, ironwood, greasewood, rosin brush and cactus. From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of Tp., hescribed in Book "F", N.O°2'W., bet. secs. 32 and 33. Over level land, through dense undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 40.00 **s32 s**33 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. Wash, 6 lks. wide, course S.20°E.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, marked on 71.90 80.00 brass cap T13S R6W S29 S28

27

```
Chains.
                   From which
             A mesquite, 8 ins. diam., brs. S.14% W.,
210 lks. dist., T13S R6W S32 BT.
No other trees within limits. Dig pits, 18 X 18 X 12 ins.,
                   in each sec., 5\frac{1}{2} ft. dist.
             Land, level.
Soil, sandy and gravelly clay, 1st rate.
             No timber.
             Undergrowth, mesquite, palo verde, greasewood and rosin
                   brush.
             East on a random line, bet. secs. 28 and 33.
             Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. and S. line, 2 lks. S. of the cor. of secs.
40.00
79•97
                  27, 28, 33 and 34.
             Phence
             S.89°59'W., on a true line, bet. secs. 28 and 33. Over level land, through dense undergrowth. Wash, course S.
39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
                 From which
            A mesquite, 12 ins. diam., brs. N.18°E.,
85 lks. dist., marked $28 BT.
A mesquite, 24 ins. diam., brs. S.57½°E.,
175 lks. dist., marked $253 BT.
Wood road, brs. N.10°E. and S.15°W.
Wash, 2 chs. wide, 2 ft. deep, course S.
The cor. of secs. 28, 29, 32 and 33.
61.15
71.45
79.97
             N.0^{\circ}2 W., bet. secs. 28 and 29.
            Over rolling land, through dense undergrowth. Asc. 290 ft., over mountainous land.
20.00
            Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in a mound of stone, 4 ft. base, 3 ft. high, for \( \frac{1}{2} \) sec. cor.,
40.00
                  marked on brass cap
                                                    s29 | s28
                  And raise a mound of stone, 3 ft. base, 2 ft. high, W.
                  of cor.
            Desc. 270 ft.

Wash, 50 lks. wide, 3 ft. deep, course E. Asc.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, marked on
54.31
73.26
80.00
                  brass cap
                                                    T13S R6W
S20 S21
S29 S28
                                                         1918
                  From which
                         A mesquite, 8 ins. diam., brs. N.47°W.
            62 lks. dist., marked T13S R6W S2O BT.

No other trees within limits. Raise a mound of stone, 2½
ft. base, 2 ft. high, W. of cor.

Land, rolling and mountainous.
```

Soil, gravelly and rocky, 3rd and 4th rates.

Survey of the Subdivision of T. 13 S 28 R. 6 W chains. No timber. Undergrowth, palo verde, mesquite, greasewood, rosin brush. East on a random line, bet. secs. 21 and 28. Set temp. 3 40.00 sec. cor. Intersect N. and S. line, 7 lks. S. of the cor. of secs. 79.94 21, 22, 27 and 28. Thence S.89°57'W., on a true line, bet. secs. 21 and 28. Over level land, through dense undergrowth. 4.95 9.55 32.55 39.97 Wash, 8 lks. wide, course S. Wash, 10 lks. wide, 2 ft. deep, course S.
Wash, 12 lks. wide, course S.25°W.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 1 S21 4 S28 1918 From which A mesquite, 8 ins. diam., brs. N.34°E.,
160 lks. dist., marked \$\frac{1}{2}\$S21 3T.

A mesquite, 10 ins. diam., brs. S.37\frac{1}{2}\$°E.,
150 lks. dist., marked \$\frac{1}{2}\$S28 BT. Dim road, brs. NE. and SW. Wash, 16 lks. wide, course SW. 40.80 50.45 56.55 72.65 76.25 Wash, 16 lks. wide, course SW.
Road, brs. NE. and S.
Wash, 10 lks. wide, 4 ft. deep, course S. Asc. 25 ft.
Desc. 15 ft. 79.94 The cor. of secs. 20, 21, 28 and 29. Land, level and rolling. sandy, gravelly and rocky, 1st and 3rd rates. No timber. Undergrowth, mesquite, palo verde, greasewood. Over rolling land, through dense undergrowth. Road, brs. E. and W. Asc. 235 ft. 12.90 30.00 Set an iron post, 3 ft. long, 1 in. diam., on bed rock, 40.00 in a mound of stone, 4 ft. base, 3 ft. high, for  $\frac{1}{4}$ sec. cor., marked on brass cap **S20** | **S21** 1918 And raise a mound of stone, 3½ ft. base, 2½ ft. high, of cor. 44.57 56.61 Desc. 60 ft. Asc. 110 ft. Ridge, brs. E. and W. Desc. 235 ft.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on 63.00 80.00 brass cap T13S R6W S17|S16 S20|S21 1918

cap

```
Survey of the
                                         of T.
 30
Chains.
                  From which
             A mesquite, 5 ins. diam., brs. S.64°W.,
83 lks. dist., marked T13S R6W S17 BT.
No other trees within limits. Dig pits, 18 X 18 X 12 ins.,
                  in each sec., 5½ ft. dist.
             Land, level.
                      sandy and gravelly adobe, 1st and 2nd rates.
             No timber.
             Undergrowth, mesquite, palo verde and greasewood.
             East on a random line, bet. secs. 9 and 16.
             Set temp. ½ sec. cor.
Intersect N. and S. line, 3 lks. S. of the cor. of secs.
 40.00
  79.87
                  9, 10, 15 and 16.
              Thence
             S.89°59'W., on a true line, bet. secs. 9 and 16. Over level land, through dense undergrowth.
              Wash, 8 lks. wide, course S.
    6.15
             Wash, 16 lks. wide, course S. Road, brs. NW. and SE. Road, brs. N. and S.
  12.35
28.75
34.85
             Wash, 8 lks. wide, course S.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap
   38.35
             Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
   48.55
50.65
57.45
64.85
             Wash, 6 lks. wide, course S. Junction of roads, br. NE. and S. and SW.
              Wash, 16 lks. wide, course S.
             Wash, 10 lks. wide, course S. Wash, 10 lks. wide, course SE. Wash, 12 lks. wide, course S.10°E. Road, brs. N.15°W. and S.10°E.
   66.75
72.65
   73.65
              The cor. of secs. 8, 9, 16 and 17.
              Land, level.
              Soil, sandy and gravelly adobe, 1st and 2nd rates.
              No timber.
              Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush.
              N.0°2'W., bet. secs. 8 and 9.
              Over level land, through dense undergrowth.
             Road, brs. NW. and SE.
Wash, 16 lks. wide, course SE.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ‡ sec. cor., marked on brass cap
   13.10
   13.90
   40.00
                                              s 8 s 9
                   And raise a mound of stone, 3 ft. base, 2 ft. high, W.
   59.99
67.18
                       25 lks. wide, course SW.
              Wash,
              Wash, 8 lks. wide, course SE.
Wash, 16 lks. wide, course SE.
Wash, 16 lks. wide, course SW.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
   73.37
77.88
   80.00
                  ground, for cor. of secs. 4, 5, 8 and 9, marked on brass
```

```
6 w.
                     Subdivision of T. 13 S..
Chains.
                                      T13S R6W
                                         8 S 9
                                         1918
             From which
                   An ironwood, 30 ins. diam., brs. S.57% W.,
19 lks. dist., marked T13S R6W S8 BT.
          No other trees within limits. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
          Land, level and gently rolling.
          Soil, gravelly and rocky, 2nd and 4th rates.
          No timber.
          Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush.
         East on a random line, bet. secs. 4 and 9.
         Set temp. 1 sec. cor. Intersect N. and S. line, 8 lks. N. of the cor. of secs.
40.00
79.96
             3, 4, 9 and 10.
          Thence
          N.89°57'W., on a true line, bet. secs. 4 and 9.
          Over rolling and mountainous land, through dense under-
             growth.
         Desc.
  2.05
         Wash, 25 lks. wide, course S. Asc. 80 ft.
3.15
17.35
26.10
34.35
35.95
39.98
         Dim road, brs. N. and S.
         Desc. 80 ft.
         Wash, 6 lks. wide, course S. Asc. 15 ft.
Road, brs. N. and S. Desc. 20ft.
Wash, 60 lks. wide, course S. Asc. 70 ft.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
             ground, for 1 sec. cor., marked on brass cap
             And raise a mound of stone, 3 ft. base, 2 ft. high, N.
             of cor.
44.00
         Desc. 35 ft.
48.15
         Wash, 6 lks. wide, course S. Asc. 40 ft.
50.85
55.15
58.60
         Desc. 60 ft.
         Wash, 8 lks. wide, course S. Desc. 30 ft. Asc. 55 ft. Desc. 75 ft.
                                               Asc. 40 ft.
66.10
71.00
79.96
         The cor. of secs. 4, 5, 8 and 9.
         Land, rolling and mountainous.
         Soil, gravelly and rocky, 3rd and 4th rates.
         No timber.
         Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush.
         N.0°2'W., on a random line, bet. secs. 4 and 5.
         Set temp. ‡ sec. cor.
Intersect N. bdy. of Tp., 15 lks. W. of the cor. of secs.
4, 5, 32 and 33, hereinbefore described.
40.00
79.92
         Thence
         S.0°4'W., on a true line, bet. secs. 4 and 5.
         Over rolling land, through dense undergrowth.
         Wash, 8 lks. wide, course SE.
 2.80
                                                 Asc. 10 ft
 6.10
         Low ridge, brs. NW. and S.15°W. Desc. 15 ft.
16.10
30.75
         Asc. 145 ft.
        Spur, slopes W. Desc. 155 ft.
Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the
```

ground, in a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high,

39.92

```
Survey of the
                        Subdivision of T. 13 S., R. 6 W.
chains.
             for ½ sec. cor., marked on brass cap
                                       S 5 | S 4
                                          1918
              And raise a mound of stone, 3 ft. base, 2 ft. high, W.
          Ravine, 50 lks. wide, 10 ft. deep, course SW. Desc. gradually, 90 ft.
              of cor.
 44.95
 49.95
79.92
          The cor. of secs. 4, 5, 8 and 9.
          Land, rolling.
          Soil, gravelly and rocky, 3rd and 4th rates.
          No timber.
          Undergrowth, palo verde, mesquite, ironwood, greasewood and rosin brush.
          From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of Tp., described in Book "R", N.0°3'W., bet. secs. 31 and 32.
           Over rolling land, through dense undergrowth.
           Asc. 150 ft.
           Spur, slopes W. Desc. 95 ft. Asc. 80 ft.
 8.90
28.83
           Desc. 65 ft.
 37.72
           Set an iron post, 3 ft. long, 1 in. diam., in a mound of stone, for \(\frac{1}{4}\) sec. cor., marked on brake cap
 40.00
                                        s31 s32
                                           1918
               And raise a mound of stone, 2 ft. base, 1 ft. high, W.
               of cor.
           Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, in a mound of stone, for cor. of secs. 29, 30, 31 and 32, marked on brass cap
           Thence over level land.
  49.98
  80.00
                                        T135 R6W
830 829
                And raise a mound of stone, 2\frac{1}{2} ft. base, 2 ft. high, W
           of cor.

Iand, level and rolling.
           Soil, rocky, 4th rate.
           No timber.
           Undergrowth, greasewood and cactus.
            East on a random line, bet. secs. 29 and 32.
           Set temp. 1 sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs.
  40.00
  79.94
                28, 29, 32 and 33.
            Thence
            s.89°58'w., on a true line, bet. secs. 29 and 32.
            Over rolling and mountainous land, through dense under-
               growth.
            Asc. 365 ft.
           Ridge, brs. N.15°E. and S.30°W. Desc. 75 ft.
Gulch, course N.20°W. Asc. 120 ft.
Set an iron post, 3 ft. long, 1 in. diam., on bed rock, in
a mound of stone, 3 ft. base, 3 ft. high, for † sec. cor.,
  24.35
28.45
  39.97
                marked on brass cap
```

	Subdivision of T. 13 S., R. 6 W.
Chains.	
-	\$29 \$32 1918
42.30 79.94	And raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.  Spur, slopes N. Desc. 390 ft.  The cor. ofsecs. 29, 30, 31 and 32.  Land, rolling and mountainous.  Soil, rocky, 4th rate.  No timber:  Undergrowth, greasewood, palo verde and cactus.
-	
40.00 79.11	West on a random line, bet. secs. 30 and 31.  Set temp. 2 sec. cor.  Intersect W. bdy. of Tp., 9 lks. N. of the cor. of secs.  25, 30, 31 and 36, hereinbefore described.  Thence
39.11	N.89456 E., on a true line, bet. secs. 30 and 31.  Over level land, through dense undergrowth.  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ‡ sec. cor., marked on brass cap
	1 S30
	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.
79.11	The cor. of secs. 29, 30, 31 and 32.  Land, level.  Soil, gravelly and sandy clay, 2nd and 3rd rates.  No timber.  Undergrowth, greasewood, mesquite.
	Sparse growth of grass.
40.00	N.0°3'W., bet. secs. 29 and 30.  Over level land, through dense undergrowth.  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
	s30 s29 1918
78.40	Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist.  Dim road, brs. NW. and SE.  Road, brs. NE. and SW.  Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, marked on brass cap  T13S R6W
	si9 s20 s30 s29 1918
*	Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist. Land, level. Soil, sandy and gravelly, 2nd and 3rd rates. No timber.
1	Undergrowth, greasewood and mesquite.

34

Survey of the Subdivision of T. 13 S., R.6Wchains. East on a random line, bet. secs. 20 and 29. Set temp. ½ sec. cor. Intersect N. and S. line, 14 lks. N. of the cor. of secs. 40.00 80.01 20, 21, 28 and 29. Thence N.89°54'W., on a true line, bet. secs. 20and 29.

Over level land, through dense undergrowth.

20.50 Wash, 25 lks. wide, 2 ft. deep, course SE.

Wash, 30 lks. wide, 4 ft. deep, course SE.

Wash, 20 lks. wide, 4 ft. deep, course SE.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for t sec. cor. marked on brass cap ground, for  $\frac{1}{4}$  sec. cor., marked on brass cap Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. 52.60 64.50 79.10 80.01 Wash, 12 lks. wide, 3 ft. deep, course S.20°E. Road, brs. NE. and SW.
The cor. of secs. 19, 20, 29 and 30.
Land, level. Old road, brs. NW. and SE. Soil, sand y and gravelly clay, 2nd rate. No timber. Undergrowth, mesquite and greasewood. West on a random line, bet. secs. 19 and 30. Set temp. 1 sec. cor. Intersect W. bdy. of Tp., 14 lks. N. of the cor. of secs. 40.00 78.91 19, 24, 25 and 30, hereinbefore described. Thence N.8954'E., on a true line, bet. secs. 19 and 30. Over level land, through dense undergrowth. Old road, brs. NE. and SW. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 20.10 38.91 ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist. 78.91 The cor. of secs. 19, 20, 29 and 30. Land, level. sandy and gravelly clay, 2nd rate. No timber. Undergrowth, greasewood and mesquite. N.0°3'W., bet. secs. 19 and 20. Over level land, through dense undergrowth. Road, brs. N.60°E. and S.60°W. 21.20 Wash, 10 lks. wide, 3 ft. deep, course SE. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the 36.60 40.00 ground, for ‡ sec. cor., marked on brass cap S19 S20 Dig pits, 18 X 18 X 12 ins., N. and S. of post, 3 ft. dist. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, marked on 80.00

brass cap

	BOOK 0000
•	Survey of the Subdivision of T. 13 S. R. 6 W. 35
Chains.	T13s /R6W
	Dig pits, 18 X 18 X 12 ins., in each sec., $5\frac{1}{2}$ ft. dist. Land, level.  Soil, sandy and gravelly, 2nd and 3rd rates.  No timber.  Undergrowth, greasewood and mesquite.
-	
40.00 79.95	East on a random line, bet. secs. 17 and 20.  Set temp. 1 sec. cor.  Intersect N. and S. line, 7 lks. N. of the cor. of secs.  16, 17, 20 and 21.  Thence
30.55	N.89\$57'W., on a true line, bet. secs. 17 and 20.  Over level land, through dense undergrowth.  Road, brs. NE. and SW.  Wash, 20 lks. wide, 3 ft. deep, course S.  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \$\frac{1}{4}\$ sec. cor., marked on brass cap
	1 S17 520 1918
60.55 74.50 79.95	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.  Wash, 60 lks. wide, 2 ft. deep, course S.15°E. Old road, brs. NW. and SE. The cor. of secs. 17, 18, 19 and 20. Land, level. Soil, sandy and gravelly, 2nd and 3rd rates. No timber. Undergrowth, greasewood and mesquite.
40.00 78.82	Vest on a random line, bet. secs. 18 and 19 Set temp. ‡ sec. cor. Intersect W. bdy. of Tp., 22 lks. N. of the cor. of secs. 13, 18, 19 and 24, here inbefore described. Thence
38.10 38.82	N.89451'E., on a true line, bet. secs. 18 and 19.  Over level land, through dense undergrowth.  Wash, 50 lks. wide, 6 ft. deep, course S.  Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1 sec. cor., marked on brass cap
	1 518 2 519 1918
78.82	Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft. dist.  The cor. of secs.17, 18, 19 and 20. Land, level. Soil, sandy and gravelly, 2nd rate. No timber. Undergrowth, greasewood and mesquite. Fair growth of grass.
40.00	N.0°3'W., bet. secs.17 and 18. Overlievel land, through dense undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the

Survey of the Subdivision of T. 13 S., R. 6 W.

```
36
   nains.
                       ground, for \( \frac{1}{4} \) sec. cor., marked on brass cap
                                                            1918
                       From which
                              A mesquite, 8 ins. diam., brs. S.65°E.,
55 lks. dist., marked $$17 BT.
A mesquite, 10 ins. diam., brs. N.36°W.,
                Wash, 50 lks. wide, 3 ft. deep, course SE.
Wash, 15 lks. wide, 2 ft. deep, course SW.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, marked on brass cap
    41.10
    69.80
    80.00
                                                        T135 R6E
                      Dig pits, 18 X 18 X 12 ins., in each sec., 5\frac{1}{2} ft. dist.
                 Land, level.
                 Soil, sandy and gravelly clay, 2nd rate.
                 No timber.
                 Undergrowth, palo verde, greasewood and mesquite.
                East on a random line, bet. secs.8 and 17.
Set temp. 1 sec. cor.
Intersect N. and S. line, 5 lks. N. of the cor. of secs.
8, 9, 16 and 17.
    40.00
    79.93
                 Thence
                 N.89°58'W., on a true line, bet. secs. 8 and 17. Over level land, through dense undergrowth.
    Wash, 20 lks. wide, 3 ft. deep, course S.
30.95 Wash, 15 lks. wide, 2 ft. deep, course S.10°W.
39:96 Set an iron post, 3 ft.long, 1 in. diam., 26 ins. in the ground, for 1/2 sec. cor., marked on brass cap
                                                          $ 8
$ $17
1918
                      Dig pits, 18 X 18 X 12 ins., E. and W. of post, 3 ft.
                      dist.
                Wash, 25 lks. wide, 2 ft. deep, course S.15°W. Wash, 12 lks. wide, 2 ft. deep, course S. The cor. ofsecs .7, 8, 17 and 18.
    46.55
    79.93
                 Land, level.
                 Soil, sandy, gravelly and rocky, 3rd rate.
                 No timber.
                 Undergrowth, greasewood, mesquite and palo verde.
                West on a random line, bet. secs. 7 and 18.

Set temp. ½ sec. cor.

Intersect W. bdy. of Tp., 22 lks. N. of the cor. of secs.

7, 12, 13 and 18, hereinbefore described.
    40.00
    78.79
                 Thence
                 N.89°51'E., on a true line, bet. secs. 7 and 18. Over level land, through dense undergrowth.
     9.20
```

Wash, 15 lks. wide, 2 ft. deep, course S.
Wash, 25 lks. wide, 2 ft. deep, course S.
Set an ironpost, 3 ft. long, 1 in. diam., 16 ins. in the ground, in a mound of earth and stone, for 1 sec. cor., 27.40 38.79 marked on brass cap

	G10 0000 0000 0	f the Subdivision of Township 13 South Range 6 West. 3
	Chains.	
		1 S 7 4 S 18 1918
		1918
	<b>5</b> 1.20 78.79	Dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist. Wash, 30 lks.wide, 4 ft. deep, course S. The cor. of secs. 7,8,17 and 18.
		Land, level. Soil, gravelly and rocky, 3rd rate. No timber. Undergrowth, greasewood, mesquite, cactus, palo verde and
		ironwood.
		***************************************
	17.40 40.00	N.0° 3'W., bet.secs. 7 and 8. Over level land, thru.dense undergrowth. Wash, 12 lks.wide, 1 ft. deep, course SE. Set an iron post, 3 ft.long, 1 in. in diam., 26 ins. in the ground, for \(\frac{1}{2}\) sec.cor., marked on brass cap,
		s 7 s 8
		1918
		and raise a mound of stone, 2 ft. base, 2 ft. high, w. of
	53.70 80.00	Wash, 15 lks. wide, 3 ft. deep, course SW. Set an iron post, 3 ft. long, 2 ins. in diam., 10 ins.in the ground, in a mound of stone, for cor. of secs. 5, 6, 7 and 8, marked on brass cap.
		T13s R6w s 6 s 5 s 7 s 8 1918
		and raise a mound of stone, 3 ft.base, 2 ft.high, w. of cor. Land, level.
		Soil, gravelly and rocky, 3rd rate.
-		Undergrowth, greasewood, mesquite, catclaw, palo verde, iron- wood and cactus.
	•	
	40.00 79.77	East, on a random line, bet. secs. 5 and 8.  Set temp. sec.cor.  Intersect N. and S. line, 2 lks.S. of the cor. of secs.4,5.
		Thence, s.89°59'W., on a true line, bet. secs.5 and 8.
	9.65 4.05	Over level land, thru.dense undergrowth.  Wash, 15 lks.wide, course S.  Wash, 16 lks.wide, course S. Ascend gradually 75 ft.
	25. 20 37. 55 39. 30 39. 88½	Low ridge, brs. N. and S. Descend gradually 75 ft.  Wash, 12 lks.wide, course Sw.  Same wash, 12 lks.wide, course N.80°W.  Set an iron post 3 ft.long, 1 in. in diam., 26 ins. in the ground, for 4 sec.cor., marked on brass cap.
	•	- <u>48 5</u> 8 8 1918
		and raise a mound of stone, 2 ft. base, 2 ft.high, N
	43.85	of cor. Wash, 12 lks.wide, course S. 80°W.

```
38 Survey of the Subdivision of Township 13 south Range
    Chains.
     50.10
                 wash, 25 lks.wide, course S.
                 wash.40 lks.wide, course 5.20° W. The cor. of secs. 5, 6, 7 and 8.
    70.60
     79.77
                 Land, level and rolling.
Soil, sandy, gravelly and rocky, 2nd and 4th rate.
                 No timber.
                 Undergrowth, palo verde, mesquite, ironwood, greasewood and
                      cactus.
                west, on a random line, bet. secs.6 and 7.

Set temp. 2 sec.cor.

Intersect w bdy.of Tp. 14 lks.N.of the cor.of secs.1,6,

7 and 12, hereinbefore described.
    40.00
    78.73
                Thence, N.89°54'E., on a true line, bet.secs.6 and 7. Over level and rolling land, thru.dense undergrowth.
                 Wash,4 lks.wide. course N. Ascend.
Top of ridge, NE. and S 70° W.
Set an iron post, 3 ft.long, 1 in. in diam., 26 ins.in the ground, for 4 sec.cor., marked on brass cap,
    4.70
23.70
38.73
                Dig pits, 18x18x12 ins., E.and W. of post, 3 ft. dist. Wash, 12 lks.wide, course S. Wash, 16 lks.wide, course SW. Wash, 12 lks.wide, course S.15° W. The cor.of secs.5, 6, 7 and 8. Land, level and rolling.
    49.35
55.34
71.45
78.73
                 Soil, gravelly and rocky, 2nd and 4th rates. No timber.
                 Undergrowth, mesquite, palo verde, greasewood, rosin
                      brush and cactus.
                N.0°3'W., on a random line, bet. secs. 5 and 6.
Set temp. 2 sec.cor.
Intersect N.bdy.of Tp., ll lks.E.of the cor. of secs. 5,6,
31 and 32, hereinbefore described.
     40.00
     79.86
                 Thence,
                 S.0°8'E., on a true line, bet. secs. 5 and 6.
Over level and gently rolling land, thru.dense undergrowth.
      8.80
                 wash. 60 lks. wide, course w.
                Top of ridge, NE. and SW.
Set an iron post 3 ft.long, 1 in. in diam. 26 ins. in the ground, for 4 sec.cor., marked on brass cap.
    11.96
39.86
                                                        s 6 s 5
                                                          1918
                      and raise a mound of stone, 3 ft. base, 2 ft.high, W.
                      of cor.
                Wash, 12 lks.wide, course S, 10°W. The cor. of secs. 5, 6, 7 and 8. Land, level and gently rolling.
     48.05
     79.86
                 Soil, gravelly and rocky, 2nd and 4th rates.
                 No timber.
                 Undergrowth, palo verde, mesquite, ironwood, greasewood,
                      rosin brush and cactus.
```

#### Boundaries of T. 13 S., R. 6 W.

	Latitudes, dep	artures	and cl	sing e	rrors.	
						rtures
signated.	True bearing.	Dist.	N.	s.	E.	W.
The same of the sa	and the second s	chs.	chs.	chs.	chs.	chs
oundary.	s.89°59'w.	479.12		.14		479.1
undary.	North.	480.00	480.00			·
oundary.	East	478.55		A house, i may make i hadin samma kandid ku asamar (samilanni).	478.55	
undary.	South.	480100		480.00		
ency.					.46	
			480.00	480.14	479.01	479.1
The second of th			Property Character Construction of the Constru	480.00		479.0
in latitude14						
						.1
	oundary.  oundary.  oundary.  oundary.  ency.	oundary. S.89°59'W.  oundary. North.  oundary. East  oundary. South.  ency.	algnated. True bearing. Dist. chs. coundary. S.89°59'W. 479.12 undary. North. 480.00 coundary. East 478.55 undary. South. 480.00 cency.	Intitude.  Latitude.  Latitude.  Dist.  Chs. Chs. Chs. Chs. Chs. Chs. Chs. Ch	### True bearing. Dist. N. S. chs. chs. chs. chs. chs. chs. chs. chs	### Argusted

#### GENERAL DESCRIPTION.

This township is level, rolling and mountainous. Soil, lst, 2nd and 4th rate. Surface covered with greasewood, palo verde, mesquite and scattering ironwood. Very little native grass; dense growth of cholla, ocotilla, and giant cactus.

No settlers. There are mining prospects in the north half of the township.

4--680

BOOK 3350

### For FIELD ASSISTANTS. to Loyd E. Sechrist,

See Book "C"					
NAMES.	CAPACITY.				
·					
·					
·					
·					

### CERTIFICATE OF UNITED STATES SURVEYOR

I. Loyd E. Sechrist, U. S. Surveyor General, for Group 54, Arizona, bearing date of the 12th day of July, 1917, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the North boundary and Subdivision Lines of Township 13 South, Range 6 West, of the Gila and Salt River Base & Meridian, in the State of Arizona, which are represented in and by disgram on page 1 hereof the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, Group 84, Arizona, and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.  St. Machaela Arizona  APPROVAL:  Obvious or this United States (Surveyor General, Original States Surveyor General, Original States Surveyor General, 1980  The foregoing field notes of the curvey of the United States Surveyor General, 1980  The foregoing field notes of the curvey of the curvey of the corners of the United States Surveyor General, 1980  The foregoing field notes of the curvey of the
bearing date of the 12th
in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the North boundary and Subdivision Lines of Township 13 South, Range 6 West,  of the Gila and Salt.  River Base & Meridian, in the State of Arizona, which are represented in and by diagram on page / herzef the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for Group 84, Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.  St. Michaels Arig.  Approval.  Other of the United States of Parts Surveyor General, 191
North boundary and Subdivision Lines of  TOWNSHIP 13 SOUTH, RANGE 6 WEST,  of the Gila and Salt  River Base & Meridian, in the State of Arizona, which are represented in and by diagram on page 1 hereof the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for
North boundary and Subdivision Lines of  TOWNSHIP 13 SOUTH, RANGE 6 WEST,  of the Gila and Salt  River Base & Meridian, in the State of Arizona, which are represented in and by diagram on page / hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S. Surveyor General, for
North boundary and Subdivision Lines of  TOWNSHIP 13 SOUTH, RANGE 6 WEST,  of the Gila and Salt  River Base & Meridian, in the State of Arizona, which are represented in and by diagram on page / hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S. Surveyor General, for
TOWNSHIP 13 SOUTH, RANGE 6 WEST.  of the Gila and Salt  River Base & Meridian, in the State of Arizona, which are represented is and by diagram on page I hereof the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for
of the Gila and Salt  River Base & Meridian, in the State of Arizona, , which are represented is and by diagram on page / hereof the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for
of the Gila and Salt  River Base & Meridian, in the State of Arizona, which are represented is and by diagram on page I hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S. Surveyor General, for
of the Gila and Salt  River Base & Meridian, in the State of Arizona, which are represented is and by diagram on page I hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U.S. Surveyor General for
River Base & Meridian, in the State of Arizona, which are represented in and by diagram on page I hereof the foregoing field notes a having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for
the foregoing field notes/as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General, for
said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the U. S. Surveyor General for
tions, and the special written instructions of the U. S. Surveyor General for
and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.  St. Michaels, Ang,  Joyd E. Hechust  U. S. Surveye  Transitma  APPROVAL.  OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
St. Michaels, Arg.  Joyd E. Gehust.  U.S. Surveyo  Transitma  APPROVAL.  OFFICE OF THE UNITED STATES SURVEYOR GENERAL,  191
St. Michaels, ang, Joyd E. Glechrist.  June 4, 1920  ———————————————————————————————————
APPROVAL.  OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
<del></del>
, <del>191-</del>
-The foregoing field notes of the survey of -
The foregoing field notes of the survey of .
-The foregoing need notes of the survey of s
· ·
<u></u>
executed by
under his special instructions dated, 191 -, having become
critically examined, and the necessary corrections and explanations made, the said field notes, and the survey they describe, are hereby approved.
U.S. Surveyor Genera
I certify that the foregoing transcript of the field notes of the above-described surveys in
, has been correctly copied from the original notes on file in this office.

BOOK 3350

4--680

# For FIELD ASSISTANTS. to Wm. H. Thorn,

See Book "A."						
NAMES.	CAPACITY.					
	•					
	•					
1	•					
<u> </u>	,					
<del></del>						

#### CERTIFICATE OF UNITED STATES SURVEYOR.

44 <sub>2350</sub>	<del></del>
William Harhom, U.S. Surv	reyor, hereby certify upon honor that, in pursuance
of special instructions received from the U. S. Surveyor Ge	neral, for Group 84, Arizona,
bearing date of the 12th day of July,	, 1917, I have well, faithfully, and truly
in my own proper person, and in strict conformity with sa	aid instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, surveyed all those	parts or portions ofthe
West boundary and Subdivision lines of	
TOWNSHIP 13 SOUTH, RANG	e 6 west.
	of the Gila and Salt
River Base and Meridian, in the State ofAris	The second secon
and by diagram on page / hereof the foregoing field notes as having been executed by me, a	
said survey have been established and perpetuated in strict	
tions, and the special written instructions of the U.S. Sur	
and in the specific manner described in the field notes, an	,
•	
Phoenix, Arizona,	William H. Phorn
June 8, 1920.	U. S. Surveyor.
APPROV	AL.
Office of the	United States Surveyor General,
Phoenix,	Arizona, June 18, 1920,
The foregoing field notes of the survey of _the	
West and North boundaries, and	·
Subdivision lines of	
TOWNSHIP 13 SOUTH,	RANGE 6 WEST,
of the Gila and Salt River Base and	Meridian, in the State of Arizona
executed by WH.H.Thorn, U.S.Surveyor, and L	oyd E.Sechrist, U.S. Transitman,
under instructions dated July 12,1917,	for Group 04. Arizone , having been
critically examined, and the necessary corrections and explanation and explanation are bounded as a superior of the second secon	anations made, the said field notes, and the surveys
they describe, are hereby approved.	Strand Fort
	U. S. Surveyor General.
I certify that the foregoing transcript of the field notes	of the above described surveys in
, has been correctly copi	ed from the original notes on file in this office.