MAR 2: 1923 APR 6192

ৰ, 3543

BOOK 3543

FIELD NOTES

OF THE SURVEY OF THE

North bour	ndary, and
Part of S	ubdivision lines (Completion)
	o f
<u> </u>	
••••	TOWNSHIP 25 NORTH, RANGE 10 WEST,
·	(within the Hualpai Indian Reservation)
	·
In the State	ofArizona.
In the State	ofArizona.
	EXECUTED BY
	Horace II. Muscott and Francis R. Ihrie,
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	U.S. Transitmen,
In the capaci	ty of U.S. Surveyor S., under Special Instructions dated Fabruary 26, 1
•	
_	e United States Surveyor General to govern surveys included in G
No. 108, Ari	2012, which were approved by the Commissioner of the General I
Office, March	1920, and Assignment Instructions dated August 7, 19

,,*

Township Range

14 - 14 - 1640

- Surveys commenced Aug. 17, 1920 and executed with Young and Sons Light Mountain transit No. 8489 and Buff Rocky Mountain Favorite transit No. 9977; the instruments are equipped with full vertical circle and the Smith Solar attachment; unless otherwise specified, all azimuth determinations are accomplished with the solar attachment.
- Field test of Young and Sons light mountain transit No. 8489.
- August 22, 1920. I examine the adjustments of the instrument, and correct all errors; then, to test the solar apparatus, by comparing its indications from observations made during a. m. and p. m. hours with a meridian established by Polaris observation, I proceed as follows:
- In camp near the NW. cor. of Sec. 35, T. 25 N., R. 10
 W., G. and S. R. B. and M., Arizona, lat. 35° 30½' N.,
 long. 113° 19½' W., at 9 hrs. 0 m., a. m., 1. m. t.,
 I set off 35° 30½' N. on the lat arc; 11° 45' N., on
 the decl. arc; and determine a meridian with the solar,
 which agrees with the meridian established by observations on Polaris on August 17, as described in Book "A".
- At apparent noon, with the lat. arc unchanged, I observe the Sun on the meridian; the resulting reading of the decl. arc is 11° 42½' N., which agrees with the computed decl. of the Sun.
- At 3 hrs. 0 m., p. m., l. m. t., with the lat. arc unchanged, I set off 11° 40' N. on the decl. arc; and determine a meridian with the solar which agrees with the true meridian.
- As all of the solar observations during the usual hours of solar work come within 1'30" of the true meridian, I conclude that the adjustments of the instrument are satisfactory.
- Unless otherwise specified, all measurements are made with a 5 ch. Lufkin steel tape, compared with a Lufkin standard steel tape and found correct. The measurements are made on the slope, the vertical angle determined and the slope measurements properly reduced to true horizontal distances.
- Field test of Buff Rocky Mountain Pavorite transit No. 9977.
- August 29, 1920. In camp near the N. W. cor. of sec. 35, T. 25 N., R. 10 W., G. and S. R. B. & M., Arizona, lat 35° 30½' N., long. 113° 19½' W., I examine the adjustments of the instrument, and correct all errors; then, to test the solar apparatus, by comparing its indications from observations made during a. m. and p. m. hours with a meridian established by Polaris observations, proceed as follows:
- At 9 hrs. 0 m., a. m., l. m. t., I set off 35° 30½' N. on the lat. arc; 9° 19½' N. on the decl. arc; and determine a meridian with the solar, which agrees with the meridian established by observations on Polaris on August 17, as described in Book "A".
- At apparent noon, with the late are unchanged, I observe the sun on the meridian; the resulting reading of the decle are is 9° 16½ No, which agrees with the computed decle of the sun.

- At 3 hrs. 0 m., p. m., l. m. t., with the lat.arc unchanged I set off 9° 14' N., on the decl. arc; and determine a meridian with the solar, which agrees with the true meridian.
- As all of the solar observations during the usual hours of solar work come within 1' 30" of the true meridian, I conclude that the adjustments of the instrument are satisfactory.
- Unless otherwise specified, all measurements are made with a 5 ch. Lufkin steel tape compared with a Lufkin standard steel tape and found correct. The measurements are made on the slope, the wertical angle determined and the slope measurements properly reduced to true horizontal distances.

```
3843
           West Boundary of T 25 N., R. 10 West.
               From the Standard cor. of Ts. 25 N., Rs. 10 and 11 W.,
Chains
              described in Book "A".,
North, bet. secs. 31 and 36.
              Over rolling land, thru scattering timber and undergrowth.
              Asc. 40. ft. to
Desc. 30 ft. to
25.00
30.00
              Asc. 57 ft. over S. slope to .
35.00
              Set an iron post, 3, ft. long, 1 in. in diam., 26 ins. in
40.00
                   the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap
                                                   S 36 T S 31
                                                          1920
              A juniper, 8 ins. in diam., bears S. 74° E., 8

lks. dist. marked ½ S 31 B T.

A pine, 10 ins. in diam., bears S. 53½° W., 75

lks. dist., marked ½ S 36 B T.

Continue ascent 16 ft. over S. slope to

Low ridge, bears E. and W. Desc. 200 ft. over broken

N. slope to

Thence along W. Slope
                  From which
42.30
               Thence along W. slope
60.00
               Set an iron post, 3 ft. long, 2 ins. in diam., in a mound
80.00
              of stone, for cor. of secs. 25, 30, 31 and 36, marked
                  on brass cap
                                                       T 2,5 N
                                           R 11 W R 10 W
S 25 | S 30
                                                   S 36 S 31
                                                        1920
                  From which
                          A pine, 6 ins. in diam., bears N. 36° E., 162
lks. dist. marked T 25 N R 10 W S 30 B T.
A pine, 8 ins. in diam., bears S. 32° E., 180
lks. dist. marked T 25 N R 10 W S 31 B T.
                          A cedar, 8 ins. in diam., bears S. 60% W., 141
lks. dist. marked T 25 N R 11 W S 36 B T.
A cedar, 6 ins. in diam., bears N. 18% W., 230
lks. dist. marked T 25 N R 11 W S 25 B T.
              Land; rolling.
              Soil; rocky, 4th rate.
              Timber; scrub pine and, cedar.
              Undergrowth; chamiso, sagebrush and cactus.
              North, bet. secs. 25 and 30.
              Over rolling land, thru scattering timber and undergrowth
              Along W. slope. Desc. 200 ft.
10.00
             Spur, slopes NW. Desc. 85 ft. over N. slope to Wash, 20 lks. wide, 2 ft. deep, course N. 10° E. Spur, slopes E. Desc. 240 ft. to Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for \( \frac{1}{4} \) sec. cor., marked on brass cap
20.00
23.00
28.00
40.00
                                                   S 25 TS 30
1920
                  From which
                           A cedar, 6 ins. in diam., bears N. 9½° E., 167
lks. dist., marked ½ S 30 B T.

A cedar, 12 ins. in diam., bears S. 79½° W., 137
lks. dist. marked ½ S 25 B T.
```

6.

15.00 40.00

43.10

```
BOOK 3543
         West Boundary of Township 25 North, Range 10 West.
            Desc. 90 ft. over rolling N. slope.
Chains
            A. T. & S. F. R. R. right of way fence brs. E. & W. Telegraph line, bears E. and W.
69.40
69.80
            Wash, 60 lks. wide, 10 ft. deep, course W. A. T. & S. R. R. R. brs. E. to Nelson and west to Peach
70.00
71.00
               Springs.
         telegraph line brs. E. and W.
71.80
            Old Trails National Highway, bears E. to Nelson and W.
72.60
               to Peach Springs.
            Asc. 115 ft. over S. slope.
Mark a cross (X) on surface rock at exact cor. point and
74.00
80.00
               over same, set an iron post, 3 ft. long, 2 ins. in
                diam. supported in a mound of stone, for cor. of secs.
               19, 24, 25 and 30, marked on brass cap
                                                T 25 N
                                         R 11 W | R 10 W
S 24 | S 19
                                            S 25 S 30
                                                 1920
                From which
                       Which
A pine, 18 ins. in diam., bears N. 82° E., 37
lks. dist. marked T 25 N R 10 W S 19 B T.
A pine, 6 ins. in dia., bears S. 14½° E., 70 lks.
dist., marked T 25 N R 10 W S 30 B T.
A pine, 10 ins. in diam., bears S. 11½° W., 77
lks. dist. marked T 25 N R 11 W S 25 B T.
A pine, 8 ins. in diam., bears N. 67½° W., 196
lks. dist. marked T 25 N R 11 W S 24 B T.
            Land; rolling mountainous. Soil; rocky, 4th rate.
             Timber; pinyon and cedar.
            Undergrowth; sagebrush and chamiso.
```

North, bet. secs. 19 and 24. Over mountainous land, thru scattering timber and undergrowth. Asc. 200 ft. over SE. slape to Spur, slopes Sw. Desc. 263 ft. over NW. slope. Set an iron post, 3 ft. long, 1 in., in diam., 6 ins. in the ground to bed rock, supported in a mound of stone, for 4 sec. cor., marked on brass cap:

S 24 TS 19

From which A pine, 8 ins. in diam., bears S. 192° E., 49
lks. dist. marked ½ S 19 B T.

A pine, 8 ins. in diam., bears S. 842° W., 116
lks. dist. marked ½ S 24 B T.

Continue descent 40 ft. to
Canyon, course SW. Asc. 200 ft. over S. slope to
Spur. slopes E. Desc. 52 ft.

56.00 Spur, slopes E. Desc. 52 ft. to
61.50 Brain, course SE. Asc. 150 ft.
80.00 Set an iron post, 3 ft. long, 2 ins. in diam., in a mound of stone, for cor. of secs. 13, 18, 19 and 24, marked on brass cap

> T 25 N R 11 W R 10 W S 13 S 18 , S 24 - S 19 -1920

From which

25/2 West Boundary of Township 25 North, Range 10 West. A cedar, 8 ins. in diam., bears N. 263° E., 91
lks. dist. marked T 25 N R 10 W 5.18 B T.

A pine, 10 ins. in diam., bears S. 13° E., 129
lks. dist. marked T 25 N R 10 W S 19 B T.

A cedar, 12 ins. in diam., bears S. 473° W., 171
lks. dist. marked T 25 N R 11 W S 24 B T.

A pine, 12 ins. in diam., bears N. 533° W., 67
lks. dist. marked T 25 N R 11 W S 13 B T.

sountainous. Chains Land; mountainous. Soil; rocky, 4th rate. Timber, scrub pine and cedar. Undergrowth; chamiso, sagebrush and cactus. North, bet. secs. 13 and 18. Over rolling land, thru scattering timber and undergrowth Road, brs. W. to Peach Springs and E. to Blue Mountain Tank and Seligman. Asc. 150 ft. over rolling S. slope to Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, with stone marked cross (X) at base of post, 22.20 40.00 for 4 sec. cor., marked on brass cap S 13 T S 18 Asc. 50 ft. over S. slope to 45.00 Spur, slopes S. 20° E. Thence along E. slope. Desc. 85 ft. over NE. slope. Asc. 165 ft. over SE. slope to 60.00 65.00 Set an iron post, 3 ft. long, 2 ins. in diam., in a mound of stone, for cor. of secs. 7, 12, 13 and 18, 80.00 marked on brass cap T 25 N R 11 W | R 10 W S 12 | S 7 S 13 | S 18 1920 From which A cedar, 8 ins. in diam., bears N. 54° E., 142 lks.

dist., marked T 25 N R 10 W S 7 B T.

A pine, 12 ins. in diam., bears S. 693° E., 211 lks.

dist. marked T 25 N R 10 W S 18 B T.

A pine, 16 ins. in diam., bears S. 28° W., 85 lks.

dist. marked T 25 N R 11 W S 13 B T.

A cedar, 8 ins. in diam., bears N. 593° W., 103 lks.

dist. marked T 25 N R 11 W S 12 B T. Lana; rolling. Soil, rocky, 4th rate. Timber; scrub pine and cedar. Undergrowth; chamiso, sagebrush and cactus. North, bet. secs. 7 and 12. Over rolling land, thru scattering timber and undergrowth. Along E. slope. 10.00 Desc. 100 ft. over NE. slope. 25.00 Desc. 180 ft. over N. slope. Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for 4 sec. cor., marked on brass cap 40.00

```
West Boundary of Township 25 North, Range 10 West.
Chai ns
            From which
              A pine, 5 ins. in diam., bears S. 574° E., 23 lks. dist. marked 2 S 7 B T.
              A pine, 6 ins. in diam., bears S. 8° W., 129 lks. dist.
                  marked 🗦 S 12 B T.
            Desc. 255 ft. over N. slope.
            Canyon, course NE. Asc. 90 ft. to
61.00
            Set an iron post, 3 ft. long, 2 ins. in diam., in a mound of stone, for cor. of secs. 1, 6, 7 and 12, marked on
80.00
               brass cap
                                               T 25 N
                                        R 11 W R 10 W
S 1 S 6
                                            S 12 | S 7
                                                1920
              From which
                      A pine, 8 ins. in diam., bears N. 582° E., 49
lks. dist. marked T 25 N R 10 W S 6 B T.
                      A pine, 8 ins. in diam., bears S 374 E., 49
lks. dist. marked T 25 N R 10 W S 7 B T.

A pine, 10 ins. in diam., bears S. 563 W., 151
lks. dist., marked T 25 N R 11 W S 12 B T.

A pine, 10 ins. in diam., bears N. 44 W., 109
lks. dist. marked T 25 N R 11 W S 1 B T.
           Land; rolling.
           Soil; rocky, 4th rate. Timber; scattering cedar and pine.
            Undergrowth; chamiso and cactus.
           North, bet. secs. 1 and 6.
            Over rolling land, thru scattering timber and undergrowth
            Asc. 40 ft. to
            Desc. 45 ft.
 5.00
            Ravine, course NE. Asc. 55 ft., over rolling land.
16.50
           Desc. 75 ft.
23.20
            Asc. 25 ft.
28.20
33.20
            Desc. 65 ft.
            Asc. 35 ft.
36.35
            Set an iron post, 3 ft. long, 1 in in diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for 2 sec. cor., marked on brass cap
40.00
                                          , S 1 T S 6
                                                1920
               From which
                      A pinyon 8 ins. in diam., bears N. 55° E., 59 lks. dist. marked ½ S 6 B T.
           A pinyon, 16 ins. in diam., bears N. 35° W., 83 iks. dist. marked & S 1 B T.

Desc. 150 ft. over N. slope.
            Rim of canyon, bears SE. and NW. Desc. 300 ft. to
58.70
         Bottom of canyon, course NW. Asc. over gradual SW.slope.
76.00
           Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground for cor. of Ts. 25 and 26 N., Rs. 10 and 11 W., marked on brass cap
80.00
                                                 T 26 N
                                         R 11 W | R 10 W
                                              S 36 | S 31
                                               S 1 | S 6
                                                 T 25 N
                                                  1920
```

For a dead

West Boundary of Township 25 North. Range 10 West.

Chains

From which ...

M which.

A pine, 10 ins. in diam., bears N. 272° E., 247

lks. dist. marked T 26 N R 10 W S 31 B T.

A pine, 12 ins. in diam., bears S. 50° E., 375

lks. dist. marked T 25 N R 10 W S 6 B T.

A pine, 12 ins. in diam., bears S. 443° W., 469

lks. dist. marked T 25 N R 11 W S 1 B T.

A pine, 10 ins. in diam., bears N. 372° W., 368

lks. dist. marked T 26 N R 11 W S 36 B T.

Land; rolling, drains NE.
Soil; rocky, 4th rate.
Timber; scattering scrub cedar and pine. Undergrowth; sagebrush, chamiso and cactus.

North Boundary of Township 25 North, Range 10 West. From the cor. of Ts. 25 and 26 N., Rs. 9 and 10 W., described in field notes of current group 107. Chains West, on a random line, along the N. Bdy. of T. 25 N.,
R. 10 W., setting temp. 1 sec. and sec. cors. at intervals
of 40.00 chs.; and at 479.35 chs. fall 30 lks. N. of
the cor. of Ts. 25 and 26 N., Rs. 10 and 11 W., herein-The falling answers to a correcbefore described. tion of 0° 02' or 5 lks. S. per mile, counting from the N. E. cor. of Tp. . Therefore from cor. of Ts. 25 and 26 N., Rs. 10 and 11 W N. 89° 58' E., on a true line bet. secs. 6 and 31. Over mountainous land, thru scattering timber and undergrowth. Asc. 710 ft. over steep W. slope. Set an iron post, 3 ft. long, l in. in diam., 5 ins. in 39.35 the ground to bed rock, supported in a mound of stone, for 4 sec. cor., marked on brass cap \$\frac{\S 31}{\S 6} From which A pine, 6 ins. in diam., bears N. $44\frac{1}{2}^{\circ}$ W., 70 lks. dist. marked 4 S 31 B T. A pine, 14 ins. in diam., bears S. 542° W., 82 lks. dist. marked 4 S 6 B T.

Continue asc. 130 ft. over NV. slope.

Ridge, bears NE. and SW. Desc. 130 ft. over SE. slope to Mark a cross (X) on surface rock at exact cor. point and 57.35 79.35 over same set an iron post, 3 ft. long, 2 ins. in diamsupported in a mound of stone, for cor. of secs. 5, 6, 31 and 32 marked on brass cap T 26 N | R 10 W S 31 S 33 S 6 S 5 T 25 N 1920 Land; rolling. Soil; rocky, 4th rate. Timber; scrub cedar. Undergrowth; sagebrush and chamiso. N. 89° 58' E., on a true line bet. secs. 5 and 32. Over rolling land, thru scattering timber and undergrowth Desc. 210 ft. over NE. slope. Wash, 30 lks. wide, course NW., asc. 20 ft. to 36.50 Mark a cross (X) on surface rock at exact cor. point, and over same set an iron post 3 ft. long, 1 in. in diam., supported in a mound of stone, for \(\frac{1}{4} \) sec. cor., 40.00 marked on brass cap 1920 Continue ascent 100 ft. over rolling SW. slope. Thence over level land. Asc. 80 ft. to cor. 55.00 70.00 Mark a cross (X) on surface rock at exact cor. point, 80.00 and over same set an iron post, 3 ft. long, 2 ins. in diam., supported in a mound of stone, for cor. of secs.

4, 5, 32 and 33, marked on brass cap

T 26 N R 10 W S 32 S 33

S 5 S 4 T 25 N 1920 Book "C"

Group 108 - Arizona.

BOOK 3543

Township 25 North, Range 10 West.

INDEX DIAGRAM.

T	1		1	1	ļ		l I	1	1	1	ļ	ī				1 a a	
	10			10		17		Ļ	11			12			13		* Thirests
8	6	4	4	5	3	5 4	. 2	9	3	2	3	2	1	8	1		
	4.5			43		35			29			22	-		17		
1	.*		-		-	e t					-		1				
7	7	4	3	8	3	4. Ś	2	8	10	2	2	11	1	7	12	e e e e e e e e e e e e e e e e e e e	
	42			42		34			28			22			17	,	
7	18	4	1	17	35	- 16	2	7	15 ,	2	1	14	1	6	13		
	40			40		33	;		26			21			16	Control and Control	
6	1 9 39	- 3	9	20 	3	2 21		6	2 2 25	2	0	23	ı	5	24		
		_				V4		F		7 -	-		14	~-~	11/2	(III)	114
5	3 0	3	7	29	3]	L 28	2	4	27	1	9	26		9	25		
	37			3 6		30			24		19 / X						7//,
5	31	3	6	32	2 9	33	2	3		0.	021	35			36		
1	6th St	Ind	hre	Para	1 61	North		111		W			1	111	11111	W	1111
	1	T		6	T	5			<i>I</i>	11/1/	1111:	3/////	1///		7 /////	11/1/	

Lines surveyed under Group 108.

Accepted surveys.

Lines surveyed under Group 107.

Areas surveyed as per accepted plats on file.

Book "C"

Group - 108 -Arizona

BOOK 3543

Township 25 North, Range 10 West.

DATE DIAGRAM

	8-28-20	8-28-20	8-27-20	8-27-20	8-27-20	8-27-20
8-28-20	6 7. 6 9-3-20	5 4 6 9=3=20	9*4-20	3 4 5 9~4-20	2 2 9 -4-2 0	1 8- 5 0-20
ł	7+3-20	3=3=21	394-20	9-4-20	9-4-21	8-30-20
8-26-20	7 2-6	æ 9-3-20	æ. 9-2-20	10 E	11 02.	12
٩	9-2-20	9-3-20	9-2-20	8-31-20	8-30-20	8=27-20
8-26-20	18 3 18 3 18 6	17 2 6 9-1-20	16 2-5 8-31-20	15 G 8-30-20	14 & 8 8-20-20	13 8-19-20
				_	_	
8-26-20	19 1-6	6	21 02-08	02-02-8 22	23	
1	8-24-20	8-23-20	8-21-20	8-20-20	8-19-20	8-19-20
8-24-20	8-23-20	أفت	0 2- 0 2- 8	27 -61-9	26	
	8-23-20	8-21-20	8-20-20	8-18-20		
8-23-20	31 [2-8	.1	33 81-8 8-81-8	8-14-8	8-17-20 35	36
	7			•	1 .	•

Indicate surveys executed by Francis R. Ihrie, U. S. T., on dates shown thereon

Indicate aurveys executed by Horace M. Muscott, U. S. T., on dates shown thereon.

```
North Boundary of Township 25 North, Range 10 West.
```

Chains.

15.00

40.00

50.00 80.00 Land; rolling. Soil; rocky, 4th rate. Timber; scrub cedar.

Undergrowth; sagebrush and chamiso.

Fair grass.

N. 89° 58' E., on a true line bet. secs. 4 and 33.

Over rolling land, thru scattering timber and undergrowth Asc. 110 ft. over SW. slope.

Ridge, bears NE. and SW. Desc. 70 ft. over gradual SE.

slope.

Mark a cross (X) on surface rock at exact cor. point and over same, set an iron post, 3 ft. long, 1 in. in diam, supported in a mound of stone, for \$\frac{1}{4}\$ sec. cor., marked on brass cap

 $\frac{1}{2} \frac{\text{S } 33}{\text{S } 4}$

From which

A pine, 8 ins. in diam., bears N. 213° W., 32 lks.

dist., marked 1 S 33 B T.

A cedar, 10 ins. in diam., bears S. 234° E., 34 lks. dist. marked \$\frac{1}{4}\$ S 4 B T. Continue desc. 40 ft. over gradual SE. slope.

Foot of descent, thence over gently rolling land. Set an iron post, 3 ft. long, 2 ins. in diam., 25 ins. in the ground for cor. of Secs. 3, 4, 33 and 34, mark-

ed on brass cap

From which

A cedar, 16 ins. in diam., bears N. 292° E., 243

lks. dist. marked T 26 N R 10 W S 34 B T.

A cedar, 16 ins. in diam., bears S. 65½° E., 176
lks. dist., marked T 25 N R 10 W S 3 B T.

A cedar, 8 ins. in diam., bears S. 29½° W., 108
lks. dist., marked T 25 N R 10 W S 4 B T.

A cedar, 12 ins. in diam., bears N. 2° W., 41
lks. dist., marked T 26 N R 10 W S 33 B T.

Land; level and rolling.

Soil; 3rd and 4th rates.

Timber; scattering scrub cedar.

Undergrowth; sagebrush and chamiso.

N. 89° 58' E., on a true line bet. secs. 3 and 34. Over gently rolling land, thru scattering timber and undergrowth.

Draw, course N. 70° E. 3.00 40.00

Set an iron post, 5 ft. long, 1 in. in diam., 24 ins. in the ground for 4 sec. cor., marked on brass cap

From which

A cedar, 16 ins. in diam., bears N. 392° E., 405 1ks. dist. marked 1 S 34 B T.

```
North Boundary of Township 25 North, Range 10 West.
                         A cedar, 18 ins. in diam., bears S. 82° W., 119
Chains
             lks. dist. marked ½ S 3, B T.

Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins.
in the ground for cor. of secs. 2, 3, 34 and 35, marked
80.00
                 on brass cap
                                               T 26 N | R 10 W
S 34 | S 35
                                                  S 3
                                                          S 2
                                                    T 25 N
                                                      1920
                 From which
                        A cedar, 14 ins. in diam., bears N. 183° E., 123
.1ks. dist. marked T 26 N R 10 W S 35 B T.
A cedar, 12 ins. in diam., bears S. 75° E., 251
                                 1ks. dist. marked T 25 N R 10 W S 2 B T.
                         A cedar, 10 ins. in diam., bears S. 12° W., 82
                         lks. dist. marked T 25 N R 10 W S 3 B T. A cedar, 10 ins. in diam., bears N. 401 W., 91
                                 1ks. dist. marked T 26 N R 10 W S 34 B T.
             Land; gently rolling. Soil; 3rd rate.
              Timber; scrub cedar.
             Undergrowth; sagebrush and chamiso.
             N. 89° 58' E., on a true line, bet. secs. 2 and 35. Over gently rolling land, thru scattering timber and
                 undergrowth.
             Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for \( \frac{1}{4} \) sec. cor., marked on brass cap
40.00
                 From which
                         A cedar, 10 ins. in diam., bears N. 5½° W., 88 lks. dist. marked ½ $ 35 B T.
                         A cedar, 5 ins. in diam.; bears S. 741° W., 83
                                 1ks. dist. marked $ 8.2 B T.
              Set an iron post, 3 ft. long, 2 ins in diam., 24 ins. in
80.00
                 the ground for cor. of secs. 1, 2, 35 and 36, marked
                 on brass cap
                                              T 26 N R 10 W
                                                 S 35 | S 36
                                                   S 2 S 1
                                                     T 25 N
                                                      1920
                 From which
                         which
A cedar, 8 ins. in diam., bears N. 63° E., 275
lks. dist. marked T 26 N R 10 W S 36 B T.
A cedar, 10 ins. in diam., bears S. 64½° E., 288
lks. dist. marked T 25 N R 10 W S 1 B T.
A cedar, 8 ins. in diam., bears S. 47° W., 260
lks. dist. marked T 25 N R 10 W S 2 B T.
A cedar, 6 ins. in diam., bears N. 24½° W., 102
lks. dist. marked T 26 N R 10 W S 35 B T.
Slightly rolling.
              Land; slightly rolling. Soil; gravelly, 3rd rate.
              Timber; scattering cedar and pinyon.
              Undergrowth; sagebrush and chamiso.
```

North Boundary of Township 25 North, Range 10 West.

3543

40.00

Chains

N. 89° 58' E., on a true line bet. secs. 1 and 36. Over gently, rolling land, thru scattering timber and undergrowth.

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked on brass cap

S 36 S 1 1920

From which

80.00

A cedar, 16 ins. in diam., bears N. 753° E., 34

lks. dist. marked ½ S 36 B T.

A cedar, 12 ins. in diam., bears S. 41° E., 96

lks. dist. marked ½ S 1 B T.

The cor. of Ts. 25 and 26 N., Rs. 9 and 10 W., described in field notes of current group No. 107.
Land; slightly rolling.
Soil; gravelly, 3rd rate.

Timber; scattering cedar and pinyon. Undergrowth; sagebrush and chamiso. Good grass.

> Boundaries of the Portion of T. 25 N., R. 10 W., surveyed under group 108.

Latitudes, departures and closing errors.

	·				<u></u>	
Line designated	True bearing	Dist- ance.	Lati	tudes.	Depa:	rtures.
	pearing	amee.	7// •	ω.	E.	YV •
S. bdy. (6th Std. Par. N.)	West	229.62				229.62
Test Boundary	North	480.00	480.00		-	
North Boundary	N.89°58'E.	479.35	.28		479 • 35	
East Boundary	South	271.44		271.44	a i	
Bdy. of Hual- pai Indian Re- servation,	S.50°00'W. S.50°10'W. S.50°00'W. S.50°10'W. S.50°00'W.	65.15 38.04 80.00 79.71 63.82		41.88 24.37 51.42 51.06 41.02		49.91 29.21 61.28 61.21 48.89
Convergency		-			•46	:
Totals			480 28	481.19	479.81	480.12
•				480.28		479.81
	1 latitude	-		•92		•21
	1 departure	•				• 17.7

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

Chains

The southeast boundary of the Hualpai Indian Reservation was originally surveyed in August, 1900, by Albert T. Colton, U. S. D. S. In April, 1912, W. H. Elliott executed the survey of those portions of the Sixth Standard Parallel North (south bdy. of T. 25 N., R. 10 W), the East bdy. of T. 25 N., R. 10 W., and the subdivisional lines of said Tp., lying outside the Reservation and retraced certain parts of the S. E. bdy. of the Reservation. No subsequent retracement or resurvey of these lines is of record in this office.

The closing cor. of secs. 25 and 26 on SE. bdy. of the Hualpai Indian Reservation is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, properly marked on brass cap and witnessed by two properly marked bearing trees as follows:

A pinyon, 8 ins. in diam., brs. S. 3° W., 97 lks.

dist.

A cedar, 8 ins. in diam., brs. S. 33° E., 323 lks. dist.

According to the record this cor. was established on the S.E.Bdy. of the Hualpai Indian Reservation at 62.35 chs. N. 0° 1' W. of the cor. of secs. 25, 26, 35 and 36.

Thence

17.65

N. 0° 01' E., bet. secs. 25 and 26.

Over rolling land, thru scattering timber and undergrowth

Asc. 200 ft. over S. slope.

(80.00 chs. N. 0° 01' W., from the cor. of secs. 25, 26,

35 and 36).

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 23 and 26 only, marked on brass cap

T 25 N R 10 W S 23 S 26 1920

From which

A pine, 12 ins. in diam., bears S. 413° W., 233 lks. dist., marked T 25 N R 10 W 8 26 B T. Raise a mound of stone, 3 ft. base, 3 ft. high W. of

Land; rolling.

Soil; rocky, 4th rate. Timber; pine and cedar.

Undergrowth; chamiso, sagebrush and cactus.

The closing cor. of secs. 24 and 25 on S. E. bdy. of the Hualpai Indian Reservation, is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, properly marked on brass cap and witnessed by two properly marked bearing trees as follows:

A pinyon, 6 ins. in diam., S. 43° E., 74 lks.dist. A pinyon, 6 ins. in diam., N.812° E., 42 lks.dist. According to the record, this cor. was established on the S. E. Bdy. of the Hualpai Indian Reservation at 58.32 chs. West of the cer. of secs. 19, 24, 25 and 30. Thence

west, on a true line bet. secs. 24 and 25. Over rolling land, thru scattering timber and undergrowth Asc. 130 ft. over NE. slope.

Spur, slopes S. 80° E. Desc. 57 ft. over SW. slope. (79.84 chs. W. of the cor. of secs. 19; 24, 25 and 30). Intersect the E. bdy. of sec. 23, 28 lks. N. 0° Ol' W.,

13.00 21.52

FOOR

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

8543

Chains

0.28

2.30

of the cor. of secs. 23 and 26, hereinbefore described. At point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 24 and 25, marked on brass cap

> R 10 W T 25 N S 24 S 25 1920

From which

A juniper, 5 ins. in diam., bears N. 54° E., 88

lks. dist. marked T 25 N R 10 W S 24 B T.

A pinyon, 6 ins. in diam., bears S. 62° E., 102

lks. dist. marked T 25 N R 10W \$ 25 B T.

Raise a mound of stone, 3 ft. base, 2½ ft. high E. of

Land; rolling mountainous. Soil; rocky, 4th rate. Timber; pinyon and cedar.

Undergrowth; chamiso, sagebrush and cactus.

From the cor. of secs. 23 and 26, hereinbefore described N. O' Ol' W. on E. bdy. of sec. 23. Over rolling land, thru scattering timber and undergrowth. Asc. 47 ft. over S. slope.

The cor. of secs. 24 and 25, hereinbefore described.

Spur, slopes Sw. Desc. 150 ft. over NW. slope. Draw, course W. Asc. 80 ft.

12.00

Fence, bears SE. and NW. 14.10

19.40 40.00

Top of ascent. Desc. 70 ft. over NW. slope.

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap

S 23- S 24-1920

From which

A cedar, 10 ins. in diam., bears S. $54\frac{1}{2}$ ° E., 190 lks. dist. marked $\frac{1}{2}$ S 24 B T.

A cedar, 10 ins. in diam., bears S. 194° W., 343 lks. dist. marked 4 S 23 B T.

Desc. 150 ft. over rolling N. slope. 45.95 Main road, hears NE. to Blue Mountain Tank and Sw. to Nelson. Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground for cor. of secs. 13, 14, 23 and 24, mark-,00.08 , ed on brass cap ,

> T 25 N R 10 W S 14 | S 13 S 23 S 1920

From which

A cedar, 10 ins. in diam., bears N. 463° E., 257 lks. dist. marked T 25 N R 10 W S 13 B T. A cedar, 12 ins. in diam., bears S. 81° E., 327

lks. dist. marked T 25 N R 10 W S 24 B T.

A cedar, 12 ins. in diam., bears S. 79° W., 622 lks. dist. marked T 25 N R 10 W S. 23 B T.

A pine, 6 ins. in diam., bears N. 6° W., 320 1ks. dist. marked T 25 N.R 10 W S 14 B T.

Land; rolling.

Soil; rocky, 4th rate.

Timber; scrub pine and cedar. Undergrowth; chamiso and cactus.

Part (Completion) of the Subdivision of . Township 25 North, Range 10 West

Chains	East, on a random line bet. secs. 13 and 24.
40.00 79.64	Set temp. 2 sec. cor. Fall 14 lks. S. of the cor. of secs. 13, 18, 19 and 24.
	on E. bdy. of Tp., described in field notes of current group No. 107.
	Thence
	S. 89° 54' W., on a true line bet. secs. 13 and 24. Over gently rolling land, thru scattering timber and
39.82	undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
	the ground for 4 sec. cor., marked on brass cap
٠ ٠	s 13 °.
, s	S 24
•	1920
	From which
	A cedar, 6 ins. in diam., bears N. 24° E., 56 lks. dist. marked \(\frac{1}{4} \) S 13 B T.
	A cedar, 6 ins. in diam., bears S. 392 E., 123
50.95	lks. dist. marked $\frac{1}{4}$ S 24 B T. Main road, bears NE. to Blue Mountain Tank and Seligman,
67.14	and SW. to Nelson. Road, bears N. to Blue Mountain Tank and Seligman and S.
	to Nelson.
79.64	The cor. of secs. 13, 14, 23 and 24. Land; gently rolling.
p 1	Soil; rocky, 4th rate.
9	Timber; scrub pine and cedar. Undergrowth; chamiso, sagebrush and cactus.
	N. 0° 01' W., bet. secs. 13 and 14. Over rolling land, thru scattering timber and undergrowth
	Asc. 86 ft. over S. slope.
20.00 35.00	Spur, slopes NE. Desc. 70 ft. over gradual N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
	the ground for 2 sec. cor., marked on brass cap
	4
,	. S 14 S 13 1920
	Dig. pits 18 x 18 x 12
59 • 40	ins. N. and S. of post 3 ft. dist. Road, bears E. to Blue Mountain Tank and Seligman, and
	W. to Peach Springs.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground for cor. of secs. 1, 12, 13 and 14,
	marked on brass cap
	T 25 N R 10 W
	S 11 S 12
	S 14 S 13 1920
, , , , ,	Dig pits 18 x 18 x 12 ins
•	in each sec. NE., SE., SW., and NW., of post, 3 ft.
	Land; gently rolling.
• • •	Soil; gravelly, 3rd rate:
*	Timber; scrub cedar.

Undergrowth; sagebrush and chamiso.

Good grass.

```
FOOK
                    Part (Completion) of the Subdivision of
                                                                                           3543
                        Township 25 North, Range 10 West.
           N. 89° 54' E., on a random line bet. secs. 12 and 13. Set. temp. 4 sec. cor.
 Chains
  40.00
            Fall 5 1ks. N. of the cor. of secs. 7, 12, 13 and 18, on
79.70
              E. bdy. of Tp., described in field notes of current
              group No. 107.
           Thence
S. 89° 56' W., on a true line bet. secs. 12 and 13.
Over slightly rolling land, thru scattering undergrowth Road, bears NE. to Blue Mountain Tank and Seligman and
22.50
           Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for \frac{1}{4} sec. cor., marked on brass cap
39.85
                                             S 13
                                             1920
                                                         Dig pits 18 x 18 x 12
           ins. E. and W. of post, 3 ft. dist. The cor. of secs. 11, 12, 13 and 14.
79.70
           Land; slightly rolling.
           Soil; gravelly, 3rd rate.
           Timber; none.
           Undergrowth; sagebrush.
           Good grass.
           N. 0° 01' W., bet. secs. 11 and 12.
           Over gently rolling land, thru sagebrush.
10.00
           Asc. 25 ft. to
15.00
           Desc. 50 ft. to
           Thence over gently rolling land.

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for ½ sec. cor., marked on brass cap
30.00
40.00
                                     S 11 $ S 12
                                                        Dig pits 18 x 18 x 12
          ins. N. and S. of post, 3 ft. dist.

Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bed rock, deposit stone marked with cross (X) at base of post and raise a mound of stone around post, for cor. of secs. 1, 2, 11 and 12, mark-
80.00
              ed on brass cap
                                      T 25 N R 10 W
S 2 | S 1
S 11 | S 12
                                            1920
           Land; slightly rolling.
           Soil; gravelly, 3rd rate.
           Timber; none.
           Undergrowth; sagebrush and chamiso.
           Good grass.
           N. 89° 56' E., on a random line, bet. secs. 1 and 12.
           Set temp. 4 sec. cor.
40.00
           Fall 18 1ks. S. of the cor. of secs. 1, 6, 7 and 12, on
79.92
             E. bdy. of Tp., described in field notes of current
              group No. 107.
           Thence
           S. 89° 48' W., on a true line bet. secs. 1 and 12.
           Over slightly rolling land, thru sagebrush.
           Road, bears NE., to Blue Mountain Tank and Seligman, and
 3.50
              Sw. to Nelson.
```

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

Chains Set an iron post, 3 ft. long, lin. in diam., 26 ins. in the ground for \(\frac{1}{4} \) sec. cor., marked on brass cap 39.96 S 12 1920 Dig pits, 18 x 18 x 12 ins. E. and W. of post 3 ft. dist.
79.92 The cor. of secs. 1, 2, 11 and 12. Land; slightly rolling. Soil; gravelly, 3rd rate. Timber; none. Undergrowth; sagebrush and chamiso. Good grass. N. 0° 01' W., on a random line bet. secs. 1 and 2. Set temp. 1 sec. cor. 40.00 Fall 18 1ks. E. of the cor. of secs. 1, 2, 35 and 36 on N. bdy. of Tp., hereinbefore described. 80.32 Thence S. 0° 09' E., on a true line bet. secs. 1 and 2. Over slightly rolling land, thru scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. in, diam., 24 ins. 40.32 in the ground for 1 sec. cor., marked on brass cap Dig pits 18 x 18 x 12 ins. N. and S. of post, 3 ft. dist. The cor. of secs. 1, 2, 11 and 12. 80.32 Land; slightly rolling. Soil; 3rd rate. Timber; scrub cedar, on N. half. None on S. half. Undergrowth; sagebrush and chamiso. The closing cor. of secs. 34 and 35, on SE. bdy. of the Hualpai Indian Reservation is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, properly marked on brass cap and witnessed by a mound of stone, 2 ft. base, 12 ft. high S. of cor. According to the records this cor. was established on the SE. bdy. of the Hualpai Indian Reservation at 75.38 chs. N. 0° 1' W. of the std. cor. of secs. 34 and 35. Thence N. 0° 01' W., bet. secs. 34 and 35.
Over rolling land, thru scattering timber and undergrowth Asc. 35 ft. over gradual S. slope. (80.00 chs. N. 0° 01' W., from the std. cor. of secs. 4.62 34 and 35). Mark a cross on surface rock at exact cor. point and over same, set an iron post, 3 ft. long, 2 ins. in diam., supported in a mound of stone, for cor. of secs. 26, 27, 34 and 35, marked on brass cap 25 N R 10 W S 27 S 26 T 25 N S 34 S 35 1920

From which

```
Part (Completion) of the Subdivision of
   Township 25 North, Range 10 West.
```

ECOK SE48

Chains

5.51

A cedar, 8 ins. in diam., bears N. 682° E., 96
lks. dist. marked T 25 N R 10 W 5 26 B T.

A cedar, 6 ins. in diam., bears S. 654° E., 150
lks. dist. marked T 25 N R 10 W S 35 B T. 150

A cedar, 6 ins. in diam., bears S. 242° W., 170 lks. dist. marked T 25 N R 10 W S. 34 B T. A pine, 10 ins. in diam., bears N. 423° W., 58 lks. dist. marked T 25 N R 10 W S. 27 B T.

Land; rolling.
Soil; rocky, 4th rate.
Timber; scrub pine and cedar.

Undergrowth; chamiso and sagebrush.

The closing cor. of secs. 26 and 35 on SE. bdy. of the Hualpai Indian Reservation is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, properly marked on brass cap and witnessed by a mound of stone, 2 ft. base, 12 ft. high E. of cor.

According to the record, this cor. was established on the S. E. Bdy. of the Hualpai Indian Reservation at 74.49 chs. West of the cor. of secs. 25, 26, 35 and 36. Thence

West, on a true line bet. secs. 26 and 35.

Over rolling land, thru scattering timber and undergrowth Asc. 40 ft. over gradual E. slope.

(80.00 chs. west of the cor. of secs. 25, 26, 35 and 36) Intersect the cor. of secs. 26, 27, 34 and 35. Land; rolling.

Soil; rocky, 4th rate. Timber; cedar and pine.

Undergrowth; sagebrush and chamiso.

N. 0° 01' W., bet. secs. 26 and 27.
Over rolling land, thru scattering timber and undergrowth Asc, 55 ft.

5.00 22.00

Desc. 55 ft.

Bottom of canyon, course Sw. Asc. 115 ft. over SE. slope
Set an iron post, 3 ft. long, 1 in. in diam., 15 ins. in the ground to bed rock, supported in a mound of stone, for 2 sec. cor., marked on brass cap

> S 27 | S 26 1920

From which

A pine, 8 ins. in diam., bears N. 572° E., 250 lks. dist. marked 2 S 26 B T.

A cedar, 5 ins. in diam., bears S. 77° W., 60° lks. dist. marked ½ S 27 B T.

Thence, over gently rolling NW. slope.

50.00

61.00 77.10

40.00

80.00

Dim road, bears E. and W. Road, bears E. to Nelson and W. to Peach Springs. Old road, bears SE. to Nelson, and NW. to tank. Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, marked on brass cap

> T 25 N. R 10 W S 22 | S 23 S 27 | S 26 1920

From which

```
Part (Completion) of the Subdivision of
                   Township 25 North, Range 10 W.
                  .A cedar, 8 ins. in diam., bears S. 8° E., 444
lks. dist. marked T. 25 N R 10 W S 26 B T.
Chai ns
                  A cedar, 10 ins. in diam., bears S. 64 W., 85 lks. dist. marked T. 25 N R 10 W S. 27 B T.
          No other trees within limits.
Raise a mound of stone, 2 ft. base, 12 ft. high W. of cor
          Land; rolling.
          Soil; rocky, 4th rate.
          Timber; scrub pine and cedar.
          Undergrowth; chamiso and sage brush.
          East, on a random line bet. secs. 23 and 26.
          Set temp. 1 sec. cor.
40.00
          Intersect N. and S. line 4 lks. N. of the cor. of secs.
80.00
             23 and 26.
          Thence
          N. 89° 58' W., on a true line bet. secs. 23 and 26.
          Over rolling land, thru scattering timber and undergrowth
          Asc. 40 ft. over SE. slope.
          Spur, slopes S. 25° W. Desc. 77 ft. over W. slope.
 2.50
          Foot of descent.
15.00
       Asc. 30 ft. over SE. slope.

Spur, slopes SW. Desc. 100 ft. over NW. slope.

Main road, bears NE. to Blue Mountain Tank, and Seligman and SW. to Nelson.
20.00
25.00
35.20
          Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground, for \frac{1}{4} sec. cor., marked on brass cap
40.00
                                        S 23
                                        S 26
                                        1920
             From which
                   A cedar, 8 ins. in diam., bears N. 802° W., 84
                   lks. dist. marked ½ S 23 B T.

A cedar, 8 ins. in diam., bears S. 772° W., 101
lks. dist. marked ½ S 26 B T.
          Desc. 100 ft. over rolling NW. slope.
80.00 The cor. of secs. 22, 23, 26 and 27.
          Land; rolling.
          Soil; rocky, 4th rate.
Timber; scrub pine and cedar.
          Undergrowth; chamiso and sagebrush.
          N. 0° 01' W., bet. secs. 22 and 23.
          Over gently rolling land, thru scattering timber and
             undergrowth.
         . Asc. 30. ft.
 5.00
10.00
         Desc. 30 ft. Asc. 25 ft.
15.00
          Desc. 55 ft.
20.00
          Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap
40.00
                                     S 22  S 23
                                                    Dig pits 18 x 18 x 12
             ins. N. and S. of post, 3 ft. dist.
          Continue desc. 92 ft. over NW. slope.
          Foot of descent. Thence over gently rolling land.
55.00
70.00
          Asc. 60 ft.
          Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22 and 23,
80.00
             marked on brass cap
```

BOOK SEKS

Part (Completion) of the Subdivision of . Township 25 North, Range 10 West.

Chains T 25 N R 10 W 25 N R 10 V S 15 | S 14 S 22 S 23 1920 ins. NE., SE., SW., and NW., of post, 3 ft. dist. Land; gently rolling. Soil; 3rd rate. Timber; scrub pine and juniper. 🥶 Undergrowth; sagebrush and cactus. S. 89° 58' E., on a random line bet. secs. 14 and 23. Set temp. 4 sec. cor. 40.00 Intersect N. and S. line, 5 lks. N. of the cor. of secs. 13, 14, 23 and 24. 80.10 Thence N. 89° 56' W., on a true line, bet. secs. 14 and 24. Over gently rolling land, thru scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for 4 sec. cor., marked on brass cap 40.05 Dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist. 65.13 Desc. 70 ft. over west slope. 80.10 The cor. of secs. 14, 15, 22 and 23. Land; gently rolling. Soil; 3rd rate. Timber; scrub cedar and pine. Undergrowth; sagebrush and cactus. N. 0° 01' W., bet. secs. 14 and 15. Over rolling land, thru scattering timber and undergrowth 5.00 Drain, course Sw. Asc. 90. ft. over S. slope.

Ridge, bears E. and W. Desc. 114 ft. over N. slope.

Thence over gently rolling land.

Set an iron post, 3 ft. long, 1 in. in diam., in a mound 10.00 23.00 35.00 40.00 of stone, for 4 sec. cor., marked on brass cap S 15 S 14 From which A pinyon, 10 ins. in diam., bears N. 40° E., 74 lks. dist. marked ½ S 14 B T. A cedar, 6 ins. in diam., bears N. 40% W., 14 lks. dist. marked 1 S 15 B T. Road, bears E. to Blue Mountain Tank and Seligman, and W. to Peach Springs. Leave timber, brs. E. and W. Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground for cor. of Secs. 10, 11, 14 and 15, 51.10 80.00 marked on brass cap T 25 N R 10 W S 10 S 11 S 15 | S 14 1920

NE., SE., Sw., and Nw., of post, 3 ft. dist.

Dig pits 18 x 18 x 12 ins.

	Part (Completion) of the Subdivision of Township 25 North, Range 10 West.
Chains	Land; rolling. Soil; 3rd rate. Timber; scrub cedar. Undergrowth; sagebrush and chamiso.
. #	
40.00 80.08	S. 89° 56' E., on a random line bet. secs. 11 and 14. Set temp. ½ sec. cor. Intersect the cor. of secs. 11, 12, 13 and 14. Thence N. 89° 56' W., on a true line bet. secs. 11 and 14.
	Over nearly level land, thru scattering scrub cedar and sagebrush.
40.04	Set an iron post, 3 ft. long, l in. in diam., 16 ins. in the ground to bed rock, deposit a stone marked with a cross (X) at base of post and raise mound of stone around post for 2 sec. cor., marked on brass cap
	\$\frac{1}{8} \frac{14}{1920}
80.08	The cor. of secs. 10, 11, 14 and 15. Land; level and slightly rolling. Soil: 3rd rate.
	Timber; scattering scrub cedar. Undergrowth; sagebrush and chamiso. Good grass.
40.00	N. 0° 01' W., bet. secs. 10 and 11. Over slightly rolling land, thru scattering undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for ½ sec. cor., marked on brass cap
	S 10 S 11 1920 Dig pits 18 x 12 ins.
55.00	N. and S. of post, 3 ft. dist. Draw, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bed rock, deposit a stone marked, with a cross (X) at base of post and raise a mound of stone around post. T 25 N, R 10 W
	In the contract of the contrac
	Land; slightly rolling. Soil; 3rd rate. Timber; none. Undergrowth; sagebrush and chamiso.
	G 000 FC I To on a mandain line hat Sacs 2 and ll.
40.00° 79.96	S. 89° 56 ° E., on a random line bet. secs. 2 and ll. Set temp. ½ sec. cor. Intersect N. and S. line, 12 lks. S. of the cor. of secs. 'l, 2, ll and l2.' Thence'
39 .9 8	S. 89° 59' W., on a true line bet. secs. 2 and ll. Over slightly rolling land, thru scattering undergrowth. Set an iron post, 3 ft. long, l in. in diam., 26 ins. in the ground for ½ sec. cor., marked on brass cap
	\$\frac{\s 2}{\s 11}

FCCK Part (Completion) of the Subdivision of Township 25 North, Range 10 West. Dig pits 18 x 18 x 12 ins.

E. and W. of post, 3 ft. dist.

The cor. of secs. 2, 3, 10 and 11.

Land; slightly rolling.

Soil; 3rd rate.

Timber: none Chains 79.96 Timber; none. Undergrowth; sagebrush and chamiso. Good grass. N. 0° 10' W., on a random line bet. secs. 2 and 3.

40.00 80.25

40.25

Set temp. 4. Sec. cor.

Fall 9 lks. W. of the cor. of secs. 2, 3, 34 and 35 on N. bdy. of Tp., hereinbefore described.

S. 0° 06' E., on a true line bet. secs. 2 and 3. Over nearly level land, thru scattering timber and under

growth. Set an iron post, 3 ft. long, l in. in diam., 7 ins. in the ground to bed rock, supported in a mound of stone, for \$\frac{1}{2}\$ sec. cor., marked on brass cap

S 3 T S 2

From which

A cedar, 16 ins. in diam., bears N. 12½° E., 52 lks. dist. marked ½ S 2 B T.

A cedar, 8 ins. in diam., bears S. 55½° W., 189 lks. dist. marked ½ S 3 B T.

45.00 80.25

Leave timber. The cor. of Secs. 2, 3, 10 and 11.

Land; slightly rolling.

Soil: 3rd rate.

Timber; scattering scrub cedar. Undergrowth; sagebrush and chamiso.

Good grass.

The closing cor. of secs. 33 and 34 on SE. bdy. of the Hualpai Indian Reservation is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set, properly marked on brass cap and witnessed by two properly marked bearing trees as follows:

A cedar, 8 ins. in diam., N. 883 E., 41 lks.dist
A pinyon, 12 ins.in.diam., S. 282 W., 296 lks.dist

According to the record, this cor. was established on the S. E. Bdy. of the Hualpai Indian Reservation at 8.70 chs. N. O° 2' W. of the standard cor. of secs. 33 and 34.

Thence
N. 0° 02' W., bet. secs. 33 and 34

Over rolling land, thru scattering timber and undergrowth

Desc. 115 ft. over N. slope.

Canyon, course N. 20° W.

Road, bears S. 20° E. and N. 20° W.

Asc. 52 ft. over S. slope. (40.00 chs. N. 0° 02' W., of the std. cor. of secs. 33 & 34.)

Mark a cross (X) on surface rock at exact cor. point and over same set an iron post, 3 ft. long, 1 in. in diam., supported in a mound of stone, for 4 sec. cor.

marked on brass cap

S 33 TS 34

10.00 21.80

22.30

25.00

31.30

```
Part (Completion) of the Subdivision of . Township 25 North, Range 10 West.
```

agent control and the separation of the second of the seco	Township 23 Moren, name to west.
Chains	From Which
	A pine, 6 ins. in diam., bears N. 422° E., 47
	lks. dist. marked & S 34 B T.
1	A pine, 12 ins. in diam., bears S. 194 W., 95
	lks. dist. marked \$ 33 B T.
36 • 30	Desc. 150 ft. over N. slope.
53.50	Road, bears E. and W.
53.80	A. T. and S. F. R. R. right of way fence brs. E. & W. Wash, 30 lks. wide, 2 ft. deep, course W.
54.70 55.20	A. T. and S. F. R. R. brs. E. to Nelson and W. to Peach
20020	Springs.
56.50	Right of way fence brs. E. & W.
56.90°	Old road, bears E. and W.
62.60	Main road, bears E. to Nelson and W. to Peach Springs.
,	Asc. 34 ft. over S. slope.
71.30	(80.00 chs. N. 0; 02 W. from the std. cor. of secs.
	33 and 34) week, for your of source St, No, 10, 12 120, 10,
	Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins.
	in the ground, for cor; of secs. 27, 28, 33 and 34, marked on brass cap
,	" to the state of
	T 25 N R 10 W
	S 28 S 27 °
<i>'</i>	S 33 S 34
	1920
·	Raise a mound of stone 3
·	ft. base, 3 ft. high W. of cor.
	Land; rolling.
, ,	Soil; rocky, 4th rate. Timber; pine and cedar.
	Undergrowth; chamiso and sagebrush.
	Test on a rendem line bet sees 27 and 54
40.00	East, on a random line bet. secs. 27 and 34.
40.00 79.98	Set temp. 1/2 sec. cor.
40.00 79.98	
	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence
	Set temp. \(\frac{1}{4} \) sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34.
	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth
79.98	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope.
79.98 5.50	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope.
79.98 5.50 15.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope.
79.98 5.50 15.00 24.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to
79.98 5.50 15.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope.
79.98 5.50 15.00 24.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
79.98 5.50 15.00 24.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
79.98 5.50 15.00 24.00	Set temp. \(\frac{1}{4}\) sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for \(\frac{1}{4}\) sec. cor., marked on brass cap
79.98 5.50 15.00 24.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap
79.98 5.50 15.00 24.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3
79.98 5.50 15.00 24.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor.
79.98 5.50 15.00 24.00 39.99	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to
79.98 5.50 15.00 24.00 39.99	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to
79.98 5.50 15.00 24.00 39.99	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to. Gulch, course S. Asc. 57 ft. to
79.98 5.50 15.00 24.00 39.99 55.30 65.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, l in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap \[\frac{1}{2} \frac{S}{34} \\ \tag{1920} \] Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to Gulch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor.
79.98 5.50 15.00 24.00 39.99 55.30 65.00 74.70	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, l in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap 1 S 27 1 S 34 1920 Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to. Gulch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor. The cor. of secs. 27, 28, 33 and 34.
79.98 5.50 15.00 24.00 39.99 55.50 65.00 74.70 78.00	Set temp. ½ Sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ Sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to Culch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor. The cor. of secs. 27, 28, 33 and 34. Land; rolling.
79.98 5.50 15.00 24.00 39.99 55.50 65.00 74.70 78.00	Set temp. ½ Sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ Sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to. Gulch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor. The cor. of secs. 27, 28, 33 and 34. Land; rolling. Soil; rocky, 4th rate.
79.98 5.50 15.00 24.00 39.99 55.50 65.00 74.70 78.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to. Gulch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor. The cor. of secs. 27, 28, 33 and 34. Land; rolling. Soil; rocky, 4th rate. Timber; scrub pine and cedar.
79.98 5.50 15.00 24.00 39.99 55.50 65.00 74.70 78.00	Set temp. ½ Sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W.; on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ Sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to. Gulch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor. The cor. of secs. 27, 28, 33 and 34. Land; rolling. Soil; rocky, 4th rate.
79.98 5.50 15.00 24.00 39.99 55.50 65.00 74.70 78.00	Set temp. ½ sec. cor. Intersect N. & S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence S. 89° 53' W., on a true line bet. secs. 27 and 34. Over rolling land, thru scattering timber and undergrowth Desc. 57 ft. over W. slope. Canyon, course S. Asc. 46 ft. over E. slope. Desc. 60 ft. over W. slope. Gulch, course S. Asc. 70 ft. to Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground, for ½ sec. cor., marked on brass cap Raise a mound of stone 3 ft. base, 2½ ft. high N. of cor. Desc. 26 ft. to Gulch, course S. Asc. 60 ft. to Top of ascent, desc. 45 ft. to. Gulch, course S. Asc. 57 ft. to Spur, slopes S. Desc. 20 ft. to cor. The cor. of secs. 27, 28, 33 and 34. Land; rolling. Soil; rocky, 4th rate. Timber; scrub pine and cedar.

N. 0° 02' W., bet. secs. 27 and 28.

```
FCCK 3543
                            Part (Completion) of the Subdivision of
                                   Township 25 North, Range 10 West.
 Chains
Over rolling land, thru scattering timber and undergrowth.
Asc. 163 ft. over SW. slope.

Spur, slopes SW. Desc. 110 ft. over NW. slope.

32.00 Drain, course S. 20° W. Asc. 120 ft. to

Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for 4 sec. cor., marked, on brass cap
                                                        S 28 | S 27
                      From which
                  A cedar, 8 ins. in diam., bears S. 64° E., 89
lks. dist. marked ½ S 27 B T.

A pine, 8 ins. in diam., bears N. 78° W., 138
lks. dist. marked ½ S 28 B T.

Old road, bears E. to Blue Mountain Tank and Seligman, and
W. to Peach Springs
  51.80
                      W. to Peach Springs
  55.00
                  Desc. 200 ft. over N. slope.
                  Foot of descent. Asc. 60 ft. over S. slope.
Spur, slopes W. Desc. 12 ft. to
Set an iron post, 5 ft. long, 2 ins. in diam., in a
mound of stone, for cor. of secs. 21, 22, 27 and 28,
marked on brass cap
  75.00
  78.20
  80.00
                                                       T 25 N R 10 W
S 21 | S 22
                                                          S 28 | S 27
                                                                1920
                      From which
                               A pine, 14 ins. in diam., bears N. 9° E., 22 lks.

dist. marked T 25 N R 10 W S 22 B T.

A pine, 12 ins. in diam., bears S. 14° E., 65 lks.

dist. marked T 25 N R 10 W S 27 B T.

A cedar, 5 ins. in diam., bears S. 14½° W., 21

lks. dist. marked T 25 N R 10 W S 28 B T.

A pine, 5 ins. in diam., bears N. 48½° W., 12

lks. dist. marked T 25 N R 10 W S 21 B T.

rolling.
                 Land; rolling.
Soil; rocky, 4th rate.
Timber; scrub pine and cedar.
                  Undergrowth; chamiso, sage brush and cactus.
                 N. 89° 53' E., on a random line bet. secs. 22 and 27. Set temp. * sec. cor. Intersect N. and S. line 9 lks. N. of the cor. of secs.
 40.00
 80.10
                     22, 23, 26 and 27.
                 Thence
                S. 89° 57' W., on a true line bet. secs. 22 and 27.
                Over rolling land, thru scattering timber and undergrowth
  1:10
                Old road, bears NW. and SE.
10.14
                Desc. 30 ft.
14.60
                Drain, course NW. Asc. 25 ft. to
                Top of ascent thence over level land.
20.00
40.05
               Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in
                   the ground for 2 sec. cor., marked on brass cap
```

From which

A cedar, 8 ins. in diam., bears N. $30\frac{1}{4}$ E., 80 lks.

dist., marked \$\frac{1}{4}\$ S 22 B T.

A cedar, 8 ins. in diam., bears \$\frac{1}{4}\$ S 27 B T.

5.00

10.00 17.50 30.00 40.00

50.00

69.00

75.00 80.00 Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

Continue over level land. Chains Desc. 167 ft. over SW. slope. Canyon, course N. 70° W. Asc. 40 ft. The cor. of secs. 21; 22, 27 and 28. 45.00 61.00 80.10 Land; rolling. Soil; rocky, 4th rate. Timber; scrub pine and cedar. Undergrowth; cactus, sagebrush and chamiso.

N. 0° 02' W., bet. secs. 21 and 22.

Over rolling land, thru scattering timber and undergrowth

Desc. 90 ft. over N. slope to Wash, course W. Asc. 86 ft. over S. slope. Spur, slopes W. Desc. 55 ft. over N. slope to
Wash, course SW. Asc. 120 ft. over S. slope.
Top of ascent. Desc. 67 ft. over N. slope to
Set an iron post, 3 ft. long, 1 in. in diam., in a mound
of stone, for 4 sec. cor., marked on brass cap

S 21 | S 22 1920

From which

A cedar, 6 ins. in diam., bears N. 23° E., 69
lks. dist. marked \(\frac{1}{4} \) S 22 B T.

A cedar, 12 ins. in diam., bears N. 26\(\frac{2}{4} \) W., 117
lks. dist. marked \(\frac{1}{4} \) S 21 B T.

Asc. 64 ft. over, S. slope. Top of ascent, desc. 35 ft.

Wash, course E. Asc. 50 ft. over S. slope.

Top of ascent, thence along E. slope.

Set an iron post, 3 ft. long, 2 ins. in diam., in a mound of stone, for cor. of secs. 15, 16, 21 and 22, marked on brass cap

T 25 N R 10 W , S 16 | S 15 S 21 S 22 1920

From which

A cedar, 6 ins. in diam., bears N. 321° E., 85 lks. dist. marked T 25 N R 10 W S 15 B T.

A cedar, 10 ins. in diam., bears S. 582° E., 140 lks. dist. marked T 25 N R 10 W S 22 B T.

A cedar, 12 ins. in diam., bears S. 20° W., 146
lks. dist. marked T 25 N R 10 W S 21 B T.
A cedar, 8 ins. in diam., bears N. 48° W., 55
lks. dist. marked T 25 N R 10 W S 16 B T.

Land; rolling.

Soil; rocky, 3rd rate. Timber; scrub cedar and scattering pinyon. Undergrowth; sagebrush, chamiso and cactus.

Poor grass.

40.00 80.16 N. 89° 57' E., on a random line bet. secs. 15 and 22. Set temp. \(\frac{1}{4}\) Sec. cor.
Intersect N. and S. line 14 lks. S. of the cor. of secs. 14, 15, 22 and 23.

Thence S. 89° 51' W., on a true line bet. secs. 15 and 22. Over rolling land, thru scattering timber and undergrowth, descending 69 ft. to 2 cor.

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

Chains Road, bears SE. to Nelson and NW. to tank. Road, bears NE. to Nelson and SW. to tank. 28.95 32.66 Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for \$\frac{1}{2}\$ sec. cor., marked on brass cap 40.08 \$\frac{\S 15}{\S 22} 1920 From which A cedar, 12 ins. in diam., bears N. 26 E., 130 lks. dist., marked 4 S 15 B T.

A cedar, 6 ins. in diam., bears S. 794 E., 380 lks. dist. marked 4 S 22 B T. Desc. 25 ft. to Drain, course Sw. Asc. 45 ft. to Spur, slopes S. Desc. 52 ft. 46.16 50.00 57.86 Dim road, bears SE. to Nelson and NW. to tank. Wash, course SE. Asc. 57 ft. over gradual E. slope. The cor. of secs. 15, 16, 21 and 22. 62.85 80.16 Land; rolling. Soil; 3rd rate. Timber; Scattering acrub cedar. Undergrowth; sagebrush and chamiso. Good grass. N. 0° 02' W., bet. secs. 15 and 16. Over gently rolling land, along E. slope, thru scattering timber and undergrowth. 37.00 Over level land. Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for 4 sec. cor., marked on brass cap 40.00 S 16 | S 15 Dig pits 18 x 18 x 12 ins. N. and S. of post 3 ft. dist. Road, bears E. to Blue Mountain Tank and Seligman, and W. 41.50 to Peach Springs. Road, bears NE. to tank and SW. to Peach Springs. Set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in the ground to bed rock, supported in a mound of 56.00 80.00 stone, for cor. of secs. 9, 10, 15 and 16, marked on brass cap T 25 N R 10 W S 9 | S 10 S 16 S 15 1920 From which A cedar, 8 ins. in diam., bears N. 404° E., 176 lks. dist. marked T 25 N R 10 W 5.10 B T. A cedar, 8 ins. in diam., bears S. 291° E., 245 lks. dist. marked T 25 N R 10 W S 15 B T.

A cedar, 6 ins. in diam., bears S. 312° W., 266
lks. dist. marked T 25 N R 10 W S. 16 B. T.
A cedar, 6 ins. in diam., bears N. 82° W., 190
lks. dist. marked T 25 N R 10 W 8 9 B T.

Land; rolling. Soil; 3rd rate.

Timber; scattering scrub cedar.

Undergrowth; sagebrush and chamiso.

Good grass.

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

	Township 25 North, Range 10 West.
Chains 40.00	N. 89° 51' E., on a random line bet. secs. 10 and 15. Set temp. \(\frac{1}{4} \) sec. cor.
80.06	Intersect N. and S. line 5 lks. N. of the cor. of secs. 10, 11, 14 and 15. Thence
,	S. 89° 53' W., on a true line bet. secs. 10 and 15. Over slightly rolling land, thru scattering clumps of scrub cedar and undergrowth.
32.56	Road, bears N. to tank and S. to Nelson. Tank with stock water bears N. about 15 chs. dist.
40.03	Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground, for \frac{1}{4} sec. cor., marked on brass cap
٠.	\$\frac{\sim 10}{\sim 15}\$ 1920
46.46 80.06	Dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist. Road, bears SE. to Peach Springs and NW. to tank. The cor. of secs. 9, 10, 15 and 16. Land; slightly rolling, drains SW. Soil: 3rd rate.
	Timber; scrub cedar. Undergrowth; sagebrush and chamiso.
	N. 0° 02' W., bet. secs. 9 and 10. Over slightly rolling land, thru scattering timber and undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to bed rock, supported in a mound of stone, for ½ sec. cor., marked on brass cap
	S 9 \(\) S 10 1920
	From which A cedar, 14 ins. in diam., bears N. 57° E., 172 lks. dist. marked ½ S 10 B T. A cedar, 16 ins. in diam., bears N. 45° W., 73 lks. dist. marked ½ S 9 B T.
68.70 80.00	Road, bears H. and W. Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground for cor. of secs. 3, 4, 9 and 10, marked on brass cap
	T 25 N R 10 W S 4 S 3 S 9 S 10 1920
	From which A cedar, 6 ins. in diam., bears N. 38½° E., 60 lks. dist. marked T 25 N R 10 W S 3 B T. A cedar, 12 ins. in diam., bears S. 44½° E., 24 lks. dist. marked T 25 N R 10 W S 10 B T. A cedar, 6 ins. in diam., bears S. 24½° W., 81 lks. dist. marked T 25 N R 10 W S 9 B T. A cedar, 16 ins. in diam., bears N. 8° W., 29 lks. dist. marked T 25 N R 10 W S 4 B T.
1	Land: Slightly rolling, drains S.

Land; slightly rolling, drains S. Soil; rocky, 3rd rate.
Timber; scrub cedar.

Undergrowth; sagebrush, chamiso and cactus.

```
BOOR 8548
                Part (Completion) of the Subdivision of
                   Township 25 North, Range 10 West.
          N. 89° 53' E., on a random line bet. secs. 3 and 10. Set temp. 1 sec. cor. Intersect N. and S. line 12 lks. N. of the cor. of secs.
Chains
40.00
80.00
              2, 3, 10 and 11.
           Thence S. 89° 58' W., on a true line bet. secs. 3 and 10.
           Over slightly rolling land, thru scattering timber and
             undergrowth.
17.50
           Drain, course S.
          Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to bed rock, supported in a mound of stone, for 2 sec. cor., marked on brass cap
40.00
                                       $ S. 3
S 10
                                           1920
             From which
                   A cedar, 10 ins. in diam., bears N. 37° E., 52
lks. dist. marked 2 S 3 B T.
                  A cedar, 6 ins. in diam., bears S. 319 E., 100 lks. dist. marked 1 S 10 B T.
65.00
          Small draw, course'S. The cor. of secs. 3, 4, 9 and 10.
80.00
          Land; slightly rolling.
           Soil; rocky, 3rd rate.
           Timber; scrub cedar.
           Undergrowth; sagebrush and chamiso.
          N. 0° 07' W., on a random line bet, secs. 3 and 4.
          Set temp. 4 sec. cor.
40.00
          Fall 19 lks. E. of the cor. of secs. 3, 4, 33 and 34, on N. bdy. of Tp., hereinbefore described.
80.47
          S. 0° 15' E., on a true line bet. secs. 3 and 4.
          Over slightly rolling land, thru scattering timber and
             undergrowth.
          Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for \frac{1}{4} sec. cor., marked on brass cap
40.47
                                     S 4 T S 3°
1920
             From which
                   A cedar, 8 ins. in diam., bears N. 82° E., 140 lks. dist. marked $ 5 3 B T.
          A cedar, 10 ins. in diam., bears N. 59° W., 52 lks. dist. marked $\frac{1}{2}$ S 4 B T.

The cor. of secs. 3, 4, 9 and 10.
80.47
          Land; slightly rolling.
          Soil; rocky, 3rd rate.
          Timber; scrub cedar.
          Undergrowth; sagebrush and chamiso.
         Good grass.
          From the Std. cor. of secs. 32 and 33 on S. bdy. of Tp.
            (Sixth Standard Parallel North) hereinbefore described.
          N. 0° 03' W., bet. secs. 32 and 33.

Over rolling land, thru scattering timber and undergrowth
          Desc. 110 ft. over M. slope, to.
19.90
          Gulch, course W.
          Road, bears N. 20° E., and S. 20° W.
28.00
          Wash, 50 lks. wide, 3 ft. deep, course N. 20° E.
31.50
```

```
Part (Completion) of the Subdivision of
                        Township 25 North, Range 10 West.
Chains Asc. 100 ft. over SE. slope to
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 4 ins. in
the ground to bed rock, supported in a mound of stone,
for 4 sec. cor., marked on brass cap
                                         S, 32 S 33
               From which
                       A cedar, 8 ins., in diam., bears S. 832 E., 29
                       lks. dist. marked. $\frac{1}{2}$ S 33 B T.

A cedar, 8 ins. in diam., bears S. 25\frac{1}{2}$ W., 88

lks. dist. marked $\frac{1}{4}$ S 32 B T.
               Continue ascent.
            Spur, slopes NE. Desc. 115 ft. over NW. slope.
45.00
         Gulch, course NE. Asc. 40 ft.
60.00
            Top of ascent. Desc. 93 ft. to
68.00
            Enter Yampai Canyon, course NW.
Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins.
in the ground for cor. of secs. 28, 29, 32 and 33, marked
75.00
00.08
               on brass cap
                                        T 25 N R 10 W
S 29 | S 28
                                           S 32 | S 33
                                                19'20
                                                                Raise a mound of stone,
                3 ft. base, 3 ft. high W. of cor.
            Land; gently rolling:
Soil; rocky and gravelly, 4th rate.
            Timber; scrub pine and cedar.
            Undergrowth; chamiso, sagebrush and cactus.
            East, on a random line bet. secs. 28 and 33.
            Set temp. 1 sec. cor.
40.00
            Intersect N. and S. line 8 lks. S. of the cor. of secs.
79.98
               27, 28, 33 and 34.
            Thence
S. 89° 57' W., on a true line bet. secs. 28 and 33.
            Over rolling land, thru scattering timber and undergrowth
            Drain, course S. Asc. 154 ft. over E. slope.

Top of ascent, thence along S. slope.

Spur, slopes S. 20° W. Desc. 40 ft. to

Set an iron post, 5 ft. long, 1 in. in diam., 6 ins. in the ground to bed rock, supported in a mound of stone, for 4 sec. cor., marked on brass cap
 3.00
20.00
35.00
39.99
                                             $ 28
$ 33
                                                 1920
               From which
                       A pine, 5 ins. in diam., bears N. 12° W., 41 lks. dist. marked 1 S 28 B T.

A pine, 7 ins. in diam., bears S. 75° W., 65 lks. dist. marked 1 S 33 B T.
            Desc. 200 ft. over rolling Sw. slope.
         Drain, course S. Enter Yampai Canyon.

Main road, bears S. 50° E. to Nelson and N. 50° W. to
59.00
64.30
               Peach Springs.
            A. T. and S. F. R. R. right of way fence, brs. N. 50° W., and S. 50° E.
68.08
             Telegraph line, bears S. 50° E., and N. 50° W.
69.60
            A. T. and S. F. R. R. bears S. 50° E., to Nelson and N. 50°
70.30
```

W., to Peach Springs.

71.00

Telephone line, bears S. 50° E., and N. 50° W.

BCCK STAR

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

```
Chains
              Wash, 15 lks. wide, 3 ft. deep, course N. 50° W. Right of way fence, bears SE. and NW. The cor. of secs. 28, 29, 32 and 33.
71.60
72.70
79.98
              Land; level and rolling.
Soil; 3rd and 4th rates.
Timber; scrub pine and cedar.
               Undergrowth; sagebrush, cactus and chamiso.
              N. 0° 03' W., bet. secs. 28 and 29
Over rolling land, thru scattering timber and undergrowth
Center of wash, 2 chs. wide, 1 ft. deep, course N. 50° W.
A. T. and S. F. R. R. right of way fence brs. N. 50° W.,
and S. 50° E.
  6.00
  6.50
              Telephone line, bears S. 50° E., and N. 50° W. A. T. and S. F. R. bears S. 50° E. to Nelson and N. 50° W. to Peach Springs.
  8.10
  8.60
              Telegraph line, bears S. 50° E., and N. 50° W.
Right of way fence bears S. 50° E., and N. 50° W.
Road, bears S. 50° E. to Nelson and N. 50° W. to Peach
 9.50
10.50
11.80
                 Springs.
             Leave Yampai Canyon, and asc. over rolling S. slope 140 ft. Spur, slopes W. Decs. 100 ft. over NW. slope. Set an iron post, 5 ft. long, l in. in diam., 26 ins. in
12.50
30.00
40.00
                  the ground, for 1 sec. cor., marked on brass cap
                                                 S 29 | S 28
                                                         1920
                 From which
                          A cedar, 16 ins. in diam., bears N. 362° E., 143
lks. dist. marked \(\frac{1}{4}\) S 28 B T.

A cedar, 6 ins. in diam., bears S. 27\(\frac{1}{4}\)° W., 106
lks. dist. marked \(\frac{1}{4}\) S 29 B T.
43.20
              Drain, course W. Asc. 70 ft. over S. slope to
             Spur, slopes W. Continue over series of low spurs, slop-
50.00
                 ing W.
62.00
              Asc. 152 ft. to
              Set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in
80.00
                  the ground to bed rock, supported in a mound of stone,
                 for cor. of secs. 20, 21, 28 and 29, marked on brass
                                                  T 25 N
                                                                R 10 W
                                                     S 20 | S 21
                                                     S 29 S 28
```

1920

From which

`A pine, 16 ins. in diam., bears N. 53° E., 32 lks.

dist. marked T 25 N R 10 W S 21 B T.

A pine, 8 ins. in diam., bears S. 55½ E., 241

lks. dist. marked T 25 N R 10 W S 28 B T.

A pine, 6 ins. in diam., bears S. 47½ W., 87

lks. dist. marked T 25 N R 10 W S 29 B T.

A pine, 6 ins. in diam., bears N. 71½ W., 27 1ks. dist. marked T 25 N R 10 W 5 20 B T.

Land; rolling. Soil; rocky, 3rd and 4th rates.

Timber; scrub pine and juniper. Undergrowth; sagebrush and cactus.

N. 89° 57' E., on a random line, bet. secs. 21 and 28.

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

Chains Set temp. 1 sec. cor. Intersect N. and S. line 21 lks. N. of the cor. of secs. 40.00 79.88 21, 22, 27 and 28. Thence N. 89° 54' W., on a true line bet. secs. 21 and 28. Over rolling land, thru scattering timber and undergrowth Desc. 74 ft. over NW. slope. Wash, course Sw., along S. slope.
Same wash, course Nw., asc. 50 ft. to
Top of ascent, desc. 75 ft. to
Set an iron post, 3 ft. long, 1 in. in diam., in a
mound of stone, for 4 sec. cor., marked on brass cap 9.50 14.20 39.60 39.94 A pine, 12 ins. in diam., bears N. 86 W., 92

lks. dist. marked 1 S 21 B T.

A pine, 8 ins. in diam., bears S. 63 W., 68.

lks. dist. marked 1 S 28 B T.

Wash, course S. 70° W. . From which 46.90 Same wash, course N. 70° W. Asc. 140. ft. to 53.60 Sharp spur, slopes N. Desc. 86 ft. to
Drain, course N. Asc. 176 ft. over NE. slope.
Spur, bears SE. and N. 80° W. Desc. 23 ft. to 56.10 60.30 74, 90 79.88 The cor. of secs. 20, 21,28 and 29. Land; broken.
Soil; rocky, 4th rate.
Timber; scrub pine and cedar. Undergrowth; sagebrush and cactus. N. 0° 03' W., bet. secs. 20 and 21. Over rolling land, thru scattering timber and undergrowth Spur, slopes W. Desc. 212 ft. over N. slope. 1.40 Ravine, course W., from N. Thence along ravine. 10.00 Leave ravine, course S. from E. 25.00 Asc. 166 ft. over S. slope. 26.00 Ridge, bears NE. and SW., along W. slope to 35-00 Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for 4 sec. cor., marked on brass cap 40.00 S 20 | S 21 1920 From which A pinyon, 12 ins. in diam., bears S. 83° E., 76 lks. dist. marked 4 S 21 B T.

A cedar, 8 ins. in diam., bears N. 57° W., 58 lks. dist. marked 1 S 20 B T.

Desc. 78 ft. to

47.00 79.00 80.00 Ravine, course SW. Asc. 260 ft. over SE. slope to Ridge, bears N. 80° E. and S. 80° W. Set an iron post; 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, marked on brass cap

> T 25 N R 10 W S 17 | S 16 S 20 | S 21

From which A cedar, 12 ins. in diam., bears N. 822° E., 34 . 1ks. dist. marked T 25 N R 10 W S 16 B T.

ECCK SEK

Part (Completion) of the Subdivision of Township 25 North. Range 10 West

A cedar, 10 ins. in diam., bears S. 73° E., 230 lks. dist. marked T 25 N R 10 W S. 21 B T. A cedar, 12 ins. in diam., bears S. 173° W., 45 lks. dist. marked T 25 N R 10 W S 20 B T. A cedar, 8 ins. in diam., bears N. 39½° W., 98 lks. dist. marked T 25 N R 10 W S 17 B T. rolling. Chains Land; rolling.
Soil; rocky, 3rd rate.
Timber; scattering scrub cedar and pinyon. Undergrowth; Sagebrush and chamiso. S. 89° 54' E., on a random line bet. secs. 16 and 21. Set temp. ½ sec. cor. Intersect N. and S. line 28 lks. S. of the cor. of secs 40.00 79.90 15, 16, 21 and 22. S. 89° 54' W., on a true line bet. secs. 16 and 21. Over rolling land, thru scattering timber and undergrowth 5.00 Desc. 25 ft. over gradual W. slope. Small drain, course SE. Asc. 115 ft. over gradual E. 10.00 slope to Set an iron post, 3 ft. long, 1 in. in diam., on bed rock, deposit a stone marked with a cross (X) at base 39.95 of post and raise a mound of stone around post, for 1 sec. cor., marked on brass cap ½ S 16 S 21 Continue ascent over gradual NE. slope.
Ridge, bears SE. and NW. Desc. gradual SW. slope.
Ridge, bears N. 80° E., and S. 80° W. Desc. 25 ft. to
The cor. of secs. 16, 17, 20 and 21. 48.00 77.90 79.90 Land; slightly rolling. Soil; rocky, 3rd rate. Timber; Scattering Scrub cedar and pine. Undergrowth; sagebrush and chamiso. Good grass. N. 0° 03' W., bet. secs. 16 and 17. Over slightly rolling land, thru scattering timber and undergrowth. Desc. 46 ft. over rolling N. slope. Foot of slope, thence over level land. 25.00 40.00

Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for 2 sec. cor., marked on brass cap

S 17 | S 16 1920

From which

A cedar, 16 ins. in diam., bears S. $82\frac{3}{2}$ ° E., 59 lks. dist. marked $\frac{1}{4}$ S 16 B T.

A cedar, 16 ins. in diam., bears N. 842° W., 156 lks. dist. marked \$ S 17 B T.

Road, bears E. to Blue Mountain Tank and Seligman, and W. to Peach Springs.

Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground for cor. of secs. 8, 9, 16 and 17, marked on brass cap

> T 25 N R 10 W S 8 | S 9 S 17 | S 16 1920

42.50

80.00

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

Chains. From which A cedar, 10 ins. in diam., bears N. $27\frac{1}{2}^{\circ}$ E., 238 1ks. dist. marked T 25 N R 10 W S 9 B T. A cedar, 12 ins. in diam., bears N. 553° W., 156 1ks. dist. marked T 25 N R 10 W S 8 B T. No other trees within limits. Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of Land; Slightly rolling. Soil; rocky, 3rd rate. Timber; scrub cedar. Undergrowth; sagebrush, chamiso and cactus. Good grass. N. 89° 54' E., on a random line bet. secs. 9 and 16. Set temp. ½ sec. cor. Intersect N. and S. line 7 lks. N. of the cor. of secs. 40.00 79.94 9, 10, 15 and 16. S. 89° 57' W., on a true line, bet. secs. 9 and 16. Over slightly rolling land, thru scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground for \(\frac{1}{4} \) sec. cor., marked on brass cap 39.97 Dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist. The cor. of secs. 8, 9, 16 and 17. 79.94 Land; slightly rolling: Soil; rocky, 3rd rate. Timber; scrub cedar. Undergrowth; sagebrush, chamiso and cactus. Good grass. N. 0° 03' W., bet. secs. 8 and 9. Over slightly rolling land, thru scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground to bed rock, supported in a mound of stone 40.00 for 1 sec. cor., marked on brass cap S 8 T S 9 From which A cedar, 12 ins. in diam., bears S. 59° E., 53 lks. dist. marked ½ S 9 B T. A cedar, 14 ins. in diam., bears N. 88 W., 33 lks. dist. marked 1 S 8 B T.

Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. 80.00 in the ground for cor. of secs. 4, 5, 8 and 9, marked on brass cap T 25 N R 10 W S 5 S 4

> S 8 | S 9 1920

From which

	Part (Completion) of the Subdivision of ECON 5543
Chains	A cedar, 6 ins. in diam., bears N. 27° E., 253 lks. dist. marked T 25 N R 10 W S 4 B T. A cedar, 6 ins. in diam., bears S. 11½° E., 252 lks. dist. marked T 25 N R 10 W S 9 B T. A cedar, 12 ins. in diam., bears S. 57½° W., 182 lks. dist. marked T 25 N R 10 W S 8 B T. A cedar, 16 ins. in diam., bears N. 22° W., 46 lks. dist. marked T 25 N R 10 W S 5 B T. Land; slightly rolling. Soil; rocky, 3rd rate. Timber; scrub cedar and pinyon. Undergrowth; sagebrush, chamiso and cactus. Fair grass.
40.00 79.88 39.94	N. 89° 57' E., on a random line bet. secs. 4 and 9. Set temp. ½ sec. cor. Intersect N. and S. line, 19 lks. N. of the cor. of secs. 3, 4, 9 and 10. Thence S. 89° 49' W., on a true line bet. secs. 4 and 9. Over rolling land, thru scattering timber and undergrowth Set an iron post, 3 ft. long, 1 in. in diam., 24 ins.
	in the ground, for \frac{1}{4} sec. cor., marked on brass cap
	1 S 4 S 9 1920
79•88	From which A cedar, 8 ins. in diam., bears N. 253° W., 54 lks. dist. marked 4 S 4 B T. A cedar, 8 ins. in diam., bears S. 8° E., 51 lks. dist. marked 4 S 9 B T. The cor. of secs. 4, 5, 8 and 9. Land; rolling, drains NE. Soil; rocky, 3rd and 4th rates. Timber; scrub cedar and pinyon. Undergrowth; chamiso and Spanish dagger. Fair grass.
40.00 ° 80.36 °	Over rolling land, thru scattering timber and undergrowth.
5.75	Desc. 40 ft. over S. slope. Foot of descent. Thence over spurs and small canyons bearing W.
23.95 40.36	Asc. 55 ft. Set an iron post, 3 ft. long, l in. in diam., 24 ins. in the ground for \$\frac{1}{2}\$ sec. cor., marked on brass cap
	S 5 T S 4 1920
,	From which A cedar, 14 ins. in diam., bears N. 601° E., 110 lks. dist. marked 1 S 4 B T. A cedar, 12 ins. in diam., bears S. 482° W., 157 lks. dist. marked 1 S 5 B T. Continue asc. 70 ft. over NE. slope.

Part (Completion) of the Subdivision of Township 25, North, Range 10 West.

Chains. Flat spur, slopes NE., descend gentle S. slope. The cor. of secs. 4, 5, 8 and 9. 58.86 80.36 Land; rolling, drains NW. Soil; rocky, 4th rate. Timber; scrub cedar and pinyon. Undergrowth: chamiso and Spanish dagger. From the Std. Cor. of secs. 31 and 32 on S. bdy. of Tp., described in Book "A". N. 0° 03' W., bet. secs. 31 and 32.

Over: rolling land, thru scattering timber and undergrowth.

Desc. 155 ft. over N. slope. Wash, 20 lks. wide, course NE. Old road in wash, brs. 14.80 NE · and Sw · Asc. 195 ft. over rolling 5. slope.
Ridge, bears N. 70° E., and S. 70° W.
Set an iron post, 5 ft. long, 1 in. in diam., in a mound of stone, for 2 sec. cor., marked on brass cap 39.00 40.00 S 31 S 32 1920 From which A pine, 12 ins. in diam., bears S. 10½° E., 69
lks. dist. marked ½ S 32 B T.

A pine, 10 ins. in diam., bears N. 48° W., 41 lks.
dist. marked ½ S 31 B T. Desc. 75 ft. over N. slope. 46.50 Drain, course NE. Asc. 52 ft. over SE. slope to 61.00 Low ridge, bears NE. and SW. Desc. 115 ft. to Draw, course NE. Asc. 25 ft. Set an iron post, 3 ft. long, 2 ins. in diam., in a mound of stone, for cor. of secs. 29, 30, 31 and 32, marked 69.30 80.00 on brass cap T 25 N R 10 W S 30 | S 29

S 31 S 32 1920

From which A pine, 8 ins. in diam., bears N. 163° E., 74 lks. dist. marked T 25 N R 10 W S 29 B T. A pine, '10' ins. in diam., bears S. 68% E., 95 lks. dist. marked T 25 N R 10' W 5.32 B T. A pine, 14 ins. in diam., bears S. 693° W., 96 lks. dist. marked T 25°N R 10 W S 31 B T. A cedar, 8 ins. in diam., bears N. 41½° W., 84 lks. dist. marked T 25 N R 10 W S 30 B T. Land; rolling. Soil; rocky, 4th rate. Timber; scrub pine and juniper. Undergrowth; chamiso, cactus and sagebrush.

East, on a random line bet. secs. 29 and 32. 40.00 Set temp. 4 sec. cor. Intersect N. and S. line 2 lks. S. of the cor. of secs. 79.98 28, 29, 32 and 33.

S. 89° 59' W., on a true line bet. secs. 29 and 32. Over rolling land, thru scattering timber and undergrowth.

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

	Township 25 North, Range 10 West.
Chains 4.00 30.00 38.00 39.99	Asc. 280 ft. from Yampai Canyon over E. slope. Spur, slopes N. Desc. 57 ft. over W. slope to Drain, course N. Asc. Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for \(\frac{1}{4} \) sec. cor., marked on brass cap
,	\$\frac{\\$5}{\\$5}\frac{\\$5}{\\$5}\frac{29}{\\$5}\frac{1920}{\\$7}
51.00 60.50 71.20 79.98	From which A cedar, 10 ins. in diam., bears N. 523° E., 56 lks. dist. marked 1 2 29 B T. A cedar, 10 ins. in diam., bears S. 381° E., 171 lks. dist. marked 1 2 32 B T. Asc. 86 ft. over SE. slope. Spur, slopes N. 20° E. Desc. 126 ft. over NW. slope to Wash, 10 lks. wide; course N. Drain, course N. Asc. 108 ft. over E. slope to The cor. of secs. 29, 30, 31 and 32. Land; rolling. Soil; rocky, 4th rate. Timber; scrub pine and cedar. Undergrowth; cactus, sagebrush and chamiso.
,	
40.00 79.94 3.75 28.50 39.94	West, on a random line bet. secs. 30 and 31. Set temp. ½ Sec. cor. Fall 4 1ks. N. of the cor. of secs. 25, 30, 31 and 36, on W. bdy. of Tp., hereinbefore described. Thence N. 89° 58' E., on a true line bet. secs. 30 and 31. Over rolling and mountainous land, thru scattering timber and undergrowth. Asc. 34 ft. over W. slope. Spur, slopes N. Desc. 190 ft. over E. slope. Canyon, course N. Asc. 40 ft. to Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for ½ sec. cor., marked on brass cap
V 8	$\frac{1}{4}$ $\frac{S}{S}$ $\frac{30}{S}$
79.94	From which A cedar, 12 ins. in diam., bears N. 48° E., 34 lks. dist. marked ½ S 30 B T. A cedar, 16 ins. in diam., bears S. 33½° W., 31 lks. dist. marked ½ S 31 B T. Asc. 182 ft. over W. slope to Ridge, bears N. and S. Desc. 176 ft. over E. slope. Small canyon, course N. Asc. 154 ft. over W. slope, to Spur, slopes N. Desc. 85 ft. to The cor. of secs. 29, 30, 31 and 32. Land; rolling. Soil; rocky, 4th rate. Timber; scrub pine and cedar. Undergrowth; chamiso, sagebrush and cactus.
	N. 0° 03' W., bet. secs. 29 and 30.

N. 0° 03' W., bet. secs. 29 and 30.
Over rolling land, thru scattering timber and undergrowth Desc. 380 ft. over N. Slope to Set an iron post, 3 ft. long, 1 in. in diam., 26 ins.

40.00

```
Part (Completion) of the Subdivision of
                       Township 25 North, Range 10 West.
Chains
              in the ground, for 4 sec. cor., marked on brass cap
                                       S 30 | S 29
1920
              From which
                     A pine, 10 ins. in diam., bears N. 53° E., 42
                            lks. dist. marked \( \frac{1}{4} \) S 29 B T.
                     A cedar, 12 ins. in diam., bears N. 71° W., 41 lks. dist. marked 4 S 30 B T.
           Continue descent 63 ft.
44.00
           Enter Yampai Canyon.
           A. T. and S. F. R. R. right of way fence bears E. and W. Wash, 30 lks. wide, 4 ft. deep, course W.
53.25
53.60.
           Telephone line, bears E. and W. A. T. and S. F. R. R. brs. East to Nelson and W. to
54.30
54.75
            . Peach Springs.
           From this point Shipley Siding brs. west 22. chs. dist. Telegraph line, bears E. and W.
55.40
           Right of way fence bears E. and W. Road, bears E. to Nelson and W. to Peach Springs.
56.65
57.35
58.00 Leave valley and asc. over S. slope, 240 ft. to
           Mark a cross (X) on surface rock at exact cor. point and
80.00
              over same, set an iron post, 3 ft. long, 2 ins. in diamsupported in a mound of stone, for cor. of secs. 19, 20, 29 and 30, marked on brass cap
                                        T 25 N
                                                  R 10 W
                                        S 19 | S 20
                                          S 30 S 29
                                              19'20
           Land; rolling.
Soil; rocky, 4th rate.
           Timber; Scrub pine and cedar.
           Undergrowth; chamiso, sagebrush and cactus.
           N. 89° 59' E., on a random line bet. secs. 20 and 29.
           Set temp. \frac{1}{2} Sec. cor.
40.00
79.90
           Intersect N. & S. line 14 lks. N. of the cor. of secs.
              20, 21, 28 and 29.
           Thence
           N. 89° 55' W., on a true line bet. secs. 20 and 29
           Over rolling land, thru scattering timber and undergrowth Desc. 267 ft. over W. slope.
Canyon, course S. 20° W. Asc. 150 ft. over SE. slope.
Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for \( \frac{1}{4} \) sec. cor., marked on brass cap
18.15
39.95
                                         $ S. 20
                                             1920
              From which
                     A pine, 5 ins. in diam., bears N. 521° E., 51 lks. dist. marked 1 S 20 B T.
                     A cedar, 6 ins. in diam., bears S. 76\frac{1}{2}^{\circ} W., 72 lks. dist. marked \frac{1}{4} S 29 B T.
           Desc. 90 ft. to
           Foot of descent. Asc. 154 ft. to
50.00
           Flat spur, slopes S. Desc. 200 ft. to
65.60
           Drain, course S. Asc. 100 ft. over E. slope. The cor. of secs. 19, 20, 29 and 30.
75.15
79.90
           Land; rolling.
           Soil; rocky, 4th rate.
```

Part (Completion) of the Subdivision of Township 25, North, Range 10 West.

```
Chains,
            Timber, scrub, pine and cedar.
            Undergrowth; chamiso, sagebrush and cactus.
            S. 89° 58' W., on a random line bet. secs. 19 and 30.
            Set temp. 1 sec. cor.
40.00
79.80
            Fall 10 1ks. N. of the cor. of secs. 19, 24, 25 and 30
               on W. bdy. of Tp., hereinbefore described.
           Thence
N. 89° 54' E., on a true line bet. secs. 19 and 30.
Over rolling spurs, sloping south, thru scattering tim-
               ber and undergrowth.
           Asc. 25 ft.
            Top of asc., desc. 50 ft.
 7.30
           Asc. 127 ft.
 9. 20
            Top of asc. over flat spur.
19.00
           Desc. 20 ft.
25.00
28.00
           Asc. 100 ft.
           Desc. 17 ft. to ½ sec. cor.

Set an iron post, 3 ft. long, 1 in. in diam., in a mound of stone, for ½ sec. cor., marked on brass cap
33.90
39.80
                                             1920
              From which
                     A pine, 4 ins. in diam., bears N. 463° W., 61
lks. dist. marked 1 S 19 B T.
A pine, 8 ins. in diam., bears S. 4° W., 77 lks.
                            dist. marked $\frac{1}{4}$ 5 30 B T.
            Desc. 45 ft.
           Drain, course S., asc. 45 ft. Top of asc., desc. 154 ft. to
56.30
59.35
           Drain, course S. Asc. 85 ft. over W. slope to Spur, slopes S., desc. 27 ft. to
72.30
77:80
            The cor. of secs. 19, 20, 29 and 30.
79.80
           Land; rolling.
           Soil; rocky, 4th rate.
           Timber; Scrub cedar and pine.
           Undergrowth; chamiso, sagebrush and cactus.
           N. 0° 03' W., bet. secs. 19 and 20.

Over rolling land, thru scattering timber and undergrowth Asc. 147 ft. over SE. slope.

Ridge, bears NE. and SW.

Desc. 85 ft. over NW. slope.
12.50
22.50
           Wash, course E. Asc. 60 ft. over S. slope to
Set an iron post, 3 ft. long, 1 in. in diam., in a mound
of stone, for 4 sec. cor., marked on brass cap
36.50
40.00
                                          S 19 3 S 20
              From which
                  A cedar, 6 ins. in diam., bears S. 87° E., 46 lks. dist. marked 4 S 20 B T.
                     A pinyon, 8 ins. in diam., bears S. 79° W., 236 lks. dist. marked \( \frac{1}{4} \) S 19 B T.
           Continue ascent 30 ft. to
           Ridge, bears E. and W. Desc. 60 ft. over N. slope to
43.00
           Wash, course E. Asc. 70 ft. over SE. slope to
54.10
           Top of asc., thence along W. slope.
75.00
```

Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in

80.00

Part (Completion) of the Subdivision of Township 25, North, Range 10 West.

the ground for cor. of secs. 17, 18, 19 and 20, marked Chains on brass cap T 25 N R 10 W S 18 | S 17 S 19 S 20 1920 From which A cedar, 12 ins. in diam., bears N. 682° E., 155 1ks. dist. marked T 25 N R 10 W S 17 B T. A cedar, 12 ins. in diam., bears S. 354° E., 289 lks. dist. marked T 25 N R 10 W S 20 B T.

A cedar, 8 ins. in diam., bears S. 373° W., 206
lks. dist. marked T 25 N R 10 W S 19 B T.

A cedar, 16 ins. in diam., bears N. 721° W., 225 1ks. dist. marked T 25 N R 10 W S-18 B T. Land; rolling, drains E. Soil; rocky, 4th rate. Timber; scrub cedar and scattering pinyon. Undergrowth; sagebrush, chamiso and cactus. S. 89° 55' E., on a random line bet. secs. 17 and 20. Set temp. ½ sec. cor. Intersect N. and S. line, 5 lks. South of the cor. of 40.00 79.96 secs. 16, 17, 20 and 21. N. 89° 57' W., on a true line bet. secs. 17 and 20. Over rolling land, thru scattering timber and undergrowth Desc. 110 ft. over gradual W. slope to 8.00 Wash, course S. Asc. 74 ft. over E. slope 27.00 Top of ascent, thence along S. slope. 32.00 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in 39.98 the ground to bed rock, supported in a mound of stone, for 4 sec. cor., marked on brass cap 8 20 1920 From which A cedar; 16 ins. in diam., bears N. 643° W., 73 lks. dist. marked 1 S 17 B T. A cedar, 8 ins. in diam., bears S. 472° E., 89 lks. dist., marked 2 S 20 B T. Desc. 63 ft. over W. slope to Wash, course S., asc. 57 ft. to 45.00 55.00 Along S. slope to 60.00 Desc. 23 ft. to cor. 70.00 The cor. of secs. 17, 18, 19 and 20. 79.96 Land; rolling, drains SW. Soil; rocky, 3rd rate. Timber; scrub cedar and scattering pinyon. Undergrowth; sagebrush, chamiso and cactus. Fair grass. S. 89° 54' W., on a random line bet. secs. 18 and 19. Set temp. \(\frac{1}{4}\) sec. cor. 40.00 Fall 7 lks. N. of the cor. of Secs. 13, 18, 19 and 24 79.74 on W. bdy. of Tp., hereinbefore described. Thence N. 89° 51' E., on a true line bet. secs. 18 and 19.

Over rolling land, thru scattering timber and undergrowth Desc. 65 ft. over E. slope to

ECCK SEAS

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

```
Chains
  7.75
             Wash, course S. Asc. 42 ft. to
             Ridge, bears N. 20° E. and S. 20° W. Desc. 154 ft. over
12.55
                SE. slope to
             Gulch, course SW. Asc. 145 ft. over W. slope to Ridge, bears N. and S. Desc. 90 ft. to Set an iron post, 3 ft. long, 1 in. in diam., 26 ins.
20.00
33.00
39.74
                 in the ground for \frac{1}{4} sec. cor., marked on brass cap
                                                $\frac{1}{5} \frac{18}{5} \frac{18}{19}
                                                     1920
                                                                 Raise a mound of stone,
             2 ft. base, 1½ ft. high N. of cor.

Wash, course S. Asc. 76 ft. over W. slope.

Top of ascent. Desc. 28 ft. to

Foot of descent. Asc. 51 ft. to

Ridge, bears N. and S. Desc. 34 ft.
40.25
45.75
49.20
56.34
71.00
             Wash, course S. Asc. 65 ft.
79.74
             The cor. of secs. 17, 18, 19 and 20.
             Land; rolling, drains S. Soil; rocky, 4th rate.
             Timber; scrub cedar and scattering pine.
             Undergrowth; sagebrush, chamiso and cactus.
             N. 0° 03' W., bet. secs. 17 and 18.

Over rolling land, thru scattering timber and undergrowth Asc. 46 ft. over gradual SW. slope to.

Spur, slopes W. Desc. 67 ft. over N. slope to \(\frac{1}{4}\) cor.
15.00
37.40
             Road brs. E. to Blue Mountain Tank and Seligman and
                West to Peach Springs.
             Set an iron post, 3 ft. long, l in. in diam., 16 ins. in the ground to bed rock, supported in a mound of stone, for 2 sec. cor., marked on brass cap
40.00
                                              S 18 | S 17
                                                   1920
                From which
                     A cedar, 10 ins. in diam., bears N. 823° E., 148 lks. dist. marked ½ S 17 B T.
             A cedar, 10 ins. in diam., bears S. 73½° W., 65 lks. dist. marked ½ S 18 B T.

Asc. over gradual S. slope, 40 ft.
50.00
             Flat spur, slopes NE. Desc. 243 ft. over rolling NW.
60.00
                slope.
             Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins. in the ground for cor. of secs. 7, 8, 17 and 18,
80.00
                marked on brass cap
                                              T 25 N R 10 W
                                                  57|58
                                                 S 18 S 17
                                                      1920
                From which
                        A cedar, 5 ins. in diam., bears S. 81° E., 181
                        lks. dist. marked T 25 N R 10 W S 17 B T. A cedar, 6 ins. in diam., bears S. 65° W., 134 lks. dist. marked T 25 N R 10 W S 18 B T.
```

No other trees within limits.
Raise a mound of stone, 2 ft. base, 12 ft. high W. of cor.
Land; rolling mountainous.

Soil; rocky, 4th rate.

A cedar, 12 ins. in diam., bears N. 313° W., 82 lks. dist. marked T 25 N R 10 W S 7 B T.

Part (Completion) of the Subdivision of

	Part (Completion) of the Subdivision of Township 25 North, Range 10 West.
Chains	Timber; pinyon and cedar. Undergrowth; chamiso and Spanish dagger.
•	• • • • • • • • • • • • • • • • • • • •
 40.00 79.86	S. 89° 57' E., on a random line bet. secs. 8 and 17. Set temp. ½ sec. cor. Intersect N. and S. line, 19 lks. N. of the cor. of secs. 8, 9, 16 and 17.
39•93	Thence N. 89° 49' W., on a true line bet. secs. 8 and 17. Over nearly level land, thru scattering timber and undergrowth. Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground to bed rock, supported in a mound of stone for \$\frac{1}{2}\$ sec. cor., marked on brass cap
	2 S 8 S 17 1920
51.00 73.80 79.86	From which A pine, 7 ins. in diam., bears N. 243° W., 188 lks. dist. marked 1 S 8 B T. A pine, 8 ins. in diam., bears S. 553° W., 80 lks. dist. marked 2 S 17 B T. Asc. gradually over E. slope. Spur, slopes N. Desc. slightly over rolling N. slope. Spur, slopes NW. Desc. 92 ft. to The cor. of secs. 7, 8, 17 and 18. Land; rolling mountainous, drains NW. Soil; rocky, 4th rate. Timber; pinyon and scrub cedar. Undergrowth; chamiso and Spanish dagger. Fair grass.
40.00 79.70 10.00 20.00 28.15 33.10 39.70	S. 89° 51' W., on a random line bet. secs. 7 and 18. Set temp. ½ Sec. cor. Fall 5 lks. N. of the cor. of secs. 7, 12, 13 and 18, on W. bdy. of Tp., hereinbefore described. Thence N. 89° 49' E., on a true line bet. secs. 7 and 18. Over rolling mountainous land, thru scattering timber and undergrowth. Desc. 138 ft. over E. slope to Foot of descent. Asc. 92 ft. to Top of ascent. Desc. 60 ft. Asc. 25 ft. Desc. 35 ft. Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bed rock, supported in a mound of stone, for ½ sec. cor., marked on brass cap
52•70 79•70	From which A pine, 6 ins. in diam., bears N. 15½° W., lks. dist., marked ½ S 7 B T. A pine, 8 ins. in diam., bears S. 13¾° E., lks. dist., marked ½ S 18 B T. Asc. 152 ft. over NW. slope. Flat spur, slopes NE. Desc. 260 ft. rolling NE. slope The cor. of secs. 7, 8, 17 and 18. Land; rolling mountainous.

POOK 3543

```
Township 25 North, Range 10 West.
Chains
             Soil; rocky, 4th rate.
             Timber; pinyon and Scrub cedar.
             Undergrowth; chamiso and Spanish dagger.
            N. 0° 03' W., bet. secs. 7 and 8. Over rolling mountainous land, thru scattering timber
            and undergrowth.

Wash, 10 lks. wide, 2 ft. deep, course NE. Asc. 36 ft.

Spur, slopes NE. Desc. 85 ft. over NW. slope.
    .70
  7.50
16.30
             Wash, 20 lks. wide, 2 ft. deep, course NW. Asc. 30 ft.
         over S. slope.

Flat spur, slopes W. Desc. 43 ft. to

Wash, 10 lks. wide, 6 ft. deep, course NW. Asc. 75 ft.

Set an iron post, 3 ft. long, 1 in. in diam., 6 ins.

in the ground to bed rock, supported in a mound of stone, for \( \frac{1}{2} \) sec. cor., marked on brass cap
22.00
33.00
40.00
                                           S 7 S 8
1920
                From which
                       A cedar, 12 ins. in diam., bears East, 4 1ks.
dist. marked \(\frac{1}{4}\) S 8 B T.

A pine, 12 ins. in diam., bears S. 52\(\frac{3}{4}\) W., 103
                                lks. dist. marked 1 S 7 B T.
            Asc. 24 ft. to
45.50
            Mat spur, slopes W. Desc. 70 ft. to
77.00
             Ravine, course W. Asc. 45 ft.
80.00
            Set an iron post, 3 ft. long, 2 ins. in diam., 24 ins.
                in the ground for cor. of secs. 5, 6, 7 and 8, marked
                on brasš cap
                                          T 25 N R 10 W
                                              S 6 | S 5
                                              S 7 | S 8
                                                 1920
                From which
                       A pine, lo ins. in diam., bears N. 59° E., 120 lks. dist. marked T 25 N R 10 W S 5 B T.
                       A pine, 10 ins. in diam., bears S. 631° E., 163
lks. dist. marked T 25 N R 10 W S. 8 B T.
                       A pine, 12 ins. in diam., bears S. 161 W., 1

1ks. dist. marked T 25 N R 10 W S. 7 B T.

A pine, 12 ins. in diam., bears N. 322 W., 1

1ks. dist. marked T 25 N R 10 W S. 6 B T.
            Land; rolling mountainous, drains W. Soil; rocky, 4th rate.
            Timber; pinyon and scrub cedar.
            Undergrowth; chamiso and Spanish dagger.
            S. 89° 49' E., on a random line bet. secs. 5 and 8. Set temp. 1 sec. cor. Intersect N. and S. line, 16 lks. S. of the cor. of
40.00
79.76
               secs. 4, 5, 8 and 9
            Thence
            N. 89° 56' W., on a true line bet. Secs. 5 and 8.
            Over slightly rolling land, thru scattering timber and
               undergrowth.
            Asc. 46 ft. to
15.00
            Desc. 23 ft. to
```

Small ravine, course N. Asc. 25 ft. to Set an iron post, 3 ft. long, 1 in. in diam., in a mound

of stone, for \frac{1}{4} sec. cor., marked on brass cap

22.50 39.88

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

1		Township 25 North, Range 10 West.
	Chains	\$ 5. \$ 8 1920
		From which A cedar, 8 ins. in diam., bears N. 3° W., 12 lks. dist. marked ½ S 5 B T. A pinyon, 16 ins. in diam., bears S. 383° E., 66 lks. dist. marked ½ S 8 B T.
	41.60 60.00 79.76	Desc. 117 ft. over W. slope Thence desc. 123 ft. over SW. slope to The cor. of secs. 5, 6, 7 and 8. Land; rolling, drains W. Soil; rocky, 3rd rate. Timber; pinyon and scrub cedar. Undergrowth; sagebrush, chamiso and cactus.
	40.00 79.70	S. 89° 49' W., on a random line bet. secs. 6 and 7. Set temp. ½ sec. cor. Fall 26 lks. S. of the cor. of secs. 1, 6, 7 and 12 on W. bdy. of Tp., hereinbefore described. Thence East, on a true line bet. secs. 6 and 7.
	20.30 25.00 32.70 39.70	Over rolling land, thru scattering timber and undergrowth Desc. 128 ft. over SE. slope. Wash, course NE. Asc. 110 ft. to Spur, slopes N. Desc. 138 ft. over E. slope to Bottom of canyon, 5 chs. wide, course N. Asc. 185 ft. to Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bed rock, supported in a mound of stone, for 2 sec. cor., marked on brass cap
		1 S 6 S 7 1920
	64.70	Raise a mound of stone, 2 ft. base, 1 ft. high N. of cor.
	40.00 80.08	N. 0° 16' W., on a random line bet. secs. 5 and 6. Set temp. ½ sec. cor. Fall 7 lks. E. of the cor. of secs. 5, 6, 31 and 32 on N. bdy. of Tp., hereinbefore described. Thence S. 0° 19' E., on a true line bet. secs. 5 and 6.
	23.00 59.00 40.08	Over rolling mountainous land, thru scattering timber and undergrowth. Asc. 30 ft. Desc. 260 ft. over S. slope to Small canyon, course W. Asc. Set an iron post, 3 ft. long, l in. in diam., 24 ins. in the ground for 2 sec. cor., marked on brass cap
	<i>1</i> .	S 6 S 5 1920

Part (Completion) of the Subdivision of Township 25 North, Range 10 West.

BOOK 3543

Chains

51.00

58.50 72.80

80.08

From which

A cedar, 12 ins. in diam., bears S. 843° E., 24 lks. dist. marked \$5 5 B T.

A pine, 10 ins. in diam., bears S. 5½° W., 43 lks. dist. marked ½ S 6 B T.

Asc. 57 ft. to

Spur, slopes W.

Spur, slopes W. Desc. 29 ft. to Canyon, course W. Asc. 166 ft. over N. slope.

Spur, slopes W. Desc. 100 ft. over S. slope to

The cor. of secs. 5, 6, 7 and 8.

Land; rolling mountainous, drains W. Soil; rocky, 4th rate.

Timber; pinyon and scrub cedar.

Undergrowth; chamiso and Spanish dagger.

Fair grass.

The continued satisfactory adjustment of the instruments thruout the survey of this township is indicated from field tests as shown in Book "D"

GENERAL DESCRIPTION.

The portion of this township surveyed as described in the foregoing field notes is situate entirely within the Hualpai Indian Reservation. The Surface is rolling. The drainage in general is toward the west. The Soil is of a gravelly and rocky nature, mostly 3rd and 4th rate.

The timber consists principally of juniper and pinyon scattered more or less thruout the township. There are no permanent streams in the township and no springs, although there is one tank in Sec. 10, containing water for Stock.

The A. T. & S. F. R. R. crosses the southern portion of the township also the Old Trails National highway. There are no settlers in the township. No apparent indications of mineral deposits were found.

4 - 680

FIELD ASSISTANTS.

to Francis R. Ih:	rie, U. S. Transitman
NAMES.	CAPACITY.
,	
Julius S. Owens	lst Chainman
Theo . Anthony	2nd Chainman
Geo . Demorest	Axman
Ed. Mitchel	Moundman
J. J. Hayden	Flagman
John Martin	Moundsman.
3	
	~,
,	
	,

6-2764

BOOK

3543 CERTIFICATE OF UNITED STATES TRANSITIAN.

I g I L L L L L L L L L L L L L L L L L	hereby certify upon honor that, in pursuance
of special instructions received from the U.S. Surveyor General,	for Group 108, Arizona,
bearing date of the 20th day of February,	
in my own proper person, and in strict conformity with said ins	structions, the Manual of Surveying Instruc-
tions, and the laws of the United States, surveyed all those parts	
Subdivision lines of	
·	e 10 West,
River Base and Meridian, in the State of Arizona,	
and by diagram on page 2 hereof the foregoing field notes as having been executed by me, and ur	
said survey have been established and perpetuated in strict accordance	dance with the Manual of Surveying Instruc-
tions, and the special written instructions of the U.S. Surveyor	General, for Group 168, Arizona,
and in the specific menner described in the field notes, and the	t the foregoing are the original field notes of
such survey.	Y Phil
Place Wash, DC	Transitmanoeyer.
Place Mash, DC. Date Copyrol 1, 1923.	
/ APPROVAL	
OFFICE OF THE UNI	TED STATES SURVEYOR GENERAL,
OFFICE OF THE UNI	
The foregoing field notes of the survey of	
The foregoing field notes of the survey of	
The foregoing field notes of the survey of	
The foregoing field notes of the survey of	191
The foregoing field notes of the survey of	191
The foregoing field notes of the survey of executed by under his special instructions dated	, 191 , having been
The foregoing field notes of the survey of	, 191 , having been
The foregoing field notes of the survey of executed by under his special instructions dated	, 191 , having been
The foregoing field notes of the survey of	, 191 , having been
executed byunder his special instructions datedcritically examined, and the necessary corrections and explanat	, 191 , having been ions made, the said field notes, and the surveys
executed by	, 191 , having been ions made, the said field notes, and the surveys
executed by	, 191 , having been ions made, the said field notes, and the surveys U. S. Surveyor General.

4 - 680

BOOK 3543

FIELD ASSISTANTS.

to Horace M. Muscott, U. S. Transitman			
NAMES.	CAPACITY.		
Ross Dykes	1st Chainman		
Geo. Way	2nd Chainman		
E. C. Merril	2nd Chainman		
Homer Pepper	Flagman		
Ted. Lizovich	Moundsman.		
I. C. Perkens	Moundsman.		
	,		
·			
	^		
······································	,		
·	·		
	·		
			
· · · · · · · · · · · · · · · · · · ·			
,			

BOOK 3543

I, Horace M. Muscott, U.S. Transitman, or, hereby certify upon honor that, in pursuance

of special instructions received from the U.S. Surveyor General for Group 108, Arizona,
bearing date of the 20th day of February, 1920, I have well, faithfully, and truly
in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, surveyed all those parts or portions of the
North boundary,
West boundary, and
Subdivision lines of
TOWNSHIP 25 NORTH, RANGE 10 WEST,
of the Gila and Salt
River Base and Meridian, in the State of Arizona, which are represented in and by diagram on page 2 hereof the foregoing field notes as having been executed by me, and under my direction; and that all the corners of
said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the U.S. Surveyor General for Group 108, Arizona,
and in the specific menner described in the field notes, and that the foregoing are the original field notes of
such survey.
and in the specific menner described in the field notes, and that the foregoing are the original field notes of such survey. Place Los Augeles, Calif Horace M. Muscott U.S. Transistman. APPROVAL.
Date march 22 1923
APPROVAL.
OFFICE OF THE UNITED STATES SURVEYOR GENERAL,
Phoenix, Arizona, JUN 18 1923, 1923.
The foregoing field notes of the survey of _the
West boundary,
North boundary, and
Subdivision lines of
TOWNSHIP 25 NORTH, RANGE 10 WEST,
of the Gila and Salt River Base and Meridian, in the State of Arizon
executed by Francis R. Ihrie and Horace M. Muscott, U.S. Transitmen.
under special instructions dated Feby. 28, 1920, for Group 108, Ariz., i.e., having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.
Hamil & Troth
U. S. Surveyor General.
I certify that the foregoing transcript of the field notes of the above-described surveys in
has been correctly copied from the original notes on file in this office.