_ 0..

Book C

BOOK 4025

FIELD NOTES

OF THE

Dependent Resurvey of a Portion, and Survey of a Portion of the
South Boundary of Township 7 South, Range 22 East;
Dependent Resurvey of a Portion of the West Boundary, a Portion
of the South Boundary and a Portion of the Subdivisional Lines;
Survey of the East Boundary and a Portion of the Subdivisional
Lines, Completing the Subdivision of
South Boundary of Township 7 South, Range 22 East; spendent Resurvey of a Portion of the West Boundary, a Portion The South Boundary and a Portion of the Subdivisional Lines; street of the East Boundary and a Portion of the Subdivisional Lines, Completing the Subdivision of Township 8 South, Range 22 East, Of the Gila and Salt River Meridian, he State of Arizona EXECUTED BY Charles E. Hunter, U. S. Transitman, he capacity of U. S. Surveyor , under Special Instructions dated February 20 , 3. issued by the District Cadastral Engineer to govern surveys included in Group 182 , which were approved by the Commissioner of the General Land
· · · · · · · · · · · · · · · · · · ·
Of the Gila and Salt River Meridian,
In the State ofArizona
EXECUTED BY
Charles E. Hunter, U. S. Transitman.
<u></u>
In the capacity of U.S. Surveyor, under Special Instructions dated February 20,
19.33., issued by the District Cadastral Engineer to govern surveys included in Group
No. 182 , which were approved by the Commissioner of the General Land
Office, March 3, 1933, and Assignment Instructions dated Sept. 30, 19.33
Survey commencedOctober, 1933.
Commence of the Property 70

4025

BOOK 4025 INDEX DIAGRAM. T. 75, R. 23 E. Township 8 SOUTH , Range 22 EAST 44 1 52 ² 57 3 59 4 42 12 55 ¹⁰ *50* ¹¹ 34 9 49 14 53 15 41 13 39 24 47 23 27 22

24 26

23 _{as}

36 ₃₆

37 25

A CONTRACT OF THE PROPERTY OF

BOOK 4025

The surveys and resurveys in T. 8 S., R. 22 E., Gila and Salt River Base and Meridian, Arizona, were executed with a Gurley solar transit, serial No. 20120, constructed in accordance with the standard specifications of the General Land Office. The horizontal circle has a diameter of 53 ins., with two double verniers reading to 30 seconds of arc. The vertical circle has a diameter of 42 ins., with one double vernier reading to single minutes. The telescope has fixed stadia wires with a ratio of 1:132, with a focal constant of 1.2 links.

The instrument is equipped with the improved Smith solar attachment, the radius of the latitude are being $2\frac{1}{2}$ ins., and of the declination are 3.1 ins., each with verniers reading to single minutes. The instrument was in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, was approved by the District Cadastral Engineer for Arizona, September 30, 1933.

The direction of the lines were determined by solar transit method. The measurements were made with a Lallie steel tape, five chains in length, graduated ever link for the first 100 links, and the balance at intervals of

The tape was tested by comparison with a Lufkin standard steel tape and found correct. The measurements were made on the slope, the vertical angle for each interval ascertained by a clinometer in good adjustment, and the horizontal equivalents entered in the field note record. The data furnished with the special instructions gives the geographic position of the SE. corner of the township as follows: latitude 32°41'07"N., longitude 110°02'24"W. October 10, 1933: In camp at the Hickman homestead in the SW. 4 of sec. 6, T. 8 S., R. 22 E., G. and SR. base and meridian, Arizona, in latitude 32°45'30"N.; longitude 110°07'21"W., at 7h 58m 42s p.m., by my watch which reads correct 105th meridian standard time, having been compared with a Western Union telegraph clock at Globe, Arizona on this date, I make an hour angle observation on Polaris east of the meridian for azimuth and latitude, two each

Mean watch time of observation ----- 7h 58m 42s
Mean horizontal angle to mark ----- 60°19'15"
Azimuth of Polaris ----- 1.09'30"
True bearing of reference mark ----- N.59°09'45"W,

with the telescope in the telescope in the direct and the reverse positions, reading the deflection angles from a reference mark which is a point on a distant hill, and in

the direction NE. to Polaris.

Watch fast of l.m.t. ----- 20m 29s Mean vertical angle to Polaris ----- 33.10.59 Reduced latitude ----- 32.45.30"

October 11: At 9 a.m., app.t., I set off 32°45½'N. on the latitude arc; 7°02'S., on the declination arc. and determine a meridian with the solar which agrees within l, of the true meridian.

At apparent noon, with the latitude are unchanged. I observe the sun on the meridian, the resulting reading of the declination are is 7°05'S., which agrees with the computed declination of the sun.

At 3h 00m p.m., app.t., with the latitude arc unchanged. I set off 709'S. on the declination arc and determine a meridian with the solar which also agrees within 1' of the true meridian obtained by observation on Polaris.

As all of the solar observations made during the usual hours of solar work, come within $1\frac{1}{2}$ of the true meridian. I conclude that the adjustments of the instrument are satisfactory.

6-815

4-678 b

RESURVEY OF A PORTION OF THE WEST BOUNDARY OF

T. 7 S., R. 23 E.

Chains

The original cor. of secs. 19, 24, 25 and 30, T. 7 S., Rs. 22 and 23 E., is a granite stone, 10 x 8 x 8 ins. above ground, mkd. with 2 notches on S. face; 4 notches on N., with a mound of stone to W. I reconstruct this cor. as follows:

In place of old stone which is set along side, set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 5 ft. base, 12 ft. high, for cor. of secs. 19, 24, 25 and 30, with brass cap marked

T7S
R22E R23E
S24 S19
S25 S30
1933

Thence

South, on a random line, on the W. bdy. of sec. 30.

40.00 No trace of the $\frac{1}{4}$ sec. cor., set temp. cor.

80.00 No trace of the cor. of secs: 25, 30, 31 and 36, set temp.

120.00 No trace of the $\frac{1}{4}$ sec., set temp. cor.

No trace of the cor. of Tps. 7 and 8 S., Rs. 22 and 23 E., set temp. township cor.

Thence

East, on a random line, bet. Tps. 7 and 8 S., R. 23 E., searching for \$\frac{1}{4}\$ sec. and sec. cors. at record distances without success, setting temp. cors. at such record distances, and at

393.78

Fall 7.17 chs. S. of the original cor. of secs. 1, 2, 35 and 36, Tps. 7 and 8 S., R. 23 E., which is a granite stone in place, 2 x 3 x 4 ft., mkd. with a cross +, on top; 5 notches on W. face; 1 notch on E., and witnessed by a mound of stone to N. The old stone is in good condition, and I therefore do not remonument with an iron post. From corner,

Old bearing trees

There is no evidence of the old bearing tree.

New bearing trees

An oak tree, 10 ins. diam., brs. N. 3°30'E.,154 lks. dist., mkd. T7S R23E S36 BT.

A juniper tree, 12 ins. diam., brs. N.84°15'W., 108 lks. dist., mkd. T7S R23E S35 BT.

At a point determined by cardinal offsets, 160.00 chs. dist. S., in latitude, from the cor. of secs. 19, 24, 25 and 30, T. 7 S., Rs. 22 and 23 E., and 398.65 chs. dist., W., in departure, from the cor. of secs. 1, 2, 35 and 36, Tps. 7 and 8 S., R. 23 E., I reestablish the cor. of T. 7 S., R. 23 E. only, as follows:

Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 2 ft. high, for cor. of T. 7 S., R. 23 E. only, with

U. S. GOVERNMENT PRINTING OFFICE: 1931 6-8155

Door 40f

T. 7 S., R. 23 E.

	Chains	brass cap marked
		T7S R23E
	,	T8s R23E
		S 6 From which
		A pine tree, 14 ins. diam., brs. N.82°00'E., 9 lks. dist. mkd. T7S R23E S31 BT.
		A pine tree, 9 ins. diam., brs. N.11°00'E., 28 lks. dist., mkd. T7S R23E S31 BT.
:		Thence
		N. 1°45'E., on true line, on the W. bdy. of sec. 31.
•		Over NE. slope, through scattering timber and brush, desc. 134 ft.
٠.	4.20	Ravine, course N.10 W., thence over NW. slope, desc. 25 ft.
	7.68	A point due E. of the cor. of secs. 32 and 33, on the S. bdy. of T. 7 S., R. 22 E., hereinafter described, which is the true point for the cor. of T. 7 S., R. 22 E. and T. 8 S., R. 23 E. This point falls in a place unsuitable
		for a permanent cor. At a point 50 lks. W. of true point for cor.,
		Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for witness cor. of T. 7 S., R. 22 E. and T. 8 S., R. 23 E. only, with brass cap marked
		T7S R22E S36 T7S R23E WC S6 T8S R23E 1933 from which
	n	A cross +, chiseled on a rock ledge, brs. N. 28°30'W 30 lks. dist., followed by mks. B& WC T7S R22E S36.
	7.80	Small ravine, course W., thence along open broken W. slope.
	40.02	Proportional distance, set temp. \(\frac{1}{4} \) sec. cor. of sec. 31 only, of R. 23 E.
		Land, rough mountainous. Soil, rocky; 4th rate. Timber, first five chs. scattering pine and fir. Undergrowth, oak brush.
		RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
		T. 7 S., R. 22 E.
		The W. two miles of the S. bdy. of T. 7 S., R. 22 E., was surveyed by C. H. Wallace, U.S. Deputy Surveyor, in 1886. In 1915, T. B. Matthews, U. S. Surveyor, reconstructed the cor. of Tps. 7 and 8 S., Rs. 21 and 22 E., in conjunction with his resurvey of the W. bdy. of T. 7 S., R.

RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF T. 7 S., R. 22 E.

Chains	22 E.
	From the cor. of Tps. 7 and 8 S., Rs. 21 and 22 E.
	S. 89°28'E., on a random line, on the S. bdy. of sec. 31.
51.40	Fall 24 lks. S. of the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.
	Thence, from cor.
	S.89°28'E., on a random line, on the S. bdy. of sec. 31.
40.32	Fall 16 1ks. S. of the cor. of secs. 5, 6, 31 and 32.
	Thence, from cor.
	S.89°28'E., on a random line, on the S. bdy. of sec. 32.
40.00	No trace of the $\frac{1}{4}$ sec. cor. of secs. 5 and 32. Set temp.
80.00	No trace of the cor. of secs. 4, 5, 32 and 33. At this point which is record distance and bearing from the cor. of secs. 5, 6, 31 and 32,
	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, $1\frac{1}{2}$ ft. high, for cor. of secs. 32 and 33 only, with brass cap marked
	T7S R22E
	S4 T8S R22E 1933
	from which
	A juniper tree, 24 ins. diam., brs. N.81°15'W.,396 lks. dist., mkd. T7S R22E S32 BT.
	A juniper tree, 24 ins. diam., brs. N.68°15'E.,355 lks. dist., mkd. T7S R22E S33 BT.
	Thence
•	N.89°28'W., on true line, on S. bdy. of sec. 32.
. •	Over nearly level ground, through scattering undergrowth.
2.00	Wire fence, brs. N.15°E. and S. 15°W.
10.00	Ascend 20 ft. over NE. slope.
12.89	A point 80 chs. W. in departure from the cor. of secs. 3 and 4, of T. 8 S., hereinafter described,
	Set an iron post, 3 ft. long, 2 ins. diam., in crevice bet. two large bowlders mounded in with stone, 2 ft. below top surface, for cor. of secs. 4 and 5, of T. 8 S., only, with brass cap marked
	T7S R22E S32 S5 S4 T8S R22E 1933
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, on top of bowlder to S.

14.50 Descend 50 ft. over NW. slope.

DOCK 4025

Chains 17.30	Gulch, course NE.; asc. 158 ft.
31.00	Rocky spur, slopes NE.; desc. 227 ft.
40.00	At this point which is record distance and bearing from the cor. of secs. 5, 6, 31 and 32,
	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a stone mkd. with a cross +. at base, in a mound of stone, 5 ft. base, 2½ ft. high. for ½ sec. cor. of sec. 32 only, with brass cap marked
	$\frac{\frac{1}{4} \text{ S } 32}{1933}$
	1933
	Descend 102 ft.
50.70	Gulch, course N.; asc. 185 ft. over NE. slope.
√ 52. 89	A point 40 chs. W. in departure from the cor. of secs. 4 and 5, of T. 8 S.,
	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for \(\frac{1}{4}\) sec. cor. of sec. 5 only, with brass cap marked
	4 S 5
	½ S 5 1933
	from which
•	JA juniper tree, 6 ins. diam., brs. S.47°45'W., 178 lks. dist., mkd. ½ S5 BT.
66.30	Spur, slopes N.30°W., desc. 123 ft.
73 • 30	Draw, course NW.
76.60	Low spur, slopes NW.
80.00	The original cor. of secs. 5, 6, 31 and 32, which is a granite stone, 10 x 8 x 10 ins. above ground, mkd. with 5 notches on E. face, and 1 notch on W., from which
	A cedar tree, 12 ins. diam., brs. N.6°W., 23 lks. dist., marks illegible.
	dead cedar tree, 14 ins. diam., brs. N.64 W 85 lks. dist., mkd. T7S R22E S31 BT.
• • •	In place of old stone, which is set along side,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. of secs. 31 and 32 only, with brass cap marked
	T7S R22E S31 S32 S5
	T8S R22E 1933 from which

'A cedar tree, 14 ins. diam., brs. N.56°15.W.,100 lks. dist., mkd. T7S R22E S31 BT.

RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF

T. 7 S., R. 22 E.

Chains A cedar tree, 14 ins. diam., brs. N.43°15'E., 167 1ks. dist., mkd. T7S R22E S32 BT.

Land, rolling. Soil, 2nd rate.

Timber, a few scattering juniper. Undergrowth, oak brush.

Thence

N.89°42'W., on true line, on the S. bdy. of sec. 31.

Over gradual NW. slope, through scattering timber and undergrowth, desc. 25 ft.

5.80 | Small draw, course NW.

12.00 Gulch, course from S. to NE.; asc. 10 ft.

12.89 A point 80 chs. W. in departure, from the cor. of secs. 4 and 5, of T. 8 S.,

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, $2\frac{1}{2}$ ft. high, for cor. of secs. 5 and 6 only, of T. 8 S., with brass cap marked

T7S R22E S31 S6 S5 T8S R22E 1933

from which

An oak tree, 10 ins. diam., brs. S.21°30'W.,236 lks. dist., mkd. T8S R22E S6 BT.

√A juniper tree, 16 ins. diam., brs. 5.56°00'E.,316 lks. dist., mkd. T8S R22E S5 BT.

14.20 | Small spur, slopes NE.; desc. 32 ft.

20.90 | Gulch, course NE.; asc. 156 ft.

35.80 Top of white felcite dike, brs. NE. and SW.; desc. 30 ft.

The original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, which is a felcite stone, 12 x 5 x 10 ins. above ground, mkd. $\frac{1}{4}$ on N. face, and witnessed by a mound of stone to N. In place of old stone, which is set along side,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap marked

1933

rebuild the mound

of stone to N.

Thence

 \vee N.89°44'W., on true line, on the S. bdy. of sec. 31.

Descend 57 ft. over open NW. slope.

9.80 | Draw, course N.; thence over nearly level ground.

T. 7 S., R. 22 E.

4025

	500K	4(
Chaina	nger -	
Chains	A point 40 chs. W. indeparture from the cor. of secs. 5 and 6, of T. 8 S.,	
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 6 only, of T. 8 S., with brass cap marked	
	4 s 6	
	1933 from which	
,	A juniper tree, 7 ins. diam., brs. S.14°30'E., 27 lks. dist., mkd. 4 S 6 BT.	
13.70	Low ridge, brs. N. and S.	
17.70	Spur, slopes NW.; desc. 92 ft. over W. slope.	,
39.50	Gulch, course NW.; asc. 25 ft. over E. slope.	
45.50	Low ridge, brs. N. and S.; desc. 50 ft.	
v 51.40	The cor. of Tps. 7 and 8 S., Rs. 21 and 22 E., which is an iron post, 3 ins. diam., 12 ins. above ground, with brass cap marked	3
•	R21E S36 S31 R22E S1 S6 T8S 1915 rebuilt the mound	
	of stone to N. of cor, a small gulley being close to S. side of corner, where mound would normally be placed.	
	Land, rolling. Soil, gravelly; 3rd rate. No timber; undergrowth, oak brush.	
¥		
	SURVEY OF A PORTION OF THE SOUTH BOUNDARY OF	
	T. 7 S., R. 22 E.	
	From true point for the cor. of T.7 S., R. 22 E., and T. 8 S. R. 23 E.,	
	West, on true line, on the S. bdy. of sec. 36.	
	Over NW. slope, through scattering timber and dense undergrowth, desc. 193 ft.	
, .50	The witness cor. of T. 7 S., R. 22 E., and T. 8 S., R. 23 E., hereinbefore described.	
3.30	Ravine, course NW.	
6.00	Small ravine course N.	
√ 6.25	A point due N. of the cor. of Tps. 8 and 9 S., Rs. 22 and 23 E., hereinafter described,	
	Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, $2\frac{1}{2}$ ft. high, for cor. of T. 8 S., Rs. 22 and 23 E. only, with brass cap marked	
	6_9155	

4–673 b

SURVEY OF A PORTION OF THE SOUTH BOUNDARY OF

T. 7 S., R. 22 E.

Chains	T7S R22E S36
	S1 S6 R22E R23E T8S 1933 from which
	vAn oak tree, 12 ins. diam., brs. S. 27°30'W., 67 lks. dist., mkd. T8S R22E S1 BT.
	Ascend 150 ft. over broken NE. slope.
14.00	Ravine, course N.
27.00	Ridge, brs. NW. and SE.; desc. 220 ft. over W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap marked
	1933 from which
	An oak tree, 15 ins. diam., brs. N. 83°15'E., 51 lks. dist., mkd. ½ 836 BT.
*	An oak tree, 9 ins. diam., brs. N. 15°30'W., 105 lks. dist., mkd. & S36 BT.
	Descend 90 ft. over NW. slope.
42.00	Gulch, course NW.; asc. 20 ft.
43.60	Low spur, slopes NW.; thence along N. slope.
46.25	A point 40 chs. W. of the cor. of T. 8 S., Rs. 22 and 23 E.,
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base. $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of sec. 1 only, of T. 8 S. with brass cap marked
	v
	1933
	from which
	An oak tree, 6 ins. diam., brs. S. 1 15 W., 22 lks. dist. mkd. ½ S1 BT.
	An oak tree, 8 ins. diam., brs. S. 82°15'W., 47 lks. dist., mkd. ½ Sl BT.
48.30	Spur, slopes NW.; desc. 193 ft. over SW. slope.
59.60	Gulch, course NW.; asc. 191 ft.
77•90	Spur, slopes NW.; desc. 77 ft.
80.00	True point for cor. of secs. 35 and 36, comes in bottom of gulch, course NW. At a point 16 lks. W. of true point,
	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 5 ft. base, 2 ft. high, for witness cor. of secs. 35 and 36 only, with brass cap marked

T. 7 S., R. 22 E.

BOOK 4025

Chains T7S R2 S35 S3 S1 T8S R2 A juniper tree, 18 ins. diam., dist., mkd. WC T7S R22E S35 B1	from which brs. N. 82°00'W., 33 lks.
T8S R2 A juniper tree, 18 ins. diam.,	from which brs. N. 82°00'W., 33 lks.
A juniper tree, 18 ins. diam.,	from which brs. N. 82°00'W., 33 lks.
	s. N.38°00'E., 30 lks. dist.,
An oak tree, 16 ins. diam., bramkd. WC T78 R22E S36 BT.	
Land, mountainous. Soil, rocky; 3rd rate. Timber, juniper and oak. Undergrowth, oak brush.	
v 1	
Thence, from true point for con	2.
West, on true line, on S. bdy.	of sec. 35.
Along N. slope, through scatter	ring timber and undergrowth.
.16 The witness cor. of secs. 35 ar	nd 36.
6.25 A point 80 chs. W. of the cor. E.,	of T. 8 S., Rs. 22 and 23
Set an iron post, 3 ft. long, 2 the ground to bedrock, in a month of the light of the secs. The brass cap marked T7S R22 S35	ound of stone, 3 ft. base, l and 2, of T. 8 S., with
S2 S1	<u>-</u>
T8s R22	·
	from which
A juniper tree, 7 ins. diam., to dist., mkd. T8S R22E S2 BT.	ors. S. 57°30'W., 83 lks.
A juniper tree, 26 ins. diam., dist., mkd. T8S R22E S1 BT.	brs. S. 41°30'E., 174 lks.
11.25 Old road, brs. NE. and SW.	
15.00 Spur, slopes NW.; desc. 57 ft.	•
17.60 Bottom of wash, 3 chs. wide, co	ourse N.; asc. 9 ft.
19.70 Spur, slopes N.; desc. 94 ft.	over gradual NW. slope.
29.80 Bend in trail from SW. to SE.	
34.24 Telephone line, brs. NW. and SI	E.
36.50 Ravine, course NW.; asc. slight	
40.00 Set an iron post, 3 ft. long, ground to bedrock, in a mound ft. high, for $\frac{1}{4}$ sec. cor. of marked	of stone, 3 ft. base, la sec. 35 only, with brass cap
193	from which
An oak tree, 9 ins. diam., brs.	. N. 47°00'W., 24 lks. dist.

T. 7 S., R. 22 E.

Chains	mkd. 4 S35 BT.
v	A juniper tree, 6 ins. diam., brs. N.62°15'E., 49 lks. dist., mkd. 4 S35 BT.
41.30	Small wash, course N.; asc. 30 ft.
46.25	A point 40 chs. W. of the cor. of secs. 1 and 2 of T. 8 S.
•	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for \(\frac{1}{4} \) sec. cor. of sec. 2 only, of T. 8 S., with brass cap marked
	± S 2 1933
	from which
	A juniper tree, 24 ins. diam., brs. S. 37°00'E., 74 lks. dist., mkd.n 2 ST.
	A juniper tree, 24 ins. diam., brs. S. 34°00'W., 63 lks. dist., mkd. 4 S2 BT.
57.00	Road, brs. NE. and SW.
58.00	Wash, 20 lks. wide, course NE.; asc. 136 ft. over SE. slope.
70.60	Spur, from NW., slopes NE.; thence along S. slope.
75.60	Ravine, course SE.; ascend 75 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 2 ft. high, for cor. of secs. 34 and 35 only, with brass cap marked
	T7S R22E S34 S35 S2
	T8S R22E 1933 from which
	An oak tree, 12 ins. diam., brs. N. 70°45'E., 66 lks. dist., mkd. T7S R22E S35 BT.
	An oak tree, 10 ins. diam., brs. N. 52°15'W., 83 lks. dist., mkd. T7S R22E S34 BT.
	Land, rolling, Soil, rocky; 2nd and 3rd rate. Timber, pine, oak and juniper. Undergrowth, manzanita and oak.
	West, on true line, on the S. bdy. of sec. 34. Over E. slope, through scattering timber and undergrowth,
v 6.25	asc. 530 ft. A point 80 chs. W. of the cor. of secs. 1 and 2 of T 8 S.,
	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for cor. of secs. 2 and 3 only, of T. 8 S., with brass cap marked

T., 7 S., R. 22 E.

BOOK	4025
133.75.21	ゴリムコ

	Chains	T7S R22E
	4 · · · · ·	3 3 S2 T 8\$ R22E
		1933 from which
		An oak tree, 10 ins. diam., brs. S.52 45 W., 32 lks. dist., mkd. T8S R22E S3 BT.
		A juniper tree, 14 ins. diam., brs. S.74°45'E., 120 lkd. dist., mkd. T8S R22E S2 BT.
	30.30	Spur, slopes N.; desc. 100 ft. over W. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 34 only, with brass cap marked
		1933
		from which
		A juniper tree, 14 ins. diam., brs. N.75°45'W., 148 lks. dist., mkd. \(\frac{1}{4}\) S34 BT.
,		An oak tree, 7 ins. diam., brs. N. 73 lks. dist., mkd. \$\frac{1}{4}\$ S34 BT.
		Descend 20 ft.
	41.80	Ravine, course NW.; asc. 80 ft.
	√ 46 . 25	A point 40 chs. W. of the cor. of secs. 2 and 3, of T. 8 S.,
	· * 1	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1 ft. high, for \(\frac{1}{4} \) sec. cor. of sec. 3 only, of T. 8 S., with brass cap marked
		$\frac{1}{4}$ S $\frac{3}{4}$
		1933 from which
73		An oak tree, 8 ins. diam., brs. S. 19°00'E., 37 lks. dist., mkd. 4 S3 BT.
		An oak tree, 8 ins. diam., brs. S. 69°15'W., 127 lks. dist., mkd. 4 83 BT.
•	49.80	Spur, slopes NW.; desc. 449 ft. over W. slope.
-	61.30	Ravine, course N.60 W.; thence over NW. slope, desc. 120 ft.
•	70.30	Spur, slopes NW.
	74.10	Draw, course NW.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft high, for cor. of secs. 33 and 34 only, with brass
		cap marked T7S R22E S33 S34
		sʒ
		T8s R22E 1933 from which

SURVEY OF A PORTION OF THE SOUTH BOUNDARY OF

T. 7 S., R. 22 E.

Chains	A juniper tree, 12 ins. diam., brs. N. 46°45'W., 290 lks. dist., mkd. T7S R22E S33 BT.
	A juniper tree, 10 ins. diam., brs. N. 36°15'E., 225 lks. dist., mkd. T7S R22E S34 BT.
	Land, mountainous. Soil, gravelly 3rd rate. Timber, pine, juniper and oak. Undergrowth, oak, and buck brush.
	West, on true line, on S. bdy. of sec. 33.
	Over NW. slope, desc. slightly.
.16	Draw, course N. 30°E.; asc. slightly.
4•90	Spur, slopes N.; desc. 160 ft. over NW. slope.
6.25	A point 80 chs. W. from the cor. of secs. 2 and 3. of T. 8 S.,
	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 3 and 4 only, of T. 8 S., with brass cap marked
	T7S R22E S33
	S4 S3 T8S R22E
	1933 from which
	A juniper tree, 12 ins. diam., brs. S. 23°45'W., 106 lks. dist., mkd. T7S R22E S4 BT.
	An oak tree, 14 ins. diam., brs. S. 25.00'E., 216 lks. dist., mkd. T8S R22E S3 BT.
11.60	Gulch, course N.30°W.; asc. 100 ft.
29.40	Spur, slopes N.; desc. 50 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins in the ground to be drock, in a mound of stone, 3 ft. base, 12 ft. high, for 4 sec. cor. of sec. 33 only, with brass cap marked
	1933
	from which
	A juniper tree, 8 ins. diam., brs. N. $38^{\circ}00^{\circ}E$., 112 lks. dist., mkd. $\frac{1}{4}$ S33 BT.
ļ	A cross +, chiseled on surface of a granite ledge. brs. N. 12°15'W., 154 lks. dist., followed by mks. \$\frac{1}{4}\$ S33 BO.
41.20	Draw, course N.
46.25	A point 40 chs. W. from the cor. of secs. 3 and 4. of T. 8 S.,
	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for 4 sec. cor. of sec. 4 only, of T. 8 S., with brass cap marked
,	

T. 7 S., R. 22 E.	T.	7	8.	\mathbb{R}_{\bullet}	22	\mathbf{E}_{\bullet}
-------------------	----	---	----	------------------------	----	------------------------

BOOK 4025

Chains	from which
	A cross +, chiseled on a granite bowlder, $6 \times 5 \times 5$ ft. above ground, brs. S. 46.45 W., 45 lks. dist., followed by mks. $\frac{1}{4}$ S4 B0.
	A cross +, chiseled on a granite bowlder, 6 x 6 x 6 ft. above ground, brs. S. 18 45 E., 81 lks. dist., followed by mks. 4 S4 B0.
	Ascend 145 ft. over NE. slope.
56.10	Top of ascent; thence along N. slope.
66.90	Descend over NW. slope 92 ft.
√73 . 36	The cor. of secs. 32 and 33, hereinbefore described.
	Land, rolling Soil, gravelly; 3rd rate. Timber, scattering juniper and oak. Undergrowth, buckbrush and oak.
, N. 1977 I	RESURVEY OF A PORTION OF THE WEST BOUNDARY OF
,	T. 8 S., R. 22 E.
-	Reestablishment of surveys executed by T. F. White, U. S. Deputy Surveyor, in 1877.
	From the cor. of Tps. 7 and 8 S., Rs. 21 and 22 E., here-inbefore described.
	South, on a random line, bet. secs. 1 and 6.
40.12	Fall 48 lks. W. of the original $\frac{1}{4}$ sec. cor. of secs. 1 and 6.
	Thence, from cor.
	South, on a random line, bet. secs. 1 and 6.
40.55	Fall 26 lks. E. of point for cor. of secs. 1, 6, 7 and 12. determined by measurement from bearing trees.
	from which
,	A juniper tree, 30 ins. diam., brs. N.89°30'E., 255 lks. dist., mkd. TVIIIS RXXIIE.
t	A juniper stump, 20 ins. diam., brs. N. 46°30'W., 153 lks. dist., mkd. TVIIIS RXXIE
	At this point, set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, $1\frac{1}{8}$ ft. high, for cor. of secs. 1, 6, 7 and 12, with brass cap marked
	T8s R21E R22E S1 S6 S12 S7 1933 from which
v	A juniper tree, 24 ins. diam., brs. N. 65°00'E., 442'lks. dist., mkd. T8S R22E S6 BT.

A juniper tree, 8 ins. diam., brs. S.75°45'E., 432 lks.

4-673 b

RESURVEY OF A PORTION OF THE WEST BOUNDARY OF T. 8 S., R. 22 E.

Chains dist., mkd. T8S R22E S7 BT.

A juniper tree, 15 ins. diam., brs. S. 55°30'W., 404 lks. dist., mkd. T8S R21E S12 BT.

A juniper tree, 14 ins. diam., brs. N.35°00'W., 181 lks. dist., mkd. T8S R21E S1 BT.

Thence

 $VN.0^{\circ}22^{\dagger}E.$, on true line, bet. secs. 1 and 6.

Over NW. slope, through scattering timber and brush, desc. 55 ft.

- 1.80 Gulch, course N.80°W., asc. 50 ft.
- 2.50 Small spur, slopes W.; desc. 50 ft.
- 3.30 | Gulch, course S.70°W.; asc. 50 ft.
- 7.40 | Road, brs. N.70°E. and S.70°W.
- 12.60 Draw, course S.60°W.
- 15.70 Low spur, slopes W.; thence over nearly level ground.
- 24.00 Draw, course S.80°W.
- The \(\frac{1}{4}\) sec. cor. of secs. l and 6, which is a decayed post. \(\frac{1}{4}\) x 4 x 12 ins. above ground. In place of old post, which is set along side,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 1 and 6, with brass cap marked

/ s1 s6

from which

Old BT.

VA hackberry tree, 12 ins. diam., brs. N. 2000 W., 292 lks. dist., mkd. 4 Sl BT.

No other suitable accessory.

Thence

 $\sqrt{N.0.41}$ W., on true line, bet. secs. 1 and 6.

Descend slightly over open grass land.

.60 | Small wash, course W.

2.80 Road, brs. S. 80°W. and N.80°E.

7.60 | Road, brs. S.80°E. and N.20°W.

10.20 Wash, course S.80°W.

30.40 Low spur, slopes W.; desc. 32 ft. over N. slope.

40.06 | Small gully, course W.

740.12 The cor. of Tps. 7 and 8 S., Rs. 21 and 22 E., hereinbefore described.

T. 8 S., R. 22 E.

EOOK 4025

15

Chains Land, rolling. Soil, gravelly loam; 2nd rate. Timber, S. 30 chs., scattering juniper and oak; remainder, open grass land. RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF T. 9 S., R. 22 E. Reestablishment of surveys executed by C. H. Wallace, U.S. Deputy Surveyor, in 1886. From the cor. of secs. 2, 3, 34 and 35, Tps. 8 and 9 S., R. 22 E.

East, on a random line, bet. secs. 2 and 35.

40.28 Fall 99 lks. N. of the 4 sec. cor. of secs. 2 and 35.

Thence, from cor.

East, on a random line, bet. secs. 2 and 35.

Fall 85 lks. S. of the original cor. of secs. 1, 2, 35 40.11 and 36.

Thence, from cor.

East, on a random line, bet. secs. 1 and 36.

40.36 Fall 28 lks. N. of the original $\frac{1}{4}$ sec. cor. of secs. 1

Thence, from cor.

East, on a random line, bet. secs. 1 and 36.

Fall 26 lks. S. of the cor. of Tps. 8 and 9 S., Rs. 22 and 23 E., which is a granite stone, 10 x 10 x 14 ins. above ground, mkd. with 6 notches on N., S., E. and W. faces, with a mound of stone to W. In place of old stone which is set along side, 38.91

> Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for cor. of Tps. 8 and 9 S., Rs. 22 and 23 E., with brass cap marked

T8s R22E R23E S36 S31 S1 | S6 T9S 1933

from which

Old bearing trees.

vAn oak tree, 16 ins. diam., brs. N.21°15'E., 31 lks. dist., with old blaze grown over.

An oak tree, 15 ins. diam., brs. S. 66°45.W., 73 lks. dist. with old blaze grown over.

New bearing trees.

An oak tree, 7 ins. diam., brs. S.13°00'E.,80 lks. dist., mkd. T9S R23E S6 BT.

An oak tree, 16 ins. diam., brs. N.55°30'W., 207 lks. distl.

4-673 b

RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF

T. 9 S., R. 22 E.

Chains | mkd. T8S R22E S36 BT.

Thence

S.89°37'W., on true line, on N. bdy. of sec. 1.

Over level ground, through scattering timber.

3.00 Ascend 600 ft. over open rocky SE. slope.

29.90 Spur, slopes S.; thence over SW. slope, desc. 79 ft.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, which is a granite stone, 6 x 10 x 12 ins., loosely set in a small mound of stone, mkd. $\frac{1}{4}$ on N. face. In place of old stone which is set along side,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a stone, mkd. with a cross +. at base, in a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap marked

½ S 1 1933

Thence

N.89°36'W., on true line, on N. bdy. of sec. 1.

Over open SW. slope, desc. 339 ft.

1.09 A point 40 chs. W. in departure, from the cor. of Tps. 8 and 9 S., Rs. 22 and 23 E.,

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a stone mkd. with a cross +. at base, in a mound of stone, 4 ft. base, 2½ ft. high, for ½ sec. cor. of sec. 36 only, of T. 8 S., with brass cap marked

± 836 1933

20.90 | Spur, slopes SW.

39.80 | Gulch, 60 lks. wide, course SW.; asc. slightly.

The original cor. of secs. 1, 2, 35 and 36, which is a schist stone, 5 x 6 x 10 ins. above ground, mkd. with 1 notch on E. and 5 notches on W. face. In place of old stone which is set along side,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 5 ft. base. 2 ft. high, for cor. of secs. 1 and 2 only, with brass cap marked

T8S R22E \$36 \$2 \$1 T9S R22E 1933

Land, mountainous.
Soil, rocky; 3rd and 4th rate.
Timber, E. 4 chs. scattering oaks, remainder open.

Thence

TOP A LOTATION OF THE MOVIE DOOM

T. 9 S., R. 22 E.

EOOK 4025

Chains VS.88°47'W., on true line, on N. bdy. of sec. 2.

Over gradual SW. slope, through scattering mesquite, desc., 76 ft.

A point 80 chs. W. in departure, from the cor. of Tps. 8 and 9 S., Rs. 22 and 23 E.,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone, mkd. with a cross +, deposited at base, in a mound of stone, 5 ft. base, 2 ft. high, for cor. of secs. 35 and 36 only, of T. 8 S., with brass cap marked

T8S R22E S35 S36 S2 T9S R22E 1933

12.90 Gulch, course Sw.; thence over gradual Sw. slope.

The original \$\frac{1}{4}\$ sec. cor. of secs. 2 and 35, which is a granite stone, 8 x 8 x 16 ins. above ground, firmly set, mkd. \$\frac{1}{4}\$ on N. face, with a mound of stone to N. In place of old stone which is set along side,

Set an iron post, 3 ft. long; 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap marked

√ ½ S 2 1933

change the mound

of stone, 2 ft. base, $l\frac{1}{2}$ ft. high, from position N. of cor. to position S.

Thence

N. 88°36'W., on true line, on N. bdy. of sec. 2.

Over gradual SW. slope, desc. 95 ft.

.62 A point 40 chs. W. in departure, from the cor. of secs. 35 and 36, of T. 8 S.,

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for 4 sec. cor. of sec. 35 only, of T. 8 S., with brass cap marked

½ S35 1933

36.70 Draw, course SW.; asc. slightly.

The original cor. of secs. 2, 3, 34 and 35, which is a granite stone, 8 x 12 x 16 ins. above ground. firmly set mkd. with 2 notches on E. and 4 notches on W. face. In place of old stone which is set along side.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 2, 3, 34 and 35, with brass cap marked

T8S R22E S34 S35 S3 S2 T9S 1933

raise a mound

RESURVEY OF A PORTION OF THE MORTH BOUNDARY OF

T. 9 S., R. 22 E.

	Chains	of stone, 3 ft. base, la ft. high, W. of cor.
		Land, rolling. Soil, gravelly; 3rd rate.
		No timber. Undergrowth, mesquite.
		EAST BOUNDARY OF T. 8 S., R. 22 E.
		From the cor. of Tps. 8 and 9 S., Rs. 22 and 23 E., here-inbefore described.
		North, bet. secs. 31 and 36.
		Over gradual SE. slope, through scattering timber and brush, asc. 186 ft.
	14.35	Draw, course S. 15°E.
	25.00	Rocky spur, slopes E.; desc. 90 ft.
	30.50	Gulch, course S. 30°E.; asc. 192 ft. over rocky SE. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass cap marked
		4
		✓ s 36 s 31
Ì		1933
		from which
		from which An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \(\frac{1}{4}\) S31 BT.
	4	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist.,
	4	✓An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. ½ S31 BT. ✓An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks.
	47•30	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \(\frac{1}{4}\) S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \(\frac{1}{4}\) S36 BT.
	47. 30 66.30	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \$\frac{1}{4}\$ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \$\frac{1}{4}\$ S36 BT. Descend slightly:
		An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. ½ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. ½ S36 BT. Descend slightly: Same gulch, course S.30°W.; asc. 110 ft.
	66.30	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \$\frac{1}{4}\$ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \$\frac{1}{4}\$ S36 BT. Descend slightly: Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft.
	66.30 68.30	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \$\frac{1}{4}\$ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \$\frac{1}{4}\$ S36 BT. Descend slightly: Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft. Gulch, course S. 30°E.; asc. 60 ft. Spur, slopes W.; desc. 30 ft. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked
	66.30 68.30 78.20	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. ½ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. ½ S36 BT. Descend slightly. Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft. Gulch, course S. 30°E.; asc. 60 ft. Spur, slopes W.; desc. 30 ft. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked T8S R22E R23E
	66.30 68.30 78.20	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \$\frac{1}{2}\$ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \$\frac{1}{2}\$ S36 BT. Descend slightly: Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft. Gulch, course S. 30°E.; asc. 60 ft. Spur, slopes W.; desc. 30 ft. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked T8S R22E R23E S25 S30
	66.30 68.30 78.20	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. ½ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. ½ S36 BT. Descend slightly: Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft. Gulch, course S. 30°E.; asc. 60 ft. Spur, slopes W.; desc. 30 ft. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked T8S R22E R23E S25 S30 S36 S31 1933
	66.30 68.30 78.20	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \$\frac{1}{4}\$ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \$\frac{1}{4}\$ S36 BT. Descend slightly: Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft. Gulch, course S. 30°E.; asc. 60 ft. Spur, slopes W.; desc. 30 ft. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked T8S R22E R23E S25 S30 S36 S31
	66.30 68.30 78.20	An oak tree, 9 ins. diam., brs. S. 44°15'E., 33 lks. dist., mkd. \$\frac{1}{4}\$ S31 BT. An oak tree, 12 ins. diam., brs. S. 46°30'W., 15 lks. dist., mkd. \$\frac{1}{4}\$ S36 BT. Descend slightly. Same gulch, course S.30°W.; asc. 110 ft. Spur, slopes SE.; desc. 50 ft. Gulch, course S. 30°E.; asc. 60 ft. Spur, slopes W.; desc. 30 ft. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked T8S R22E R23E S25 S30 S36 S31 1933 from which An oak tree, 8 ins. diam., brs. N. 28°00'E., 10 lks. dist.,

'An oak tree, 8 ins. diam., brs. S. 33°00'W., 105 lks. dist., mkd. T8S R22E S36 BT.

An oak tree, 8 ins. diam., brs. N. 72°45'W., 67 lks. dist.,

```
Chains | mkd. T8S R22E S25 BT.
           Land, mountainous.
           Soil, rocky; 4th rate.
           Timber, oak, pinyon and juniper.
           Undergrowth, oak.
          North, bet. secs. 25 and 30.
          Over SW. slope, through scattering timber and undergrowth,
            asc. 40 ft.
 3.00
           Thence over S. slope, asc. 375 ft.
15.60
           Top of ascent; thence along broken E. slope.
30.30
           Gulch, course E.; asc. 145 ft. over SE. slope.
           Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for 4 sec. cor. of secs. 25 and 30, with brass cap
40.00
           marked
                                           s25 s30
                                                                       from which
          An oak tree, 14 ins. diam., brs. N.51°30'W., 35 lks. dist.,
            mkd. 1 S25 BT.
           A juniper tree, 12 ins. diam., brs. N.11°15/E., 63 lks. dist., mkd. \frac{1}{4} S30 BT.
           Descend 134 ft.
50.10
           Gulch, course SE.; asc. 395 ft. over S. slope.
58.20
           Spur, slopes SW.; thence over SW. slope, asc. 171 ft.
           Spur, slopes SE.; desc. 10 ft.
79.20
           Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1 ft. high, for cor. of secs. 19, 24, 25 and 30, with brass
80.00
            cap marked
                                             T8s
                                        R22E R23E
S24 S19
                                          S25 | S30
                                             1933
                                                                       from which
          A pine tree, 12 ins. diam., brs. N. 40°45'E., 127 lks. dist., mkd. T8S R23E S19 BT.
          A pine tree, 8 ins. diam., brs. S. 16°45'E., 37 lks. dist.,
            mkd. T8S R23E S30 BT.
          A pine tree, 10 ins. diam., brs. S. 39°15'W., 54 lks. dist., mkd. T8S R22E S25 BT.
          A pine tree, 8 ins. diam., brs. N. 64°15 W., 38 lks. dist.,
            mkd. Tös R22E S24 BT.
           Land, mountainous.
           Soil, gravelly; 3rd rate.
```

TING OFFICE: 1931 6-815

Timber, pine, oak and juniper; undergrowth, oak.

Chains North, bet. secs. 19 and 24. Over NE. slope, through scattering timber and dense undergrowth, desc. 15 ft. .90 Ravine, course S. 60°E.; asc. 750 ft. over SW. slope. 21.00 Spur, slopes SE.; desc. 227 ft. over NE. slope through heavy pine timber. 21.37 Forest Service lookout station, brs. N.11°15'E. Bottom of slope; asc. slightly over SE. slope. 37.50 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 19 and 24. with brass 40.00 cap marked √ S24 S19 1933 from which A pine tree, 20 ins. diam., brs. S. 19^{\bullet} 00 W., 46 lks. dist., mkd. $\frac{1}{4}$ S24 BT. A pine tree, 20 ins. diam., brs. N. 38° 30'E., 102 lks. dist., mkd. \(\frac{1}{4} \) S19 BT. 46.20 Draw, drains SE.; asc. 155 ft. over SE. slope. 53.50 Top of ascent; thence over NE. slope, desc. 49 ft. 58.50 Draw, drains S. 60° E.; asc. 440 ft. over general SE. stope. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base. 2 ft. high, for cor. of secs. 13, 18, 19 and 24, with 80.00 brass cap marked T8s R22E R23E S13 S18 **S24** | **S19** 1933 from which A pine tree, 30 ins. diam., brs. N. 50°45'E., 26 lks. dist., mkd. T8S R23E S18 BT. A pine tree, 24 ins. diam., brs. S. 74°30'E., 66 lks. dist., mkd. T8S R23E S19 BT. A pine tree, 30 ins. diam., brs. S. 69°45'W., 61 lks. dist., mkd. T8S R22E S24 BT. A pine tree, 8 ins. diam., N. 60°00'W., 14 lks. dist., mkd. T8S R22E S13 BT. Land, mountainous. Soil, rocky and gravelly; 3rd rate. Timber, pine and oak. Undergrowth, oak.

U. S. GOVERNMENT PRINTING OFFICE: 1931 6-8155

Over SE. slope, through timber and brush, asc. 242 ft.

North, bet. secs. 13 and 18.

Chains 9.65	Top of mountain, brs. NE. and SW; desc. 223 ft. over NW. slope.
20.20	Swale, drains W.; thence over nearly level ground.
23.60	Descend 250 ft. over gradual NW. slope.
26.70	Trail, brs. N.80°W. and S.80°E.
38.20	Draw, drains, N.80°W.; asc. slightly.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for 4 sec. cor. of secs. 13 and 18, with brass cap marked
	4
	s13 s18
	1933 from which
	An oak tree, 8 ins. diam., brs. N. 13°30'E. 21 lks. dist., mkd. 4 S18 BT.
	A pine tree, 6 ins. diam., brs. N. 14°15'W., 49 lks. dist., mkd. ½ S13 BT.
	Ascend 30 ft.
41.56	Forest Service lookout station brs. S.58°00'E.
44.00	Flat spur, slopes W.; desc. 450 ft. over general NE. slope.
49.60	Trail, brs. N.80°W. and S.80°E.
64.65	Telephone line, brs. NW. and SE.
75.00	Low spur, slopes NE.; thence over N. slope, desc. 160 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for cor. of secs. 7, 12, 13 and 18, with brass cap marked
	T8S R22E R23E
	<u>\$12 \$7</u> \$13 \$18
	1933 from which
	A pine tree, 12 ins. diam., brs. N. 28°00'E., 42 lks. dist., mkd. T8S R23E S7 BT.
	A pine tree, 16 ins. diam., brs. S.22°00'E., 47 lks. dist., mkd. T8S R23E S18 BT.
	A pine tree, 14 ins. diam., brs. S.53°30'W., 11 lks. dist., mkd. T8S R22E S13 BT.
	A pine tree, 12 ins. diam., brs. N.29°00'W., 22 lks. dist., mkd. T8S R22E S12 BT.
	Land rolling mountainous. Soil, gravelly loam; 3rd rate. Timber, Yellow and white pine; Douglas and balsom fir.oak. Undergrowth, manzanita, buckbrush, mountain mahogany and willow.

EAST BOUNDARY OF T. 8 S., R. 22 E.

Chains	North, bet. secs. 7 and 12.
	Over N. slope, through heavy timber, desc. 675 ft.
5.60	Old trail, brs. NW. and SE.
23.30	Sawmill Canyon, near head, course NW., small stream of water; asc. 220 ft. over S. slope.
34•40	Spur, slopes W.; desc. 111 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 7 and 12, with brass cap marked
	v s12 s7
	1933
. e 125	from which
	A pine tree, 20 ins. diam., brs. S. 6°45'W., 116 lks. dist., mkd. 4 S12 BT.
	A pine tree, 14 ins. diam., brs. N. 51°45'E., 147 lks. dist., mkd. ½ S7 BT.
	Over level ground.
42.00	Descend 256 ft. over N. slope.
46.30	Ravine, course W.; asc. 145 ft.
54.20	Spur, slopes W.; desc. 46 ft.
59.20	Gulch, course W.; asc. 430 ft. over S. slope.
73.70	Spur, slopes W.; desc. 106 ft. over N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 12 ins. high, for cor. of secs. 1, 6, 7 and 12, with brass cap marked
	T8S R22E R23E <u>S1 S6</u> S12 S7 1933 from which
	A juniper tree, 10 ins. diam., brs. N. 55°00'E., 37 lks. dist., mkd. T8S R23E S6 BT.
	A pine tree, 24 ins. diam., brs. S. 52°15'E., 66 lks. dist., mkd. T8S R23E S7 BT.
	A pine tree, 6 ins. diam., brs. S. 50°30'W., 26 lks. dist., mkd. T8S R22E S12 BT.
	A pine tree, 5 ins. diam., brs. N. 21°00'W., 20 lks. dist., mkd. T8S R22E S1 BT.
	Land, mountainous. Soil, rocky; 3rd and 4th rate. Timber, scattering pine and juniper. Undergrowth, manzanita, mountain mahogany and oak.

EAST BOUNDARY OF T. 8 S., R. 22 E.

BOUK	4025
	- 5 UZ 0

Chains	North, bet. secs. 1 and 6.
	Over N. slope, through scattering timber and undergrowth, desc. 57 ft.
2.20	Head of gulch, course W.; asc. 467 ft. over general SW. slope.
33.00	Gulch, course W.
40.00	True point for the 4 sec. cor. on edge of rocky cliff, where it is unsuitable for a permanent cor.
	Descend 51 ft. over NW. slope.
42.90	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1½ ft. high, for witness ½ sec. cor. of secs. 1 and 6, with brass cap marked
	sı sı s6
	1933 from which
	$^{\vee}$ A pine tree, 18 ins. diam., brs. N.0 $^{\circ}$ 45 E.,215 lks. dist. mkd. WC $\frac{1}{4}$ S6 BT.
	√A pinyon tree, 16 ins. diam., brs. S.61°45'W., 41 lks. dist., mkd. WC ½ Sl BT.
44.20	Head of gulch, course SW.; asc. 20 ft.
47.40	Ridge, brs. E. and W.; desc. 1034 ft. over general N. slope, through heavy timber.
74•34	The cor. of T. 8 S., Rs. 22 and 23 E., hereinbefore described.
	Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, pine, fir, oak and mountain laurel. Undergrowth, oak, mountain mahogany, locust and willow.
V -	
	RESURVEY OF A PORTION OF THE SUBDIVISION
	LINES OF T. 8 S., R. 22 E.
	From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of the township, hereinbefore described.
	North, on a random line, bet. secs. 34 and 35.
40.43	Fall 86 lks. W. of the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Thence, from cor.
	North, on a random line, bet. secs. 34 and 35.
40.00	Fall 9 lks. E. of the cor. of secs. 26, 27, 34 and 35, which is a granite stone, 12 x 12 x 10 ins. above ground, firmly set, mkd. with 1 notch on S. face, and 2 notches on E., with a mound of stone to W. In place of old stone which is set along side,
141,	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a stone mkd. with a cross +. deposited at base, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for cor. of secs. 27 and 34 only, with brass

4-673 b

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

cap marked

T8S R22E \$27 S26 \$34 1933

Thence

S. 0°08'E., on true line, on E. bdy. of sec. 34.

Over SW. slope, through scattering timber and brush, desc. 90 ft.

11.00 Draw, drains S.60°W.; asc. 40 ft.

13.00 Thence over gradual SW. slope, desc. 75 ft.

36.10 Draw, course SW.; asc. 20 ft.

40.00 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, which is a granite stone, 8 x 5 x 4 ins. above ground, firmly set, mkd. $\frac{1}{4}$ on W. face and witnessed by a mound of stone to W. In place of old stone which is set along side,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 34 only, with brass cap marked

34 334

1933

rebuild the mound

of stone, 2 ft. base, 12 ft. high, W. of cor.

Thence

S. 1°13'W., on true line, on E. bdy. of sec. 34.

Over nearly level ground.

.59 A point 40 chs. S. in latitude, from the closing cor. of secs. 26 and 35, hereinafter described,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 35 only, with brass cap marked

\$35

1933

from which

An oak tree, 8 ins. diam., brs. N.31°45'E.,167 lks. dist. mkd. ½ S35'BT.

An oak tree, 15 ins. diam., brs. N.69°30'E., 281 lks. dist., mkd. 2 S35 BT.

14.60 Draw, drains SW.

40.44 The cor. of secs. 2, 3, 34 and 35, hereinbefore described

Land, rolling.
Soil, gravelly; 2nd rate.
Timber, scattering oak and mesquite.

From the cor. of secs. 27 and 34, hereinbefore described.

S. GOVERNMENT PRINTING OFFICE: 1931 6-815

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

DOOK 4025

Chains North, on a random line, bet. secs. 26 and 27. 40.18 Fall 23 lks. E. of the ½ sec. cor. of secs. 26 and 27. Thence, from cor. North, on a random line, bet. secs. 26 and 27. Yell 3 lks. W. of the cor. of secs. 22, 23, 26 and 27, which is a granite stone, 8 x 9 x 8 ins. above ground, mkd. with 2 notches on S. face, and 2 notches on E., and witnessed by a mound of stone to W. In place of old stone, which is set along side,
Thence, from cor. North, on a random line, bet. secs. 26 and 27. Fall 3 lks. W. of the cor. of secs. 22, 23, 26 and 27, which is a granite stone, 8 x 9 x 8 ins. above ground, mkd. with 2 notches on S. face, and 2 notches on E., and witnessed by a mound of stone to W. In place of old
North, on a random line, bet. secs. 26 and 27. Fall 3 lks. W. of the cor. of secs. 22, 23, 26 and 27, which is a granite stone, 8 x 9 x 8 ins. above ground, mkd. with 2 notches on S. face, and 2 notches on E., and witnessed by a mound of stone to W. In place of old
Fall 3 lks. W. of the cor. of secs. 22, 23, 26 and 27, which is a granite stone, 8 x 9 x 8 ins. above ground, mkd. with 2 notches on S. face, and 2 notches on E., and witnessed by a mound of stone to W. In place of old
which is a granite stone, 8 x 9 x 8 ins. above ground, mkd. with 2 notches on S. face, and 2 notches on E., and witnessed by a mound of stone to W. In place of old
Stone, willow in not along state,
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 26 and 27 only, with brass cap marked T8S R22E S23
\$27\\$26 1933 change the mound
of stone, 3 ft. base, $l^{\frac{1}{2}}$ ft. high, from position W., to position S. of cor.
Thence
S. 0°03'W., on true line, on E. bdy. of sec. 27.
Over S. slope, through scattering timber and brush, desc. 57 ft.
3.70 Draw, drains S.60°W.; asc. 220 ft.
21.18 Spur, slopes SW.; desc. 191 ft.
22.50 Wire fence, brs. SW. and NE.
32.10 Gulch, course S.75°W.
36.00 Draw, drains W.
The 4 sec. cor. of secs. 26 and 27, which is a granite stone, 7 x 8 x 8 ins. above ground, mkd. 4 on W. face, and witnessed by a mound of stone to W. In place of old stone, which is set along side,
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 4 sec. cor. of secs. 27 only, with brass cap marked
\$27
1933 from which
A juniper tree, 22 ins. diam., brs. S.3°00'W., 159 1ks. dist., mkd. 4 S27 BT.
A juniper tree, 42 ins. diam., brs. N.47°00'W.,106 lks. dist., mkd. 4 S27 BT.
Thence
S. 0°20'E., on true line, on E. bdy. of sec. 27.
Over general SW. slope, through scattering timber and brush, desc. 170 ft.
.81 A point 39.95 chs. S., in latitude, from the cor. of secs.

RESURVEY OF A PORTION OF THE SUBDIVISION

.. LINES OF T. 8 S., R. 22 E.

	, , , himboor is o be, its 22 He
Chains	26 and 27, and 39.96 chs. N. in latitude, from the closing cor. of secs. 26 and 35, hereinafter described,
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 26 only. with brass cap marked
÷	s26.
,	1933 raise a mound
	of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
20.90	Draw, course S. 30°W.
40.18	The cor. of secs. 27 and 34, hereinbefore described.
V	Land, rolling. Soil, gravelly; 2nd rate. Timber, oak and juniper. Undergrowth, oak and buckbrush.
,	
	From the cor. of secs. 26 and 27, hereinbefore described.
-	West, on a random line, bet. secs. 22 and 27.
40.02	Fall 2 lks. N. of the 4 sec. cor. of secs. 22 and 27.
•	Thence, from cor.
	West, on a random line, bet. secs. 22 and 27.
40.07	Fall 81 lks. S. of the cor. of secs. 21, 22, 27 and 28, which is a granite stone, 8 x 8 x 7 ins. above ground. mkd. with 2 notches on S. face, and 2 notches on E. and witnessed by a mound of stone, to W. In place of old stone, which is set along side,
	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for cor. of secs. 21, 22, 27 and 28, with brass cap marked TOS R22E
	\$21 \s22 \s28 \s27 \s233
	Thence
	S. 88°50'E., on true line, on N. bdy. of sec. 27.
	Over general SW. slope, through scattering brush, asc. 156 ft.
6.10	Draw, drains SW.
31.50	Low spur, slopes SW.
39-22	A point 40 chs. W. in departure from the cor. of secs. 22 and 23, hereinafter described,
	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a stone, mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2½ ft. high, for 4 sec. cor. of sec. 22 only, with brass cap marked

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

BOOK 4025

	Chains	1933 1933
	~ 40.08	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, which is a porphyry stone, 12 x 7 x 11 ins. above ground, mkd. $\frac{1}{4}$ on N. face. and witnessed by a mound of stone to N. In place of old stone which is set along side,
		Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross +. deposited at base, in a mound of stone, 4 ft. base. 2 ft. high, for 4 sec. cor. of sec. 27 only, with brass cap marked
		1933 the mound
		of stone to N. is removed.
		Thence
		N. 89°58'E., on true line, on N. bdy. of sec. 27.
		Over W. slope, asc. 112 ft.
	9.50	Spur, slopes SW.; desc. 20 ft.
	15.10	Enter heavy oak and juniper timber.
	20.30	Gulch, course SW.; asc. 135 ft. over SW. slope.
	25.00	Leave heavy timber; enter scattering timber.
	39•14	A point 80 chs. W. in departure, from the cor. of secs. 23, 24, 25 and 26, hereinafter described,
		Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 12 ft. high, for cor. of secs. 22 and 23 only, with brass cap marked
		T8s R22E S22 S23 S27 1933
	√40 . 02	The cor. of secs. 26 and 27, hereinbefore describe.
		Land, rolling. Soil, gravelly; 3rd rate. Timber, oak and juniper. Undergrowth, oak, buckbrush and cactus.
	V	
ŧ		From the cor. of secs. 21, 22, 27 and 28, hereinbefore described.
		North, on a random line, bet. secs. 21 and 22.
	40.10	Fall 17 lks. E. of the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
		Thence, from cor.
		North, on a random line, bet. secs. 21 and 22.
	39.76	Fall 40 lks. E. of the cor. of secs. 15, 16, 21 and 22, which is a granite stone, 8 x 5 x 15 ins. above ground,

4–673 b 28

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

Chains

mkd. with 3 notches on S. face, and 3 notches on E., witnessed by a mound of stone, to W. In place of old stone which is set along side,

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for cor. of secs. 16 and 21 only, with brass cap marked

T8S R22E × S16 515 S21 1933

from which

An oak tree, 5 ins. diam., brs. S. 77°00'W., 69 lks. dist., mkd. T8S R22E S21 BT.

An oak tree, 6 ins. diam., brs. N. 37°00'W., 39 lks. dist., mkd. T8S R22E S16 BT.

Thence

S.0°34'E., on true line, on E. bdy. of sec. 21.

Over S. slope, through scattering brush, desc. 250 ft.

.71 A point 79.72 chs. W. of the cor. of secs. 14, 15, 22 and 23, hereinafter described,

Set an iron post, 3 ft. long, 2 ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, $2\frac{1}{2}$ ft. high, for cor. of secs. 15 and 22 only, with brass cap marked

T8S R22E S15 S22 1933

from which

An oak tree, 8 ins. diam., brs. S.86°00'E., 18 lks. dist. mkd. T8S R22E S22 BT.

An oak tree, 18 ins. diam., brs. N.62°15'E., 185 lks. dist., mkd. T8S R22E S15 BT.

15.00 Old road, brs. E. and W.

16.80 | Gulch, course W.; asc. 127 ft.

24.80 | E. slope of low hill, brs. E. and W.; desc. 155 ft.

35.30 | Small draw, drains SW.

39.76 The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, which is a granite stone, 12 x 8 x 15 ins. above ground, mkd. $\frac{1}{4}$ on W. face. In place of old stone which is set along side,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor. of sec. 21 only, with brass cap marked

√ S21

1933

Thence

S. 0°15'E., on true line, on E. bdy. of sec. 21.

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

EOOK 4025

29

	Chains	Over gradual SW. slope, desc. 89 ft.
	• • 95	in latitude A point 40 chs. S. of the cor. of secs. 15 and 22,
		Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone, mkd. with a cross +. deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for 4 sec. cor. of sec. 22 only, with brass cap marked
		S22
		ls22 1933
	21.50	Gulch, course S. 60°W.; asc. 45 ft.
	26.60	Spur, slopes SW.
	28.00	Draw, drains SW.
	37.40	Spur, slopes SW.; desc. 25 ft.
	40.10	The cor. of secs. 21, 22, 27 and 28, hereinbefore described.
		Land, rolling. Soil, gravelly and rocky; 2nd and 3rd rate. Timber, a few scattering oak and juniper. Undergrowth, oak and cactus.
	V.	
		From the cor. of secs. 16 and 21, hereinbefore described.
		West, on a random line, bet. secs. 16 and 21.
-	39•76	Fall 17 lks. S. of the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
-	79•19	Thence from cor.
	40 40 -	West, on a random line, bet. secs. 16 and 21.
2	40.40	Fall 7 lks. S. of the cor. of secs. 16, 17, 20 and 21, which is a wooden stake, 3 x 3 x 36 ins. above ground, mkd. with 3 notches on S. and 4 notches on E. face, set in a mound of stone. In place of old stake which is set along side,
		Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap marked T8SIR22E
		\$17 \$16 \$20 \$21 1933
	** .	from which
		An oak tree, 36 ins. diam., brs. N.70°00'E., 334 lks. dist., mkd. T8S R22E S16 BT.
	., .	A hackberry tree, 9 ins. diam., brs. S.77°45'E., 194 lks. dist., mkd. T8S R22E S21 BT.
		An oak tree, 5 ins. diam., brs. S.66°00'W., 173 lks. dist., mkd. T8S R22E S20 BT.
		An oak tree, 6 ins. diam., brs. N.64°45'W., 342 lks. dist., mkd. T8S R22E S17 BT.
1		

Thence

4-673 b 30

RESURVEY OF A PORTION OF THE SUBDIVISION LINES OF T. 8 S., R. 22 E.

	· · · · · · · · · · · · · · · · · · ·	
Chains	S. 89°54'E., on true line bet. secs. 16 and 21.	
.	Over gradual SE. slope, through scattering timber and brush, desc. 20 ft.	
•70	Old road, brs. NW. and SE.	
2.00	Ravine, course S.30°W.; asc. 285 ft. over general SW. slope.	
6.00	Small spur, slopes SW.	
28.00	Spur, slopes S.; desc. 101 ft. over SE. slope.	
40.40	The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, which is a granite stone, 8 x 7 x 10 ins. above ground, mkd. $\frac{1}{4}$ on N. face, and witnessed by a mound of stone to N. In place of old stone which is set along side,	
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +. deposited at base, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 16 and 21, with brass cap marked	
	1933	
	Thence	
	S. 89°45'E., on true line, bet. secs. 16 and 21.	
	Over nearly level ground.	A.,
3.60	Road, brs. NE. and SW.	
6.20	Ravine, course SW.	
15.50	Gulch, course SW.	
17.20	Same road, brs. N. and S.; asc. 350 ft. over W. slope.	
34.20	Spur, slopes SW.; desc. slightly over SE. slope.	
39.20	Wire fence, brs. N. and S.	.•
39.76	The cor. of secs. 16 and 21, hereinbefore described.	
	Land, rolling. Soil, rocky and gravelly; 2nd and 3rd rate. Timber, Scattering oak, mesquite and juniper. Undergrowth, oak, catclaw and cactus.	
/		
	From the cor. of secs. 16, 17, 20 and 21, hereinbefore described.	
	North, on a random line, bet. secs. 16 and 17.	
40.26	Fall 68 lks. W. of the 2 sec. cor. of secs. 16 and 17.	
	Thence, from cor.	
	North, on a random line, bet. secs. 16 and 17.	4~
40.07	Fall 5 lks. W. of the cor. of secs. 8, 9, 16 and 17, which is a granite stone, 15 x 10 x 15 ins. above ground, mkd. with 4 notches on S., and 4 notches on E. face. In place of old stone which is set along side,	

LINES OF T. 8 S., R. 22 E.

FOOK 402F

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, for cor. of 8 and 17 only, with brass cap Chains marked T8S, R22E 1933 from which Old bearing tree. An oak tree, 15 ins. diam., brs. N.14°30'E.. 99 lks. dist., mkd. T8S R22E S9 BT. New bearing tree. An oak tree, 6 ins. diam., brs. N.18°15'W., 195 lks. dist., mkd. T8S R22E S8 BT. Thence S. 0°04'W., on true line, on E. bdy. of sec. 17. Over open SW. slope, desc. 359 ft. 17.80 Ravine, course SW.; asc. 25 ft. Low spur, slopes SW.; desc. 20 ft. 19.30 Draw, course S.60°W., asc. 25 ft. 21.30 36.00 Low spur, slopes SW.; desc. 30 ft. Draw, course SW.; asc. 30 ft. 37.40 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, which is a granite stone, $8 \times 8 \times 8$ ins. above ground, mkd. $\frac{1}{4}$ on W. face, and witnessed by a mound of stone to W. In place of old 40.07 stone which is set along side, Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1 ft. high, for \(\frac{1}{4} \) sec. cor. of sec. 17 only, with brass cap marked 1933 raise a mound A-mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Thence S.0°58'W., on true line, on E. bdy. of sec. 17. Over gradual SW. slope, desc. 158 ft. A point 40 chs. S. in latitude, from the closing cor. 1.22 of secs. 9 and 16, hereinafter described, Set an iron post, 3 ft. long, l in. diam., 22 ins. in the ground, in a small mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 16 only, with brass cap marked

S16

4-673 b

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

Chains 25.90	Gulch, course SW.
39.60	Old road, brs. N.75°E. and S.75°W.
40.27	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling. Soil, gravelly; 2nd and 3rd rate. Timber, a few scattering oak, hackberry and juniper. Undergrowth, mesquite, oak and cactus.
	From the cor. of secs. 8 and 17, hereinbefore described.
	North, on a random line, bet. secs. 8 and 9.
39.56	Fall Fall 37 lks. W. of the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	Thence, from cor.
	North, on a random line, bet. secs. 8 and 9.
40.00	No trace of the cor. of secs. 4, 5, 8 and 9. Set temp. sec. cor.
	Thence
	West, on a random line, bet. secs. 5 and 8.
39•97	No trace of the $\frac{1}{4}$ sec. cor. of secs. 5 and 8. Set temp. $\frac{1}{4}$ sec. cor.
81.60	Fall 50 lks. S. of the cor. of secs. 5, 6, 7 and 8, which is a granite stone, 8 x 10 x 9 ins. above ground, firmly set, mkd. with 5 notches on S., and 5 notches on E. face witnessed by a mound of stone to W. In place of old stone which is set along side,
	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for cor. of secs. 7 and 8 only, with brass cap marked
	T8S R22E S6
	<u>s7</u> s8
	1933
-	Thence
	S.89°39'E., on true line, on N. bdy. of sec. 8.
	Over gradual SE. slope, through scattering brush, desc. 20 ft.
•70	A point 80 chs. W. in departure, from the cor. of secs. 4 and 5, hereinafter described,
	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 5 and 6 only, with brass cap marked
	T8s R22E s6 s5
	\$8 1933
	from which

10 ins. diam., brs. N. 76°45'E., 185 1ks.

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

BOOK 4025

	Chains	dist., mkd. T8S R22E S5 BT.
		Raise a mound of stone, 3 ft. base, 12 ft. high, N. of cor.
	2.20	Gulch, course SW.; asc. 90 ft. over general NW. slope.
	5.00	Bend in same gulch, from NE. to NW.
	16.00	Descend 25 ft. over NE. slope.
	21.50	Same gulch, course NW.; asc. 192 ft.
	33.20	Rocky spur, slopes N.; desc. 30 ft.
	39.96	A point record distance E. in departure, from the cor. of secs. 7 and 8,
	A Parties	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for 4 sec. cor. of sec. 8 only, with brass cap marked
		
i		1933
•	•	from which
		A juniper tree, 5 ins. diam., brs. S.5°00'E., 126 lks. dist., mkd. 4 S8 BT.
		A juniper tree, 7 ins. diam., brs. S.23°00'E., 208 lks. dist., mkd. ½ S8 BT.
	40.70	✓A point 40 chs. W. in departure, from the cor. of secs. 4 and 5, hereinafter described,
	. ,	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone mkd. with a cross +. deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for \(\frac{1}{4} \) sec. cor. of sec. 5 only, with brass cap marked
		1933
	47.60	Gulch, course NW.; asc. 142 ft. over W. slope.
	61.00	Spur, slopes NW.; desc. slightly.
	70.00	Gulch, course N.60°W.; asc. 220 ft. over SW. slope.
	79•93	A point determined by cardinal offsets record distance N. in latitude, from # sec. cor. of secs. 8 and 9 and record distance E. in departure, from the cor. of secs. 7 and 8
		Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for cor. of sec. 8 only, with brass cap marked
,		T8s R22E \$5
		1933
		Land, rolling. Soil, rocky and gravelly; 3rd rate. Timber, a few scattering oak and juniper. Undergrowth, oak, mesquite and cactus.

4-6787b

RESURVEY OF A PORTION OF THE SUBDIVISION LINES OF T. 8 S., R. 22 E.

	Chains	Thence
		S. 2°23'E., on true line, on E. bdy. of sec. 8.
	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	Over SW. slope, through scattering timber and brush, desc. 68 ft.
	7.80	Gulch, course N.60°W.; asc. 208 ft. over NE. slope.
	23.50	Ridge, brs. N.60°W. and S.60°E.; desc. 60 ft.
	35.20	Ravine, course N.70°W.; asc. over NW. slope, 60 ft.
	40.04	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, which is a granite stone, 8 x 6 x 8 ins. above ground, firmly set, mkd. $\frac{1}{4}$ on W. face. In place of old stone which is set along side,
	· · · · · · · · · · · · · · · · · · ·	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of sec. 8 only, with brass cap marked
		4
	·	s8
ر.		1933 from which
		Old bearing trees.
		A fallen oak tree, 18 ins. diam., brs. N.8°30'W 49 lks. dist., mkd. 4 S BT.
		A dead oak tree, 15 ins. diam., brs. S.4°30'W., 76 lks. dist., mkd. 4 S BT.
		New bearing tree.
		A juniper tree, 8 ins. diam., brs. S.88°15'W., 66 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
		Thence
		S. 0°32'W., on true line, on E. bdy. of sec. 8.
		Descend 85 ft. over SW. slope.
	93	A point on the W. bdy. of sec. 9, midway bet. the closing cor. of secs. 5 and 9, and the closing cor. of sec. 9 and 16, both hereinafter described,
		Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base. 2 ft. high, for 4 sec. cor. of sec. 9 only, with brass cap marked
		$\begin{vmatrix} \frac{1}{4} \\ \mathbf{s}_9 \end{vmatrix}$
	*	1933
		from which
		An oak tree, 18 ins. diam., brs. S.62°00'E., 105 lks. dist., mkd. 4 S9 BT.
		An oak tree, 6 ins. diam., brs. N.78°00'E., 17 lks. dist., mkd. 4 S9 BT.
	11.50	Gulch, course N.60°W.; asc. over NE. slope, 292 ft.
	20:10	Ridge, brs. E. and N.60°W.; desc. 289 ft. over SW. slope.

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

BOOK (CI

Chains 39.56	The cor. of secs. 8 and 17, hereinbefore described.
	Land, mountainous. Soil, gravelly and rocky; 3rd rate. Timber, oak and juniper. Undergrowth, oak and buckbrush.
	From the cor. of secs. 7 and 8, hereinbefore described.
	West, on a random line, bet. secs. 6 and 7.
40.22	Fall 8 lks. N. of the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	Thence, from cor.
	West, on a random line, bet. secs. 6 and 7.
38.01	Fall 5.68 chs. N. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described.
	Thence, from cor.
	N.81°30'E., on true line, on N. bdy. of sec. 7.
	Over NE. slope, through scattering timber and brush, desc. 25 ft.
6.00	Gulch, course N.60°W.; asc. 178 ft. over general W. slope
15.00	Hickman's house, brs. N. 5 chs. distance.
22.36	Wire fence, brs. N.60°W. and S.60°E.
29.30	Spur, slopes NW.
35.63	Wire fence, brs. N.30°E. and S.30°W.
38•43	The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, which is a granite stone, 8 x 8 x 8 ins. above ground, firmly set, mkd. $\frac{1}{4}$ on N. face. In place of old stone which is set along side,
	Set an iron post, 3 ft. long, l in. diam. 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of sec. 7 only, with brass cap marked
	1933 raise a mound
	of stone, 3 ft. base, $l_{2}^{\frac{1}{2}}$ ft. high, S. of cor.
-	Thence
	N. 89°53'E., on true line, on N. bdy. of sec. 7.
	Over open gradual NW. slope, asc. 200 ft.
•92	A point 40 chs. W. in departure, from the cor. of secs. 5 and 6, hereinbefore described,
	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for a sec. cor. of sec. 6 only, with brass cap marked

RESURVEY OF A PORTION OF THE SUBDIVISION

LINES OF T. 8 S., R. 22 E.

25, 26, 35 and 36, hereinafter described, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass cap marked 4 S35 336 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked T8S R22E S26 S25 S35 S36 1933 from which		
7.80 Top of felsite dike, brs. NE, and SW.; thence over gradual SW. slope, asc. 80 ft. 12.90 Small draw, drains SW. 24.30 Top of felsite dike, brs. NE. and SW.; desc. 47 ft. over gradual SE. slope. The cor. of secs. 7 and 8, hereinbefore described. Land, rolling. Soil, rocky and gravelly; 2nd and 3rd rute. Timber, a few scattering jumiper and oak. Undergrowth, mesquite, oak and cactus. SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E. From the cor. of secs. 35 and 36, on S. bdy. of the Tp., hereinbefore described. N. 0*01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. Small spur, slopes SW.; desc. 55 ft. 17.40 Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0*01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross **, deposited at base, in a mound of stone, 3 ft. base, 12 ft. high, for **, sec. cor. of secs. 35 and 36, with brass cap marked **S35** Ascend 435 ft. over SE. slope. 52.20 Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. 60.02 A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked **Top of felsite dike, brs. N.54*00'E. 58 lks. dist. An oak tree, 12 ins. diam., brs. N.54*00'E. 58 lks. dist.	Chains	± S 6
ual SW. slope, asc. 80 ft. 24.30 Top of felsite dike, brs. NE. and SW.; desc. 47 ft. over gradual SE. slope. 40.22 The cor. of secs. 7 and 8, hereinbefore described. Lund. rolling. Soil, rocky and gravelly; 2nd and 3rd rate. Timber, a few scattering jumiper and oak. Undergrowth, mesquite, oak and cuctus. SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E. From the cor. of secs. 35 and 36, on S. bdy. of the Tp hereinbefore described. N. 0°01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. Small spur, slopes SW.; desc. 55 ft. Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. With a cross *, deposited at base, in a mound of stone; 3 ft. base, 15 ft. high, for \$ sec. cor. of secs. 35 and 36, with brass can marked **S35 336 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W. from the cor. of secs. 25, 36, 31 and 36, with brass cap marked **T83 R22E** S26 S25 S35 S36 S27 S36 S37 S36 Tom which An oak tree, 12 ins. diam., brs. N.64°00'E., 58 lks. dist.		
Top of felsite dike, brs. NE. and SW.; desc. 47 ft. over gradual SE. slope. 40.22 The cor. of secs. 7 and 8, hereinbefore described. Land, rolling. Soil, rocky and gravelly; 2nd and 3rd rate. Timber, a few scattering jumiper and oak. Undergrowth, mesquite, oak and cactus. SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E. From the cor. of secs. 35 and 36, on S. bdy. of the Tp., hereinbefore described. N. 0°01"W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. Small spur, slopes SW.; desc. 55 ft. 17.40 Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0°01"E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 13 ft. high, for 2 sec. cor. of secs. 35 and 36, with brass capmarked \$335 336 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope, through seattering timber and brush. 76.70 Guich, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked **T8S R22E* **S26 S25* **S35 356 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist.	7.80	
gradual SE. slope. The cor. of sees. 7 and 8, hereinbefore described. Land, rolling. Soil, rocky and gravelly; 2nd and 3rd rate. Timber, a few scattering juniper and oak. Undergrowth, mesquite, oak and cactus. SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E. From the cor. of sees. 35 and 36, on S. bdy. of the Tp., hereinbefore described. N. 0*01'W., bet. sees. 35 and 36. Over open gradual SW. slope, asc. 145 ft. Small spur, slopes SW.; desc. 55 ft. Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0*01'E., from the cor. of sees. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ thigh, for \$\frac{1}{2}\$ see. cor. of sees. 35 and 36, with brass cap marked \$355 336	12.90	Small draw, drains SW.
Land, rolling. Soil, rocky and gravelly; 2nd and 3rd rate. Timber, a few scattering juniper and oak. Undergrowth, mesquite, oak and cactus. SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E. From the cor. of secs. 35 and 36, on S. bdy. of the Tp hereinbefore described. N. 0°01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. 3.40 Small spur, slopes SW.; desc. 55 ft. 17.40 Draw, drains SW.; asc. 439 ft. over S. slope. 40.02 A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post. 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone made. with a cross + deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass cap marked \$355 336 1933 Ascend 435 ft. over SE. slope. \$2.20 Spur, slopes SW.; desc. 282 ft. over NW. slope. through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. 80.02 A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked T8S R2EE \$26 S25 \$35 336 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E.58 lks. dist.	24.30	
Soil, rocky and gravelly; 2nd and 3rd rate. Timber, a few scattering jumiper and oak. Undergrowth, mesquite, oak and oactus. SUBDIVISION OF A FORTION OF T. 8 S., R. 22 E. From the cor. of secs. 35 and 36, on S. bdy. of the Tp., hereinbefore described. N. 0°01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. Small spur, slopes SW.; desc. 55 ft. Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 25, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mXd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for \$\frac{1}{2}\$ sec. cor. of secs. 35 and 36, with brass cap marked \$335 336 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W., from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked Tess R2EE	40.22	The cor. of secs. 7 and 8, hereinbefore described.
From the cor. of secs. 35 and 36, on S. bdy. of the Tp hereinbefore described. N. 0°01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. 13.40 Small spur, slopes SW.; desc. 55 ft. Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass cap marked **335 336 1933 Ascend 435 ft. over SE. slope. \$2.20 Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked **R83 R22E* **\$26 S25 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.04°00'E., 58 lks. dist.		Soil, rocky and gravelly; 2nd and 3rd rate. Timber, a few scattering juniper and oak.
From the cor. of secs. 35 and 36, on S. bdy. of the Tp hereinbefore described. N. 0°01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. 13.40 Small spur, slopes SW.; desc. 55 ft. Draw, drains SW.; asc. 439 ft. over S. slope. A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass cap marked **335 336 1933 Ascend 435 ft. over SE. slope. \$2.20 Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked **R83 R22E* **\$26 S25 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.04°00'E., 58 lks. dist.		
hereinbefore described. N. 0°01'W., bet. secs. 35 and 36. Over open gradual SW. slope, asc. 145 ft. 13.40 Small spur, slopes SW.; desc. 55 ft. 17.40 Draw, drains SW.; asc. 439 ft. over S. slope. 40.02 A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 12 ft. high, for 1 sec. cor. of secs. 35 and 36, with brass capmarked 335 336 1933 Ascend 435 ft. over SE. slope. 52.20 Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. 80.02 A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 788 R22E 826 S25 837 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist.		SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E.
Over open gradual SW. slope, asc. 145 ft. 13.40 Small spur, slopes SW.; desc. 55 ft. 17.40 Draw, drains SW.; asc. 439 ft. over S. slope. 40.02 A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross *, deposited at base, in a mound of stone, 3 ft. base, 12 ft. high, for ‡ sec. cor. of secs. 35 and 36, with brass capmarked 4 S35 S36 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 78S R22E \$26 S25 \$35 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E58 lks. dist.		From the cor. of secs. 35 and 36, on S. bdy. of the Tp., hereinbefore described.
13.40 Draw, drains SW.; asc. 439 ft. over S. slope. 40.02 A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 25, 35 and 36, hereinafter described, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass can marked 535 336 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 783 R22E \$26 S25 \$35 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E58 lks. dist.		N. 0°01'W., bet. secs. 35 and 36.
Draw, drains SW.; asc. 439 ft. over S. slope. 40.02 A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass cap marked 4 S35 336 1933 Ascend 435 ft. over SE. slope. 52.20 Spur, slopes SW.; desc. 282 ft. over NW. slope, through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 783 R22E \$26 S25 \$35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist.		Over open gradual SW. slope, asc. 145 ft.
A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass capmarked \$35 \begin{align*} 336 \\ 1933 \end{align*} Ascend 435 ft. over SE. slope. \$2.20 \text{Spur, slopes SW.; desc. 282 ft. over NW. slope. through scattering timber and brush. 76.70 \text{Gulch, course SW.; asc. 111 ft. over SE. slope.} \$0.02 \text{A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described.} Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked \$783 R22E \text{ \frac{526 \frac{525}{335} \frac{336}{336} \text{ \frac{536}{1933}} \text{ from which} An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist.	13.40	Small spur, slopes SW.; desc. 55 ft.
25, 26, 35 and 36, hereinafter described, Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone. 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 35 and 36, with brass cap marked 336 1933 Ascend 435 ft. over SE. slope. Spur, slopes SW.; desc. 282 ft. over NW. slope. through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 788 R22E 526 S25 535 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.	17.40	Draw, drains SW.; asc. 439 ft. over S. slope.
ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 1½ ft. high, for ¼ sec. cor. of secs. 35 and 36, with brass cap marked S35 336	40.02	A point 40 chs. dist., S. 0°01'E., from the cor. of secs. 25, 26, 35 and 36, hereinafter described,
Ascend 435 ft. over SE. slope. 52.20 Spur, slopes SW.; desc. 282 ft. over NW. slope. through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. 80.02 A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 788 R22E \$26 \$25 \$35 \$36 \$1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.		Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 3 ft. base, 12 ft. high, for 4 sec. cor. of secs. 35 and 36, with brass cap marked
Ascend 435 ft. over SE. slope. 52.20 Spur, slopes SW.; desc. 282 ft. over NW. slope. through scattering timber and brush. 76.70 Gulch, course SW.; asc. 111 ft. over SE. slope. 80.02 A point 79.91 chs. dist. W from the cor. of secs. 25, 30, 31 and 36, hereinbefore described, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 788 R22E \$26 \$25 \$35 \$36 \$1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.		
Spur, slopes SW.; desc. 282 ft. over NW. slope. through scattering timber and brush. 76.70 Gulch, course SW.; asc. lll ft. over SE. slope. 80.02 A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 78S R22E S26 S25 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64°00'E58 lks. dist.		1933
scattering timber and brush. 76.70 Gulch, course SW.; asc. lll ft. over SE. slope. 80.02 A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked 785 R22E 526 S25 535 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.		Ascend 435 ft. over SE. slope.
A point 79.91 chs. dist. W. from the cor. of secs. 25, 30, 31 and 36, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked T8S R22E S26 S25 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.	52.20	
30, 31 and 36, hereinbefore described, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked T8S R22E S26 S25 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.	76.70	Gulch, course SW.; asc. lll ft. over SE. slope.
the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked #85 R22E S26 S25 S35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E58 lks. dist.	80.02	
s35 S36 1933 from which An oak tree, 12 ins. diam., brs. N.64*00'E.,58 lks. dist.		the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap marked T8s R22E
An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist.		\$35 \\$36 1933
An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist. mkd. T8S R22E S25 BT.		
	 r	An oak tree, 12 ins. diam., brs. N.64°00'E.,58 lks. dist. mkd. T8S R22E S25 BT.

BOOK 4025

	Chains	An oak tree, 10 ins. diam., brs. S.10°30'E., 94 lks. dist., mkd. T8S R22E S36 BT.
		An oak tree, 12 ins. diam., brs. S. 71°00'W., 127 lks. dist., mkd. T8S R22E S35 BT.
	."	An oak tree, 5 ins. diam., brs. N.87°15'W., 205 lks. dist., mkd. T8S R22E S26 BT.
		Land, mountainous. Soil, gravelly and rocky; 3rd rate. Timber, oak and juniper. Undergrowth, mesquite, oak and buckbrush.
		From the cor. of secs. 25, 30, 31 and 36, on E. bdy. of Tp., hereinbefore described.
		West, on sectional correction line, bet. secs. 25 and 36.
		Over rocky SW. slope, through scattering timber and brush desc. 100 ft.
	2.50	Gulch, course SE.; asc. 410 ft. over SE. slope.
	17.40	Spur, slopes SE.; desc. 75 ft.
	24.30	Gulch, course SE.; asc. 472 ft. over SE. slope.
	39.00	Ridge, brs. N. and S.50°W.; desc. 26 ft.
	39.96	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of secs. 25 and 36, with brass cap marked
٠		\$\frac{\square s 25}{\square s 36}\$\$ \$1933\$ raise a mound
		of stone, 3 ft. base, 2 ft. high, N. of cor.
		Descend 1025 ft. over general NW. slope.
	70.00	Enter ravine, course from S.60°E. to W.
	73.60	Leave ravine, course N.75°W.
	75.60	Gulch, course SW.; asc. 73 ft. over SE. slope.
	79.91	The cor. of secs. 25, 26, 35 and 36.
	79.92	Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, oak, hackberry and juniper. Undergrowth, oak and buckbrush.
		N. 0°01'W., bet. secs. 25 and 26.
		Over SE. slope, through scattering timber and brush, asc. 260 ft.
	15.50	Small spur, slopes SE.; desc. 50 ft.
	17.50	Ravine, course SE.; thence over general S. slope, asc. 454 ft.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the

4—673 b • 38

Chains	ground to bedrock, in a mound of stone $3\frac{1}{2}$ ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor. of secs. 25 and 26, with brass cap marked
-	
	∨ s26 s25
	1933 from which
	An oak tree, 7 ins. diam., brs. S.34°00'W., 32 lks. dist., mkd. 2 S26 BT.
	An oak tree, 15 ins. diam., brs. N.47°00'E., 40 lks. dist., mkd. 4 S25 BT.
	Ascend over S. slope 53 ft.
43.00	Ridge, brs. N.75°E. and S.75°W.; desc. 537 ft. over N. slope.
56.40	Gulch, course W.; asc. 319 ft. over SW. slope.
67.50	Spur, slopes W.; desc. 119 ft.
74.10	Gulch, course S.60°W.; asc. 178 ft. over S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap marked
-	T8S R22E S23 S24
	\$26\\$25 1933
	from which
	An oak tree, 6 ins. diam., brs. S.80°00'E., 34 lks. dist., mkd. T8S R22E S25 BT.
	An oak tree, 24 ins. diam., brs. N.35°00'W., 15 lks. dist., mkd. T8S R22E S23 BT.
	An oak tree, 6 ins. diam., brs. N.30°E., 29 lks. dist., mkd. T8S R22E S24 BT.
	No other suitable accessory.
	Land, rough mountainous. Soil, rocky; 4th rate.
	Timber, oak, juniper and pine. Undergrowth, oak, buckbrush and manzanita.
	East, on a random line, bet. secs. 24 and 25.
40.00	Set temp. 4 sec. cor.
80.00	Intersect E. bdy. of Tp. at the cor. of secs. 19, 24, 25 and 30.
	Thence
	West, on true line, bet. secs. 24 and 25.
	Over NE. slope, through scattering timber and undergrowth asc. 10 ft.
•60	Spur, slopes SE.; desc. 76 ft. over W. slope.
	, · · · · · · · · · · · · · · · · · · ·

EGCK 4025

	Chains 7.40	Ravine, course SE.; asc. 644 ft. over general E. slope.
	33.40	Ridge, brs. N. and S.; desc. 150 ft. over NW. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 24 and 25, with brass cap marked
		1 S 24 S 25 S 25 S 25 S 1933 S from which
		A juniper tree, 38 ins. diam., brs. N.45°00'W 50 lks. dist., mkd. ½ S24 BT.
		A pine tree, 7 ins. diam., brs. S.64°30'E 48 lks. dist. mkd. 4 S25 BT.
		Descend 238 ft. over NW. slope.
	47.20	Gulch, course S.60°W.; thence over SW. slope, desc. 535 ft.
	80.00	The cor. of secs. 23, 24, 25 and 26.
		Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate.
•		Timber, pine, oak and juniper. Undergrowth, oak, buckbrush and manzanita.
	•	
		N. 0°01'W., bet. secs. 23 and 24.
		Over S. slope, through scattering timber and brush, asc. 214 ft.
	6.25	Ridge, brs. N.80°E. and S.60°W.; desc. 540 ft. over NW. slope.
	32.70	Gulch, course W.; asc. 50 ft.
,	33.80	Small spur, slopes W.; desc. 30 ft.
	34•40	Gulch, course S.60°W.; asc. 235 ft. over S. slope.
	40.00	True point for the $\frac{1}{4}$ sec. cor. falls on rock ledge, a place unsuitable for a permanent cor. I chisel a mark +, on ledge at this point.
•	40.09	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, 2 ft. high, for witness ½ sec. cor. of secs. 23 and 24, with brass cap marked
		1 S23 S24
		1933 from which
		A pinyon tree, 10 ins. diam., brs. N.13°00'W., 35 lks. dist., mkd. WC 4 S23 BT.
		A pinyon tree, 8 ins. diam., brs. N.72°00'E., 32 lks. dist., mkd. WC 4 S24.
	41.50	Spur, slopes W.; desc. 50 ft. over NW. slope.

Chains 45.90	Ravine, course N.75°W.; asc. 245 ft. over general SW. slope.
50.00	Draw, drains SW.
59-50	Spur, slopes SW.; desc. 290 ft. over NW. slope.
68.10	Gulch, course SW.; asc. 500 ft. over S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base. 1 ft. high, for cor. of secs. 13, 14, 23 and 24, with brass cap marked
	T8S R22E S14 S13 S23 S24
	1933 from which
	An oak tree, 12 ins. diam., brs. N.23°45'E.,54 lks. dist., mkd. T8S R22E S13 BT.
	An oak tree, 14 ins. diam., brs. S.22°45'E.,53 lks. dist., mkd. T8S R22E S24 BT.
	A pine tree, 4 ins. diam., brs. S.88°30'W.,49 lks. dist., mkd. BT enly.
	An oak tree, 16 ins. diam., brs. N.3°30'W.,75 lks. dist., mkd. T8S R22E S14 BT.
	Land, rough mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, pine, oak, pinyon and juniper. Undergrowth, manzanita, buckbrush and oak.
	East, on a random line, bet. secs. 13 and 24.
40.00	Set temp. 4 sec. cor.
80.04	Intersect E. bdy. of Tp., 5 lks. N. of the cor. of secs. 13, 18, 19 and 24, hereinbefore described.
	Thence
	N. 89°58'W., on true line, bet. secs. 13 and 24.
	Over SE. slope, through heavy pine timber, asc. 60 ft.
12.00	Top of mountain, brs. NE. and SW; desc. 131 ft. over NW. slope.
26.90	Draw, drains N.30°W.; asc. 23 ft.
29.40	Ridge, brs. NW. and SE.; desc. 203 ft. over SW. slope.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for \(\frac{1}{4} \) sec. cor. of secs. 13 and 24, with brass cap marked
	$ \begin{array}{c c} \frac{1}{4} & \frac{S \ 13}{S \ 24} \\ 1933 & \text{from which} \end{array} $
	f pine tree, 24 ins. diam., brs. S.26°30'W.,117 lks.

ECCX (!!

Chains	dist., mkd. 4 S24 BT.
	A pine tree, 16 ins. diam., brs. N.14.45 W., 79 lks. dist., mkd. 4 S13 BT.
	Descend 1100 ft. over broken SW. slope.
80.04	The cor. of secs. 13, 14, 23 and 24.
,	Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, pine, pinyon, juniper and oak. Undergrowth, oak, buckbrush and manzanita.
	N. 0°01'W., bet. secs. 13 and 14.
¥. 1	Over SW. slope, through scattering timber and dense undergrowth, asc. 21 ft.
1.90	Low spur, slopes SW.; desc. 50 ft.
5.10	Ravine, course SW.; asc. 120 ft. over SW. slope.
13.60	Ridge, brs. N.60°W. and S.60°E.; desc. 147 ft. over NW. slope.
23.30	Gulch, course NW.; asc. 46 ft. over SW. slope.
33-30	Low spur, slopes W.; desc. 25 ft.
37•40	Draw, drains SW.; asc. 48 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for \(\frac{1}{4}\) sec. cor. of secs. 13 and 14. with brass cap marked
	s14 s13
	1933 from which
	· A pine tree, 6 ins. diam., brs. N.76°15'W., 26 lks. dist.,
	mkd. ½ S14 BT.
· •	An oak tree, 7 ins. diam., brs. S.59°15'E., 61 lks. dist., mkd. ½ S13 BT.
*	Ascend 26 ft.
43.00	Spur, slopes NW.; desc. 398 ft. over NW. slope.
60.70	Gulch, course S.80°W.; asc. 424 ft. over broken S. slope.
74.60	Ridge, brs. N.70°E. and S.70°W.; desc. 185 ft. over N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for cor. of secs. 11, 12, 13 and 14, with brass cap marked TOS R22E
	S11 S12 S14 S13
	1933 from which
, '	

ECCX 4025

Chains	dist., mkd. T8S R22E S12 BT.
3	A pine tree, 9 ins. diam., brs. S.43°15'E.,93 lks. dist., mkd. T8S R22E S13 BT.
	A pine tree, 18 ins. diam., brs. S.66°45'W.,58 lks. dist. mkd. T8S R22E S14 BT.
	A pine tree, 8 ins. diam., brs. N.80°00'W.,19 lks. dist., mkd. T8S R22E S11 BT.
	Land, mountainous. Soil, rocky and gravelly; 3rd rate. Timber, pine, and oak. Undergrowth, oak, buckbrush and manzanita.
	S. 89°58'E., on a random line, bet. secs. 12 and 13.
40.00	Set temp. ½ sec. cor.
79•94	Intersect E. boundary of Tp., 16 lks. N. of the cor. of secs. 7, 12, 13 and 18, hereinbefore described.
	Thence
	N. 89°51'W., on true line, bet. secs. 12 and 13.
	Over general NE. slope, through heavy timber and scattering brush, axc. gradually 100 ft.
25.00	Low spur, slopes N.; desc. 30 ft.
26.30	Ravine, course N.; asc. 75 ft.
28.70	Spur, slopes NW.; desc. 191 ft. over NW. slope.
39•97	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 12 ft. high, for 4 sec. cor. of secs. 12 and 13, with brass cap marked
. :	s 12 s 13 1933
	from which
	A pine tree, ll ins. diam., brs. S.14°45'W.,31 lks. dist. mkd. \(\frac{1}{4} \) S13 BT.
	A pine tree, 9 ins. diam., brs. N.23°00'W., 24 lks. dist., mkd. 4 S12 BT.
	Descend 223 ft.
48.60	Gulch, course NW.; asc. over NE. slope, 55 ft.
64.00	Thence over NW. slope, desc. 183 ft.
79•94	The cor. of secs. 11, 12, 13 and 14.
	Land, mountainous. Soil, rocky and gravelly; 3rd rate. Timber, pine, fir, oak and ash. Undergrowth, oak, manzanita, willow and mountain mahogany.
V	
	N. 0°01'W., bet. secs. 11 and 12.

ECCK 4025

	Chains	Over NW. slope, through scattering timber and undergrowth desc. 551 ft.
	27•45	Gulch, course NW.; asc. 54 ft. over SW. slope.
	33.60	Spur, slopes NW.; desc. slightly.
	36.00	Gulch, course NW.; asc. 44 ft.
	39.00	Spur, slopes W.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, in a small mound of stone, for $\frac{1}{4}$ sec. cor. of secs. 11 and 12, with brass cap marked
		sll sl2 1933 from which
		An oak tree, 10 ins. diam., brs. N.79°00'E., 15 lks. dist., mkd. 4 S12 BT.
	Same of	A pine tree, 8 ins. diam., brs. N.87°30'W., 41 lks. dist. mkd. $\frac{1}{4}$ S11. BT.
	42.80	Descend 20 ft. over N. slope.
. •	43.20	Small ravine, course NW.; asc. 20 ft.
	50.20	Spur, slopes NW.; desc. 28 ft.
	51.20	Gulch, course W.; asc. over S. slope, 233 ft.
	63.40	Ridge, brs. E. and W.; desc. 373 ft. over NE. slope.
	75-40	Gulch, near head; asc. 19 ft.
	75.80	Small spur, slopes E.; desc. 25 ft.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1½ ft. high, for cor. of secs. 1, 2, 11 and 12, with brass cap marked T8S,R22E
		S2 S1 S11 S12 1933 from which A juniper tree, 12 ins. diam., brs. N.51°30'E., 57 lks.
		1ks. dist., mkd. T8S R22E S1 BT. A juniper tree, 9 ins. diam., brs. S.35°00'E.,88 1ks.
		dist., mkd. T8S R22E S12 BT.
	v	A juniper tree, 48 ins. diam., brs. S.71°30'W.,84 iks. dist.,mkd. T8S R22E S11 BT.
		A pine tree, 14 ins. diam., brs. N.78°45'W.,50 lks. dist., mkd. T8S R22E S2 BT.
		Land, mountainous. Soil, gravelly; 3rd rate. Timber, pine, juniper, laurel and oak. Undergrowth, oak, locust and mountain mahogany.

4-673 b 44 BOOK 4025

	Chains	S.89°51'E., on a random line bet. secs. 1 and 12.
	40.00	Set temp. 4 sec. cor.
	80.02	Intersect E. bdy. of Tp., 14 lks. S. of the cor. of secs. 1. 6, 7 and 12, hereinbefore described.
		Thence
		N.89°57'W., on true line, bet. secs. 1 and 12.
		Over NW. slope, through heavy timber and scattering brush desc. 50 ft.
	8.20	Thence, over NE. slope, asc. 29 ft.
	10.60	Spur, slopes NW.; desc. 820 ft. over W. slope.
ı	40.01	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1½ ft. high, for 4 sec. cor. of secs. 1 and 12, with brass cap marked
	·	1 S 1 S12
		1933 from which
	v	An oak tree, 7 ins. diam., brs. N.47°00 E., 24 lks. dist. mkd. $\frac{1}{4}$ Sl BT.
	V	An oak tree, 8 ins. diam., brs. S.66°00'W.,51 lks. dist., mkd. ½ S12 BT.
		Descend slightly.
	46.00	Sawmill Gulch, course NW.; asc. 184 ft. over E. slope.
	66.70	Spur, slopes NE.; desc. 63 ft. over gradual NE. slope.
	71.90	Telephone line, brs. N. and S.
	74,20	Ravine, course NE.; asc. 109 ft.
	78.35	Trail, brs. NW. and SE.
	80.02	The cor. of secs. 1, 2, 11 and 12.
	:	Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, pine, fir, oak and mountain laurel. Undergrowth, oak, willow, locust and manzanita.
	v	
		North, on a random line, bet. secs. 1 and 2.
	40.00	Set temp. \(\frac{1}{4}\) sec. cor.
	74.41	Intersect N. bdy. of Tp., 7 lks. E. of the cor. of secs. 1 and 2, hereinbefore described.
		Thence
		S. 0°03'E., on true line bet. secs. 1 and 2.
		Over gradual SE. slope, through scattering juniper timber.
	P	asc. 88 ft.
ļ	8.40	Spur, slopes NW.; desc. 10 ft.
	ı j	

BOOK 4025

	Chains 16.60	Sawmill Gulch, course NW.; asc. 191 ft. over N. slope.
	19.50	Old road, brs. NW. and SE.
	34•41	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground in a mound of stone, for 4 sec. cor. of secs. 1 and 2, with brass cap marked
		v s2 s1
		1933 from which
	Y	A juniper tree, 8 ins. diam., brs. N.70°45'W., 33 lks. dist., mkd. 4 S2 BT.
		A juniper tree, 20 ins. diam., brs. N.26°45'E., 75 lks. dist., mkd. ± Sl BT.
	•	Ascend 195 ft. over NE. slope.
	40.50	Trail, brs. NW. and SE.
-	40.65	Same trail, brs. N.70°W. and S.70°E.
	42.20°	Telephone line, brs. NW. and SE.
	43.00	Spur, slopes E.; desc. 24 ft.
	45•50	Ravine, course E.; asc. 409 ft. over NE. slope.
	51.60	Trail, brs. N.80°W. and S.80°E.
	52.25	Telephone line, brs. NW. and SE.
	65.00	Spur, slopes E.; desc. slightly.
	71.90	Bend in trail, from NE. to SE.
	72.40	Ravine, course E.; asc. 60 ft. over NE. slope.
	72.90	Trail, brs. NW. and SE.
	74.41	The cor. of secs. 1, 2, 11 and 12.
		Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, pine, oak and juniper. Undergrowth, oak and manzanita.
		From the cor. of secs. 25, 26, 35 and 36.
	-	West, on sectional correction line, bet. secs. 26 and 35.
		Over SE. slope, through scattering pinyon and oak, asc. 56 ft.
	4.70	Spur, slopes S.; desc. 130 ft.
	10.20	Gulch, course S.; asc. 180 ft.
	16.00	Spur, slopes S.; desc. 225 ft. over general SW. slope.
	30.90	Ravine, course S.; asc. 185 ft. over SE. slope.
	39.70	Spur, slopes SW.; desc. slightly.
	١ ١	t de la companya de

	Chains 40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 2 ft. high, for 4 sec. cor. of secs. 26 and 35, with brass cap marked
		$\begin{array}{c c} & \underline{s} & \underline{26} \\ \hline & \underline{s} & \underline{35} \\ & \underline{1933} & \underline{from \ which} \end{array}$
		An oak tree, 7 ins. diam., brs. S.49°45'W.,173 lks. dist., mkd. ± S35 BT.
		A pinyon tree, 8 ins. diam., brs. N.21°30'W.,144 lks. dist., mkd. 4 S26 BT.
		Descend 620 ft. over W. slope.
	64.20	Gulch, course S.60°W.; asc. slightly over SE. slope.
	70.00	Low spur, slopes SW.; desc. 80 ft. over SW. slope.
	78.76	Intersect E. bdy. of sec. 34, 59 lks. dist., S.0°08'E., from the cor. of secs. 27 and 34, hereinbefore described.
	·	At this point, which falls on sloping rock ledge, where the cor. monument would be insecure, I chisel a mark +. and at a point 3 lks. E. of true point for cor.,
		Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 2½ ft. high, for witness closing cor. of secs. 26 and 35, with brass cap marked
		T8s R22E S26 S35 1933
		Land, mountainous. Soil, rocky; 4th rate. Timber, scattering pinyon and oak. Undergrowth, oak and manzanita.
		From the cor. of secs. 26 and 27, hereinbefore described.
	·	East, on a random line, bet. secs. 23 and 26.
	40.00	Set temp. 2 sec. cor.
	79.12	Intersect N. and S. line, 14 lks. S. of the cor. of secs. 23, 24, 25 and 26.
		Thence
		S. 89°54 W., on true line, bet. secs. 23 and 26.
•		Over broken SW. slope, through scattering timber and under- growth, desc. 330 ft.
	16.80	Gulch, course S.; asc. 100 ft.
	23.00	Ridge, brs. N.38°E. and S.38°W.; desc. 133 ft. over NW. slope.
	35.20	Spur, slopes NW.; thence over SW. slope, desc. 230 ft.
	40.00	A point midway bet. the cor. of secs. 23, 24, 25 and 26, and the cor. of secs. 22 and 23, hereinbefore described.
_		

EGON 4025

Chains	Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 23 and 26, with brass cap marked
	$\frac{1}{4}$ $\frac{s}{s}$ $\frac{23}{s}$
	1933 from which
<i>ν</i>	An oak tree, 15 ins. diam., brs. N.17°45'W., 44 lks. dist., mkd. \(\frac{1}{4}\) S23 BT.
· . V	An oak tree, 14 ins. diam., brs. S.31°15'W.,68 lks. dist., mkd. 4 S26 BT.
-	Descend 305 ft. over SW. slope.
49,20	Wire fence, brs. N.70°E. and S.10°W.
54.20	Ravine, course SW.; asc. 43 ft. over general SE. slope.
63.10	Spur, slopes SW.; desc. 255 ft. over W. slope.
76.50	Draw, drains S.; asc. 50 ft. over SE. slope.
79.12	The cor. of secs. 26 and 27.
	Land, mountainous. Soil, rocky; 4th rate. Timber, oak and juniper. Undergrowth, manzanita and oak.
V	
	From the cor. of secs. 22 and 23, hereinbefore described.
	N. 0°01'W., bet. secs. 22 and 23.
	Over S. slope, through scattering timber and brush, asc. 178 ft.
10.00	Spur, slopes S.60°W.; desc. 147 ft. over NW. slope:
14.20	Wire fence, brs. E. and W.
17.10	Gulch, course W.; asc. 60 ft.
26.20	Descend 20 ft. over N. slope.
28.20	Gulch, course SW.; asc. 275 ft. over S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, $2\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 22 and 23, with brass cap marked
	r S22 S23
	1933
	from which

from which

An oak tree, 8 ins. diam., brs. S.65°00'W.,156 lks. dist. mkd. $\frac{1}{4}$ S22BT.

An oak tree, 7 ins. diam., brs. N.39°15'E.,128 lks. dist., mkd. 2 S 23 BT.

Ascend 188 ft. over S. slope.

s. sovernment printing office: 1931 6-815

	'Chains 46.20	Spur, slopes W.; desc. 276 ft. over general NW. slope.
	53.60	Ravine, course N.70°W.
	59•90	Gulch, course W.; asc. 163 ft. over SW. slope.
	72.50	Spur, slopes W.; desc. 123 ft.
	77•50	Ravine, course W.; asc. 40 ft. over SW. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap marked TOS, R22E
		S15 S14 S22 S23
		1933 from which
	<u>.</u>	An oak tree, 7 ins. diam., brs. N.23°15'E.,61 lks. dist., mkd. T8S R22E S14 BT.
		An oak tree, 8 ins. diam., brs. S.25°00'E.,70 lks. dist., mkd. T8S R22E S23 BT.
		An oak tree, 9 ins. diam., brs. S.85°45'W.,33 lks. dist., mkd. T8S R22E S22 BT.
		An oak tree, 8 ins. diam., brs. N.56°15'W.,72 lks. dist., mkd. T8S R22E S15 BT.
		Land, mountainous. Soil, rocky; 4th rate. Timber, pine, oak and juniper. Undergrowth, oak and manzanita.
		N.89°54'E., on a random line, bet. secs. 14'and 23.
	40.00	Set temp. & sec. cor.
	79•94	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 13, 14, 23 and 24.
		Thence
		S. 89°53'W., on true line, bet. secs. 14 and 23.
		Over general W. slope, through scattering timber and brush, desc. 700 ft.
	20.00	Ravine, course S.; asc. 370 ft. over general SE. slope.
	39.20	Spur, slopes SW.; Thence along broken S. slope.
	39•97	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base. 2 ft. high, for \(\frac{1}{4}\) sec. cor. of secs. 14 and 23, with brass cap marked
		s 14 s 23 1933
		from which
		An oak tree, 14 ins. diam., brs. N.19°00'E.,31 lks. dist. mkd. 4 S14 BT.
_	1.	An oak tree, 6 ins. diam., brs. S.34°00'W., 115 lks. dist.

FOOK 4025

	EQUIC 402
Chains	mkd. ½ S23 BT.
54.80	Spur, slopes SW.; desc. 460 ft. over W. slope.
79•94	The cor. of secs. 14, 15, 22 and 23.
	Land, mountainous. Soil, rocky; 4th rate. Timber, pine, oak and juniper. Undergrowth, oak and manzanita.
	N. 0°01'W., bet. secs. 14 and 15.
	Over NW. slope, through scattering timber and brush, desc. 50 ft.
3.20	Draw, course W.
17.80	Draw, S.30°W.; asc. 147 ft.
21.30	Small spur, slopes S.30°W.; desc. 50 ft.
22.80	Draw, course S.30°W.; 190 ft. over SE. slope.
39•50	Draw, course S.30°W.; asc. 426 ft. over S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 14 and 15, with brass cap marked
	ν s15 s14
	1933 from which
. , .	An oak tree, 8 ins. diam., brs. S.19°00'E.,55 lks. dist., mkd. 4 S14 BT.
	A juniper tree, 24 ins. diam., brs. N. 65 00 W., 54 lks. dist., mkd. 4 S15 BT.
52.10	Ridge, brs. E. and W.; desc. 168 ft. over NW. slope.
55.60	Small draw, course NW.
69.10	Small draw, course W.; asc. 220 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for cor. of secs. 10, 11, 14 and 15, with brass cap marked
4	T8s R22E \$10 \$11 \$15 \$14 1933 from which
	A pinyon tree, 10 ins. diam., brs. S.11°15'E139 lks. dist., mkd. T8S R22E S14 BT.
-	An oak tree, 10 ins. diam., brs. N.45°45'E., 22 lks. dist., mkd. T8S R22E S11 BT.
	A juniper tree, 12 ins. diam., brs. S.36°45'W.,74 lks. dist., mkd. T8S R22E S15 BT.
	i ,

An oak tree, 9 ins. diam., brs. N.64°45'W.,24 lks. dist.,

	Chains	T8S R22E S10 BT.
		Land, mountainous. Soil, gravelly; 3rd rate. Timber, pine, pinyon, juniper and oak. Undergrowth, oak, buckbrush and manzanita.
		N. 89°53'E., on a random line, bet. secs. 11 and 14.
	40.00	Set temp. 4 sec. cor.
	80.01	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 11, 12, 13, and 14.
	r	Thence
		S. 89°52'W., on true line, bet. secs. 11 and 14.
		Over NW. slope, through scattering timber and brush, desc. 39 ft.
	9•50	Thence over broken W. slope, desc. 743 ft.
	35•50	Gulch, course N.30°W.; asc. 142 ft. over E. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft.
	.	high, for 4 sec. cor. of secs. 11 and 14, with brass cap marked
		S 11
		1933
		from which
~		vA juniper tree, 9 ins. diam., brs. S.2°45'W.,67 lks. dist., mkd. 4 S14 BT.
		WA pine tree, 7 ins. diam., brs. N.51°00'W58 lks. dist., mkd. 4 Sll BT.
		Ascend 347 ft. over general E. slope.
	68.00	Ridge, brs. N. and S.; desc. 181 ft. over SW. slope.
	80.01	The cor. of secs. 10, 11, 14 and 15.
		Land, mountainous. Soil, rocky and gravelly; 3rd and 4th rate. Timber, pine, juniper, oak and fir. Undergrowth, oak, manzanita and willow.
,		N. 0°01'W., bet. secs. 10 and 11.
		Over SW. slope, through scattering timber and brush, asc. slightly.
	.80	Thence over general NW. slope, desc. 220 ft.
	29.80	Rayine, course W.; asc. 84 ft.
:	36.00	Spur, slopes SW.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 10 and 11, with brass

BOOK 4025

_	Chains	cap marked
	,	4
		S10 S11
		1933 from which
	** .	An oak tree, ll ins. diam., brs. S.33°00'W.,26 lks. dist., mkd. 4 S10 BT.
,		A pinyon tree, ll ins. diam., brs. N.34°45'E., 72 lks. dist., mkd. 4 Sll BT.
		Ascend 45 ft.
	44.00	Rocky spur, slopes NW.; desc. 475 ft. over N. slope.
	65.00	Draw, course NE.; asc. 20 ft.
	70.00	Spur, slopes NE.; desc. 191 ft. over NE. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for cor. of secs. 2, 3, 10 and 11, with
		brass cap marked T8S R22E
		S3 S2 S10 S11
	•	1933 from which
		A juniper tree, 16 ins. diam., brs. S.67°15'E.,88 lks. dist., mkd. T8S R22E Sll BT.
		A juniper tree, 5 ins. diam., brs. N.63°00'E56 lks. dist., mkd. T8S R22E S2 BT.
		An oak tree, 7 ins. diam., brs. S83°30'W.,41 lks. dist., mkd. T8S R22E S10 BT.
		An oak tree, 10 ins. diam., brs. N.22°00'W., 58 lks. dist., mkd. T8S R22E S3 BT.
		Land, mountainous. Soil, rocky; 3rd and 4th rate. Timber, pine, juniper, pinyon and oak. Undergrowth, oak and manzanita.
	· · · · · · · · · · · · · · · · · · ·	
	•	
		N. 89°52'E., on a random line, bet. secs. 2 and 11.
	40.00	Set temp. 4 sec. cor.
	79.76	Intersect N. and S. line, 9 lks. S. of the cor. of secs. 1, 2, 11 and 12.
		Thence
	. •	S. 89°48'W., on true line, bet. secs. 2 and 11.
		Over NE. slope, through timber and brush, asc. 101 ft.
	10.00	Top of ascent; thence along N. slope.
	29.50	Ridge, brs. NW. and SE.; desc. 226 ft. over SW. slope.
	39.88	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 12

4-673 b

52

_	Chains	ft. high, for $\frac{1}{4}$ sec. cor. of secs. 2 and 11, with brass cap marked
		$ \begin{array}{ccc} \iota & \frac{1}{4} & \frac{S}{S} & \frac{2}{S} & \frac{1}{S} & \frac{1}{S} \end{array} $
		s 11 1933
	1 1 2 1 2 2	from which
		\sim An oak tree, 7 ins. diam., brs. N.51°00'E.,54 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
		An oak tree, 8 ins. diam., brs. S.4°00'E.,44 lks. dist mkd. ½ S11 BT.
		Descend 534 ft. over general W. slope.
	61.30	Gulch, course NW.; asc. 169 ft. over NE. slope.
	79.76	The cor. of secs. 2, 3, 10 and 11.
		Land, mountainous.
	з.	Soil, rocky; 3rd rate. Timber, pine, juniper and oak. Undergrowth, mountain mahogany, locust, willow and oak.
	r	
		3) - 2
		N. 0°03'W., on a random line, bet. secs. 2 and 3.
	40,00	Set temp. 4 sec. cor.
	74•90	Intersect N. bdy. of the Tp., 16 lks. E. of the cor. of secs. 2 and 3, hereinbefore described.
		Thence
		S. 0°10'E., on a true line, bet. secs. 2 and 3.
		Over SE. slope, through scattering timber and undergrowth desc. 213 ft.
	27.30	Small gulch, course NE.
	29.15	Gulch, 1 chain wide. course NE.
	34.65	Road, brs. NE. and SW.
	34.90	
	74•90	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 1½ ft. high, for ½ sec. cor. of secs. 2 and 3, with brass cap marked
		27 GO
		s3 s2
		1933 from which
		An oak tree, 30 ins. diam., brs. N.44°45'W.,35 lks. dist. mkd. ½ S3 BT.
		A pine tree, 12 ins. diam., brs. S.42°15'E.,70 lks. dist., mkd. \(\frac{1}{4}\) S2 BT.
	36.20	Gulch, 50 lks. wide, course NE.
	51.00	Same gulch, course NW.; asc. 353 ft. over NE. slope.
	74•90	The cor. of secs. 2, 3, 10 and 11.
	V	Land, rolling and level.
_		

BOOK 4025

	Chains	Soil, S. 2, rocky; 3rd rate; N. 2 gravelly loam; 2nd rate. Timber, pine, oak, and juniper. Undergrowth, oak, willow and buckbrush.
	ι	
	* .	
		From the cor. of secs. 14, 15, 22 and 23, hereinbefore described.
		West, on true line, bet. secs. 15 and 22.
		Over W. slope, through scattering timber and heavy undergrowth, desc. 200 ft.
	12.30	Gulch, course SW.
	25•50	Ascend 160 ft. over SE. slope.
	39.86	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 2 ft. high, for ½ sec. cor. of secs. 15 and 22, with brass cap marked
	• • • • • • • • • • • • • • • • • • •	$\frac{1}{4} \frac{\text{S 15}}{\text{S 22}}$
	•	1933
		from which
-		A juniper tree, 12 ins. diam., brs. N.36°00'W.,119 lks. dist., mkd. 4 S.15 BT.
-		A juniper tree, 6 ins. diam., brs. S.47°00'W.,71 lks. dist., mkd. 4 S22 BT.
		This cor. is situated on small spur, sloping S.
	42.00	Descend 243 ft. over SW. slope.
	50.80	Ravine, course S.15°W.; asc. slightly.
	55.10	Low spur, slopes S.
	58.40	Ravine, course S.10°E.; asc. 124 ft.
-	65.00	Spur, slopes SE.; desc. 206 ft.
	70.00	Ravine, course S.30°E.; asc. 106 ft. over E. slope.
	79•72	The cor. of secs. 15 and 22, hereinbefore described.
		Land, mountainous. Soil, rocky; 4th rate. Timber, oak and juniper. Undergrowth, buckbrush and oak.
		From the cor. of secs. 16 and 21, hereinbefore described.
		N. 0°02'W., bet. secs. 15 and 16.
		Over S. slope, through scattering timber and brush, asc. 136 ft.
	4.70	Crest of spur, slopes SW.; wire fence, brs. NE. and SW.; desc. 160 ft. over NW. slope.
-	32.00	Ravine, course N.75°W.
	39.29	A point 40 chs. N. in latitude, from the cor. of secs.

BOOK 4025

SUBDIVISION OF A PORTION OF T. 8 S., R. 22E

15 and 22, hereinbefore described, Chains. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for 4 sec. cor. of secs. 15 and 16, with brass cap marked s16 s15 from which VA juniper tree, 9 ins. diam., brs. N.16°45'E.,27 lks. dist., mkd. 4 S15 BT. An oak tree, 10 ins. diam., brs. N.44 00 W., 94 lks. dist. mkd. \$\frac{1}{4}\$ S16 BT. Desc. 103 ft. over NW. slope. Gulch, course S.30°W.; asc. 597 ft. over SE. slope. 42.40 A point 80 chs. N. in latitude, from the cor. of secs. 15 79.29 and 22, hereinbefore described. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 42 ft. base, 2 ft. high, for cor. of secs. 9, 10, 15 and 16, with brass cap marked T8S R22E S9 | S10 s16 s15 1933 from which An oak tree, 10 ins. diam., brs. N.58°00'E., 81 lks. dist. mkd. T8S R22E S10 BT. An oak tree, 8 ins. diam., brs. S.59°45'E..62 lks. dist., mkd. T8S R22E S15 BT. An oak tree, 10 ins. diam., brs. S.13°45'W.,32 lks. dist. mkd. T8S R22E,S16 BT. An oak tree, 10 ins. diam., brs. N.51°15'W.,50 lks. dist. mkd. T8S R22E S9 BT. Land, mountainous. Soil, rocky; 3rd rate. Timber, Juniper and oak. Undergrowth, buckbrush and oak. East, on a random line, bet. secs. 10 and 15. 40.00 Set temp. 4 sec. cor. Intersect N. and S. line, 5 lks. S. of the cor. of secs. 79.72 10, 11, 14 and 15. Thence

14.40 Gulch, course N.30°W.; asc. 437 ft. over E. slope.

desc. 490 ft.

S.89°58'W., on true line, bet. secs. 10 and 15.

Over W. slope, through scattering timber and undergrowth.

BOOK 4025

Chains 28.40	Ridge, brs. N.15°W. and S.15°E.; desc. 220 ft. over broken W. slope.
39.86	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 10 and 15, with brass cap marked
	<u> </u>
4.	S 10 S 15 1933
-	from which
	An oak tree, 14 ins. diam., brs. S. 9°00'W.,4 lks. dist., mkd. 4 S15 BT.
	(An oak tree, 12 ins. diam., brs. N.53°00'E.,109 lks. dist., mkd. & S10 BT.
	Descend 488 ft. over NW. slope.
70.00	Gulch, course SW.; asc. 170 ft. over broken E. slope.
75.00	Ravine, course SE.
79•72	The cor. of secs. 9, 10, 15 and 16.
	Land, mountainous. Soil, rocky; 4th rate. Timber, juniper and oak. Undergrowth, oak and manzanita.
• • • •	
1	N. 0°02'W., bet. secs. 9 and 10.
	Over NE. slope, through scattering timber and brush, desc. 58 ft.
3.60	Ravine, course SE.; asc. 654 ft. over SE. slope.
25.50	Crest of hill, brs. NE. and SW.; desc. 30 ft. over NW. slope.
29.90	Crest of same hill, brs. NW. and SE.; desc. 76 ft. over NE. slope.
3 5•90	Head of ravine, course NE.; asc. 35 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, for $\frac{1}{4}$ sec. cor. of secs. 9 and 10, with brass cap marked
	s9 s10
	1933 from which
	An oak tree, 14 ins. diam., brs. N.27°00'W., 27 lks. dist., mkd. 4 S9 BT.
	<pre>/An oak tree, 10 ins. diam., brs. S.7000'E.,30 lks. dist., mkd. 4 \$10 BT.</pre>
	Ascend 44 ft.
43.10	Spur, slopes NE.; desc. 375 ft. over NW. slope.

BOOX 4025

	Chains 74.50	Ravine, course W.; asc. 125 ft. over SW. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked
		T8S R22E S4 S3 S9 S10
		1933 from which
	•	An oak tree, 10 ins. diam., brs. N.70°E.,8 lks. dist., mkd. T8S R22E S3 BT.
		An oak tree, 9 ins. diam., brs. S.70°00'E.,97 lks. dist., mkd. T8S R22E S10 BT.
		An oak tree, 9 ins. diam., brs. S.41°45'W.,41 lks. dist., mkd. T8S R22E S9 BT.
	***	A juniper tree, 10 ins. diam., brs. N.83°30'W.,180 lks. dist., mkd. T8S R22E S4 BT.
		Land, mountainous. Soil, rocky; 4th rate. Timber, oak and juniper. Undergrowth, manzanita and oak.
	,	
		N.89°58'E., on a random line, bet. secs. 3 and 10.
	40.00	Set temp. 4 sec. cor.
	79.68	Intersect N. and S. line, 7 lks. S. of the cor. of secs. 2, 3, 10 and 11.
		Thence
		S.89°55'W., on true line, bet. secs. 3 and 10.
		Over NE. slope, through scattering timber and brush, asc. 81 ft.
	4.60	Spur, slopes N.; desc. 36 ft.
	10.10	Ravine, course N.; asc. 38 ft.
	13.70	Descend 289 ft. over W. slope.
	28.00	Gulch, course N.; asc. 1065 ft. over E. slope.
	39.84	Set an iron post, 3 ft. long, 1 in. diam., over a cross, +, chiseled on surface of rock ledge, in a mound of stone, b ft. base, 3 ft. high, for 4 sec. cor. of secs. 3 and 10. with brass cap marked
		\$ 3 \$10
		1933 from which
-		An oak tree, 12 ins. diam., brs. N.39°00'W.,61 lks. dist., mkd. 4 S3 BT.
		An oak tree, 7 ins. diam., brs. S.4°00'E.,102 lks. dist., mkd. ½ S10 BT.
	48.10	Wire fence, brs. N. and S.

SUBDIVISION OF A PORTION OF T. 8 S., R. 22 E.

ECCK 4025

		ECON Source
	Chains 48.70	Ravine, course SE.
i	69.00	S. slope of hill; desc. 245 ft. over SW. slope.
	79.68	The cor. of secs. 3, 4, 9 and 10.
		Land, mountainous. Soil, rocky; 3rd and 4th rate. Timber, juniper and oak. Undergrowth, manzanita and oak.
		N. 0°10'W., on a random line, bet. secs. 3 and 4.
	40.00	Set temp. 4 sec. cor.
	75•07	Intersect N. bdy. of Tp., 24 1ks. E. of the cor. of secs. 3 and 4, hereinbefore described.
		Thence
		S. 0°21'E., on true line, bet. secs. 3 and 4.
		Over NE. slope, through scattering timber and brush, asc. 117 ft.
	8.10	Spur, slopes NW.; desc. 85 ft.
	13.80	Gulch, course NW.; asc. 372 ft. over NE. slope.
	23.90	Rocky spur, slopes NW.; thence over N. slope, asc. 159 ft.
	35•07	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for \(\frac{1}{4} \) sec. cor. of secs. 3 and 4, with brass cap marked
-		✓ S4 S3
		1933
		from which
		An oak tree, 10 ins. diam., brs. S.43°30'E., 20 lks. dist., mkd. 4 S3 BT.
		(An oak tree, 16 ins. diam., brs. S.88°00'W., 84 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
		Ascend 644 ft. over NW. slope.
	72.60	West slope of hill; desc. 40 ft. over SW. slope.
	75.07	The cor. of secs. 3, 4, 9 and 10.
		Land, mountainous. Soil, rocky; 3rd and 4th rate. Timber, juniper and oak. Undergrowth, oak and manzanita.
	1	
		From the cor. of secs. 9, 10, 15 and 16, hereinbefore described.
		West, on true line, bet. secs. 9 and 16.
		Over E. slope, through scattering timber and brush, asc.

II. S. SOVERNMENT PRINTING OFFICE: 1921 6-815

4–673 в 58

 A	
Chains	514 ft.
17.10	Spur, slopes S.; desc. 767 ft. over W. slope.
 36.20	Draw, drains SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of secs. 9 and 16, with brass cap marked
	s 9 s16 1934 from which
	An oak tree, 16 ins. diam., brs. N.30°00'E.,67 lks. dist., mkd. 4 S9 BT.
	(An oak tree, 14 ins. diam., brs., S.43°15'W.,32 lks. dist., mkd. 4 S16 BT.
	Ascend 20 ft.
43.00	Small spur, slopes S.; desc. 426 ft. over SW. slope.
56.60	Ravine, course S. 30°E.
59.80	Small spur, slopes S.15°E.
70.00	Gulch, course S.15°E.; asc. 134 ft.
76.70	Spur, slopes S.; desc. over W. slope, 71 ft.
79•48	Intersect E. bdy. of sec. 17, 1.29 chs. dist., S. 0°04'W. from the cor. of secs. 8 and 17, hereinbefore described. At point of intersection,
•	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 5 ft. base, 2½ ft. high, for closing cor. of secs. 9 and 16, with brass cap marked
	T8S, R22E
	\$17\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	Land, mountainous. Soil, rocky; 4th rate. Timber, juniper and oak. Undergrowth, oak brush.
. V	
	From the cor. of secs. 3, 4, 9 and 10, hereinbefore described.
	West, on true line, bet. secs. 4 and 9.
	Over general W. slope, through scattering timber and brush, desc. 631 ft.
27.95	Gulch, course N.; asc. 152 ft. over NE. slope.
40.00	True point for a sec. cor. falls on sloping ledge, where the cor. monument would be insecure. At a point 10 lks. E. of true point,
	Set an iron post, 3 ft. long, 1 in. diam., over a cross +, chiseled on surface of a rock ledge, in a mound of

300K 4025

	300K 402
Chains	stone, 5 ft. base, 3 ft. high, for witness 4 sec. cor. of secs. 4 and 9, with brass cap marked
·	<u>1</u> <u>S 4</u>
	\$ 4 \$ 9 1933
	1933 from which
	An oak tree, 6 ins. diam., brs. N.11°45'W.,41 lks. dist., mkd. WC 4 S4 BT.
	A juniper tree, 8 ins. diam., brs. S.54°45'E.,85 lks. dist., mkd. WC 4 S9 BT.
	Ascend 42 ft.
44•50	Spur, slopes N.; desc. 389 ft. over broken NW. slope.
 53.10	Spur, slopes NW.
73.60	Draw, drains NW.; asc. 16 ft.
77.80	Spur, slopes N.60°W.; desc. 53 ft. over SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, with a stone mkd. with a cross +. deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for cor. of secs. 4 and 5 only, with brass cap marked
	T8S R22E
	<u>\$5 \$4</u>
	\$9 1933
	Thence, with continued measurement, bet. secs. 5 and 9.
80.73	Intersect E. bdy. of sec. 8, 1 ch. dist., S. 2°23'E., from the cor. of sec. 8, hereinbefore described. At point of intersection,
	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, 2 ft. high, for closing cor. of secs. 5 and 9, with brass cap marked
	T8s R22E
	1933
	from.which
·	An oak tree, 16 ins. diam., brs. S.59°15!E.,35 lks. dist. mkd. T8S R22E S9 CC BT.
	Land, mountainous.
	Soil, rocky; 4th rate. Timber, oak, juniper and pinyon.
	Undergrowth, oak, locust and cactus.
·	
	From the cor. of secs. 4 and 5, hereinbefore described.
	N. 0°21'W., on a random line, bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
·	
75•21	Intersect N. bdy. of Tp., 15 lks. W. of the cor. of secs. 4 and 5, hereinbefore described.

Thence

BOOX 4025

		•
Ch	ains	S. 0°14'E., on true line, bet. secs. 4 and 5.
		Over broken N. slope, asc. 276 ft.
21	•00	East slope of hill, bearing E. and W.; desc. 136 ft. over S. slope.
26	•40	Gulch, course SW.; asc. 187 ft. over NW. slope.
33	•74	At this point which is E. by calculation, from the $\frac{1}{4}$ sec. cor. on W. bdy. of sec. 5, hereinafter described,
		Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, with a stone mkd. with a cross +, deposited at base, in a mound of stone, 4 ft. base, 2 ft. high, for \(\frac{1}{4} \) sec. cor. of sec. 5 only, with brass cap marked
		\$5
		1933
34	.10	Wire fence, brs. E. and W.
35	.21	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for a sec. cor. of sec. 4 only, with brass cap marked
		V S4
		·
		1933 raise a mound
		of stone, 3 ft. base, $l_2^{\frac{1}{2}}$ ft. high, E. of cor.
38	• 70	Ravine, course NW.
47	•30	Spur, slopes W.; desc. 72 ft.
53	.00	Ravine, coursé SW.
54	.60	Spur, slopes SW.
58	.00	Ravine, course NW.; asc. 243 ft. over N. slope.
74	•00	Spur, slopes NW.; desc. 20 ft.
75	.21	The cor. of secs. 4 and 5.
	• • •	Land, rolling. Soil, gravelly; 3rd rate. Timber, scattering oak and juniper. Undergrowth, oak and manzanita.
		From the sen of sees E and h haroinhafers described
		From the cor. of secs. 5 and 6, hereinbefore described.
		N. 0°14'W., on a random line, bet. secs. 5 and 6.
	•00	Set temp. 4 sec. cor.
74	.•50	Intersect N. bdy. of Tp., 4 lks. E. of the cor. of secs. 5 and 6, hereinbefore described.
		Thence
		S. 0°16'E., on true line, bet. secs. 5 and 6.

4-67810

BOOK 400°

	BOO 3 3 3		
Chains	Over SE. slope, through scattering timber and brush, descipling timber and		
4.30	Bend in gulch, from SE. to N.30°E.; asc. 100 ft.		
16.50	Spur, slopes E.; desc. slightly over SE. slope.		
23.50	Thence over NE. slope, asc. 141 ft.		
34•50	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, for \(\frac{1}{4} \) sec. cor. of sec. 5 only, with brass cap marked		
. •	\$5		
	S5		
	1933		
	from which		
	(A juniper tree, 7 ins. diam., brs. S.70°15'E.,26 lks. dist., mkd. ½ S5 BT.		
	A juniper tree, 14 ins. diam., brs. N.89°45'E.,416 lks. dist., mkd. 4 S5 BT.		
	Ascend 33 ft.		
38.10	Spur, slopes NW.; desc. 71 ft. over S. slope.		
40.00	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft high, for \(\frac{1}{4}\) sec. cor. of sec. 6 only, with brass cap marked		
	4		
	* s6		
	1933 from which		
	A juniper tree, 4 ins. diam., brs. S.5°15'W.,343 lks. dist., mkd. 4 S6 BT.		
	An oak tree, 5 ins. diam., brs. S.35°45'W.,354 lks. dist. mkd. 4 S6 BT.		
50.60	Gulch, course N.70°W.; asc. 144 ft. over N. slope.		
59.20	Ridge, brs. E. and W.; desc. 198 ft. over S. slope.		
74•50	The cor. of secs. 5 and 6.		
	Land, mountainous. Soil, gravelly; 3rd rate. Timber, scattering oak and juniper. Undergrowth, oak and manzanita.		
	FINAL TEST OF INSTRUMENT		
	For final test of instrument, see preliminary test		

For final test of instrument, see preliminary test of instrument, in connection with the lines of T.4 S., R. 28 E., surveyed and resurveyed under this group.

BOCK. 4025

GENERAL DESCRIPTION

This portion of township is situated on the west slope of the Graham Mountains, about fifteen miles in a south-westerly direction from Pima, Arizona. It may be reached by a good road, which leads from Pima into section 2.

by a good road, which leads from Pima into section 2. The land which is quite rough, breaks rapidly from the highest points in sections 12 and 13, to the west, north-west, and south-west.

Yellow pine, white pine, Douglas fir, spruce and mountain laurel grow in the higher sections bordering on the east boundary, while pinyon, juniper, oak and hackberry are found over the lower portions of the township. The undergrowth is oak, buckbrush, manzanita, mountain mahogany and cactus. There is a fair stand of native grass over the lower portion of the township.

Stockraising is the only industry being carried on in the township at the present time. The only settler is Willis Hickman, who is engaged in stockraising in section 6. There is considerable evidence over the township of prospecting for mineral in former years. In sections 12 and 13, a number of old sawmill sites indicate former lumber operations.

of instrument, in goomechion with

S. GOVERNMENT PRINTING OFFICE: 1931 6-8155

BOOK 4025

4--680 (August, 1926)

FIELD ASSISTANTS.

NAMES.	, CAPACITY.
J. P. Hester	lst Chainman
Howard W. Blout	2nd Chainman
Albert Heath	Flagman
Ed Winsor	Cornerman
Seth S. Vestal	Axeman
,	
,	
· · · · · · · · · · · · · · · · · · ·	
•	

CERTIFICATE OF UNITED STATES SURVEYOR

I, Charles E. Hunter, U.S. Transitman, hereby certify upon honor that, in pursuance
of special instructions received from the District Cadastral Engineer for Arizona
bearing date of the 20th day of February , 19.33, I have well, faithfully, and truly
in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-
tions, and the laws of the United States, resurveyed a portion, and surveyed a por-
tion of the south boundary of Township 7 South, Range 22 East; resur-
veyed a portion of the west boundary, a portion of the south boundary.
and a portion of the subdivisional lines; surveyed the east boundary
and a portion of the subdivisional lines, completing the subdivision
of Township 8 South, Range 22 East, of the Gila and
Salt River Meridian, in the State of Arizona, which are represented in
the foregoing field notes as having been executed by me, and under my direction; and that all the corners of and resurvey said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-
tions, and the special written instructions of the District Cadastral Engineer forAri-zona
and in the specific manner described in the field notes, and that the foregoing are the original field notes of
such survey and resurvey.
Glendale, California, August, 29, 1934. Charles E. Hunter U. S. Transitman
APPROVAL
Office of U. S. Supervisor of Surveys.
,
Denver, Colorado, February 4, 1935.
The foregoing field notes of the survey of dependent resurvey of a portion, and
survey of a portion of the south boundary of Township 7 South, Range
22 East: dependent resurvey of a portion of the west boundary, a por-
tion of the south boundary and a portion of the subdivisional lines;
survey of the east boundary and a portion of the subdivisional lines,
completing the subdivision of Township 8 South, Range 22 East, of the
Gila and Salt River Meridian in the State of Arizona,
executed by Charles E. Hunter, U. S. Transitman,
under his special instructions dated February 20 , 19 33, having been
critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys and resurveys they describe, are hereby approved.
MANTE Dringon
-I certify that the foregoing transcript of the field notes of the above-described surveys in
has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Survens.

S. GOVERNMENT PRINTING OFFICE: 1927 6-2764