

Book "D"

4-679

BOOK 4041

FIELD NOTES

OF THE RESURVEY OF

South Boundary of

Township 39 North, Range 1 West

AND OF THE SURVEY OF

the West Boundary

and

Subdivision Lines of

Township 38 North, Range 1 West

Of the Gila and Salt River Base and Meridian,

In the State of Arizona

EXECUTED BY

John L. Warboys, U. S. Cadastral Engineer

Ben D. Procter, U. S. Transitman

J. P. Hester, U. S. Transitman

In the capacity of U. S. Surveyors, under Special Instructions dated May 1, 1931, issued by the District Cadastral Engineer to govern surveys included in Group No. 168 Arizona, which were approved by the Commissioner of the General Land Office, May 25, 1931, and Assignment Instructions dated June 20, 1934

Resurvey and Survey commenced August 5, 1934

Resurvey and Survey completed August 27, 1934

4041

4041

INDEX DIAGRAM.

Township _____, Range _____

6	5	4	3	2	1
7	8	9	10	11	12
13	17	16	15	14	13
19	20	21	22	23	24
29	29	26	27	26	25
31	32	33	34	35	36

INDEX-DIAGRAM

BOOK 4041

T.39N.-R.1W.

	31		32		33		34		35		36		
	18	17	16	15	15	14	14	13	12	11	11	10	
8		74						40		30			
	6		5	60	4	50	3		2		1		
7		75						41		29			
	73	74	73		59	50	49		40	39	29	28	
7		72				49		39					
	7		8	58	9		10		11	27	12		
6		71				48		38					
	71		70		57		48		38	37	27	26	MERIDIAN
5								37					
	18	69	17	56	16	47	15		14	25	13		
	68		67		T.38N.-R.1W.		46	36	36	35	25	24	RIVER
4				55				35					
	19	66	20		21	45	22		23	23	24		
				54				34					
	65	66	65	64	54	45	44		34	33	22		
3								33					
	30	64	29	53	28	43	27		26	21	25		
		63						32					
	62	63	62		52	43	42		32	31	20		GILA &
2								31					
	31	61	32	51	33	41	34		35	19	36		
								30					

Accepted surveys.

Unsurveyed.

Surveyed under this group.

Resurveyed under this group.

Areas surveyed as per accepted plats on file.

The surveys herein described were executed by John L. Warboys, U.S. Cadastral Engineer, and B.D. Procter, and J.P. Hester, U.S. Transitmen, using Young & Sons transits No's. 8478, 8592, and 8477 respectively. The instruments are equipped with Smith solar attachments and otherwise conform to standard requirements of the General Land Office. The instruments were examined and tested by the Cadastral Engineer of Arizona & California prior to the field work, and found satisfactory subject to field tests.

PRELIMINARY FIELD TESTS

Y. & S. transits Nos. 8478, 8592,
8477 by John L. Warboys, U.S.C.E.,
B.D. Procter & J.P. Hester, U.S.T's.

August 5, 1934; at stations in camp, about 10 chs. northerly from cor. of secs. 19, 24, 25, and 30, T. 37 N., Rs. 1 E. and 1 W., G. & S.R. Meridian, Arizona, in latitude $36^{\circ}35' N.$, longitude $112^{\circ}21'23'' W.$, as determined from data accompanying special instructions, examine the adjustments of the transits and find no appreciable error; then to test the indications of the solar apparatus by comparison with the true meridian as determined at this station on July 10th and 11th, 1934 as described in Book "A" of this Group.

August 5, 1934, at 9h 00m, a.m., app. t., we, the above named engineers, at our respective stations, set off $36^{\circ}38\frac{1}{2}' N.$ on the lat. arcs, $17^{\circ}03' N.$ on the decl. arcs, and determine meridians with the solar attachments which agree with the true meridian.

At 12h 00m, app. noon, with lat. arcs unchanged, observe the sun on the meridian; the resultant readings of the decl. arcs are $17^{\circ}01' N.$, which agrees with the computed declination of the sun.

At 3h 00m, p.m., app. t., with lat. arcs unchanged, set off $16^{\circ}59' N.$ on the decl. arcs and determine meridians with the solars which agree with the true meridians.

As all of the observations taken during the usual hours of solar work agree within $1'30''$ of the true meridian, conclude that the instruments are in a satisfactory state of adjustment.

Unless otherwise specified, all azimuth determinations are accomplished with the solar attachments, except the special observation upon Polaris for a meridian upon which to test the solar apparatus.

The measurements, unless otherwise specified, are made with Lallie 5-chain steel tapes, compared with a Lufkin standard and found correct. The measurements are made on the slope, the vertical angle determined and the slope measurements properly reduced to horizontal equivalents for entry in the field tablets.

Survey of West Boundary of T. 38 N., R. 1 W.

chains

Beginning at the cor. of Tps. 37 and 38 N., Rs. 1 and 2 W., described in Book "C" of this group. North, on a random line, setting temp. $\frac{1}{4}$ sec. and sec. cors. alternately at intervals of 40 chs., and at 479.14 chs. intersect E. and W. Tp. line 79 lks. W. of the cor. of Tps. 38 and 39 N., Rs. 1 and 2 W., which is an iron post, 3 ins. diam., projecting 12 ins. above the ground, firmly set, mkd. and witnessed as described in the official records.

Return to the cor. of Tps. 37 and 38 N., Rs. 1 and 2 W.

Thence

N.0°06'E., bet. secs. 31 and 36.

Over rolling land, through a scattering growth pinon and juniper timber and undergrowth.

- 4.00 Enter scattering timber, bears NW. and SE.
- 11.60 Low ridge, bears N.30°W. and S.30°E., desc. 59 ft. over NE. slope.
- 21.00 Leave scattering timber, bears NW. and SE.
- 26.80 Wash, 6 lks. wide, 5 ft. deep, course NW., continue over rolling land.
- 35.60 Road, bears N.30°W. to Slide Canyon and S.30°E. to Ryan, Ariz.
- 38.30 Draw, course W., continue over rolling land.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$
S36 | S31
1934
- from which
- A pinon, 5 ins. diam., bears N.52 $\frac{1}{2}$ °E., 149 lks. dist., mkd. $\frac{1}{4}$ S31 BT.
- A pinon, 5 ins. diam., bears N.9 $\frac{1}{2}$ °W., 147 lks. dist., mkd. $\frac{1}{4}$ S36 BT.
- 41.00 Enter scattering timber, bears NW. and SE.
- 45.00 Low spur, slopes W., desc. 10 ft. over N. slope.
- 49.00 Draw, course W., asc. 20 ft. over S. slope.
- 52.20 Spur, slopes W., desc. rolling N. slope.
- 54.00 Draw, course S.70°W., asc. 77 ft. over S. slope.
- 61.50 Ridge, bears N.70°W. and S.70°E., desc. 90 ft. over N. slope.
- 74.20 Wash, 20 lks. wide, course N.60°W., asc. 50 ft. over SW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 25, 30, 31, and 36, with brass cap mkd.

T38N
R2W R1W
S25 S30
S36 | S31
1934

Survey of West Boundary of T. 38 N., R. 1 W.

4041

chains

from which

A pinon, 10 ins. diam., bears N.40 $\frac{3}{4}$ °E., 369 lks.
dist., mkd. T38N R1W S30 BT.

A pinon, 5 ins. diam., bears S.36 $\frac{1}{4}$ °E., 165 lks.
dist., mkd. T38N R1W S31 BT.

A juniper, 5 ins. diam., bears S.33°W., 210 lks.
dist., mkd. T38N R2W S36 BT.

A pinon, 10 ins. diam., bears N.74 $\frac{1}{2}$ °W., 316 lks.
dist., mkd. T38N R2W S25 BT.

Land, rolling hills.

Soil, sandy and stony, clay loam, 2nd and 3rd rates.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

N.0°06'E., bet. secs. 25 and 30.

Over rolling land, through a scattering growth of pinon and juniper timber, and undergrowth.

Asc. 23 ft. over S. slope.

4.40 Low spur, slopes W., desc. 40 ft. over N. slope.

9.40 Ravine, 5 lks. wide, course W., asc. gentle S. slope.

12.70 Spur, slopes W., desc. 25 ft. over N. slope.

15.50 Ravine, 3 lks. wide, 2 ft. deep, course S.70°W., asc. 25 ft. over SW. slope.

23.80 Spur, slopes W., desc. 73 ft. over N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S25|S30

1934.

from which

A pinon, 5 ins. diam., bears S.50 $\frac{1}{2}$ °E., 268 lks.
dist., mkd. $\frac{1}{4}$ S30 BT.

A juniper, 8 ins. diam., bears N.84 $\frac{1}{4}$ °W., 400 lks.
dist., mkd. $\frac{1}{4}$ S25 BT.

Desc. 28 ft. over N. slope.

48.70 Wash, 6 lks. wide, 4 ft. deep, course NW., continue over rolling land.

55.10 Gulch, 15 lks. wide, course SW., continue over rolling land.

58.65 Road, bears S.60°W. and N.60°E.

75.70 Low ridge, bears NE. and SW., desc. gentle NW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.

T38N

R2W R1W

S24|S19

S25|S30

1934

from which

Survey of West Boundary of T. 38 N., R. 1 W.

chains

A juniper, 10 ins. diam., bears N. $64\frac{1}{4}^{\circ}$ E., 81 lks. dist., mkd. T38N R1W S19 BT.

A pinon, 10 ins. diam., bears S. 33° E., 32 lks. dist., mkd. T38N R1W S30 BT.

A juniper, 7 ins. diam., bears S. $85\frac{1}{2}^{\circ}$ W., 119 lks. dist., mkd. T38N R2W S25 BT.

A juniper, 11 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ W., 66 lks. dist., mkd. T38N R2W S24 BT.

Land, rolling:

Soil, sandy and gravelly, clay loam, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush, cliffrose, and service.

N. $0^{\circ}06'$ E., bet. secs. 19 and 24.

Over rolling land, through a scattering growth of pinon and juniper timber, and undergrowth.

Desc. 50 ft. over N. slope.

2.30 Road, bears NW. and SE.

21.90 Draw, course NW., asc. over gentle SW. slope.

32.30 Top of flat ridge, bears NW. and SE., continue over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S24 | S19

1934

from which

A pinon, 6 ins. diam., bears N. $51\frac{1}{4}^{\circ}$ E., 40 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

A juniper, 12 ins. diam.; bears S. 89° W., 142 lks. dist. mkd. $\frac{1}{4}$ S24 BT.

Desc: 55 ft. over NE. slope.

52.30 Draw, course E., continue over rolling land.

59.10 Spur, slopes NE., desc. 50 ft. over N. slope.

63.50 Wash, 30 lks. wide, course S. 80° W., asc. 70 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top; for cor. of secs. 13, 18, 19, and 24, with brass cap mkd.

T38N

R2W R1W

S13 | S18

S24 | S19

1934

from which

A juniper, 8 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E., 96 lks. dist., mkd. T38N R1W S18 BT.

Survey of West Boundary of T. 38 N., R. 1 W.

404

chains

A juniper, 14 ins. diam., bears S.38 $\frac{1}{2}$ °E., 64 lks.
dist., mkd. T38N R1W S19 BT.

A pinon, 8 ins. diam., bears S.57 $\frac{1}{2}$ °W., 147 lks.
dist., mkd. T38N R2W S24 BT.

A pinon, 10 ins. diam., bears N.65°W., 190 lks.
dist., mkd. T38N R2W S13 BT.

Land, rolling.

Soil, gravelly and stony, clay loam, 3rd rate.

Timber; pinon and juniper.

N.0°06'E., bet. secs. 13 and 18.

Over rolling land, through a scattering growth of timber
and undergrowth.

Along E. slope.

- 1.50 Across head of draw, drains SE., continue over rolling
land.
- 4.20 Spur, slopes NE., desc. over gentle NW. slope.
- 12.40 Draw, course SE.; asc. over gentle SW. slope.
- 17.00 Spur, slopes N.30°W., desc. 50 ft. over N. slope.
- 30.80 Ravine, 8 lks. wide, course NW., asc. 25 ft. over SW. slope
- 33.15 Spur, slopes W., desc. 25 ft. over NW. slope.
- 34.60 Ravine, course S.60°W., asc. 25 ft. over SW. slope.
- 39.70 Ridge, bears NW. and SE.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in
the ground to bedrock, and in a mound of stone to top,
for $\frac{1}{4}$ sec. cor, with brass cap mkd.

$\frac{1}{4}$
 S13 | S18
 1934

from which

A juniper, 8 ins. diam.; bears S.35°E., 34 lks.
dist., mkd. $\frac{1}{4}$ S18 BT.

A juniper, 6 ins. diam., bears S.85 $\frac{3}{4}$ °W., 128 lks.
dist., mkd. $\frac{1}{4}$ S13 BT.

Desc. 90 ft. over gradual NE. slope.

- 62.50 S. rim of canyon, bears NW. and SE., desc. 300 ft. over
broken NE. slope.
- 72.80 Wash in bottom of canyon, 30 lks. wide, course N.60°W.,
asc. 46 ft. over SW. slope.
- 80.00 Set an iron post 3 ft. long, .2 ins diam., 6 ins in the
ground to bedrock, and in a mound of stone to top, for
cor. of secs. 7, 12, 13, and 18, with brass cap mkd.

Survey of West Boundary of T. 38 N., R. 1 W.

chains	
	<p style="text-align: center;">T38N R2W R1W S12 S7 S13 S18 1934</p> <p style="text-align: right;">from which</p> <p>A pinon, 18 ins. diam., bears N.31°E., 397 lks. dist., mkd. T38N R1W S7 BT.</p> <p>A pinon, 12 ins. diam., bears S.64°E., 265 lks. dist., mkd. T38N R1W S18 BT.</p> <p>A juniper, 20 ins. diam., bears N.76$\frac{3}{4}$°W., 535 lks. dist., mkd. T38N R2W S12 BT.</p> <p>No other bearing tree available.</p> <p>Land, rolling and mountainous. Soil, gravelly and stony, clay loam, 3rd. and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.</p> <hr style="border-top: 1px dashed black;"/> <p>N.0°06'E., bet. secs. 7 and 12.</p> <p>Over mountainous land, through a scattering growth of timber and undergrowth.</p> <p>Asc. 147 ft. over SW. slope.</p> <p>7.20 N. rim of canyon, bears SE. and NW., desc. gentle NW. slope.</p> <p>10.40 Same rim, bears SW. and NE., desc. 178 ft. over steep broken NW. slope.</p> <p>14.85 Wash, course S.60°W., asc. 185 ft., over broken SE. slope.</p> <p>27.00 Ridge, bears E. and W., desc. 53 ft. over NW. slope.</p> <p>31.30 Ravine, course NE., asc. 20 ft. over S. slope.</p> <p>34.00 S. rim of Snake Canyon, bears N.70°W. and S.70°E., desc. 262 ft. over broken N. slope.</p> <p>40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S12 S7 1934</p> <p style="text-align: right;">from which</p> <p>A pinon, 7 ins. diam., bears N.89°E., 39 lks. dist., mkd. $\frac{1}{4}$ S7 BT.</p> <p>A pinon, 9 ins. diam., bears S.45$\frac{1}{2}$°W., 12 lks. dist., mkd. $\frac{1}{4}$ S12 BT.</p> <p>A pinon, 3 ins. diam.; bears N.59$\frac{1}{2}$°W., 132 lks. dist., mkd. BT.</p> <p>Desc. 310 ft. over broken NE. slope.</p> <p>49.00 Snake Canyon, wash in bottom, 8 lks. wide, 5 ft. deep, course NW., asc. 102 ft. over S. slope.</p>

Survey of West Boundary of T. 38 N., R. 1 W.

4041

chains	
50.70	Road, bears N.60°W. and S.60°E.
55.60	Spur, slopes SW., along broken W. slope.
60.20	Ravine, course SW., asc. 214 ft. over broken SW. slope.
69.00	N. rim of Snake Canyon, bears NW. and SE.
69.60	Ridge, bears E. and W., desc. 223 ft. over broken NE. slope.
78.20	Wash, 20 lks. wide, course W., asc. 60 ft. over rocky S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 3 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 1, 6, 7, and 12, with brass cap mkd.
	T38N R2W R1W S1 S6 S12 S7 1934
	from which
	A juniper, 8 ins. diam., bears S.36 $\frac{3}{4}$ °E., 220 lks. dist., mkd. T38N R1W S7 BT.
	A pinon, 10 ins. diam., bears S.36 $\frac{3}{4}$ °W., 211 lks. dist., mkd. T38N R2W S12 BT.
	No other bearing trees available.
	Land, mountainous. Soil, gravelly, and stony, clay loam, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°06'E., bet. secs. 1 and 6.
	Over mountainous land, through a scattering growth of timber and undergrowth.
	Asc. 124 ft. over broken SW. slope.
2.00	Spur, slopes SW., continue asc. 34 ft. along W. slope.
6.90	Across head of ravine, course SW., asc. 38 ft. over S. slope.
10.00	Leave scattering, enter heavy timber, bears E. and W.
12.20	N. rim of ravine, bears N.75°W. and S.75°E., continue gentle asc.
14.15	Ridge, bears E. and W., desc. gentle N. slope.
17.00	Ravine, 6 lks. wide, course W., asc. 24 ft. over S. slope.
26.65	Old road, bears E. and W.
30.00	Old road. bears NW. and SE.
30.50	Ridge, bears NW. and SE., leave mountainous; enter rolling land, desc. gentle N. slope.

Survey of West Boundary of T. 38 N., R. 1 W.

chains	
32.00	Draw, course NW.; continue over rolling land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$
	S1 S6
	1934
	from which
	A juniper, 12 ins. diam., bears S.10°E., 63 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
	A pinon, 10 ins. diam., bears N.69 $\frac{3}{4}$ °W., 135 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
	Asc. gentle S. slope.
44.30	Spur, slopes NW., desc. gentle NE. slope.
60.70	Draw, course NW., continue over rolling land.
62.50	Old road, bears NW. and SE.
79.14	The cor. of Tps. 38 and 39 N., Rs. 1 and 2 W., which is an iron post, 3 ins. diam., projecting 12 ins. above the ground, firmly set, mkd. and witnessed as described in the official record.

Land, mountainous and rolling.
 Soil, gravelly and stony, clay loam, 2nd and 3rd rates.
 Timber, pinon and juniper.
 Undergrowth, sagebrush and cliffrose.

Resurvey of South Boundary of T. 39 N., R. 1 W.

FORM 4041

chains

The S. bdy. of T. 39 N., R. 1 W., was surveyed in 1916, by Thomas B. Matthews, U.S.S., establishing common reference corners thereon at 40.00 ch. intervals, counting from the E. No retracement or resurvey of any part of this line is of record.

The following notes describe a resurvey of the entire line altering the reference of all cors. to areas N. of line only, with the exception of the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, which retains its original common reference. Westerly from the closing cor. of secs. 1 and 2, T. 38 N., R. 1 W., $\frac{1}{4}$ sec. and sec. cors. referring to areas S. of line only are established alternately at 40.00 ch. intervals.

Retracement for Resurvey

From cor. of Tps. 38 and 39 N., Rs. 1 E. and 1 W.

West, on random line, bet. secs. 1 and 36 (E. $\frac{1}{2}$)

40.03 A point 19 lks. N. of $\frac{1}{4}$ sec. cor. of secs. 1 and 36.

True course and dist.; S. 89°43'W., 40.03 chs.

Thence

West, on random line, on S. bdy. sec. 36 (W. $\frac{1}{2}$)

39.88 A point 34 lks. N. of cor. of secs. 1, 2, 35, and 36.

True course and dist.; S. 89°31'W., 39.88 chs.

West, on random line, on S. bdy. sec. 35 (E. $\frac{1}{2}$)

39.97 A point 1 lk. S. of $\frac{1}{4}$ sec. cor. of secs. 2 and 35.

True course and dist.; N. 89°59'W., 39.97 chs.

Thence

West, on random line, on S. bdy. sec. 35 (W. $\frac{1}{2}$)

39.94 A point 3 lks. N. of cor. of secs. 2, 3, 34, and 35.

True course and dist.; S. 89°57'W., 39.94 chs.

West, on random line, on S. bdy. sec. 34 (E. $\frac{1}{2}$)

39.99 Intersect $\frac{1}{4}$ sec. cor. of secs. 3 and 34.

True course and dist.: West, 39.99 chs.

Thence

West, on random line, on S. bdy. sec. 34 (W. $\frac{1}{2}$)

39.92 A point 2 lks. N. of cor. of secs. 3, 4, 33, and 34.

True course and dist.: S. 89°58'W., 39.92 chs.

Resurvey of South Boundary of T. 39 N., R. 1 W.

chains	West, on random line, on S. bdy. sec. 33. (E. $\frac{1}{2}$)
39.98	A point 2 lks. N. of $\frac{1}{4}$ sec. cor. of secs. 4 and 33. True course and dist.: S. $89^{\circ}58'W.$, 39.98 chs. Thence
	West, on random line, on S. bdy. sec. 33 (W. $\frac{1}{2}$)
39.99	A point 3 lks. N. of cor. of secs. 4, 5, 32, and 33. True course and dist.: S. $89^{\circ}57'W.$, 39.99 chs. -----
	West, on random line, on S. bdy. sec. 32 (E. $\frac{1}{2}$)
39.97	Intersect $\frac{1}{4}$ sec. cor. of secs. 5 and 32. True course and dist.: West, 39.97 chs. Thence
	West, on random line, on S. bdy. sec. 32 (W. $\frac{1}{2}$)
40.05	Intersect the cor. of secs. 5, 6, 31, and 32. True course and dist.: West, 40.05 chs. -----
	West, on random line, on S. bdy. sec. 31 (E. $\frac{1}{2}$)
39.96	A point 3 lks. S. of $\frac{1}{4}$ sec. cor. of secs. 6 and 31. True course and dist.: N. $89^{\circ}57'W.$, 39.96 chs. Thence
	West, on random line, on S. bdy. sec. 31 (W. $\frac{1}{2}$)
38.88	A point 2 lks. S. of cor. of Tps. 38 and 39 N., Rs. 1 and 2 W. True course and dist.: N. $89^{\circ}58'W.$, 38.88 chs. -----
	Resurvey -----
	From the cor. of Tps. 38 and 39 N., Rs. 1 E. and 1 W., which is an iron post, 3 ins. diam., projecting 12 ins. above the ground, firmly set, mkd. and witnessed as described in the official record.
	S. $89^{\circ}43'W.$, bet. secs. 1 and 36 (E. $\frac{1}{2}$)
	Over rolling land, through a heavy growth of timber and scattering undergrowth.
	Desc. 30 ft. over NW. slope.
0.95	Small draw, course NW., continue desc. over rolling land.
7.10	Draw, course NW., continue gentle desc.
14.20	Wash, 5 lks. wide, course SW., asc. 25 ft. over SE. slope

Resurvey of South Boundary of T. 39 N., R. 1 W.

BOOK 4042

chains	
30.00	Spur, slopes S.30°W., desc. 65 ft. over SW. slope.
40.03	The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, which is an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record.
	Thence
	S.89°31'W., on S. bdy. sec. 36 (W. $\frac{1}{2}$)
5.40	Wash, course N., asc. 40 ft. over E. slope.
5.80	Road, bears N. and S.
12.00	Spur, slopes N., desc 55 ft. over NW. slope.
19.40	Draw, course N.15°E., asc. 45 ft. over E. slope.
26.50	Spur, slopes N., road on top bears NW. and SE., desc. 80 ft. over W. slope.
38.50	Draw, course N.70°W., continue over rolling land.
39.88	The cor. of secs. 1, 2, 35, and 36, which is an iron post, 2 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record., alter this cor. monument to refer to secs. 35 and 36 only, by changing marking on brass cap to read.
	T39N RLW S35 S36 S1 T38N 1916-34
	Obliterate marking on SE. and SW. bearing trees.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush.

	N.89°59'W., on S. bdy. sec. 35 (E. $\frac{1}{2}$)
	Over rolling land, through a scattering growth of timber and undergrowth.
0.46	Intersect sub. line bet. sec. 1 and 2, closing cor. of said secs. established at this point as hereinafter described.
5.16	U.S.P.S. 4 wire fence, bears N.20°E. and S.20°W.
7.40	Draw, course S.30°W., asc. gentle SE. slope.
10.80	Old road, bears NE. and SW.
15.00	Short spur, slopes S., desc. 50 ft. over SW. slope.
25.00	Draw, course N.30°W., continue over rolling land.
25.50	Old road, bears NW. and SE.
39.70	Spur, slopes N.

Resurvey of South Boundary of T. 39 N., R. 1 W.

chains 39.97	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, which is an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to sec. 35 only, by changing marking on brass cap to read</p> <p style="text-align: center;">$\frac{1}{4}$ S35 1916-34</p> <p>Thence</p> <p>S.89°57'W., on S. bdy. sec. 35 (W.$\frac{1}{2}$)</p>
0.49	<p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 2 1934</p> <p style="text-align: right;">from which</p> <p>A juniper, 10 ins. diam., bears S.53$\frac{1}{2}$°E., 302 lks. dist., mkd. $\frac{1}{4}$ S 2 BT.</p> <p>A pinon, 10 ins. diam., bears S.18°W., 81 lks. dist., mkd. $\frac{1}{4}$ S 2 BT.</p> <p>U.S.G.S Triangulation Station "Ryan", bears S. 40°35'E. Desc. 70 ft. over SW. slope.</p>
9.50	Draw, course N., asc. 30 ft. over E. slope.
13.50	U.S.F.S. telephone line, bears N.30°W. and S.30°E.
21.00	Spur, slopes NW., desc. 20 ft. over SW. slope.
25.10	Draw, course N.30°W., asc. 25 ft. over NE. slope.
39.94	<p>The cor. of secs. 2, 3, 34, and 35, which is an iron post, 2 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. as described in the official record; alter this cor. monument to refer to secs. 34 and 35 only by changing marking on brass cap to read.</p> <p style="text-align: center;">T39N RLW S34 S35 S 2 T38N 1916-34</p> <p>Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush.</p>

Resurvey of South Boundary of T. 39 N., R. 1 W.

chains	
	West, on S. bdy. sec. 34. (E. $\frac{1}{2}$).
	Over rolling land, through a scattering growth of timber and undergrowth.
0.55	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 2 and 3 only, with brass cap mkd.
	T39N R1W <u>S34</u> S3 S2 T38N R1W 1916-34
	from which
	A pinon, 10 ins. diam., bears S.53°E., 263 lks. dist., mkd. T38N R1W S2 BT.
	A pinon, 8 ins. diam., bears S.39 $\frac{1}{2}$ °W., 152 lks. dist., mkd. T38N R1W S3 BT.
	Desc. 95 ft. along N. slope.
7.00	Low ridge, bears NW. and SE., gentle desc. along S. slope.
13.00	Short spur, slopes SW., gentle desc. over W. slope.
27.00	Old road, bears N.20°W. and S.20°E.
28.20	Draw, course NW., continue over rolling land.
36.00	Low spur, slopes N., desc. gentle NW. slope.
39.20	Draw, course N.15°W., asc gentle NE. slope.
39.99	The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, which is an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to sec. 34 only, by changing marking on brass cap to read.
	<u>$\frac{1}{4}$ S34</u> 1916-34
	Thence
	S.89°58'W., on S. bdy. sec. 34 (W. $\frac{1}{2}$)
0.56	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap mkd.
	<u>$\frac{1}{4}$ S 3</u> 1934
	from which
	A pinon, 10 ins. diam., bears S.49 $\frac{1}{4}$ °E., 268 lks. dist., mkd. $\frac{1}{4}$ S 3 BT.
	A pinon, 16 ins. diam., bears S.75 $\frac{3}{4}$ °W., 101 lks. dist., mkd. $\frac{1}{4}$ S 3 BT.
	Asc. gentle NE. slope.

Resurvey of South Boundary of T. 39 N., R. 1 W.

chains	
5.00	Spur, slopes NW., desc. 75 ft. over SW. slope.
9.00	Ravine, course NW., asc. 90 ft. over NE. slope.
18.70	Ridge, and old road along top, bears N.30°W. and S.30°E. desc. 110 ft. over rolling SW. slope.
39.00	Wash, course N.30°W., continue over rolling land.
39.92	The cor. of secs. 3, 4, 33, and 34, which is an iron post, 2 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. as described in the official record; alter this cor. monument to refer to secs. 33 and 34 only, by changing marking on brass cap to read. <div style="text-align: center;"> T39N RLW S33 S34 S 3 T38N 1916-34 </div>
	Land, rolling, Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.

	S.89°58'W., on S. bdy. sec. 33 (E. $\frac{1}{2}$) Over rolling land, through a scattering growth of timber and undergrowth. Asc. 60 ft. over NE. slope.
0.64	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 3 and 4 only, with brass cap mkd. <div style="text-align: center;"> T39N RLW S33 S4 S3 T38N RLW 1934 </div>
	from which
	A juniper, 12 ins. diam., bears S.21 $\frac{3}{4}$ °E., 405 lks. dist. mkd. T38N RLW S 3 BT.
	A pinon, 10 ins. diam., bears S.30 $\frac{1}{2}$ °W., 125 lks. dist., mkd. T38N RLW S 4 BT.
10.00	Ridge, bears NW. and SE., desc. 33 ft. over SW. slope.
20.50	Draw, course N.30°W., asc. gentle NE. slope.
29.00	Spur, slopes NW., desc. 45 ft. over SW. slope.
39.10	Draw, course N.30°W., asc. gentle NE. slope.
39.98	The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, which is an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to sec. 33 only, by changing marking on brass cap to read.

Resurvey of South Boundary of T. 39 N., R. 1 W.

chains

¼ S 33

1916-34

Thence

S. 89° 57' W., on S. bdy. sec. 33 (W. ½)

0.66 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor. of sec. 4 only, with brass cap mkd.

¼ S 4

1934

from which

A juniper, 8 ins. diam., bears S. 88½° E., 190 lks. dist., mkd. ¼ S 4 BT.

A juniper, 8 ins. diam., bears S. 60¾° W., 299 lks. dist., mkd. ¼ S 4 BT.

Asc. 20 ft. over gentle NE. slope.

7.00 Ridge, bears NW. and SE., desc. 33 ft. over SW. slope.

25.00 Swale, drains S. 30° W., asc. gentle SE. slope.

35.00 Spur, slopes S., desc. 28 ft. over SW. slope.

39.99 The cor. of secs. 4, 5, 32, and 33, which is an iron post, 2 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to secs. 32 and 33 only, by changing marking on brass cap to read.

T39N R1W

S32|S33

S 4

T38N

1916-34

Remove mound of stone W., and raise a mound of stone 3 ft. base, 3 ft. high, N. of cor.

Obliterate marking on SE. bearing tree.

Land, rolling.

Soil, gravelly and sandy loam, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush, cliffrose, and service.

West, on S. bdy. sec. 32 (E. ½)

Over rolling land, through a scattering growth of timber and undergrowth.

Desc. 30 ft. over SW. slope.

0.67 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock, with a lava stone 4x3x3 ins. mkd. with cross, deposited alongside, and in a mound of stone to top, for cor. of secs. 4 and 5 only, with brass cap mkd.

T39N R1W

S32

S5|S4

T38N R1W

1934

No suitable bearing trees available.

Resurvey of South Boundary of T. 39 N., R. 1 W.

chains	
3.70	Draw, course NW., asc. gentle NE. slope.
8.00	Low spur, slopes N., desc. 20 ft. over W. slope.
9.10	Old road, bears N.30°E. and S.30°W.
12.50	Draw, course NW., asc. gentle NE. slope.
14.80	Old road, bears NW. and SE.
19.00	Spur, slopes N., desc. gentle NW. slope.
24.50	Draw, course SW., asc. 40 ft. over SW. slope.
24.90	Old road, bears NW. and SE.
39.97	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, which is an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to sec. 32 only, by changing marking on brass cap to read. $\frac{1}{4}$ S32 1916-34
	Thence
	West. on S. bdy. sec. 32 (W. $\frac{1}{2}$)
0.70	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 5 only, with brass cap mkd. $\frac{1}{4}$ S5 1934 from which A pinon, 12 ins diam., bears S.2 $\frac{1}{4}$ °E., 240 lks. dist., mkd. $\frac{1}{4}$ S 5 BT. A juniper, 8 ins. diam., bears S.29 $\frac{1}{4}$ °W., 417 lks. dist., mkd. $\frac{1}{4}$ S 5 BT.
1.00	Flat spur; slopes; S.20°W.; desc. 124 ft. over gradual W. slope.
21.90	Old road, bears N. and S.
22.00	Draw, course N., asc. 90 ft. over E. slope.
37.50	Ridge, bears N.30°W. and S.30°E., desc. 15 ft. over SW. slope.
40.05	The cor. of secs. 5, 6, 31, and 32, which is an iron post, 2 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to secs. 31 and 32 only, by changing marking on brass cap to read. T39N R1W S31 S32 S 5 1916-34
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.

Resurvey of South Boundary of T. 39 N., R. 1 W.

6041

chains

N.89°57'W., on S. bdy. sec. 31 (E.½)

Over rolling land, through a scattering growth of timber and undergrowth.

Desc. gentle SW. slope.

0.65 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 5 and 6 only, with brass cap mkd.

T39N RLW

S31

S6TS5

T38N RLW

1934

from which

A pinon, 14 ins. diam., bears S.42½°E., 290 lks. dist., mkd. T38N RLW S 5 BT.

A juniper, 10 ins. diam., bears S.87°W., 132 lks. dist., mkd. T38N RLW S 6 BT.

1.80 Draw, course N.30°W., asc. 35 ft. over NE. slope.

14.00 Spur, slopes N.20°W., desc. 35 ft. over SW. slope.

22.20 Head of gulch, course N., asc. gentle NE, slope.

27.00 Spur, slopes N.30°W., desc. 65 ft. over SW. slope.

36.50 Wash, course N.60°W., asc. 45 ft. over NE. slope.

39.96 The ¼ sec. cor. of secs. 6 and 31, which is an iron post, 1 in. diam., projecting 10 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record; alter this cor. monument to refer to sec. 31 only, by changing marking on brass cap to read.

¼ S31

1916-34

Thence

N.89°58'W., on S. bdy. sec. 31 (W.½)

0.69 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, and in a mound of stone to top, for ¼ sec. cor. of sec. 6 only, with brass cap mkd.

¼ S6

1934

from which

A juniper, 10 ins. diam., bears S.48½°E., 24 lks. dist., mkd. ¼ S 6 BT.

A pinon, 10 ins. diam., bears S.10¾°W., 21 lks. dist., mkd. ¼ S 6 BT.

Asc. 40 ft. over NE. slope.

3.95 Spur, slopes N., desc. 75 ft. over gentle NW. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains

From the cor. of secs. 1, 2, 35, and 36, on S. bdy. of the Tp., described in Book "C" of this group.

N.0°01'W., bet. secs. 35 and 36.

Asc. 40 ft. over SW. slope, through a heavy growth of timber and dense undergrowth.

5.70 Short spur, slopes NW., desc. 20 ft. over NW. slope.

8.70 Draw, course S.30°W., asc. 45 ft. over SE. slope.

17.00 Ridge, bears NE. and SW., desc. 176 ft. over NE. slope.

32.80 Gulch, 10 lks. wide, course NE., asc. 31 ft. over SE. slope

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 35 and 36, with brass cap mkd.

$\frac{1}{4}$

S35 | S36

1934

from which

A pinon, 9 ins. diam., bears N.86 $\frac{3}{4}$ °E., 28 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

A pinon, 12 ins. diam., bears S.20 $\frac{1}{4}$ °W., 34 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

Asc. 23 ft. over SE. slope.

46.00 Spur, slopes E., desc. 215 ft. over NE. slope.

63.80 Gulch, 12 lks. wide, course N.30°W., asc. 177 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.

T38N RLW

S26, S25

S35 | S36

1934

from which

A pinon, 14 ins. diam., bears N.22°E., 24 lks. dist., mkd. T38N RLW S25 BT.

A pinon, 9 ins. diam., bears S.46 $\frac{1}{4}$ °E., 68 lks., dist., mkd. T38N RLW S36 BT.

A pinon, 8 ins. diam., bears S.69 $\frac{3}{4}$ °W., 74 lks. dist., mkd. T38N RLW S35 BT.

A pinon, 8 ins. diam., bears N.76 $\frac{3}{4}$ °W., 90 lks. dist., mkd. T38N RLW S26 BT.

Land, rolling mountainous.

Soil, gravelly and sandy clay loam, 3rd rate.

Timber, pinon, juniper, and yellow pine.

Undergrowth, oakbrush, cliffrose, service, and sagebrush.

SUBDIVISION of T. 38 N., R. 1 W.

chains	East, on a random line bet. secs. 25 and 36
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.14	Intersect E. bay. of Tp. (G. & SR. Mer.) 20 lks. N. of the cor. of secs. 25, 30, 31, and 36, which is an iron post, 3 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record.
	Thence
	N. $89^{\circ}51'W.$, on true line bet. secs. 25 and 36.
	Desc. 176 ft. over SW. slope through a dense growth of timber and scattering undergrowth.
12.54	U.S.F.S. 4 wire fence, bears N. $15^{\circ}W.$ and S. $15^{\circ}E.$
14.34	Road, bears N. $15^{\circ}W.$ and S. $15^{\circ}E.$
15.34	U.S.F.S. telephone line, bears N. $15^{\circ}W.$ and S. $15^{\circ}E.$
16.44	Nail Canyon, gulch, 12 lks. wide, 6 ft. deep, course N. $15^{\circ}W.$, asc. 600 ft. over broken E. slope, through scattering timber.
32.14	Top of W. rim of Nail Canyon; bears N. $15^{\circ}W.$ and S. $15^{\circ}E.$, continue gradual asc. over E. slope.
32.60	Leave scattering, enter heavy timber, bears N. and S.
33.65	Spur, slopes N. $15^{\circ}E.$, desc. 15 ft. over NW. slope.
40.07	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top; for $\frac{1}{4}$ sec. cor. of secs. 25 and 36, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S25 \\ \hline S36 \\ 1934 \end{array}$
	from which
	A pinon, 10 ins. diam., bears S. $63^{\circ}E.$, 43 lks. dist., mkd. $\frac{1}{4}$ S36 BT.
	A pinon, 12 ins. diam., bears N. $30\frac{1}{2}^{\circ}W.$, 59 lks. dist., mkd. $\frac{1}{4}$ S25 BT.
	Desc. 26 ft. over NW. slope.
43.14	Ravine, 6 lks. wide, course N. $20^{\circ}E.$, asc. 53 ft. over E. slope.
52.54	Low spur, slopes N., desc. 130 ft. over NW. slope.
55.27	Gulch, 10 lks. wide, course N. $10^{\circ}E.$, asc. 130 ft. over NE. slope.
62.10	Spur, slopes N., desc. 67 ft. over NW. slope.
67.24	Gulch, 10 lks. wide, course N. $10^{\circ}E.$, asc. 130 ft. over NE. slope.
78.14	Ridge, bears S. $30^{\circ}E.$ and N. $30^{\circ}W.$, desc. gentle SW. slope.
80.14	The cor. of secs. 25, 26, 35, and 36.
	Land, mountainous. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon, juniper, and yellow pine, Undergrowth, oakbrush, cliffrose, service, and sagebrush.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
	N.0°01'W., bet. secs. 25 and 26.
	Asc. 34 ft. over SW. slope, through a heavy growth of timber and dense undergrowth.
7.00	Ridge, bears NW. and SE., desc. 63 ft. over NE. slope.
20.50	Across head of draw, drains NE., asc. 43 ft. over SE. slope
33.50	Spur, slopes NE., desc. 50 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 25 and 26, with brass cap mkd.
	$\frac{1}{4}$ S26 S25 1934
	from which
	A pinon, 6 ins. diam., bears N.58°E., 118 lks. dist., mkd. $\frac{1}{4}$ S25 BT.
	A pinon, 6 ins. diam., bears S.61 $\frac{1}{2}$ °W., 28 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	Begin desc. 846 ft. over NE. slope.
44.80	Spur, slopes NE., desc. 800 ft. over steep, broken NW. slope.
75.50	Base of steep desc., bears E. and W., leave heavy, enter scattering timber, continue gradual desc. over N. slope.
77.50	Road, bears E. and W.
78.60	U.S.F.S. 4 wire fence, bears E. and W.
79.60	Nail Canyon, wash in bottom, 60 lks. wide, 10 ft. deep, course W.
80.00	The point for cor. of secs. 23, 24, 25, and 26, falls in edge of above wash, where it is impracticable to monument the cor., therefore W.C. is established N.0°01'W., 14 lks. dist., hereinafter described.
	Land, mountainous. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon, juniper, and yellow pine. Undergrowth, oakbrush, cliffrose, service, and sagebrush.

	From true point for cor. of secs. 23, 24, 25, and 26.
	S.89°51'E., on a random line bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.38	Intersect E. bdy. of Tp. (G. & SR. Mer.) 19 lks. N. of the cor. of secs. 19, 24, 25, and 30, which is an iron post, 3 ins. diam., firmly set in a mound of stone to top, with brass cap mkd. and witnessed as described in the official record.
	Thence

SUBDIVISION of T. 38 N., R. 1 W.

chains	
	N.89°43'W., on true line bet. secs. 24 and 25.
	Desc. 762 ft. over steep, broken SW. slope, through a heavy growth of timber and dense undergrowth.
22.50	Cliff, 75 ft. high, bears N. and S., continue desc. over broken W. slope.
26.00	Road, bears N. and S.
26.23	U.S.F.S. telephone line, bears N. and S.
27.38	Water supply pipe line, 4 ins. diam., bears N. to Ryan, Ariz. and S.
27.50	Oak Canyon, wash in bottom, 50 lks. wide, course S., asc. 252 ft. over SE. slope.
29.23	U.S.F.S. 4 wire fence, bears N. and S.
40.19	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 24 and 25, with brass cap mkd.
	$\begin{array}{r} S24 \\ \frac{1}{4} \\ S25 \\ 1934 \end{array}$
	from which
	A pinon, 12 ins. diam., bears S.42 $\frac{1}{2}$ °W., 20 lks. dist., mkd. $\frac{1}{4}$ S25 BT.
	A pinon, 12 ins. diam., bears N.4°W., 65 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	Asc. 44 ft. over SE. slope.
45.38	Spur, slopes S., desc. 90 ft. over steep, broken SW. slope
56.38	Ravine, course SW., desc. 237 ft. along SW. slope.
63.78	Top of rim rock, 100 ft. high, bears NW. and SE., desc. 120 ft. over broken SW. slope.
69.00	Leave heavy, enter scattering timber, bears NW. and SE.
69.88	U.S.F.S. 4 wire fence, and base of broken desc., bears NW. and SE., gradual desc.
71.38	Nail Canyon, wash in bottom, 40 lks. wide, 8 ft. deep, course N.15°W., desc. 15 ft. along left bank of canyon.
74.98	Same fence, bears N.75°E. and S.75°W.
77.88	Nail Canyon, wash in bottom, 40 lks. wide, 10 ft. deep, course S.80°W., desc. 17 ft. along right bank of canyon.
80.38	The true point for cor. of secs. 23, 24, 25, and 26.
	Land, rough mountainous.
	Soil, gravelly and sandy loam, 3rd rate.
	Timber, pinon and juniper.
	Undergrowth, oakbrush, cliffrose, and service.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	From the true point for cor. of secs. 23, 24, 25, and 26. N. 0° 01' W., bet. secs. 23 and 24.
0.14	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for witness cor. to cor. of secs. 23, 24, 25, and 26, with brass cap, mkd. <div style="text-align: center;"> T38N RLW S23 S24 S26 S25 WC 1934 </div> from which A juniper, 24 ins. diam., bears N. 31½° E., 235 lks. dist. mkd. WC T38N RLW S24. BT. A pinon, 12 ins. diam., bears S. 9¼° E., 418 lks. dist., mkd. WC T38N RLW S25 BT. A pinon, 12 ins. diam., bears S. 39° W., 320 lks. dist., mkd. WC T38N RLW S26 BT. A pinon, 10 ins. diam., bears N. 17½° W., 310 lks. dist., mkd. WC T38N RLW S23 BT. Begin asc. 435 ft. over steep S. slope, through a scattering growth of timber and undergrowth.
15.20	Top of rim of Nail Canyon, bears E. and W., desc. 165 ft. over gentle NE. slope.
35.40	Wash, 10 lks. wide, course NW., asc. 35 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor. of secs. 23 and 24, with brass cap mkd. <div style="text-align: center;"> ¼ S23 S24 1934 </div> from which A pinon, 5 ins. diam., bears N. 87° E., 3 lks. dist., mkd. ¼ S24 BT. A juniper, 7 ins. diam., bears S. 82½° W., 120 lks. dist., mkd. ¼ S23 BT. Asc. 86 ft. over rocky SW. slope.
49.40	Ridge, bears NW. and SE., desc. 185 ft. over NE. slope.
70.10	Drain, course NW., along gentle W. slope.
76.65	Wire fence, bears E. and W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd. <div style="text-align: center;"> T38N RLW S14 S13 S23 S24 1934 </div> from which

SUBDIVISION of T. 38 N., R. 1 W.

chains	<p>A juniper, 18 ins. diam., bears N.26°E., 31 lks. dist., mkd. T38N RLW S13 BT.</p> <p>A juniper, 19 ins. diam., bears S.69$\frac{3}{4}$°E., 163 lks. dist., mkd. T38N RLW S24 BT.</p> <p>A pinon, 12 ins. diam., bears S.24$\frac{1}{2}$°W., 141 lks. dist., mkd. T38N RLW S23 BT.</p> <p>A pinon, 7 ins. diam., bears N.52$\frac{3}{4}$°W., 125 lks. dist., mkd. T38N RLW S14 BT.</p> <p>Land, mountainous. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, oakbrush, cliffrose, service, and sagebrush.</p> <hr style="border-top: 1px dashed black;"/> <p>S.89°43'E., on a random line bet. secs. 13 and 24.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.50 Intersect E. bdy. of Tp. (G. & SR. Mer.) 7 lks. N. of the cor. of secs. 13, 18, 19, and 24, which is an iron post, 3 ins. diam., projecting 24 ins. above the ground, and in a mound of stone, firmly set, with brass cap mkd. and witnessed as described in the official record.</p> <p>Thence</p> <p>N.89°40'W., on true line bet. sec. 13 and 24</p> <p>Desc. 400 ft. over broken W. slope, through a scattering growth of timber and dense undergrowth.</p> <p>10.00 Wire fence and base of steep desc., bears N.70°W. and S.70°E., gradual desc. over SW. slope.</p> <p>18.98 Ryan Mill smokestack bears N.20$\frac{3}{4}$°W. Ryan Ranger Station, bears N.40$\frac{1}{4}$°W. Main dwelling in Ryan, Ariz., bears N.54$\frac{1}{2}$°W.</p> <p>19.05 Road, bears S.20°E. and N.20°W.</p> <p>24.60 Drain, course NW., asc. 20 ft. over NE. slope.</p> <p>25.30 Short spur, slopes NW., desc. 50 ft. over W. slope.</p> <p>28.50 Gulch, course N.30°W., asc. 30 ft. over NE. slope.</p> <p>29.77 U.S.F.S. telephone line, bears N.10°W. and S.10°E.</p> <p>36.30 Ryan Mill smokestack, bears N.23$\frac{1}{4}$°E. Ryan Ranger Station, bears N.25$\frac{3}{4}$°E. Main dwelling in Ryan, bears N.38$\frac{1}{2}$°E.</p> <p>36.50 Spur, slopes N., dsec. 100 ft. over NW. slope.</p> <p>39.40 Gulch, 10 lks. wide, course N., asc. 40 ft. over E. slope.</p> <p>40.25 Set an iron post, 3 ft. long, 1 in. diam., on bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 13 and 24, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> $\frac{1}{4} \frac{S13}{S24}$ <p>1934</p> </div>
--------	--

from which

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	A pinon, 14 ins. diam., bears N.15 $\frac{1}{2}$ °E., 106 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	A pinon, 14 ins. diam., bears S.31 $\frac{3}{4}$ °W., 30 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	Asc. 150 ft. over E. slope.
44.40	Spur, slopes N., desc. 30 ft. over NW. slope.
48.50	Drain, course N.20°E., asc. 90 ft. over E. slope.
50.10	Wire fence, bears N.75°E. and S.75°W.
58.90	Spur, slopes N. desc. 60 ft. over W. slope.
62.30	Gulch, course N., asc. 100 ft. over E. slope.
70.50	Spur, slopes NW., desc. 60 ft. over NW. slope.
80.50	The cor. of secs. 13, 14, 23, and 24.
	Land, mountainous and rolling. Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, oakbrush, cliffrose, service, and sagebrush.

	N.0°01'W., bet, secs. 13 and 14.
	Desc. 20 ft. over gentle NW. slope, through a scattering growth of timber and scattering undergrowth.
7.00	Draw, course S.60°W., asc. 50 ft. over SE. slope.
25.00	Spur, slopes E., (from NW.) desc. 75 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 13 and 14, with brass cap mkd.
	$\frac{1}{4}$ S14 S13 1934
	from which
	A pinon, 10 ins. diam., bears N.40°E., 43 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
	A pinon, 10 ins. diam., bears N.44 $\frac{1}{4}$ °W., 133 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	Desc. 15 ft. over gentle N. slope.
45.00	Head of draw, course E., asc. 18 ft. over S. slope.
49.00	Spur, slopes E., desc. 444 ft. over steep, broken N. slope
62.25	Warm Springs Canyon, wash in bottom, 40 lks. wide, 10 ft. deep, course W., asc. 418 ft. over broken S. slope.
76.90	Top of broken asc., bears NW. and SE., gradual asc. over SW. slope.
79.00	Ridge, bears NW. and SE., desc. gentle NE. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
80:00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 11, 12, 13, and 14, with brass cap mkd.</p> <p style="text-align: center;">T38N RLW S11 S12 S14 S13 1934</p> <p style="text-align: right;">from which</p> <p>A pinon, 12 ins. diam., bears N.43°E., 326 lks. dist., mkd. T38N RLW S12 BT.</p> <p>A pinon, 16 ins. diam., bears S.66½°E., 394 lks. dist., mkd. T38N RLW S13 BT.</p> <p>A pinon, 8 ins. diam., bears S.44½°W., 132 lks. dist., mkd. T38N RLW S14 BT.</p> <p>A pinon, 8 ins. diam., bears N.45½°W., 138 lks. dist., mkd. T38N RLW S11 BT.</p> <p>Land, rolling and mountainous. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush, oakbrush, and cliffrose.</p> <hr style="border-top: 1px dashed black;"/> <p>S.89°40'E., on a random line bet. secs. 12 and 13.</p>
40:00	Set temp. ¼ sec. cor.
80:40	<p>Intersect E. bdy. of Tp. (G. & SR. Mer.) 12 lks. S. of the cor. of secs. 7, 12, 13, and 18, which is an iron post, 3 ins. diam., projecting 16 ins. above the ground and in a mound of stone, firmly set, with brass cap mkd. and witnessed as described in the official record.</p> <p>Thence</p> <p>N.89°45'W., on true line bet. secs. 12 and 13.</p> <p>Desc. 635 ft. over steep W. slope, through a scattering growth of timber and dense undergrowth</p>
28:50	Base of steep desc., bears N. and S., continue desc. gentle W. slope.
28:90	Road, bears N. and S.
36:45	Wash, 10 lks. wide, course SW.; asc. 37 ft. over E. slope.
40:20	<p>Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor. of secs. 12 and 13, with brass cap mkd.</p> <p style="text-align: center;">S12 ¼ ——— S13 1934</p> <p style="text-align: right;">from which</p> <p>A juniper, 10 ins. diam., bears S.45½°E., 231 lks. dist., mkd. ¼ S13 BT.</p> <p>A pinon, 6 ins. diam., bears N.6½°W., 76 lks. dist., mkd. ¼ S12 BT.</p>

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	Asc. gentle SE. slope.
45.90	Low spur, slopes S., desc. gentle SW. slope.
46.50	U.S.F.S. telephone line, bears NW. and SE.
49.40	Draw, course NW., asc. gentle NE. slope.
50.90	Short spur, slopes N., desc. 30 ft. over NW. slope.
54.90	Ravine, course NE., asc. 104 ft. over SE. slope.
68.40	Short spur, slopes NE., desc. 18 ft. over NW. slope.
75.90	Across head of draw, course NE., asc. 17 ft. over NE. slope.
80.40	The cor. of secs. 11, 12, 13, and 14.
	Land, mountainous and rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush, oakbrush, and cliffrose.

	N.0°01'W., bet. secs. 11 and 12.
	Desc. 45 ft. over rolling NE. slope, through a scattering growth of timber and undergrowth.
5.00	Swale, drains NE., asc. 20 ft. over SE. slope.
16.40	Short spur, slopes NE., desc. 230 ft. over N. and NE. slope.
36.20	Wash, 10 lks. wide, course NW.
38.70	Wash, 10 lks. wide, course W., (from NE.) asc. gentle SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec, cor. of secs. 11 and 12, with brass cap mkd.
	$\frac{1}{4}$
	S11 S12
	1934
	from which
	A pinon, 10 ins. diam., bears S.44 $\frac{1}{4}$ °E., 171 lks. dist., mkd. $\frac{1}{4}$ S12 BT.
	A pinon, 10 ins. diam., bears N.50 $\frac{3}{4}$ °W., 166 lks. dist., mkd. $\frac{1}{4}$ S11 BT.
	Asc. 148 ft. over SE. slope.
56.80	Spur, slopes S.60°W., and old road, bears S.60°W. and N.60°E., desc. 85 ft. over NW. slope.
62.20	U.S.F.S. telephone line, bears N.30°W. and S.30°E.
64.35	Drain, course NW., asc. 30 ft. over SW. slope.
68.00	Spur, slopes N.60°W., desc. 125 ft. over N. slope.
73.40	Wash, 10 lks. wide, course N.80°W., asc. 60 ft. over SW. slope.

SUBDIVISION of T, 38 N., R. 1 W.

chains	
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to top, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.
	T38N RLW S2 S1 S11 + S12 1934
	from which
	A pinon, 14 ins. diam., bears N.58 $\frac{1}{2}$ °E., 133 lks. dist., mkd. T38N RLW S1 BT.
	A pinon, 12 ins. diam., bears S.50°E., 156 lks. dist., mkd. T38N RLW S12 BT.
	A pinon, 9 ins. diam., bears S.88 $\frac{1}{2}$ °W., 152 lks. dist., mkd. T38N RLW S 11 BT.
	A pinon, 8 ins. diam., bears N.10 $\frac{1}{2}$ °W., 144 lks. dist., mkd. T38N RLW S 2 BT.
	Land, rolling. Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, oakbrush, cliffrose, service, and sagebrush.

	S.89°45'E., on a random line bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.46	Intersect E.bdy. of Tp. (G. & SR. Mer.) 12 lks. S. of the cor. of secs. 1, 6, 7, and 12, which is an iron post, 3 ins. diam., projecting 12 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record.
	Thence
	N.89°50'W., on true line bet. secs. 1 and 12.
	Desc. rolling W. slope, through a scattering growth of timber and undergrowth.
2.16	Road, bears N.25°W. and S.10°W.
9.76	Old road, bears N.30°W. and S.30°E.
10.36	Drain, course NW., asc. gentle NE. slope.
24.46	Short spur, slopes NW., desc. 160 ft. over SW. slope.
38.76	Drain, course NW., asc. gentle NE. slope.
40.23	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 1 and 12, with brass cap mkd.
	$\frac{1}{4}$ S1 S12 1934
	from which

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	A juniper, 8 ins. diam., bears S. $57\frac{1}{2}^{\circ}$ E., 146 lks. dist., mkd. $\frac{1}{4}$ S12 BT.
	A juniper, 8 ins diam., bears N. $59\frac{1}{4}^{\circ}$ W., 136 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
	Asc. gentle NE. slope.
42.90	Short spur, slopes NW., desc. gentle W. slope. Old road on top, bears N. 30° W. and S. 30° E.
45.00	Drain, course NW., asc. gentle NE. slope.
53.00	Short spur, slopes NW., desc. 160 ft. over SW. slope.
66.75	Drain, course N. 60° W., continue desc. over gentle NW. slope
71.25	Wash, 15 lks. wide, course SW., asc. 60 ft. over SE. slope
78.00	Spur, slopes SW., desc. 25 ft. over SW. slope.
80.46	The cor. of secs. 1, 2, 11, and 12.
	Land, rolling. Soil, gravelly and sandy clay loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N. $0^{\circ} 01'$ W., bet. secs. 1 and 2.
	Asc. 129 ft., over rolling SW. and S. slope, through a scattering growth of timber and undergrowth.
9.80	A juniper post, 5 ins. diam., 5 ft. above the ground, and in a mound of stone, firmly set, and mkd. 1989' S of $\frac{1}{4}$ cor. secs. 1 and 2, on W. face and FS T38N RLW, on N. face, bears N. $69\frac{3}{4}^{\circ}$ E., 99 lks. dist.
12.50	Ridge, bears NE. and SW., desc. 26 ft. over NW. slope.
17.30	Old road, bears NE. and W.
24.30	Across head of draw, course NW., gentle asc. along SW. slope.
28.50	Spur, slopes NW., desc. over gentle N. slope.
33.70	Draw, course W., gentle asc. over S. slope.
37.30	Low ridge, bears E. and NW., gentle desc. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top; for $\frac{1}{4}$ sec. cor. of secs. 1 and 2, with brass cap mkd.
	$\frac{1}{4}$ S2 S1 1934
	from which
	A juniper, 18 ins. diam., bears S. $17\frac{1}{4}^{\circ}$ E., 111 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
	A pinon, 10 ins. diam., bears S. $54\frac{1}{2}^{\circ}$ W., 136 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
	Desc. 45 ft. over N. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains

45.00 Draw; course NW., gentle desc. over SW. slope.

53.00 Spur, slopes NW., desc. 29 ft. over rolling NE. slope.

62.00 Draw, course NW., gentle asc. over SW. slope.

71.40 Spur, slopes W., gentle desc. over N. slope:

79.52 Intersect the N. bdy. of Tp. 38 N., R. 1 W.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.

T39N RLW
S35
S2|S1
T38N RLW
CC.
1934

from which

A pinon, 12 ins. diam., bears S.69 $\frac{1}{2}$ °E., 169 lks. dist., mkd. T38N RLW S1 CC BT.

A juniper, 12 ins. diam., bears S.15 $\frac{3}{4}$ °W., 99 lks. dist., mkd. T38N RLW S2 CC BT.

From point of intersection the cor. of secs. 35 and 36, T. 39 N., R. 1 W. bears S:89°59'E., 46 lks. dist., hereinafter described.

Land, rolling.
Soil, gravelly and sandy clay loam, 3rd rate.
Timber, pinon and juniper:
Undergrowth, sagebrush, cliffrose, and service.

From the cor. of secs. 2, 3, 34, and 35, on S. bdy. of Tp., described in Book "C" of this group.

N.0°01'W., bet, secs. 34 and 35.

Asc. gently rolling land, through a scattering growth of timber and dense undergrowth.

3.00 Spur; slopes W., desc. 55 ft. over N. slope.

7.50 Draw, course W., gentle asc. over S. slope.

9.50 Low spur, slopes W., desc. 51 ft. over N. slope.

16.40 Wash, 5 lks. wide, course NW., gentle asc. over SW. slope.

32.30 Spur, slopes W., desc. gently over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 34 and 35, with brass cap mkd.

$\frac{1}{4}$
S34|S35
1934

from which

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	A pinon, 12 ins. diam., bears N.71 $\frac{1}{4}$ °E., 101 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	A pinon, 10 ins. diam., bears N.84 $\frac{1}{2}$ °W., 56 lks. dist., mkd. $\frac{1}{4}$ S34 BT.
	Desc. 32 ft. over NW. slope.
43.40	Wash, 10 lks. wide, course W., asc. along gentle W. slope.
45.00	Spur, slopes W., gentle desc. along W. slope.
47.40	Draw, course W., gentle asc. over S. slope.
52.50	Spur, slopes W., desc. 70 ft. over rolling NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34, and 35, with brass cap mkd.
	T38N RLW S27 S26 S34 + S35 1934
	from which
	A pinon, 12 ins. diam., bears N.46 $\frac{1}{4}$ °E., 93 lks. dist., mkd. T38N RLW S26 BT.
	A juniper, 10 ins. diam., bears S.48 $\frac{3}{4}$ °E., 10 lks. dist. mkd. T38N RLW S35 BT.
	A pinon, 12 ins. diam., bears S.74 $\frac{1}{2}$ °W., 89 lks. dist., mkd. T38N RLW S34 BT.
	A juniper, 16 ins. diam., bears N.27 $\frac{1}{2}$ °W., 56 lks. dist., mkd. T38N RLW S27 BT.
	Land, rolling. Soil, gravelly and sandy clay loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, cliffrose and sagebrush.

	East, on a random line bet. secs. 26 and 35.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect N. and S. line, 16 lks. S. of the cor. of secs. 25, 26, 35, and 36.
	Thence
	S.89°53'W., on true line bet. secs. 26 and 35.
	Desc. 310 ft. over SW. slope, through a heavy growth of timber and dense undergrowth.
13.58	Wash, 30 lks. wide, course NW., asc. 40 ft. over broken E. slope.
15.48	Spur, slopes N., desc. 34 ft. over W. slope.
18.00	Wash, 25 lks. wide, course N., asc. along N. slope.
21.08	Wash, 10 lks. wide, course NE., asc. 240 ft. over steep E. slope.
30.10	Spur, slopes N., desc. 243 ft. over steep W. slope.

chains	
38.68	Wash, 10 lks. wide, course SW., continue desc. 32 ft. over SW. slope.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 26 and 35, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S26}{S35}$
	1934
	from which
	A pinon, 14 ins. diam., bears N. $28\frac{1}{4}^{\circ}$ E., 71 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	A pinon, 15 ins. diam., bears S. $33\frac{3}{4}^{\circ}$ E., 114 lks. dist., mkd. $\frac{1}{4}$ S 35 BT.
	Desc. 209 ft. over SW. slope.
54.58	Wash, 20 lks. wide, course NW., asc. 70 ft. over NE. slope.
62.60	Spur, slopes N., desc. 100 ft. over NW. slope.
80.08	The cor. of secs. 26, 27, 34, and 35.
	Land, rolling and mountainous. Soil, gravelly and sandy clay loam, 3rd rate. Timber, pinon and juniper. Undergrowth, cliffrose and sagebrush.

	N. $0^{\circ}01'$ W., bet. secs. 26 and 27.
	Desc. 50 ft. over rolling NW. slope, through a heavy growth of timber and scattering undergrowth.
2.20	Hillside drain, course NW., continue gentle desc.
4.80	Road, bears NE. and SW.
13.60	Gulch, 8 lks. wide, course NW., asc. 20 ft. along W. slope.
18.00	Top of asc., begin desc. of 87 ft. over NW. slope.
26.70	Same gulch, course N., (from S. 30° W.) desc. down bottom of gulch.
30.10	Small reservoir in same gulch, approx. 1 ch. long and 30 lks. wide, leave bottom of gulch, course NW., (from S.) asc. gentle SW. slope.
35.50	Spur, slopes W., gentle desc. along NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 26 and 27, with brass cap mkd.
	$\frac{1}{4}$
	S27 S26
	1934
	from which
	A pinon, 8 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ E., 40 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	A pinon, 12 ins. diam., bears S. $69\frac{1}{2}^{\circ}$ W., 43 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	Desc. 114 ft. over rolling NW. slope.
60.40	Drain, course N.30°W., gentle asc. over SW. slope.
66.00	Spur, slopes W., desc. 75 ft. over NW. slope.
80.00	Set an iron post, 3-ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.
	T38N RLW S22 S23 S27 S26 1934
	from which
	A pinon, 12 ins. diam., bears N.57½°E., 75 lks. dist., mkd. T38N RLW S23 BT.
	A pinon, 20 ins. diam., bears S.73½°E., 47 lks. dist., mkd. T38N RLW S26 BT.
	A pinon, 16 ins. diam., bears S.19¼°W., 38 lks. dist., mkd. T38N RLW S27 BT.
	A pinon, 8 ins. diam., bears N.21¼°W., 55 lks. dist., mkd. T38N RLW S22 BT.
	Land, rolling. Soil, gravelly and sandy clay loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, cliffrose and sagebrush.

	N.89°53'E., on a random line bet. secs. 23 and 26.
40.00	Set temp. ¼ sec. cor.
80.02	Intersect N. and S. line, 2 lks. N. of the true point for cor. of secs. 23, 24, 25, and 26.
	Thence
	S.89°54'W., on true line bet. secs. 23 and 26.
	Desc. 15 ft. along bottom of Nail Canyon gulch.
27.00	Leave bottom of same gulch, course N.75°W., (from E.)
28.87	U.S.F.S. wire fence, bears S.75°E. and N.75°W.
28.95	Road, bears N.75°W. and S.75°E., asc. 150 ft. NE. slope.
34.00	Enter scattering timber and dense undergrowth, bears NW. and SE.
39.40	Sharp spur, slopes N. abruptly, desc. 5 ft. over steep NW. slope.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor. of secs. 23 and 26, with brass cap mkd.

¼ S23
 ¼ S26
 1934

from which

SUBDIVISION of T. 38 N., R. 1 W.

chains	
	A pinon, 5 ins. diam., bears N.38°E., 34 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	A pinon, 6 ins. diam., bears S.72 $\frac{1}{2}$ °W., 13 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	Desc. 120 ft. over steep NW. slope.
43.60	Road, bears N.15°E. and S.15°W.
44.00	Wash, 20 lks. wide, course N.15°E., asc. 210 ft. over broken E. slope.
50.90	Spur, slopes N., desc. 28 ft. over W. slope.
53.50	Drain, course N.15°W., along N. slope.
57.50	Drain, course N.30°E., asc. 60 ft. over NE. slope.
61.50	Spur, slopes N.15°W., desc. 85 ft. over SW. slope.
67.20	Gulch, 6 lks. wide, course N.30°W., asc. 75 ft. over NE. slope.
72.50	Spur, slopes N.20°W., desc. 70 ft. over SW. slope.
76.80	Drain, course N.15°W., gentle asc. over NE. slope.
79.00	Spur, slopes N., desc. 25 ft. over NW. slope.
80.02	The cor. of secs. 22, 23, 26, and 27.
	Land, rolling and mountainous. Soil, gravelly and sandy clay loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, cliffrose, oakbrush, service, and sagebrush.

	N.0°01'W., bet. secs. 22 and 23.
	Desc. 48 ft. over broken NW. slope, through a heavy growth of timber and scattering undergrowth.
3.75	Ravine, 10 lks. wide, course N.15°E., asc. 58 ft. over SE. slope.
8.00	Spur, slopes N.60°E., desc. 52 ft. over NW. slope.
13.40	Wash, 10 lks. wide, course NE., asc. 103 ft. over SE. slope
22.50	Spur, slopes NE., desc. 31 ft. over NW. slope.
33.00	Ravine, 8 lks. wide, course NE., asc. 20 ft. over SE. slope.
36.00	Spur, slopes NE., desc. gentle N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs, 22 and 23, with brass cap mkd..
	$\frac{1}{4}$
	S22 S23
	1934.
	from which
	A pinon, 18 ins. diam., bears S.37 $\frac{3}{4}$ °E., 173 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	A juniper, 30 ins. diam., bears N.27 $\frac{3}{4}$ °W., 61 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	Desc. gentle N. slope.
45.00	Draw, course E., asc. gentle S. slope.
55.00	Spur, slopes E., desc. gentle N. slope.
60.00	Head of draw, course E., asc. gentle S. slope.
63.00	Wide spur, slopes E., desc. 32 ft. over gentle N. slope.
77.95	Rim of Nail Canyon, bears N.30°W. and S.30°E., desc. 50 ft. over broken NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground and in a mound of stone to top, for cor. of secs. 14, 15, 22, and 23, with brass cap mkd.
	T38N RLW S15 S14 S22 S23 1934
	from which
	A juniper, 5 ins. diam., bears N.21½°E., 95 lks. dist., mkd. T38N RLW S14 BT.
	A pinon, 8 ins. diam., bears S.26¼°E., 19 lks. dist., mkd. T38N RLW S23 BT.
	A pinon, 12 ins. diam., bears S.51¾°W., 68 lks. dist., mkd. T38N RLW S22 BT.
	A pinon, 12 ins. diam., bears N.40¼°W., 94 lks. dist., mkd. T38N RLW S15 BT.
	Land, rolling. Soil, gravelly and sandy clay loam, 3rd rate. Timber, pinon and juniper. Undergrowth, cliffrose, sagebrush, and service.

	N.89°54'E., on a random line bet. secs. 14 and 23.
40.00	Set temp. ¼ sec. cor.
80.08	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 13, 14, 23, and 24.
	Thence
	S.89°55'W., on true line bet. secs. 14 and 23.
	Desc. 80 ft. over NW. slope, through a heavy growth of timber and scattering undergrowth.
8.33	U.S.F.S. wire fence, bears NW. and SE.
10.83	Wash, 10 lks. wide, course SW., asc. 118 ft. over SE. slope.
32.10	Wide ridge, bears N.10°E. and S., desc. 105 ft. over SW. slope.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of secs. 14 and 23, with brass cap mkd.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
	$\frac{\frac{1}{4} S14}{S23}$ 1934
	from which
	A pinon, 8 ins. diam., bears N.13°E., 70 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	A pinon, 8 ins. diam., bears S.10°E., 170 lks. dist., mkd. $\frac{1}{4}$ S23 BT.
	Desc. 122 ft. over steep SW. slope.
47.20	Wash, 10 lks. wide, course N., asc. 91 ft. over NE. slope.
53.10	Ridge, bears N.30°W., and S.30°E., desc. 430 ft. over broken SW. slope.
68.60	Base of broken desc., and leave heavy, enter scattering timber, bears NW. and SE., across bottom of Nail Canyon.
70.98	U.S.F.S. wire fence, bears NW. and SE.
72.00	Nail Canyon, wash in bottom, 30 lks. wide, 5 ft. deep, course NW., across bottom of canyon.
72.60	Road, bears NW. and SE.
74.10	Leave bottom of canyon, bears NW. and SE., asc. 237 ft. over broken NE. slope.
80.08	The cor. of secs. 14, 15, 22, and 23.
	Land, mountainous and rolling. Soil, gravelly and sandy clay loam, 1st and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°01'W., bet. secs. 14 and 15.
	Desc. 275 ft. over broken NE. slope, through a scattering growth of timber and undergrowth.
10.50	Base of broken desc., and leave timber, bears N.10°W. and S.10°E., gradual desc. along bottom of Nail Canyon.
17.50	Road, bears N.15°W. and S.15°E.
22.20	Nail Canyon, wash in bottom, 25 lks. wide, 6 ft. deep, course N.15°W.
25.00	Same wash, course N.15°E., desc. along left bank of wash.
27.40	Same road, bears N.15°E. and S.15°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 14 and 15, with brass cap mkd.
	$\frac{1}{4}$ $S15 S14$ 1934
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

SUBDIVISION of T. 38 N., R. 1 W.

37

BOOK 4041

chains	
42.80	Same road, bears N.10°W. and S.10°E.
59.80	Same road, bears S.10°W. and N.10°E.
67.00	Leave bottom of Nail Canyon, bears S.10°W. and N.10°E., asc. steep, broken SE. slope.
80.00	The true point for cor. of secs. 10, 11, 14, and 15, falls on sloping face of rimrock, where it is impracticable to monument the cor., therefore W.C. is established N.0°01'W., 125 lks. dist., hereinafter described.
	Land, mountainous.
	Soil, along bottom of canyon, sandy loam; 1st and 2nd rates; remainder, gravelly and stony, 3rd rate.
	Timber, pinon and juniper.
	Undergrowth, sagebrush, service, and cliffrose.

	From true point for cor. of secs. 10, 11, 14, and 15 N89°55'E., on a random line bet. secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.18	Intersect N. and S. line 12 lks. N. of cor. of secs. 11, 12, 13, and 14.
	Thence
	West, on true line bet. secs. 11 and 14.
	Asc. gentle NE. slope, through a scattering growth of timber and undergrowth.
5.20	Ridge, bears NW. and SE., desc. gentle SW. slope.
7.40	E. rim of Warm Springs Canyon, bears NW. and SE., desc. 500 ft. over steep; broken SW. slope.
27.40	Warm Springs Canyon, wash in bottom, 20 lks. wide, 6 ft. deep, course NW., asc. 130 ft. over rocky NE. slope.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 11 and 14, with brass cap mkd:
	$\frac{1}{4} \frac{S11}{S14}$
	1934
	from which
	A pinon, 10 ins. diam., bears N.13 $\frac{1}{4}$ °E., 78 lks. dist., mkd. $\frac{1}{4}$ S11 BT.
	A pinon, 12 ins. diam., bears S.16 $\frac{3}{4}$ °E., 62 lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	Asc. 224 ft. over rocky NE. slope.
45.60	W. rim of Warm Springs Canyon, bears NW. and SE., gentle asc. over NE. slope.
49.20	Wide spur, slopes gently NW., desc. 86 ft. over gentle SW. slope.
65.00	E. rim of Nail Canyon, bears N. and S., desc. 338 ft. over broken W. slope.

SUBDIVISION of T. 38 N., R. 1 W.

- chains
73.20 Base of broken desc., and leave timber, bears N. and S.
74.50 Nail Canyon, wash in bottom, 30 lks. wide, 10 ft. deep,
course N.10°E., across bottom of canyon.
75.60 Road, bears N.10°E., and S.10°W.
77.00 Base of asc., bears N. and S., asc. 290 ft. over E. slope.
80.18 The true point for the cor. of secs. 10,11,14, and 15.

Land, mountainous.
Soil, gravelly and sandy clay loam, 1st., 2nd, and 4th rates.
Timber, pinon and juniper.
Undergrowth, sagebrush, service, and cliffrose.

From the true point for cor. of secs. 10,11,14, and 15

N.0°01'W., bet. secs. 10 and 11.

Asc. 75 ft. over rimrock, facing SE.

- 1.25 Falls on shelf, 20 ft. in diam., below point of rim, mark
a cross (X) on flat ledge over which, set an iron post,
3 ft. long, 2 ins. diam., and in a mound of stone to
top, for witness cor. to the cor. of secs. 10,11,14,
and 15, with brass cap mkd.

T38N RLW

S10 | S11

S15 | S14

WC

1934

No suitable bearing trees available.

Asc. 90 ft. over broken SE. slope, through a scattering
growth of timber and undergrowth.

- 13.15 Spur, slopes NE., along broken, rocky, steep E. slope,
below top of rimrock of W. rim of Nail Canyon, bears
N. and S.
40.00 The true point for $\frac{1}{4}$ sec. cor. of secs. 10 and 11, falls
on broken cliffs, where it is impractical to monument
the cor.
44.50 Set an iron post, 3 ft. long, 1 in. diam., over a mkd.
cross (X) on bedrock, in a mound of stone to top, for
witness cor. to $\frac{1}{4}$ sec. cor. of secs. 10 and 11, with
brass cap mkd.
 $\frac{1}{4}$
S10 | S11
WC
1934
from which
A pinon, 12 ins. diam., bears N.74 $\frac{1}{4}$ °W., 85 lks. dist.,
mkd. WC $\frac{1}{4}$ S10 BT,
Above WC. $\frac{1}{4}$ sec. cor, falls on top of sharp, rocky spur,
slopes NE., desc. 200 ft. over broken NW. slope.
52.85 Ravine, 12 lks. wide, course N.30°E., continue desc. 50
ft. over gradual N. slope.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
53.00	Old stone house, bears E., approximately 15 chs. dist.
59.50	Road, bears E. and W.
60.20	Snake Canyon, wash in bottom, 100 lks. wide, 10 ft. deep, course W., begin asc. of 478 ft. over broken S. slope.
72.70	N. rim of Snake Canyon, bears E. and W., continue gradual asc.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.
	T38N RLW S3 S2 S10 S11 1934
	from which
	A pinon, 10 ins. diam., bears N. 62½° E., 153 lks. dist., mkd. T38N RLW S2 BT.
	A pinon, 10 ins. diam., bears S. 86¼° E., 269 lks. dist., mkd. T38N RLW S11 BT.
	A pinon, 14 ins. diam., bears S. 65° W., 340 lks. dist., mkd. T38N RLW S10 BT.
	A juniper, 10 ins. diam., bears N. 46½° W., 124 lks. dist., mkd. T38N RLW S3 BT.
	Land, rough mountainous. Soil, gravelly and sandy, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	East, on a random line bet. secs. 2 and 11.
40.00	Set temp. ¼ sec. cor.
80.24	Intersect N. and S. line, 18 lks. S. of cor. of secs. 1, 2, 11, and 12.
	Thence
	S. 89° 52' W., on true line bet. secs. 2 and 11.
	Gentle asc. along broken, general S. slope, through a scattering growth of timber and undergrowth.
2.30	Spur, slopes S., desc. 78 ft. over SW. slope.
10.30	Bend in Snake Canyon, 20 lks. wide, 6 ft. deep, course SW., (from SE.) asc. 108 ft. over steep SE. slope.
17.20	Spur, slopes S.,
18.80	Rim of Snake Canyon, bears NW. and SE., desc. 188 ft. over steep, rocky SW. slope.
23.30	Snake Canyon, wash in bottom, 20 lks. wide, 7 ft. deep, course NW., asc. 74 ft. over E. slope.
30.20	Spur, slopes N., desc. 129 ft. over broken W. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains	Snake Canyon, course SW., asc. 85 ft. over SE. slope.
35.60	
40.12	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 2 and 11, with brass cap mkd.
	$\frac{1}{4} \frac{S 2}{S 11}$ 1934
	from which
	A pinon, 10 ins. diam., bears N.59 $\frac{3}{4}$ °E., 72 lks. dist., mkd. $\frac{1}{4}$ S2 BT.
	A pinon, 12 ins. diam., bears S.28 $\frac{1}{4}$ °W., 131 lks. dist., mkd. $\frac{1}{4}$ S11 BT.
	Asc. 44 ft. over E. slope.
43.50	Spur, slopes S., desc. 88 ft. over W. slope.
49.34	Ravine, course S., asc. 107 ft. over SE. slope.
65.14	Wire fence, bears N.20°E. and S.20°W.
80.24	The cor. of secs. 2, 3, 10, and 11.
	Land, rolling mountainous. Soil, gravelly and sandy clay loam, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°01'W., on a random line bet. secs. 2 and 3.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.62	Intersect N. bdy. of Tp. at a point 12 lks. W. of the cor. of secs. 2 and 3, only hereinbefore described.
	Thence
	S.0°04'W., on true line bet. secs. 2 and 3
	Over rolling land, through a scattering growth of timber and undergrowth
3.40	Low ridge, bears E. and W., desc. gentle S. slope.
9.60	Draw, course S.60°W., gentle asc. over N. slope.
14.66	Ridge, bears E. and W., gentle desc. over S. slope.
19.60	Draw, 15 lks. wide, course W., gradual asc. over N. slope.
32.30	Ridge and road on top, bears E. and W., desc. 45 ft. over S. slope.
39.62	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 2 and 3, with brass cap mkd.
	$\frac{1}{4} \frac{S 3}{S 2}$ 1934
	from which

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains

A juniper, 8 ins. diam., bears S. $68\frac{1}{4}^{\circ}$ E., 114 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

A pinon, 8 ins. diam., bears N. $40\frac{3}{4}^{\circ}$ W., 202 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

43.40 Shallow draw, course W., gentle asc. over N. slope.

48.46 Ridge, bears E. and W., desc. 46 ft. over S. slope.

57.10 Old road, bears NE. and SW.

62.40 Draw, course W., asc. 50 ft. over gradual N. slope.

79.62 The cor. of secs. 2, 3, 10, and 11.

Land, rolling.

Soil, gravelly and sandy clay loam, 2nd and 3rd rates.

Timber, pinon and juniper

Undergrowth, sagebrush and cliffrose.

From the cor. of secs. 3, 4, 33, and 34, on S. bdy. of the Tp., described in Book "C" of this group.

N. $0^{\circ}02'$ W., bet. secs. 33 and 34.

Desc. 88 ft. along NW. slope, through a heavy growth of timber and scattering undergrowth.

21.50 Bottom of saddle in ridge, ridge bears N. 30° W. and S. 15° E. continue desc. 100 ft. over NE. slope.

37.20 Drain, course NW., asc. gentle SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 33 and 34, with brass cap mkd.

$\frac{1}{4}$

S33 | S34

1934

from which

A pinon, 14 ins. diam., bears S. $65\frac{1}{2}^{\circ}$ E., 48 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

A pinon, 16 ins. diam., bears N. $53\frac{3}{4}^{\circ}$ W., 40 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Asc. gentle SW. slope.

48.00 Spur, slopes NW., desc. 135 ft. over NE. slope.

63.00 Leave heavy, enter scattering timber, bears NW. and SE.

78.00 Wash, 20 lks. wide, course N. 30° W., gradual asc. along gentle W. slope.

79.70 Old road, bears N. 30° W. and S. 30° E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 27, 28, 33, and 34, with brass cap mkd.

SUBDIVISION of T. 38 N., R. 1 W.

chains

T38N RLW

S28 | S27

S33 | S34.

1934

from which

A juniper, 14 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E., 72 lks. dist.; mkd. T38N RLW S27 BT.

A juniper, 16 ins. diam., bears S. $72\frac{1}{2}^{\circ}$ E., 123 lks. dist.; mkd. T38N RLW S34 BT.

A juniper, 8 ins. diam., bears S. $68\frac{1}{2}^{\circ}$ W., 139 lks. dist.; mkd. T38N RLW S33 BT.

A juniper, 30 ins. diam., bears N. 23° W., 86 lks. dist.; mkd. T38N RLW S28 BT.

Land, rolling.

Soil, gravelly sandy, 2nd and 3rd rates.

Timber, pinon and juniper.

Undergrowth, sagebrush, service, and cliffrose.

East, on a random line bet. secs. 27 and 34.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.06 Intersect N. and S. line, 11 lks. N. of the cor. of secs. 26, 27, 34, and 35.

Thence

N. $89^{\circ}55'$ W., on true line, bet. secs. 27 and 34.

Desc. over rolling NW. slope, through a heavy growth of timber and scattering undergrowth.

6.10 Drain, course N. 30° W.

6.40 Road, bears N. 20° E. and S. 20° W.

9.36 Drain, course N. 10° E., gentle asc. over E. slope.

15.36 Ridge and road, bears N. 20° W. and S. 20° E., desc. 60 ft. over SW. slope.

23.40 Draw, course N. 30° W., asc. 60 ft. over NE. slope.

30.00 Spur, slopes NW., desc. 55 ft. over SW. slope.

37.00 Gulch, 20 lks. wide, course NW., gentle asc. over NE. slope

40.03 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 27 and 34, with brass cap mkd.

$\frac{1}{4}$ S27
S34

1934

from which

A pinon, 12 ins. diam., bears S. $47\frac{1}{2}^{\circ}$ W., 20 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

A pinon, 12 ins. diam., bears N. $32\frac{3}{4}^{\circ}$ W., 64 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	Gentle asc. over NE. slope.
41.00	Spur, slopes NW., gentle desc. over NW. slope.
49.00	Bottom of saddle in ridge, ridge bears NE. and SW., gentle asc. along N. slope.
58.10	Same ridge, bears S.60°E. and NW., desc. 130 ft. over SW. slope.
75.50	Small draw, course NW., continue desc. over gentle W. slope
80.06	The cor. of secs. 27, 28, 33, and 34.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush, oakbrush, and cliffrose.

	N.0°-02'W., bet. secs. 27 and 28.
	Gentle desc. over rolling land, through a heavy growth of timber and scattering undergrowth.
5.00	Draw, 5 lks. wide, course NW., gentle asc. over SW. slope.
10.00	Low spur, slopes NW., gentle desc.
15.00	Draw, course NW.
20.00	Low ridge, bears NW. and SE., gentle desc. over NE. slope.
29.00	Head of draw, course NE., gentle asc.
34.00	Rocky spur, slopes E., desc 32 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 27 and 28, with brass cap mkd.
	$\frac{1}{4}$ S28 S27 1934
	from which
	A juniper, 24 ins. diam., bears N.45°E., 202 lks. dist., mkd. $\frac{1}{4}$ S27 BT.
	A juniper, 14 ins. diam., bears S.85°W., 133 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
41.10	Wash, 10 lks. wide, course NW., continue over rolling land
50.00	Low spur, slopes NW.
64.00	Wash, 10 lks wide, course W., gentle asc. over gradual S. slope.
64.50	Road, bears E. and W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in ground, for cor. of secs. 21, 22, 27, and 28, with brass cap mkd.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
	T38N RLW S21 S22 S28 S27 1934
	from which
	A juniper, 16 ins. diam., bears N.59½°E., 23 lks. dist. mkd. T38N RLW S22 BT.
	A pinon, 18 ins. diam., bears S.66¼°E., 36 lks. dist., mkd. T38N RLW S27 BT.
	A pinon, 16 ins. diam., bears S.62½°W., 154 lks. dist., mkd. T38N RLW S28 BT.
	A pinon, 16 ins. diam., bears N.33½°W., 116 lks. dist., mkd. T38N RLW S21 BT.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	S.89°55'E., on a random line bet. secs. 22 and 27.
40.00	Set temp. ¼ sec. cor.
80.22	Intersect N. and S. line 5 lks. S. of the cor. of secs. 22, 23, 26, and 27.
	Thence
	N.89°57'W., on true line bet. secs. 22 and 27.
	Desc. 128 ft. over steep NW. slope, through a scattering growth of timber and undergrowth.
0.83	Ravine, 12 lks. wide, course N., asc. 100 ft. over E. slope.
6.70	Spur, slopes N., desc. 33 ft. over W. slope.
9.60	Ravine, course N., gentle asc.
11.20	Spur, slopes N., gentle desc. over NW. slope.
14.30	Wash, 10 lks. wide, course NE., gentle asc.
19.20	Spur, slopes N., gentle desc. over W. slope.
22.20	Ravine, course N., asc. 49 ft. over NE. slope.
29.20	Ridge, bears NW. and SE., gentle desc. over SW. slope.
40.11	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor. of secs. 22 and 27, with brass cap mkd.
	¼ S22 S27
	1934
	from which
	A pinon, 10 ins. diam., bears S.128°E., 175 lks. dist., mkd. ¼ S27 BT.
	A juniper, 10 ins. diam., bears N.19°W., 108 lks. dist., mkd. ¼ S22 BT.

SUBDIVISION of T. 38 N., R. 1 W.

45

OK 4041

chains	Gentle asc. over W. slope.
47.40	Wash, 5 lks. wide, course SW., gentle asc.
55.20	Low spur, slopes S., gentle desc.
58.20	Head of draw, course S., gentle asc. along S. slope.
80.22	The cor. of secs. 21, 22, 27, and 28.
	Land, rolling. Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.

	N.0°02'W., bet. secs. 21 and 22.
	Over rolling land, through a scattering growth of timber and undergrowth.
2.00	Low ridge, bears E. and SW., gentle desc. 45 ft. over NE. slope.
22.70	Drain, course NE., gentle desc. along rolling E. slope.
31.40	Small drain, course NE., gentle asc.
37.00	Spur, slopes E., gentle desc. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 21 and 22, with brass cap mkd.
	$\frac{1}{4}$ S21 S22 1934
	from which
	A pinon, 14 ins. diam., bears S.52°E., 133 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	A juniper, 10 ins. diam., bears S.85°W., 36 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	Gentle desc. over NE. slope.
42.70	Drain, course NE. gentle asc.
46.00	Spur, slopes E., gentle desc. over NE. slope.
52.60	Gulch, 12 lks. wide, course N.30°W., gentle asc.
66.00	Spur, slopes NW., desc. 50 ft. over N. slope.
73.00	Drain, course W., gentle desc. along W. slope.
80.00	Set an iron post, 3 ft. long 2 ins. diam., 26 ins. in the ground, for cor. of secs. 15, 16, 21, and 22, with brass cap mkd.
	T38N R1W S16 S15 S21 S22 1934
	from which
	A juniper, 18 ins. diam., bears N.76 $\frac{1}{2}$ °E., 106 lks. dist., mkd. T38N R1W S15 BT.

SUBDIVISION of T. 38 N., R. 1 W.

chains

A juniper, 10 ins. diam., bears S.66°E., 49 lks. dist., mkd. T38N RLW S22 BT.

A pinon, 10 ins. diam., bears S.19½°W., 73 lks. dist., mkd. T38N RLW S21 BT.

A pinon, 14 ins. diam., bears N.37¾°W., 31 lks. dist., mkd. T38N RLW S16 BT.

Land, rolling.
Soil, gravelly and sandy loam, 2nd and 3rd rates.
Timber, pinon and juniper.
Undergrowth, sagebrush, cliffrose, and service.

S.89°57'E., on a random line bet, secs. 15 and 22.

40.00 Set temp. ¼ sec. cor.

80.18 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 14,15,22, and 23.

Thence

N.89°52'W., on true line, bet. secs. 15 and 22.

Asc. 85 ft. over rolling land, through a scattering growth of timber and undergrowth.

0.68 W. rim of Nail Canyon, bears N.15°W. and S.30°E., gentle asc. over general E. slope.

12.20 Ridge, bears N.30°W. and SE., desc. 75 ft. over SW. slope.

19.40 Gulch, 8 lks. wide, course NW., asc. 60 ft. over NE. slope.

26.30 Spur, slopes N., desc. 60 ft. over W. slope.

30.40 Drain, course N., asc. 56 ft. over E. slope.

40.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of secs. 15 and 22, with brass cap mkd.

¼ S15
S22

1934

from which

A pinon, 10 ins. diam., bears N.30¾°E., 13 lks. dist., mkd. ¼ S15 BT.

A juniper, 10 ins. diam., bears S.13°W., 47 lks. dist., mkd. ¼ S22 BT.

Asc. 40 ft. over E. slope.

44.20 Spur, slopes N.30°W., gentle desc.

46.70 Head of draw, course NW., gentle asc. over NE. slope.

52.20 Top of ridge bears NW. and SE., desc. over SW. slope.

59.50 Draw, course N.40°W., asc. over gentle NE. slope.

73.20 Spur, slopes NW., desc. 75 ft. over rolling SW. slope.

80.18 The cor. of secs. 15,16,21, and 22.

Land, rolling.
Soil, gravelly and sandy loam, 3rd rate.
Timber, pinon and juniper,
Undergrowth, sagebrush, cliffrose, oakbrush, and service.

SUBDIVISION OF T. 38 N., R. 1 W.

47

BOOK 4041

chains

N.0°02'W., bet. secs. 15 and 16.

Gentle asc. over rolling land, through a scattering growth of timber and undergrowth.

28.00 Low spur, slopes W., desc. over gentle N. slope.

33.00 Wash, 5 lks. wide, course W., gentle asc. over S. slope.

39.00 Low spur, slopes N.80°W., desc. gentle N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 15 and 16, with brass cap mkd. $\frac{1}{4}$

S16 | S15

1934

from which

A pinon, 8 ins. diam., bears S.38 $\frac{1}{4}$ °E., 160 lks. dist., mkd. $\frac{1}{4}$ S15 BT.A pinon, 10 ins. diam., bears S.26 $\frac{1}{2}$ °W., 275 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Desc. 40 ft. over N. slope.

46.45 Ravine, course W., gradual asc.

57.00 Spur, slopes W., desc. 84 ft. over N. slope.

68.90 Wash, 10 lks. wide, course W., gradual asc. 70 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, and in a mound of stone to top, for cor. of secs. 9,10,15, and 16, with brass cap mkd.

T38N RLW

S9 | S10

S16 | S15

1934

from which

A pinon, 14 ins. diam., bears N.55 $\frac{1}{4}$ °E., 265 lks. dist., mkd. T38N RLW S10 BT.A juniper, 14 ins. diam., bears S.51 $\frac{1}{4}$ °E., 93 lks. dist., mkd. T38N RLW S15 BT.

A pinon, 12 ins. diam., bears S.68°W., 87 lks. dist., mkd. T38N RLW S16 BT.

A pinon, 12 ins. diam., bears N.46 $\frac{1}{2}$ °W., 65 lks. dist., mkd. T38N RLW S9 BT.

Land, rolling.

Soil, sandy and gravelly, 2nd and 3rd rates.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

SUBDIVISION of T. 38 N., R. 1 W.

chains	S.89°52'E., on a random line, bet. sec. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.20	Intersect N. and S. line, at the true point for cor. of secs. 10,11,14, and 15.
	Thence.
	N.89°52'W., on true line, bet. secs. 10 and 15.
	Asc. 40 ft. over broken E. slope, through a scattering growth of timber and undergrowth.
4.20	W. rim of Nail Canyon, bears N. and S.15°W. , asc. 80 ft. over E. slope.
8.00	Ridge, bears N. and S., desc. 40 ft. over rolling W. slope.
15.75	Wash, course NW., along rolling N. slope.
22.20	Wash,, course NE., asc. 38 ft. over NE. slope.
35.20	Spur, slopes W., (from S.60°E.) gradual desc. along top of spur.
40.10	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 10 and 15, with brass cap mkd.
	$\frac{1}{4}$ S10 S15
	1934
	from which
	A pinon, 10 ins. diam., bears N.21 $\frac{3}{4}$ °E., 60 lks.. dist., mkd. $\frac{1}{4}$ S10 BT.
	A pinon, 6 ins. diam., bears S.12 $\frac{1}{4}$ °W., 66 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	Gradual desc. 54 ft. along top of spur.
80.20	The cor. of secs. 9,10,15, and 16.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°02'W.; bet. secs. 9 and 10.
	Desc. 85 ft. over rolling N. slope, through a scattering growth of timber and undergrowth.
14.35	Ravine, course W., asc. 62 ft. over S. slope.
22.00	Small butte, on spur, slopes NW., desc. 120 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., on bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 9 and 10, with brass cap mkd.
	$\frac{1}{4}$ S9 S10
	1934
	from which

chains	
	A pinon, 6 ins. diam., bears N.55 $\frac{3}{4}$ °E., 113 lks. dist., mkd. $\frac{1}{4}$ S10 BT.
	A pinon, 4 ins. diam., bears N.63 $\frac{1}{4}$ °W., 167 lks. dist., mkd. BT.
	Begin desc. of 323 ft. over rocky NE. slope.
52.00	Enter ravine, course N., (from SE.) desc. down bottom of ravine.
55.50	Leave ravine, course NW., (from S.) continue desc. along NW. slope.
65.85	Spur, slopes NW., desc. 131 ft. over rocky NE. slope.
74.10	Road, bears E. and W.
75.40	Snake Canyon, wash in bottom, 100 lks. wide, 10 ft. deep. course W., asc. 120 ft. over S. slope of sandstone ledges.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 3, 4, 9, and 10, with brass cap mkd.
	T38N RLW S4 S3 S9 S10 1934
	from which
	A pinon, 8 ins. diam., bears S.12 $\frac{1}{2}$ °W., 199 lks. dist., mkd. T38N RLW S9 BT.
	No other bearing trees available.
	Land, rolling and mountainous. Soil, gravelly, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.

	S.89°52'E., on a random line, bet. secs. 3 and 10.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect the cor. of secs. 2, 3, 10, and 11.
	Thence
	N.89°52'W., on true line, bet. secs. 3 and 10.
	Gradual desc. of 83 ft. over rolling land, through a scattering growth of timber and undergrowth
40.04	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 3 and 10, with brass cap mkd.
	$\frac{1}{4}$ S3 S10 1934
	from which
	A juniper, 12 ins diam., bears N.5 $\frac{1}{2}$ °E., 182 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
	A pinon, 14 ins. diam., bears S.31 $\frac{1}{2}$ °E., 111 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

chains	Desc. 123 ft. along S. and SW. slopes.
51.84	N. rim of Snake Canyon, bears N. and S. for 3 chs. thence E., desc. 235 ft. over steep broken W. slope.
56.70	Ravine, course S., asc. 145 ft. over broken SE. slope.
63.30	Top of rocky point, (N. rim of Snake Canyon) slopes S., desc. 165 ft. along broken, steep S. slope.
80.08	The cor. of secs. 3, 4, 9, and 10. Land, rolling mesa and mountainous. Soil, gravelly, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°04'E., on a random line, bet. secs. 3 and 4.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.34	Intersect N. bdy. of the Tp. at a point 19 lks. W. of the cor. of secs. 3 and 4 only, hereinafter described. Thence S.0°12'W., on true line, bet. secs. 3 and 4. Asc. 100 ft. over rolling N. slope, through a scattering growth of timber and undergrowth.
10.75	Draw, course N.30°E., continue asc.
25.15	Low ridge, bears E. and W., gentle desc. over S. slope.
39.34	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 3 and 4, with brass cap mkd.
	$\frac{1}{4}$ S 4 S 3 1934
	from which
	A juniper, 16 ins. diam., bears N.41 $\frac{1}{2}$ °E., 79 lks. dist., mkd. $\frac{1}{4}$ S 3 BT.
	A pinon; 18 ins. diam., bears S.81 $\frac{1}{4}$ °W., 37 lks. dist., mkd. $\frac{1}{4}$ S 4 BT.
	Desc. 40 ft. over rolling S. slope.
49.24	Draw, course S.60°W., road in bottom, bears S.60°W. and N.60°E., asc. 35 ft. over NW. slope.
60.15	Spur, slopes W., gentle desc.
65.15	Draw, course N.60°W., gentle asc.
73.65	Wide ridge, bears S.75°W. and N.75°E., desc. 60 ft. over broken S. slope.
77.30	N. rim of Snake Canyon, bears E. and W., desc. 195 ft. over broken S. slope.
79.34	The cor. of secs. 3, 4, 9, and 10.

SUBDIVISION of T. 38 N., R. 1 W.

51

SECTION 4041

chains

Land, rolling and mountainous.
Soil, gravelly and sandy loam, 2nd and 3rd rates.
Timber, pinon and juniper.

From the cor. of secs. 4, 5, 32, and 33, on S. bdy. of the
Tp., described in Book "C" of this group.

N. 0° 03' W., bet. secs. 32 and 33.

Gentle desc. over rolling land, through a scattering
growth of timber and undergrowth.

- 5.00 Head of draw, course W., asc. 34 ft. over SW. slope.
17.00 Ridge, bears NW. and SE., desc. 79 ft. over NE. slope.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground to bedrock, and in a mound of stone to top, for
 $\frac{1}{4}$ sec. cor. of secs. 32 and 33, with brass cap mkd.

 $\frac{1}{4}$

S32 | S33

1934

from which

A juniper, 8 ins. diam., bears S. 53 $\frac{1}{4}$ ° E., 57 lks.
dist., mkd. $\frac{1}{4}$ S33 BT.

A juniper, 16 ins. diam., bears S. 67° W., 161 lks.
dist., mkd. $\frac{1}{4}$ S32 BT.

Asc. 38 ft. over SE. slope.

- 51.50 Spur, slopes E., desc. 118 ft. over NE. slope.
67.90 Wash, 10 lks. wide, course NW., gentle asc. over SW. slope.
80.00 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in
the ground to bedrock, and in a mound of stone to top,
for cor. of secs. 28, 29, 32, and 33, with brass cap mkd.

T38N RLW

S29 | S28

S32 | S33

1934

from which

A pinon, 8 ins. diam., bears N. 47 $\frac{3}{4}$ ° E., 50 lks. dist.,
mkd. T38N RLW S28 BT.

A pinon, 12 ins. diam., bears S. 44 $\frac{1}{2}$ ° E., 49 lks. dist.,
mkd. T38N RLW S33 BT.

A pinon, 10 ins. diam., bears S. 38 $\frac{3}{4}$ ° W., 41 lks. dist.,
mkd. T38N RLW S32 BT.

A pinon, 14 ins. diam., bears N. 53 $\frac{1}{4}$ ° W., 145 lks.
dist., mkd. T38N RLW S29 BT.

Land, rolling.
Soil, gravelly and sandy loam, 2nd and 3rd rates.
Timber, pinon and juniper.
Undergrowth, sagebrush and cliffrose.

chains	East, on a random line, bet. secs. 28 and 33.
40.00	Set temp. $\frac{1}{4}$ sec. cor..
80.20	Intersect N. and S. line 18 lks. S. of the cor. of secs. 27, 28, 33, and 34.
	Thence
	S.89°52'W., on true line bet. secs. 28 and 33.
	Desc. gentle W. slope over rolling land, through a scattering growth of timber and undergrowth.
0.20	Old road, bears NW. and SE.
1.70	Wash, 5 lks. wide, course NW., gentle asc.
15.20	Spur, slopes NW., gentle desc.
20.70	Draw, course NW., gentle asc. 30 ft.
24.80	Spur, slopes N., gentle desc. over W. slope.
30.80	Wash, 5 lks. wide, course N., gentle asc. 31 ft.
34.40	Spur, slopes N., desc. 52 ft. over W. slope.
40.10	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 28 and 33, with brass cap mkd.
	$\frac{1}{4} \frac{S28}{S33}$ 1934
	from which
	A pinon, 20 ins. diam., bears S.47°W., 43 lks. dist., mkd. $\frac{1}{4}$ S33 BT.
	A pinon, 10 ins. diam., bears N.29°W., 22 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
40.80	Draw, 5 lks. wide, course N., asc. 81 ft. over NE. slope.
50.20	Ridge, bears NW. and SE., desc. 45 ft. over SW. slope.
57.20	Wash, 5 lks. wide, course NW., gentle asc.
69.70	Ridge, bears NW. and SE., gradual desc. 70 ft. over SW. slope.
80.20	The cor. of secs. 28, 29, 32, and 33.
	Land, rolling. Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

chains	
	N.0°03'W., bet. secs. 28 and 29.
	Asc. 35 ft. over rolling land, through a scattering growth of timber and undergrowth.
7.00	Ridge, bears NW. and SE., desc. 45 ft. over NE. slope.
13.70	Draw, 10 lks. wide, course N.60°W., asc. 35 ft. over SW. slope.
20.50	Ridge, bears N.60°W. and S.60°E., desc. 70 ft. over NE. slope.
38.50	Draw, course N.75°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 28 and 29, with brass cap mkd.
	$\frac{1}{4}$ S29 S28 1934
	from which
	A juniper, 10 ins. diam., bears N.32 $\frac{1}{2}$ °E., 73 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
	A juniper, 8 ins. diam., bears S.16 $\frac{1}{4}$ °W., 57 lks. dist., mkd. $\frac{1}{4}$ S29 BT.
	Gentle asc. over S. slope.
49.50	Low ridge, bears E. and W., desc. 100 ft. over N. slope.
70.60	Gulch, 12 lks. wide, 4 ft. deep, course N.70°W., asc. 50 ft. over rolling SW. slope.
71.40	Road, bears N.70°W. and S.70°E.
74.60	Drain, course W., continue gentle asc.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20, 21, 28, and 29, with brass cap mkd.
	T38N RLW S20 S21 S29 S28 1934
	from which
	A pinon, 10 ins. diam., bears N.59 $\frac{1}{4}$ °E., 102 lks. dist., mkd. T38N RLW S21 BT.
	A pinon, 16 ins. diam., bears S.28°E., 143 lks. dist., mkd. T38N RLW S28 BT.
	A pinon, 12 ins. diam., bears S.66 $\frac{1}{2}$ °W., 114 lks. dist., mkd. T38N RLW S29 BT.
	A pinon, 12 ins. diam., bears N.38 $\frac{3}{4}$ °W., 15 lks. dist., mkd. T38N RLW S20 BT.
	Land, rolling.
	Soil, gravelly and sandy loam, 2nd and 3rd rates.
	Timber, pinon and juniper.
	Undergrowth, sagebrush and cliffrose.

chains	N.89°52'E., on a random line, bet. secs. 21 and 28.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect N. and S. line 7 lks. N. of the cor. of secs. 21, 22, 27, and 28.
	Thence
	S.89°55'W., on true line, bet. secs. 21 and 28.
	Gentle asc. over rolling land, through a scattering growth of timber and undergrowth.
3.00	Low spur, slopes SW., desc. 40 ft. over NW. slope.
16.00	Head of draw, course NW., gentle asc.
25.00	Spur, slopes NW., along rolling N. slope.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 21 and 28, with brass cap mkd.
	$\frac{1}{4} \frac{S21}{S28}$ 1934
	from which
	A juniper, 12 ins. diam., bears S.35 $\frac{1}{2}$ °W., 93 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
	A pinon, 6 ins. diam., bears N.30 $\frac{3}{4}$ °W., 138 lks. dist. mkd. $\frac{1}{4}$ S21 BT.
43.50	Low spur, slopes N.75°W., desc. 65 ft. over rolling SW. slope.
70.00	Draw, course SW., asc. 85 ft. over SE. slope.
76.50	Spur, slopes S., desc. 35 ft. over SW. slope.
80.02	The cor. of secs. 20, 21, 28, and 29.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°03'W., bet. secs. 20 and 21.
	Asc. 50 ft. over rolling SW. slope, through a scattering growth of timber and undergrowth.
8.00	Spur, slopes N.75°W., desc. 100 ft. over N. and NW. slope.
25.80	Wash, 10 lks. wide, course SW., asc. 92 ft. over S. slope.
36.60	Ridge, bears E. and W. gentle desc.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{2}$ sec. cor. of secs. 20 and 21, with brass cap mkd.

SUBDIVISION of T. 38 N., R. 1 W.

55

BOOK 4041

chains

$$\frac{1}{4}$$

$$\begin{array}{c} \text{S20} | \text{S21} \\ \hline 1934 \end{array}$$

from which

A juniper, 20 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ E., 100 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

A juniper, 6 ins. diam., bears S. 85° W., 93 lks. dist., mkd. $\frac{1}{4}$ S20 BT.

Desc. 129 ft. over rolling N. slope.

60.30 Wash, 10 lks. wide, course W., asc. 79 ft. over gentle SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 16, 17, 20, and 21, with brass cap mkd.

$$\begin{array}{c} \text{T38N RLW.} \\ \text{S17} | \text{S16} \\ \hline \text{S20} | \text{S21} \\ \hline 1934 \end{array}$$

from which

A juniper, 16 ins. diam., bears N. 22° E., 59 lks. dist., mkd. T38N RLW S16 BT.

A pinon, 12 ins. diam., bears S. $73\frac{1}{4}^{\circ}$ E., 195 lks. dist., mkd. T38N RLW S21 BT.

A pinon, 6 ins. diam., bears S. 36° W., 154 lks. dist., mkd. T38N RLW S20 BT.

A pinon, 10 ins. diam., bears N. $41\frac{1}{4}^{\circ}$ W., 132 lks. dist., mkd. T38N RLW S17 BT.

Land, rolling.

Soil, gravelly and sandy loam, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

N. $89^{\circ}55'$ E., on a random line bet. secs. 16 and 21.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.16 Intersect N. and S. line, 7 lks. S. of the cor. of secs. 15, 16, 21, and 22.

Thence

S. $89^{\circ}52'$ W., on true line bet. secs. 16 and 21.

Desc. 76 ft. over rolling SW. slope, through a scattering growth of timber and undergrowth.

38.66 Draw, course SW., continue gentle desc.

40.08 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 16 and 21, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} \text{S16} \\ \hline \text{S21} \end{array}$$

1934

from which

SUBDIVISION of T. 38 N., R. 1 W

chains

A juniper, 14 ins. diam., bears S.0 $\frac{3}{4}$ °W., 228 lks.
dist., mkd. $\frac{1}{4}$ S21 BT.

A pinon, 12 ins. diam., bears N.29 $\frac{1}{2}$ °W., 200 lks.
dist., mkd. $\frac{1}{4}$ S16 BT.

Continue over rolling land.

80.16 The cor. of secs. 16,17,20, and 21.

Land, rolling.

Soil, gravelly and sandy loam, 2nd and 3rd rates.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

N.0°03'W., bet. secs. 16 and 17.

Gentle asc. over rolling land, through a scattering
growth of timber and undergrowth.

5.00 Wide ridge, bears E. and W., desc. 34 ft. over N. slope.

15.50 Wash, 10 lks. wide, course W., gentle asc.

30.00 Spur, slopes W., gentle desc.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground to bedrock, and in a mound of stone to top, for
 $\frac{1}{4}$ sec. cor. of secs. 16 and 17, with brass cap mkd.

$\frac{1}{4}$

S17 | S16

1934

from which

A juniper, 26 ins. diam., bears S.61 $\frac{3}{4}$ °E., 176 lks.
dist., mkd. $\frac{1}{4}$ S16 BT.

A juniper, 16 ins. diam., bears S.83 $\frac{3}{4}$ °W., 80 lks.
dist., mkd. $\frac{1}{4}$ S17 BT.

Gentle desc. over NE. slope.

44.00 Wash, 10 lks. wide, course NW., asc. 45 ft. over SW. slope

57.50 Ridge, bears NW. and SE., gentle desc.

67.00 Draw, course NW., gentle asc.

75.50 Low ridge, bears NW. and SE., gentle desc.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the
ground to bedrock, and in a mound of stone to top, for
cor. of secs. 8,9,16, and 17, with brass cap mkd.

T38N RLW

S8, S9

S17 | S16

1934

from which

A pinon, 8 ins. diam., bears N.40 $\frac{1}{4}$ °E., 76 lks.
dist., mkd. T38N RLW S9 BT.

A juniper, 10 ins. diam., bears S.13 $\frac{3}{4}$ °E., 185 lks.
dist., mkd. T38N RLW S16 BT.

SUBDIVISION of T. 38 N., R. 1 W.

57

BOOK 4041

chains

A pinon, 12 ins. diam., bears S.44 $\frac{1}{2}$ °W., 134 lks. dist., mkd. T38N RLW S17 BT.

A pinon, 16 ins. diam., bears N.72 $\frac{1}{4}$ °W., 168 lks. dist., mkd. T38N RLW S8 BT.

Land, rolling.

Soil, gravelly and sandy loam, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

N.89°52'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect the cor. of secs. 9,10,15, and 16.

Thence

S.89°52'W., on true line bet. secs. 9 and 16.

Desc. 45 ft. over rolling W. slope, through a scattering growth of timber and undergrowth.

24.18 Draw, course N., (from SE.) gentle asc.

31.10 Spur, slopes NW., gentle desc.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 9 and 16, with brass cap mkd.

$$\frac{1}{4} \frac{S9}{S16}$$

1934

from which

A pinon, 16 ins. diam., bears S.18 $\frac{1}{2}$ °E., 30 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

A pinon, 12 ins. diam., bears N.14°W., 56 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Desc. 34 ft. over general SW. slope.

50.58 Wash, 5 lks. wide, course NW., continue gentle desc.

58.10 Low spur, slopes NW., desc. 70 ft. over SW. slope.

62.60 Wash, 20 lks. wide, course NW., asc. 155 ft. over NE. slope.

69.80 Spur, slopes N., desc. 30 ft. over W. slope.

73.70 Ravine, course N., asc. 59 ft. over NE. slope.

80.08 The cor. of secs. 8,9,16, and 17.

Land, rolling and hilly.

Soil, gravelly and sandy loam, 3rd and 4th rates.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
	N.0°03'W., bet. secs. 8 and 9.
	Desc. gentle NE. slope, over mountainous land, through a scattering growth of timber and undergrowth.
1.40	S. rim of canyon, bears E. and W., desc. 285 ft. over steep, broken N. slope.
8.00	Wash in bottom of canyon, 10 lks. wide, course N.60°W., asc. 280 ft. over broken SW. slope.
17.30	Rocky point on S. rim of Snake Canyon, rim bears SE. and NE., desc. 520 ft. over steep, broken NW.
38.90	Gulch, 8 lks. wide, course NW., asc. 20 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 8 and 9, with brass cap mkd.
	$\frac{1}{4}$ s8 s9 1934
	from which
	A pinon, 12 ins. diam., bears S.48 $\frac{1}{4}$ °E., 69 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
	A pinon, 10 ins. diam., bears N.63 $\frac{1}{4}$ °W., 112 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
	Asc. 15 ft. over SW. slope.
41.00	Spur, slopes W., desc. 130 ft. over broken NW. slope.
47.25	Snake Canyon, wash in bottom 12 lks. wide, 8 ft. deep, course S.60°W.
49.40	Road, bears S.60°W. and N.60°E., begin asc. 400 ft. over steep, broken S. slope.
61.00	N. rimrock of Snake Canyon, approx. 90 ft. high, bears N.60°E. and S.60°W., asc. 75 ft. over broken S. slope.
76.65	Wide ridge and road along top, bears E. and W., gentle desc.
80.00	Set iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 4, 5, 8, and 9, with brass cap mkd.
	T38N RLW S5 S4 s8 s9 1934
	from which
	A juniper, 16 ins. diam., bears N.22 $\frac{1}{2}$ °E., 106 lks. dist., mkd. T38N RLW S4 BT.
	A pinon, 10 ins. diam., bears S.6°E., 46 lks. dist., mkd. T38N RLW S9 BT.
	A pinon, 12 ins. diam., bears S.85 $\frac{1}{2}$ °W., 61 lks. dist., mkd. T38N RLW S8 BT.
	A pinon, 14 ins. diam., bears N.71 $\frac{3}{4}$ °W., 122 lks. dist., mkd. T38N RLW S5 BT.

SUBDIVISION of T. 38 N., R. 1 W.

59

BOOK 4041

chains

Land, mountainous.
Soil, gravelly and rocky, 3rd rate.
Timber, pinon and juniper.
Undergrowth, sagebrush, cliffrose, and service.

N.89°52'E., on a random line, bet. secs. 4 and 9

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 Intersect N. and S. line, 23 lks. N. of the cor. of secs. 3, 4, 9, and 10.

Thence

N.89°58'W., on true line bet. secs. 4 and 9.

Asc. 200 ft. along broken S. slope, over sandstone cliffs, through a scattering growth of timber and undergrowth.

18.50 Rimrock, approx. 100 ft. high, bears N.80°E. and S.60°W., asc. 90 ft. over rocky SE. slope.

27.80 N. rimrock of Snake Canyon, bears N.80°E. and S.60°W., gradual asc. over SE. slope.

35.30 Ridge, bears N.60°E. and S.60°W., desc. gentle NW. slope.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 4 and 9, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$

1934

from which

A juniper, 12 ins. diam., bears S.32 $\frac{1}{4}$ °W., 67 lks. dist., mkd. $\frac{1}{4}$ S 9 BT.

A juniper, 14 ins. diam., bears N.19 $\frac{1}{4}$ °W., 95 lks. dist., mkd. $\frac{1}{4}$ S 4 BT.

Desc. 50 ft. along rolling N. slope.

53.90 Drain, course N.20°W., continue along rolling N. slope.

59.20 Old road, bears N.60°E. and S.60°W.

60.50 Drain, course N., continue along rolling N. slope.

66.70 Wood road, bears N. and S.

79.98 The cor. of secs. 4, 5, 8, and 9.

Land, mountainous and rolling.
Soil, stony and sandy loam, 3rd and 4th rates.
Timber, pinon and juniper.
Undergrowth, sagebrush, cliffrose, and service.

chains	N.0°12'E., on a random line bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.18	Intersect N. bdy. of the Tp. at a point 14 lks. W. of the cor. of secs. 4 and 5 only hereinbefore described.
	Thence
	S.0°18'W., on true line bet. secs. 4 and 5.
	Desc. gentle SW. slope, over rolling land, through a scattering growth of timber and undergrowth.
6.68	Draw, course W. (for 3 chs. thence N.30°W.), gentle asc.
17.80	Low ridge, bears E. and W., gentle desc.
21.18	Wash, course W., asc. 40 ft. over N. slope.
21.30	Old road, bears E. and W.
34.20	Spur, slopes NW., desc. 37 ft. over SW. slope.
39.18	Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 4 and 5, with brass cap mkd.
	$\frac{1}{4}$
	S5 S4
	1934
	from which
	A pinon, 14 ins. diam., bears S.63 $\frac{3}{4}$ °E., 224 lks. dist., mkd. $\frac{1}{4}$ S 4 BT.
	A pinon, 10 ins. diam., bears N.88 $\frac{1}{2}$ °W., 208 lks. dist., mkd. $\frac{1}{4}$ S 5 BT.
	Desc. 34 ft. over rolling SW. slope.
54.20	Draw, course NW., gradual asc. 97 ft. over N. slope.
79.18	The cor. of secs. 4, 5, 8, and 9.
	Land, rolling.
	Soil, gravelly and sandy loam, 2nd and 3rd rates.
	Timber, pinon and juniper.
	Undergrowth, sagebrush, cliffrose, and service.

SUBDIVISION of T. 38 N., R. 1 W.

4041

chains

From the cor. of secs. 5, 6, 31, and 32, on S. bdy. of the Tp., described in Book "C" of this group.

N.0°03'W., bet. secs. 31 and 32.

Desc. gentle NE. slope, over rolling land, through a scattering growth of timber and undergrowth.

- 7.20 Drain, course NW., gentle asc. over SW. slope.
 15.00 Spur, slopes NW., desc. 45 ft. over gentle N. slope.
 26.80 Road, bears E. and W.
 28.20 Wash, 12 lks. wide, course W., asc. 36 ft. over S. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 31 and 32, with brass cap mkd.

$\frac{1}{4}$
 S31 | S32
 1934

from which

A juniper, 12 ins. diam., bears S.17 $\frac{1}{2}$ °E., 126 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A juniper, 10 ins. diam., bears N.53 $\frac{1}{2}$ °W., 33 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Gentle asc. over rolling S. slope.

- 52.00 Ridge, bears E. and W., desc. 50 ft. over gentle NE. slope
 65.40 Draw, course N.60°W., gentle asc.
 75.00 Spur, slopes W., desc. 20 ft. over N. slope.
 79.00 Drain, course W., asc. SW. slope.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29, 30, 31, and 32, with brass cap mkd.

T38N RLW
 S30 | S29
 S31 | S32

1934

from which

A juniper, 16 ins. diam., bears N.67 $\frac{1}{4}$ °E., 123 lks. dist., mkd. T38N RLW S29 BT.

A juniper, 10 ins. diam., bears S.51 $\frac{3}{4}$ °E., 92 lks. dist., mkd. T38N RLW S32 BT.

A juniper, 18 ins. diam., bears S.58°W., 67 lks. dist., mkd. T38N RLW S31 BT.

A juniper, 16 ins. diam., bears N.42 $\frac{1}{4}$ °W., 125 lks. dist., mkd. T38N RLW S30 BT.

Land, rolling.

Soil, gravelly and sandy loam, 2nd and 3rd rates.

Timber, juniper and pinon.

Undergrowth, sagebrush and cliffrose.

SUBDIVISION of T. 38 N., R. 1 W.

chains	East, on a random line bet. secs. 29 and 32.
40.00	set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 4 lks. S. of the cor. of secs. 28, 29, 32, and 33.
	Thence
	S. $89^{\circ}58'W.$, on true line bet. secs. 29 and 32.
	Desc. gentle SW. slope over rolling land, through a scattering growth of timber and undergrowth.
17.80	Wash, 10 lks. wide, course NW., continue gentle desc.
31.00	Same wash, course S. $70^{\circ}W.$, continue gentle desc.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 29 and 32, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S29}{S32}$
	1934
	from which
	A pinon, 14 ins. diam., bears N. $39\frac{1}{2}^{\circ}E.$, 195 lks. dist., mkd. $\frac{1}{4}$ S29 BT.
	A juniper, 12 ins. diam., bears S. $6\frac{3}{4}^{\circ}W.$, 414 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
40.15	Wash, 8 lks. wide, course N. $75^{\circ}W.$, gentle desc.
46.90	Draw, 6 lks. wide, course NW., asc. 45 ft. over NE. slope.
61.00	Drain, course N. $15^{\circ}E.$, gentle asc. over rolling NE. slope.
74.00	Spur, slopes NW., gentle desc. over SW. slope.
80.00	The cor. of secs. 29, 30, 31, and 32.
	Land, rolling. Soil, gravelly and sandy loam, 1st to 3rd rate. Timber, juniper and pinon. Undergrowth, sagebrush and cliffrose.

	West, on a random line bet. secs. 30 and 31.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.18	Intersect the W. bdy. of the Tp., 4 lks. S. of the cor. of secs. 25, 30, 31, and 36, hereinbefore described.
	Thence
	S. $89^{\circ}58'E.$, on true line bet. secs. 30 and 31.
	Gradual asc. 65 ft. over rolling SW. slope, through a scattering growth of timber and undergrowth.
21.20	Spur, slopes N. $70^{\circ}W.$, remains of prehistoric stone cabins along spur at this point, gradual desc. 30 ft. over NE. slope.
36.90	Draw, course NW., gentle asc. over SW. slope.

SUBDIVISION of T. 38 N., R. 1 W.

63

BLK 4041

chains	
39.18	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 30 and 31, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S30}{S31}$</p> <p style="text-align: center;">1934</p> <p style="text-align: right;">from which</p> <p>A juniper, 6 ins. diam., bears S.48°W., 84 lks. dist., mkd. $\frac{1}{4}$ S31 BT.</p> <p>A juniper, 7 ins. diam., bears N.36$\frac{1}{2}$°W., 79 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>Gradual asc. 39 ft. over rolling SW. slope.</p>
51.20	Ridge, bears NW. and SE., desc. 35 ft. over NE. slope.
69.50	Draw, course NW., gradual asc. 39 ft. over SW. slope.
79.18	The cor. of secs. 29, 30, 31, and 32.
	<p>Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.</p> <p>-----</p> <p>N.0°03'W., bet. secs. 29 and 30.</p> <p>Asc. gentle SW. slope, over rolling land, through a scattering growth of timber and undergrowth.</p>
7.80	Low spur, slopes NW., desc. 111 ft. over rolling NE. slope
26.30	Wash, 10 lks. wide, 2 ft. deep, course N.60°W., continue gentle desc.
32.90	Wash, 15 lks. wide, 3 ft. deep, course N.60°W., gentle asc. over SW. slope.
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 29 and 30, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S30 S29</p> <p style="text-align: center;">1934</p> <p style="text-align: right;">from which</p> <p>A pinon, 8 ins. diam., bears N.51$\frac{1}{4}$°E., 165 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>A juniper, 8 ins. diam., bears N.86$\frac{1}{2}$°W., 325 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>Gentle asc. over rolling SW. slope.</p>
42.20	Ridge, bears NW. and SE., desc. 77 ft. over NE. slope.
52.20	Draw, course NW., continue gentle desc.
54.20	Low spur, slopes NW., continue desc.
60.90	Wash, course NW., continue desc.

SUBDIVISION of T 38 N., R. 1 W.

chains	
65.50	Spur, slopes NW., gradual desc. over NE. slope.
73.90	Wash, 10 lks. wide, 2 ft. deep, course NW., gentle asc.
78.50	Spur, slopes NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 19, 20, 29, and 30, with brass cap mkd.
	T38N RLW S19 S20 S30 S29 1934
	from which
	A juniper, 8 ins. diam., bears N.40 $\frac{1}{2}$ °E., 202 lks. dist., mkd. T38N RLW S20 BT.
	A juniper, 5 ins. diam., bears S.64 $\frac{1}{2}$ °E., 328 lks. dist., mkd. T38N RLW S29 BT.
	A pinon, 5 ins. diam., bears S.49°W., 96 lks. dist., mkd. T38N RLW S30 BT.
	A juniper, 10 ins. diam., bears N.61 $\frac{3}{4}$ °W., 254 lks. dist., mkd. T38N RLW S19 BT.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.89°58'E., on a random line bet. secs. 20 and 29.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.80	Intersect N. and S. line 7 lks. N. of the cor. of secs. 20, 21, 28, and 29.
	Thence
	N.89°59'W., on true line bet. secs. 20 and 29.
	Desc. 67 ft. over rocky SW. slope, through a scattering growth of timber and undergrowth.
4.65	Road, bears NW. and SE.
6.90	Wash, 15 lks. wide, 10 ft. deep, course NW., along N. slope
11.95	Draw, course NE., asc. 106 ft. over rolling E. slope.
13.30	Short spur, slopes NE., continue gentle asc.
23.80	Spur, slopes N.70°W., (from S.30°E.) along rolling S. slope.
33.80	Short spur, slopes SE., gentle desc.
39.90	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 20 and 29, with brass cap mkd.

chains	
	$\frac{1}{4} \frac{S20}{S29}$ 1934 from which A pinon, 7 ins. diam., bears N.71°E., 72 lks. dist., mkd. $\frac{1}{4}$ S20 BT. A juniper, 16 ins. diam., bears S.30°E., 85 lks. dist., mkd. $\frac{1}{4}$ S29. BT. Desc. 41 ft. along rolling S. slope. 59.80 Bend in gulch, course SW., (from S.75°E.) gentle asc. 69.40 Spur, slopes SW., along rolling N. slope. 79.80 The cor. of secs. 19, 20, 29, and 30. Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.89°58'W., on a random line bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.99	Intersect the W. bdy. of the Tp. 5 lks. N. of the cor. of secs. 19, 24, 25, and 30, hereinbefore described.
	Thence
	East, on true line bet. secs. 19 and 30.
	Over rolling land, through a scattering growth of timber and undergrowth.
0.20	Ridge, bears S.15°W. and N.75°E., asc. 45 ft. over rolling SW. slope.
6.15	Road, bears N.80°W. and S.80°E.
25.00	Draw, course S.75°W., continue gentle asc.
35.50	Same draw, course NW., (for 3 chs. thence W.) gentle asc.
38.99	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 19 and 30, with brass cap mkd.
	$\frac{1}{4} \frac{S19}{S30}$ 1934 from which A pinon, 10 ins. diam., bears N.32 $\frac{1}{2}$ °E., 41 lks. dist., mkd. $\frac{1}{4}$ S19 BT. A juniper, 14 ins. diam., bears S.3 $\frac{1}{4}$ °W., 58 lks. dist., mkd. $\frac{1}{4}$ S30 BT. Gentle asc. over rolling SW. slope. 42.20 Road, bears SW. and NE.

chains	
46.30	Ridge, bears NW. and SE., gentle desc.
51.70	Wash, 10 lks. wide, course N.30°W., gentle asc.
55.00	Low ridge, bears NW. and SE., desc. rolling NE. slope.
65.00	Wash, course N.30°W., gentle asc.
69.50	Spur, slopes NW., gradual asc.
74.00	Draw, course NW., gradual asc. 23 ft. over W. slope.
78.99	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling. Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.0°03'W., bet. secs. 19 and 20.
	Desc. 15 ft. over rolling NE. slope, through a scattering growth of timber and undergrowth.
11.00	Draw, course NW., gentle asc. over S. slope.
15.60	Low spur, slopes SW., desc. 30 ft. over NW. slope.
23.50	Draw, course S.60°W., gentle asc. 20 ft. over S. slope.
24.80	Road, bears NE. and SW.
31.00	Spur, slopes SW., desc. 21 ft. over rolling N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 19 and 20, with brass cap mkd.
	$\frac{1}{4}$ S19 S20 1934
	from which
	A pinon, 10 ins. diam., bears N.52 $\frac{3}{4}$ °E., 144 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	A juniper, 8 ins. diam., bears N.80 $\frac{1}{2}$ °W., 83 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
46.70	Wash, 10 lks. wide, 6 ft. deep, course S.60°W., asc. 25 ft. over SE. slope.
50.00	Spur, slopes W., continue over rolling land.
59.60	Wash, course NE., gentle asc.
68.00	Low spur, slopes NE., desc. 70 ft. along W. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 17, 18, 19, and 20, with brass cap mkd.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains

T38N RLW

S18 S17

S19 S20

1934

from which

A juniper, 14 ins. diam., bears N.39 $\frac{1}{2}$ °E., 150 lks. dist., mkd. T38N RLW S17 BT.

A juniper, 10 ins. diam., bears S.85 $\frac{1}{4}$ °E., 79 lks. dist., mkd. T38N RLW S20 BT.

A juniper, 12 ins. diam., bears S.62 $\frac{1}{4}$ °W., 88 lks. dist., mkd. T38N RLW S19 BT.

A juniper, 14 ins. diam., bears N.60 $\frac{1}{2}$ °W., 51 lks. dist., mkd. T38N RLW S18 BT.

Land, rolling.

Soil, gravelly and sandy loam, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

S.89°59'E., on a random line bet. secs. 17 and 20.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.74 Intersect N. and S. line 7 lks. N. of the cor of secs. 16, 17, 20, and 21.

Thence

N.89°56'W., on true line bet. secs. 17 and 20.

Desc. 60 ft. over rolling SW. slope, through a scattering growth of timber and undergrowth.

15.34 Draw, course NW., gentle asc.

27.64 Low spur, slopes NW., desc. 25 ft. over SW. slope.

31.55 Draw, course NW., gradual asc.

39.87 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 17 and 20, with brass cap mkd.

$\frac{1}{4}$ $\frac{S17}{S20}$

1934

from which

A juniper, 8 ins. diam., bears N.47°E., 186 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

A pinon, 12 ins. diam., bears S7 $\frac{1}{4}$ °E1, 144 lks. dist., mkd. $\frac{1}{4}$ S20 BT.

40.65 Spur, slopes NW., desc. 55 ft. over rolling SW. slope.

54.25 Draw, course NW., gentle asc.

59.65 Short spur, slopes NW., desc. 80 ft. over SW. slope.

67.55 Wash, 8 lks. wide, course N.30°W., asc. 80 ft. over rolling NE. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
75.15	Spur, slopes N.15°E., desc. 40 ft. over W. slope.
78.65	Across head of draw, course N.30°W., gentle asc.
79.74	The cor. of secs. 17,18,19, and 20.
	Land, rolling. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	West, on a random line bet. secs., 18 and 19.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.80	Intersect the W. bdy. of the Tp., 16 lks. S. of the cor. of secs. 13,18,19, and 24, hereinbefore described.
	Thence
	S.89°53'E., on true line bet. secs. 18 and 19.
	Desc. gentle E. slope, over rolling land, through a scattering growth of timber and undergrowth.
1.30	Draw, course S.20°E., gentle asc.
6.80	Spur, slopes, SE., gradual asc. 20 ft.
16.40	Draw, course SE., continue over rolling land.
38.80	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 18 and 19, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S18}{S19}$
	1934
	from which
	A pinon, 10 ins. diam., bears N.56 $\frac{3}{4}$ °E., 56 lks. dist., mkd. $\frac{1}{4}$ S18 BT.
	A juniper, 8 ins. diam., bears S.58 $\frac{1}{2}$ °E., 92 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Continue over rolling land.
52.40	Spur, slopes NW., gentle desc.
63.90	Small draw, course N.15°E.
65.90	Spur, slopes N., gentle desc. 30 ft.
67.50	Head of ravine, course N.20°W., asc. 25 ft. over NE. slope.
69.50	Spur, slopes N., desc. 50 ft. over SE. slope.
77.50	Draw, course NE., asc, 10 ft. to cor.
78.80	The cor. of secs. 17,18,19, and 20.
	Land, rolling. Soil, gravelly and sandy loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

SUBDIVISION of T. 38 N., R. 1 W.

BOOK 4041

chains	
	N.0°03'W., bet. secs. 17 and 18.
	Desc. 30 ft. over rolling NW. slope, through a scattering growth of timber and undergrowth.
1.12	Small ravine, course N.20°E., gentle asc.
5.00	Short spur, slopes NE., desc. 68 ft. over N. slope.
13.20	Draw, course NW., continue over rolling land..
15.50	Gulch, 10 lks. wide, course W., asc. 40 ft. over S. slope.
20.50	Spur, slopes W., gentle desc.
27.00	Draw, course W., asc. 90 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 17 and 18, with brass cap mkd.
	$\frac{1}{4}$ S18 S17 1934
	from which
	A juniper, 14 ins. diam., bears S.75 $\frac{1}{2}$ °E., 55 lks. dist., mkd. $\frac{1}{4}$ S17 BT.
	A pinon, 12 ins. diam., bears S.77 $\frac{3}{4}$ °W., 57 lks. dist., mkd. $\frac{1}{4}$ S18 BT.
	Desc. 120 ft. over rolling NE. slope.
56.20	Gulch, 10 lks. wide, course N.60°W., asc. 110 ft. over SW. slope.
72.50	Spur, slopes N.60°W., gentle desc.
77.60	Draw, course N.60°W., gradual asc.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 7, 8, 17, and 18, with brass cap mkd.
	T38N RLW S7 S8 S18 S17 1934
	from which
	A pinon, 8 ins. diam., bears N.30 $\frac{1}{2}$ °E., 81 lks. dist., mkd. T38N RLW S8 BT.
	A juniper, 22 ins. diam., bears S.35 $\frac{3}{4}$ °E., 72 lks. dist., mkd. T38N RLW S17 BT.
	A pinon, 12 ins. diam., bears S.60°W., 17 lks. dist., mkd. T38N RLW S18 BT.
	A juniper, 10 ins. diam., bears N.17°W., 116 lks. dist. mkd. T38N RLW S7 BT.
	Land, rolling.
	Soil, gravelly and stony clay loam, 3rd rate.
	Timber, pinon and juniper.
	Undergrowth, sagebrush and cliffrose.

chains	S.89°56'E., on a random line bet. secs. 8 and 17.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.82	Intersect N. and S. line 9 lks. N. of the cor. of secs. 8, 9, 16, and 17.
	Thence
	N.89°52'W., on true line bet. secs. 8 and 17.
	Gentle asc. over rolling land, through a scattering growth of timber and undergrowth.
1.80	Low spur, slopes N., gentle desc.
3.80	Rim of canyon, bears NE. and SW., leave rolling, enter mountainous land, desc. 200 ft. over NW. slope.
11.25	Ravine, course N.30°W., asc. 195 ft. over NE. slope.
19.90	Rim of canyon, bears NW. and SE., leave mountainous, enter rolling land, gentle desc. 20 ft. over SW. slope.
39.91	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 8 and 17, with brass cap mkd.
	$\frac{1}{4} \frac{S 8}{S 17}$
	1934
	from which
	A pinon, 8 ins. diam., bears N.50°E., 172 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.
	A pinon, 10 ins. diam., bears S.60°E., 207 lks. dist., mkd. $\frac{1}{4}$ S 17 BT.
	Desc. 115 ft. over rolling SW. slope.
54.40	Draw, course N.15°W., continue desc.
72.60	Wash, 8 lks. wide, course NW., gentle asc.
73.60	Low spur, slopes N., gentle desc.
74.57	Drain, course N.30°E., asc. 25 ft. over E. slope.
78.20	Low spur, slopes NW., gentle desc. 24 ft.
79.82	The cor. of secs. 7, 8, 17, and 18.
	Land, rolling and mountainous. Soil, gravelly and stony clay loam, 3rd rate. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N.89°53'W., on a random line bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.42	Intersect the W. bdy. of the Tp., 2 lks. N. of the cor. of secs. 7, 12, 13, and 18, hereinbefore described.
	Thence

SUBDIVISION of T. 38 N., R. 1 W.

71

BOOK 4041

chains

S. 89° 54' E., on true line bet. secs. 7 and 18.

Abrupt asc. 125 ft. over SW. slope, through a scattering growth of timber and undergrowth.

3.90 Sharp spur, slopes S., desc. 170 ft. over steep E. slope.

12.20 Gulch, 20 lks. wide, course SW., asc. 80 ft. over W. slope.

14.40 Spur, slopes N., desc. 45 ft. over NE. slope.

17.10 Same gulch, course N. 30° W., asc. 227 ft. over broken W. slope.

28.40 Spur, slopes NW., gentle desc. over NE. slope.

38.42 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 7 and 18, with brass cap mkd.
$$\frac{S 7}{\frac{1}{4} S 18}$$

1934

from which

A pinon, 16 ins. diam., bears N. 39 $\frac{1}{4}$ ° E., 80 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.A pinon, 14 ins. diam., bears S. 67° E., 99 lks. dist., mkd., $\frac{1}{4}$ S 18 BT.

39.90 Rim of canyon, bears N. 80° W. and S., desc. 90 ft. over E. slope.

43.60 Bottom of rocky canyon, 10 lks. wide, course N. 10° E., asc. 120 ft. over SW. slope.

59.40 Spur, slopes NW., desc. 45 ft. over NE. slope.

63.60 Ravine, course NW., asc. 90 ft. over SW. slope.

78.42 The cor. of secs. 7, 8, 17, and 18.

Land, mountainous.

Soil, gravelly and stony, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush, cliffrose, and service.

N. 0° 03' W., on true line bet. secs. 7 and 8.

Asc. gentle SW. slope, over mountainous land, through a scattering growth of timber and undergrowth.

3.00 Low spur, slopes NW., desc. 24 ft. over N. slope.

5.50 S. rim of Snake Canyon, bears NW. and S. 75° E., desc. 625 ft. over steep, broken N. slope.

19.74 Ravine, course NW., continue desc. over NW. slope.

27.80 Snake Canyon, wash in bottom, 20 lks. wide, 8 ft. deep, course W., across bottom of canyon.

28.80 Road, bears E. and W.

31.00 Base of cliffs, bears E. and W., asc. 490 ft. over steep, broken S. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
40.00	Set an iron post, 3 ft. long, 1 in. diam., on bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 7 and 8, with brass cap mkd.
	$\frac{1}{4}$ S7 S8 1934
	from which
	A pinon, 10 ins. diam., bears N.78°E., 227 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.
	A pinon, 6 ins. diam., bears S.84 $\frac{3}{4}$ °W., 90 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.
	Asc. 115 ft. over broken S. slope.
42.50	N. rim of Snake Canyon, bears E. and W., leave scattering, enter heavy timber, over rolling mesa.
44.00	Small draw, course W., gentle asc.
58.00	Ridge, bears E. and W., desc. 37 ft. over N. slope.
69.90	Ravine, course W., asc. 70 ft. along SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 5, 6, 7, and 8, with brass cap mkd.
	T38N RLW S6 S5 S7 S8 1934
	from which
	A pinon, 10 ins. diam., bears N.21 $\frac{1}{2}$ °E., 64 lks. dist., mkd. T38N RLW S5 BT.
	A juniper, 12 ins. diam., bears S.49 $\frac{3}{4}$ °E., 48 lks. dist., mkd. T38N RLW S8 BT.
	A pinon, 10 ins. diam., bears S.52°W., 25 lks. dist., mkd. T38N RLW S7 BT.
	A pinon, 12 ins. diam., bears N.34 $\frac{3}{4}$ °W., 99 lks. dist., mkd. T38N RLW S6 BT.
	Land, mountainous and rolling. Soil, gravelly and stony, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.

	S.89°52'E., on a random line bet. secs. 5 and 8.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line 18 lks. S. of the cor. of secs. 4, 5, 8, and 9.
	Thence

SUBDIVISION of T. 38 N., R. 1 W.

4041

chains	
	West, on true line bet. secs. 5 and 8.
	Over rolling land, through a scattering growth of timber and undergrowth.
9.86	Old road, bears N. and S.
17.40	Road, bears NW. and SE.
20.00	Spur, slopes NE., continue over rolling land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 5 and 8, with brass cap mkd.
	$\frac{1}{4} \frac{S \ 5}{S \ 8}$
	1934
	from which
	A juniper, 12 ins. diam., bears S. $24\frac{1}{2}^{\circ}$ W., 228 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.
	A pinon, 6 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ W., 425 lks. dist., mkd. $\frac{1}{4}$ S 5 BT.
46.00	Desc. 40 ft. over SW. slope.
49.00	Draw, course NW., gradual asc. 23 ft. over NE. slope.
56.00	Short spur, slopes N., desc. 40 ft. over NW. slope.
62.00	Draw, course N., asc. 58 ft. over NE. slope.
74.00	Leave scattering, enter heavy timber, bears N. and S.
78.00	Ridge, bears N. and S., continue over rolling land.
80.00	The cor. of secs. 5, 6, 7, and 8.
	Land, rolling mesa. Soil, gravelly and sandy loam, 2nd and 3rd rates. Timber, pinon and juniper. Undergrowth, sagebrush and cliffrose.

	N. $89^{\circ}54'$ W., on a random line bet. secs. 6 and 7.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.22	Intersect the W. bdy. of the Tp. 5 lks. S. of the cor. of secs. 1, 6, 7, and 12, hereinbefore described.
	Thence
	S. $89^{\circ}52'$ E., on true line bet. secs. 6 and 7.
	Along broken S. slope over mountainous land, through a scattering growth of timber and undergrowth.
5.00	Begin desc. 40 ft. over rocky SE. slope.
8.70	Gulch, 20 lks. wide, course S. 70° W., asc. 66 ft. over rocky NW. slope.
12.40	Spur, slopes abruptly N., desc. 20 ft. over NE. slope.

SUBDIVISION of T. 38 N., R. 1 W.

chains	
15.40	Same gulch, course NW., asc. 280 ft. over broken SW. slope.
24.00	Spur, slopes S., desc. 200 ft. over broken SE. slope.
31.00	Same gulch, course SW.; asc. 90 ft. over NW. slope.
34.40	Spur, slopes N., desc. 30 ft. over NE. slope.
38.22	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 6 and 7, with brass cap mkd.
	$\frac{\frac{1}{4} \text{ S } 6}{\text{S } 7}$
	1934
	from which
	A juniper, 24 ins. diam., bears S. $13\frac{1}{4}^{\circ}$ W., 184 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.
	A pinon, 16 ins. diam., bears N. $10\frac{3}{4}^{\circ}$ W., 217 lks. dist., mkd. $\frac{1}{4}$ S 6 BT.
40.20	Draw, course NW., asc. 160 ft. over W. slope.
48.60	Short spur, slopes N. 20° W., asc. 15 ft. over NE. slope.
51.20	Draw, course N. 30° W., asc. 30 ft. over W. slope.
56.70	Short spur, slopes N., desc. 70 ft. over NE. slope.
67.50	Draw, course NW., asc. 115 ft. over SW. slope.
78.22	The cor. of secs. 5, 6, 7, and 8.
	Land, mountainous. Soil, gravelly and stony, 3rd and 4th rates. Timber, pinon and juniper. Undergrowth, sagebrush, cliffrose, and service.

	N. $0^{\circ}18'E.$, on a random line bet. secs. 5 and 6.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.34	Intersect N. bdy. of the Tp. at a point 7 lks. E. of the cor. of secs. 5 and 6 only, hereinbefore described.
	Thence
	S. $0^{\circ}15'W.$, on true line bet. secs. 5 and 6
	Asc. 59 ft. over rolling N. slope, through a heavy growth of timber and scattering undergrowth.
14.84	Low ridge, bears E. and W., gentle desc.
20.84	Wash, 10 lks. wide, course NW., gradual asc.
24.00	Leave heavy, enter scattering timber.
34.34	Road, bears NW. and SE.
35.00	Low ridge, bears NW. and S. 10° E., along rolling W. slope.
39.34	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 5 and 6, with brass cap mkd.

SUBDIVISION OF T. 38 N., R. 1 W.

75

4041

chains

s6 | s5

1934

from which

A pinion, 16 ins. diam., bears S.62 $\frac{1}{4}$ °E., 21 lks. dist.,
mkd. $\frac{1}{4}$ S 5 BT.

A pinion, 10 ins. diam., bears S.20 $\frac{1}{4}$ °W., 19 lks. dist.,
mkd. $\frac{1}{4}$ S 6 BT.

Desc. 68 ft. over rolling SW. slope.

- 53.94 Ravine, course SW., gentle asc.
56.15 Short spur, slopes SW., gentle desc.
60.34 Draw, course SW., continue over rolling land.
64.85 Draw, course W., asc. 100 ft. along rolling W. slope.
79.34 The cor. of secs. 5, 6, 7, and 8.

Land, rolling.

Soil, gravelly, stony, 3rd rate.

Timber, pinon and juniper.

Undergrowth, sagebrush and cliffrose.

FINAL TEST OF SOLAR ATTACHMENTS.

August 28, 1934: On the meridian hereinbefore described with Young & Sons transits Nos. 8478, 8592, and 8477, at 9h 00m, a.m. app. t., we set off 36°38 $\frac{1}{2}$ 'N. on the lat. arcs; 9°49'N. on the decl. arcs; and orient the instruments with the solar; the line of sight agrees with the meridian established by Polaris observation.

At 3h 00m p.m. app. t., we set off 36°38 $\frac{1}{2}$ 'N. on the lat. arcs; 9°43'N. on the decl. arcs; and repeat the test of the solar; the line of sight agrees with the meridian established by Polaris observation.

August 28, 1934.

GENERAL DESCRIPTION.

T. 38 N., R. 1 W., lies about 40 miles N. of the Grand Canyon of the Colorado River and about 20 miles SE. of Fredonia, Ariz., from which it is reached by a moderately good road which runs southerly through the most easterly tier of secs. Secondary roads branch to the west reaching every portion of the Tp.

The Tp. lies in the U.S. Kaibab National Forest and is generally rolling in character. The drainage is westerly by Snake Canyon, Nail Canyon, Warm Springs Canyon, and their tributary washes. Sea-level elevation is from 5,000 ft. in the western portion to 7,000 ft. in the eastern portion of the Tp.

There is a scattering growth of pinon and juniper timber, suitable only for fuel and fence posts and scrub sage, oakbrush, cliffrose, and service undergrowth.

Soil is generally of sandy, gravelly, and rocky origin of shallow depth.

No mineral was observed, although an old unused smelter was noted in sec. 13. Also U.S.F.S. Ranger Station and 1 main dwelling was noted at Ryan in the same sec.

There are no permanent springs or running water.

There is some fencing (mostly U.S.F.S. drift fences) and 2 small reservoirs used in connection with stock grazing.

There are numerous old Indian petroglyphs, both painted and carved, at the bottom of the North rim of Snake Canyon. These extend for some distance to the W. of this Tp. and through secs. 7 and 8. Some of these paintings are well executed and are in several colors.

165
77

4-680
(Revised May 1934)

4041

FIELD ASSISTANTS

to J. P. Hester

NAMES	CAPACITY
James Chumley	1st Chainman
Dawson Cooley	2nd Chainman
M.L. Patrick	Moundsman
John Arrington	Moundsman
J. E. Kelly	Axman
Chas. Powers	Axman
Perry Munger	Axman
Paul Greenhaw	Flagman

78

166

BOOK 4041

CERTIFICATE OF UNITED STATES SURVEYOR

I, J.P. Hester U.S. Transitman, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of May, 1931, received from the district cadastral engineer for Arizona, with assignment instructions dated June 20, 1934, I have surveyed

Part of the Subdivision Lines of Township 38 North, Range 1 West and resurveyed the South boundary of Township 39 North, Range 1 West

of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey, and resurvey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona February 12, 1935

J.P. Hester U.S. Transitman

CERTIFICATE OF APPROVAL

Office of U.S. Supervisor of Surveys,

, 19

The foregoing field notes of the survey of executed by under special instructions dated and assignment instructions dated, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

U.S. Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys in, is a true copy of the original field notes on file in the public survey office.

U.S. Supervisor of Surveys.

BOOK 4041

4-680
(August, 1926)

FIELD ASSISTANTS.

to Ben D. Procter

NAMES.	CAPACITY.
H. Neil Greenhaw	1st Chainman
Orson A. Stone	2nd Chainman
Albert A. Blevins	Moundsman
James A. Kelley	Axman
Wm. P. Carver	Axman
Bert Alexander	Axman
Guy E. Tripp	Axman
Chas. L. Turner	Flagman

80

168

BOOK 4041

CERTIFICATE OF UNITED STATES SURVEYOR

I, Ben D. Procter, U.S. Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 1st day of May, 1931, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the Subdivision Lines of Township 38 North, Range 1 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Phoenix, Arizona
February 12, 1935

Ben D. Procter
U.S. Transitman

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS

19

The foregoing field notes of the survey of

executed by under his special instructions dated, 19, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys

169
81

FORM 4041

4-680
(August, 1926)

FIELD ASSISTANTS.

to John L. Warboys

NAMES.	CAPACITY.
Delmar F. Vincent	1st Chainman
Frank Burt	2nd Chainman
Paul Hulquist	Moundsman
John W. Martinie	Axman
Francis Sweeney	Axman
Merrill E. Silverthorn	Flagman

82 170
BOOK 4041

CERTIFICATE OF UNITED STATES SURVEYOR

I, John L. Warboys U.S. Cadastral Engineer, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 1st day of May, 1931, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the West boundary and Subdivision Lines of Township 38 North, Range 1 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Phoenix, Arizona.
March 26, 1935.

John L. Warboys
U.S. Cadastral Engineer

APPROVAL

OFFICE OF U. S. SUPERVISOR OF SURVEYS,
Denver, Colorado, April 18, 1935

The foregoing field notes of the resurvey of the South boundary of Township 39 North, Range 1 West and of the survey of the West boundary and Subdivision Lines of Township 38 North, Range 1 West of the Gila and Salt River Base and Meridian in the State of Arizona executed by John L. Warboys, U. S. Cadastral Engineer, and assisted by Ben D. Procter and J. P. Hester, U. S. Transitmen under special instructions dated May 1, 1931, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the resurveys and surveys they describe, are hereby approved.

Wm. H. ...
U. S. Supervisor of Surveys.

~~I certify that the foregoing transcript of the field notes of the above described surveys in ... has been correctly copied from the original notes on file in this office.~~

U. S. Supervisor of Surveys.