

Book "J"

4-879

BOOK 4059

# FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISIONS of

Township 9 South, Range 7 West

Of the Gila and Salt River Base<sup>2d</sup> Meridian,

In the State of ARIZONA

### EXECUTED BY

Frank C. Mulford, R.E. McMahan, K.K. Bowsher

and Ben D. Procter, Temporary Transmitters

In the capacity of U. S. Surveyors, under Special Instructions dated Dec. 12, 1933, issued by the District Cadastral Engineer to govern surveys included in Group No. 199, Arizona, which were approved by the Commissioner of the General Land Office, February 17, 1934, and Assignment Instructions dated Dec. 15, 1933.

Survey commenced January 18, 1934.

Survey completed February 5, 1934.

4059

4059

# INDEX DIAGRAM.

*Township* ..... , *Range* .....

6	5	4	3	2	1
7	8	9	10	11	12
13	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

INDEX-DIAGRAM.

BOOK 4059

	6 39	5 29	4 21	3 15	2 8	1	
	38	38 37	28 22	21	14	7	
	7 37	8 28	9 21	10 14	11 7	12	
	36 37	36 27	27 20	20	13 6	6	
	18 35	17 26	16 19	15 13	14 6	13	
	34 35	34 33	26 25	19 12	12 5	5	
	19 33	20 25	21 18	22 11	23 4	24	
	32 33	32	24	17	11 10	4 3	
	30 31	29 24	28 17	27 10	26 3	25	
	30 31	30 23	23 16	16	10 9	2	
	31 29	32 22	33 15	34 9	35 2	36	
				8	1		

2nd Standard Parallel South

————— Surveyed under this group.

----- Resurveyed under this group.

————— Surveyed under Group No. 200.

----- Resurveyed under Group No. 200.

## SUBDIVISIONS OF T.9 S., R.7 W.

16

BOOK 4059

## Chains

The subdivisional survey of T.9 S., R.7 W., was executed with Young & Sons light-mountain transits Nos. 8477, 8588 and 8592 and W. & L. E. Gurley transit No. 20117 by Frank C. Mulford, R. E. McMahan, K. K. Bowsher and Ben B. Procter, Temporary Transitmen. The instruments are constructed in accordance with the standard specifications of the General Land Office, with full vertical circles reading to single minutes, which is also the least count of the two verniers of the horizontal circles of each instrument. The instruments were in good condition, and having been placed in satisfactory adjustment prior to beginning the survey, and tested and found free from appreciable error, were approved by the district cadastral engineer on Dec. 15, 1933.

The types of land timber and undergrowth in T.9 S., R.7 W., offer few objections to projection of lines by back and foresight method; that method is selected in view of the unfamiliarity of the instrumentmen with the solar attachments with which the instruments are equipped.

Lines are initiated from the standard parallel on the S. bdy. of the Tp., which is independently resurveyed at this time as described in the notes of the first Book of this Group. The true bearings of all lines are checked by repetition of angles, double back and foresights and occasional direct altitude observations on the sun for azimuth, and where feasible, by check of the azimuths initiated at different points on the parallel against each other.

The measurements were made with Lallie and Lufkin steel tapes, 5 chs. in length, graduated every link for the first 100 lks. and the balance at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope; the vertical angle of each interval is ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

## SURVEY

From the standard cor. of secs. 35 and 36, on the S. bdy. of T.9 S., R.7 W., as relocated by independent resurvey under this Group, described in notes of resurvey of 2nd Standard Parallel, S.,

N.0°01'W., bet. secs. 35 and 36.

Over gently rolling land; through scattering timber and dense undergrowth.

- 20.00 Foot of slope, bears E. and W.; asc. 116 ft. over S. slope.
- 27.70 Ridge, bears E. and W.; desc. 24 ft. over N. slope.
- 30.70 Draw, course NE.; asc. 82 ft. over SE. slope.
- 38.55 Rocky spur, slopes E.; desc. 38 ft. over N. slope.
- 40.00 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- Desc. 89 ft. over NW. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
46.60	Wash, 15 lks. wide, course NE.; asc. 84 ft. over SE.slope.
54.20	Spur, slopes NE.; desc. 122 ft. over NW. slope.
58.80	Wash, 10 lks. wide, course NE.; asc. 132 ft. over SE.slope.
63.60	Spur, slopes NE.; desc. 85 ft. over NW. slope.
75.00	Wash, 20 lks. wide, course NE.; asc. 61 ft.
79.90	Over spur, slopes N.70°E.
80.00	Set a lava stone, 24 x 8 x 6 ins., 18 ins. in the ground, for cor. of secs. 25,26,35 and 36, mkd. with 1 groove on S. and 1 groove on E. faces, and  raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  Land: rolling and gently rolling. Soil: sandy and gravelly loam, rocky, 2nd and 4th rates. Timber: scattering palo verde. Undergrowth: greasewood and cacti.
-----	
	East, on random line, bet. secs. 25 and 36.
40.00	Set temp. ¼ sec. cor.
79.86	Intersect the cor. of secs. 25,30,31 and 36, on the E. bdy. of the Tp., described in the official record of this Group.
	Thence
	West, on true line, bet. secs. 25 and 36.
	Over rolling land; through scattering timber and dense undergrowth.
7.55	Wash, 45 lks. wide, course N.
9.85	Road, bears N. and S.
20.45	Wash, 20 lks. wide, course NE.
28.85	Wash, 30 lks. wide, course N.; asc. 63 ft. over E. slope.
36.00	Spur, slopes NE.; desc. 24 ft. over W. slope.
39.93	Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for ¼ sec. cor., mkd. ¼ on N. face, and  raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  Desc. 15 ft. over W. slope.
43.75	Wash, 20 lks. wide, course NE.; over gently rolling land.
54.25	Wash, 20 lks. wide, course SE.; asc. 61 ft. over N.slope.
68.85	Wash, 20 lks. wide, course NE.; asc. 174 ft. over E.slope.
79.86	The cor. of secs. 25,26,35 and 36.  Land: gently rolling and rolling. Soil: sandy and gravelly loam, 2nd and 4th rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, ocotillo and cactus.
-----	

## SUBDIVISIONS OF T.9 S., R.7 W.

3

BOOK 4059

Chains	
	N.0°01'W., bet. secs. 25 and 26. Desc. 165 ft. over NW. slope; through scattering timber and dense undergrowth.
12.60	Wash, 30 lks. wide, course NE.; asc. 75 ft. over SE. slope.
21.00	Spur, slopes NE.; desc. 125 ft. over NW. slope.
27.70	Wash, 60 lks. wide, course E.; asc. 113 ft. over SE. slope.
38.00	Spur, slopes NE.; desc. 26 ft. over NW. slope.
40.00	Set a lava stone, 20 x 10 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Desc. 15 ft. over NW. slope.
44.00	Wash, 20 lks. wide, course NE.; asc. 12 ft.
46.80	Spur, slopes NE.; desc. 102 ft. over NW. slope.
52.60	Wash, 60 lks. wide, course NE.; asc. 87 ft. over SE. slope.
59.20	Spur, slopes NE.; desc. 51 ft. over NW. slope.
62.70	Wash, 15 lks. wide, course E.; asc. 73 ft. over S. slope.
69.50	Spur, slopes SE.; desc. 70 ft. over NE. slope.
74.60	Wash, 20 lks. wide, course SE.; asc. 27 ft. over S. slope.
79.90	Over spur, slopes SE.
80.00	Set a lava stone, 20 x 8 x 8 ins., 15 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, mkd. with 2 grooves on S. and 1 groove on E. faces, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Land: rolling and broken. Soil: sandy and gravelly loam, rocky, 4th rate. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, ocotillo and cactus.
-----	
	East, on random line, bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.92	Intersect the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., described in the official record of this Group.
	Thence
	West, on true line, bet. secs. 24 and 25. Over gently rolling land; through scattering timber and undergrowth.
17.30	Old road, bears NW. and S.
20.00	Foot of slope, bears NW. and S.; asc. 132 ft. over E. slope.
37.60	Spur, slopes NE.; desc. 39 ft. over NW. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
39.96	Set a lava stone, 24 x 8 x 6 ins., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Over gently rolling land.
42.10	Wash, 30 lks. wide, course N.
64.00	Wash, 30 lks. wide, course SE.; asc. 40 ft. over NE. slope.
79.92	The cor. of secs. 23, 24, 25 and 26. Land: gently rolling and rolling. Soil: sandy and gravelly loam, stony, 2nd and 3rd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N.0°01'W., bet. secs. 23 and 24. Desc. 23 ft. over N. slope; through scattering timber and undergrowth.
4.80	Wash, 30 lks. wide, course SE.; asc. 76 ft. over S. slope.
11.40	Rocky spur, slopes E.; desc. 108 ft. over N. slope.
18.55	Wash, 45 lks. wide, course E.; asc. 16 ft.
20.00	Point of spur, slopes E.; desc. 12 ft.
21.20	Wash, 20 lks. wide, course SE.; asc. 80 ft. over S. slope.
29.00	Change to N. slope; desc. 54 ft.
33.00	Wash, 30 lks. wide, course E.; desc. 44 ft. along E. slope.
36.90	Wash, 10 lks. wide, course E.
40.00	True point for $\frac{1}{4}$ sec. cor. falls in wash, 10 lks. wide, course SE.
40.40	(40 lks. N.0°01'W. of true point) Set a lava stone, 20 x 8 x 7 ins., 16 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., mkd. WC on S. and $\frac{1}{4}$ on W. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Asc. 49 ft. over S. slope.
43.70	Spur, slopes SE.; desc. 73 ft. over NE. slope.
57.30	Wash, 20 lks. wide, course SE.; over broken E. slope.
62.10	Wash, 40 lks. wide, course NE.
68.20	Wash, 20 lks. wide, course E.
75.30	Wash, 10 lks. wide, course SE.
80.00	Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, mkd. with 3 grooves on S. and 1 groove on E. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land: rolling and broken.

## SUBDIVISIONS OF T.9 S., R.7 W.

## Chains

Soil: sandy and gravelly loam, rocky, 2nd and 4th rates.  
 Timber: scattering palo verde and mesquite.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 East, on random line, bet. secs. 13 and 24.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.88 Intersect the E. bdy. of the Tp. at a point 14 lks. S. of the cor. of secs. 13, 18, 19 and 24, described in the official record of this group.

Thence

S.89°54'W., on true line, bet. secs. 13 and 24.

Over gently rolling land; through scattering timber and undergrowth.

9.90 Wash, 150 lks. wide, course N.10°W.

22.30 Wash, 20 lks. wide, course N.10°W.

26.70 Wash, 15 lks. wide, course NW.

39.60 Old road, bears NW. and SE.

39.94 Set a lava stone, 24 x 8 x 6 ins., 18 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and

raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

46.00 Wash, 20 lks. wide, course NE.; asc. 81 ft. over gradual E. slope.

71.90 Wash, 10 lks. wide, course S.; asc. 49 ft. over SE. slope.

79.88 The cor. of secs. 13, 14, 23 and 24.

Land: gently rolling.

Soil: sandy and gravelly loam, rocky, 2nd and 4th rates.

Timber: scattering palo verde.

Undergrowth: ocotillo, greasewood and cactus.

-----  
 N.0°01'W., bet. secs. 13 and 14.

Over gently rolling land; through scattering timber and undergrowth.

Desc. 68 ft. over gradual N. slope.

19.60 Wash, 10 lks. wide, course NE.; asc. gently.

22.50 Foot of slope; bears NE. and SW.; asc. 63 ft. over SE. slope.

31.00 Hill, bears NE. and SW.; desc. 90 ft. over NW. slope.

34.50 Foot of slope, bears NE. and SW.; over gently rolling land.

37.20 Old road, bears E. and W.

40.00 Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
	dig pits, 18 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.
42.40	Wash, 40 lks. wide, course E.; asc. 67 ft. over S. slope.
46.90	Top of hill, bears E. and W.; desc. 67 ft. over N. slope.
49.50	Foot of hill, bears E. and W.; over gently rolling land.
52.85	Old road, bears E. and W.
61.75	Foot of slope, bears NW. and E.; asc. 192 ft. over SW. slope.
79.90	Over top of hill, bears NW. and SE.
80.00	Set a lava stone, 22 x 9 x 6 ins., 16 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, mkd. with 4 grooves on S. and 1 groove on E. faces, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land: gently rolling and rolling. Soil: sandy and gravelly loam, rocky, 2nd and 4th rates. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	N. 89° 54' E., on random line, bet. secs. 12 and 13.
40.00	Set temp. ¼ sec. cor.
79.84	Intersect the E. bdy. of the Tp. at a point 5 lks. N. of the cor. of secs. 7, 12, 13 and 18, described in the official record of this Group.
	Thence
	S. 89° 56' W., on true line, bet. secs. 12 and 13.
	Over gently rolling land; through scattering timber and undergrowth.
31.15	Wash, 90 lks. wide, course NW.
39.92	Set a lava stone, 20 x 12 x 6 ins., 15 ins. in the ground, for ¼ sec. cor., mkd. ¼ on N. face, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
42.50	Wash, 40 lks. wide, course N.
53.20	Old road, bears N. and S.
56.20	Foot of slope, bears N. and SW.; asc. 186 ft. over broken E. slope.
79.84	The cor. of secs. 11, 12, 13 and 14. Land: gently rolling and rolling. Soil, sandy & gravelly loam, 1st, 2nd and 4th rates. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	N. 0° 01' W., bet. secs. 11 and 12.
	Desc. 225 ft. over rocky NE. slope; through scattering timber and undergrowth.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
17.00	Foot of slope, bears E. and W.; over gently rolling land.
29.10	Foot of slope, bears NE. and SW.; asc. 70 ft. over SE. slope.
39.90	Over top of hill, bears NE. and SW.
40.00	Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Desc. 144 ft. over NW. slope.
43.50	Wash, 10 lks. wide, course NE.; asc. 52 ft. over SE. slope.
47.10	Hill, bears NE. and SW.; desc. 47 ft. over NW. slope.
52.10	Foot of hill, bears NE. and SW.; over flat.
63.90	Begin ascent of 80 ft. over SE. slope.
68.75	Hill, bears NE. and SW.; desc. 78 ft. over NW. slope.
72.30	Foot of hill, bears NE. and SW.; over gently rolling land.
80.00	Set a lava stone, 20 x 9 x 7 ins., 15 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, mkd. with 5 grooves on S. and 1 groove on E. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land: gently rolling and rolling. Soil: sandy and gravelly loam, rocky, 2nd and 4th rates. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N. 89° 56' E., on random line, bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.92	Intersect the E. bdy. of the Tp. at a point 5 lks. N. of the cor. of secs. 1, 6, 7 and 12, described in the official record of this Group.
	Thence
	S. 89° 58' W., on true line, bet. secs. 1 and 12.
	Over gently rolling land; through scattering timber and dense undergrowth.
39.96	Set a lava stone, 22 x 6 x 6 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and dig pits, 18 x 18 x 12 ins., E. and W. of cor, 3 ft. dist.
49.70	Wash, 30 lks. wide, course NW.
51.70	Wash, 40 lks. wide, course NW.; road, bears NE. and SW.
59.65	Wash, 40 lks. wide, course NW.
65.30	Foot of slope, bears NE. and SW.; asc. 22 ft. over E. slope.
67.30	Hill, bears NE. and SW.; desc. 21 ft. over NW. slope.
72.70	Foot of slope, bears NE. and SW.; over gently rolling land.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
79.92	The cor. of secs. 1,2,11 and 12.  Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, catclaw, ocotillo and cactus.  -----
	N.0°01'W., on random line, bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect the N. bdy. of the Tp. at a point 9 lks. E. of the cor. of secs. 1,2,35 and 36, described in the official record of this Group.  Thence  S.0°05'E., on true line, bet. secs. 1 and 2.  Over gently rolling land; through scattering timber and undergrowth.
38.80	(1.20 chs. N.0°05'W. of true point) Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. WC on S. and $\frac{1}{4}$ on W. faces, and  dig pits, 18x18x12 ins., N. and S. of cor., 3 ft. dist.
40.00	True point for $\frac{1}{4}$ sec. cor. falls in wash, 120 lks. wide, course NW.
44.00	Wash, 100 lks. wide, course NW.
49.15	Wash, 45 lks. wide, course NW.
59.15	Begin ascent of 69 ft. over N. slope.
61.25	Top of butte; desc. 59 ft. over S. slope.
63.50	Foot of slope; over gently rolling land.
80.00	The cor. of secs. 1,2,11 and 12.  Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.  -----
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., as relocated by independent resurvey under this Group, described in notes of resurvey of 2nd Standard Parallel, S.,  N.0°01'W., bet. secs. 34 and 35.
	Asc. 23 ft. over gentle S. slope; through scattering timber and undergrowth.
7.80	Spur, slopes SE.; desc. 323 ft. over N. slope.
30.90	Wash, 25 lks. wide, course SE.; asc. 44 ft. over SW.slope.
36.70	Spur, slopes S.80°E.; desc. 37 ft. over N. slope.
40.00	Set a lava stone, 24 x 7 x 6 ins., 18 ins. in the ground,

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
	for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Over gently rolling land.
47.20	Wash, 30 lks. wide, course S. $80^{\circ}$ E.
60.00	Foot of slope, bears E, and W.; asc. 236 ft. over S. slope.
72.00	Rim of mesa, bears NW. and SE.; over rolling top of same.
79.00	Rim of mesa, bears NW. and SE.; desc. 41 ft. over NE. slope.
80.00	Set a lava stone, 20 x 14 x 6 ins., 15 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, mkd. with 1 groove on S. and 2 grooves on E. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land: gently and heavily rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
	East, on random line, bet. secs. 26 and 35.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	A point 9 lks. N. of the cor. of secs. 25, 26, 35 and 36. Thence N. $89^{\circ}56'$ W., on true line, bet. secs. 26 and 35. Asc. slightly over SE. slope; through scattering timber and undergrowth.
0.60	Spur, slopes NE.; over rolling top.
5.00	Spur, slopes N.; desc. 179 ft. over W. slope.
8.30	Wash, 30 lks. wide, course N.; asc. 188 ft. over E. slope.
13.30	Over flat ridge, bears N. and S.
20.90	Leave same, bears N. and S.; desc. 32 ft. over SW. slope.
24.85	Draw, course NW.; asc. 20 ft. over NE. slope.
28.30	Spur, slopes NW.; desc. 99 ft. over SW. slope.
33.20	Wash, 30 lks. wide, course NE.; asc. 59 ft. over SE. slope.
39.95	Set a lava stone, 26 x 8 x 6 ins., 19 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Asc. 20 ft. over SE. slope.
41.80	Spur, slopes N.; desc. 50 ft. over W. slope.
46.30	Wash, 20 lks. wide, course NE.; over gently rolling land.
58.60	Foot of slope, bears N. and S.; asc. 122 ft. over E. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
66.70	Spur, slopes N.; desc. 27 ft. over W. slope.
68.30	Draw, course N.; asc. 72 ft. over E. slope.
73.30	Spur, slopes N.; desc. 20 ft. over W. slope.
77.50	Draw, course N.; asc. 31 ft. over E. slope.
79.90	The cor. of secs. 26, 27, 34 and 35.
	Land: rolling and broken. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N.0°01'W., bet. secs. 26 and 27.
	Desc. 46 ft. along E. slope; through scattering timber and undergrowth.
22.50	Spur, slopes NE.; desc. 141 ft. over NW. slope.
31.45	Wash, 20 lks. wide, course N.30°E.; asc. 52 ft. over S. slope.
37.10	Over flat spur, slopes NE.
40.00	Set a lava stone, 24 x 10 x 8 ins., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	Desc. 29 ft. over gentle N. slope.
49.20	Leave spur, slopes NE.; desc. 103 ft. over NW. slope.
52.85	Draw, course NE.; asc. 81 ft. over SE. slope.
55.90	Spur, slopes NE.; desc. 159 ft. over NW. slope.
66.00	Wash, 50 lks. wide, course NE.; asc. 54 ft. over S. slope.
68.80	Flat-topped spur, slopes NE.; desc. 63 ft. over gradual N. slope.
80.00	Set a lava stone, 30 x 10 x 8 ins., 22 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, mkd. with 2 grooves on S. and 2 grooves on E. faces, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering ironwood and palo verde. Undergrowth: greasewood, ocotillo and cactus.
-----	
	S.89°56'E., on random line, bet. secs. 23 and 26.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	A point 5 lks. S. of the cor. of secs. 23, 24, 25 and 26.
	Thence
	N.89°58'W., on true line, bet. secs. 23 and 26.

## SUBDIVISIONS OF T.9 S., R.7 W.

4059

Chains	Asc. 55 ft. over top of spur, slopes E.; through scattering timber and undergrowth.
19.60	Spur, slopes N.; desc. 66 ft. over W. slope.
23.80	Head of ravine, course NW.; asc. 45 ft. over NE. slope.
30.20	Spur, slopes NW.; desc. 68 ft. over SW. slope.
40.00	Set a lava stone, 30 x 8 x 6 ins., 20 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. Desc. 13 ft. over gentle W. slope.
49.00	Wash, 30 lks. wide, course NW.; asc. 85 ft. over E. slope.
54.40	Spur, slopes N.; desc. 85 ft. over W. slope.
61.10	Wash, 40 lks. wide, course NE.; asc. 63 ft. over SE. slope.
68.00	Spur, slopes NE.; desc. 52 ft. along N. slope.
71.10	Head of ravine, course NW.; asc. 65 ft. over NE. slope.
80.00	The cor. of secs. 22, 23, 26 and 27.
	Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
----- N.0°01'W., bet. secs. 22 and 23.	
	Desc. 54 ft. over gradual N. slope; through scattering timber and undergrowth.
5.70	Foot of slope; over gently rolling land.
12.00	Wash, 20 lks. wide, course NE.
14.50	Begin ascent of 48 ft. over S. slope.
16.90	Over flat spur, slopes NE.
24.00	Leave same; desc. 50 ft. over N. slope.
25.00	Foot of slope; over gently rolling land.
29.00	Wash, 40 lks. wide, course NE.
40.00	Set a lava stone, 20 x 8 x 8 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
47.00	Wash, 75 lks. wide, course NE.
56.40	Begin ascent of 217 ft. over S. slope.
68.10	Spur, slopes SE.; desc. 167 ft. over NE. slope.
80.00	Set a lava stone, 20 x 9 x 6 ins., 14 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, mkd. with 3 grooves on S. and 2 grooves on E. faces, and

## SUBDIVISIONS OF T.9 S., R.7 W.

## Chains

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land: gently and heavily rolling.

Soil: gravel and rocky, 4th rate.

Timber: scattering palo verde and mesquite.

Undergrowth: greasewood, ocotillo and cactus.

S.89°58'E., on random line, bet. secs. 14 and 23.

40.00 Set temp. ¼ sec. cor.

79.96 Intersect the cor. of secs. 13, 14, 23 and 24.

Thence

N.89°58'W., on true line, bet. secs. 14 and 23.

Over gentle E. slope; through scattering timber and undergrowth.

2.00 Over mesa, bears N. and S.

18.10 Leave same, bears N. and S.; desc. 60 ft. over W. slope.

26.20 Wash, 30 lks. wide, course NE.; asc. 56 ft. over E. slope.

29.40 Spur, slopes NE.; desc. 104 ft. over W. slope.

36.00 Wash, 10 lks. wide, course N.; over N. slope.

39.98 Set a lava stone, 22 x 8 x 6 ins., 16 ins. in the ground, for ¼ sec. cor., mkd. ¼ on N. face, and

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

49.00 Wash, 50 lks. wide, course N.

49.70 Wash, 50 lks. wide, course NE.

63.10 Wash, 20 lks. wide, course SE.

73.10 Begin ascent of 98 ft. over NE. slope.

79.96 The cor. of secs. 14, 15, 22 and 23.

Land: rolling.

Soil: sandy and gravelly, rocky, 2nd and 4th rates.

Timber: scattering palo verde, mesquite and ironwood.

Undergrowth: greasewood, ocotillo and cactus.

N.0°01'W., bet. secs. 14 and 15.

Desc. 52 ft. over NE. slope; through scattering timber and undergrowth.

9.55 Wash, 10 lks. wide, course SE.; asc. 152 ft. over SE. slope.

14.80 Over top of spur, slopes NE.

22.90 Leave same; desc. 141 ft. over N. slope.

24.95 Wash, 20 lks. wide, course NE.; asc. 141 ft. over S. slope.

26.80 Over mesa, bears E. and W.

## SUBDIVISIONS OF T.9 S., R.7 W.

13

BOOK 400

Chains	
40.00	Set a lava stone, 36 x 12 x 12 ins., 16 ins. in the ground to bedrock and supported in a mound of stone, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and  raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
43.00	Leave mesa, bears NE. and SW.; desc. 92 ft. over NW. slope.
49.70	Gulch, course NW.; asc. 16 ft. along W. slope.
53.60	Top of ascent; desc. 21 ft. along W. slope.
57.00	Gulch, course NW.; asc. 32 ft. over SW. slope.
62.90	Point of spur, slopes NW.; desc. 34 ft. over N. slope.
69.90	Wash, 90 lks. wide, course NE.; over gently rolling land.
74.15	Road, bears NW. and SE.
80.00	Set a lava stone, 24 x 12 x 12 ins., 16 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, mkd. with 4 grooves on S. and 2 grooves on E. faces, and  raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.  Land: rolling and gently rolling. Soil: sandy and gravelly, rocky, 2nd and 4th rates. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
S. 89° 58' E., on random line, bet. secs. 11 and 14.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	A point 2 lks. S. of the cor. of secs. 11, 12, 13 and 14.
Thence	
N. 89° 59' W., on true line, bet. secs. 11 and 14.	
Asc. 28 ft. over SE. slope; through scattering timber and undergrowth.	
13.20	Top of hill, bears NE. and SW.; desc. 160 ft. over NW. slope.
17.90	Foot of hill, bears NE. and SW.; over gently rolling land.
39.95	Set a lava stone, 24 x 8 x 7 ins., 18 ins. in the ground, for $\frac{1}{2}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and  raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
63.90	Wash, 25 lks. wide, course N.
70.50	Wash, 30 lks. wide, course NE.
72.50	Wash, 20 lks. wide, course NE.
79.90	The cor. of secs. 10, 11, 14 and 15.  Land: gently rolling and rolling. Soil: sandy and gravelly loam, 2nd and 4th rates. Timber: scattering ironwood, mesquite and palo verde. Undergrowth: greasewood, ocotillo and cactus.
-----	

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
	N.0°01'W., bet. secs. 10 and 11. Over gently rolling land; through scattering timber and undergrowth.
40.00	Set a lava stone, 20 x 12 x 12 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
43.10	Wash, 40 lks. wide, course NW.
60.00	Wash, 30 lks. wide, course NE.
80.00	Set a lava stone, 20 x 9 x 6 ins., 14 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, mkd. with 5 grooves on S. and 2 grooves on E. faces, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.  Land: gently rolling. Soil: sandy and gravelly loam, 1st and 2nd rates. Timber: scattering palo verde, mesquite and ironwood. Undergrowth: greasewood, ocotillo and cactus.
-----	
	S.89°59'E., on random line, bet. secs. 2 and 11.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.92	A point 2 lks. S. of the cor. of secs. 1, 2, 11 and 12. Thence West, on true line, bet. secs. 2 and 11. Over gently rolling land; through scattering timber and undergrowth.
39.96	Set a lava stone, 24 x 10 x 6 ins., 12 ins. in the ground to bedrock and supported in a mound of stone, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face.
55.10	Begin ascent of 68 ft. over E. slope.
59.30	Top of hill, bears N. and S.; desc. 84 ft. over W. slope.
62.10	Foot of hill, bears N. and S.; over gently rolling land.
73.10	Wash, 40 lks. wide, course NE.
79.92	The cor. of secs. 2, 3, 10 and 11.  Land: gently rolling. Soil: sandy and gravelly, 2nd and 4th rates. Timber: scattering palo verde, mesquite and ironwood. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N.0°05'W., on random line, bet. secs. 2 and 3.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect the N. bdy. of the Tp. at a point 12 lks. E. of the cor. of secs. 2, 3, 34 and 35, described in the official record of this Group.

## SUBDIVISIONS OF T. 9 S., R. 7 W.

4059

## Chains

Thence

S. 0° 10' E., on true line, bet. secs. 2 and 3.

Over gently rolling land; through scattering timber and undergrowth.

- 9.60 Wash, 60 lks. wide, course N. 80 W.
- 11.40 Wash, 100 lks. wide, course W.
- 18.40 Wash, 20 lks. wide, course NW.
- 20.40 Wash, 20 lks. wide, course W.
- 39.90 Set a lava stone, 20 x 10 x 10 ins., 14 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- 40.30 Wash, 10 lks. wide, course NW.
- 62.10 Begin ascent of 96 ft. over NE. slope
- 68.40 Hill, bears NW. and SE.; desc. 96 ft. over SW. slope.
- 72.90 Foot of hill, bears NW. and SE.; over gently rolling land.
- 79.90 The cor. of secs. 2, 3, 10 and 11.

Land: gently rolling.

Soil: sandy and gravelly loam, 2nd and 3rd rates.

Timber: scattering palo verde and mesquite.

Undergrowth: greasewood, ocotillo and cactus.

-----

From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., as relocated by independent resurvey under this Group, described in notes of resurvey of 2nd standard Parallel S.,

N. 0° 02' W., bet. secs. 33 and 34.

Asc. 73 ft. over SW. slope; through scattering timber and undergrowth.

- 26.00 Spur, slopes E.; desc. 264 ft. over N. slope.
- 40.00 Mark a cross (X) on top of a lava stone in place, 2 x 2 x 2 ft. above ground, for  $\frac{1}{4}$  sec. cor., and mark  $\frac{1}{4}$  W. of cross, and raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
- 40.70 Wash, 100 lks. wide, course N. 80° E.; asc. 192 ft. over S. slope.
- 48.30 Spur, slopes E.; desc. 92 ft. over N. slope.
- 62.30 Wash, 30 lks. wide, course NE.; over gently rolling land.
- 69.00 Wash, 15 lks. wide, course NE.
- 80.00 Set a lava stone, 24 x 8 x 6 ins., 18 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, mkd. with 1 groove on S. and 3 grooves on E. faces, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Chains	
	<p>Land: gently rolling and rolling.            Soil: Gravelly and rocky, 4th rate.            Timber: scattering palo verde and mesquite.            Undergrowth: greasewood, ocotillo and cactus.</p> <p>-----</p> <p>East, on random line, bet. secs. 27 and 34.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.92	A point 19 lks. S. of the cor. of secs. 26, 27, 34 and 35. Thence
	S. $89^{\circ}52'W.$ , on true line, bet. secs. 27 and 34. Over N. slope; through scattering timber and undergrowth.
21.30	Spur, slopes N.; desc. 192 ft. over NW. slope.
29.90	Wash, 20 lks. wide, course N.; asc. 90 ft. over NE. slope.
39.96	Set a lava stone, 20 x 9 x 6 ins. 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
40.20	Ridge, bears NW. and SE.; desc. 222 ft. over SW. slope.
57.70	Foot of slope, bears NW. and SE.; over gently rolling land.
73.40	Wash, 10 lks. wide, course SE.
79.92	The cor. of secs. 27, 28, 33 and 34. Land: rolling and gently rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	N. $0^{\circ}02'W.$ , bet. secs. 27 and 28. Over gently rolling land; through scattering timber and undergrowth.
4.80	Wash, 15 lks. wide, course E.
12.10	Begin ascent of 239 ft. over S. slope.
21.30	Ridge, bears E. and W.; desc. 58 ft. over N. slope.
26.30	Gulch, course NE.; over gentle SE. slope.
36.25	Spur, slopes NE.; over gentle NW. slope.
40.00	Set a lava stone, 20 x 12 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Desc. 55 ft. over NW. slope.
43.75	Wash, 20 lks. wide, course N. $70^{\circ}E.$ ; asc. 26 ft. over SE. slope.
49.60	Spur, slopes NE.; desc. 65 ft. over NW. slope.
54.60	Wash, 10 lks. wide, course NW.; over gently rolling land.

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 417  
409

## Chains

- 58.60 Wash, 20 lks. wide, course NE.; asc. 60 ft. over SE. slope.
- 68.30 Spur, slopes NE.; over E. slope.
- 77.20 Spur, slopes E.; desc. 176 ft. over N. slope.
- 80.00 Mark a cross (X) on exposed bedrock, and over cross, set a lava stone, 30 x 10 x 8 ins., supported in a mound of stone, cor. cor. of secs. 21, 22, 27 and 28, mkd. with 2 grooves on S. and 3 grooves on E. faces, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
- Land: rolling.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N.89°52'E., on random line, bet. secs. 22 and 27.
- 40.00 Set temp. ¼ sec. cor.
- 80.02 A point 28 lks. N. of the cor. of secs. 22, 23, 26 and 27.
- Thence
- N.89°56'W., on true line, bet. secs. 22 and 27.
- Desc. 49 ft. along N. slope; through scattering timber and undergrowth.
- 6.50 Wash, 10 lks. wide, course NE.; over gently rolling land.
- 13.30 Begin ascent of 78 ft. over E. slope.
- 17.50 Over top of spur, slopes N.
- 19.90 Leave same; desc. 75 ft. over W. slope.
- 28.00 Wash, 30 lks. wide, course N.20°E.; asc. 103 ft. over E. slope.
- 37.10 Spur, slopes N.; desc. 20 ft. over W. slope.
- 40.01 Set a lava stone, 20 x 10 x 8 ins., 15 ins. in the ground, for ¼ sec. cor., mkd. ¼ on N. face, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
- Over gentle W. slope.
- 41.80 Wash, 10 lks. wide, course NW.; asc. 50 ft. over E. slope.
- 54.20 Spur, slopes N.; desc. 115 ft. over W. slope.
- 58.90 Wash, 15 lks. wide, course N.10°W.
- 60.30 Wash, 15 lks. wide, course N.10°E.; asc. 124 ft. over SE. slope.
- 65.00 Spur, slopes NE.; desc. 120 ft. over NW. slope.
- 70.20 Wash, 10 lks. wide, course N.; asc. 17 ft. along N. slope.
- 80.02 The cor. of secs. 21, 22, 27 and 28.
- Land: rolling.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	<p>Soil: gravel, rocky, 4th rate.            Timber: scattering palo verde and mesquite.            Undergrowth: greasewood, ocotillo and cactus.</p>								
	N.0°02'W., bet. secs. 21 and 22.								
	Desc. 54 ft. over N. slope; through scattering timber and undergrowth.								
2.50	Foot of slope; over gently rolling land.								
9.80	Wash, 20 lks. wide, course NE.								
19.30	Begin ascent of 14 ft. over S. slope.								
20.60	Point of spur, slopes NE.; desc. 23 ft. over NW. slope.								
30.60	Wash, 15 lks. wide, course N.70°E.; asc. 39 ft. over SE. slope.								
37.30	Spur, slopes NE.; desc. 35 ft. over NW. slope.								
40.00	<p>Set a lava stone, 20 x 10 x 8 ins., 15 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., mkd. <math>\frac{1}{4}</math> on W. face, and</p> <p>raise a mound of stone, 2 ft. base, 1<math>\frac{1}{2}</math> ft. high, W. of cor.</p>								
	Over gentle N. slope.								
45.70	Wash, 20 lks. wide, course W.; asc. 172 ft. over S. slope.								
52.60	Spur, slopes SW.; desc. 57 ft. over NW. slope.								
56.70	Wash, 15 lks. wide, course NW.; asc. 26 ft. over SW. slope.								
60.00	Spur, slopes W.; desc. 84 ft. over NW. slope.								
62.50	Wash, 15 lks. wide, course NE.; over E. slope.								
73.15	Wash, 15 lks. wide, course N.70°W.; over W. slope.								
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.</p>								
	<table border="1"> <tr><td>T9S</td><td>R7W</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td colspan="2">1934</td></tr> </table>	T9S	R7W	S16	S15	S21	S22	1934	
T9S	R7W								
S16	S15								
S21	S22								
1934									
	<p>and raise a mound of stone, 2 ft. base, 1<math>\frac{1}{2}</math> ft. high, W. of cor.</p>								
	<p>Land: rolling.            Soil: gravel, rocky, 4th rate.            Timber: scattering palo verde and mesquite.            Undergrowth: greasewood, ocotillo and cactus.</p>								
	S.89°56'E., on random line, bet. secs. 15 and 22.								
40.00	Set temp. $\frac{1}{4}$ sec. cor.								
79.92	A point 14 lks. N. of the cor. of secs. 14, 15, 22 and 23.								
	Thence								

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4079

## Chains

- N.89°50'W., on true line, bet. secs. 15 and 22.  
Asc. 383 ft. over NE. slope; through scattering timber and undergrowth.
- 16.40 Ridge, bears N. and S.; desc. 322 ft. over W. slope.
- 39.96 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.  
Desc. 132 ft. over W. slope.
- 51.30 Wash, 15 lks. wide, course NW.; asc. 112 ft. over NE. slope.
- 62.50 Spur, slopes N. 20°W.; desc. 107 ft. over W. slope.
- 68.10 Wash, 15 lks. wide, course N.; asc. 136 ft. over E. slope.
- 76.10 Spur, slopes N.; desc. 46 ft. over W. slope.
- 79.92 The cor. of secs. 15, 16, 21 and 22.  
Land: rolling and mountainous.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N.0°02'W., bet. secs. 15 and 16.  
Asc. 48 ft. over SW. slope; through scattering timber and undergrowth.
- 10.35 Spur, slopes NW.; desc. 106 ft. over NE. slope.
- 17.30 Wash, 10 lks. wide, course NW.; asc. 18 ft. over S. slope.
- 29.40 Low spur, slopes SW.; desc. 70 ft. over NW. slope.
- 35.90 Wash, 15 lks. wide, course SW.; asc. 94 ft. over SE. slope.
- 40.00 True point for  $\frac{1}{4}$  sec. cor. falls on sloping ledge, an unsuitable place for cor. monument.
- 40.07 (7 lks. N.0°02'W. of true point) Mark a cross (K) on rock in place, 3 x 3 x 2 ft. above ground, for witness  $\frac{1}{4}$  sec. cor., and mark WC on S. and  $\frac{1}{4}$  on W. of cross, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.  
Asc. 30 ft. over SE. slope.
- 44.70 Spur, slopes SW.; over gentle NW. slope.
- 49.70 Wash, 20 lks. wide, course NE.; asc. 115 ft. over SE. slope.
- 54.20 S. rim of mesa; bears NE. and SW.; asc. gently.
- 72.00 Begin descent of 72 ft. over N. slope.
- 80.00 Set a lava stone, 22 x 9 x 8 ins., 6 ins. in the ground, and supported in a mound of stone, for cor. of secs. 9, 10, 15 and 16, mkd. with 4 grooves on S. and 3 grooves on E. faces, . . .

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land: rolling and mountainous. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	S. $89^{\circ}50'E.$ , on random line, bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	A point 5 lks. S. of the cor. of secs. 10, 11, 14 and 14.
	Thence
	N. $89^{\circ}52'W.$ , on true line, bet. secs. 10 and 15.
	Over gently rolling land; through scattering timber and undergrowth.
11.30	Old road, bears NW. and SE.
24.80	Wash, 12 lks. wide, course N.; asc. 110 ft. over E. slope.
39.00	Spur, slopes N.; desc. 63 ft. over W. slope.
39.98	Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Desc. 88 ft. over W. slope.
52.90	Wash, 20 lks. wide, course N.; asc. 57 ft. over E. slope.
75.80	Over rolling mesa, bears N. and S.
79.96	The cor. of secs. 9, 10, 15 and 16.
	Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	N. $0^{\circ}02'W.$ , bet. secs. 9 and 10.
	Over rolling mesa; through scattering timber and undergrowth.
2.00	Begin descent of 52 ft. over NW. slope.
3.30	Gulch, course NE.; asc. 32 ft. over SE. slope.
5.70	Over flat spur, slopes NE.
11.20	Leave same; desc. 42 ft. over NW. slope.
25.35	Wash, 15 lks. wide, course N. $15^{\circ}E.$ ; asc. 37 ft. over SE. slope.
33.00	Spur, slopes NE.; desc. 50 ft. over NW. slope.
40.00	Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4000

## Chains

- raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Asc. 105 ft. over SW. slope.
- 47.00 Spur, slopes NW.; desc. 97 ft. over NE. slope.
- 55.45 Wash, 20 lks. wide, course NW.; over gently rolling land.
- 65.40 Wash, 50 lks. wide, course NW.
- 67.00 Old road, bears N.80°W. and S.80°E.
- 67.20 Begin ascent of 75 ft. over S. slope.
- 80.00 Mark a cross (X) on lava stone, in place, 5 x 3 x 3 ft. above ground, for cor. of secs. 3, 4, 9 and 10, mkd. with 5 grooves S. and 3 grooves E. of cross, and  
raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Land: rolling.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- S.89°52'E., on random line, bet. secs. 3 and 10.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.12 A point 9 lks. S. of the cor. of secs. 2, 3, 10 and 11.  
Thence  
N.89°56'W., on true line, bet. secs. 3 and 10.  
Over gently rolling land; through scattering timber and undergrowth.
- 40.06 Set a lava stone, 24 x 10 x 8 ins., 18 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and  
dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.
- 65.60 Begin ascent of 120 ft. over SE. slope.
- 80.12 The cor. of secs. 3, 4, 9 and 10.  
Land: gently rolling and rolling.  
Soil: sandy and gravelly loam, 2nd and 4th rates.  
Timber: scattering ironwood, mesquite and palo verde.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N.0°10'W., on random line, bet. secs. 3 and 4.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.83 Intersect the N. bdy. of the Tp. at a point 23 lks. W. of the cor. of secs. 3, 4, 33 and 34, described in the official record of this Group.  
Thence  
South, on true line, bet. secs. 3 and 4.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
	Over gently rolling land; through scattering timber and undergrowth.
18.10	Begin ascent of 63 ft. over N. slope.
20.70	Spur, slopes E.; desc. 37 ft. over S. slope.
22.90	Wash, 10 lks. wide, course NE.; asc. 61 ft. over N. slope.
29.25	Spur, slopes E.; desc. 16 ft. over S. slope.
39.83	Set a lava stone, 20 x 8 x 8 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Desc. 36 ft. over SE. slope.
42.40	Wash, 20 lks. wide, course NE.; asc. 80 ft. over N. slope.
55.00	Spur, slopes NW.; desc. 25 ft. over SW. slope.
61.00	Gulch, course NW.; asc. 40 ft. over NE. slope.
65.80	Hill, bears NW. and SE.; over gradual S. slope.
79.83	The cor. of secs. 3, 4, 9 and 10.  Land: rolling and gently rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
	From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., as relocated by independent resurvey under this Group, described in the notes of the resurvey of the 2nd standard parallel, S., N.0°02'W., bet. secs. 32 and 33. Asc. 153 ft. over S. slope; through scattering timber and undergrowth.
6.50	Spur, slopes SE.; desc. 56 ft. over N. slope.
8.50	Gulch, course E.; asc. 56 ft. over S. slope.
11.00	Rim, bears NW. and SE.; over mesa land.
18.50	Rim bears NW. and SE.; desc. 55 ft. over NE. slope.
22.95	Wash, 30 lks. wide, course SE.; asc. 52 ft. over SW. slope.
30.40	Spur, slopes E.; desc. 23 ft. over gentle N. slope.
40.00	Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Desc. 43 ft. over gentle N. slope.
56.40	Wash, 40 lks. wide, course E.; asc. gently.
64.00	Begin ascent of 25 ft. over SW. slope.
66.80	Spur, slopes SE.; desc. 20 ft. over NE. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

23

BOOK 4039

Chains

- 67.90 Gulch, course SE.; asc. 37 ft. over SE. slope.
- 76.10 Ridge, bears E. and W.; over gentle N. slope.
- 80.00 Set a lava stone, 24 x 12 x 8 ins., 4 ins. in the ground to solid rock, and supported in a mound of stone, for cor. of secs. 28, 29, 32 and 33, mkd. with 1 groove on S. and 4 grooves on E. faces, and  
raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
Land: rolling.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- East, on random line, bet. secs. 28 and 33.
- 40.00 Set temp. ¼ sec. cor.
- 80.00 A point 9 lks. S. of the cor. of secs. 27, 28, 33 and 34.  
Thence  
S. 89° 56' W., on true line, bet. secs. 28 and 33.  
Asc. 336 ft. over E. slope; through scattering timber and undergrowth.
- 18.00 Spur, slopes N.; desc. 18 ft. over W. slope.
- 25.80 Wash, 20 lks. wide, course N.; asc. 25 ft. over E. slope.
- 30.80 Spur, slopes N.; desc. 120 ft. over W. slope.
- 38.80 Wash, 20 lks. wide, course N.; asc. 61 ft. over E. slope.
- 40.00 Mark a cross (X) on a lava stone in place, 3 x 2 x 2 ft. above ground, for ¼ sec. cor., and mark ¼ N. of cross, and  
raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.  
Asc. 117 ft. over broken E. slope.
- 49.90 Spur, slopes N.; desc. 20 ft. over W. slope.
- 58.30 Wash, 10 lks. wide, course N.; asc. 169 ft. over E. slope.
- 68.50 Spur, slopes N.; desc. 60 ft. over W. slope.
- 75.30 Gulch, course N.; asc. 60 ft. over NE. slope.
- 80.00 The cor. of secs. 28, 29, 32 and 33.  
Land: rolling and mountainous.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N. 0° 02' W., bet. secs. 28 and 29.  
Desc. 62 ft. over NE. slope; through scattering timber and undergrowth.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
4.20	Gulch, course NE.; over gentle S. slope.
15.80	Spur, slopes E.; over E. slope.
20.00	Head of gulch, course SE.; over gentle SE. slope.
23.80	Spur, slopes NE.; desc. 113 ft. over NW. slope.
28.10	Gulch, course NE.; asc. 74 ft. over SE. slope.
31.20	Rim, bears NE. and SW.; desc. 43 ft. over gentle N. slope.
40.00	Set a lava stone, 20x12 x 8 ins., 13 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Desc. 103 ft. over rolling N. slope.
80.00	Set a lava stone, 24 x 12 x 6 ins., 12 ins. in the ground to solid rock, and supported in a mound of stone, for cor. of secs. 20, 21, 28 and 29, mkd. with 2 grooves on S. and 4 grooves on E. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	N.89°56'E., on random line, bet. secs. 21 and 28.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	A point 14 lks. N. of the cor. of secs. 21, 22, 27 and 28.
	Thence
	N.89°58'W., on true line, bet. secs. 21 and 28.
	Desc. 47 ft. along N. slope; through scattering timber and undergrowth.
11.10	Wash, 10 lks. wide, course N.; asc. 147 ft. over E. slope.
18.00	Spur, slopes N.; desc. 128 ft. over W. slope.
39.97	Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Over gently rolling land:
43.30	Wash, 30 lks. wide, course NE.; asc. 216 ft. over E. slope.
55.00	Rim bears N. and S.; over flat spur, slopes N.
58.10	Rim, bears N. and S.; desc. 80 ft. over W. slope.
65.70	Wash, 20 lks. wide, course N.; asc. 141 ft. over E. slope.
75.50	Rim of mesa, bears N. and S.; asc. 20 ft. along N. slope.
79.94	The cor. of secs. 20, 21, 28 and 29. Land: rolling and mountainous.

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4059

## Chains

Soil: gravelly and rocky, 4th rate.  
 Timber: scattering palo verde and mesquite.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 N.0°02'W., bet. secs. 20 and 21.

Desc. 45 ft. over gentle N. slope; through scattering timber and undergrowth.

- 9.50 Rim of mesa, bears SW. and E.; desc. 100 ft. over N. slope.
- 15.40 Foot of slope; over gently rolling land.
- 25.40 Wash, 20 lks. wide, course N.30°W.; asc. 131 ft. over S. slope.
- 33.50 Rim of mesa, bears E. and W.; over mesa.
- 40.00 Set a lava stone, 20 x 12 x 6 ins., 14 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- 64.60 Rim of mesa, bears NE. and SW.; desc. 55 ft. over N. slope.
- 69.10 Gulch, course NE.; asc. 55 ft. over SE. slope.
- 74.60 Rim, bears NE. and SW.; desc. 40 ft. over N. slope.
- 80.00 Set a lava stone, 20 x 12 x 6 ins., 6 ins. in the ground to solid rock, supported in a mound of stone, for cor. of secs. 16, 17, 20 and 21, mkd. with 3 grooves on S. and 4 grooves on E. faces, and Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- Land: rolling.  
 Soil: gravelly and rocky, 4th rate.  
 Timber: scattering palo verde and mesquite.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 S.89°58'E., on random line, bet. secs. 16 and 21.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.90 A point 2 lks. S. of the cor. of secs. 15, 16, 21 and 22.
- Thence
- N.89°59'W., on true line, bet. secs. 16 and 21.
- Desc. 57 ft. over rocky W. slope; through scattering timber and undergrowth.
- 7.00 Wash, 20 lks. wide, course N.; asc. 108 ft. over E. slope.
- 20.40 Spur, slopes N.; desc. 112 ft. over W. slope.
- 27.70 Head of gulch, course N.; asc. 47 ft. over E. slope.
- 33.40 Rim of mesa, bears N. and S.; over mesa.
- 39.95 Set a lava stone, 24 x 8 x 6 ins., 5 ins. in the ground to solid rock, supported in a mound of stone, for  $\frac{1}{4}$  sec. cor., mkd. on N. face, and

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains	
	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Desc. 50 ft. over NW. slope.
44.20	Wash, 25 lks. wide, course NE.; asc. 281 ft. over E. slope.
53.90	Rim, bears N. and S.; over mesa.
62.00	Rim bears N. and S.; desc. 73 ft. over W. slope.
65.20	Wash, 20 lks. wide, course N.
66.80	Wash, 10 lks. wide, course NE.; asc. 106 ft. over NE. slope.
72.40	Rim of mesa, bears NW. and SE.; desc. 20 ft. along N. slope.
79.90	The cor. of secs. 16, 17, 20 and 21.
	Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N.0°02'W., bet. secs. 16 and 17.
	Over mesa, slopes NW.; through scattering timber and undergrowth.
2.00	Rim of mesa, bears NE. and SW.; desc. 213 ft. over NW. slope.
13.30	Wash, 20 lks. wide, course NE.; asc. 45 ft. over SE. slope.
20.00	Top of ascent; desc. 48 ft. over NE. slope.
28.85	Wash, 20 lks. wide, course NW.; over W. slope.
31.85	Point of spur, slopes W.; desc. 71 ft. over N. slope.
40.00	Set a lava stone, 28 x 12 x 10 ins., 6 ins. in the ground to solid rock, supported in a mound of stone, for ¼ sec. cor., mkd. ¼ on W. face, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Desc. 25 ft. over NW. slope.
43.50	Head of gulch, course W.; asc. 82 ft. over rocky SW. slope.
50.50	Spur, slopes SW.; desc. 76 ft. over NW. slope.
58.80	Gulch, course SW.; asc. 112 ft. over SE. slope.
67.10	Spur, slopes SW.; desc. 137 ft. over NW. slope.
80.00	Set a lava stone, 24 x 12 x 8 ins., 18 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, mkd. with 4 grooves on S. and 4 grooves on E. faces, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4059

Chains	
	S.89°59'E., on random line, bet. secs. 9 and 16.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	A point 9 lks. S. of the cor. of secs. 9,10,15 and 16.
	Thence
	S.89°57'W., on true line, bet. secs. 9 and 16.
	Over rolling mesa; through scattering timber and undergrowth.
5.00	Head of gulch, course NE.
18.05	Rim, bears N. and S.; desc. 54 ft. over W. slope.
22.35	Wash, 10 lks. wide, course NE.; asc. 63 ft. over E. slope.
24.50	Spur, slopes NE.; desc. 47 ft. over NW. slope.
33.40	Wash, 20 lks. wide, course NE.; asc. 86 ft. over SE.slope.
37.30	Rim of mesa, bears N. and S.; over mesa.
40.01	Set a lava stone, 24 x 10 x 6 ins., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
45.00	Rim of mesa, bears N. and S.; desc. 96 ft. over W. slope.
50.40	Wash, 20 lks. wide, course N.15°E.; asc. 90 ft. over E. slope.
57.90	Spur, slopes N.20°E.; desc. 60 ft. over NW. slope.
62.50	Wash, 20 lks. wide, course NE.; asc. 106 ft. over SE.slope.
69.10	Spur, slopes NE.; desc. 94 ft. over NW. slope.
80.02	The cor. of secs. 8,9,16 and 17.
	Land: rolling. Soil: sandy and gravelly, rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	N.0°02'W., bet. secs. 8 and 9.
	Over gentle NW. slope; through scattering timber and undergrowth.
2.70	Wash, 30 lks. wide, course NE.; asc. 111 ft. over SE. slope.
15.90	Rim of mesa, bears NE. and SW.; over mesa.
40.00	Set a lava stone, 20 x 10 x 9 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
43.50	Rim of mesa, bears NE. and SW.; desc. 58 ft. over NW.slope.
50.20	Head of gulch, course W.; asc. 38 ft. over SW. slope.
59.00	Rim bears NW. and SE.; over mesa.

## SUBDIVISIONS OF T.9 S., R.7 W.

## Chains

- 70.00 Rim, bears NE. and W.; desc. 96 ft. over NW. slope.
- 80.00 Set a lava stone, 24 x 15 x 15 ins., 18 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, mkd. with 5 grooves on S. and 4 grooves on E. faces, and  
raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
Land: rolling.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N. 89°57'E., on random line, bet. secs. 4 and 9.
- 40.00 Set temp. ¼ sec. cor.
- 80.02 A point 14 lks. N. of the cor. of secs. 3, 4, 9 and 10.  
Thence  
N. 89°57'W., on true line, bet. secs. 4 and 9.  
Desc. 136 ft. over SW. slope; through scattering timber and undergrowth.
- 10.00 Foot of slope, bears N. and S.; over gently rolling land.
- 20.00 Road, bears N. and SE.
- 27.90 Wash, 25 lks. wide, course N. 20°W.
- 32.90 Begin ascent of 74 ft. over E. slope.
- 35.20 Rim, bears N. and S.; over mesa.
- 40.01 Set a lava stone, 22 x 12 x 10 ins., 6 ins. in the ground to solid rock, supported in a mound of stone, for ¼ sec. cor., mkd. ¼ on N. face, and  
raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
- 42.60 Rim bears N. and S.; desc. 34 ft. over W. slope.
- 44.70 Wash, 20 lks. wide, course N.; asc. 83 ft. over E. slope.
- 55.00 Rim, bears N. and S.; over mesa.
- 62.20 Rim, bears N. and S.; desc. 39 ft. over W. slope.
- 67.00 Wash, 10 lks. wide, course N.; asc. 34 ft. over E. slope.
- 75.10 Spur, slopes N.; desc. 69 ft. over NW. slope.
- 80.02 The cor. of secs. 4, 5, 8 and 9.  
Land: rolling and mesa.  
Soil: sandy and gravelly loam, 2nd and 4th rates.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- North, on random line, bet. secs. 4 and 5.
- 40.00 Set temp. ¼ sec. cor.

## SUBDIVISIONS OF T. 9 S., R. 7 W.

BOOK 4059

Chains	
79.80	Intersect the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., established under this Group, described in notes of that line.
	Thence
	South, on true line, bet. secs. 4 and 5.
	Over gently rolling land; through scattering timber and undergrowth.
24.80	Wash, 25 lks. wide, course W.
39.80	Set a lava stone, 24 x 12 x 8 ins., 8 ins. in the ground to solid rock, supported in a mound of stone, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
59.10	Wash, 10 lks. wide, course NE.; asc. 81 ft. over NW. slope.
66.90	Spur, slopes NE.; desc. 55 ft. over SE. slope.
69.80	Foot of slope, bears NE. and SW.; over gently rolling land.
79.00	Wash, 50 lks. wide, course NE.
79.80	The cor. of secs. 4, 5, 8 and 9.
	Land: rolling and gently rolling.
	Soil: sandy and gravelly loam, rocky, 2nd and 4th rates.
	Timber: scattering ironwood, mesquite and palo verde.
	Undergrowth: greasewood, ocotillo and cactus.
-----	
	From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., as relocated by independent resurvey under this Group, described in notes of resurvey of 2nd standard parallel, S.,
	N. 0° 03' W., bet. secs. 31 and 32.
	Over gently rolling land; through scattering timber and undergrowth.
10.60	Wash, 7 lks. wide, course SE.; asc. 342 ft. over SE. slope.
27.30	Spur, slopes SW.; desc. 57 ft. over N. slope.
32.55	Gulch, course SW.; asc. 67 ft. over S. slope.
40.00	Set a lava stone, 20 x 8 x 7 ins., 10 ins. in the ground to solid rock and in a mound of stone, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, and
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Desc. 24 ft. over NE. slope.
43.30	Gulch, course SE.; asc. 246 ft. over S. slope.
58.10	Ridge, bears E. and W.; desc. 235 ft. over N. slope.
71.35	Wash, 6 lks. wide, course NW.; desc. 57 ft. over NW. slope.
76.30	Gulch, course W.; asc. 71 ft. over W. slope.
80.00	Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, mkd. with 1 groove on S. and 5 grooves on E. faces, and

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land: gently rolling to mountainous.

Soil: gravelly and rocky, 4th rate.

Timber: scattering palo verde and mesquite.

Undergrowth: greasewood, ocotillo and cactus.

-----  
East, on random line, bet. secs. 29 and 32.

40.00 Set temp.  $\frac{1}{2}$  sec. cor.

80.08 A point 12 lks. S. of the cor. of secs. 28, 29, 32 and 33.

Thence

S.  $89^{\circ}55'$  W., on true line, bet. secs. 29 and 32.

Over gentle NE. slope; through scattering timber and undergrowth.

4.00 Spur, slopes N.; over gentle W. slope.

5.40 Head of gulch, course NW.; asc. 10 ft. along N. slope.

20.10 Spur, slopes N.; desc. 220 ft. over NW. slope.

40.04 Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

Desc. 71 ft. along N. slope.

48.90 Wash, 40 lks. wide, course NE.; asc. 220 ft. over SE. slope.

65.30 Spur, slopes NE.; desc. 47 ft. over NW. slope.

71.45 Head of wash, 10 lks. wide, course NE.; asc. 55 ft. over SE. slope.

73.40 Ridge, bears S.  $80^{\circ}$  E. and W.; spur, slopes NE.; desc. 160 ft. over W. slope.

80.08 The cor. of secs. 29, 30, 31 and 32.

Land: rolling.

Soil: gravelly and rocky, 3rd rate.

Timber: scattering palo verde and mesquite.

Undergrowth: greasewood, ocotillo, catclaw and cactus.

-----  
West, on random line, bet. secs. 30 and 31.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the W. bdy. of the Tp. at a point 12 lks. N. of the cor. of secs. 25, 30, 31 and 36, established under this Group, described in notes of that line.

Thence

N.  $89^{\circ}55'$  E., on true line, bet. secs. 30 and 31.

Over gentle S. slope; through scattering timber and undergrowth.

12.80 Wash, 10 lks. wide, course SW.; asc. 133 ft. over W. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4059

Chains	
25.00	Spur, slopes SW.; desc. 178 ft. over E. slope.
40.00	Set a lava stone, 20 x 9 x 6 ins., 15 ins. in the ground, for sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
41.00	Wash, 20 lks. wide, course SW.
43.45	Wash, 20 lks. wide, course SW.; over gentle W. slope.
57.75	Point of spur, slopes SW.; asc. 101 ft. over broken S. slope.
71.00	Wash, 20 lks. wide, course SW.; asc. 131 ft. over SW. slope.
80.00	The cor. of secs. 29, 30, 31 and 32.  Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cacti.
-----	
	N. $0^{\circ}03'$ W., bet. secs. 29 and 30. Asc. 171 ft. over SW. slope; through scattering timber and undergrowth.
6.80	Ridge, bears NW. and SE.; desc. 172 ft. over NE. slope.
15.30	Wash, 40 lks. wide, course E.; asc. 261 ft. over SE. slope.
23.90	Spur, slopes NE.; desc. 212 ft. over NW. slope.
34.50	Wash, 30 lks. wide, course NE.; asc. 38 ft. over SE. slope.
40.00	Set a lava stone, 22 x 8 x 6 ins., 16 ins. in the ground, for sec. cor., mkd. $\frac{1}{2}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Asc. 62 ft. over SE. slope.
51.20	Spur, slopes NE.; desc. 292 ft. over NW. slope.
64.65	Wash, 50 lks. wide, course NW.; asc. 251 ft. over SW. slope.
80.00	Mark a cross (X) on exposed bedrock and over it, in a mound of stone, set a lava stone, 20 x 9 x 6 ins., for cor. of secs. 19, 20, 29 and 30, mkd. with 2 grooves on S. and 5 grooves on E. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.  Land: rolling and mountainous. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
-----	
	N. $89^{\circ}55'$ E., on random line, bet. secs. 20 and 29.
40.00	Set temp. sec. cor.
79.98	A point 7 lks. S. of the cor. of secs. 20, 21, 28 and 29. Thence

## SUBDIVISIONS OF T.9 S., R.7 W.

## Chains

S.89°52'W., on true line, bet. secs. 20 and 29.

Over rolling mesa; through scattering timber and undergrowth.

- 3.10 Rim, bears NE. and SW.; desc. 113 ft. over NW. slope.  
 7.00 Foot of slope, bears NE. and SW.; over gently rolling land.  
 8.70 Wash, 60 lks. wide, course NE.  
 15.60 Wash, 30 lks. wide, course NE.; asc. 223 ft. over E. slope.  
 30.70 Rim, bears N. and S.; over mesa.  
 39.99 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and  
 raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 41.50 Rim, bears N. and S.; desc. 214 ft. over W. slope.  
 53.80 Wash, 30 lks. wide, course N.; asc. 377 ft. over E. slope.  
 78.30 Spur, slopes N.; desc. 25 ft. over W. slope.  
 79.98 The cor. of secs. 19, 20, 29 and 30.

Land: mesa, rolling and mountainous.

Soil: gravelly and rocky, 4th rate.

Timber: scattering palo verde and mesquite.

Undergrowth: greasewood, ocotillo and cactus.

S.89°55'W., on random line, bet. secs. 19 and 30.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.91 Intersect the W. bdy. of the Tp. at a point 2 lks. N. of the cor. of secs. 19, 24, 25 and 30, established under this group, described in notes of that line.

## Thence

N.89°54'E., on true line, bet. secs. 19 and 30.

Over gentle S. slope; through scattering timber and undergrowth.

- 1.10 Wash, 10 lks. wide, course N.70°E.; desc. 76 ft. along N. slope.  
 11.00 Point of spur, slopes NE.; desc. 125 ft. over E. slope.  
 17.00 Wash; 30 lks. wide, course N.; asc. 356 ft. over W. slope.  
 27.00 Rim, bears N. and S.; desc. 89 ft. over mesa, slopes N.  
 39.91 Set a lava stone, 24 x 8 x 6 ins., 16 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and  
 raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 Over nearly level mesa.  
 46.90 Rim, bears N. and S.; desc. 258 ft. over E. slope.  
 52.00 Wash, 30 lks. wide, course N.; asc. 284 ft. over W. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4059

## Chains

- 58.30 Rim, bears N. and S.; desc. 37 ft. over E. slope.  
 60.80 Gulch, course NE.; asc. 31 ft. over W. slope.  
 64.70 Spur, slopes N.; desc. 341 ft. over E. slope.  
 72.40 Wash, 30 lks. wide, course N.; asc. 352 ft. over W. slope.  
 79.91 The cor. of secs. 19, 20, 29 and 30.

Land: mountainous.  
 Soil: gravelly and rocky, 4th rate.  
 Timber: scattering palo verde and mesquite.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 N.0°03'W., bet. secs. 19 and 20.

Desc. 190 ft. along W. slope; through scattering timber and undergrowth.

- 14.60 Foot of descent; asc. 69 ft. along W. slope.  
 22.70 Spur, from SE., slopes N.; desc. 310 ft. over N. slope.  
 38.10 Foot of descent; over saddle, drains E. and W.  
 40.00 Set a lava stone, 20 x 12 x 6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and  
     raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 52.40 Leave saddle; begin ascent of 117 ft. over SE. slope.  
 67.00 Top of butte; desc. 178 ft. over N. slope.  
 75.10 Foot of slope; over gently rolling land.  
 80.00 Set a lava stone, 20 x 8 x 7 ins., 15 ins. in the ground, for cor. of secs. 17, 18, 19 and 20, mkd. with 3 grooves on S. and 5 grooves on E. faces, and  
     raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land: rolling and mountainous.  
 Soil: gravelly and rocky, 4th rate.  
 Timber: scattering palo verde and mesquite.  
 Undergrowth: greasewood, ocotillo and cactus.

-----  
 N.89°52'E., on random line, bet. secs. 17 and 20.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.00 Intersect the cor. of secs. 16, 17, 20 and 21.

Thence

S.89°52'W., on true line, bet. secs. 17 and 20.

Over mesa; through scattering timber and undergrowth.

- 5.80 Rim, bears NE. and SW.; desc. 251 ft. over NW. slope.  
 13.60 Wash, 10 lks. wide, course N.; asc. 50 ft. over E. slope.  
 15.00 Spur, slopes N.; desc. 51 ft. over W. slope.

## SUBDIVISIONS OF T.9 S., R.7 W.

## Chains

- 16.30 Foot of slope, bears N. and S.; over gently rolling land.
- 20.90 Wash, 30 lks. wide, course NE.; asc. 56 ft. over SE.slope.
- 24.00 Spur, slopes NE.; desc. 56 ft. over NW. slope.
- 38.40 Wash, 20 lks. wide, course NE.; asc. 19 ft. over SE.slope.
- 40.00 Set a lava stone, 20 x 14 x 6 ins., 8 ins. in the ground to solid rock and supported in a mound of stone, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and  
raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.  
Asc. 187 ft. over SE. slope.
- 49.70 Spur, slopes NE.; desc. 195 ft. over NW. slope.
- 57.10 Gulch, course N.; asc. 59 ft. over E. slope.
- 58.60 Spur, slopes N.; desc. 87 ft. over W. slope.
- 61.40 Foot of slope, bears N. and S.; over gently rolling land.
- 68.00 Wash, 70 lks. wide, course NW.
- 77.10 Wash, 60 lks. wide, course NW.
- 80.00 The cor. of secs. 17, 18, 19, and 20.  
Land: gently rolling to mountainous.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- S.89°54'W., on random line, bet. secs. 18 and 19.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.87 Intersect the W. bdy. of the Tp. at a point 7 lks. N. of the cor. of secs. 13, 18, 19 and 24, established under this Group, described in notes of that line.
- Thence  
N.89°51'E., on true line, bet. secs. 18 and 19.  
Asc. 179 ft. over NW. slope; through scattering timber and undergrowth.
- 3.50 Over flat top of spur, slopes NE.
- 6.70 Leave same; desc. 257 ft. over SE. slope.
- 14.30 Wash, 30 lks. wide, course NE.; asc. 44 ft. over NW, slope.
- 26.50 Rocky spur, slopes N.; desc. 76 ft. over SE. slope.
- 34.80 Wash, 50 lks. wide, course NW.; over gently rolling land.
- 39.87 Set a lava stone, 30 x 12 x 10 ins., 20 ins. in the ground for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on N. face, and  
raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.
- 51.40 Wash, 100 lks. wide, course NW.

## SUBDIVISIONS OF T.9 S., R.7 W.

BOOK 4059

## Chains

- 65.90 Begin ascent of 62 ft. over SW. slope.
- 67.70 Spur, slopes S.; desc. 50 ft. over E. slope.
- 74.70 Wash, 60 lks. wide, course SW.; over gently rolling land.
- 79.87 The cor. of secs. 17,18,19 and 20.
- Land: rolling and gently rolling.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N.0°03'W., bet. secs. 17 and 18.
- Over gently rolling land; through scattering timber and undergrowth.
- 1.90 Wash, 60 lks. wide, course W.; asc. 186 ft. over SE.slope.
- 7.05 Spur, slopes SW.; desc. 151 ft. over NW. slope.
- 24.55 Wash, 30 lks. wide, course NW.; asc. 21 ft. over SW. slope.
- 25.90 Spur, slopes NW.; desc. 106 ft. over NE. slope.
- 37.80 Wash, 15 lks. wide, course NW.; asc. slightly over SW. slope.
- 40.00 Set a lava stone, 22 x 9 x 6 ins., 16 ins. in the ground, for  $\frac{1}{4}$  sec. cor., mkd.  $\frac{1}{4}$  on W. face, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. Asc. 147 ft. over SW. slope.
- 60.40 Spur, slopes NW.; desc. 111 ft. over NE. slope.
- 65.30 Wash, 100 lks. wide, course NW.; asc. 99 ft. over S. slope.
- 70.10 Point of spur, slopes W.; desc. 119 ft. over N. slope.
- 74.50 Wash, 30 lks. wide, course W.; asc. 105 ft. over SE.slope.
- 77.00 Spur, slopes SW.; over gentle NW. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7,8,17 and 18, with brass cap mkd.
- |      |     |
|------|-----|
| T9S  | R7W |
| S7   | S8  |
| S18  | S17 |
| 1934 |     |
- and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.
- Land: rolling.  
Soil: gravelly and rocky, 4th rate.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.
- 
- N.89°52'E., on random line, bet. secs. 8 and 17.
- 40.00 Set temp.  $\frac{1}{2}$  sec. cor.

Chains	
79.94	A point 21 lks. N. of the cor. of secs. 8,9,16 and 17. Thence N.89°59'W., on true line, bet. secs. 8 and 17. Over rolling NW. slope; through scattering timber and undergrowth.
11.40	Wash, 20 lks. wide, course NE.
13.90	Foot of slope, bears NE. and SW.; asc. 116 ft. over SE. slope.
19.10	Rim, bears NE. and SW.; over mesa land.
34.40	Rim, bears NE. and SW.; desc. 87 ft. over W. slope.
39.45	Wash, 10 lks. wide, course N.; asc. gently.
39.97	Set a lava stone, 20 x 10 x 8 ins., 6 ins. in the ground to solid rock and supported in a mound of stone, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Asc. 107 ft. over NE. slope.
48.20	Spur, slopes NW.; desc. 97 ft. over SW. slope.
60.30	Wash, 20 lks. wide, course SW.; asc. 79 ft. over SE. slope.
70.65	Spur, slopes SW.; desc. 85 ft. over NW. slope.
75.50	Wash, 10 lks. wide, course SW.; asc. 73 ft. over SE. slope.
79.10	Spur, slopes SW.; over gentle NW. slope.
79.94	The cor. of secs. 7,8,17 and 18. Land: rolling. Soil: gravelly and rocky, 4th rate. Timber: scattering palo verde and mesquite. Undergrowth: greasewood, ocotillo and cactus.
	-----
	S.89°51'W., on random line, bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.83	Intersect the W. bdy. of the Tp. at a point 2 lks. N. of the cor. of secs. 7,12,13 and 18, established under this Group, described in notes of that line. Thence N.89°50'E., on true line, bet. secs. 7 and 18. Over gently rolling land; through scattering timber and undergrowth.
10.80	Wash, 20 lks. wide, course N.30°W.
39.83	Set a lava stone, 20 x 12 x 8 ins., 16 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

SUBDIVISIONS OF T.9 S., R.7 W.

Chains

53.00 Wash, 60 lks. wide, course N.20°E.

64.00 Begin ascent of 187 ft. over W. slope.

79.83 The cor. of secs. 7,8,17 and 18.

Land: gently rolling to mountainous.  
Soil: gravelly and rocky, 2nd and 4th rates.  
Timber: scattering palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.

N.0°03'W., bet. secs. 7 and 8.

Asc. 84 ft. along W. slope; through scattering timber and undergrowth.

9.65 Spur, slopes W.; desc. 139 ft. over N. slope.


14.20 Foot of slope, bears E. and W.; over gently rolling land.

18.50 Begin ascent of 77 ft. over SW. slope.

22.90 Hill, bears NW. and SE.; desc. 163 ft. over NE. slope.


32.60 Foot of slope, bears NW. and SE.; over gently rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 5,6,7 and 8, with brass cap mkd.



and dig pits, 18 x 18 x 12 ins., one in each sec., 3 ft. dist.

Land: rolling and gently rolling.  
Soil: sandy and gravelly loam, 2nd and 4th rates.  
Timber: scattering ironwood, palo verde and mesquite.  
Undergrowth: greasewood, ocotillo and cactus.

S.89°59'E., on random line, bet. secs. 5 and 8.

40.00 Set temp. 1/4 sec. cor.

79.92 Intersect the cor. of secs. 4,5,8 and 9.

Thence

N.89°59'W., on true line, bet. secs. 5 and 8.

Over gently rolling land; through scattering timber and undergrowth.

## SUBDIVISIONS OF T.9 S., R.7 W.

Chains

- 0.70 Wash, 50 lks. wide, course NE.; asc. 63 ft. over E. slope.  
 10.00 Spur, slopes N.; over flat top of same.  
 17.40 Leave same; desc. 85 ft. over W. slope.  
 23.00 Foot of slope, bears NE. and S.; over gently rolling land.  
 39.96 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{S5}{438}$$

1934

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

- 73.40 Wash, 35 lks. wide, course N.  
 79.92 The cor. of secs. 5,6,7 and 8.

Land: rolling and gently rolling.  
 Soil: sandy and gravelly loam, 2nd and 4th rates.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, ocotillo and cactus.

S.89°50'W., on random line, bet. secs. 6 and 7.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.

- 79.78 Intersect the cor. of secs. 1,6,7 and 12, on the W. bdy. of the Tp., established under this Group, described in notes of that line.

Thence

N.89°50'E., on true line, bet. secs. 6 and 7.

Over gently rolling land; through scattering timber and undergrowth.

- 31.70 Wash, 10 lks. wide, course N.  
 39.78 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{S6}{437}$$

1934

and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

- 79.78 The cor. of secs. 5,6,7 and 8.

Land: gently rolling.  
 Soil: sandy and gravelly loam, 2nd rate.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

## SUBDIVISIONS OF T.9 S., R.7 W.

9039

- Chains North, on random line, bet. secs. 5 and 6.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.66 Intersect the N. bdy. of the Tp. at a point 26 lks. E. of the cor. of secs. 5, 6, 31 and 32, established under this Group, described in notes of that line.
- Thence
- S.0°11'E., on true line, bet. secs. 5 and 6.
- Over gently rolling land; through scattering timber and undergrowth.
- 24.60 Wash, 50 lks. wide, course NW.
- 39.66 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   
 S6 | S5  
 1934
- 79.66 and dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.  
 The cor. of Secs. 5, 6, 7, and 8.  
 Land: gently rolling.  
 Soil: sandy and gravelly loam, 2nd rate.  
 Timber: scattering ironwood, mesquite and palo verde.  
 Undergrowth: greasewood, catclaw, ocotillo and cactus.

## GENERAL DESCRIPTION

T.9 S., R.7 W., lies about 25 miles south-westerly from the town of Gila Bend and about 20 miles south-easterly from the town of Sentinel, Ariz. Two secondary roads from Sentinel cross the NE. part of the Tp., continuing south-easterly to the town of Ajo.

About two-thirds of the township exposes a volcanic formation, which drains northerly and southerly from a ridge about 1 mile north of the S. bdy. of the Tp. It is eroded and broken, with only small portions of the top of the lava flow remaining. Configuration is generally flat ridges, breaking sharply into flat valleys of varying width. The area is shown on maps as Crater Mts.

The sea-level of the highest part of the Tp. is about 1,700 ft., from which it lowers to 1000 to 1200 ft., the elevation of the alluvial areas in the north and west parts of the Tp.

Soil in the volcanic portion is shallow and almost non-existent; in about 9 square miles along the north and west boundaries it is of fairly good depth and quality, suitable for agriculture if irrigated.

Vegetation is of the usual desert varieties, sparse and of small size except along some of the washes. A small amount of the timber species are suitable for fuel and fencing.

There are three small tanks in sec. 22, one natural and two with concrete dams built by a cow-man. Stock-raising is the only industry in the township, though grass and browse are poor. There are no other improvements.

There are no residents; there is no evidence of mineral.

4-679 b

~~SECTION~~ DIAGRAM.

Township *9 South*, Range *7 West*

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

6-4817

- Surveyed by Frank C. Mulford, Temporary Transitman.
- Surveyed by R. E. McMahan, Temporary Transitman.
- Surveyed by K. K. Bowsher, Temporary Transitman.
- Surveyed by Ben D. Proctor, Temporary Transitman.



BOOK 4059

CERTIFICATE OF UNITED STATES SURVEYOR

I, Frank C. Mulford *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of \_\_\_\_\_ the SUBDIVISION LINES of \_\_\_\_\_ Township 9 South, Range 7 West \_\_\_\_\_ of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*Frank C. Mulford*  
*Temporary Transitman.*

~~APPROVAL~~

~~Office of U. S. Supervisor of Surveys,~~

~~\_\_\_\_\_ , 19\_\_\_\_~~

~~The foregoing field notes of the survey of \_\_\_\_\_~~

~~executed by \_\_\_\_\_~~

~~under his special instructions dated \_\_\_\_\_, 19\_\_\_\_, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in \_\_\_\_\_, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~



44 BOOK 4059

CERTIFICATE OF UNITED STATES SURVEYOR

I, R. E. McMahan *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of  
Township 9 South, Range 7 West  
of the Gila and Salt  
River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

*R. E. McMahan*  
*Temporary Transitman*

~~APPROVAL~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~, 19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under his special instructions dated~~ 10 ~~, 19~~ ~~having been~~

~~critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above described surveys in~~

~~, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~



214  
46  
BOOK 4059

CERTIFICATE OF UNITED STATES SURVEYOR

I, K. K. Bowsher *Temporary Transitman*, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of  
Township 9 South, Range 7 West  
of the Gila and Salt  
River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

K. K. Bowsher  
*Temporary Transitman.*

~~APPROVAL~~

~~OFFICE OF U. S. SUPERVISOR OF SURVEYS,~~

~~, 19~~

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under his special instructions dated~~, 10~~th~~, ~~having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.~~

~~U. S. Supervisor of Surveys.~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in~~

~~, has been correctly copied from the original notes on file in this office.~~

~~U. S. Supervisor of Surveys.~~



CERTIFICATE OF UNITED STATES SURVEYOR

I, Ben D. Procter Temporary Transitman, hereby certify upon honor that, in pursuance of special instructions received from the District Cadastral Engineer for Arizona bearing date of the 12th day of December, 1933, I have well, faithfully, and truly in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of the SUBDIVISION LINES of Township 9 South, Range 7 West of the Gila and Salt River Base and Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the District Cadastral Engineer for Arizona and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

Ben D. Procter Temporary Transitman.

APPROVAL

Office of U. S. SUPERVISOR of SURVEYS.

Denver, Colorado, May 16, 1935

The foregoing field notes of the survey of the SUBDIVISION LINES of Township 9 South, Range 7 West of the Gila and Salt River Base and Meridian, in the State of Arizona

executed by Frank C. Mulford R.E. McMahan K.K. Bowsher and Ben D. Procter, Temporary Transistmen

under special instructions dated December 12, 1933-Group 100, Arizona, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above described surveys in has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.