

4237

ORIGINAL 2/1

4-679
(April 1933)

Book "E"

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

BOOK 4237

FIELD NOTES

of the survey of

4237

NORTH BOUNDARY

and

SUBDIVISION LINES of

TOWNSHIP NO. 8 SOUTH, RANGE NO. 2 WEST

Of the Gila and Salt River Meridian,

In the State of ARIZONA

EXECUTED BY

TY WHITE

FRANK KENNON and NORVILLE E. SHEARER

PUBLIC LAND SURVEYORS

4237

Under special instructions dated December 1, 1937, which provided for the surveys included under Group No 197 Arizona, bearing the approval of the Commissioner of the General Land Office under date of January 14, 1938 and assignment instructions dated February 18 and April 4, 1938.

Survey commenced April 8, 1938

Survey completed April 20, 1938

INDEX DIAGRAM.

Township _____, *Range* _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

~INDEX-DIAGRAM~

BOOK 4287

36	31	32	33	34	35	36	31					
	3	4	5	6	6	7	7	8				
1	6	57	5	45	4	36	3	27	2	17	1	6
	56	57	58	56	44	35	27	26	18	17		
12	7	55	8	44	9	34	10	26	11	16	12	7
	54	53	43	43	42	34	32	25	24	15		
13	18	53	17	42	16	33	15	24	14	15	13	18
	52	52	41	T. 8 S. 32 R. 2 W. 25		41	32	23	14	13		
24	19	50	20	40	21	31	22	22	23	13	24	19
	49	50	49	40	39	31	30	21	12	12	11	
25	30	48	29	39	28	30	27	20	26	11	25	30
	47	48	47	46	38	37	29	20	19	10	10	
36	31	46	32	37	33	28	34	19	35	9	36	31
	45	36						18				
1	6	5	4	3	2	1	6					

———— Lines of accepted surveys.

———— Lines surveyed under this group.

- - - - Lines to be surveyed under this group.

———— Lines surveyed under current Group 198 (Approval pending)



Areas surveyed as per accepted plats on file.



Areas surveyed under current Group 198 (Approval pending)

The surveys herein described were executed by Ty White, Norville E. Shearer, and Frank Kennon, Public Land Surveyors, using, respectively, Buff and Buff transits Nos. 18002 and 10125, and Young and Sons' transit No. 8584. Each of these instruments is equipped with an improved Smith solar attachment and otherwise conforms to the standard specifications of the General Land Office.

The instruments were examined and tested by the District Cadastral Engineer for Arizona and California prior to the beginning of the surveys of this group, and were approved conditional upon satisfactory field tests of same.

The azimuths of all of the lines of survey herein described were determined with the solar attachments.

All measurements were made with Lufkin and Dietzgen steel tapes, 5 chs. in length, graduated every link for the first 100 lks., and the remainder at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard steel tape, and found to be correct. All of the measurements were made on the slope, the vertical angle of each interval determined with a clinometer in good adjustment and the horizontal equivalents entered in the field notes.

PRELIMINARY FIELD TESTS OF INSTRUMENTS.

Buff and Buff transit No. 18002
Ty White, Public Land Surveyor.

April 7, 1938; at camp near cor. of secs. 2, 3, 10 and 11, T. 8 S., R. 2 W., G. & S.R. Meridian, Arizona, in latitude $32^{\circ} 45' 15''$ N.; longitude $112^{\circ} 26\frac{1}{2}'$ W., examine the adjustments of Buff and Buff transit No. 18002 and find no errors; then, to test the solar apparatus by comparing its indications with a true meridian, proceed as follows:

At 6h. 35.5 m., p.m., l.m.t., observe Polaris at western elongation, making four observations, two each with the telescope in direct and reversed positions, and mark the mean point in the line thus determined by a nail in a stake driven firmly in the ground about 10 chs. N. Azimuth of Polaris at western elongation = $1^{\circ} 13' 22''$.

April 8, 1938; at 7h. 00m., a.m., lay off the azimuth of Polaris $1^{\circ} 13\frac{1}{2}'$ to the east, and mark the true meridian thus determined by a nail in a stake driven firmly in the ground about 10 chs. N.

April 10, 1938; at 9h. 00m., a.m., app.t., set off $32^{\circ} 45'$ N. on the latitude arc; $7^{\circ} 53'$ N. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of $7^{\circ} 56'$ N. on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged; set off $7^{\circ} 59'$ N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

BOOK 4201

2.

As all of the solar observations made during the usual hours of solar work come within 1' 30" of the true meridian, conclude that this instrument is in satisfactory adjustment on this date prior to beginning the surveys with same which are hereinafter described.

Buff and Buff transit No. 10125
Norville E. Shearer, Public Land Surveyor.

April 10, 1938; at same station described in the preceding test, examine the adjustments of Buff and Buff transit No. 10125 and find no errors; then, to test the solar apparatus by comparing its indications with the same true meridian, proceed as follows:

At 9h. 00m., a.m., app.t., set off 32° 45' N. on the latitude arc; 7° 53' N. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of 7° 56' N. on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged; set off 7° 59' N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within 1' 30" of the true meridian, conclude that this instrument is in satisfactory adjustment on this date prior to beginning the surveys with same which are hereinafter described.

Young and Sons' transit No. 8584
Frank Kennon, Public Land Surveyor.

April 10, 1938; at same station described in preliminary test of Buff and Buff transit No. 18002, examine the adjustments of Young and Sons' transit No. 8584 and find no errors; then, to test the solar apparatus by comparing its indications with the same true meridian, proceed as follows:

At 9h. 00m., a.m., app.t., set off 32° 45' N. on the latitude arc; 7° 53' N. on the declination arc; and determine a meridian with the solar which agrees with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of 7° 56' N. on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged, set off 7° 59' N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within 1' 30" of the true meridian, conclude that this instrument is in satisfactory adjustment on this date prior to beginning the surveys with same which are hereinafter described.

Chains

From the cor. of Tps. 7 and 8 S., Rgs. 1 and 2 W.,
West, on random line, N. of T. 8 S., R. 2 W., setting
temp. $\frac{1}{4}$ sec. and sec. cors., alternately, at 40 chain
intervals, and at

479.44 Intersect N. and S. line, 28 lks. N. of the cor. of Tps.
7 and 8 S., Rgs. 2 and 3 W., which is an iron post, 3
ins. in diam., projecting 18 ins. above ground, firmly
set in ground and in a mound of stone to top, with
brass cap marked as described in the official record.
No accessories.

Thence

N. 89° 58' E., on true line, bet. secs. 6 and 31.

Over gently rolling land, thru scattering timber and under-
growth. Over general N. slope from a range of low hills
bearing E, and W., about 2 chs. S. of line. Asc.
gradually with slight changes in elevation.

39.44 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4} \frac{S 31}{S 6}$

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, N.
of cor.

Asc. gradually over N. slope.

45.20 Enter heavily rolling land. Asc. 57 ft. over NW. slope.

50.24 Top of ascent and point from which south gable of sheet
iron cabin, bears N. 59° E. and chimney on an old
smelter bears N. 72° 40' E. Desc. 46 ft. over NE.
slope to

54.75 Foot of slope, bears NW. and SE. Enter gently rolling
land. Desc. gradually over NE. slope.

61.44 Wash, 30 lks. wide, course NW. Asc. 29 ft. over SW. slope.

66.70 Desc. 16 ft. over SE. slope.

70.24 Bend in same wash, course S. 85° W.; from SE. Asc.
gradually over NW. slope to

79.44 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins.
in the ground, for cor. of secs. 5, 6, 31 and 32, with
brass cap marked

T7S R2W
S31 | S32
S6 | S5

T8S
1938

No bearing trees available.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W.
of cor.

Land, gently and heavily rolling.

Survey: North Boundary: T. 8 S.; R. 2 W.

4.

Chains	Soil, sandy and gravelly, 2nd and 3rd rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood, sagebrush, catclaw and cacti.
	N. 89° 58' E., on true line, bet. secs. 5 and 32.
	Over gently rolling land, thru scattering timber and undergrowth. Asc. 46 ft. over NW. slope.
4.65	Ungraded road, bears NW. to Gila Bend, and SE. to Vekol Valley.
10.00	Desc. 21 ft. over NE. slope.
13.00	Enter heavily rolling land. Asc. 63 ft. over NW. slope.
18.38	Top of ascent and point from which south gable of sheet iron cabin bears N. 57° W. and chimney on an old smelter bears N. 82 $\frac{3}{4}$ ° W. Enter gently rolling land. Desc. 46 ft. over NE. slope.
24.20	Wash, 25 lks. wide, course NW. Asc. gradually over NW. slope.
33.20	Dim, ungraded road, bears NW. and SE.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{c} S \ 32 \\ S \ 5 \end{array}$
	1938
	No bearing trees available.
	Asc. gradually over NW. slope.
45.00	Top of ascent and point from which E. peak of Double Butte bears N. 5° 33' E. Desc. gradually over NE. slope.
55.70	West bank of wash, bears NW. and SE.; thence across shallow wash, course NW.
61.00	East bank of wash, bears NW. and SE. Leave wash. Asc. gradually over NW. slope.
67.75	Desc. 15 ft. over NE. slope.
71.80	Wash, 50 lks. wide, course NW. Asc. 25 ft. over NW. slope.
77.70	Desc. 18 ft. over N. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 4, 5, 32 and 33, with brass cap marked
	$\begin{array}{cc} T7S & R2W \\ S32 & & S33 \\ S5 & & S4 \end{array}$
	T8S 1938
	No bearing trees available.
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Survey: North Boundary: T. 8 S., R. 2 W.

Chains											
	Land, gently and heavily rolling. Soil, sandy and gravelly, 2nd and 3rd rates. Timber, paloverde, mesquite and ironwood. Undergrowth, greasewood, sagebrush, catclaw and cacti.										
	N. 89° 58' E., on true line bet. secs. 4 and 33.										
	Over gently rolling land, thru scattering timber and undergrowth. Asc. 16 ft. over N. slope.										
2.23	Desc. gradually over NE. slope.										
13.90	Wash, 35 lks. wide, course NW. Asc. 43 ft. over NW. slope.										
30.20	Desc. 12 ft. over N. slope.										
32.80	Asc. 20 ft. over NW. slope to										
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground to bedrock, with a stone marked with a cross (x) deposited at base, and in a mound of stone to top, for ¼ sec. cor., with brass cap marked										
	$\frac{1}{4} \frac{S \ 33}{S \ 4}$ <p>1938</p>										
	No bearing trees available.										
	Asc. gradually over NW. slope.										
46.95	Enter heavily rolling land. Asc. 52 ft. over NW. slope.										
51.90	Desc. 18 ft. over NE. slope.										
54.50	Asc. 40 ft. over NW. slope.										
67.00	Desc. 16 ft. over NE. slope.										
68.76	Asc. 42 ft. over W. slope.										
73.30	Spur, slopes N.; Squawtit Peak bears N. 18 ³ / ₄ ° W. Desc. 45 ft. over E. slope.										
79.20	Wash, 20 lks. wide, course N. Enter mountainous land. Asc. 15 ft. over W. slope to										
80.00	Set an iron post; 3 ft. long, 2 ins. in diam., on exposed bedrock, over a cross (x) marked thereon and in a mound of stone to top, for cor. of secs. 3, 4, 33 and 34, with brass cap marked										
	<table style="margin: auto;"> <tr> <td>T7S</td> <td>R2W</td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">T8S</td> </tr> <tr> <td colspan="2" style="text-align: center;">1938</td> </tr> </table>	T7S	R2W	S33	S34	S 4	S 3	T8S		1938	
T7S	R2W										
S33	S34										
S 4	S 3										
T8S											
1938											
	No bearing trees available.										
	Land, gently and heavily rolling. Soil, gravelly, 3rd rate. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood, sagebrush, catclaw and cacti.										

Survey: North Boundary: T. 8 S., R. 2 W.

6

Chains							
	N. 89° 58' E., on true line, bet. secs. 3 and 34. Over mountainous land, thru scattering timber and undergrowth. Asc. 210 ft. over broken W. slope.						
15.20	Spur, slopes N. Desc. 194 ft. over E. slope.						
24.00	Wash, 8 lks. wide, course N. Asc. 21 ft. over NW. slope.						
28.00	Desc. 32 ft. over NE. slope.						
32.40	Wash, 10 lks. wide, course N. Asc. 20 ft. over NW. and N. slopes to						
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked						
	$\frac{1}{4} \frac{S \ 34}{S \ 3}$ 1938						
	No bearing trees available.						
	Desc. 6 ft. over NE. slope.						
40.70	Wash, 8 lks. wide, course N. Asc. 323 ft. over broken, NW. slope.						
61.33	Top of rocky butte, on spur, sloping N. Old mine shaft bears S. 37 $\frac{1}{2}$ ° E.; Squawtit Peak bears N. 28° 10' W. East peak of Double Butte bears N, 16° 37' W. Desc. 230 ft. over E. slope.						
72.40	Wash, 15 lks. wide, course N.; Asc. 60 ft. over W. slope to						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 2, 3, 34 and 35, with brass cap marked						
	<table border="1"> <tr> <td>T7S</td> <td>R2W</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> </table> T8S 1938	T7S	R2W	S34	S35	S 3	S 2
T7S	R2W						
S34	S35						
S 3	S 2						
	No bearing trees available.						
	Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.						
	Land, mountainous. Soil, rocky, 4th rate. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood, sagebrush, catclaw and cacti.						
	N. 89° 58' E. on true line bet. secs. 2 and 35. Over mountainous land, thru scattering timber and undergrowth. Asc. 20 ft. over W. slope.						
0.88	Spur, slopes N. Old mine shaft bears S. 31 $\frac{1}{2}$ ° W. Desc. 76 ft. over E. slope.						
4.00	Wash, 15 lks. wide, in bottom of gulch, course N.; Asc. 43 ft. over W. slope.						

Survey: North Boundary: T. 8 S., R. 2 W.

7.

Chains

- 7.09 Point of spur, slopes N. Desc, 17 ft. over NE. slope.
- 10.60 Wash, 10 lks. wide, in bottom of gulch, course N. 80° W.
Asc. 380 ft. over broken SW. slope.
- 36.15 Spur, slopes NW. Desc. 38 ft. over NE. slope to
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground to bedrock, with a stone marked with a cross (x) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \begin{array}{c} S 35 \\ S 2 \end{array}$$

1938

No bearing trees available.

Desc. 50 ft. over NE. slope.

- 42.70 Bottom of ravine, course N. Asc. 67 ft. over W. slope.

- 45.80 Point of spur, slopes N. Desc. 25 ft. over NE. slope.

- 48.30 Side hill drain, course NW. Asc. 160 ft. over steep NW. slope.

- 55.56 Ridge, bears N. and S. Desc. 283 ft. over NE. slope.

- 68.80 Wash, 6 lks. wide, in bottom of gulch, course N. Asc. 253 ft. over steep NW. slope.

- 77.90 Spur, slopes N. 10° W. Desc. 27 ft. over NE. slope to

- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, with brass cap marked

$$\begin{array}{cc} T7S & R2W \\ S35 & S36 \\ \hline S2 & S1 \end{array}$$
T8S
1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high,
W. of cor.

Land, mountainous.

Soil, rocky, 3rd and 4th rates.

Timber, palo verde, ironwood and mesquite.

Undergrowth, greasewood, sagebrush, catclaw and cacti.

N. 89° 58' E. on true line bet. secs. 1 and 36.

Over mountainous land, thru scattering timber and undergrowth. Desc. 140 ft. over broken NE. slope.

- 19.00 Wash, 10 lks. wide, in bottom of gulch, course NW. Asc. 90 ft. over W. slope.

- 22.00 Point of spur, slopes NW. Asc. 15 ft. over N. slope.

- 23.00 Asc. 80 ft. over NW. slope.

- 27.50 Spur, slopes NW. Desc. 178 ft. over broken NE. slope.

Survey: North Boundary: T. 8 S., R. 2 W.

Chains

39.60 Bottom of ravine, 5 lks. wide, course N. 20° W. Asc. 5 ft. over W. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for 1/4 sec. cor., with brass cap marked

1/4 S 36
S 1

1938

No bearing trees available.

Asc. 50 ft. over W. slope.

43.39 Point of spur, slopes NW. Desc. 19 ft. over NE. slope.

45.00 Bottom of ravine, 3 lks. wide, course NW. Asc. 345 ft. over broken W. slope.

64.43 Ridge, bears N. 10° W. and S., turning to SE. at 4 chs. S. of this point. Desc. 180 ft. over steep E. slope.

72.90 Bottom of ravine, course N. Asc. 50 ft. over NW. slope.

76.20 Spur, slopes N. 20° E. Desc. 68 ft. over steep E. slope.

78.80 Bottom of ravine, 2 lks. wide, course NE. Asc. 18 ft. over NW. slope to

80.00 The cor. of Tps. 7 and 8 S., Rgs. 1 and 2 W., established under this group as described in the field notes of survey of the W. bdy. of T. 8 S., R. 1 W.

Land, mountainous.
Soil, rocky, 3rd and 4th rates.
Timber, paloverde, ironwood and mesquite.
Undergrowth, greasewood, sagebrush, catclaw and cacti.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

9

Chains	Commence the subdivisional survey of T. 8 S., R. 2 W. at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. established under this group as described in the field notes of survey of N. bdy. of T. 9 S., R. 2 W.
	Thence
	N. 0° 01' W., bet. secs. 35 and 36.
	Over mountainous land, thru scattering timber and undergrowth. Desc. 10 ft. over NE. slope to
1.00	Wash, 15 lks. wide, course NW. Enter nearly level land. Asc. gradually.
11.70	Leave nearly level land and enter mountainous land. Asc. 189 ft. over SW. slope.
17.70	Ridge, bears E. and W. Thence across top of ridge.
18.70	Leave top of ridge. Desc. 161 ft. over NW. slope.
24.17	Wash, 15 lks. wide, course NW. Asc. 89 ft. over SW. slope.
32.50	Spur, slopes W. Desc. 178 ft. over NW. slope.
38.40	Wash, 10 lks. wide, course N. 80° W. Asc. 7 ft. over SW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., on exposed bedrock, over a cross (X) marked thereon and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S35 S36 1938
	No bearing trees available.
	Asc. 102 ft. over SW. slope.
44.70	Spur, slopes W. from NE. Thence across top of spur.
46.00	Leave top of spur. Desc. 20 ft. over NW. slope.
47.20	Bottom of gulch, course NW. near head. Asc. 72 ft. over SW. slope.
51.42	Top of butte. Desc. 255 ft. over NE. slope.
66.70	Wash, 30 lks. wide, course W. Enter nearly level and gently rolling land. Asc. gradually over S. and SE. slopes to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 25, 26, 35 and 36, with brass cap marked
	T8S R2W S26 S25 S35 S36 1938
	No bearing trees available.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

10

Chains	
	Land, mountainous, nearly level and gently rolling. Soil, rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood, catclaw and cacti.
	East, on random line, bet. secs. 25 and 36.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect the cor. of secs. 25, 30, 31 and 36 on E. bdy. of the Tp. established under this group and described in the field notes of survey of the W. bdy. of T. 8 S., R. 2 W.
	Thence
	West, on true line, bet. secs. 25 and 36.
	Over heavily rolling land, thru scattering timber and undergrowth. Desc. 20 ft. over NW. slope to
2.85	Enter gently rolling land. Desc. gradually over NW. slope.
8.04	Wash, 30 lks. wide, course S. 80° W. Enter nearly level land. Desc. gradually over SW. slope to $\frac{1}{4}$ sec. cor.
36.74	Wash, 10 lks. wide, course SW.
40.02	Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to bedrock with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{S\ 25}{S\ 36}$
	1938
	No bearing trees available.
	Continue over nearly level land. Desc. gradually over SW. slope.
48.04	Wash, 20 lks. wide, course SW. Enter gently rolling land. Asc. gradually over SE. slope.
65.04	Low spur, slopes SW. Desc. 23 ft. over W. slope.
69.24	Drain, course SW. Asc. 39 ft. over SE. slope to
80.04	The cor. of secs. 25, 26, 35 and 36.
	Land, heavily and gently rolling and nearly level. Soil, rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood, catclaw and cacti.
	N. 0° 01' W., bet. secs. 25 and 26.
	Over heavily rolling and mountainous land, thru scattering timber and undergrowth. Asc. 98 ft. over SE. slope.
9.87	Spur, slopes SW. Asc. gradually over W. slope to
11.80	Desc. 76 ft. over broken NW. slope.
16.00	Bottom of ravine, 20 lks. wide, course W. Asc. 81 ft. over S. slope.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

11

Chains

- 19.25 Spur, slopes W. Desc. 40 ft. over NW. and W. slopes to
 24.20 Asc. 116 ft. over SW. slope.
 30.30 Point of spur, slopes NW. Desc. 194 ft. over N. slope.
 38.50 Drain, course E. Asc. 20 ft. over S. slope to
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in
 the ground to bedrock, with a stone marked with a cross
 (X) deposited at base, and in a mound of stone to top,
 for $\frac{1}{4}$ sec. cor., with brass cap marked

 $\frac{1}{4}$

S26 | S25

1938

No bearing trees available.

Asc. 15 ft. over S. slope.

- 41.40 Low spur, slopes E. Desc. 65 ft. over NE. slope.

- 47.20 Wash, 15 lks. wide, course W. Asc. 160 ft. over broken
 SW. slope.

- 68.15 Spur, slopes W. Desc. 161 ft. over NW. slope.

- 74.70 Wash, 15 lks. wide, course NW. Asc. 69 ft. over SW. slope
 to

- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in
 the ground to bedrock, with a stone marked with a cross
 (X) deposited at base, and in a mound of stone to top,
 for cor. of secs. 23, 24, 25 and 26, with brass cap
 marked

T8S	R2W
S23	S24
S26	S25

1938

No bearing trees available.

Land, heavily rolling and mountainous.
 Soil, rocky, 3rd and 4th rates.
 Timber, paloverde, ironwood and mesquite.
 Undergrowth, greasewood and cacti.

East on random line, bet. secs. 24 and 25.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.

- 80.06 Intersect E. bdy. of the Tp., 9 lks. N. of the cor. of
 secs. 19, 24, 25 and 30, established under this group
 as described in the field notes of survey of the W.
 bdy. of T. 8 S., R. 2 W.

Thence

N. 89° 56' W., on true line, bet. secs. 24 and 25.

Over mountainous land, thru scattering timber and under-
 growth. Asc. 68 ft. over SE. slope.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

12

Chains	
3.76	Narrow spur, slopes SW. Desc. 194 ft. over W. slope to
17.06	Wash, course SW. Desc. 145 ft. over S. and SW. slopes to
30.06	Wash, course SW. Enter rolling land. Desc. gradually over S. slope to
40.03	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{l} S 24 \\ S 25 \end{array}$
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Desc. 35 ft. over SW. slope.
46.22	Wash, 20 lks. wide, course NW. Enter mountainous land. Asc. 242 ft. over E. slope.
53.56	Spur, slopes NW., from S. Desc. 220 ft. over SW. slope.
63.25	Wash, 15 lks. wide, course NW. Asc. 94 ft. over N. and NE. slopes.
76.11	Spur, slopes N. 80° W. Desc. 41 ft. over SW. slope to
80.06	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.
	N. 0° 01' W., bet. secs. 23 and 24.
	Over mountainous land, thru scattering timber and undergrowth. Asc. 18 ft. over SW. slope.
1.10	Spur, slopes NW. Desc. 140 ft. over N. slope.
9.90	Wash, 40 lks. wide, course W. Enter rolling land. Asc. 25 ft. over SW. slope.
14.50	Wash, 40 lks. wide, course SW. Enter mountainous land. Asc. 141 ft. over S. slope.
27.50	Ridge, bears E. and W. Desc. 138 ft. over N. slope.
33.40	Wash, 30 lks. wide, course W. Enter gently rolling land. Asc. gradually over SW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S23 S24
	1938
	No bearing trees available

Survey: Subdivision Lines: T. 8 S., R. 2 W.

13

Chains							
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.						
	Asc. gradually over SW. slope.						
43.30	Desc. 25 ft. over NW. slope.						
48.00	Asc. gradually over W. slope to						
58.70	Wash, 200 lks. wide, course SW. Asc. slightly over SW. slope to						
60.70	Wash, 20 lks. wide, course SW. Asc. 36 ft. over S. slope.						
67.00	Top of low, round knoll. Desc. 46 ft. over N. slope.						
69.20	Wash, 10 lks. wide, course SW. Asc. gradually to sec. cor. over general SW. slope.						
74.00	Wash, 15 lks. wide, course S. 70° W.						
79.70	Wash, 10 lks. wide, course S. 10° W. from N. 20° W.						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground, to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 13, 14, 23 and 24, with brass cap marked						
	<table border="1"> <tr> <td>T8S</td> <td>R2W</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> </table>	T8S	R2W	S14	S13	S23	S24
T8S	R2W						
S14	S13						
S23	S24						
	1938						
	No bearing trees available.						
	Land, mountainous, rolling and gently rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, grasswood and cacti.						
	S. 89° 56' E. on random line, bet. secs. 13 and 24.						
40.00	Set temp. ¼ sec. cor.						
80.10	Intersect E. bdy. of the Tp. 23 lks. S. of the cor. of secs. 13, 18, 19 and 24, established under this group as described in the field notes of the survey of the W. bdy. of T. 8 S., R. 1 W.						
	Thence						
	S. 89° 54' W., on true line, bet. secs. 13 and 24.						
	Over mountainous land, thru scattering timber and undergrowth. Desc. 242 ft. over steep W. slope to						
13.10	Bottom of ravine, 10 lks. wide, course N. 80° W. Desc. 100 ft. over NW. slope.						
23.80	Wash, 20 lks. wide, course SW. Enter gently rolling land. Desc. gradually over S. slope.						
36.20	Low spur, slopes S. 60° W. Desc. gradually over W. slope to						
40.05	Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground to bedrock, with a stone marked with a cross						

Survey: Subdivision Lines: T. 8 S., R. 2 W.

14

Chains

(X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S 13}{S 24}$$

1938

No bearing trees available.

Desc. 85 ft. over W. slope.

61.70 Wash; 80 lks. wide, course S. 30° W. Asc. 45 ft. over SE. slope.

68.56 Point of spur, slopes S. Desc. 18 ft. over SW. slope.

71.80 Head of wash, course S. Asc. 14 ft. over SE. slope.

74.90 Spur, slopes S. near point of same. Desc. 44 ft. over W. slope to

80.10 The cor. of secs. 13, 14, 23 and 24.

Land, mountainous and gently rolling.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, paloverde, ironwood and mesquite.

Undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 13 and 14.

Over heavily rolling land, thru scattering timber and undergrowth. Asc. 76 ft. over W. slope.

9.32 Spur, slopes S. 20° E. Asc. 34 ft. over SE. slope.

13.50 Same spur, slopes S. 5° W. from E. Thence across top of spur.

15.60 Leave top of spur. Desc. 69 ft. over NW. slope.

20.10 Wash, 30 lks. wide, course SW. Asc. 40 ft. over SW. slope.

25.44 Asc. gradually over W. slope.

39.90 Drain, course W. Asc. slightly over SW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4}$$

$$S14 \mid S13$$

1938

No bearing trees available.

Asc. 36 ft. over SW. slope.

43.50 Spur, slopes W. Desc. 14 ft. over NW. slope.

47.00 Asc. 112 ft. over S. slope.

56.00 Ridge, bears E. and W. Desc. 131 ft. over N. slope to

Chains

65.83 Enter gently rolling land. Desc. 35 ft. over gradual N. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 11, 12, 13 and 14, with brass cap marked

T8S	R2W
S11	S12
S14	S13

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

U.S. Coast and Geodetic Survey Bench Mark, a 3 in. brass cap set in a cement block 8x8 ins., marked "U 86", bears N. 2° E., 12.58 chs. dist.
1935

Land, heavily and gently rolling.
Soil, gravelly and rocky, 3rd and 4th rates.
Timber, paloverde, ironwood and mesquite.
Undergrowth, greasewood and cacti.

N. 89° 54' E., on random line, bet. secs. 12 and 13.

40.00 Set temp. ¼ sec. cor.

80.02 Intersect E. bdy. of the Tp. 12 lks. N. of the cor. of secs. 7, 12, 13 and 18 established under this group as described in field notes of survey of the W. bdy. of T. 8 S., R. 2 W.

Thence

S. 89° 59' W., on true line, bet. secs. 12 and 13.

Over gently rolling land, thru scattering timber and undergrowth. Asc. 3 ft. over SE. slope.

0.22 Low ridge, bears NE. and SW. Desc. 56 ft. over W. slope to

15.00 Thence over N. slope, descending gradually to

40.01 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap marked

¼	S 12
	S 13

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue over gently rolling land, descending gradually over N. slope to

80.02 The cor. of secs. 11, 12, 13 and 14.

Land, gently rolling.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

16

Chains							
	Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.						
	N. 0° 01' W., bet. secs. 11 and 12.						
	Over gently rolling land, thru scattering timber and undergrowth. Desc. gradually over N. slope.						
12.20	Ungraded road, bears N. 70° W. and S. 70° E.						
16.00	Wash, 40 lks. wide, 10 ft. deep, course W. Asc. gradually over SW. slope to $\frac{1}{4}$ sec. cor.						
21.10	Wash, 20 lks. wide, course S. 60° W.						
38.50	Bottom of ravine, 10 lks. wide, 20 ft. deep, course S. 80° W.						
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">1938</td></tr> <tr><td>S11</td><td>S12</td></tr> </table>	1938		S11	S12		
1938							
S11	S12						
	No bearing trees available.						
	Asc. 43 ft. over SW. slope.						
46.77	Asc. gradually over W. slope.						
54.00	Desc. 25 ft. over NW. slope.						
55.80	Bottom of ravine, 10 lks. wide, course S. 20° W. Enter mountainous land. Asc. 472 ft. over steep SW. slope to						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>T8S</td><td>R2W</td></tr> <tr><td>S2</td><td>S1</td></tr> <tr><td>S11</td><td>S12</td></tr> </table>	T8S	R2W	S2	S1	S11	S12
T8S	R2W						
S2	S1						
S11	S12						
	1938						
	No bearing trees available.						
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.						
	Land, gently rolling and mountainous. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.						
	N. 89° 59' E., on random line, bet. secs. 1 and 12.						
40.00	Set temp. $\frac{1}{4}$ sec. cor.						
79.96	Intersect E. bdy. of the Tp. 2 lks. N. of the cor. of secs. 1, 6, 7 and 12, established under this group as described in the field notes of survey of the W. bdy. of T. 8 S., R. 1 W.						

Survey: Subdivision Lines: T. 8 S., R. 2 W.

17

Chains	
	Thence
	West, on true line, bet. secs. 1 and 12.
	Over mountainous land, thru scattering timber and undergrowth. Desc. 22 ft. over NW. slope.
3.26	Wash, 15 lks. wide, course S. 10° W. Asc. 349 ft. over broken E. slope.
24.66	Spur, slopes S. 10° W. Desc. 168 ft. over steep W. slope.
30.06	Wash, 15 lks. wide, in bottom of gulch, course S. 10° W. Asc. 113 ft. over SE. slope.
36.66	Spur, slopes S. 20° W. Desc. 106 ft. over steep W. slope to
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{c} S 1 \\ S 12 \end{array}$
	1938
	No bearing trees available.
	Desc. 210 ft. over steep, broken W. slope.
46.16	Drain, course S. Desc. 124 ft. over steep SW. slope.
54.10	Bottom of ravine, course S. Asc. 32 ft. over E. slope.
58.76	Spur, slopes S. 10° W. Desc. 93 ft. over broken SW. slope.
65.96	Wash, 20 lks. wide, course S. Asc. 175 ft. over E. slope.
72.56	Spur, slopes S. 10° E. Thence across top of spur.
77.86	Leave top of spur. Desc. 70 ft. over steep SW. slope to
79.96	The cor. of secs. 1, 2, 11 and 12.
	Land, mountainous. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.
	N. 0° 01' W., on random line, bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.91	Intersect N. bdy. of the Tp., 8 lks. W. of the cor. of secs. 1, 2, 35 and 36, hereinbefore described.
	Thence
	S. 0° 02' W., on true line, bet. secs. 1 and 2.
	Over mountainous land, thru scattering timber and undergrowth. Asc. 139 ft. over NE. slope.
6.65	Spur, slopes N. 10° W. Asc. gradually over W. slope.
8.33	Desc. 49 ft. over SW. slope.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

18

Chains	
12.90	Wash, 15 lks. wide, course N. 10° W. Asc. 210 ft. over NE. slope.
22.00	Spur, slopes NW. Desc. 237 ft. over SW. slope to
39.91	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S2 S1
	1938
	No bearing trees available.
	Desc. 7 ft. over SW. slope.
40.60	Wash, 15 lks. wide, course NW. Asc. 373 ft. over NE, slope.
52.70	Spur, slopes NW. Desc. 225 ft. over SW. slope.
65.40	Wash, 15 lks. wide, course N. 70° W. Asc. 262 ft. over NW. slope.
76.90	Ridge bears N. 60° W. and S. 80° E. Desc. 79 ft. over SW. slope to
79.91	The cor. of secs. 1, 2, 11 and 12.
	Land, mountainous.
	Soil, rocky, 3rd and 4th rates.
	Timber, paloverde and ironwood.
	Undergrowth, greasewood and cacti.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. established under this group as described in the field notes of survey of the N. bdy. of T. 9 S., R. 2 W.
	N. 0° 01' W., bet. secs. 34 and 35.
	Over heavily rolling land, thru scattering timber and undergrowth. Asc. 24 ft. over SE. slope.
1.30	Spur, slopes SW. Asc. gradually over W. slope to
5.00	Side hill drain, course SW. near head. Enter mountainous land. Asc. 140 ft. over steep S. slope.
11.02	Same spur, slopes SE. Asc. 43 ft. over SE. slope.
12.81	Spur ridge bearing E. and W. The top of a butte about 140 ft. above this point bears W., 4 chs. dist. and a saddle bears E. 3 chs. dist., which is about 60 ft. below this point. Desc. 227 ft. over N. slope.
23.40	Bottom of ravine, 2 lks. wide, course W. Asc. 90 ft. over S. slope.
29.70	Spur, slopes W. Desc. 94 ft. over NE. slope.
35.50	Bottom of ravine, course N., from S. 5° E. Desc. 13 ft. in same.
38.90	Leave bottom of ravine, course N. 5° W. from S. Desc.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

19

Chains							
	slightly over W. slope to						
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked						
	$\frac{1}{4}$						
	S34 S35						
	1938						
	No bearing trees available.						
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor..						
	Desc. 9 ft. over NW. slope.						
42.00	Wash, 8 lks. wide, course N. 75° W. Asc. gradually over W. slope to						
50.00	Foot of slope, bears E. and W. Asc. 103 ft. over S. slope.						
56.36	Spur, slopes W. Desc. 90 ft. over NW. slope.						
63.40	Bottom of ravine, 3 lks. wide, course SW. from E. Asc. 260 ft. over broken S. slope.						
77.30	Ridge, bears NW. and SE. Desc. 30 ft. over NE. slope to						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., on exposed bedrock over a cross (X) marked thereon and in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">T8S</td> <td style="padding: 2px;">R2W</td> </tr> <tr> <td style="padding: 2px;">S27</td> <td style="padding: 2px;">S26</td> </tr> <tr> <td style="padding: 2px;">S34</td> <td style="padding: 2px;">S35</td> </tr> </table>	T8S	R2W	S27	S26	S34	S35
T8S	R2W						
S27	S26						
S34	S35						
	1938						
	No bearing trees available.						
	Land, heavily rolling and mountainous.						
	Soil, rocky, 3rd and 4th rates.						
	Timber, paloverde, ironwood and mesquite.						
	Undergrowth, greasewood, sagebrush, catclaw and cacti.						
	East, on random line, bet. secs. 26 and 35.						
40.00	Set temp. $\frac{1}{4}$ sec. cor.						
79.96	Intersect N. and S. line, 14 lks. S. of the cor. of secs. 25, 26, 35 and 36.						
	Thence						
	S. 89° 54' W., on true line, bet. secs. 26 and 35.						
	Over mountainous land, thru scattering timber and undergrowth. Asc. slightly over SE. slope.						
1.68	Sidehill drain, course SE. Asc. 92 ft. over E. slope.						
6.76	Spur, slopes SE. Desc. 154 ft. over steep SW. slope.						
19.96	Foot of steep slope, bears NW. and SE. Enter gently rolling land. Desc. gradually over SW. slope.						

Chains	
34.86	Wash, 30 lks. wide, course NW. Asc. 15 ft. over NE. and N. slopes to
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S \ 26}{S \ 35}$ <p style="text-align: center;">1938</p>
	No bearing trees available.
	Asc. gradually over N. slope.
54.89	Low spur, slopes NW. Desc. 25 ft. over SW. slope.
59.96	Wash, 15 lks. wide, course NW. Asc. 15 ft. over gradual NE. slope to
66.70	Enter mountainous land. Asc. 105 ft. over NE. slope to
79.96	The cor. of secs. 26, 27, 34 and 35.
	Land, mountainous and gently rolling. Soil, rocky, 3rd and 4th rates. Timber, paloverde, mesquite and ironwood. Undergrowth, greasewood, catclaw, sagebrush and cacti.
	N. 0° 01' W., bet. secs. 26 and 27.
	Over mountainous land, thru scattering timber and undergrowth. Desc. 135 ft. over NE. slope.
10.30	Wash, 35 lks. wide, course NW. Enter gently rolling land. Asc. 63 ft. over gradual SW. slope.
31.60	Spur, slopes NW. Desc. 50 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 15 ins. in the ground to bedrock with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S27 \ \ S26}{1938}$
	No bearing trees available.
	Desc. 10 ft. over N. slope.
42.20	Wash, 12 lks. wide, course W. Enter mountainous land. Asc. 153 ft. over S. slope.
50.00	Sharp spur, slopes SW. Desc. 165 ft. over broken NE. slope.
66.30	Wash, 15 lks. wide, course N. 80° W. Enter rolling land. Asc. 56 ft. over SW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 15 ins. in the ground, to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to

Survey: Subdivision Lines: T. 8 S., R. 2 W.

21

Chains	<p>top, for cor. of secs. 22, 23, 26 and 27, with brass cap marked</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T8S</td> <td>R2W</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> </table> <p style="text-align: center;">1938</p> <p>No bearing trees available.</p> <p>Land, mountainous, gently rolling and rolling. Soil, rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood, sagebrush, catclaw and cacti.</p> <hr/> <p>N. 89° 54' E., on random line, bet. secs. 23 and 26.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>79.98 Intersect the cor. of secs. 23, 24, 25 and 26.</p> <p>Thence</p> <p>S. 89° 54' W., on a true line, bet. secs. 23 and 26.</p> <p>Over mountainous land, thru scattering timber and undergrowth. Desc. 130 ft. over SW. slope.</p> <p>9.28 Bottom of ravine, 15 lks. wide, course N. 80° W. Enter rolling land. Asc. 25 ft. over NE. slope.</p> <p>14.38 Point of spur, slopes N. Desc. 48 ft. over NW. slope.</p> <p>19.28 Wash, 15 lks. wide, course S. 20° W. Enter mountainous land. Asc. 113 ft. over SE. slope.</p> <p>30.24 Spur, slopes S. Enter rolling land. Desc. 20 ft. over SW. slope.</p> <p>34.00 Asc. 18 ft. over S. slope.</p> <p>38.55 Desc. 25 ft. over SW. slope to</p> <p>39.99 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>$\frac{1}{4}$</td> <td>S 23</td> </tr> <tr> <td></td> <td>S 26</td> </tr> </table> <p style="text-align: center;">1938</p> <p>No bearing trees available.</p> <p>Desc. 13 ft. over SW. slope.</p> <p>41.38 Asc. 46 ft. over SE. slope.</p> <p>51.95 Spur, slopes S. Enter mountainous land. Desc. 91 ft. over SW. slope.</p> <p>58.79 Enter rolling land. Asc. 12 ft. over SE. slope.</p> <p>63.80 Desc. 54 ft. over SW. slope.</p> <p>70.74 Asc. 26 ft. over SE. slope.</p>	T8S	R2W	S22	S23	S27	S26	$\frac{1}{4}$	S 23		S 26
T8S	R2W										
S22	S23										
S27	S26										
$\frac{1}{4}$	S 23										
	S 26										

BOOK 201

Survey: Subdivision Lines: T. 8 S., R. 2 W.

Chains

74.00 Desc. 29 ft. over SW. slope to

79.98 The cor. of secs. 22, 23, 26 and 27.

Land, mountainous and rolling.
Soil, rocky, 3rd and 4th rates.
Timber, paloverde, mesquite and ironwood.
Undergrowth, greasewood, cacti, catclaw and sagebrush.

N. 0° 01' W., bet. secs. 22 and 23.

Over heavily rolling land, thru scattering timber and undergrowth. Asc. 40 ft. over SW. slope.

4.95 Enter mountainous land. Asc. 274 ft. over S. slope.

15.36 Long spur, slopes SW. Desc. 296 ft. over NW. slope.

27.04 Enter rolling land. Desc. 20 ft. over NW. slope.

34.73 Wash, course SW. Asc. 26 ft. over S. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S22 | S23

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 18 ft. over S. slope.

45.00 Enter mountainous land. Asc. 113 ft. over S. slope.

51.50 Point of spur, slopes S. 70° W. Desc. 90 ft. over NW. slope.

57.93 Draw, 10 lks. wide, course SW. Asc. 260 ft. over S. slope.

67.70 Ridge, bears N. 80° E. and S. 80° W. Desc. 249 ft. over N. slope to

80.00 Set an iron post, 3-ft. long, 2 ins. in diam., on exposed bedrock, over a cross (X) marked thereon and in a mound of stone to top, for cor. of secs. 14, 15, 22 and 23, with brass cap marked

T8S R2W
S15 | S14
S22 | S23

1938

No bearing trees available.

Land, mountainous and rolling.
Soil, rocky, 4th rate.
Timber, paloverde.
Undergrowth, greasewood and cacti.

Chains	
	N. 89° 54' E., on random line, bet. secs. 14 and 23.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect N. and S. lines, 7 lks. N. of the cor. of secs. 13, 14, 23 and 24.
	Thence
	S. 89° 57' W., on true line, bet. secs. 14 and 23.
	Over heavily rolling land, thru scattering timber and undergrowth. Desc. slightly over W. slope.
0.22	Wash, 10 lks. wide, course S. 20° E. turning to S. 10° W. at 30 lks. SE. of this point. Asc. 57 ft. over SE. slope.
1.92	Dim, ungraded road, bears N. 25° W. and S. 25° E.
8.20	Desc. 20 ft. over SW. slope.
13.00	Enter mountainous land. Asc. 110 ft. over E. slope.
25.16	Spur, slopes SE. Desc. 120 ft. over SW. slope.
33.00	Draw, course SE. near head. Asc. 102 ft. over E. slope.
38.90	Ridge, bears NE. and SW. Desc. 10 ft. over NW. slope to
40.01	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S\ 14}{S\ 23}$
	1938
	No bearing trees available.
	Desc. 8 ft. over NW. slope.
41.00	Asc. 74 ft. over NE. slope.
45.25	Desc. 57 ft. over N. slope.
51.60	Asc. 52 ft. over NE. slope.
59.40	Spur, slopes N. 70° W. Desc. 250 ft. over W. slope.
73.87	Desc. 20 ft. over NW. slope to
80.02	The cor. of secs. 14, 15, 22 and 23.
	Land, heavily rolling and mountainous. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 0° 01' W., bet. secs. 14 and 15.
	Over mountainous land thru scattering timber and undergrowth. Desc. 57 ft. over NW. slope.
5.60	Wash, 12 lks. wide, course SW. Asc. 159 ft. over SE. slope.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

24

Chains

16.64 Spur, slopes SW. Enter rolling land. Desc. 132 ft. over NW. slope.

30.70 Draw, 10 lks. wide, course SW. Asc. 75 ft. over SE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S15 | S14

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 16 ft. over SE. slope.

42.00 Desc. 40 ft. over NW. slope.

48.56 Enter mountainous land. Asc. 100 ft. over S. slope.

54.80 Long spur, slopes S. 70° W. Desc. 82 ft. over N. slope to

59.62 Enter gently rolling land. Desc. 30 ft. over gradual N. slope to

65.37 Foot of slope, bears E. and W. Enter nearly level land.

70.00 Enter gently rolling land. Asc. 18 ft. over SW. slope.

74.25 Desc. gradually over NW. slope.

77.96 Wash, 10 lks. wide, course SW. Asc. 9 ft. over S. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap marked

T8S R2W
S10 | S11
S15 | S14

1938.

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous, rolling, gently rolling and nearly level.
Soil, rocky, 4th rate.
Timber, paloverde and ironwood.
Undergrowth, cacti.

N. 89° 57' E., on random line, bet. secs. 11 and 14.

40.00 Set temp. 1/4 sec. cor.

79.98 Intersect the cor. of secs. 11, 12, 13 and 14.

Thence

S. 89° 57' W., on true line, bet. secs. 11 and 14.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

25

Chains	Over gently rolling land, thru scattering timber and undergrowth. Desc. 54 ft. over N. and NW. slopes.
26.34	Asc. 23 ft. over SE. slope.
29.23	Enter rolling land. Desc. 22 ft. over S. slope.
33.00	Asc. 47 ft. over SE. slope.
36.75	Spur, slopes SW. Desc. 37 ft. over W. slope to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{l} S 11 \\ S 14 \end{array}$
	1938
	No bearing trees available.
	Desc. 129 ft. over SW. slope.
69.18	Wash, course S. 70° W. Asc. 6 ft. over SE. slope.
75.29	Desc. 22 ft. over S. slope to
79.98	The cor. of secs. 10, 11, 14 and 15.
	Land, gently rolling and rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 0° 01' W., bet. secs. 10 and 11.
	Over gently rolling land, thru scattering timber and undergrowth. Asc. gradually over S. slope to
11.60	Enter heavily rolling land. Asc. 50 ft. over S. slope.
14.40	Low ridge, bears E. and W. Thence across top of ridge.
15.93	Leave top of ridge. Desc. 36 ft. over N. slope to
19.80	Foot of slope, bears E. and W. Enter gently rolling land. Desc. 45 ft. over N. slope to.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S10 S11
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	A well and windmill bears N. 19° 04' E., 6.24 chs. dist.
	Desc. gradually over N. slope.

BOOK 4237

Survey: Subdivision Lines: T. 8 S., R. 2 W.

26

Chains

42.00 Wash, 30 lks. wide, course NW. Asc. gradually over SW. slope.

55.80 Ungraded road, bears N. 86° W. and S. 67° E. Desc. gradually over N. slope to

60.00 Rim of canyon bears NW. and SE. Enter mountainous land. Desc. 60 ft. over steep N. slope.

61.00 Wash, 60 lks. wide, course N. 86° W. Thence across nearly level bottom of canyon.

69.00 Leave bottom of canyon. Asc. 169 ft. over S. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap marked

T8S	R2W
S3	S2
S10	S11

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, gently and heavily rolling, nearly level and mountainous.

Soil, rocky, 3rd and 4th rates.

Timber, paloverde, ironwood and mesquite.

Undergrowth, greasewood and cacti.

N. 89° 57' E. on random line, bet. secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 Intersect N. and S. line, 12 lks. N. of the cor. of secs. 1, 2, 11 and 12.

Thence

N. 89° 58' W., on true line, bet. secs. 2 and 11.

Over mountainous land, thru scattering timber and undergrowth. Desc. 31 ft. over SW. slope.

3.34 Asc. 57 ft. over SE. slope.

11.20 Spur, slopes S. Desc. 69 ft. over SW. slope.

13.28 Desc. 70 ft. over S. slope.

21.98 Spur, slopes SW. Desc. 515 ft. over W. slope.

39.99 Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground, to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	S 2
	S 11

1938

No bearing trees available.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

27

Chains	Desc. 160 ft. over SW. slope.
49.00	Wash, 15 lks. wide, course SW. Asc. 59 ft. over SE. slope to
54.95	Thence along broken S. slope, ascending gradually.
69.84	Spur, slopes S. Desc. 58 ft. over W. slope.
74.48	Bottom of ravine, course S. Asc. 34 ft. over broken SE. slope to
79.98	The cor. of secs. 2, 3, 10 and 11. Land, mountainous. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
40.00	N. 0° 01' W., on random line, bet. secs. 2 and 3. Set temp. $\frac{1}{4}$ sec. cor.
79.85	Intersect the cor. of secs. 2, 3, 34 and 35, on N. bdy. of the Tp., hereinbefore described. Thence S. 0° 01' E., on true line, bet. secs. 2 and 3. Over mountainous land, thru scattering timber and undergrowth. Asc. gradually over W. slope from spur sloping N.
9.65	A point 1 ch. W. from top of spur, sloping N. from SE. Desc. 16 ft. over SW. slope.
12.95	Drain, course NW. Asc. 378 ft. over N. slope.
35.48	Narrow spur, slopes NE. Asc. gradually over E. slope.
38.45	Desc. 9 ft. over SE. slope to
39.85	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S3 S2 1938 No bearing trees available.
39.90	Drain, course N. 80° E. near head. Asc. 20 ft. over NE. slope.
41.05	Narrow spur, slopes E. Desc. 112 ft. over SE. slope.
44.35	Drain, course N. 80° E. Asc. 83 ft. over N. slope.
48.25	Narrow ridge, bears E. and W. Desc. 46 ft. over S. slope.
53.35	Wash, 10 lks. wide, course SW. Asc. 135 ft. over NW. slope.
61.15	Narrow spur, slopes W. Desc. 230 ft. over S. slope to

Survey: Subdivision Lines: T. 8 S., R. 2 W.

28

Chains

79.85

The cor. of secs. 2, 3, 10 and 11:

Land, mountainous.
Soil, rocky, 4th rate.
Timber, paloverde and ironwood.
Undergrowth, greasewood and cacti.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., established under this group as described in the field notes of survey of the N. bdy. of T. 9 S., R. 2 W.

N. 0° 02' W., bet. secs. 33 and 34.

Over mountainous land, thru scattering timber and undergrowth. Asc. 98 ft. over S. slope.

5.80

Ridge bears NW. and SE. Desc. 113 ft. over NE. slope to

10.50

Enter gently rolling land. Desc. 76 ft. over gradual NE. slope.

33.67

Wash, course W. Asc. 36 ft. over S. slope to

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S33 | S34

1938

No bearing trees available.

Enter mountainous land. Asc. 88 ft. over S. slope.

44.80

Long spur, slopes W. Desc. 106 ft. over NW. slope.

55.56

Wash, course W. Asc. 85 ft. over S. slope.

60.50

Spur, slopes W. Desc. 92 ft. over N. slope.

64.12

Wash, course W. Asc. 63 ft. over S. slope.

70.40

Spur, slopes SE. near point of same. Asc. 45 ft. over E. slope to

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., on exposed bedrock, over a cross (X) marked thereon and in a mound of stone to top, for cor. of secs. 27, 28, 33 and 34, with brass cap marked

T8S R2W
S28 | S27
S33 | S34

1938

No bearing trees available.

Land, mountainous and gently rolling.
Soil, rocky, 4th rate.
Timber, paloverde and ironwood.
Undergrowth, cacti.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

29

Chains	East, on random line, bet. secs. 27 and 34.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect the cor. of secs. 26, 27, 34 and 35.
	Thence
	West, on true line, bet. secs. 27 and 34.
	Over mountainous land, thru scattering timber and undergrowth. Asc. 25 ft. over NE. slope.
4.02	Ridge, bears NW. and SE.. Desc, 276 ft. over SW. slope.
30.85	Draw, course S. Asc. 81 ft. over SE. slope.
35.05	Desc. 46 ft. over SW. slope to
40.01	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S 27}{S 34}$
	1938
	No bearing trees available.
	Desc. 13 ft. over SW. slope.
41.33	Asc. 124 ft. over SE. slope.
46.02	Spur, slopes SW. Desc. 154 ft. over NW. slope.
52.30	Asc. 110 ft. over NE. slope.
58.45	Desc. 247 ft. over NW. and W. slopes.
76.92	Draw, course S. 10° W. Asc. 70 ft. over E. slope to
80.02	The cor. of secs. 27, 28, 33 and 34.
	Land, mountainous. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, cacti.
	N. 0° 02' W., bet. secs. 27 and 28.
	Over mountainous land, thru scattering timber and undergrowth. Asc. 76 ft. over E. slope.
11.20	Head of draw, course SE. Asc. 30 ft. over S. slope.
14.50	Ridge, bears E. and W. Desc. 114 ft. over N. slope.
24.95	Draw, course W. Asc. 176 ft. over S. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., on exposed bedrock, over a cross (X) marked thereon and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S28. S27
	1938

Survey: Subdivision Lines: T. 8 S., R. 2 W.

30

Chains

No bearing trees available.

Asc. 119 ft. over S. slope.

49.80 Spur, slopes NW. Desc. 198 ft. over N. slope.

60.27 Wash, 60 lks. wide, course S. 85° W. Thence over gently rolling land. Asc. 20 ft. over gradual S. slope to

71.77 Foot of slope, bears E. and W. Enter mountainous land. Asc. 126 ft. over S. slope to

.80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap marked

T8S	R2W
S21	S22
S28	S27

1938

No bearing trees available.

Land, mountainous and gently rolling.
Soil, rocky, 4th rate.
Timber, paloverde and ironwood.
Undergrowth, cacti.

East, on random line, bet. secs. 22 and 27.

40.00 Set temp. 1/4 sec. cor.

79.98 Intersect the cor. of secs. 22, 23, 26 and 27.

Thence

West, on true line, bet. secs. 22 and 27.

Over rolling land, thru scattering timber and undergrowth. Desc. 69 ft. over SW. slope to

14.98 Enter gently rolling land at N. edge of small valley. Desc. 6 ft. over S. slope.

22.50 Asc. 18 ft. over S. slope to

32.00 Enter heavily rolling land. Asc. 75 ft. over SE. slope.

39.99 Spur, slopes SW.
Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for 1/4 sec. cor., with brass cap marked

S 22
1/4 S 27

1938

No bearing trees available.

Desc. 114 ft. over NW. slope to

51.73 Foot of slope, bears NE. and SW. Enter nearly level land.

Survey; Subdivision Lines: T. 8 S., R. 2 W.

Chains

- 57.43 Wash, 30 lks. wide, course SW. Enter rolling land.
Asc. 46 ft. over SE. slope to
- 72.34 Enter mountainous land. Asc. 42 ft. over SE. slope.
- 76.80 Asc. 7 ft. over S. slope to
- 79.98 The cor. of secs. 21, 22, 27 and 28.
- Land, rolling, nearly level and mountainous.
Soil, rocky and sandy, 4th rate.
Timber, paloverde and ironwood.
Undergrowth, cacti.
-
- N. 0° 02' W., bet. secs. 21 and 22.
- Over mountainous land, thru scattering timber and undergrowth. Asc. 322 ft. over S. slope.
- 12.20 Ridge, bears N. 80° E. and W. Desc. 239 ft. over N. slope.
- 21.14 Draw, course S. 80° W. Asc. 109 ft. over S. slope.
- 26.70 Long spur, slopes S. 70° W. Desc. 294 ft. over N. slope to
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$
- S21 | S22
- 1938
- No bearing trees available.
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- Desc. 39 ft. over N. slope.
- 43.75 Wash, 25 lks. wide, course N. 70° W. for 5.00 chs., thence S. 70° W. Enter rolling land. Asc. 27 ft. over SW. slope.
- 47.37 Desc. 15 ft. over W. slope.
- 49.86 Asc. 48 ft. over W. slope.
- 59.70 Desc. 50 ft. over NW. slope.
- 67.50 Wash, 30 lks. wide, course S. 70° W. Asc. 46 ft. over S. slope to
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap marked

T8S R2W
S16 | S15
S21 | S22

1938

Survey: Subdivision Lines: T. 8 S., R. 2 W.

32

Chains	
	No bearing trees available.
	Land, mountainous and rolling.
	Soil, rocky, 4th rate.
	Timber, paloverde and ironwood.
	Undergrowth, greasewood and cacti.
	East, on random line, bet. secs. 15 and 22.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect the cor. of secs. 14, 15, 22 and 23.
	Thence
	West, on true line, bet. secs. 15 and 22.
	Over mountainous land, thru scattering timber and undergrowth. Desc. 40 ft. over N. slope.
6.41	Asc. 38 ft. over N. slope.
13.68	Desc. 149 ft. over NW. slope.
26.14	Wash, 20 lks. wide, course SW. from N. 88° E. Asc. 185 ft. over SE. slope.
32.68	Point of spur, slopes SW. Desc. 106 ft. over W. slope to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S 15}{S 22}$
	1938
	No bearing trees available.
	Desc. 100 ft. over W. slope.
49.63	Wash, 30 lks. wide, course S. 70° W. Enter heavily rolling land. Asc. 47 ft. over SE. slope.
63.94	Desc. 62 ft. over SW. slope.
67.72	Asc. 15 ft. over S. slope.
74.00	Asc. 19 ft. over S. slope to
79.98	The cor. of secs. 15, 16, 21 and 22.
	Land, mountainous and heavily rolling.
	Soil, rocky, 4th rate.
	Timber, paloverde and ironwood.
	Undergrowth, cacti.
	N. 0° 02' W., bet. secs. 15 and 16.
	Over heavily rolling land, thru scattering timber and undergrowth. Asc. 173 ft. over S. slope.
14.70	Spur, slopes W. Desc. 163 ft. over N. slope.
30.73	Draw, course S. 70° W. Enter rolling land. Asc. 17 ft. over SW. slope.

Chains	
37.26	Asc. gradually over W. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S16 S15
	1938
	No bearing trees available.
	Desc. slightly over NW. slope.
41.30	Wash, course SW. Asc. 66 ft. over SW. slope.
50.82	Desc. 63 ft. over NW. slope.
55.73	Asc. 15 ft. over W. slope.
63.83	Wash, 25 lks. wide, course SW. Asc. 9 ft. over SW. slope.
65.45	Desc. 6 ft. over W. slope.
70.40	Asc. 46 ft. over SW. slope.
76.00	Desc. 28 ft. over NW. slope to
80.00	True point for cor. of secs. 9, 10, 15 and 16 is in wash course SW., where it is impracticable to monument the cor., therefore establish witness cor. at 0.60 chs. S. 89° 59' W., as hereinafter described.
	Land, heavily rolling and rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	From true point for cor. of secs. 9, 10, 15 and 16. East, on random line, bet. secs. 10 and 15.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 10, 11, 14 and 15.
	Thence
	N. 89° 59' W., on true line, bet. secs. 10 and 15.
	Over gently rolling land, thru scattering timber and undergrowth. Along general S. slope. Desc. 51 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S 10}{S 15}$
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

34

Chains	Desc. gradually over SW. slope.										
68.85	Asc. 23 ft. over SE. slope.										
73.84	Desc. 28 ft. over NW. slope to										
80.00	The true point for cor. of secs. 9, 10, 15 and 16, in wash, course SW. (W.C. 0.60 chs. S.89°59'W.)										
	Land, gently rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.										
	From true point for cor. of secs. 9, 10, 15 and 16. N. 0° 02' W., bet. secs. 9 and 10. Over gently rolling land, thru scattering timber and undergrowth. Asc. 19 ft. over SE. slope.										
6.59	Desc. 5 ft. over NE. slope.										
11.30	Asc. 33 ft. over SE. slope.										
29.68	Enter heavily rolling land. Asc. 81 ft. over S. slope.										
36.87	Desc. 19 ft. over NE. slope to										
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked										
	<table border="1"> <tr><td colspan="2"> </td></tr> <tr><td>S9</td><td>S10</td></tr> <tr><td colspan="2">1938</td></tr> </table>			S9	S10	1938					
S9	S10										
1938											
	No bearing trees available.										
	Enter gently rolling land. Desc. gradually over NE. slope.										
45.00	Enter mountainous land. Asc. 79 ft. over S. slope.										
50.15	Ridge, bears N. 70° E. and W. Desc. 107 ft. over N. slope to										
54.90	Enter rolling land. Desc. 96 ft. over N. slope to										
68.70	Foot of slope, bears E. and W. Enter nearly level land. Desc. slightly to wash.										
79.50	Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for witness cor. to cor. of secs. 3, 4, 9 and 10, with brass cap marked										
	<table border="1"> <tr><td colspan="2">T8S R2W</td></tr> <tr><td colspan="2">W C</td></tr> <tr><td>S4</td><td>S3</td></tr> <tr><td>S9</td><td>S10</td></tr> <tr><td colspan="2">1938</td></tr> </table>	T8S R2W		W C		S4	S3	S9	S10	1938	
T8S R2W											
W C											
S4	S3										
S9	S10										
1938											
	No bearing trees available.										
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.										

Survey: Subdivision Lines: T. 8 S., R. 2 W.

35

Chains

80.00 True point for cor. of secs. 3, 4, 9 and 10 is in wash, 30 lks. wide, course W. from S. 70° E., where it is impracticable to monument the cor., therefore establish W.C. 0.50 chs. S. 0° 02' E.

Land, gently and heavily rolling, mountainous and nearly level.

Soil, rocky, 4th rate.

Timber, paloverde and ironwood.

Undergrowth, greasewood and cacti.

From true point for cor. of secs. 3, 4, 9 and 10.

S. 89° 59' E., on random line, bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect N. and S. line, 3 lks. S. of the cor. of secs. 2, 3, 10 and 11.

Thence

West, on true line, bet. secs. 3 and 10.

Over mountainous land, thru scattering timber and undergrowth. Desc. slightly over S. slope to

2.90 Desc. 168 ft. over SW. slope.

15.00 Enter gently rolling land. Desc. 50 ft. over W. slope.

34.00 Wash, 50 lks. wide, course N. 70° W. Ungraded road bears N. 70° W. and S. 70° E. Desc. gradually over N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S. 3}{S. 10}$$

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue over gently rolling land. Desc. gradually over N. and NW. slopes.

72.70 S. edge of same wash, bears N. 80° W. and N. 87° E. Enter nearly level land.

80.00 The true point for cor. of secs. 3, 4, 9 and 10. (W.C. 0.50 chs. S. 0° 02' E.)

Land, mountainous, gently rolling and nearly level.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, paloverde, ironwood and mesquite.

Undergrowth, greasewood and cacti.

From true point for cor. of secs. 3, 4, 9 and 10.

N. 0° 02' W., on random line, bet. secs. 3 and 4.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

BOOK

Survey: Subdivision Lines: T. 8 S., R. 2 W.

36

Chains	
79.78	Intersect N. bdy. of the Tp., 2 lks. E. of the cor. of secs. 3, 4, 33 and 34, hereinbefore described.
	Thence
	S. 0° 03' E., on true line, bet. secs. 3 and 4.
	Over mountainous land, thru scattering timber and undergrowth. Asc. gradually over W. slope to
1.00	A point 80 lks. E. of bend in wash, course N. from S. 10° W. Continue ascent over W. slope.
6.28	Drain, course NW. Enter rolling land. Asc. 67 ft. over NW. slope.
17.70	Point of spur, slopes W. Desc. 23 ft. over SW. slope.
23.00	Asc. gradually over W. slope,
29.25	Wash, 15 lks. wide, course NW. Asc. 34 ft. over NW. slope.
34.80	Point of spur, slopes NW. Asc. gradually over W. slope to
39.78	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for ¼ sec. cor., with brass cap marked
	$\frac{1}{4}$ S4 S3 .1938
	No bearing trees available.
39.90	Wash, 10 lks. wide, course NW. Asc. 78 ft. over NW. slope.
55.25	Spur, slopes NW. Desc. 86 ft. over SW. and S. slopes.
78.10	Wash, 50 lks. wide, course N. 70° W. Enter nearly level land.
78.68	Ungraded road, bears N. 70° W. and S. 80° E.
79.78	The true point for cor. of secs. 3, 4, 9 and 10, in wash, 30 lks. wide, course W. from S. 70° E. (W.C. 0.50 chs. S. 0° 02' E.)
	Land, mountainous, rolling and nearly level. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., established under this group as described in the field notes of survey of the N. bdy. of T. 9 S., R. 2 W.
	N. 0° 02' W., bet. secs. 32 and 33.
	Over gently rolling land, thru scattering timber and undergrowth. Asc. slightly over SW. slope.
1.40	Desc. 34 ft. over NW. slope.
6.37	Wash, 10 lks. wide, course W. Asc. 35 ft. over SW. slope.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

37

Chains	
15.75	Spur, slopes W. Desc. 40 ft. over N. slope.
20.70	Drain, course W. Asc. 30 ft. over S. slope.
29.80	Spur, slopes W. Desc. 74 ft. over N. slope.
34.15	Wash, 20 lks. wide, course N. 80° W: Enter nearly level land.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor.; with brass cap marked
	$\frac{1}{4}$ S32 S33 1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Enter heavily rolling land. Asc. 106 ft. over S. slope.
46.50	Spur, slopes W. Thence across top of spur.
50.18	Leave top of spur. Desc. 80 ft. over N. slope to
58.29	Enter gently rolling land. Desc. 39 ft. over gradual N. slope.
66.50	Wash, 20 lks. wide, course N. 80° W. Thence over W. slope with slight change in elevation.
73.70	Wash, 40 lks. wide, course S. 70° W. Asc. 25 ft. over S. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap marked
	T8S R2W S29 S28 S32 S33 1938
	No bearing trees available.
	Land, gently and heavily rolling and nearly level. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.
	East, on random line, bet. secs. 28 and 33.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect N. and S. line, 7 lks. S. of the cor. of secs. 27, 28, 33 and 34.
	Thence
	S. 89° 57' W., on true line, bet. secs. 28 and 33.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

38

Chains	Over heavily rolling land, thru scattering timber and undergrowth. Asc. 72 ft. over E. and SE. slopes.
10.70	Spur, slopes S. Desc. 173 ft. over W. and SW. slopes to
20.83	Enter gently rolling land. Desc. gradually over S. slope.
31.00	Asc. 30 ft. over SE. slope.
38.16	Spur, slopes S. 10° W. Desc. 11 ft. over W. slope to
39.98	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{r} S 28 \\ S 33 \end{array}$
	1938
	No bearing trees available.
	Desc. 11 ft. over W. slope.
40.96	Drain, course S. Enter heavily rolling land. Asc. 55 ft. over E. slope.
47.96	Spur, slopes S. Desc. 98 ft. over SW. slope to
61.66	Enter gently rolling land. Desc. gradually over S. slope to
79.96	The cor. of secs. 28, 29, 32 and 33.
	Land, heavily and gently rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.
	N. 0° 02' W., bet. secs. 28 and 29.
	Over rolling land, thru scattering timber and undergrowth. Asc. 109 ft. over S. slope.
14.60	Spur, slopes SW. Enter mountainous land. Desc. 59 ft. over NW. slope.
18.50	Drain, course SW. Asc. 134 ft. over SE. slope.
28.96	Ridge, bears E. and W. Desc. 85 ft. over NE. slope.
35.80	Wash, 90 lks. wide, course N. 70° W. Enter nearly level land.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{r} S 29 \\ S 28 \end{array}$
	1938
	No bearing trees available.
	Over nearly level land.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

39

Chains							
45.00	Enter mountainous land. Asc. 150 ft. over SW. slope.						
58.90	Spur, slopes N. 70° W. Desc. 94 ft. over N. slope.						
63.00	Wash, 10 lks. wide, course N. 70° W. Asc. 74 ft. over S. slope.						
66.72	Ridge, bears N. 70° W. and S. 70° E. Desc. 149 ft. over N. slope.						
77.50	Wash, 10 lks. wide, course NW. Asc. 30 ft. over SW. slope to						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 4 ins. in the ground to bedrock, over a cross (X) marked thereon and in a mound of stone to top, for cor. of secs. 20, 21, 28 and 29, with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T8S</td> <td>R2W</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> </table>	T8S	R2W	S20	S21	S29	S28
T8S	R2W						
S20	S21						
S29	S28						
	1938						
	No bearing trees available.						
	Land, rolling, mountainous, and nearly level. Soil, rocky, 4th rate. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.						
	N. 89° 57' E. on random line, bet. secs. 21 and 28.						
40.00	Set temp. ¼ sec. cor.						
79.98	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 21, 22, 27 and 28.						
	Thence						
	S. 89° 56' W., on true line, bet. secs. 21 and 28.						
	Over mountainous land, thru scattering timber and undergrowth. Asc. 92 ft. over E. and SE. slopes.						
11.98	Spur, slopes S. Desc. 90 ft. over W. slope.						
17.48	Wash, 15 lks. wide, course SW. Asc. 91 ft. over E. and SE. slopes.						
26.98	Spur, slopes S. Desc. 202 ft. over W. slope to						
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground to bedrock over a cross (X) marked thereon, and in a mound of stone to top, for ¼ sec. cor., with brass cap marked						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>¼</td> <td>S 21</td> </tr> <tr> <td></td> <td>S 28</td> </tr> </table>	¼	S 21		S 28		
¼	S 21						
	S 28						
	1938						
	No bearing trees available.						
	Desc. 70 ft. over SW. slope.						
49.00	Wash, 10 lks. wide, course N. 70° W. Enter rolling land. Desc. gradually over N. slope.						

Survey: Subdivision Lines: T. 8 S., R. 2 W.

40

Chains

69:00 Ast. 52 ft. over NE: slope.

74:00 Spur; slopes N. 70° W. Desc. 45 ft. over SW. slope to

79:98 The cor. of secs. 20, 21, 28 and 29:

Land, mountainous and rolling.
Soil, rocky, 4th rate.
Timber, paloverde, ironwood and mesquite.
Undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 20 and 21.

Over rolling land, thru scattering timber and undergrowth.
Asc. slightly over SW. slope.

1:70 Point of spur slopes N. 80° W. Desc. 46 ft. over NW.
slope to

6:70 Foot of slope, bears NE and SW. Enter gently rolling
land. Desc. gradually over NW. and W. slopes.

33:55 Asc. 10 ft. over SW. slope.

36:40 Low spur, slopes W. near point of same. Desc. 30 ft.
over NW. slope to

40:00 Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in
the ground to bedrock, with a stone marked with a cross
(X) deposited at base, and in a mound of stone to top,
for 1/4 sec. cor., with brass cap marked

1/4
S20 | S21

1938

No bearing trees available.

Desc. 10 ft. over NW: slope.

44:80 Wash, 15 lks. wide, course SW. Enter nearly level land.

51:80 Wash, 15 lks. wide, course SW.

80:00 Set an iron post, 3 ft. long, 2 ins. in diam., 16 ins. in
the ground to bedrock, with a stone marked with a cross
(X) deposited at base, and in a mound of stone to top,
for cor. of secs. 16, 17, 20 and 21, with brass cap
marked

T8S R2W
S17 | S16
S20 | S21

1938

No bearing trees available.

Land, rolling, gently rolling and nearly level.
Soil, gravelly and rocky, 3rd and 4th rates.
Timber, paloverde, ironwood and mesquite.
Undergrowth, greasewood and cacti.

Chains	N. 89° 56' E., on random line, bet. secs. 16 and 21.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	Intersect N. and S. line, 2 lks. S. of the cor. of secs. 15, 16, 21 and 22.
	Thence
	S. 89° 55' W., on true line, bet. secs. 16 and 21.
	Over heavily rolling land, thru scattering timber and undergrowth. Desc. 74 ft. over S. and SW. slopes.
13.98	Drain, course S. Enter mountainous land. Asc. 125 ft. over SE. and S. slopes.
26.78	Asc. 20 ft. over NE. slope.
31.10	Spur, slopes N. from rocky knoll, the top of which is 150 lks. S. of this point. Desc. 179 ft. over NW. slope to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Enter gently rolling land. Desc. 23 ft. over NW. slope.
48.00	Wash, 15 lks. wide, course SW. Asc. 12 ft. over SE. slope.
51.15	Desc. 19 ft. over SW. slope.
54.80	Asc. 43 ft. over SE. slope.
62.70	Enter nearly level land.
79.98	The cor. of secs. 16, 17, 20 and 21.
	Land, heavily and gently rolling, mountainous and nearly level. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde, ironwood and mesquite. Undergrowth, greasewood and cacti.
	N. 0° 02' W., bet. secs. 16 and 17.
	Over nearly level land, thru scattering timber and undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S17 S16
	1938

Survey: Subdivision Lines: T. 8 S., R. 2 W.

42

Chains

- No bearing trees available.
- Enter rolling land. Asc. 102 ft. over S. slope.
- 56.00 Spur, slopes E. Rocky butte bears W. about 6 chs. dist.
Desc. 29 ft. over N. slope.
- 60.20 Drain, course E. Asc. 10 ft. over S. slope.
- 61.90 Spur, slopes E. Desc. 69 ft. over NE. slope.
- 68.60 Drain, course E. Asc. 23 ft. over S. slope.
- 71.00 Spur, slopes E. Desc. 46 ft. over N. slope to
- 76.00 Foot of slope, bears E. and W. Enter nearly level land.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 8, 9, 16 and 17, with brass cap marked

T8S	R2W
S8	S9
S17	S16

1938

No bearing trees available.

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Land, nearly level and rolling.
Soil, gravelly and rocky, 3rd and 4th rates.
Timber, paloverde and ironwood.
Undergrowth, greasewood and cacti.

- N. 89° 55' E., on random line, bet. secs. 9 and 16..
- 40.00 Set temp. ¼ sec. cor.
- 79.98 Intersect N. and S. line, 9 lks. N. of the true point for cor. of secs. 9, 10, 15 and 16, in wash, course SW.
- Thence
- S. 89° 59' W., on true line, bet. secs. 9 and 16.
- Over nearly level land, thru scattering timber and undergrowth.
- 0.60 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for witness cor. to cor. of secs. 9, 10, 15 and 16, with brass cap marked

T8S	R2W	
S9	S10	WC
S16	S15	

1938

from which

A paloverde, 8 ins. diam., bears N. 30¾° E., 85 lks. dist., marked WC T8S R2W S9 BT.

An ironwood, 10 ins. diam., bears S. 50½° E., 118 lks. dist., marked WC T8S R2W S15 BT.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

43

Chains	
	<p>A paloverde, 8 ins. diam., bears S. 21° W., 180 lks. dist., marked WC T8S R2W S16 BT..</p> <p>A paloverde, 8 ins. diam., bears N. 40$\frac{3}{4}$° W., 64 lks. dist., marked WC T8S R2W S9 BT.</p>
35.00	Enter rolling land. Asc. 8 ft. over E. slope.
38.78	Low spur, slopes S. Desc. 11 ft. over W. slope to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S 9}{S 16}$ <p>1938</p>
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Desc. slightly over W. slope.
40.98	Drain, course S. Asc. 110 ft. over SE. slope.
55.98	Spur, slopes SW. Desc. 168 ft. over W. slope to
66.68	Foot of slope, bears N. and S. Thence over nearly level land.
79.98	The cor. of secs. 8, 9, 16 and 17.
	<p>Land, nearly level and rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.</p>
	N. 0° 02' W., bet. secs. 8 and 9.
	Over nearly level land, thru scattering timber and undergrowth.
2.10	Wash, course NE.
5.00	Enter gently rolling land. Asc. 13 ft. over SE. slope.
7.00	Point of low spur, slopes E. Desc. 29 ft. over NE. slope to
12.07	Enter nearly level land. Undergrowth becomes dense. Desc. very gradually over general E. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ <p>S8 S9</p> <p>1938</p>
	No bearing trees available.
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Survey: Subdivision Lines T. 8 S., R. 2 W.

Chains	Continue over nearly level land, thru scattering timber and dense undergrowth. Desc. very gradually over NE. slope.						
74.60	Wash, 10 lks. wide, course NW.						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked						
	<table border="1"> <tr><td>T8S</td><td>R2W</td></tr> <tr><td>S5</td><td>S4</td></tr> <tr><td>S8</td><td>S9</td></tr> </table>	T8S	R2W	S5	S4	S8	S9
T8S	R2W						
S5	S4						
S8	S9						
	1938						
	No bearing trees available.						
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.						
	Land, nearly level and gently rolling. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.						
	N. 89° 59' E., on random line, bet. secs. 4 and 9.						
40.00	Set temp. ¼ sec. cor.						
80.00	Intersect N. and S. line, 3 lks. N. of the true point for cor. of secs. 3, 4, 9 and 10, in wash, course N. 70° W. (W.C. 0.50 chs. S. 0° 02' E.)						
	Thence from true point for sec. cor.						
	West, on true line, bet. secs. 4 and 9.						
	Over nearly level land, thru scattering timber and dense undergrowth, in wash, course W.						
5.00	Leave wash, 30 lks. wide, course N. 70° W. from E. Desc. very gradually over N. and NW. slopes to						
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap marked						
	¼ · $\frac{S\ 4}{S\ 9}$						
	1938						
	No bearing trees available.						
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.						
	Continue over nearly level land, thru scattering timber and dense undergrowth. Desc. very gradually over NW. slope.						
62.11	Enter gently rolling land. Desc. 16 ft. over NW. slope to						
65.00	Enter nearly level land.						
80.00	The cor. of secs. 4, 5, 8 and 9.						
	Land, nearly level and gently rolling. Soil, gravelly and rocky, 3rd and 4th rates.						

Survey: Subdivision Lines: T. 8 S., R. 2 W.

BOOK 107

45

Chains	Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 0° 02' W., on random line, bet. secs. 4 and 5.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.64	Intersect N. bdy. of the Tp. 2 lks. E. of the cor. of secs. 4, 5, 32 and 33, hereinbefore described.
	Thence
	S. 0° 03' E., on true line, bet. secs. 4 and 5.
	Over gently rolling land, thru scattering timber and undergrowth. Asc. 20 ft. over N. slope.
3.64	Top of ascent, bears E. and W. Enter nearly level land, and dense undergrowth.
15.44	Wash, 100 lks. wide, course N. 54° W., from S. 25° E.
27.54	Wash, 150 lks. wide, course NW.
39.64	Set an iron post, $\frac{3}{4}$ ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S5 S4
	1938
	No bearing trees available.
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
	U.S. Coast and Geodetic Survey bench mark, a brass tablet marked "W 86", set in a concrete block, 1935 8x8 ins. projecting 2 ins. above ground, bears N. 87° 04' W., 34.80 chs. dist.
	Continue over nearly level land, thru scattering timber and dense undergrowth.
54.34	Ungraded road, bears N. 70° W. and S. 67° E.
71.14	Wash, 20 lks. wide, course W.
79.64	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling and nearly level. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., established under this group as described in the field notes of survey of the N. bdy. of T. 9 S., R. 2 W.
	N. 0° 03' W., bet. secs. 31 and 32.
	Over nearly level land, thru scattering timber and under- growth. Over slight W. slope. Asc. 5 ft.
5.00	Desc. 11 ft.

. Survey: Subdivision Lines: T. 8 S., R. 2 W.

46

Chains	
9.60	Asc. 10 ft.
19.50	Desc. 18 ft.
24.50	Asc. 20 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S31 S32
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Asc. slightly over W. slope.
40.41	Enter gently rolling land. General W. slope. Desc. 35 ft.
50.50	Asc. 16 ft.
66.00	Enter rolling land. Asc. 58 ft. over W. slope.
75.86	Desc. 18 ft. to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 29, 30, 31 and 32, with brass cap marked
	T8S R2W S30 S29 S31 S32
	1938
	No bearing trees available.
	Land, nearly level, gently rolling and rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth; greasewood and cacti.
	East, on random line, bet. secs. 29 and 32.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect the cor. of secs. 28, 29, 32 and 33.
	Thence
	West, on true line, bet. secs. 29 and 32.
	Over rolling land, thru scattering timber and undergrowth. Asc. 68 ft. over S. slope.
10.50	Desc. 111 ft. over SW. slope.
25.84	Wash, course SW. Enter gently rolling land. Asc. 15 ft. over SE. slope.
35.00	Desc. 23 ft. over SW. slope.

Chains

38.74 Draw, course S. Asc. 5 ft. over E. slope to
 40.02 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in
 the ground to bedrock, with a stone marked with a cross
 (X) deposited at base, and in a mound of stone to top,
 for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S 29}{S 32}$$

1938

No bearing trees available.

Thence over rolling land. Asc. 20 ft. over E. slope.

43.95 Desc. 18 ft. over W. slope.

48.34 Wash, course S. Asc. 40 ft. over E. slope.

56.70 Desc. 58 ft. over W. slope.

62.90 Draw, course S. Asc. 47 ft. over E. slope.

72.63 Desc. 38 ft. over W. slope to

80.04 The cor. of secs. 29, 30, 31 and 32.

Land, rolling and gently rolling.

Soil, rocky, 4th rate.

Timber, paloverde and ironwood.

Undergrowth, greasewood and cacti.

West, on random line, bet. secs. 30 and 31.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.84 Intersect W. bdy. of the Tp. 12 lks. N. of the cor. of
 secs. 25, 30, 31 and 36, which is an iron post, 2 ins.
 in diam., projecting 8 ins. above ground, firmly set,
 marked on brass cap and witnessed as described in the
 official record.

Thence

N. 89° 55' E., on true line, bet. secs. 30 and 31.

Over gently rolling land, thru scattering timber and
undergrowth. Asc. gradually over NW. slope.

3.67 Desc. 23 ft. over NE. slope.

8.36 Asc. 66 ft. over N. and NW. slopes.

30.20 Low ridge bears NE. and SW. Asc. 28 ft. over S. slope to

39.84 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in
 the ground to bedrock, with a stone marked with a cross
 (X) deposited at base, and in a mound of stone to top,
 for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S 30}{S 31}$$

1938

No bearing trees available.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

48

Chains	Desc. 21 ft. over SE. slope.
48.08	Asc. 32 ft. over SW. slope.
51.45	Desc. 51 ft. over SE. slope.
60.80	Wash, 20 lks. wide, course SW. Asc. 45 ft. over W. slope.
73.25	Desc. 21 ft. over SE. slope to
79.84	The cor. of secs. 29, 30, 31 and 32.
	Land, gently rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 0° 03' W., bet. secs. 29 and 30. Over gently rolling land, thru scattering timber and undergrowth. Asc. 30 ft. over SE. slope.
6.48	Desc. 35 ft. over NW. slope.
12.55	Wash, 20 lks. wide, course SW. Asc. 56 ft. over SE. slope.
20.21	Desc. 34 ft. over NE. slope.
27.00	Asc. 52 ft. over SE. slope.
35.15	Low ridge, bears N. 70° E. and S. 70° W. Desc. 12 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S30 S29
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Thence over nearly level land. Desc. 6 ft. over N. slope.
44.90	Wash, 70 lks. wide, course S. 86° W. Asc. very gradually over SW. slope.
62.70	Desc. over very gradual NW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap marked
	T8S R2W S19 S20 S30 S29
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Chains	
	<p>Land, gently rolling and nearly level. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.</p>
	<p>East, on random line, bet. secs. 20 and 29.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect N. and S. line, 7 lks. S. of the cor. of secs. 20, 21, 28 and 29.
	Thence
	S. 89° 57' W., on true line, bet. secs. 20 and 29.
	Over rolling land, thru scattering timber and undergrowth. Desc. 35 ft. over SW. slope.
1.90	Wash, 10 lks. wide, course NW. Asc. 70 ft. over NE. slope.
11.25	Asc. slightly over N. slope.
14.45	Desc. 153 ft. over N. slope to
40.05	Set an iron post, $\frac{3}{4}$ ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S. 20}{S. 29}$
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Thence over gently rolling land. Asc. 21 ft. over N. slope.
49.62	Desc. 40 ft. over NW. slope to
59.30	Enter nearly level land. Desc. over very gradual NW. slope to
80.10	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling and gently rolling and nearly level. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.</p>
	S. 89° 55' W., on random line, bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.76	Intersect W. bdy. of the Tp., 2 lks. N. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, 2 ins. in diam., projecting 12 ins. above ground, firmly set and marked on brass cap as described in the official record. No accessories.
	Thence
	N. 89° 54' E., on true line, bet. secs. 19 and 30.

Chains	Over nearly level land, thru scattering timber and undergrowth. Asc. over very gradual SW. slope.
35.40	Wash, 60 lks. wide, course S. 80° W. Asc. over very gradual NW. slope to
39.76	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Thence over gently rolling land. Asc. 43 ft. over NW. slope.
54.75	Enter nearly level land. Asc. over very gradual N. slope.
62.26	Wash, 20 lks. wide, course NW. Asc. over very gradual NW. slope to
79.76	The cor. of secs. 19, 20, 29 and 30.
	Land, nearly level and gently rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 0° 03' W., bet. secs. 19 and 20.
	Over nearly level land, thru scattering timber and undergrowth. Desc. over very gradual NW. slope.
19.50	Wash, 60 lks. wide, course SW. Asc. over very gradual S. slope.
31.19	Enter gently rolling land. Asc. 19 ft. over S. slope.
35.38	Low spur, slopes W. Desc. 37 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S19 S20
	1938
	No bearing trees available.
	Thence over nearly level land. Desc. over very gradual NW. slope.
63.40	Wash, 20 lks. wide, course S. 70° W. Enter gently rolling land. Asc. gradually over SW. and W. slopes to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 17, 18, 19 and 20, with brass cap marked

Survey: Subdivision Lines: T. 8 S., R. 2 W.

E 137 137

51

Chains							
	<table border="1" style="margin: auto;"> <tr> <td>T8S</td> <td>R2W</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> </table>	T8S	R2W	S18	S17	S19	S20
T8S	R2W						
S18	S17						
S19	S20						
	1938						
	No bearing trees available.						
	Land, nearly level and gently rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and catclaw.						
	N. 89° 57' E., on random line, bet. secs. 17 and 20.						
40.00	Set temp. $\frac{1}{4}$ sec. cor.						
80.08	Intersect N. and S. line, 9 lks. S. of the cor. of secs. 16, 17, 20 and 21.						
	Thence						
	S. 89° 53' W., on true line, bet. secs. 17 and 20.						
	Over nearly level land, thru scattering timber and undergrowth.						
7.48	Wash, course S. Enter heavily rolling land. Asc. 106 ft. over SE. slope.						
21.60	Spur, slopes S. Desc. 137 ft. over W. slope.						
37.70	Draw, course S. 10° W. Asc. 17 ft. over E. slope to						
40.04	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked						
	<table border="1" style="margin: auto;"> <tr> <td>$\frac{1}{4}$</td> <td>S 17</td> </tr> <tr> <td></td> <td>S 20</td> </tr> </table>	$\frac{1}{4}$	S 17		S 20		
$\frac{1}{4}$	S 17						
	S 20						
	1938						
	No bearing trees available.						
	Enter mountainous land. Asc. 102 ft. over E. slope.						
45.47	Long spur slopes S. Thence across top of spur.						
47.90	Leave top of spur. Desc. 186 ft. over W. slope.						
57.70	Bottom of ravine, course S. Asc. 179 ft. over E. slope.						
64.20	Spur, slopes S. 10° W. Desc. 192 ft. over W. slope to						
75.10	Foot of slope, bears N. and S. Enter gently rolling land. Desc. 12 ft. over very gradual W. slope to						
80.08	The cor. of secs. 17, 18, 19 and 20.						
	Land, nearly level, heavily and gently rolling and mountainous. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, cacti and greasewood.						

Survey: Subdivision Lines: T. 8 S., R. 2 W.

52

Chains	S. 89° 54' W., on random line, bet. secs. 18 and 19.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.74	Intersect the cor. of secs. 13, 18, 19 and 24 on W. bdy. of the Tp., which is an iron post, 2 ins. in diam., projecting 20 ins. above ground, firmly set in ground and in a mound of stone to top with brass cap marked as described in the official record. No accessories.
	Thence
	N. 89° 54' E., on true line, bet. secs. 18 and 19.
	Over heavily rolling land, thru scattering timber and undergrowth. Asc. 111 ft. over SW. slope.
12.24	Ridge, bears N. and S. Head of spur sloping W. bears N. 1 ch. dist. Enter mountainous land. Desc. 221 ft. over E. slope.
22.58	Wash, course S. 10° E. Enter gently rolling land, Asc. 16 ft. over SW. slope.
30.00	Desc. 35 ft. over SE. slope to
39.74	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{c} S 18 \\ S 19 \end{array}$ 1938
	No bearing trees available.
	Desc. 9 ft. over SE.
48.84	Asc. 22 ft. over S. slope.
66.55	Asc. 26 ft. over W. slope to
79.74	The cor. of secs. 17, 18, 19 and 20.
	Land, heavily and gently rolling and mountainous. Soil, rocky; 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 0° 03' W., bet. secs. 17 and 18.
	Over gently rolling land, thru scattering timber and undergrowth. Asc. 31 ft. over general W. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{c} S 18 \\ S 17 \end{array}$ 1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Chains	Desc. slightly over NW. slope to						
41.40	Wash, course SW. Asc. 43 ft. over SW. slope to						
63.30	Wash, course SW. Enter heavily rolling land. Asc. 94 ft. over SW. and W. slopes to						
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for cor. of secs. 7, 8, 17 and 18, with brass cap marked						
	<table border="1" style="margin: auto;"> <tr> <td>T8S</td> <td>R2W</td> </tr> <tr> <td>S7</td> <td>S8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> </table>	T8S	R2W	S7	S8	S18	S17
T8S	R2W						
S7	S8						
S18	S17						
	1938						
	No bearing trees available.						
	Land, gently and heavily rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.						
	N. 89° 53' E., on random line, bet. secs. 8 and 17.						
40.00	Set temp. 1/4 sec. cor.						
80.04	Intersect N. and S. line, 5 lks. N. of the cor. of secs. 8, 9, 16 and 17.						
	Thence						
	S. 89° 55' W., on true line, bet. secs. 8 and 17.						
	Over nearly level land, thru scattering timber and undergrowth.						
2.64	Wash, course NE. from nearly W. Enter rolling land. Asc. 120 ft. over general S. slope to 1/4 sec. cor. along N. side of draw, course E.						
40.02	Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground, to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for 1/4 sec. cor., with brass cap marked						
	<table border="1" style="margin: auto;"> <tr> <td>1/4</td> <td>S 8</td> </tr> <tr> <td></td> <td>S 17</td> </tr> </table>	1/4	S 8		S 17		
1/4	S 8						
	S 17						
	1938						
	No bearing trees available.						
	Enter heavily rolling land.						
	Desc. 112 ft. over SW. slope.						
48.73	Draw, course S. 80° E. Asc. 96 ft. over E. slope.						
62.02	Ridge, bears N. and S. Desc. 137 ft. over W. slope to						
80.04	The cor. of secs. 7, 8, 17 and 18.						
	Land, nearly level, rolling and heavily rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, cacti and greasewood.						

Survey: Subdivision Lines: T. 8 S., R. 2 W.

54

Chains	S. 89° 54' W., on random line, bet. secs. 7 and 18.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.60	Intersect W. bdy. of the Tp., 5 lks. N. of the cor. of secs. 7, 12, 13 and 18, which is an iron post, 2 ins. in diam., projecting 24 ins. above ground, firmly set in ground and a mound of stone to top, with brass cap marked as described in the official record. No accessories.
	Thence
	N. 89° 52' E., on true line, bet. secs. 7 and 18.
	Over heavily rolling land, thru scattering timber and undergrowth.
	Asc. 46 ft. over W. slope.
4.10	Ridge, bears N. and S. Desc. 113 ft. over E. slope.
11.47	Asc. 40 ft. over SW. slope.
16.43	Enter gently rolling land. Asc. 22 ft. over SW. slope.
25.92	Desc. 37 ft. over SE. slope.
39.55	Wash, course S.
39.60	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S 7}{S 18}$
	1938
	No bearing trees available.
	Enter heavily rolling land. Asc. 52 ft. over SW. slope.
45.12	Desc. 31 ft. over SE. slope.
49.00	Asc. 11 ft. over SW. slope.
54.00	Asc. 80 ft. over W. slope.
58.84	Spur, slopes S. from NE. Desc. 21 ft. over SE. slope.
63.43	Asc. 75 ft. over NW. slope.
73.10	Spur, slopes SW. Asc. 20 ft. over S. slope to
76.80	Wash, course SW. Asc. 17 ft. over W. slope to
79.60	The cor. of secs. 7, 8, 17 and 18.
	Land, heavily and gently rolling. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

BOOK 417

55

Chains	
	N. 0° 03' W., bet. secs. 7 and 8.
	Over heavily rolling land, thru scattering timber and undergrowth. Asc. 14 ft. over W. slope to
3.00	Wash, course SW. Asc. 82 ft. over S. slope.
8.12	Spur, slopes W. Enter mountainous land. Desc. 193 ft. over N. slope.
20.60	Draw, course W., from SE. Enter heavily rolling land. Asc. 27 ft. over S. slope.
22.80	Ridge, bears W. and SE. Desc. 140 ft. over N. slope to
38.20	Enter gently rolling land. Desc. slightly over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$
	S7 S8
	1938
	No bearing trees available.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Desc. over very gradual N. slope.
48.00	Wash, 40 lks. wide, course W. Asc. gradually over SW. slope.
59.20	Desc. slightly over W. slope.
67.40	Enter heavily rolling land. Asc. 27 ft. over SW. slope.
70.00	Desc. 16 ft. over W. slope.
74.65	Asc. 39 ft. over SW. slope.
78.80	Desc. 15 ft. over NW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base; and in a mound of stone to top, for cor. of secs. 5, 6, 7 and 8, with brass cap marked
	T8S R2W
	S6 S5
	S7 S8
	1938
	Land, heavily and gently rolling and mountainous. Soil, rocky, 4th rate. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.
	N. 89° 55' E., on random line, bet. secs. 5 and 8.
40.00	Set temp. $\frac{1}{4}$ sec. cor.

Survey: Subdivision Lines: T. 8 S., R. 2 W.

56

Chains

- 80.04 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 4, 5, 8 and 9.
Thence
S. 89° 54' W., on true line, bet. secs. 5 and 8.
Over nearly level land, thru scattering timber and dense undergrowth.
- 6.50 Shallow wash, 15 lks. wide, course NW.
- 30.00 Enter rolling land. Asc. 25 ft. over E. slope.
- 35.80 Top of low granite knoll. Desc. 34 ft. over W. slope to
- 40.02 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4} \frac{S 5}{S 8}$
- 1938
- No bearing trees available.
- Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
- Thence over nearly level land, thru scattering timber and dense undergrowth.
- 75.00 Enter rolling land. Asc. 26 ft. over NE. slope.
- 77.80 Granite spur, slopes N. Desc. 10 ft. over NW. slope to
- 80.04 The cor. of secs. 5, 6, 7 and 8.
- Land, nearly level and rolling.
Soil, gravelly and rocky, 3rd and 4th rates.
Timber, paloverde and ironwood.
Undergrowth, greasewood and cacti.
-
- S. 89° 52' W., on random line, bet. secs. 6 and 7.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.61 Intersect W. bdy. of the Tp., 2 lks. N. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, 2 ins. in diam., projecting 36 ins. above ground, firmly set in a mound of stone to top, with brass cap marked as described in the official record. No accessories.
- Thence
N. 89° 51' E., on true line, bet. secs. 6 and 7.
Over heavily rolling land, thru scattering timber and undergrowth. Asc. 51 ft. over NW. slope.
- 5.10 Spur, slopes N. from SW. Desc. 75 ft. over E. slope.
- 15.00 Wash, 15 lks. wide, course N. Thence over gently rolling land, ascending gradually over general N. slope.

Chains	
39.61	<p>Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground to bedrock, with a stone marked with a cross (X) deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 6^c}{S 7}$</p> <p style="text-align: center;">1938</p> <p>No bearing trees available.</p>
	<p>Desc. over very gradual NE. slope.</p>
45.60	<p>Wash, 80 lks. wide, course NW. Asc. over very gradual W. slope to</p>
51.87	<p>Enter mountainous land. Asc. 125 ft. over W. slope.</p>
57.60	<p>Spur, slopes N. Desc. 61 ft. over NE. slope.</p>
61.60	<p>Drain, course N. Asc. 142 ft. over NW. slope.</p>
69.20	<p>Spur, slopes N. Desc. 110 ft. over NE. slope.</p>
76.60	<p>Enter rolling land. Asc. 10 ft. over NW. slope to</p>
79.61	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, heavily and gently rolling and mountainous. Soil, gravelly and rocky, 3rd and 4th rates. Timber, paloverde and ironwood. Undergrowth, greasewood and cacti.</p>
	<p>N. 0° 03' W., on random line, bet. secs. 5 and 6.</p>
40.00	<p>Set temp. $\frac{1}{4}$ sec. cor.</p>
79.80	<p>Intersect N. bdy. of the Tp., 3 lks. E. of the cor. of secs. 5, 6, 31 and 32, hereinbefore described.</p>
	<p>Thence</p>
	<p>S. 0° 04' E., on true line, bet. secs. 5 and 6.</p>
	<p>Over gently rolling land, thru scattering timber and undergrowth. Asc. 75 ft. to $\frac{1}{4}$ sec. cor. over general NW. slope.</p>
39.80	<p>Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S6 S5</p> <p style="text-align: center;">1938</p> <p>No bearing trees available.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>Asc. 32 ft. over NW. slope to</p>
54.10	<p>Wash, course NW. Enter heavily rolling land. Asc. 85 ft. over NE. slope.</p>

Survey: Subdivision Lines: T. 8 S., R. 2 W.

58

Chains

62.11 Desc. 56 ft. over SW. slope.
68.46 Asc. 70 ft. over NW. slope to
79.80 The cor. of secs. 5, 6, 7 and 8.

Land, gently and heavily rolling.
Soil, rocky, 4th rate.
Timber, paloverde and ironwood.
Undergrowth, greasewood and cacti.

GENERAL DESCRIPTION

Township 8 South, Range 2 West is situated in the Gila River drainage basin, about 20 miles SE. from the southerly extremity of a large horseshoe bend in the Gila River, known as Gila Bend, which is also the name of a town on the Southern Pacific R.R. and U.S. Highway No. 80, about 4 miles south from same point in the river.

The elevation of this township ranges from about 1600 to 3000 ft. above sea level, the highest elevation being in the northeastern part and the lowest in the southwestern part.

The surface, ranges from level to mountainous, including all of the intermediate classes; nearly level, gently rolling, rolling, hilly, broken, and heavily rolling. The mountainous and heavily rolling surface is mainly in the east half of the township, consisting of spurs and spur ridges extending in a general westerly direction from the Sand Tank Mountains, the main ridge of which bears northerly and southerly thru the western part of the adjoining township on the east. The mountainous and heavily rolling land in the west half of the township is situated in small scattered areas, on ridges, buttes, hills, and spurs, the greater part of which are detached from the ridges in the east half. The surface of the larger part of the west half of the township is gently rolling and nearly level, and there are scattered areas of gently rolling land throughout the east half, and some nearly level land in secs. 25, 35 and 36.

The soil varies from sandy, 2nd rate to rocky 4th rate. The most of the land has gravelly and rocky soil, 3rd and 4th rates.

The timber, in scattering and very scattering growths, in all sections, consists of ironwood, paloverde and mesquite, of no commercial value except for fence posts or fuel. Undergrowth of greasewood, sagebrush, and cacti is prevalent in all sections, mainly scattering, but in some parts is dense.

The entire township is arid, there being no flowing streams or springs, but a well is located in the western part of section 1, equipped with a windmill and stock tank which furnishes the only water supply for the few cattle which periodically graze over this township.

There are no present mining activities in this township, but several old mine shafts in secs. 2 and 3 give evidence of previous mining for low grade gold and copper ore. There are no indications of valuable mineral deposits in any other part of the township.

There are no settlers, and the only improvements are

Chains

a windmill, well, tank and corrals in western part of sec. 11, now the property of O.A. Bender, who also has similar improvements in other townships in this region.

The only road in the township is an unimproved one crossing the northern part of the township from N. bdy. of sec. 5, easterly to E. bdy. of sec. 12, which extends northwesterly to Gila Bend and easterly thru the Sand Tank Mountains to the Vekol Valley.

Paved State Highway No. 84, from Gila Bend to Casa Grande is about 7 miles north, and paved State Highway No. 85 from Gila Bend to Ajo is about 20 miles west.

FINAL FIELD TESTS OF INSTRUMENTS

Buff and Buff transit No. 18002
Ty White, Public Land Surveyor.

April 22, 1938; at camp near cor. of secs. 2, 3, 10 and 11, T. 8 S., R. 2 W., in latitude $32^{\circ} 45' 15''$ N.; longitude $112^{\circ} 26\frac{1}{2}'$ W.; examine the adjustments of Buff and Buff transit No. 18002 and find no errors, then, to test the solar apparatus of same by comparing its indications with a true meridian determined at this station by Polaris observation on April 7, 1938, as hereinbefore described, proceed as follows:

At 9h. 00m., a.m., app.t., set off $32^{\circ} 45'$ N. on the latitude arc; $12^{\circ} 8\frac{1}{2}'$ N. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of $12^{\circ} 10\frac{1}{2}'$ N. on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged, set off $12^{\circ} 13\frac{1}{2}'$ N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1' 30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same which are described in the foregoing field notes.

Buff and Buff transit No. 10125
Norville E. Shearer, Public Land Surveyor.

April 22, 1938, at same station described in the preceding test, examine the adjustments of Buff and Buff transit No. 10125 and find no errors; then, to test the solar apparatus of same by comparing its indications with the same true meridian, proceed as follows:

At 9h. 00m., a.m., app.t., set off $32^{\circ} 45'$ N. on the latitude arc; $12^{\circ} 8\frac{1}{2}'$ N. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of $12^{\circ} 10\frac{1}{2}'$ N. on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged, set off $12^{\circ} 13\frac{1}{2}'$ N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian..

As all of the solar observations made during the usual hours of solar work come within $1' 30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same which are described in the foregoing field notes.

Young and Sons' transit No. 8584
Frank Kennon, Public Land Surveyor

April 22, 1938; at same station hereinbefore described in test of Buff and Buff transit No. 18002, examine the adjustments of Young and Sons' transit No. 8584 and find no errors; then, to test the solar apparatus of same by comparing its indications with the same true meridian, proceed as follows:

At 9h. 00m., a.m., app.t., set off $32^{\circ} 45'$ N. on the latitude arc; $12^{\circ} 8\frac{1}{2}'$ N. on the declination arc; and determine a meridian with the solar, which agrees with the true meridian.

At app. noon, with the latitude arc unchanged, observe the sun on the meridian and obtain a reading of $12^{\circ} 10\frac{1}{2}'$ N. on the declination arc, which agrees with the computed declination of the sun.

At 3h. 00m., p.m., app.t., with the latitude arc unchanged, set off $12^{\circ} 13\frac{1}{2}'$ N. on the declination arc, and determine a meridian with the solar, which agrees with the true meridian.

As all of the solar observations made during the usual hours of solar work come within $1' 30''$ of the true meridian, conclude that this instrument is in satisfactory adjustment on this date, and that it has remained in such condition throughout the surveys executed with same which are described in the foregoing field notes.

85
61

BOOK 207

4-680
(Revised May 1934)

FIELD ASSISTANTS
To

Norville E. Shearer

Public Land Surveyor

NAMES	CAPACITY
Clark Blevins	Principal Assistant
Charles F. Bobo, Jr.	Chainman
Jack Bowker	Cornerman
Winston C. Gill	Cornerman
Roger P. Bowling	Axman
David Gammill	Axman
Alfred A. Sussex	Axman
Glenn P. Snyder	Flagman

88
64

BOOK 4237

CERTIFICATE OF SURVEYOR

I, Frank Kennon, Public Land Surveyor, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 1st day of December, 1937
received from the district cadastral engineer for Arizona, with assignment
instructions dated April 4, 1938, I have surveyed
Part of the Subdivision Lines
of
Township No. 8 South, Range No. 2 West
of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that said
survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.
January 4, 1939
Phoenix, Arizona
Frank Kennon
Public Land Surveyor

~~CERTIFICATE OF APPROVAL~~

~~OFFICE OF SUPERVISOR OF SURVEYS,~~

....., 19.....

~~The foregoing field notes of the survey of~~

~~executed by~~

~~under special instructions dated~~, ~~and assignment~~
~~instructions dated~~, ~~having been critically examined, and~~
~~the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey~~
~~therein described, are hereby approved.~~

~~Supervisor of Surveys.~~

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in~~

~~....., is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~

90
66

BOOK 4237

CERTIFICATE OF SURVEYOR

I, Ty White, Assistant Cadastral Engineer, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 1st day of December, 1937,
received from the district cadastral engineer for Arizona, with assignment
instructions dated February 18, 1938, I have surveyed
North Boundary and
Part of the Subdivision Lines of
Township No. 8 South, Range No. 2 West
of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that said
survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.
September 19, 1941
Phoenix, Arizona

Ty White
Assistant Cadastral Engineer
(formerly Public Land Surveyor)

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,
Denver, Colorado, February 25, 1942.

The foregoing field notes of the survey of North Boundary and
All of the Subdivision Lines of
Township No. 8 South, Range No. 2 West
of the Gila and Salt River Meridian, in the State of Arizona
executed by Ty White, Frank Kennon and Norville E. Shearer,
Public Land Surveyors,
under special instructions dated December 1, 1937 for Group 197, Arizona, and assignment
instructions dated February 18, 1938 and April 4, 1938, having been critically examined, and
the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey
therein described, are hereby approved.

Wm. A. Pinnock
Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.