Book G

## UNITED STATES DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE

BOOK 4269

## FIELD NOTES

OF THE

Of the Gila and Salt River Meridian,  In the State of Arizona  EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer		Township 9 North, Range 5 East,
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.	***********	Township y nor on, hange y basy,
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and september 19, 1941.		······································
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		·
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		·
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.	**************************************	······································
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		·
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.		
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and September 19, 1941.	*	
EXECUTED BY  Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and assignment instructions dated August 1, 1941 and September 19, 1941.	• <b></b>	· 
Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and assignment instructions dated August 1, , 1941 and September 19, 1941.		Of the Gila and Salt River Meridian,
Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and assignment instructions dated August 1, , 1941 and September 19, 1941.	In. t.h.	e State of Arizona
Raymond F. Moss, Assistant Cadastral Engineer  Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of  Commissioner of the General Land Office under date of June 21, 1941  and assignment instructions dated August 1, , 1941 and  September 19, 1941.		
Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of  Commissioner of the General Land Office under date of June 21, 1941  and assignment instructions dated August 1, , 1941 and  September 19, 1941.		EXECUTED BY
General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of  Commissioner of the General Land Office under date of June 21, 1941  and assignment instructions dated August 1, , 1941 and  September 19, 1941.		
General Land Office  Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of  Commissioner of the General Land Office under date of June 21, 1941  and assignment instructions dated August 1, , 1941 and  September 19, 1941.	**********	Raymond F. Moss, Assistant Cadastral Engineer
Under special instructions dated May 13 , 1941, which prove for the surveys included under Group No. 238 , bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and assignment instructions dated August 1, , 1941 and September 19, 1941.	************	
for the surveys included under Group No. 238, bearing the approval of Commissioner of the General Land Office under date of June 21, 1941 and assignment instructions dated August 1, 1941 and September 19, 1941.		Bert E. Wakeman, Junior Cadastral Engineer
Commissioner of the General Land Office under date of June 21, 1941  and assignment instructions dated August 1, , 1941 and September 19, 1941.		Bert E. Wakeman, Junior Cadastral Engineer
Commissioner of the General Land Office under date of June 21, 1941  and assignment instructions dated August 1, , 1941 and September 19, 1941.	Unde	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office
and assignment instructions dated August 1, , 19 41 and September 19, 1941.		Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide
September 19, 1941.	for th	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide the surveys included under Group No. 238 , bearing the approval of the
	for th Comr	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide the surveys included under Group No. 238 , bearing the approval of the missioner of the General Land Office under date of June 21, 1941
Survey commenced November 7 , 19 41	for th	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide  the surveys included under Group No. 238 , bearing the approval of the  missioner of the General Land Office under date of June 21, 1941  ssignment instructions dated August 1, , 1941 and
survey commenced november 1 , 19 41	for th	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide  the surveys included under Group No. 238 , bearing the approval of the  missioner of the General Land Office under date of June 21, 1941  ssignment instructions dated August 1, , 1941 and
·	for th	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide the surveys included under Group No. 238 , bearing the approval of the missioner of the General Land Office under date of June 21, 1941 ssignment instructions dated August 1, , 1941 and September 19, 1941.
	for th	Bert E. Wakeman, Junior Cadastral Engineer  General Land Office  r special instructions dated May 13 , 1941, which provide the surveys included under Group No. 238 , bearing the approval of missioner of the General Land Office under date of June 21, 1941 ssignment instructions dated August 1, , 1941 and September 19, 1941.

.100

BOOK 4269

## INDEX DIAGRAM.

I owns.	hip9.N	ortn	, Range	) Bast	
6	55 s	<b>41</b> 4	30 °3	20 2	10 1
54	53	40	29	19	9
7	53 <sup>8</sup>	39 °	28 10	18 11	8 12
52	51	39	27	18	7
18	50 17	37 <sup>18</sup>	26 15	16 14	6 13
49	49	37	25	16	6
19 47	48 <sup>20</sup>	35 <sup>21</sup>	24 22 24	15 <sup>23</sup>	4 24 3
۲۲۲ 30	45 <sup>29</sup>	33 <sup>28</sup>	23 <b>27</b> 22	13 <sup>26</sup>	2 <sup>25</sup>
81	Ц2 <b>з</b> г	31 <sup>88</sup>	21 84	12 85	1 36

Chains

The subdivisional survey of T.9 N., R.5 E., was executed by Raymond F. Moss, Assistant Cadastral Engineer and Bert E. Wakeman, Junior Cadastral Engineer, using respectively Gurley solar transit No.371537 and Buff solar transit No. 16730. For description of instruments, determination of meridian and other preliminary data, see the field notes of the exterior lines of Ts.9,  $9\frac{1}{2}$  and 10 N., Rs.4 and 5 E. surveyed under this group.

surveyed under this group.

November 5, 1941: at camp, near the \(\frac{1}{2}\) sec. cor. of secs.

1 and 2, T.9 N., R.5 E., on the meridian established Sept.

10, every hour from 8 to 11 a.m. and from 1 to 4 p.m., with the proper settings on the arcs of the solar attachment, Gurley transit No.371537 was oriented with the solar; the resulting lines of sight when compared with the meridian established from Polaris, had a maximum deviation of less than 1'30".

Buff transit No.16730 was tested in a similar manner on November 6 and found to be in satisfactory adjustment.

From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., described in the field notes of the S. bdy. of T.9 N., R.5 E., surveyed under this group,

N.0901 W., bet. secs. 35 and 36.

Over mountainous land, through scattering timber and medium undergrowth. Desc. 77 ft. along a W. slope.

4.90 Ravine, course S.70°W.; asc. 230 ft. over S. slope.

Spur, slopes S.70°W.; desc. 117 ft. over NW. slope. 13.40

Ravine, near head, course W.; asc. 30 ft. over SW. slope. 19.80

23.20 Spur, slopes W.; desc. 394 ft. over N. slope.

Junction of two ravines from S.10°E. and E., course 38.55 N.80°W.; asc. 50 ft. over steep S. slope.

True point for \( \frac{1}{2} \) sec. cor. falls on rocky ledge, an unsuitable place to set cor. 40.00

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock, with a stone mkd. with a cross (X) 40.30 deposited at the base, and in a mound of stone to top, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd. (b).

s 35 | s 36

from which

A juniper, 6 ins. diam., bears S.51°E., 61 lks. dist., mkd. W C 4 S 36 B T

This witness cor, is on top of rocky spur, sloping W. Desc. 110 ft. over steep N. slope.

43.05 Rocky ravine, course N.80°W.; asc. 110 ft. over broken SW. slope.

50.70 Spur, slopes W.; thence along broken W. slope.

59.50 Point of a spur, slopes W.; desc. 100 ft. over NW. slope.

Deep, rocky ravine, course N.80°W.; asc. 190 ft. over 64.80 broken SW. slope.

79.10 Point of a spur, slopes W.; desc. 20 ft. over NW. slope.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with a stone mkd. with a cross (X) 80.00

Chains deposited at the base, and in a mound of stone to top, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T 9 N R 5 E S 26 | S 25 S 35 | S 36 1941

from which

A juniper, 3 ins. diam., bears N.16 E., 123 lks. dist., mkd. B T.

Land, mountainous.
Soil, rocky, 3rd. and 4th. rates.
Timber, juniper; Undergrowth, oak, mountain mahogany, catclaw and ocotillo.

East, on a random line bet. secs. 25 and 36.

40.00 Set temp. \(\frac{1}{4}\) sec. cor.

79.90 A point 3 lks. S. of the cor. of secs. 25 and 36 only, on the E. bdy. of Tp., described in the field notes of the E. bdy., surveyed under this group.

Thence

S.89°59'W., on a true line, bet. secs. 25 and 36.

Over mountainous land, through scattering timber and undergrowth; desc. 150 ft. over W. slope.

5.45 Ravine, course SW.; asc. 115 ft. over E. slope.

11.20 Spur, slopes S.20°W.; desc. 170 ft. over W. slope.

22.60 Spur, slopes W.; continue descent over top of spur, 115 ft.

39.95 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for \( \frac{1}{2} \) sec. cor., with brass cap mkd.

\$ 25 \$ 36 1941

from which

A juniper, 7 ins. diam., bears N.402°E.,20 lks. dist. mkd. 4 S 25 B T

A juniper, 5 ins. diam., bears  $S.42\frac{1}{2}$ °E.,64 lks. dist. mkd.  $\frac{1}{4}$  S 36 B T

Desc. 340 ft. over W. slope, along top of spur.

53.40 Leave top of spur, slopes SW. from E.; continue descent.

67.90 Head of a spur, slopes S.60°W.; desc. 255 ft. over W.slope.

79.90 The cor. of secs. 25, 26, 35 and 36.

Land, mountainous.
Soil, rocky, 3rd. and 4th. rates.
Timber, juniper; undergrowth, oak and catclaw.

N.0°01'W., bet. secs. 25 and 26.

Over mountainous land, through scattering timber and undergrowth; desc. 25 ft. over a W. slope.

rech en

	Chains.	
	5.10	Head of a ravine, course SW.; asc. 2 ft. over a SE. slope.
	8.00	Spur, slopes W.; desc. 118 ft. over a N. slope.
	17.15	Pocky ravine, course W.; asc. h01 ft. over a steep, rocky SW. slope.
	30.60	Point of a rocky spur, slopes N. 80° W., continue ascent 2 ft. over a W. slope.
		Head of a ravine, course W., continue ascent 81 ft. over a W. slope.
٠	40.00	Set an iron post, 3 ft. long, 1 in. diam., $2\frac{1}{4}$ ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	• 14 TT	$\frac{1}{4}$
	•	s 26 s 25
		1941
	·	from which
		A juniper, 6 ins. diam., bears S.342° E., 81 lks. dist., mkd. 4 S 25 B T.
		A juniper, 10 ins. diam., bears N. $40\frac{3}{4}$ ° W., 65 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.
		Asc. 275 ft. over a rolling SW. slope.
	70.00	Spur, slopes W.; desc. 236 ft. over a N. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.
	•	T 9 N R 5 E S 23 S 24.
		s 26 s 25 19l <sub>4</sub> 1
		from which
		A juniper, 8 ins. diam., bears N. 29\frac{1}{20} E., 48 lks. dist., mkd. T 9 N R 5 E S 24 B T.
		A juniper, 12 ins. diam., bears S. $56\frac{3}{4}$ ° E., 61 lks. dist., mkd. T 9 N R 5 E S 25 B T.
		A juniper, ll ins. diam., bears S. 662° W., 59 lks. dist., mkd. T 9 N R 5 E S 26 B T.
	•	A juniper, 6 ins. diam., bears N. 56 W., 77 lks. dist., mkd. T 9 N R 5 E S 23 B T.
	•	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, catclaw and mountain mahogany.
		N. 89° 59' E., on a random line, bet. secs. 24 and 25.
	110.00	Set temp. $\frac{1}{4}$ sec. cor.
	79.82	A point 3 lks. N. of the true point for cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., described in the field notes of the bdrs. of T.9 N., R.5 E., surveyed under

Chains.	this group. Thence
	West, on true line, bet. secs. 24 and 25.
	Over mountainous land, through scattering timber and undergrowth; ascend over a precipitous NE. slope.
7.00	Rim of E. Cedar Mountain, bears N. 30° W. and S. 30° E.; desc. 46 ft. over a W. slope.
7.56	The witness cor. of secs. 24 and 25 only, described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group. Descend 202 ft. over a W. slope.
10.00	From this point, a Department of Agriculture, Forest Service Marker, bears N. 2° 04' E., 7.10 chs. dist., mkd. Fire Control Visible Area Map Point E. Cedar Mt. 5-18, 1938.
18.45	Head of a ravine, course SW.; desc. 53 ft. over a S. slope
24.40	Long spur, slopes SW.; desc. 282 ft. over a W. slope.
39.40	Head of a ravine, course S. 40° W.; desc. 5 ft.
39.91	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$ \frac{\frac{1}{4} \frac{\text{S } 2l_4}{\text{S } 25}}{\text{19l}_{41}} $ from which
	A juniper, 15 ins. diam., bears N. 73° W., 155 lks. dist., mkd. \(\frac{1}{4}\) S 24 B T.
	A juniper, 6 ins. diam., bears S. 56° E., 90 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.
	Descend 22 ft. over a S. slope.
45.50	Spur, slopes S. approx. 5 chs. then W.; desc. 240 ft. over a W. slope.
53.80	Head of a ravine, course NW.; desc. 73 ft. over a steep N. slope.
60.70	Short spur, slopes N. 15° W., continue descent 275 ft. over a NW. slope.
71.20	Small hillside ravine, course N. 30° W.; desc. 45 ft. over a N. slope.
75.70	Short spur, slopes N. 10° W.; desc. 93 ft. over a NW. slope.
79.82	The cor. of secs. 23, 24, 25 and 26.
er en gra	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
	N. 0° 01' W., bet. secs. 23 and 24.
e de egrande egrande de egrande de egrande de egrande de egrande de egrande egra	Over mountainous land, through scattering timber and undergrowth; desc. 107 ft. over a NW. slope.

		•
	Chains. 5.55	Small hillside ravine, course W.; asc. 5 ft.
	7.60	Point of a spur, slopes W.; desc. 31 ft. over a NW. slope.
	10.70	Ravine, course S. 30° W. for 5 chs. to a junction with a ravine from the E., then SW.; asc. 259 ft. over a SE. slope.
-	. 29.60	Low saddle in a spur, which slopes W. Trail, bears E. and W.; asc. 159 ft. over a S. slope.
	33.90	Spur, slopes SW.; asc. 5 ft. over a rolling W. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., $24$ ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
		<u>.</u> 4 1
		s 23 s 24
	•	19/41 from which
	•	A juniper, 9 ins. diam., bears S. $75\frac{1}{4}^{\circ}$ E., 33 lks. dist., mkd. $\frac{1}{4}$ S 24 B.T.
<b>a</b>		A juniper, 8 ins. diam., bears S. $79\frac{1}{2}^{\circ}$ W., 30 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.
		Asc. 24 ft. over a W. slope.
- ·	53,00	Ridge, bet. E. and W. Cedar Mountains, bears E. and S. 60° W. This is the divide bet. Tangle Creek and Long Canyon; desc. 127 ft. over a NW. slope.
	54.94	Barbed wire fence, bears N. 662° E. and S. 662° W.
	60.60	Ravine, course W.; asc. 2 ft. over a SW. slope.
	65.90	Spur, slopes NW.; desc. 305 ft. over a steep N. slope.
	75.40	Rocky ravine, course N. 80° W., continue descent 46 ft. over a W. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.
	•	T 9 N R 5 E S 14 S 13.
		\$ 23 \s 24 . 19\lambda 1
		from which
-		A juniper, 12 ins. diam., bears N. 75° E., 57 lks. dist., mkd. T 9 N R 5 E S 13 B T.
		A juniper, 14 ins. dism., bears S. 434° E., 43 lks. dist., mkd. T 9 N R 5 E S 24 B T.
•		A juniper, 13 ins. dism., bears S. $21\frac{1}{4}^{\circ}$ W., 86 lks. dist., mkd. T 9 N R 5 E S 23 B T.

NW.

A juniper, 12 ins. diam., bears N.  $79\frac{1}{2}^{\circ}$  W., 51 lks. dist., mkd. T 9 N R 5 E S 14 B T.

This cor. is located on top of a spur, which slopes

	,
Chains.	Land, mountainous. Soil, 3rd and Lith rates, rocky. Timber, juniper; undergrowth, oak, catclaw, mountain mahogany and mountain laurel.
	East, on a random line, bet. secs. 13 and 24.
40.00	Set temp. ½ sec. cor.
80.00	A point 3 lks. N. of the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group.
	Thence
	N. 89° 59' W., on true line, bet. secs. 13 and 24.
	Over mountainous land, through scattering timber and undergrowth; asc. 264 ft. over a SE. slope.
8.70	Rocky spur, slopes N. 20° E. A low saddle in same, bears S. 20° W. approx. 3 chs. dist.; desc. 171 ft. over a W. slope.
15.75	Small ravine, course NW.; asc. 28 ft. over an E. slope.
18.45	Point of a spur, slopes N.; desc. 71 ft. over a NW. slope.
22.85	Ravine, course N. 20° E.; asc. 108 ft. over an E. slope.
25.65	Point of a spur, slopes SE.; asc. 166 ft. over an E. slope.
34.90	Spur, slopes N. 30° E.; a low saddle in same spur bears N. 30° E., 1.50 chs. dist.; desc. 19 ft. over a N. slope.
38.90	Rocky ravine, course N.; asc. 20 ft. over an E. slope.
1,0.00	Set an iron post, 3 ft. long, 1 in. diem., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  S 13  S 214
	19/11
•	of stone, 4 ft. base, 3 ft. high, N. of cor.
	Ascend 590 ft. over a steep rocky NE. slope.
57.40	Spur, slopes N. 30° W.; desc. 458 ft. over a steep W. slope.
67.90	Deep ravine, course N. 60° W.; desc. 281 ft. over a broken NW. slope.
00.08	The. cor. of secs. 13, 14, 23 and 24.
	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany, mountain laurel and catclaw.
	N. 0° 01' W., bet. secs. 13 and 14.
	Over mountainous land through scattering timber and undergrowth; desc. 133 ft. over a N. slope.

4-678 b

	Chains. 5.35	Ravine, course NW,; desc. 28 ft. over a W. slope.
	7.60	Spur, slopes NW.; desc. 116 ft. over a NW. slope.
	12.60	Deep ravine, course N. 50° W.; desc. 190 ft. over a broken NW. slope.
	20.80	Junction of a ravine from S. 60° E. and a creek from SW., course NW.
	22.35	Center of same creek, 20 lks. wide, clear running water, 10 lks. wide, 1 in. deep, course N. from SW.
	26.35	Leave creek bed, course NE. from S.; asc. 37 ft. over a SE. slope.
	30.10	Spur, slopes E.; asc. 67 ft. over an E. slope.
	40.00	Set an iron post, 3 ft. long. 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for \( \frac{1}{4} \) sec. cor,, with brass cap mkd.
		s 14 s 13
	•	1941
		Desc. 219 ft. over a NE. slope.
	48.35	Rocky ravine, course N. 50° E.; asc. 15 ft.
	51.55	Point of a spur, slopes NE.; desc. 46 ft. over a NE. slope.
	58.10	Small ravine, course SE.; asc. 108 ft. over a SE. slope.
	67.30	Broad spur, slopes NE.; desc. 229 ft. over a N. slope.
	. 80.00	Set an iron post, 3 ft: long, 2 ins. diam., 8 ins. in the ground to bedrock, with a stone mkd. with a cross (X) deposited at the base and in a mound of stone to top, for cor. of secs. 11, 12, 13 and 11, with brass cap mkd.
		T 9 N R 5 E S 11 S 12
	•	S 14 S 13 1941
		from which
		A juniper, 4 ins. diam., bears S. $21\frac{1}{4}^{\circ}$ W., $2\frac{1}{4}$ lks. dist., mkd. B T.
		A juniper, 5 ins. diam., bears N. 35° W., 48 lks. dist., mkd. T 9 N R 5 E S 11 B T.
		Land, mountainous. Soil, 3rd and lith rates, rocky. Timber, juniper; undergrowth, oak, catclaw, mountain mahogany.
	e:	S. 89° 59' E., on a random line, bet. secs. 12 and 13.
	<u>ф</u> 0.00	Set temp. 4 sec. cor.
	80.00	A point 3 lks. S. of the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., described in the field notes of
_		

	Chains.	the bdrs. of T. 9 N., R. 5 E., surveyed under this Group.
		Thence
		West, on true line, bet. secs. 12 and 13.
,	:	Over mountainous land, through scattering timber and undergrowth; desc. 52 ft. over a W. slope.
	11.90	Ravine, course N.; asc. 19 ft. over an E. slope.
	14.90	Spur, slopes N.; desc. 39 ft. over a W. slope.
	16.50	Ravine, course N.; asc. 161 ft. over an E. slope.
	20.07	A 4-strand barbed wire fence, bears N. 32호 W. and S. 32호 E.
	30.00	Spur, slopes N.; desc. 51 ft. over a W. slope.
0	և0.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with a stone mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
		S 12
		S 13
		1941 from which
		A juniper, 5 ins. dism., bears S. $72\frac{3}{4}$ ° E., 127 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
	•	Desc. 69 ft. over a W. slope.
	42.00.	Ravine, course N.; asc. 52 ft. over an E. slope.
	45.00	Spur, slopes N.; desc. 63.ft. over a NW. slope.
	50.95	Ravine, course N. 30° E.; asc. 134 ft. over a SE. slope.
(	57.20	Horse trail, bears N. and S.
	60.80	Spur, slopes N. 35° E.; desc. 1/4 ft. over a NW. slope.
	69.05	Ravine, course N. 35° E., asc. 114 ft. over a SE slope.
	75.00	Spur, slopes N. 35° E.; desc. 42 ft. over a NW. slope.
	.80.00	The cor. of secs. 11, 12, 13 and 14.
	•	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany, mountain laurel and catclaw.
		N. 0° 01' W., bet. secs. 11 and 12.
	, • A :	Over mountainous land, through scattering timber and undergrowth; desc. 38 ft. over an E. slope.
	3.40	Dry creek bed, 20 lks. wide, course E.for approx. 2 chs. then course NE.; asc. 18 ft. over a rolling E. slope.
	13.35	Top of broad spur, slopes NE., 10 chs. to toe; desc. 61 ft. over a NE. slope.

Chains.	Pavine, course E.; asc. 89 ft. over a S. slope.
26.60	Low, flat ridge, bears E. and W.; desc. 84 ft. over a N. slope.
34.50	Pavine, course NE.; asc. 14 ft. over a rolling E. slope.
10.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
•	s 11 s 12
	1941 from which
•	A juniper, 山 ins. diam., bears S. 43章 E., 158 lks. dist., mkd. B T.
	A juniper, 4 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ W., 68 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
•	Desc. 29 ft. over an E. slope.
53.60	Ravine, course NE.; asc. 3 ft. over a SE. slope.
65.50	Broad, low spur. slopes NE., 15 chs. to toe.; desc. 33 ft. over a broken NE. slope.
72.95	Ravine, course NE
79.00	Low spur, slopes NE.; desc. 7 ft. over a NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diem., 10 ins. in the ground, to bedrock, and in a mound of stone to top, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.
	T 9 N R 5 E S 2 S 1
	s 11 s 12 1941
	from which
	A juniper, 4 ins. dism., bears N. 71° E., 44 lks. dist., mkd. T 9 N R 5 E S 1 B T.
	A juniper, 3 ins. diam., bears S. $38\frac{1}{4}^{\circ}$ E., 60 lks. dist., mkd. B T.
•	A juniper, 6 ins. diam., bears S. 654° W., 91 lks. dist., mkd. T 9 N R 5 E S 11 B T.
· .	A juniper, Lins. diam:, bears N. 734° W., 121 lks. dist., mkd. T 9 N R 5 E S 2 B T.
	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany, mountain laurel and catclaw.
:	East, on a random line, bet. secs. 1 and 12.
40.00	Set temp. \(\frac{1}{4}\) sec. cor.
80.08	The cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N.

и. в. соувеннями рашины сортов 6—8155

**4—673 b** 10

Subdivision of T. 9 N., R. 5 E.

_		
	Chains.	R. 5 E., surveyed under this Group.
		Thence,
		West, on true line, bet. secs. 1 and 12.
	•	Over mountainous land, through scattering timber and undergrowth; desc. 10 ft. over a W. slope.
	3.85	Ravine, course S. 30° E.for 1 ch. then S.; asc. 205 ft. over a NE. slope.
	20.35	Spur, slopes SE.; desc. 266 ft. over a SW. slope.
	37.70	Tangle Creek, clear running water, 20 lks. wide, 10 ins. deep, course SE.; asc. 48 ft. over a NE. slope.
	39.50	Road, to the Verde River, bears SE. from NW.
	40.04	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 4 sec. cor., with brass cap. mkd.
	•	S 1
		\$ 12 1941
		from which
	•	A juniper, 5 ins. diam., bears S. 25\frac{1}{4}\cdot W., 69 lks. dist., mkd. \frac{1}{4} S 12 B T.
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft, high, N. of cor.
	• 5, 1	Asc. 187 ft. over a NE. slope.
	51.50	Spur, slopes N.; desc. 136 ft. over a NW. slope.
	65.70	Ravine, course N. 20° E.; asc. 47 ft. over a broken NE. slope.
	73.45	Ravine, course NE.; asc. 53 ft. over a SE. slope.
	78.30	Spur, slopes NE.; desc. 2 ft. over a NW. slope.
	80.08	The cor. of secs. 1, 2, 11 and 12.
	•	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany, mountain laurel and catelaw.
	•	N. 0° Ol' W., on a rendom line, bet. secs. 1 and 2.
	40.00	Setetemp. Lisec. cor. Sime well nor line in the second to
	80.01	l
		Thence S. 0° 02' W., on true line, bet. secs. 1 and 2.
		Asc. 41 ft. over a N. slope.
	1.55	
	//	

. G. GOVERNMENT PRINTING OFFICE 6-815

///

		TOTAL 1960
C	hains. 7.45	Spur, slopes W.; desc. 45 ft. over a S. slope.
	13.60	Ravine, course W.; asc. 46 ft. over a N. slope.
	16.20	Spur, slopes N. 70° W.; desc. 90 ft. over a SW. slope.
	27.30	Ravine, course W.; asc. 21 ft. over a W. slope.
	33•35	Spur, slopes W.; desc. 61 ft. over a steep S. slope.
	35 <b>.1</b> 0	Graded road, bears N. 80° E. to the Verde River and S. 80° W. to Phoenix and Cordes.
	36.50	Enter bottom land, bears E. and W.
	38.55	Left bank of Tangle Creek, bears NW and SE.
	39.60	.Center of Tangle Creek, clear running water, 25 lks. wide, 2 ins. deep, course SE.
	40.0i	True point for 4 sec. cor. falls in the bed of Tangle Creek, an unsuitable place to set a permanent corner.
	40.25	Right bank of Tangle Creek, bears NW. and SE.
	և0.50	Road, bears SE. to Ranger Station and NW. to Verde River road.
	41.51	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for witness 4 sec. cor., with brass cap mkd.
	•	W C
	•	s 2 s 1
		1941 from which
		A mesquite, 7 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ E., 47 lks. dist., mkd. W C $\frac{1}{4}$ S l B T.
		A juniper, $\mu$ ins. diam., bears N. $47\frac{1}{4}^{\circ}$ W. 34 lks. dist., mkd. W C $\frac{1}{4}$ S 2 B T.
		Pump at well at the Ranger Station bears S. 50½° E. 127 lks. dist.  NW. cor. of the Ranger Station, bears S. 8½° E., 143 lks. dist.
	li.79	
	46.96	Forest Service pasture fence, bears N. 32° E. and S. 32° W.; SW. cor. of Forest Service corral, bears N. 32° E. 1.27 chs. dist.; Forest Service barn, bears N. 81° E., 75 lks. dist.
	49.33	Trail, bears E. and W.; leave bottom land, bears E. and W.
	49.90	Spur, slopes E.; desc. 64 ft. over a S. slope.
	52.45	Deep, rocky, dry wash, 15 lks. wide, course NE.; asc. 89 ft. over a N. slope.
	58.20 <b>65.65</b> <b>7</b> 5.45	Spur, slopes N. 60° W. Continue ascent 45 ft.on NW. slope. Top of ascent; desc. over rolling SE. slope. Dry wash, 10 lks. wide, course E.; asc. 71 ft. over a N. slope.

12 BOOK 4269

Subdivision of T. 9 N., R. 5 E.

Chains. 80.01

The cor. of secs. 1, 2, 11 and 12...

Land, mountainous.
Soil, 2nd and 3rd rates, rocky.

Timber, juniper, mesquite, cottonwood, sycamore and hackberry; undergrowth, oak, catclaw and algerita.

From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group,

N. 0° 01' W., bet. secs. 34 and 35.

Over mountainous land, through scattering timber and undergrowth; asc. 38 ft. over a broken E. slope.

22.95 Ravine, course E.; asc. 190 ft. over a broken E. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

from which

A juniper,  $l_1$  ins. diam., bears N. 59° E., 17 lks. dist., mkd.  $\frac{1}{4}$  S 35 B T.

A juniper, 8 ins. diam., bears S. 16° W., 167 lks. dist., mkd.  $\frac{1}{4}$  S 34 B T.

Asc. 329 ft. over a broken E. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diem., 28 ins. in the ground for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

from which

A juniper, 5 ins. dism., beers N. 13° E., 236 lks. dist., mkd. T 9 N R 5 E S 26 B T.

A juniper, 3 ins. diam., bears S. 24° E., 93 lks. dist., mkd. B T.

A juniper, 8 ins. diam., bears S.  $78\frac{1}{2}$ ° W., 58 lks. dist., mkd. T 9 N R 5 E S 34 B T.

A juniper, h ins. diam., bears N.  $71\frac{1}{2}^{\circ}$  W., 138 lks. dist., mkd B T.

Land, mountainous.
Soil, 2nd and 3rd rates, rocky.
Timber, juniper; undergrowth, oak and catalaw.

East, on a random line, bet. secs. 26 and 35.

40.00

Set temp. 4 sec. cor.

4--678 b

Chains.	A point 3 lks. N. of the cor. of secs. 25, 26, 35 and 36.
	Thence
	N. 89° 59' W., on true line, bet. secs. 26 and 35.
	Over mountainous land, through scattering timber and undergrowth; desc. 391 ft. over a broken W. slope.
33.35	Wash, in bottom of Long Canyon, 40 lks. wide, with water in pools, course S.; asc. 91 ft. over a broken E. slope.
39.99	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	s 26
	s, 35
	1941 from which
	A juniper, $l_1$ ins. dism., bears N. $29\frac{1}{4}^{\circ}$ E., $9l_1$ lks. dist., mkd. B T.
	A juniper, 5 ins. diam., bears S. 22° E., 111 lks. dist., mkd 4 S 35 B T.
~	Asc. 520 ft. over a broken E. slope.
79.98	The cor. of secs. 26, 27, 34 and 35.
-	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
-	N. 0° 01' W., bet. secs. 26 and 27.
	Over mountainous land, through scattering timber and undergrowth; asc. 463 ft. over a broken E. slope.
39.90	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness \( \frac{1}{4} \) sec. cor., with brass cap mkd.
	$\begin{array}{c} & & & & \\ & & \\ & & & \\ & & & \\ & & \\ & & & \\ & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & &$
	s 27 s 26
	1941 from which
	A juniper, 8 ins. diam., bears S. $8\frac{3}{7}$ ° E., 91 lks. dist., mkd. W C $\frac{1}{4}$ S 26 B T.
	A mountain laurel. 8 ins. diam., bears N. 66° W., 40
40.00	lks. dist., mkd. W C 4 S 27 B T.  The true point for 4 sec. cor. falls on rock ledge.  Asc. 136 ft. over a broken rocky, E. slope.
51.20	High spur, slopes S. 30° W.; asc. 19 ft. over a W. slope of same.
60.70	Same spur, slopes S. 2° E.; head of another spur, slopes W.; desc. 261 ft. over a N. slope.
7.8.00	Head of a ravine, course W.; asc. gradually.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the
1	

BOOK 4269

4—673 b

Chains. ground, to bedrock, and in a mound of stone to top, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

from which

A juniper, 8 ins. diam., bears N.  $51\frac{3}{4}$ ° E. 62 lks. dist., mkd. T. 9 N R 5 E S 23 B T.

A juniper, 3 ins. diam., bears S.  $32\frac{1}{4}^{\circ}$  E., 98 lks. dist. mkd. B T.

A juniper, 10 ins. diam., bears S.  $37\frac{1}{2}^{\circ}$  W., 185 lks. dist., mkd. T 9 N R 5 E S 27 B T.

A juniper, 8 ins. diam., bears N. 33° W., 156 lks. dist., mkd. T 9 N R 5 E S 22 B T.

Land, mountainous.
Soil, 2nd and 3rd rates, rocky.
Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.

S. 89° 59' E., on a random line, bet. secs. 23 and 26.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 A point 7 lks. S. of the cor. of secs. 23, 24, 25 and 26.

Thence

S. 89° 58' W., on true line, bet. secs. 23 and 26.

Over mountainous land, through scattering timber and undergrowth; desc. 248 ft. over a NW. slope.

9.70 Wash, in bottom of Long Canyon, 30 lks. wide, course SW.; asc. 66 ft. over a broken S. slope.

24.15 Spur, slopes S.; desc. 20 ft. over a W. slope.

27.90 Ravine, course S.; asc. 56 ft. over an E. slope.

34.00 Spur, slopes S.; desc. 50 ft. over a W. slope.

39.85 Wash, 50 lks. wide, course SE.

lio.00 True point for cor. falls on the W. bank of a wash, an unsuitable place to set a permanent cor.

Let an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{\text{S } 23}{\text{S } 26} \text{W C}$$

from which

A juniper, 20 ins. diam., bears N.  $58\frac{3}{4}^{\circ}$  E.,  $22\frac{1}{4}$  lks. dist., mkd. W C  $\frac{1}{4}$  S 23 B T.

A juniper, 12 ins. diam., bears S.  $48\frac{1}{4}$ ° E., 40 lks. dist., mkd. W C  $\frac{1}{4}$  S 26 B T.

EOOK 4269

Chains.	Asc. 770 ft. over a broken E. slope.
76.70	A saddle in a ridge, which bears N. and S.; desc. 46 ft. over a W. slope.
77.20	A wire fence, bears irregularly N. and S.
80.00	The corner of secs. 22, 23, 26 and 27.
•	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany, and catclaw.
	N. 0° 01' W., bet. secs. 22 and 23.
	Over mountainous land, through scattering timber and undergrowth; asc. 350 ft. over a broken W. slope.
1.0.00	Set an iron post, 3 ft. long, 1 in. diam., $2h$ ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S 22 $\frac{1}{4}$ S 23 1941 from which
* • • • • • • • • • • • • • • • • • • •	1941 from which
	A juniper, 8 ins. diam., bears N. $16\frac{1}{4}^{\circ}$ E., 65 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.
	A juniper, 16 ins. diam., bears S. $48\frac{1}{2}$ ° W., 98 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.
40.80	Spur, slopes SE. for 5 chs. then S.; asc. 626 ft. over a steep rocky S. slope.
40.87	Wire fence, bears N 30° W. and SE. for 5.00 chs. then S.
60.20	Rimrock, 20 ft. high, faces SE.
60.30	Divide, bet. Long Canyon and Lime Creek, bears NE. and SW.; desc. 122 ft. over a NW. slope.
73.60	Head of a ravine, course SW.; asc. 135 ft. over a SE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of sees. 14, 15, 22 and 23, with brass cap mkd.
•	T 9 N R 5 E
	s 22 s 23 1911
	raise a mound of stone. 3 ft. base, 2 ft. high, W. of cor.
t	This sec. cor. is located at the base of a rock ledge, 1 ch. long, 6 ft. high, facing S.
	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.

. 8

**4—678 b** 16

. Subdivision of T. 9 N., R. 5 E.

	Chains.	
	Ona Ins.	N. 89° 58' E., on a random line, bet. secs. 14 and 23.
	40.00	Set temp. 3 sec. cor.
	80.00	A point 9 lks. N. of the cor. of secs. 13, 14, 23 and 24.
		Thence
		N. 89° 58' W., on true line, bet. secs. 14 and 23.
	,	Over mountainous land, through scattering timber and undergrowth; desc. 197 ft. over a W. slope.
	9.30	Ravine, course N. 20° E.; asc. 98 ft. over an E. slope.
	12.70	Spur, slopes NE.; desc. 41 ft. over a NW. slope.
	14.30	Ravine, course NE. from S. 80° W; Asc. 312 ft. over a SE. slope.
	33.30	Enter same ravine, course SE. from W.; asc. 77 ft. along bottom of ravine.
	36.10	Leave ravine, course E. from NW.; trail bears N. and S.; asc. 77 ft. over a N. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	• • •	$\frac{1}{4}$ $\frac{1}{4}$
		S 23 1921
		from which
		A juniper, $1l_1$ ins. diam., bears N. $1l_1\frac{1}{4}$ ° E., 58 lks. dist., mkd. $\frac{1}{4}$ S $1l_1$ B T.
•		A juniper, $2\mu$ ins. diam., bears S. $5\mu_4^2$ ° W., 59 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.
		Asc. 240 ft. over a broken NE. slope.
	51.40	Top of ascent; bears SW., and NE.; desc. 11 ft. over a steep N. slope.
	53.20	Recross ravine, course NE.; asc. 771 ft. over a steep NE. slope.
	68.70	Top of a cliff, 100 ft. high, facing NE.; asc. 318 ft. over a steep NE. slope.
	77.50	Top of a cliff, 60 ft. high, facing E.; continue ascent.
	77.70	Figh spur, slopes S.; desc. 41 ft. over a SW. slope.
	80.00	The cor. of secs. 14, 15, 22 and 23.
	· ·	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		N. 0° 01' W., bet. secs. 14 and 15.
		11. 0 0 m., 000, 0000, 124 and 1).

о. а. осумением размене сертов 6—815

Over mountainous land, through scattering timber and undergrowth; asc. 99 ft. over a SE. slope.

	Chains.	Top of W. Cedar Mountain and main divide bet. Lime Creek and Roundtree Canyon, bears SE. and S. 70° W. A lava outcropping, mkd. ELEV. 5512 FT. +, bears N. 34° 30' W.; 61 lks. dist.; desc. 130 ft. over a steep E. slope.	
	.9.90	Head of a high rocky spur, slopes E.; desc. 764 ft. over a N. slope.	
-	27.90	Ravine, course NE.; asc. Lu ft. over a SE. slope.	
	33.30	Top of a spur, slopes NE.; desc. 93 ft. over a NW. slope.	
	37.50	Revine, course NE.; asc. 1/15 ft. over a SE. slope.	
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 4 sec. cor., with brass cap mkd.	
		S 15 S 1h  19h1  from which	
		A juniper, 8 ins. diam., bears N. 874° E., 49 1ks. dist., mkd. 4 S 14 B T.	
:		A juniper, 8 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ W., 63 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.	
_	•	Asc. 3 ft. over a SE. slope.	
	41.30	Spur, slopes NE.; desc. 120 ft. over a NW. slope.	
	frji • 60	Ravine, course NE.; asc. 40 ft. over a SE. slope.	
	52.30	Spur, slopes NE.; desc. 257 ft. over a NW. slope.	
	60.80	Ravine, course NW. from SW.; desc. 215 ft. over NW. slope	
	79.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. of secs. 10, 11, 14 and 15, with brass cap mkd.	
		T 9 N R 5 E S 10 S 11	
		S 15 S 14 1941 from which	
		A juniper, 12 ins. diam., bears N. $77\frac{1}{2}^{\circ}$ E., 26 lks. dist. mkd. WCT 9 NR 5 ES 14 BT.	
_		A juniper, 10 ins. diam., bears S. 78° E., 48 lks. dist., mkd. W C T 9 N R 5 E S 14 B T.	
		A juniper, 8 ins. diam., bears S. 372° W., 46 lks. dist., mkd. W C T 9 N R 5 E S 15 B T.	
•		A juniper, 14 ins. diam., bears N. 25 W., 49 lks. dist., mkd. W C T 9 N R 5 E S 15 B T.	
•	79.20	Line crosses an Indian ruins.	
	80.00	The true point for the cor. of secs. 10, 11, 11 and 15 falls in a wash, 12 lks. wide, course N. from SW., an unsuitable place to set a permanent cor.	

U. S. GOVERNMENT PRINTING OFFICE 6-8155

Subdivision of T. 9 N., R. 5 E.

Chains.	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
	S. 89° 58' E., on a random line, bet. secs. 11 and 14.
1,0.00	Set temp. ½ sec. cor.
80.06	A point 6 lks. N., of the cor. of secs. 11, 12, 13 and 14.
	Thence
·	N. 89° 55' W., on true line, bet. secs. 11 and 14.
	Over mountainous land, through scattering timber and undergrowth; Asc. 12 ft. over an E. slope.
1.20	Low spur, slopes NE.; desc. 12 ft. over a NW. slope.
3.20	Ravine, course NE.; asc. 262 ft. over a SE. slope.
30.40	Spur, slopes NE.; desc. 56 ft. over a NW. slope.
34.65	Ravine, course NE.; asc. 108 ft.
36.10	Top of a red sandstone cliff, 5 chs. long, 50 ft. high, facing E.; asc. 108 ft. over a SE.slope.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
	S 11
	of stone, 3 ft. base, 2 ft. high, N. of cor.
•	Asc. 111 ft. over a SE. slope.
46.50	Spur, slopes NE.; asc. 324 ft. over a broken NE. slope.
68.20	Spur, slopes N.; desc. 228 ft. over a W. slope.
80.06	The true point for cor. of secs. 10, 11, 14 and 15. For witness cor. see line bet. secs. 14 and 15.  Land, mountainous.  Soil, 3rd and 4th rates, rocky.  Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
• (	From the true point for cor. of secs. 10, 11, 14 and 15. For witness cor. see line bet. secs. 14 and 15),
	N. 0° Cl' W., bet. secs. 10 and 11.
*	Over mountainous land, through scattering timber and undergrowth; descend along the bottom of a ravine.
1.50	Leave ravine, course NE. from S.; desc. 加 ft. over a broken NE. slope.
20.20	Spur, slopes NE.; desc. 81 ft. over a broken E. slope.
l+0.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for 4 sec. sor., with brass cap mkd.

	Chains.	j.
		s 10 s 11
		1941
	•	from which
		A juniper, 8 ins. diam., bears N. 37° E., 75 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
		A juniper, 12 ins. diam., bears N. $82\frac{1}{2}$ ° W., 60 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
	•	Desc. 72 ft. over a broken E. slope.
	63.30	Spur, slopes NE.; desc. 184 ft. over a NW. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.
		T9NR5E S3S2
		s 10 s 11 19!t1
		from which
		A juniper, 5 ins. diam., bears N. 264° E., 88 lks. dist., mkd. T 9 N R 5 E S 2 B T.
	•	A juniper, 3 ins. dism., bears S. 53 E., 132 lks. dist., mkd. B T.
		A juniper, 8 ins. diam., bears S. $56\frac{1}{4}^{\circ}$ W., 89 lks. dist., mkd. T 9 N R 5 E S 10 B T.
•		A juniper, 20 ins. diam., bears N. 574° W., 194 lks. dist., mkd. T 9 N R 5 E S 3 B T.
		Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
		S. 89° 55' E., on a random line, bet. secs. 2 and 11.
	1,0.00	Set temp. 4 sec. cor.
	80.02	A point 6 lks. S. of the cor. of secs. 1, 2, 11 and 12.
		Thence
	ı	N. 89° 58' W., on true line, bet. secs. 2 and 11.
		Desc. 28 ft. over a NW. slope.
	7.20	Favine, course N. 60° E.; asc. 70 ft. over a SE. slope.
	12.70	Spur, slopes N. 20° E.; desc. 20 ft. over a NW. slope.
	15.50	Ravine, course N. 20° E.; asc. 43 ft. over a SE. slope.
	17.80	A fence cor. bears N., 10 chs. dist., from which fences run NE. and NW.
	21.80	Spur, slopes N. 10° E.; desc. 20 ft. over a NW. slope.
	26.20	Ravine, course N. 10° E.; asc. 26 ft. over a SE. slope.
		i ,

4-673 b

20

Subdivision of T. 9 N., R. 5 E.

Chains. Spur, slopes N. 20° E.; desc. 25 ft. over a NW. slope. 31.10 34.20 Ravine, course NE.; asc. 77 ft. over a SE. slope. 40.01 Set an iron post, 3 ft. long, 1 in. dism., 28 ins, in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.  $\begin{array}{c} \frac{1}{4} & \frac{S}{4} & \frac{2}{S} & \frac{11}{19} \\ 19 & 1 & 1 \end{array}$ from which A juniper, 16 ins. diam., bears N. 74° W., 95 lks. dist., mkd. 4 S 2 B T. A juniper, 14 ins. diam., bears S.  $21\frac{3}{4}$ ° E., 159 lks. dist., mkd.  $\frac{1}{4}$  S 11 B T. Asc. 287 ft. over a SE. slope. 74.50 Spur, slopes NE.; desc. 19 ft. over a NW. slope. 80.02 The cor. of secs. 2, 3, 10 and 11. Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw. N. 0° 01' E., on a random line, bet. secs. 2 and 3. 40.00 Set temp 4 sec. cor. A point 5 lks. E. of the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Croup. 80.12 Thence S. 0° Ol' E., on true line, bet. secs. 2 and 3. Over mountainous land, through scattering timber and undergrowth; desc. 26 ft. over a gentle E. slope. 8.30 A graded road, bears W. to Phoenix and E. to Dugan's ranch. Wash in bottom of Roundtree Canyon, 50 lks. wide, course N. 80° E.; asc. 162 ft. over a N. slope. 26.25 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd. 40.12

from which

A juniper, 5 ins. dism., bears S. 65° E.,  $18l_1$  lks. dist., mkd.  $\frac{1}{4}$  S 2 B T.

A juniper,  $\mu$  ins. diam., bears S. 67 ° W., 65 lks. dist., mkd.  $\frac{1}{4}$  S 3 B.T.

Asc. 53 ft. over a NE. slope.

			_
	Chains. 47.80	Spur, slopes N. 20° W.; asc. 251 ft. over a NW. slope.	
	80.12	The cor. of secs. 2, 3, 10 and 11.	
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.	
		From the true point for the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group (For witness cor. see the line on the S. bdy. of sec. 33);	
		N. 0° 02' W., bet. secs. 33 and 34.	
	₹	Over mountainous land, through scattering timber and undergrowth; desc. 350 ft. over a precipitous NE. slope.	
	19.55	Lime Creek, 40 lks. wide, running water, 10 lks. wide, 4 ins. deep, course S. 65° E.; asc. 211 ft. over a steep SW. slope.	
	32.00	Top of steep ascent, bears NW. and SE.; asc. 2h ft. over a gentle S. slope.	
	1,0.00	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a stone mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.	
		<u>.</u> <u>4</u>	
		s 33 s 34	} -
		19l:1	
	1,0.25	Small rocky wash, course S. 75° W.; asc. 218 ft. over a SW. slope.	
	49.41	A barbed wire fence, bears N. 80° E. and S. 80° W.	
	53.00	Point of a spur, slopes W.; desc. 81 ft. over a NW. slope.	
	56.00	Ravine, course N. 70° W.; asc. 134 ft. over a SW. slope.	
	63.45	An abandoned road, bears E. and W.	
	FL.30	Spur, slopes W.; desc. 10 ft. over a N. slope; corner of fences, bearing N 464° E., N. 80° W. and S. 4° E.	
	69.12	A well worn trail, bears E. and W.	
	73.00	Spur, slopes W.; desc. 130 ft. over a steep N. slope.	
٠	<b>75</b> •95	Deep ravine, course W.; asc. 135 ft. over a steep S. slope.	
	79.65	Rim of deep canyon bears N. 30° E. and W., continue asc. of 5 ft.	
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., over a cross (X) marked on solid surface rock, and in a mound of stone to top, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.	

Subdivision of T. 9 N., R. 5 E.

Chains.	
•	T 9 N R 5 E S 28 S 27
	s 33 s 34
	1941 from which
	A juniper, 8 ins. diam., bears N. 563° E., 129 lks. dist., mkd. T 9 N R 5 E S 27 B T.
ž	A juniper, 4 ins. diam., bears S. 59% W., 19 lks. dist., mkd. T 9 N R 5 E S 33 B T.
	A juniper, 4 ins. diem., bears N. 18° W., 96 1ks. dist., mkd. T 9 N R 5 E S 28 B T.
	Land, mountainous. Soil, 3rd and 1th rates, rocky. Timber, juniper, ash, sycamore, hackberry and cottonwood; undergrowth, oak, mountain mahogany, catclaw and algerita.
	East, on a random line, bet, secs. 27 and 34.
10.00	Set temp. $\frac{1}{4}$ sec. cor.
79.96	A point L lks. S. of the cor. of secs. 26, 27, 34 and 35.
	Thence
•	S. 89° 58' W., on true line. bet. secs. 27 and 34.
	Over mountainous land, through scattering timber and undergrowth; asc. 如7 ft. over an E. slope.
7.75	Short rocky spur, slopes E.; continue ascent 163 ft. over a precipitous E. slope.
11.25	Top of a lava rim 25 ft. high.
11.65	Top of a high ridge, bears N. and S.; desc. 474 ft. over a broken W. slope.
29.30	A barbed wire fence, bears N. 80° E. and S. 80° W.
39 <b>.9</b> 8	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
	$ \frac{\frac{1}{4} \frac{\text{S } 27}{\text{S } 34}}{\text{1941}} $ from which
	A juniper, 6 ins. diam., bears N 62° W., 34 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.
	A juniper, 8 ins. diam., bears S. 40° E., 69 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.
	This $\frac{1}{4}$ sec. cor. is located at the S. end of an old Indian ruin.
	Descend 229 ft. over a broken W. slope.
55.10	Ravine, course S. 75° W.; desc. 104 ft. over a broken W. slope.
64.65	Old well worn trail, bears N. and S.

	Chains. 71.04	Point of a spur, slopes SW.; a cor. of fences, bears S. 29½° E., 6 chs. dist., from which fences bear N. 83° E. and S. 163° W.; desc. 193 ft. over a steep W. slope.
	75.40	Deep ravine, course S. 45° W. for approx. 3 chs. then W.; asc. 112 ft. over a SE. slope.
	79•55	Rim of deep ravine, bears N. 30° E. and S. 30° W.
-	- 79.96	The cor. of secs. 27, 28, 33 and 34.
		Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
		N. 0° 02' W., bet. secs. 27 and 28.
•	· .	Over mountainous land, through scattering timber and undergrowth; asc. 42 ft. over a W. slope.
•	19.50	Draw, drains W.; asc. 193 ft. over a SW. slope.
	21.29	A barbed wire fence, bears N. 632° E. and S. 632° W.
	22.59	Old well worn trail, bears NE, and W.
	1.0.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
-	•	s 28 s 27
	•	19/11 from which
		A juniper, 18 ins. diam., bears N. $25\frac{1}{2}^{\circ}$ E., 400 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.
		A juniper, 7 ins. diam., bears N. $23\frac{1}{4}^{\circ}$ W., 132 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.
		Asc. 9 ft. over a S. slope.
	43.00	Point of a spur, slopes W.; desc. 128 ft. over a NW. slope
	66.25	Ravine, course S. 70° W.; asc. 19 ft. over a W. slope.
	76.50	Ravine, course S. 70° W.; asc. 70 ft. over a SW. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to bedrock, with a stone mkd with a cross (X) deposited at the base, and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.
_		T 9 N R 5 E s 21 s 22
		s 28 s 27 1941 from which
•		A juniper, 4 ins. diam., bears S. 27° W., 87 lks. dist., mkd. T 9 N R 5 E S 28 B T.
	* ·	A juniper, 3 ins. diam., bears N. $27\frac{3}{4}^{\circ}$ W., 221 lks., dist., mkd. B T.

**4-678 b** 24

Subdivision of T. 9 N., R. 5 E.

-	1	
	Chains.	Land, mountainous. Soil, 3rd and lith rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
		N. 89° 58' E., on a random line, bet. secs. 22 and 27.
	40.00	Set temp, 4 sec. cor.
	80.00	A point 4 lks. N. of the cor. of secs. 22,23, 26 and 27.
		Thence
		West, on true line, bet. secs. 22 and 27.
,		Over mountainous land, through scattering timber and undergrowth; desc. 108 ft. over a W. slope.
	4.65	Head of a ravine, course NW.; asc. 34 ft. over a NE. slope.
	15.85	Point of a spur, slopes N.; desc. 292 ft. over a NW. slope.
	10.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
		\$ 22 \frac{1}{4} \frac{1}{5.27} 1941 from which
		A juniper, 5 ins. diam., bears N. $48^{\circ}$ E., 57 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.
	6.1	A juniper, 5 ins. diam., bears S. 58° E., 71 lks. dist., mkd. ½ S 27 B T.
	•	Desc. 18 ft. over a NW. slope.
	42.55	Ravine, course S. 50° W.; asc. 113 ft. over a SE. slope.
	50.35	Broad, flat topped spur, slopes SW.; desc. 263 ft. over a rolling W. slope.
	80.00	The cor. of secs. 21, 22, 27 and 28.
	•	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, catclaw, oak, algerita, mountain mahogany and mountain laurel.
		N. 0° 02' W., bet. secs. 21 and 22.
	•	Over mountainous land, through scattering timber and undergrowth; asc. 58 ft. over a SW. slope.
	4.00	Spur, slopes W.; desc. 117 ft. over a N. slope.
	9.40	Deep ravine, course W.; asc. 193 ft. over a S. slope.
	16.50	Broad spur, slopes S. 60° W.; continue escent 23 ft. over a rolling W. slope.
	26.50	Point of a spur, slopes S. 60° W.; desc. 67 ft. over a NW. slope.
	30.90	Pavine, course S. 70° W.; asc. 170 ft. over a SW. slope.
		1

		hains. 40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	,	. (1	$.s 21 \int_{19l_11}^{\frac{1}{2}} s.22$
			$19l_{\downarrow}1$ from which
			A juniper, 4 ins. diam., bears S. $46\frac{1}{2}$ ° E., 58 lks. dist., mkd. 4 S 22 B T.
			A juniper, 5 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ W., 68 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.
			Asc. 14 ft. over a SW. slope.
	į	ļД.05	Spur, slopes N. 70° W.; desc. 13 ft. over a rolling W. slope.
	Ì	47.20	Top of steep descent; desc. 151 ft. over a NW. slope.
		54.50	Deep rocky revine, course W.; asc. 185 ft. over a S. slope
	•	67 <b>.</b> 00	Ridge, bears E. and W., divide between Lime Creek and Round tree Canyon.; desc. 17 ft. over a N. slope.
		77.10	Deep ravine, course W.; asc. 119 ft. over a precipitous S. slope.
		80.00	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, to bedrock, with a stone mkd. with a cross (X) deposited at the base and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.
			T 9 N R 5 E S 16 S 15
			s 21 s 22 1941 from which
-			A juniper, 3 ins. diam., bears N. $59\frac{1}{4}^{\circ}$ E., 66 lks. dist., mkd. B T.
	-		A juniper, 4 ins. diam., bears S. 49° E., 110 lks. dist., mkd. T 9 N R 5 E S 22 B T.
		•	A juniper, 7 ins. diam., bears S. 山岩 W., 105 lks. dist., mkd. T 9 N R 5 E S 21 B T.
		÷	A juniper, 9 ins. diem., bears N. 403° W., 163 lks. dist., mkd. T 9 N R 5 E S 16 B T.
		•	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, catclaw, oak and mountain mahogany.
			East, on a random line, bet. secs. 15 and 22.
		ho.00	Set temp. 1/4 sec. cor.
		80.06	A point 7 lks. S. of the cor. of secs. 14, 15, 22 and 23.
			Thence

Chains.	S. 89°.57' W., on true line, bet. secs. 15 and 22.
	Over mountainous land, through scattering timber and undergrowth; desc. 154 ft. over a SW. slope.
13.30	Main divide, between, Lime Creek and Roundtree Canyon, bears SW. and NE.; desc. 751 ft. over a steep W. slope.
1,0.03	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, and in a mound of stone to top for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	s 15
n	s 22 1911 . from which
	A juniper, li ins. dism., bears N. 72° W., 57 lks. dist., mkd. 4 S-15 B T.
	A jumiper, 5 ins. diam., bears S. 50° W., 49 lks.
•	dist., mkd. 4 S 22 B T.
1	Desc. 100 ft. over a NW. slope.
44.15	Small ravine, course SW.; asc. 25 ft. over an E. slope.
46.55	Point of a spur, slopes S.; desc. 244 ft. over a SW. slope.
67.40	Junction of two ravines from N. 60° E. and S. 70° E., course N, 80° W.; asc. 3 ft. over an E. slope.
48.50	Point of a spur, slopes N.; desc. 31 ft. over a NW. slope.
70.50	Ravine, course S. 30° W.; asc. 42 ft. over a SE. slope.
 76.95	Point of a spur, slopes S.; desc. 40 ft. over a S. slope.
80.06	The cor. of secs. 15, 16, 21 and 22.
e e	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, catclaw, oak and algerita.
	N. 0° 02' W., bet. secs. 15 and 16.
•	Over mountainous land, through scattering timber and undergrowth; asc. 81 ft. over a SW. slope.
10.30	Broad spur, slopes W.; desc. 131 ft. over a NW. slope.
29.85	Deep rocky ravine, course W.; asc. 124 ft. over a SW. slope.
36.50	Broad spur, slopes W.; asc. 8 ft. over a W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
	1 4
	s 16 s 15
	1941

from which

Chains.	
	A juniper, lip ins. diam., bears S. 742° E., 43 lks. dist., mkd. & S 15 B.T.
	A juniper, 8 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 82 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	Asc. 88 ft. over a SW. slope.
54.95	Proad spur, slopes W.; desc. 37 ft. over a rolling.W. slope.
66.90	Leave rolling W. slope; desc. 119 ft. over a NW. slope.
71.45	Rocky ravine, course N. 80° W.; asc. 156 ft. over a steep SW. slope.
79.20	Rocky spur, slopes W.; desc. 3 ft. over a N. slope.
80,00	Set an iron post, 3 ft. long, 2 ins. dism., 12 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.
	T 9 N R 5 E S 9 S 10
	s 16 s 15 19l <sub>4</sub> 1
	from which
	A juniper, 10 ins. dism., bears N. 40° E., 107 lks. dist., mkd. T 9 N R 5 E S 10 B T.
	A juniper, 5 ins. diam., bears S. 45° E., 126 lks. dist., mkd. T 9 N R 5 E S 15 B T.
	A mountain mahogeny, 6 ins. diam., bears S. 334° W. 108 lks. dist., mkd.T 9 N R 5 E S 16 B T.
•	A juniper, 7 ins. diam., bears N. 25° W., 54 lks. dist., mkd. B T.
	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, catclaw, oak and mountain mahogany.
	N. 89° 57! E., on a random line, bet. secs. 10 and 15.
ji0.00	Set temp. ½ sec. cor.
79.94	A point 14 lks. S. of the cor, of secs. 10, 11, 14 and 15.  For witness cor., see line bet. secs. 14 and 15.  Thence
•	S. 89° 51' W., on true line, bet. secs. 10 and 15.
	Over mountainous land, through scattering timber and undergrowth; Asc. 1073 ft. over a NE. slope.
37.35	The main ridge of West Cedar Mountain, bears N. 10° W. and S. 10° E.; desc. 35 ft. over a W. slope.
37.71	Barbed wire fence, bears N. 10° W. and S. 10° E.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

4—673 b BOOK 4269 28

. Subdivision of T. 9 N., R. 5 E.

Chains.	S 10
	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
•	1941
	from which
	A juniper, 5 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 13 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
•	A juniper, 6 ins. diam., bears S. 77% E., 1/17 lks. dist., mkd. 4 S 15 B T.
1	Desc. 391 ft. over a steep W. slope.
55.90	Rocky ravine, course NW.; asc. 46 ft. over a.N. slope.
61.75	Short spur, slopes N. 20° W.; desc. 211 ft. over a NW. slope.
79.94	The cor. of secs. 9, 10, 15 and 16.
e.	Land, mountainous.
	Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrwoth, oak, catclaw and mountain mahogany.
	N. 0° 02' W., bet. secs. 9 and 10.
• *	Over mountainous land, through a medium growth of timber and scattering undergrowth; desc. 176 ft. over a NW. slope.
7.18	Deep rocky ravine, course W.; asc. 171 ft. over a steep S. slope.
i2.95	Spur, slopes W.; desc. 101 ft. over a N. slope.
18,25	Rocky ravine, course W.; asc. 125 ft. over a SW. slope.
27.05	Broad spur, slopes W.; desc. 48 ft. over a NW. slope.
33.80	Head of a ravine, course W.; asc. 35 ft. over a SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., $24$ ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap. mkd.
4	$\frac{1}{4}$
	in the line of the line seeman and the line se
	from which
	A juniper, 10 ins. diam., bears S. $15\frac{1}{4}^{\circ}$ E., 61 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
	A juniper, 9 ins. dism., bears N. 23° W., 38 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
	Asc. 73 ft. over a SW. slope.
51.60	Spur, slopes W. and a rimrock, bears E. and W.; desc. 952 ft. over a steep N. slope.
76.00	Deep ravine, course N. 75° W., desc. 2 ft.
78.35	Spur, slopes NW. desc. 22 ft. over a NE. slope.

-678 b

BCOK 4269 Chains. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 3,  $l_{\rm t}$ , 9 and 10, with brass cap 80.00 T 9 N R 5 E S 4 S 3 S 9 S 10 19k1 from which A juniper, 6 ins. diam., bears N. 27° E., 84 lks. dist., mkd. T 9 N R 5 E S 3 B T. A juniper, 5 ins. dism., bears S. 774 Phys. 45 lks. dist., mkd. T 9 N R 5 E S 10 B T. A juniper, 5 ins. diam., bears S.  $17\frac{1}{2}$ ° W., 71 lks. dist., mkd. T 9 N R 5 E S 9 B T. A juniper, 3 ins. diam., bears N.  $47_4^{10}$  W., 91 lks. dist., mkd. B T. Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak, catclaw and mountain N. 89° 51' E., on a random line, bet. secs. 3 and 10. 40.00 Set temp. 1/4 sec. cor. A point 9 lks. N., of the cor. of secs. 2, 3, 10 and 11. 79.98 Thence S. 89° 55! W., on true line, bet. secs. 3 and 10. Over mountainous land, through scattering timber and undergrowth; desc. 94 ft. over a NW. slope. Pavine, course NE.; asc. 399 ft. over a broken E. slope. 11.35 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock and in a mound of stone to top, for  $\frac{1}{4}$ 39.99. sec. cor., with brass cap mkd. from which A mountain mahogany, 6 ins. diam., bears N. 71° E. 19 lks. dist., mkd. & S 3 B T. A mountain mahogany,  $\mu$  ins. diam., bears S.  $63\frac{1}{4}^{\circ}$  E.,  $\mu$ 0 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T. Asc. 29 ft. over a NE. slope. High rocky spur, slopes N.; desc. 306 ft. over a steep 42.15 W. slope. Rocky ravine, course N. 10° E.; asc. 87 ft. over an E. 51.55

Spur, slopes N.; asc. 6 ft. over a N. slope.

54.25

<del>4—673ъ</del> 30 BOOK 4269

Subdivision of T. 9 N., R. 5 E.

Chains. 59.25	Rocky spur, slopes N.; desc. 181 ft. over a NW. slope.
67.55	Rocky ravine, course N.; asc. 85 ft. over a NE. slope.
74.45	Spur, slopes N.; desc. 38 ft. over a NW. slope.
79.98	The cor. of secs. 3, 1, 9 and 10.
	Land, mountainous. Soil, 2nd and 3rd rates, rocky.
	Timber, juniper; undergrowth, oak, catclaw and mountain mahogany.
•	North; on random line, bet. secs. 3 and 4.
1,0.00	Set temp. \(\frac{1}{4}\) sec. cor.
80.16	A point.5 lks. E. of the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group.
	Thence
	S. 0° 02' E., on true line, bet. secs. 3 and 4.
	Over mountainous land, through scattering timber and under growth; desc. 134 ft. over a S. slope.
5.50	Dry wash, 25 lks. wide, course E.; asc. 56 ft. over a N. slope.
7.35	Point of a broad spur, slopes N. 60° E., desc. 8 ft. over an E. slope.
12.55	Dry wash, 15 lks. wide, course N. 20° H.; ssc. 99 ft. over a N. slope.
20.30	Short spur, slopes NE.; desc. 17 ft. over an E. slope.
30.55	Deep ravine, course E.; asc. 204 ft. over a NE. slope.
h0.16	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	1 4
	S 4 S 3
	1941 from which
-	A juniper, 3 ins. diam., bears N. $86\frac{1}{4}^{\circ}$ E., $1l_1$ lks. dist., mkd. $\frac{1}{4}$ S 3 B T.
	A juniper, 8 ins. diam., bears N. 234° W., 54 lks. dist., mkd. 4 S 4 B T.
	Asc. 17 ft. over a NE. slope.
41.20	Spur, slopes S. 60° E.; desc. 195 ft. over a broken SE. slope.
· 55.40	Spur, slopes SE.; continue descent 125 ft. over a SE. slope.
62.50	Graded road, bears N. 30° E. to Cordes and S. 60° W. to Phoenix.

Subdivision of T. 9 N., R. 5 E. Chains, Creek, in bottom of Roundtree Canyon, clear running. 43.30 water, 15 lks. wide, 3 ins. deep, course N. 40° E.; asc. 297 ft. over a NW. slope. 80.16 The cor. of secs. 3, 4, 9 and 10. Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper, sycamore and cottonwood; undergrowth, oak and catclaw. From the true point for the standard cor. of secs. 32 and 33 on the S. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group (For witness cor, see line on the S. bdy. of sec. 32). N. 0° 02' Wa, bet. secs. 32 and 33. Over mountainous land, through scattering timber and undergrowth; across a small flat in the bend of a creek; desc. 9 ft. Dry creek bed, 20 lks. wide, course N. 45° E. for approx. 1.50 chs. then course N. 10° E.; asc. 200 ft. over a steep SE. slope. 2.30 Rim of a canyon, bears NE. and SW. 11.80

4--678 b

Barbed wire fence, bears N.  $16\frac{1}{2}^{\circ}$  E. and S.  $16\frac{1}{2}^{\circ}$  W.; desc. 14.25 68 ft. over a gentle N. slope.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$ 40.00 sec. cor., with brass cap mkd.

from which

A juniper, 6 ins. diam., bears S.  $71\frac{1}{2}^{\circ}$  E., 100 lks. dist., mkd. B T.

A hackberry, 6 ins. diam., bears N. 13° W., 134 1ks. dist., mkd. 4 S 32 B T.

Desc. 9 ft. over a NE. slope.

Head of a draw, drains E.; asc. 9 ft. over a S. slope. 42.50

Graded road, bears N. 25° E. to Cordes and S. 25° W. to Phoenix; continue ascent 17 ft. over a gentle S. slope. 43.85

Top of a flat ridge, bears E. and W.; desc. 18 ft. over 50.00 a gentle NE. slope.

Edge of mesa, bears NW. and SE.; junction of large washes flowing from W. and NW., bears N. 85° W.; a connecting gate between two corrals bears N 68° 52' E.; S. cor. of a stone house on the T. C. Cavness Ranch, bears N. 31° 08' E.; desc. 295 ft. over a steep NE. slope. 67.26

A graded road, bears N. 36° W. to Cordes and S. 36° E. to Phoenix., continue descent 15 ft. over a NE. slope. 79.15

Subdivision of T. 9 N., R. 5 E.

Chains. 80.00

Set an iron post, 30ft. long, 2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T 9 N R 5 E S 29 S 28 s 321s 33 1941

from which

A juniper,  $\mu$  ins. diam., bears N.  $67\frac{2}{7}$ ° E., 70 lks. dist., mkd. T 9 N R 5 E S 28 B T.

A juniper, 6 ins. dism., bears S. 41° E., 148 1ks. dist., mkd. T 9 N R 5 E S 33 B T.

A juniper, 5 ins. diam., bears S.  $19\frac{1}{2}^{\circ}$  W., 95 lks. dist., mkd. T 9 N R 5 E S 32 B T.

A jumiper, 6 ins. diam., bears N.  $17\frac{1}{8}$ ° W., 102 lks. dist., mkd. T 9 N R 5 E S 29 B T.

The SW. cor. of a building in the SW. cor. of a group of 10 buildings at a CGC camp, bears N. 21° 47' W.

The SE. cor. of the SE. building of the same group as above, bears N. 12° 20'  $W_{\star}$ 

The N. gable of the northernmost building of the above group, bears N. 18° 33' W.

The S. end of the headwall at the E. end of a cattle guard, bears N.  $2l_{\perp}^{\circ}$  20  $^{\circ}$  W.

Land, mountainous:

Soil, 2nd and 3rd rates, rocky.
Timber, juniper and hackberry; undergrowth, oak, catclaw, mountain laurel and mountain mahogany.

East, on a random line, bet. secs. 28 and 33.

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

79.92

A point 5 lks. N. of the cor. of secs. 27, 28, 33 and 34.

Thence

N. 89° 58' W., on true line, bet. secs. 28 and 33.

Over mountainous land, through scattering timber and undergrowth.; desc. 309 ft. over a broken W. slope.

37.42

Corral fence, bears N. and S.

37.山

Intersect line 4-1 of Homestead Entry Survey No. 415 at a point from which cor. No. 4, bears N. 32° 20' E., 6.34 chs. dist.; a cedar, 24 ins. in diam., marked and witnesses ed as described in the official record.

From the same point, cor: No. 1, of Homestead Entry Survey No. 415, bears S. 32° 20' W., 12.00 chs. dist.; a cedar 24 ins. dismon marked and witnessed as described in the official record.

From cor. No. 1 of Homestead Entry Survey No. 415, USLM No. 415 HES, bears S. 63° 57' W., 25.68 chs. dist.; a baselt stone, 30x20x15 ins. above ground, marked and witnessed as described in the official record.

	Chains.	Wash, course SW.
	39.96	Set an iron post, 3 ft. long, 1 in. diam., 34 ins. in the ground for 4 sec. cor., with brass cap mkd.
		s 28
-		S 33
		1941 from which
		The SE. cor. of a branding chute, bears N. $67\frac{1}{4}^{\circ}$ W., 212 lks. dist.
		A water supply pipe, 1 in. diam., at the S. end of a metal water trough, bears N. $18\frac{1}{2}$ ° E., 186 lks. dist.
		Cor. No. 4 of Homestead Entry Survey No. 415, bears N. 47° 47' E., 8.00 chs. dist.; hereinbefore described.
		USLM No. 115 HES, bears S. 51° 28' W., 34.46 chs. dist.; hereinbefore described.
	1,2.33	Fence, bears N. and S. on the W. side of a corral which is 5 chs. square.
	45.00	Road, bears NE. and Sw.
	149.28	Intersect line 1-2 of Homestead Entry Survey No. 415 at a point from which cor. No. 1 bears S. 28° 08' E., 11.49 chs. dist.; hereinbefore described.
		From the same point, cor. No. 2 of Homestead Entry Survey No. 415, bears N. 28° 08' W., 26.58 chs. dist., a basalt stone, 15x16x4 ins. above ground, marked and witnessed as described in the official record.
	62.10	Wash, course SE.; asc. 154 ft. over a NE. slope.
	78.52	Wire fence bears NW. and SE.
	79.92	The cor. of secs. 28, 29, 32 and 33.
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, catclaw and oak.
		N. 0° 02! W., bet. secs. 28 and 29.
		Over mountainous land, through scattering timber and undergrowth; desc. llh ft. over a NE. slope.
	2.34	Fence, bears N. 294° W. and S. 294° E.
	. 8.80	Road, bears NW. and SE.
	11.70	Fence, bears N. 86° E. and S. 86° W.
	15.20	Graded road, bears E. and W.
	19.65	Ash Springs Creek, running water, 3 lks. wide, 3 ins. deep, course SE.; asc. 98 ft. over a SW. slope.
	33.30	Top of ascent; desc. 28 ft. over a N. slope.
	36.30	Creek, running water, 2 lks. wide, 4 ins. deep, course SW. from NE.; asc. 62 ft. over a steep rocky S. slope.

Subdivision of T. 9 N., R. 5 E.,

Chains. 39.00	Point of a rocky spur, slopes E. from NW.; desc. 22 ft. over a N. slope.
39.85	Recross creek, course SE. from NW.; asc. 5 ft. over a SW. slope.
140.00	The true point for \( \frac{1}{4} \) sec. cor. falls on steep sloping surface rock, an unsuitable place to set a permanent cor.; asc. 32 ft. over a steep W. slope.
42.30	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness 4 sec. cor., with brass cap mkd.
	1 4 4
	s 29 s 28
	W C
	from which
•	A juniper, 4 ins. diam., bears S. 594° E., 45 lks. dist., mkd. W C 4 S 28 B T.
	A juniper, 5 ins. diam., bears N. 332 W., 327 lks. dist., mkd. W C & S 29 B T.
	This witness $\frac{1}{4}$ sec. cor. falls on top of a spur, slopes W.; desc. 16 ft. over a NW. slope.
43.50	Ravine, course W.; asc. 241 ft. over a SW. slope.
52.00	Spur, slopes SE.; desc. 63 ft. over an E. slope.
52.40	Trail, bears SE. to Cavmess Ranch and NW. to 6 Bar Ranch.
73.30	Pavine, course S. 10° E.; asc. 189 ft. over a W. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20,21,28 and 29, with brass cap marked
	T 9 N R 5 E S 20   S 21
	\$ 29 S 28
	1941 from which
	A juniper, 8 ins. diam., bears N. 7孝° E., 113 lks. dist., mkd. T 9 N R 5 E S 21 B T.
	A juniper, 6 ins. diam., bears S. $10\frac{1}{4}^{\circ}$ E., 105 lks. dist., mkd. T 9 N R 5 E S 28 B T.
	A juniper, 8 ins. diam., bears S. 812 W., 104 lks. dist., mkd. T 9 N R 5 E S 29 B T.
	A juniper, 16 ins. diam., bears N. 84 W., 118 lks. dist., mkd. T 9 N R 5 E S 20 B T.
,	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, catclew and oak.
	S. 89° 58' E., on a random line, bet. secs. 21 and 28.
1,0.00	Set temp. $\frac{1}{4}$ sec. cor.

EOCK 4269

Chains.	A point 21 lks. N. of the cor. of secs. 21, 22, 27 and 28.
	Thence
.•	N. 89° 49' W., om true line. bet. secs. 21 and 28.
•	Over mountainous land, through scattering timber and undergrowth; desc. 202 ft. over a SW. slope.
14.25	Spur, slopes W.from N. 75° E.; continue descent 172 ft. along top, of same.
34.00	Graded road, beers N. 32 E. to Cordes and S. 32 W. to Phoenix.
37.20	Dry wash, 15 lks. wide, course S.; asc. 11 ft. over an E. slope.
39.25	Trail, bears N. and S.
39-97	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
1	s 21 .
;	$\frac{1}{4} \frac{\text{S 21}}{\text{S 28}}$
•	1941 from which
	A juniper, 7 ins. diam., bears N. 27° E., 130 lks. dist., mkd. 4 S 21 B T.
	A juniper, 10 ins. diam., bears S. $41\frac{3}{4}$ E., 52 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.
•	Asc. 36 ft. over a E. slope.
119.10	Bavine, course S. 50° E.; asc. 118 ft. over a steep E. slope.
55.85	Ravine, course S. 70° E.; asc. 129 ft. over a steep E. slope.
60.75	Point of a spur, slopes S. 45° E.; desc. 90 ft. over a SW. slope.
66.15	Ravine, course S. 60° E.; asc. 284 ft. over a steep E. slope.
77.00	Ridge, bears N. 10° W. and S. 10° E.; desc. 31 ft. over a W. slope.
179.94	The cor. of secs. 20, 21, 28 and 29.
	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper and hackberry; undergrowth, catclaw, oak and algerita.
	N. 0° 02' W., bet. secs. 20 and 21.
	Over mountainous land, through scattering timber and undergrowth; Asc. 56 ft. over a SW. slope.
4.10	Spur, slopes S. 30° E.; desc. 66 ft. over a NE. slope.
9.90	Head of a ravine, course S. 70° E.; asc. 111 ft. over a SE. slope.

## Subdivision of T. 9 N., R. 5 E.

	neins. .7.70	Ridge, divide bet. Holmes Creek and Lime Creek, bears E. and S. 60° W.; desc. 283 ft. over a N. slope.
7	50.60	Dry wash, 15 lks. wide, course N. 80° E.; asc. 241 ft. over a SE. slope.
14	10.00	Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
		$\frac{1}{4}$ .
	•	s 20 s 21
		19/ <sub>+</sub> 1 from which
		A juniper, 5 ins. dism., bears N. $50\frac{1}{2}$ ° E., 60 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.
	•	A juniper, 5 ins. diam., bears S. $\mu$ W., 93 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.
		Asc. 52 ft. over a SE, slope.
5	50.40	Spur, slopes E. for 8 chs. then it forks, one fork slopes N. and the other slopes SE.; desc. 168 ft. over a N. slope.
5	6.25	Head of a ravine, course N. 30° W.; asc. 24 ft. over a W. slope.
6	3.65	Spur, slopes N. 80° W.; desc. 127 ft. over a NW. slope.
6	9.35	Spur, slopes NW.; continue descent 200 ft. over a N. slope.
7	78 <b>.</b> 15	Road, bears E. to Cordes to Phoenix road and SW. to Bloody Basin Mines.
7	'9•35	Holmes Creek, 30 lks. wide, running water, 10 lks. wide, 1 in. deep, course N. 45° E.; asc. 23 ft. over a SE. slope.
8	30.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.
		T 9 N R 5 E S 17 S 16 S 20 S 21 1941
		from which
		A juniper, 8 ins. diam., bears N. 69° E., 100 lks. dist., mkd. T 9 N R 5 E S 16 B T.
	y	A juniper, 7 ins. diam., bears S. 31 E., 118 lks. dist., mkd. T 9 N R 5 E S 21 B T.
		A juniper, 5 ins. diam., bears S. 86 W., 204 lks. dist., mkd. T 9 N R 5 E S 20 B T.
	10°	A juniper, 3 ins. diam., bears N. $65\frac{3}{4}$ ° W., 192 lks. dist., mkd. B T.

Land, mountainous.
Soil, 2nd and 3rd rates, rocky.
Timber, juniper; undergrowth, catclaw and oak.

Chains.	S. 89" 49' E., on a random line, bet. secs. 16 and 21.
110.00	Set temp. 1/4 sec. cor.
79.94	The cor. of secs. 15, 16, 21 and 22.
	Thence
	N. 89° 49' W., on true line, bet. secs. 16 and 21
	Over mountainous land, through scattering timber and undergrowth; desc. 215 ft. over a W. slope.
8.05	Ravine, course NW.; asc. 137 ft. over a NE. slope.
20.45	Point of a spur, slopes N.; desc. 339 ft. over a broken W. slope.
20.94	Trail in a bend, bears SE. and SW.
25.22	Recross trail, bears N. 20° W. and S. 20° E.
39 <b>.</b> 97	Set an iron post, 3 ft. long, 1 in. dism., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$ \frac{\frac{1}{4} \cdot \frac{\text{S } 16}{\text{S } 21}}{\text{1941}} $ from which
	A juniper, 5 ins. diam., bears N. $57\frac{1}{2}$ E., 72 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	A juniper, 6 ins. dist., mkd. $\frac{1}{4}$ S 21 B T.
	Desc. 145 ft. over a rolling SW. slope.
56.95	Graded road, bears N. 45° W. to Cordes and S. 23° E., to Phoenix.
58.60	A fork of Holmes, Creek, very small stream of water, course N. 10° W.;.asc. 21 ft. over a N. slope.
64.15	Point of spur, slopes N. 10° W.; desc. 28 ft. over a rolling W. slope.
69.05	Road, bears NE. to Cordes-Phoenix road and SW. to Bloody Basin mines.
76.95	Holmes Creek, 30 lks. wide, course N. 45° E.; asc. 21 ft. over a SE. slope.
79.94	The cor. of secs. 16, 17, 20 and 21.
	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, catclaw, oak and mountain mahogany.
	N. 0° 02' W., bet. secs. 16 and 17.
•	Over mountainous land, through scattering timber and undergrowth; asc. 14 ft. over a SE. slope.
4.00	Spur, slopes N. 70° E.; desc. 29 ft. over a NE. slope.

<del>1—673 b</del> 38

Subdivision of T. 9 N., R. 5 E.

_		
	Chains.	Ravine, course N. 70° E.; asc. 23 ft. over a SW. slope.
	14.40	Spur, slopes N. 70° E.; desc. lil ft.over a broken E. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 4 sec. cor., with brass cap mkd.
		<u>1</u> 4
		s 17 s 16
	, .	1941 from which
	r	A juniper, 8 ins. diam., bears N. $82\frac{1}{5}$ ° E., 205 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
		A juniper, 4 ins. diam., bears S. $62\frac{3}{4}$ W., 26 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.
		Desc. 35 ft. over a broken E. slope.
	46.30	Graded road, bears S. 26° E. to Phoenix and N. 20° W. to Cordes.
	52.20	Same road, bears NE. and SW.
	53•35	Ravine, course NE.; asc. 58 ft. over a SE. slope.
	58.80	Spur, slopes E.; desc. 124 ft. over a NE. slope.
	62.45	Same road, bears N. 10° W. and S. 20° E.
	69:10	Creek, in bottom of Roundtree Canyon, running water 2 lks. wide, 4 ins. deep, course N. 10° W.; asc. 71 ft. over a SW. slope.
	73.80	Spur, slopes W.; desc. 59 ft. over a N. slope.
	77.20	Recross Creek, course NE.; asc. 27 ft. over a S. slope.
	79.50	Recross road, bears NE. and SW.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.
		- T 9 N R 5 E S 8 S 9
		S 17 S 16 19/41 from which
		A juniper, 5 ins. diam., bears N. 75 E., 68 lks. dist., mkd. T 9 N R 5 E S 9 B T.
		A juniper, 8 ins. diam., bears S. 48° E., 141 lks. dist., mkd. T 9 N R 5 E S 16 B T.
		A juniper, 6 ins. diam., bears S. 30美 W., 132 lks. dist., mkd. T 9 N R 5 E S 17 B T.
	·	A juniper, 8 ins. diam., beers N. 54° W., 82 lks. dist., mkd. T 9 N R 5 E S 8 B T.
	• /	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak, catclaw and mountain

BOOK 4269

	Chains.	S. 89° 49' E., on a random line, bet. secs. 9 and 16.
	40.00	Set. temp. 1/4 sec. cor.
	80.00	A point 4 lks. S. of the cor. of secs. 9, 10, 15 and 16.
		Thence
		N. 89° 51' W., on true line, bet. secs. 9 and 16.
		Over mountainous land, through scattering timber and undergrowth; desc. 287 ft. along the top of a spur, slopes W.
	25.70	Leave top of a spur, slopes S. 75° W.; desc. 199 ft. over a NW. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	:	S 9.
		s 16
	•	1941 from which
	•	A juniper, 8 ins. dism., bears N. 2° E., 91 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
-		A juniper, 12 ins. diam., bears S. 75° W., 58 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
		Desc. 147 ft. over a NW. slope.
	49.40	Ravine, course SW.; asc. 51 ft. over a SE. slope.
	54.80	Top of a spur, slopes W. from NE.; desc. 81 ft. along top of spur.
	-68.80	Leave top of spur, slopes SW. from E.; continue descent 177 ft. over a steep rocky W. slope.
	75•90	Creek, in bottom of Round tree Canyon, running water, 3 lks. wide, 4 ins. deep, course NE.; asc. 51 ft. over a S. slope.
	78.30	Road, bears NE. to Cordes and S. 80° W. to Phoenix.
	80.00	The cor. of secs. 8, 9, 16 and 17.
		Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, catclaw, oak and mountain mahogany.
	,	N. 0° 02' W., bet. secs. 8 and 9.
		Over mountainous land, through scattering timber and undergrowth; asc. 55 ft. over a S. slope.
	3.90	Spur, slopes E.; desc. 106 ft. over a NE. slope.
	7.70	Ravine, course E.for 2 chs. to junction with Round tree Creek; asc. 140 ft. over a SW. slope!
	15.80	Spur, slopes E.; desc. 89 ft. over a NE. slope.
	23.40	Ravine, running water, la lks. wide, 3 ins. deep, course S. 70° E.; asc. 361 ft. over a SW. slope.

Subdivision of T. 9 N., R. 5 E.

Chains.	Fence, bears SE. and NW.
38.20	Spur, slopes SE.; desc. gradually over a NE. slope.
1,0.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for 4 sec. cor., with brass cap mkd.
	$\frac{1}{4}$
•	s 8 s 9
1	1941 from which
	A juniper, 8 ins. diam., bears N. $45\frac{1}{4}^{\circ}$ E., 31 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
	A juniper 7 ins. diam., bears N. $71\frac{3}{4}$ W., 83 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.
	Desc. 305 ft. over a NE. slope.
50.30	Ravine, course SE.; asc. 200 ft. over a SW. slope.
59.00	Spur, slopes SE.; desc. 137 ft. over a NE. slope.
64.60	Ravine, course SE.; asc. 554 ft. over a SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 4, 5, 18 and 19, with brass cap mkd.
	T. 9 N R 5 E . S 5 S 4
,	S 8 S 9 . 1941 from which
	A juniper, 12 ins. diam., bears N. 544 E., 88 lks.
	dist,, mkd. T 9 N R 5 E S 4 B T.
	A juniper, 6 ins. diam., bears S. 47 E., 152 lks. dist., mkd. B T.
- /	A juniper, 7 ins. diam., bears S. 314 W., 168 lks. dist., mkd. T 9 N R 5 E S 8 B T.
	A juniper, 5 ins. diam., bears N. 63 W., 116 lks. dist., mkd. T 9 N R 5 E S 5 B T.
į r	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
	S. 89° 51' E., on a random line, bet. secs. 4 and 9.
40.00	Set temp. 4 sec. cor.
80.06	A point 16 lks. N. of the cor. of secs. 3, 4, 9 and 10.
	Thence
SST	N. 89° 山 W., on true line, bet. secs. 4 and 9.

Over mountainous land, through scattering timber and undergrowth; desc. 108 ft. over a W. slope.

	Chains. 3.65	Deep ravine, course N. 10 W.; asc. 4 ft. over a NE. slope.
	5•75	Point of a spur, slopes N.; desc. 20 ft. over a NW. slope.
1	6.40	Ravine, course N. 20° E. for 2 chs. dist. then N.; asc. 59 ft. over a NE. slope.
	9.15	Spur, slopes N. 15° E.; desc. 75 ft. over a W. slope.
	11.35.	Ravine, course N. 10° E.; asc. 8 ft. over a broken N. slope.
	17.45	Head of a draw, drains N.; continue ascent 28 ft. over a N. slope.
	21.50	Spur, slopes N.; desc. 94 ft. over a steep W. slope.
	24.15	Ravine, course N. 15° W.; continue descent 34 ft. over a W. slope.
	27.80	Creek, in bottom of Round tree Canyon, running water, 15 lks. wide, 3 ins. deep, course NE.; asc. 154 ft. over an E. slope.
	35.00	Graded road, bears NE. to Cordes and S. to Phoenix.
	40.03	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
		$\frac{1}{4} \frac{s}{s} \frac{4}{s} \frac{19!}{19!}$
		from which
		A juniper, 8 ins. diam., bears N. $6\frac{1}{2}$ E., 57 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.
		A juniper, 6 ins. diam., bears S. 30° W., 47 lks. dist., mkd. 4 S. 9 B T.
	1	Asc. 275 ft. over a NE. slope.
	47.45	spur, slopes SE.; desc. 53 ft. over a SW. slope.
	53.20	Ravine, course S. 30° E.; asc. 526 ft. over a NE. slope.
	78.00	Spur, slopes S. 20° E.; desc. 2 ft. over a SW. slope.
	80.06	The cor. of secs. 4, 5, 8 and 9.
		Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
		N. 0° 03' W., on a random line, bet. secs. 4 and 5.
	40.00	Set temp. 1/4 Sec. cor.
	79•97	A point 7 lks. E. of the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group.
		Thence
	•	S. 0° 06' E., on true line, bet. secs. 4 and 5.

. Subdivision of T. 9 N., R. 5 E.

. !	Chains.	Over mountainous land, through scattering timber and undergrowth; asc. 91 ft. over a broken E. slope.
	11.15	Spur, slopes NE; desc. 254 ft. over a steep SE. slope.
	25.15	Wash, in the bottom of a deep canyon, running water, 12 lks. wide, 4 ins. deep, course N. 60° E.; asc. 243 ft. over a NW. slope.
	31.30	Spur, slopes NE.; desc. 108 ft. over a SE. slope.
	37-55	Ravine, course NE.; asc. 47 ft. over a NW. slope.
	39•97	Set an iron post, 3 ft. long, 1 in. diem., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	•	s 5 s 4
	,	of stone, 3 ft. base, 2 ft. high, W. of cor.
	*	Asc. 11 ft. over a NW. slope.
	1,0.95	Spur, slopes N. 20° E., 4 chs. to toe; desc. 24 ft. over a SE. slope.
	43.65	Ravine, course N. 20° E.; asc. 505 ft. over a steep NW. slope.
	58.05	Spur, slopes E.; desc. 29 ft. over an E. slope.
	75.00	Spur, slopes S. 20° E.; desc. 98 ft. over a SW. slope.
	79.97	The cor. of secs. 4, 5, 8 and 9.
	•	Land, mountainous. Soil, 2nd and 3rd rates, rocky. Timber, juniper; undergrowth, oak and catclaw.
		From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group,
		N. 0° 03' W., bet. secs. 31 and 32.
		Over mountainous land, through scattering timber and undergrowth; asc. 11 ft. over a gentle E. slope.
	20.00	Spur, slopes NE.; asc. 28 ft. over a brokem W. slope.
	1,0.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	٩	$\frac{1}{4}$
		s 31 s 32
	•	1941 From which

A juniper, 3 ins diam., bears N.  $49\frac{1}{4}^{\circ}$  E., 58 lks. dist., mkd. B T.

A juniper, 4 ins. diam., bears N.  $44^{\circ}$  W., 81 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

from which

	Chains.	Desc. 110 ft. over a broken W. slope.
	57.00	A bend în a wash, 30 lks. wide, course N. 30° W. from S. 30° W.; desc. & ft. over a W. slope.
	59.90	Right bank of same wash, bears NE. and SW.; desc. 13 ft. over dry bed of the wash.
<b>⇒</b> .	63.30	Leave wash, left bank, bears NE. and SW.; asc. 8 ft. over an E. slope.
	.67.20	Mouth of a ravine, course SE.; asc. 29 ft. over a SW. slope.
	72.00	Spur, slopes SE.; desc. 24 ft. over a NE. slope.
:	72.87	Ash Spring, bears E., 317 lks. dist. From this spring, a cement water trough, 8 x \( \alpha \) x 1\( \frac{1}{2} \) ft. high, bears N. 60° E., 50 lks. dist. and another cement water trough, 7 x \( \alpha \) x 1 ft. high, bears N. 60° E., 110 lks. dist.
	75.80	Ravine, course SE.; asc. 52 ft. over a SW. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diem., 28 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.
	•	T .9 N R .5 E S 30 S 29
		s 31 s 32
		from which
		A juniper, 6 ins. diam., bears N. 412° E., 136 lks. dist., mkd. T 9 N R 5 E S 29 B T.
		A juniper, 8 ins. diam., bears S. 73° E., 232 lks. dist., mkd. T 9 N R 5 E S 32 B T.
		A juniper, 4 ins. diam., bears S. $57\frac{1}{4}^{\circ}$ W., 133 lks. dist., mkd. T 9 N R 5 E S 31 B.T.
		A juniper, 24 ins. diem., bears N. $17\frac{1}{2}^{\circ}$ W., 34 lks. dist., mkd. T 9 N R 5 E S 30 B T.
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, catclaw and oak.
		East, on a random line, bet. secs. 29 and 32.
	100000	Set temp. ½ sec. cor.
	80.00	The cor. of secs. 28, 29, 32 and 33.
		Thence
	•	West, on true line, bet. secs. 29 and 32.
•		Over mountainous land, through scattering timber and undergrowth; asc. 300 ft. over a NE. slope.
<u>-</u>	0.50	Graded road, bears NW. to Cordes and SE. to Phoenix.
•	15.14	From this point, the SW. cor. of a building in the SW. cor. of a group of buildings at a CCC camp, bears N. 33° 26' E.; the SE. cor. of the SE. cabin, bears N. 37° 25' E.; the N. gable of the northernmost

. Subdivision of T. 9 N., R. 5 E.

	Chains.	cabin, bears N. 27° 30' E.; the S. end of the headwall on the E. end of the cattle guard, bears N. 39° 35' E.
	16.50	Top of steep ascent, bears NW. and SE., enter Lockwood Mesa.
	19.00	Spur, slopes NE.; desc. 346 ft. over a steep rocky NW. slope.
	32.15	Ash Springs Creek, 40 lks. wide, course NE., running water, 1 lks. wide, 4 ins. deep. A concrete dam, 20 ft. wide, 6 ft. high, is located 2 chs. below this crossing; asc. 201 ft. over a NE. slope.
	110.00	Set an iron post, 3 ft. long, 1 in. diam., $2l_1$ ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
τ <b>*</b>		$\begin{array}{c} \frac{1}{4} & \frac{329}{832} \\ 1941 & \end{array}$
	e	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. This \( \frac{1}{4} \) sec. cor. is located on top of a spur, slopes SE.; desc. 21 ft. over a SW. slope.
	46.25	Ravine, course SE.; asc. 212 ft. over a NE. slope.
	64.00	Spur, slopes SE.; desc. 59 ft. over a S. slope.
	73.80	Spur, slopes S.; desc. 112 ft. over a SW. slope.
	80.00	The cor. of secs. 29, 30, 31 and 32.
	•	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, and catclaw.
	<b>3</b>	West, on a random line, bet. secs. 30 and 31.
	40.00	Set temp. 4 sec. cor.
	79.95	A point 9 lks. S. of the cor. of secs. 25, 30, 31 and 36, on the W.bdy. of the Tp., described in the field notes of the boundaries of T. 9 N., R. 4 E., surveyed under this Group.
		Thence
		S. 89° 56' E., on true line, bet. secs. 30 and 31.
r		Over mountainous land, through scrttering timber and undergrowth; desc. 27 ft. over a broken NE. slope.
	12.50	Spur, slopes N.; desc. 258 ft. over an E. slope.
	20.50	Ravine, course NE.; asc. 24 ft. over a NW. slope.
	28.80	Spur, slopes NE.; desc. 186 ft. over an E. slope.
	39 <b>•</b> 95	Set an iron post, 3 ft. long, 1 in. diem., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	•	S 30 S 31 1941
		from which

	Chains.	
	i vi •	A juniper, 10 ins. diam., bears N. $83\frac{1}{4}^{\circ}$ E., $1\mu$ lks. dist., mkd. $\frac{1}{4}$ S 30 B T.
		A juniper, $2\mu$ ins. diam., bears S. $6\frac{1}{2}^{\circ}$ W., 87 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.
	L** 125	Desc. 67 ft. over.an E. slope.
	42.25	Ravine, course NE.; asc. 9 ft. over a W. slope.
	43.25	Spur, slopes N. 20° E.; desc. 301 ft. over a Broken E. slope.
	59.85	Wire fence, bears N. $67\frac{1}{2}^{\circ}$ E. and S. $67\frac{1}{2}^{\circ}$ W.
	78.30	Ravine, course SE.; asc. 29 ft. over a SW. slope.
	79•95	The cor. of secs. 29, 30, 31 and 32.
	•	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		N. 0° 03' W., bet. secs. 29 and 30.
		Over mountainous land, through scattering timber and undergrowth; desc. 8 ft. over a W. slope.
	1.50	Ravine, course W.; asc. 51 ft. over a W. slope.
	7.00	Spur, slopes S. 80° W.; descend gradually over a broken W. slope.
	9.60	Wire fence, bears S. 492° W. and N. 492° E.
	28.55	Spur, slopes W.; desc. 144 ft. over a N. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
	•	4
	ยยา	. s 30 s 29
		1911 from which
		A juniper, 10 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ E., 39 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.
	, . (	A mountain mahogany, 3 ins. diam., bears S. 1930 W. 60 lks. dist., mkd. 4 S 30 B T.
		Desc. 102 ft. over a N. slope.
	771.00	Wash, in the bottom of a canyon, course N. 20° E. for 2 chs. them E.; asc. 23 ft. over a SE. slope.
	146.140	Point of a spur, slopes E.; desc. 27 ft. over a NE. slope.
	47.80	Ravine, course SE. for 1.50 chs. to the junction with a wash in a canyon, course E.; asc. 346 ft. over a S. slope.
	62.80	Trail, bears E. to Cavness Ranch and W. to 6 Bar Ranch.
,	64.60	Ridge and main divide between Lime Creek and Roundtree Canyon, bears E. and W.; desc. 123 ft. over a W. slope.
		l l

-678 b

46

Subdivision of T. 9 N., R. 5 E.

Chains. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. ir the ground, for cor. of secs. 19, 20, 29 and 30, with .80.00 brass cap mkd. T 9 N R 5 E S 19 S 20 30 S 29 19/1 from which A juniper, 3 ins. dism., bears N.  $51\frac{1}{4}^{\circ}$ . E., 86 lks. dist., mkd. B T. A juniper, 6 ins. diam., bears S.  $18\frac{1}{4}^{\circ}$  E., 85 lks. dist., mkd. T. 9 N R 5 E S 29 B T. A juniper, 3 ins. diam., bears S.  $71\frac{1}{4}^{\circ}$  W., 18 lks. dist., mkd. T 9 N R 5 E S 30 B T. A juniper, 9 ins. diam., bears N. 40° W., 83 lks. dist., mkd. T 9 N R 5 E S 19 B T. Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw. East, on a random line, bet. secs. 20 and 29. 10.00 Set temp.  $\frac{1}{4}$  sec. cor. 80.00 A point 7 lks. S. of the cor. of secs. 20, 21, 28 and 29. Thence S. 89° 57' W., on true line, bet. secs. 20 and 29. Over mountainous land, through scattering timber and undergrowth; desc. 100 ft. over a W. slope. 6.30 Ravine, course SE.; asc. 207 ft. over an E. slope. 17.30 Head of a spur, slopes SE.; descend slightly along the top of the divide between Lime Creek and Roundtree Canyon. 29.50 Leave divide, bears E. and S. 80° W. Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$ 40.00 sec. cor., with brass cap mkd. S 20 S 29 1941 from which A juniper,  $\mu$  ins. diam., bears N.  $55\frac{1}{4}^{\circ}$  W., 98 lks. dist., mkd.  $\frac{1}{4}$  S 20 B T. A juniper, 6 ins. diam., bears S.  $37\frac{1}{2}^{\circ}$  W., 194 lks.

U. S. GOVERNMENT PRINTING OFFICE 6-8155

Fecross top of divide, bears W. and S. 80° E.

dist., mkd. \(\frac{1}{4}\) S 29 B T.

Trail, bears S. 80° W. and S. 85° E.

57.00

59.80

	Chains, 68.00	Leave top of same divide, bears SW. and E.; desc. 203 ft. over a W. slope.
	80.00	The cor. of secs. 19, 20, 29 and 30.
	•	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		N. 89° 56' W., on a random line, bet. secs. 19 and 30.
	l.0.00	Set temp. \(\frac{1}{4}\) sec. cor.
	79.94	A point 7 lks. S. of the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 4 E., surveyed under this Group.
		Thence
		S. 89° 53' E., on true line, bet. secs. 19 and 30.
	•	Over mountainous land, through scattering timber and undergrowth; desc. 186 ft. over a NE. slope.
	8.45	Ravine, course SE.; asc. slightly over a broken SW. slope.
	35•95	Ridge and main divide between Lime Creek and Roundtree Canyon, bears NW. and SE.
•	39.94	Set an iron post, 3 ft. long, 1 in dism., 10 ins. in the ground , to bedrock and in a mound of stone to top for \(\frac{1}{4}\) sec. cor., with brass cap mkd.
	T	\$ 30 1941 from which
		A juniper, 3 ins. diam., bears N. 6山東 W., 山山 lks. dist., mkd. B T.
		A juniper, 5 ins. diam., bears S. $61\frac{1}{2}$ ° W., 59 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.
	i.	Desc. 191 ft. over a broken E. slope.
:	53.65	Trail, bears NW. to 6 Bar Ranch and SE. to Cavness Ranch.
	55.50	The NE. cor. of a net wire corral, bears S., 125 lks. dist.
	65.95	Ravine, course SE.; asc. 28 ft. over a SW. slope.
	48.25	Point of a spur, slopes, NW.; desc. 79 ft. over an E. slope.
	73.110	Ravine, course ME.; asc. 55 ft. over a W. slope.
	79.9/1	The cor. of secs. 19, 20, 29 and 30.
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.

**4—673 b** Ц8

· Subdivision of T. 9 N., R. 5 E.

,	Chains.	N. 0°.03' W., bet. secs. 19 and 20.
		Over mountainous.land, through scattering timber and undergrowth; desc. 87 ft. over a W. slope.
	7.00	Ravine, course N. 70° E.; asc. 256 ft. over a S. slope.
	25.30	Spur, slopes NE.; desc. 336 ft. over a NW. slope.
	29.85	Smoke stack of boiler at stamp mill, bears N. 27° 40' W.; the Sh. cor. of framework at stamp mill, bears N. 28° 15' W.
	1.0.00	Set an iron post, 3 ft. long, 1 in. dism., 28 ins. in the ground, for 4 sec. cor., with brass cap mkd.
		$\begin{array}{c c} & \frac{1}{4} \\ \hline S & 20 \end{array}$
		$1\dot{9}l_{4}1$ from which
	•	A juniper, 4 ins. diam., bears S. 312° E., 93 lks. dist., mkd. B T.
		A juniper, 10 ins. diam., bears S. $l_45^{\circ}$ W., 11 lks, dist., mkd. $\frac{1}{4}$ S 19 B T.
	ಂಕಿಡ ್ಷ	Desc. 58 ft. over a NW, slope.
	43.00	Road, bears SE. and W.
	43.40	Wash, in the bottom of Holmes Canyon, running water, 4 lks. wide, 2 ins. deep, course SE. for 4 chs. then NE. Asc. 510 ft. over a broken SW. slope.
	52.79	Smoke stack of boiler at stamp mill, bears N. 81° 45' W.; the SE. cor. of framework of stamp mill, bears N. 82° 12' W.; mouth of a tunnel, bears S. 69° 35' W.
	64.30	The N. gable of a cabin, bears S. 87° 24' W.
	68.90	Wire fence, hears ME. and SW.
	72.45	Favine, course SW.; continue ascent over a broken W. slope.
	77.20	Trail, bears E. and W.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 25 ins. in the ground, to bedrock and in a mound of stone to top, for cor. of secs. 17, 18, 19 and 20, with bress cap mkd.
a		T 9 N R 5 E S 18 S 17 S 19 S 20 19/11 from which
		A juniper, 8 ins. dism., bears N. $82\frac{1}{4}$ ° E., 102 lks. dist., mkd. T 9 N R 5 E S 17 B T.
-		

A juniper, lh ins. diam., bears S. 60° E., 110 lks. dist., mkd T 9 N R 5 E S 20 B T.

A juniper, 8 ins. diam., bears, S. 33° W., 95 lks. dist., mkd. T 9 N R 5 E S 19 B T.

<del></del> -		
	Chains.	A juniper, 12 ins. dism., bears.N. 78° W., 120 lks. dist., mkd. T 9 N R 5 E S 18 B T.
	19 <b>8</b> ( )	Land, mountainous. Soil, 3rd and lith rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		N. 89°.57' E., on a random line, bet. secs. 17 and 20.
	<u>l.</u> 0.00	
	80.08	Set temp. 4 sec. cor.  The cor. of secs. 16, 17, 20 and 21.
	00.00	er .
	:	Thence
		S. 89° 57' W., on true line, het. secs. 17 and 20.
		Over mountainous land, through scattering timber and undergrowth; asc. 306 ft. over a SE. slope.
	19.10	Spur, slopes S.; desc. 69 ft. over a W. slope.
	24.65	Head of a ravine, course S.; asc. 209 ft. over an E. slope.
	36.10	Spur, slopes N. 60° E.; desc. 41 ft. over a NW. slope.
	lio.oli.	Set an iron post, 3 ft. long, 1 in diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
		s 17
	•	\$ 20
		1911 from which
		A juniper, 10 ins. diam., bears N. 5½° E., 52 lks. dist., mkd. 4 S 17 B T.
		A juniper, 6 ins. diam., bears S. $45\frac{1}{4}$ ° W., $114$ lks. dist., mkd. $\frac{1}{4}$ S 20 B T.
	•	Desc. 188 ft. over a NW. slope.
	57.90	Ravine, course NE.; asc. 334 ft. over an E. slope.
	68.08	Wire fence, bears N. 30° E. and S. 50° W.
	73.08	Spur, slopes S.; mouth of tunnel, bears S. 37° W.; desc. 50 ft. over a W. slope.
	80.08	The cor. of secs. 17, 18, 19 and 20.
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany, and catclaw.
		N. 89° 53' W., on a random line, bet. secs. 18 and 19.
	l10.00	Set temp. 4 sec. cor.
	79.70	A point 28 lks. N. of the cor. of secs.13, 18, 19 and 24, on the W. bdy. of Tp., described in the field notes of the bdrs. of T.9 N., R.4 E., surveyed under this group.
	,	Thence

- Subdivision of T. 9 N., R. 5 E.

Chains.	N. 89° 55' E., on true line, bet. secs.18 and 19.
	Over mountainous land, through scattering timber amd undergrowth; Asc. 177 ft. over a W. slope.
8.50	Ridge and main divide bet. Squaw Creek and Roundtree Canyon, bears N. and S.; desc. 937 ft. over a steep, broken, rocky E. slope.
39.70	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a stone mkd. with a cross (X) deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	s 18
,	S 18 S 19 19/11
	Desc. 54 ft.over a broken E. slope.
42.20	Ravine, course NE.; asc. 29 ft. over a NW. slope.
46.79	Trail, bears NE. and SW.
1,8.20	Spur, slopes N. 20° E.; desc. 310 ft. over an E. slope.
66.30	Wash, in bottom of Holmes Canyon, running water, 4 lks. wide, 2 ins. deep, course S. 20° E.; asc. 337 ft. over a W. slope.
66.70	Trail, bears N. 20° W. and S.
79.70	The cor. of secs. 17, 18, 19 and 20.
	Land, mountainous. Soil, 3rd and 1th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
•	N. 0° 03' W., bet. secs. 17 and 18.
	Over mountainous land, through scattering timber and undergrowth; asc. 281 ft. over a broken W. slope.
22.30	The N. gable of the Bloody Basin Mine cabin, bears S. 16° W.
22.50	Spur, slopes W.; desc. 297 ft. over a N. slope.
40.00	The true point for 4 sec. cor. falls in a ravine, course NW., an unsuitable place to set a permanent cor.
h1.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness \(\frac{1}{4}\) sec. cor., with brass cap mkd.
	4
	s 18 s 17
	W C 1941 from which
	A juniper, 4 ins. diam., bears N. 20½° E., 24 lks. dist., mkd. W C ½ S 17 B T.

Chains.	Asc. 399 ft. over a SW. slope.
63.00	Spur, slopes SE. for approx. 15 chs., then S.; asc. over an E. slope.
67.74	Wire fence, bears S. 30° E. and N. 30° W.
72.60	Spur, slopes E.; desc. 174 ft. over a NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.
	T 9 N B 5 E 8
	s 18 s 17 1941
i -	from which
<b>^</b> •	A juniper, 3 ins. diam., bears N. 24 ° E., 65 lks. dist., mkd. PT.
-	A juniper, 3 ins. diam., bears S. $41\frac{1}{4}^{\circ}$ E., 59 lks. dist., mkd. B T.
	A mountain mehogany, 3 ins. diam., bears S. 81° W., 23 lks. dist., mkd. B T.
	A juniper, 5 ins. diam., bears N. 77° W., 23 lks. dist., mkd. T 9 N R 5 E S 7 B T.
7	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclew.
	N. 89° 57' E., on a random line, bet, secs. 8 and 17.
1,0.00	Set temp. 4 sec. cor.
80.06	A point 7 lks. N. of the cor. of secs. 8, 9, 16 and 17.
	Thence
	West, on true line, bet. secs. 8 and 17.
	Over mountainous land, through scattering timber and undergrowth; asc. 178 ft. over a S. slope.
11.80	Trail, bears NW. and S.
14.70	Spur, slopes N. 70° E.; asc. 9 ft. over a N. slope.
14.94	Wire fence, bears NE. and SW.
19.50	Short spur, slopes N.; desc. 51 ft. over a NW. slope.
25.50	Ravine, course N. 70° E.; asc. 182 ft. over a SE. slope.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for \( \frac{1}{4} \) sec. cor., with brass cap mkd.
	<u>s</u> 8
	\$ 17 1941
	from which
ļ	

**4—673 b** 52

Subdivision of T. 9 N., R. 5 E.

Chains.	A juniper, 10 ins. diam., bears N. $3\frac{1}{4}^{\circ}$ W., 84 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.
•	A juniper, 5 ins. diam., bears S. $544^{\circ}$ W., 63 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.
	Asc. 362 ft. over a SE. slope.
67.85	Ravine, course SE., continue ascent 361 ft. over an E. slope.
80.06	The cor. of secs. 7, 8, 17 and 18.
	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
	S. 89° 55' W., on a random line, bet. secs. 7 and 18.
1,0.00	Set temp. $\frac{1}{4}$ sec. cor.
79.69	A point 9 lks. S. of the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 4 E., surveyed under this Group.
	Thence
•	N. 89° 59' E., on true line, bet. secs. 7 and 18.
	Over mountainous land, through scattering timber and undergrowth; desc. 545 ft. over an E. slope.
32.40	Spur, slopes SE.; continue descent over an E. slope.
38.00	Wash, 50 lks. wide, in bottom of Holmes Canyon, course S.; asc. 36 ft. over a steep, rocky W. slope.
39.69	Set an iron post, 3 ft. long, l·in. diem., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{s}{s}$ $\frac{7}{18}$
	s 18
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	Asc. 163 ft. over a W. slope.
48.50	Spur, slopes SW.; desc. 115 ft. over a SE. slope.
53.15	Ravine, course SW.; asc. 495 ft. over a W. slope.
67.49	Trail, bears S. 10° E. and N.
72.70	Spur, slopes S.; desc. 264 ft. over an E. slope.
72.94	Wire fence, bears NW. and SE.
79.69	The cor. of secs. 7, 8, 17 and 18.
	Land. mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.

# Subdivision of T. 9 N., R. 5 E.

ECOK 4269

	Chains.	N. 0° 03! W., bet. secs. 7 and 8.
		Over mountainous land, through scattering timber and undergrowth; asc. 209 ft. over a broken E. slope.
	19.60	Long spur, slopes SW. for approx. 5 chs. then S.; desc. 240 ft. over a NW. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 4 sec. cor., with brass cap mkd.
		$\frac{1}{4}$
		s 7 s.8
		19/11 from which
	•	A juniper, 4 ins. diam., bears S. 59° E., 27 lks. dist., mkd. 4 S 8 B T.
		A juniper, 4 ins. diam., bears N. 374° W., 11 lks. dist., mkd. 3 7 B T.
		Desc. 36 ft. over a NW. slope.
	43.15	Head of a ravine, course W.; asc. 219 ft. over a SW. slope.
	43.30	Wire fende, bears E. and W.
	64.10	Short spur, slopes W.; desc. 23 ft. over a W. slope.
	71.10	Head of a ravine, course S. 30° W.; asc. 14 ft. over a S. slope.
`	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 25 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 5, 6, 7 and 8, with brass cap mkd.
		T 9 N R 5.E S 6 S 5
		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
•		A juniper, 3 ins. diam., bears N. 454° E., 98 lks. dist., mkd. B T.
	• !	A. juniper, 3. ins. diam., bears S. $77\frac{1}{2}^{\circ}$ E., 111 lks. dist., mkd. B T.
	r ·	A juniper, 3 ins. diam., bears S. 412° W., 49 lks. dist., mkd. B T.
		A juniper, 4 ins. diam., bears N. 86° W., 20 lks. dist., mkd. T 9 N R 5 E S 6 B T.
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		East, on a random line, bet. secs, 5 and 8.
	1,0.00	Set temp. 4 sec. cor.

Subdivision of T. 9 N., R. 5 E.

_		
	Chains. 80.04	A point 21 lks. S. of the cor. of secs. 4, 5, 8 and 9.
		Thence
		S. 89° 51' W., on true line, bet. secs. 5 and 8.
		Over mountainous land, through scattering timber and undergrowth; desc. 224 ft. over a SW. slope.
	14.00	Ravine, course SE.; asc. 280 ft. over a NE. slope.
	31.00	Spur, slopes SE.; desc. 174 ft. over a SW. slope.
	38.00	Ravine, course S. 20° E.; asc. 21 ft. over an E. slope.
	39.90	Trail, bears N. and S.
	l10.02	Set an iron post, 3 ft. long, l in. diam., 27 ins. in the ground, for \(\frac{1}{4}\) sec. cor., with brass cap mkd.
		S 5
	•	S 5 S 8
		1941 . from which
	•	A juniper, 10 ins, diam., bears N. 81° W. 68 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.
		A juniper, 10 ins. diam., bears S. 42° E., 88 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.
	• 1	Asc. 579 ft. over a SE. slope.
	53.00	Line runs over large Indian ruins.
	71.75	Top of a perpendicular cliff, 50 ft. high, facing E., bears S. and N. 15° E.; asc. 149 ft. over a broken E. slope.
	76.25	Spur, slopes S.; desc. 30 ft. over a S. slope.
	80.04	The cor. of secs. 5, 6, 7 and 8,
		Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		S. 89° 59' W., on a random line, bet. secs. 6 and 7.
	140.00	Set temp. \(\frac{1}{4}\) sec. cor.
	79•70	A point 12 lks. S. of the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., described in the field notes of the bdrs. of T. 9 N., R. 4 E., surveyed under this
		Group.
		Thence
	u	S. 89° 56' E., on true line, bet. secs. 6 and 7.
		Over mountainous land, through scattering timber and undergrowth; asc. 61 ft. over a broken S. slope.
	35.00	Spur, slopes S. 10° E.; desc. 131 ft. over an E. slope.
	39.70	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for \( \frac{1}{4} \) sec. cor., with brass cap mkd.

	Chains.	s 6
	•	S 7 1941 from which
		A juniper, 6 ins. diam., bears N. 13° W., 96 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.
•	0.	A juniper, 18 ins. diam., bears S. 40° W., 83 lks.
		, dist., mkd. 4 S 7 B T.
		Desc. 95 ft. over an E. slope.
	Mr.00	Wash, 50 lks. wide, in bottom of Holmes Canyon, course S.; asc. 549 ft. over a NW. slope.
-	45.70	Trail, bears N. and S.
	73.40	Spur, slopes S. 30° W.; desc. 7 ft. over a S. slope.
	79.70	The cor. of secs. 5, 6, 7 and 8.
	ļ r	Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.
		N. 0° 07' W., on a random line, bet. secs. 5 and 6.
	110.00	Set temp. $\frac{1}{4}$ sec. cor.
	80.23	A point & lks. E. of the cor. of sees. 5, 6, 31 and 32, on the N. bdy. of the Tp., described in the field notes of the N. bdy. of T. 9 N., R. 5 E., surveyed under this Group.
7	. 4	Thence
		S. 0° 09' E., on true line, bet. secs. 5 and 6.
- <del>-</del>		Over mountainous land, through scattering timber and undergrowth; desc. 2 ft. over a SW. slope.
	2,15	Ravine, course W.; asc. 130 ft. over a NW. slope.
-	6.25	Spur, slopes W.; desc. 35 ft. over a S. slope.
	13.35	Trail, bears ME, to Mud Spring and SW. to 6 Bar Ranch.
	13.93	Center of a cement and rock dam, below a spring in the bottom of a ravine, course NE., bears S. $49\frac{1}{4}^{\circ}$ W., 10.50 chs. dist.; asc. 319 ft. over a NE. slope.
	36 <b>.</b> 90°	Ridge and main divide between Holmes Canyon and Mud Springs Creek, bears N. 60° W., and S. 60° E.; desc. 56 ft. over a S. slope.
	_Lo:23	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 4 sec. cor., with brass cap mkd.
·		<u> </u>
	;	s 6 s 5
	er (	1941 from which
		l

Chains

A juniper, Lins. diam., bears S. 73° E., 69 lks. dist., mkd. & S 5 B T.

A juniper, 8 ins. diam., bears S. 26° W., 85 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

Desc. 83 ft. over a S. slope.

Ravine, course S. 70° W.; asc. 448 ft. over a NW. slope.

74.80 Spur, slopes SW.; desc. 22 ft. over a S. slope,

The cor. of secs. 5, 6, 7 and 8. 80.23

> Land, mountainous. Soil, 3rd and 4th rates, rocky. Timber, juniper; undergrowth, oak, mountain mahogany and catclaw.

#### FINAL TESTS OF TRANSITS.

The final tests of Buff solar transit No. 16730 and Gurley solar transit No. 371537, may be found in the field notes of the bdrs. of T. 9 N., R. 5 E., surveyed under this Group.

#### GENERAL DESCRIPTION.

The elevation of T. 9 N., R. 5 E., ranges from about 2900 ft. to 5512 ft.above sea level. The lowest point of elevation being where Tangle Creek leaves the Tp. on the E. bdry. of sec. 12 and the highest point is the top of W. Cedar Mountain, in the E. central part of the Tp. East Cedar Mountain which is crossed by the E. bdy. of the Tp. has an elevation of 5475 ft above sea level and the rim of the Bloody Basin, which runs along the W. bdy. of the Tp. has an average elevation of about 5000 ft. above sea level. The drainage of the S. portion of the Tp. is furnished by Lime Creek and Long Canyon, the general direction being to the S. The N. half of the Tp. is drained by Holmes Canyon which heads in the NW. part of the Tp. and drains SE., emptying into Roundtree Canyon near the center of the Tp., thence, by Roundtree Canyon northeasterly, emptying into Tangle Creek in section 2 and leaving the TpC on the E. bdy. of sec. 12. The soil is rocky, 2nd, 3rd and 4th rates. There is a good growth of native grass over the entire township which furnishes grazing for sheep and cattle during the winter months. A stream of water flows in Roundtree Canyon and Holmes Canyon has an intermittent stream. A part of the L X Bar Ranch, H E S No. 416 is located in section 2 and the Cavness Ranch, H E.S No. 415 is located in sections 28 and 33. A C C C side camp is located in section 29. A good graded road from Phoenix to Cordes enters the Tp. on the S. bdy. of sec. 32 and leaves it on the N. bdy. of sec. 3. A trail from the Cavness Ranch to the 6 Bar Ranch leaves the Tp. on the W. bdy. of section 19 and another trail from the Bloody Basin Mine in section 19 leaves the Tp. on the N. bdy. of section 5. There is a scattering growth of juniper timber over the entire township with a medium growth on East and West Juniper Mountains. A scattered undergrowth of oak, mountain mahogany, mountain laurel and catclaw prevails over the entire township with a dense growth on most of the north slopes of the mountains, ridges and spurs. The mean magnetic declination is 15°30'E.

ECCK 4269

4-680 (Revised May 1934)

# UNITED STATES DEPARTMENT OF THE INTERIOR GENERAL LAND OFFICE

## FIELD ASSISTANTS

NAMES	CAPACITY
Lynn Ferrell	Principal Assistant
Robert M. Warren	Principal Assistant
Mike Knezevich	Chainman
Charles W. Shadle	Chainman
C. Richard Blount	Chainman
Ralph L. Lee	Flagman
Lloyd E. Hackler	Moundman
Leeland A. Terry	Moundman
John T. Tomsich	Moundman
Mike G. Angelovic	Axeman
Garland M. Garrett	Axeman
Gladwyn Gregory	Axeman

BOOK 4269

## CERTIFICATE OF SURVEYOR

We, Raymond F. Moss, Assistant Cade Sf.Engineering Aide, General Land	Stral Engineer Office , HEREBY (	and Bert E. Wakeman
pursuance of special instructions bearing date of the	13th day of	May ,1941,
received from the district cadastral engineer for Arizo	ona	with assignment
instructions dated Sept. 19, 1941, we have su	rveyed the subdiv	risional lines of
Township 9 North, Range 5 East,		·
		·
River of the Gila and Salt . Meridian, in the State o	f Arizona	, which are
represented in the foregoing field notes as having been ex	recuted by ## and under	our direction; and that said
survey has been made in strict conformity with said ins	tructions, the Manual of	f Instructions for the Survey
of the Public Lands of the United States, and in the spe	· • • • • • • • • • • • • • • • • • • •	
Phoenix, Arizona, January 31, 1942	Haymurs Assistant	Cadastral Engineer.
Phoenix, Arizona, Sept. 14, 1942.	Berl EN	akeman
		ering Aid . . Cadastral Enginee
OFFITIOATE O	General	l Land Office
CERTIFICATE O	F APPROVAL	• .
	Office of Supervisor	of Surveys,
Den	ver, <u>Colorado</u> ,	December 23, 1942.
The foregoing field notes of the survey ofthe_S	ubdivisional Lir	es of Township
9 North, Range 5 East, of the Gila a	nd Salt River Me	ridian, in the
State of Arizona, executed by Raymone	d F. Moss, Assis	stant Cadastral
Engineer and Bert E. Wakeman, Jr. Ca	dastral Engineer	, General
Land Office		
under special instructions datedMay	13, 1941,	and assignment
instructions dated . Aug. 1 and Sept.	19, 1941, having l	been critically examined, and
the necessary corrections made prior to their certification	by the engineer, the sa	id field notes, and the survey
therein described, are hereby approved.	On One	$\bigcap$
	Manifel	Supervisor of Surveys.
,		Supervisor of Surveys.
CERTIFICATE OF	TRANSORIPT	
- I century that the foregoing transcript of the field r	notes of the above descri	bed surveys in
, is a true copy of the ori	ginal field notes on file i	n the public survey office.
		-Sameran of Samaran

.S. GOVERNMENT PRINTING OFFICE 6-841