UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

BOOK 4887

FIELD NOTES

of the

	SUB	DIVISION	
		of	
		·•••··································	
	<u></u>		
		-	
$\it Of\ the\$	Gila and	d Salt River	
In the State of	Ar	izona.	
·			
		CUTED BY	
G. Ma	rvin Litz		
			·
Under special instruct	ions dated	December 1	, 19.37_, which provided
for the surveys include	ed under Group	o No. 197 ,	bearing the approval of the
Commissioner of the G	eneral Land Of	fice under date of .	January 14, 1938
and assignment instru			
		-	•
,	-	Fahmiam: 04	10 17
		February 24	
Survey	completed	March 14	, 19 41 •

nock 4367

INDEX DIAGRAM.

Ç	Towns	hip .		S.	, Range	1 W., G.&	S.R.M.
	6	49	5	35 4	26 s	18 2	10 1
-	48		48	34	26	18	9
	7 46	47	s 45	33 •	25 10	17 11	8
	18	44	17	32 16	23 15	16 14	7 18
-	43	<u> </u>	42	31	23	15	6
	19	41	20	30 21	22 ₂₂	14 23	5 24
ŀ	40	 	39	30	21	13	5
	30	38	29	29 28	21 27	13 26	4 25
L	38		37	28	20	12	3
	81	36	32	27 38	19 34	11 25	2 36
					6—151		

6—151

4367

The survey herein noted was executed with Gurley transits Nos. 371537 and 371612, equipped with Smith solar attachments, constructed in accordance with the standard specifications of the Bureau of Land Management. The instruments were placed in satisfactory adjustment prior to beginning the survey, and tested and found to be free from appreciable error.

The bearings of the lines were determined by direct observation upon the sun and Polaris for azimuth, supplemented by observations with the solar units. Measurements were made with steel tapes, 5 chains in length, graduated every link for the first 100 links, and the balance at intervals of 10 links. The tapes were first tested with a Lufkin Standard 1 chain tape and found correct. The measurements were made on the slope, the vertical angle of each interval was ascertained by a clinometer in good adjustment, and the true horizontal equivalents are entered in the field note record.

. The data presented with the special instructions gives the geographical position of the southeast corner of T. 7 S., R. 1 W., G. & S. R. M., as follows:

Latitude: 32° 46! 02"N. Longitude: 112° 18' 24"W.

February 23, 1947; at camp situated near the northeast corner of section 6, T. 7 S., R. 1 W., G. & S. R. M., at 10h. oom. 35s. a.m., M.S.T., make an observation on Polaris at eastern elongation, taking four sights each with the telescope in the direct and reversed positions, and noting the horizontal angle counter-clockwise to a reference mark approximately five miles distant:

Mean horizontal angle to Polaris 96°30° 07" Reduced bearing to reference mark S.84° 40° 00"W.

At 4h. 03m. 25s. p.m., M.S.T., the same day, transit on the above determined meridian, make an observation on Polaris at upper culmination:

Mean observed vertical angle Polaris 33° 51' 30" Reduced latitude 32° 51' 10"

The solar units were tested upon this meridian and maintained in good adjustment throughout the survey.

The Gila and Salt River Meridian, which is the east boundary of the township, was resurveyed by Mr. W. H. Thorn, U. S. Surveyor, in 1914. The north, south, and west boundaries were surveyed by Mr. Ty White, Cadastral Engineer, in 1938.

Chains.

The cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., is marked with an iron post, 2 ins. diam., 10 ins. above ground, firmly set, marked as described in the official record, and witnessed by a mound of stone, 4 ft. base, 2 ft. high W. of cor.

N. 0° 01' W., bet. secs. 35 and 36.

Through desert timber and undergrowth, over rolling hills. Ascend slightly over a S. slope.

- 1.10 Top of short ridge, bears W. and SE.; desc. 97 ft. over a N. slope.
- 11.00 Enter wash, 20 lks. wide, 2 ft. deep, course N. from SE.
- 13.30 Leave wash, course N. 10° W.
- 24.30 Recross wash, 30 lks. wide, 3 ft. deep, course N. 80° E.
- 32.50 Low spur, slopes NE.
- 36.800 Unused desert road, bears N. 30° E. and S. 40° W.
- 39.80 | Wash, 1 ch. wide, 3 ft. deep, course N. 80° E.
- .40.00 Point for the \(\frac{1}{4}\) sec. cor. of secs. 35 and 36, in the bottom of the above wash.
- 41.00 Establish a witness \(\frac{1}{4} \) sec. cor. of secs. 35 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

from which

An ironwood, 24 ins. diam., bears N. $76\frac{1}{2}$ ° E., 43 lks. dist., mkd. WC $\frac{1}{4}$ S36 BT.

A catclaw, 3 ins. diam., bears S.32° W., 64 lks. dist., mkd. WC BT.

- 50.50 Wash, 15 lks. wide, 2 ft. deep, course E.
- 72.20 Enter large main wash, course N. 30° W.
- 76.30 | Leave wash; asc. 57 ft. over a S. slope.
- 79.20 | Spur, slopes W.; desc. 6 ft. over NW. slope.
- 80.00 | Point for the cor. of secs. 25,26,35, and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T7S R1W S 26 S 25 S 35 S 36

1947

The cor. is on a loose rocky NW. slope.

#3**37**

Chains	Land, rolling hills. Soil, 3rd. rate, gravelly and rocky.
•	Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.
	The cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., is marked with an iron post, 3 ins. diam., firmly set in a mound of stone 4 ft. base, 1½ ft. high, to top, marked and witnessed as described in the 1914 resurvey record.
	The cor, is on the W. edge of a wash, 20 lks. wide, 4 ft. deep, course N. 10° E.
	West, bet. secs. 25 and 36.
	Over rolling hills thru scattering timber and undergrowth.
4.70	Wash, 15 lks. wide, 3 ft. deep, course N. 20°E.
11.70	Wash, 20 lks. wide, 5 ft. deep, course NE.
16.90	Drain, 15 lks. wide, 2 ft. deep. course N. 15° E.
23.50	Wash, 20 lks. wide, 8 ft. deep, course NE.
30.90	Wash, 50 lks. wide, 10 ft. deep, course NE.; asc. 120 ft. over a SE. slope.
39•99	Point for the 4 sec. cor. of secs. 25 and 36.
•	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone 4 ft. base to top, with brass cap mkd.
•	½ S 25 S 36
	1947 The cor. is on a steep SE. slope.
	Asc. 75 ft.
46.10	Spur, slopes SW., desc. 25 ft.
50.50	Spur, slopes N., continue descent over W. slope, 145 ft.
57•55	Wash, 15 lks. wide, course N. 15° W.; asc. 23 ft.
59 . 60	Low spur, slopes N. 15° W., desc. 23 ft. over W. slope.
61.90	Wash, 30 lks. wide, 2 ft. banks, course N.; asc. 127 ft. over an E. slope.
70.90	Spur, slopes S. from top of hill; desc. 60 ft. along SW. slope.
78.50	Spur, slopes S. 70° W., desc. 14 ft. along NW. slope.
79.98	The cor. of secs. 25, 26, 35, and 36.
. r 	Land, rolling hills. Soil, gravelly and rocky, 4th. and 3rd. rates. Timber, paloverde and ironwood, undergrowth, creosote brush, ocotillo and eactuses.

4-678 b / 16

Chains.	
	N. 0° 01' W., bet. secs. 25 and 26.
•	Through a medium stand of desert growth; desc. 33 ft. over NW. slope.
3.15	Wash, 15 lks. wide, course S. 80° W.; asc. 45 ft. over a S. slope.
8.80	Spur, slopes NW.; desc. 45 ft. over NE. slope.
13.90	Foot of descent; asc. 23 ft. over S. slope.
15.75	Small round hill; desc. 70 ft. over a N. slope.
22.30	Wash, 15 lks. wide, 2 ft. deep, course NE.:
33.90	Wash, 10 lks. wide, course N. 70° E.
36.80	Wash, 20 lks. wide, 4 ft. deep, course E.
40.00	Point for the 4 sec. cor. of secs. 25 and 26.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	s 26 s 25
-	1947
	Dig pits, 18x18x18 ins., N. and S. of cor.3ft. dist.
44.20	Drain, 15 lks. wide, 3 ft. deep, course N. 50° E.
48.90	Wash, 20 lks. wide, 2 ft. deep, course E.
51.95	Four strand barbed wire fence, bears N. 70° E., and S. 70° W.
58.10	Old road, bears N. 40° E. and S. 40° W.
62.00	Enter wash, 10 ft. cut-bank, course N. 40° E.
65.00	Leave wash,
78.40	Wash, N. 80° E., 20 lks. wide, 2 ft. deep.
80.00	Point for the cor, of secs. 23, 24, 25, and 26.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S RIW S 23 S.24 S 26 S 25
^	1947
	from which
*	A paloverde, 8 ins. diam., bears N.484°E., 109 lks. dist., mkd. T7S R1W S24 BT
	An ironwood, 10 ins, diam., bears \$,80\pm^c E., 91 lks. dist., mkd. T7S R1W S25 BT.
	An ironwood, 5 ins. diam., bears S. 194°W., 181 lks. dist., mkd. T7S R1W S26 BT.
	An ironwood 5 ins. diam., bears N. 42° W., 71 lks. dist., mkd. T7S R1W S23 BT.

Subdivision of T. 7 S., R. 1 W. Chains. Land, rolling desert. Soil, sandy to rocky, 3 rd. rate.
Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses. The cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp. is marked with an iron post, 3 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the 1914 resurvey record. from which An aerial gunnery range boundary marker, bears South, 12 lks. dist.; a standard T type iron fence post, 1½ in. legs, 5 ft. above ground, with a lx1½ ft. enameled steel sign, red lettering on white. N. 89° 55' W., bet. secs. 24 and 25. Giver rolling land, through medium heavy desert growth. 31.00 Wash, 15 lks. wide, 3 ft. deep, course N. 20° E. 39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. \$\frac{5}{4} \text{S} \frac{24}{5} 1947 Raise a mound of stone, 2 ft. base, l_2^{\perp} ft. high, N. of cor. Desc. 10 ft. over a W. slope. Drain, 10 lks. wide, 1 ft. deep, course N. 40° E. 41.55 45.55 Wash, 20 lks. wiwe, 2 ft. deep, course N. 80° E. 51.32 Four wire barbed wire fence, bears NE. and SW. 54.25 Desert road, bears NE. and SW. 59.65 Drain, 10 lks. wide, course N. 10° E. Wash, 1.50 chs. wide, 5 ft. E. bank, course N.

73.35

78.90 Wash, 20 lks. wide, $1\frac{1}{2}$ ft. deep, course N. 70° E.

The cor. of secs. 23, 24, 25, and 26. 79.94

> Land, nearly level desert. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde and ironwood.

N. 0° 01' W., bet. secs. 23 and 24.

Over rolling land, through medium dense desert growth.

Asc. 50 ft. over a SE. slope.

	Subdivision of r. / S., R. I w.
Chains. 8.30	Spur, slopes Sw.; desc. 47 ft. over a N. slope.
15.80	Foot of descent, thence over rolling desert land.
26.80	Desert road, bears N. 35° E,, and S. 30° W.
40.00	Point for the 4 sec. cor. of secs. 23 and 24.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	s 23 s 24 1947
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
40.80	Center of same road, bears N. 15° W., and S. 10° E.
66.90	Recross road, bears N. 50° E. and S. 35° W.
80.00	Point for the com. of secs. 13, 14, 23, and 24.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S R1W. S 14 S 13 S 23 S 24
	1947
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling desert. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde, ironwood, and, mesquite; undergrowth, creosote brush, ocotillo, and cactuses.
	The cor. of secs. 13, 10, 19, and 24 on the E. bdy. of the Tp. is marked with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1914 resurvey record.
	from which An aerial gunnery range bdy. marker, bears North,
	6 lks. dist.
	N. 89° 51' W., bet. secs. 13 and 24.
	Over rolling desert land, through a medium dense growth.
10.20	Desert road, bears N. and S. 30° W.
27.40	Desert road, bears N. 30° E., and S. 30° W.
30.10	Enter wash area at main channel, 1 ch. wide, 8 ft. cut- bank, course N.
34.40	Leave wash area, course N.
39.96	Point for the 4 sec. cor. of secs. 13 and 24.
r I	, · · · · · · · · · · · · · · · · · · ·

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

	Chains.		
		\$\frac{\sqrt{5}}{4}\frac{\sqrt{3}}{\sqrt{24}}	İ
	_	1947 Raise a mound of stone, 2 ft. base, 12 ft. high,	
		N. of cor.	
	46,.10	Wash, 20 lks. wide, 12 ft. E. bank, course N. 10° E.	
	69.15	Wash, 25 lks. wide, 5 ft. deep course N. 20° W.	
	7 9 •5 5	Desert road, bears N. 20° W., and S. 20° E.	
	79.92	The cor. of secs. 13, 14, 23, and 24.	
	,	Land , nearly level. Soil, 2nd. and 3rd. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.	
	-	N. 0° 01' W., bet. secs. 13 and 14.	
		Over rolling land, through medium dense desert growth.	
	5.20	Drain, 5 lks. wide, course NW.	
	15.80	Wash, 15 lks. wide, 3 ft. deep, course NE.	
	24.20	Wash, 20 lks. wide, 6 ft. deep, course NE.	
	40.00	Point for the 4 sec. cor. of secs. 13 and 14.	
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.	
	•	s 14 s 13 1947	
		1947	
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.	
	•	The cor. is on the edge of a small drain.	
	61.50	Long low spur, slopes NE,	
	76.00	Enter wash area, course N. 50° E.	į
	78.20	Main wash, 50 lks. wide, course N. 35° E.	
	80.00	Point for the cor. of secs. 11, 12, 13, and 14.	
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.	
		T7S R1W S 11 S 12 S 14 S 13	
		1947	
		Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
		Land, rolling.	
		Soil, sandy and gravelly, 2nd and 3rd. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, cactuses, and cats claw.	
- 1			

1	
\sim	
	•

Chains.	
	The cor. of secs. 7, 12, 13, and 10, on the E. bdy. of the Tp, is mkd. with an iron post, 3 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the 1914 resurvey record.
	from which
	An aerial gunnery range bdy. marker, bears SW., 1.14 chs. dist.
	N. 89° 52' W., bet. secs. 12 and 13.
	Over rolling to level land, through medium dense growth.
12.55	Drain, 15 lks. wide, 2 ft. deep, course N. 30° E.
33.05,	Wash, 15 lks. wide, 3 ft. deep, course N. 10° W.
39.97	Point for the 4 sec. cor. of secs. 12 and 13.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	\$ <u>12</u> \$ 13
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high,
·	N. of cor.
	Asc. 50 ft. over a NE. slope.
44.20	Wash, 1 ch. wide, 3 ft. banks, course N. 5° E.
55.15	N. slope of isolated hill; desc. 40ft. over a NW. slope
61.65	Wash, 30 lks. wide, 8 ft. E. bank, course N.
67.95	Wash, 15 lks. wide, 2 ft. deep, course N. 10° W.
76.45	Enter wash area, drains N. 20° E.
7 9 • 35	Wash, course N. 35° E.
79•94	The cor. of secs. 11, 12, 13, and 14.
÷	Land, rolling to level. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.
	N 0° 01 W bot good 11 and 10
	N. 0° 01' W., bet. secs. 11 and 12.
6.00	Over nearly level land, through medium dense desert growth.
6.00	Leave wash area, drains N. 20° E.
30.80	Drain, 10 lks. wide, course N. 35° E.
33.70	Enter Wash, 15 lks. wide, 3 ft. deep, course N.
36.20	Leave wash, course NE.
40.00	Point for the 4 sec. cor. of secs. 11 and 12.

	Subdivision of T. 7 S., R. 1 W.	17
 Chains		
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.	
	S 11 T S 12	
	1947	
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.	
66.50	Wash, 15 lks. wide, 3 ft. deep, course N. 30° E.	
69.10	Wash, 30 lks. wide, 3 ft. deep, course N. 30° E.	
78.90	Wash, 10 lks. wide, course N. 20° E.	
80.00	Point for the cor. of secs.1, 2, 11, and 12.	
	Set an iron post, 3 ft, long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.	
	T7S R1W S 2 S 1 S 11 S 12	
	1947	
	Raise a mound of stone 2½ ft. base, 2 ft. high,	
	Land, nearly level. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.	
ų.		
	The cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., is marked with an iron post, 3 ins. diam., 6 ins. above ground, firmly set, marked and vitnessed as described in the 1914 resurvey record.	
	The cor. is in a drain, 10 lks. wide, course N. 10° E.	
	N. 89° 51' W., bet. secs. 1 and 12.	
	Over level desert land, through scattering timber.	
8.45	Wash, 10 lks. wide, 1 ft. deep, course NE.	
22.95	Wash, 2 chs. wide, course N.	
33.15	Wash, 15 lks. wide, 8 ft. deep, course N. 60° E.	
38.20	Desert road, bears N. 40° E. and S. 20° W.	
39 • 45	Wash, 20 lks. wide, 6 ft. deep, course N.	
39.97	Point for the # sec. cor. of secs. 1 and 12.	
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.	

Chains	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,
	N. of cor.
49.35	Wash, 80 lks. wide, 3 ft. deep, course N. 30° E.
72.75	Wash, 1.20 chs. wide, course N. 30° E.
79.55	Drain, 10 lks. wide, 1 ft. deep, course N. 20° E.
79•94	The cor. of secs. 1, 2, 11, and 12.
	Eand, nearly level. Soil, sandy, 2nd. and 3rd. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.
, '	
	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp,, is marked with an iron post, 2 ins. diam., firmly set in a mound of stone, 5 ft. base, to top, marked and witnessed as described in the official record.
	S. 0° 01' E., bet. secs. 1 and 2.
	Over low broken hills through scattering desert growth.
	Desc. 63 ft. over a SE. slope.
5.40	Wash, 40 lks wide, 5 ft. deep, course SW.; asc. along a NW. slope.
19.30	Rocky spur, slopes W.; desc. 80 ft. over a SW. slope.
34.30	Foot of descent; thence over level land.
39.77	Point for the ½ sec. cor. of secs. 1 and 2.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	S 2 S 1
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	U. S. C. & G. S. benchmark, lears S. 18° 39' E., 20.18 chs. dist.; a standard brass cap, mkd. P83 1935, set in a concrete block, 10x10x8 ins. above ground. The benchmark is about 1 ch. south of Ariz. highway No. 84 on a spur sloping S.
48.20	Wash, 15 lks. wide, 1 ft. deep, course W.
55 •7 7	Centerling of Arizona State Highway No. 84 in curve, approximate bearing, S. 65° E. to Gasa Grande, and N.65°W. to Gila Bend.
70.00	Five wire barbed wire fence, bears NW., and SE. around stock-watering reservoir.
70.42	Same fence, bears SW., and NE. 51 lks. to corner, along top of 12 ft. reservoir bank.

F 3387

Chains	
73.20	Desert road, NE. and SW.
74.30	Wash, 25 lks. wide, 1 ft. deep, course NE.
79.45	Drain, 5 lks, wide, 1 ft. deep, course NE.
79.77	The cor. of secs. 1, 2, 11, and 12.
	Land, broken hills to level desert. Soil, sandy to rocky, 3 rd. and 4th. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses;
	The cor. of secs. 2, 3, 34, and 35. on the S. bdy. of the Tp. is/an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
	N. 0° 01! W., bet. secs. 34 and 35.
	Over rolling desert land through medium heavy desert growth
2.40	Wash, 10 lks. wide, course E.
10.40	Wash, 20 lks. wide, course E.
22.80	Wash, 1 ch. wide, 15 ft. deep, course NE.
28.10	Wash, 50 lks. wide, 14 ft. S. bank, at crossing of old desert road, bears W. and N. 10° E.
29.54	Four wire fence, bears N. 35° E., and S. 35° W.
40.00	Point for the 4 sec. cor. of secs. 34 and 35.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	S 34 S 35
	1947 from which
	An ironwood, 3 ins. diam., bears S. 394° E., 49 lks. dist., mkd. BT.
	A paloverde, 5 ins. diam., bears S. 65½° W., 24 lks. dist., mkd. 4 S34 BT.
44.90	Wash; 25 lks. wide, course E.
55.00	Drain, 10 lks. wide, course E.
60.10	Wash, 20 lks. wide, 2 ft. deep, course N. 80° E.
78.70	Drain, 10 lks. wide, 3 ft. deep, course NE.
80.00	Point for the cor. of secs. 26,27, 34, and 35.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S R1W S 27 S 26 S 34 S 35

Chains.	-
	Raise a mound of stone, 2½ ft. base, ½ ft. high, W. of cor.
	Land, rolling. Soil, sandy to rocky, 3rd. and 4th. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	From the cor. of secs. 25, 26, 35, and 36,
·	S. 89° 59' W., bet. secs. 26 and 35.
	Over rolling land through medium dense desert growth.
*	Desc. 52 ft. over a NW. slope.
4.70	Desert road, bears N. 20° W. and S. 20° E.
6.80	Wash, 1 ch. wide, 1 ft. deep, course N. 30° W.
17.20	Wash, 20 lks. wide, 2 ft. deep, course N.
31.80	Wash, 60 lks. wide, 2 ft. deep, course NE.
38.33	Desert road, bears NE. and SW.
38.95	Four wire fence, bears S.354° W., and N. 354° E.
39.98	Point for the 4 sec. cor. of secs. 26 and 35.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	+ <u>S 26</u> + S 35
*.	1947
	Raise a mound of stone, 3 ft. base, $l_2^{\frac{1}{2}}$ ft. high, N. of cor.
43.10	Wash, 15 lks. wide, course N.5° E.
52.90	Drain, 10 lks. wide, course N. 50°E.
60.00	Wash, 40 lks. wide, 2 ft. deep, course NE.
69.70	Drain, 10 lks. wide, course N. 80° E.
73.00	Low spur, slopes SW.; desc. 25 ft. over NW. slope.
78.90	Drain, 10 lks. wide, 3 ft. deep, course N.
79.96	The cor. of secs. 26, 27, 34, and 35.
	Land, rolling. Soil; 3rd. and 4th. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
•	

Chains	
	N.0° 01' W., bet. secs. 26 and 27.
	Over rolling land thru scattering desert growth.
3.40	Drain, course NE.
8.00	Wash, 1 ch. wide, 4 ft. deep, course N. 30° E.
15.00	Enter wash area, drains NE.
19,00	Main wash, 40 lks. wide, 3 ft. deep, course N. 60° E.
25.00	Leave wash area.
36.10	Wash, 15 lks. wide, 3 ft. deep, course N. 30° E.
40.00	Point for the 4 sec. cor. of secs. 26 and 27.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	g 27 g 26
	s 27 s 26
	1941
	Raise a mound of stone, 3 ft. base, 2 ft. high, w. of cor.
58.50	Wash, 10 lks. wide, 3 ft. deep, course N. 10° E.
74.50	Wash, 10 lks. wide, 2 ft. deep, course N. 40° E.; asc. 20 ft.
7 8.50	Spur slopes NE.; desc. slightly.
80.00	Point for the cor. of secs. 22,23,26, and 27.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S R1W S 22 S 23 S 27 S 26
	1947 Raise a mound of stone 3 ft hags 2 ft high
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Land, rolling. Soil, sandy and gravelly, 3rd. rate.
	Timber, paloverde, ironwood and mesquite; undergrowth, creosote brush, ocotillo and cactuses.
	;
·	From the cor of secs 23 24 25 and 26
	From the cor. of secs. 23, 24, 25, and 26, S. 89° 55' W., bet. secs. 23 and 26.
	Over rolling land through medium heavy desert growth.
	Asc. 15 ft. over E. slope.
4.00	Low spur, slopes S.
	Desert road, bears N. 15° E. and S. 15° W.
0.20	and b. in w.

	•
Čhains.	
16.80	Wash, 40 lks wide, 3 ft. deep, course NE,
20.90	Wash, 20 lks. wide, 2 ft. deep, course NE.
33.00	Wash, 25 lks. wide, 5 ft. E. bank, course NE.
37.00	oot of samll round hill; asc. 25 ft.
39.20	Top of small round hill, desc. 12 ft.
40.00	Point for 4 sec. cor. of secs. 23 and 26.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	S 23 4 S 26
•	1947
	Raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.
	Desc. 13 ft. over W. slope.
49 • 25	Wash, 50 lks. wide, 3 ft. deep, course N. 30° E.
68.85	Wash, 5 lks. wide, 3 ft. deep, course N. 10° W.
73.00	Wash, 15 lks. wide, 3 ft. deep, course N. 10° E.; asc. 25 ft. over E. slope.
74.50	Wash, 15 lks. wide, 3 ft. deep, course N. 10° E.
78.90	Spur, slopes NE.
80.00	The cor. of secs. 22, 23, 26, and 27.
•	Land, rolling. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde and ironwood, some mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
	N. 0° 01' W., bet. secs. 22 and 23.
	Over rolling land through medium dense desert growth.
`	Desc. 17 ft. over a N. slope.
3.30	Wash, 15 lks. wide, 2 ft. deep, course NE.
8,20	Low spur, slopes NE.
16.20	Drain, 15 lks. wide, 2 ft. deep, course NE.
36,40	Spur, slopes NE.
38.70	Drain, 10 lks. wide, course NE.
40.00	Point for the 4 sec. cor. of secs. 22 and 23.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with braks cap mkd.
	s 22[s_23

T	Chains	
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor.
	46.70	Right bank of wash, course H., thence along same.
	51.00	Leave right bank of wash, course N. 10° W.
	53.80	Wash, 20 lks. wide, course NW.
	80.00	Point for the cor. of secs. 14, 15, 22, and 23.
	•	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
		T7S R1W S 15 S 14 S 22 S 23
		1947
	٠	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	,	Land, rolling. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde and ironwood, some mesquite. Undergrowth, cressote brush, ocotillo and cactuses.
	•	From the cor. of secs. 13, 14, 23, and 24,
	, 6	S. 89° 58' W., bet. secs. 14 and 23.
	•	Over rolling desert through medium dense desert growth.
	6.60	Wash, 10 lks. wide, 1 ft. deep, course NE.
	17.70	Wash, 75 lks. wide, 2ft. deep, course N.
	26.30	Wash, 120 lks. wide, 2 ft. deep, course NE.
	30.40	Low spur, slopes N.
	35.40	Wash, 15 lks. wide, course NE.
	39.96	Point for 4 sec. cor. of secs. 14 and 23.
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		\$\frac{14}{5} \frac{23}{23}
		1947
		Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.
	43.20	Spur, slopes N. 20° E.; desc, 37 ft.
	54.10	Wash, 25 lks. wide, 3 ft. deep, course N. 35° E.; asc. 32 ft.
	62.30	Spur, slopes NE.
	75.80	Wash, 40 lks. wide, 2 ft. deep, course N.10° W.

-33 -6781b

Subdivision of T. 7 S., R. 1 W.

Chains The cor. of secs. 14, 15, 22, and 23. 79.92 Land, rolling, Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde, ironwood, and mesquite.
Undergrowth, creosote brush, ocotillo, and cactuses. N. 0° 01' W., bet. secs. 14 and 15. $^{
m O}{
m ver}$ rolling land through medium dense desert growth. Wash, 15 lks. wide, 3 ft. deep, course N. along line. 9.10 13.10 Leave wash, course N. 60° E. Same wash, course N. 59° W. 24.10 40.00 Point for the 4 sec. cor. of secs. 14 and 15. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. s 15 s 14 Raise a mound of stone, 21 ft. base, 2 ft. high, W. of cor. Same, wash, 30 lks. wide, 4 ft. deep, course N. 30° E. 47.90 Same wash, 40 lks. wide, 4 ft. deep, course N. 30° W. 79.30 00.08 Point for the cor. of secs. 10, 11, 14, and 15. Set an iron post, 3ft. long, 2, ins. diam., 30 ins. in the ground, with brass cap mkd. T7S R1W . 10 S 11 1947 Maise a mound of stone 3 ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde, ironwood and mesquite. Undergrowth, creosote brush, ocotillo, and cactuses. From the cor. of secs. 11, 12, 13, and 14, S. 89° 55' W., bet. secs. 11 and 14. Over rolling desert through scattering desert growth. 1.60 Wash, 10 lks. wide, 3 ft. deep, course N. 30° E. 10.50 Wash, 25 lks. wide, 4 ft. deep, course N. 12.50 Enter wash area, drains N. 5° E.

4367

****	Chains.	
	14.50	Leave wash area, drains N. 5° E.
	28.00	Desert road, bears NW. and SE.
	32.00	Wash, 20 lks. wide, 5 ft. deep, course N. 10° E.
	39.99	Point for the 4 sec. cor. of secs, 11 and 14.
		Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
		\(\frac{1}{4} \frac{11}{15 14} \)
		. 1947
		Raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
	40.05	Wash, 5 lks. wide, 1 ft. deep, course N. 20° W.
	51.00	Wash, 30 lks. wide, 6 ft. deep, course N. 10° E.
	63.10	Wash, 20 lks. wide, 3 ft. deep, course N. 20° E.
	79.56	Aerial gunnery range bdy. marker, bears south, 4 lks. dist.
	79.98	The cor. of secs. 10, 11, 14, and 15.
		Land, rolling. Soil, sandy and gravelly, 2md and 3rd. rates. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, and cactuses.
		N. 0° 01' W., bet. secs. 10 and 11.
		Over rolling land, through scattering desert growth.
	4.00	Wash, 60 lks. wide, course N. 30° E., thence over wash area.
		Same wash, 50 lks. wide, course NW., leave wash area.
	40.00	Point for the z sec. cor. of secs. 10 and 11.
	,	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	Si .	S 10 S 11
		1947
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
	42.80	Wash, 10 lks. wide, course N. 35° W., at junction of washes from the SW. and SE.
	5015	Wash, 10 lks. wide, 3 ft. deep, course NE.
		Wash, 80 lks. wide, 8 ft. N. bank, course NW.
	_	Point for the cor. of secs. 2, 3, 10, and 11.
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

Subdivision of T. 7 S., R. 1 \mbox{W} .

Chains.	
*	T7S R1W S 3 S 2 S 10 S 11
	1947
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
<u>-</u>	Land, rolling to nearly level. Soil, sandy to gravelly, 2nd. and 3rd. rates. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
	From the cor. of secs. 1, 2, 11, and 12,
	S. 89° 57' W., bet. secs. 2 and 11.
	Over flat desert land through heavy growth of creosote brush.
7.10	Desert road, bears NE. and SW.
8.50	Earth cut-off embankment, 5 ft. high, bears SW., and NE. to stock watering reservoir.
9.50	Wash, 40 lks. wide, course NE.
39.97	Point for the 4 sec. cor. of secs. 2 and 11.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	½ S 2 5 11
	1947
•	Raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
48.40	Wash, 5 lks. wide, 1 ft. deep, course NW.
79•94	The cor. of secs. 2, 3, 10 and 11.
	Land, level desert. Soil, sandy, sand loam and clay, 2nd. rate. Timber, very little.Undergrowth, creosote brush, cactuses.
	The cor. of secs. 2, 3, 34, and 35 on the N. bdy. of the Tp. is an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
	S. 0° 01' E., bet. secs. 2 and 3.
	Over level bottom land through scattered desert growth.
10.00	Swale, at head, drains S. 10° W.
17.30	Drain, course SW.
21.20	Wash, 15 lks. wide, 3 ft. deep, course S.75° W. from NE.
^	
	1

	·
Chains	3
23.59	Center-line of Arizona State Highway No. 84 at end of curve from W., bears S. 73° 33' E. on tangent. Ascend 35 ft. over a NW. slope.
31.10	Wash, 20 lks. wide, 6 ft. deep, course W. from SE. Continue ascent.
39.83	Point for the 4 sec. cor. of secs. 2 and 3.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	S 3 S 2 1947
	1947
	Raise a mound of stone 3 ft. base, 2 ft. high, W.of cor.
	Asc. 30 ft. over NW. slope.
46.30	Spur, slopes SW.; desc. 70 ft. over a SE. slope.
58 -20	Foot of slope, thence over level land.
71.20	Strip 4 chs. wide bare of vegetation, drains W.
7 9.83	The cor. of secs. 2, 3, 10, and 11.
	Land, level and rolling. Soil, sandy to rocky, 2nd. to 4th. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, and cactuses.
	The cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp. is/an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
	N. 0° 02' W., bet. secs. 33 and 34.
	Over low rolling foot hills, thru medium dense desert growth along the washes.
	Asc. 25 ft. over SE. slope.
3.00	Spur, slopes NE.; desc. 40 ft. over NW. slope.
8.00	Drain, course NE.; asc. 10 ft.
12.00	pur, slopes NE.; desc. 23 ft.
16.00	Wash, 50 lks. wide, 8 ft. deep, course NE.
17.00	Same wash, course NW.
20.00	Same wash, course N. 40° E; Asc. 63 ft. over a S. slope.
27.50	Low.hill, slopes NE. and SW.; desc. 48. ft. over NW. slope.
34.00	Wash, 20 lks. wide, 4 ft. deep, course N. 30° E.
40.00	Point for the 4 sec. cor. of secs. 33 and 34.

Chains.	
	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	s 33 s 34
	1947
	The cor. is on the sloping E. bank of a wash, 40 lks. wide, 4 ft. deep, course N. along line.
42.50	Same wash, 40 lks. wide, 8 ft. deep, course N. 10° E. Asc. 22 ft.
51.00	Drain, course N. 30° E.
53 • 45	Spur, slopes. E.; desc. 16 ft.
57.00	Drain, course NE.
62.00	Spur, slopes N. 25° E.; desc. 36 ft.
69.50	Wash, 20 lks. wide, 8 ft. deep, course NE.
80.00	Point for the cor. of secs. 27,28,33, and 34.
	Set an iron post, 3 ft. long, 2 ins. diam., 3 ins. in the ground and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T7S R1W S 28 S 27 S 33 S 34
	1947
-	Land, rolling, low hills. Soil, gravelly and rocky, 3rd. and 4th. rates. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
	D 06 07 74 75
	From the cor. of secs. 26, 27, 34, and 35,
	S. 89° 52' W., bet. secs. 27 and 34.
- 15	Over rolling land through medium dense desert growth. Wash, 30 lks. wide, 4 ft. deep, course N. 20° E.
5.15	Wash, 10 lks. wide, 2 ft. deep, course N. 20° E.
13.15	Wash, 30 lks, wide, 7 ft. deep, course N. 30° E.
40.07	Point for the 4 sec. cor. of secs. 27 and 34.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the
	ground, with brass cap mkd.
*	\$\frac{\sigma}{4} \cdot \frac{\sigma}{\sigma} \frac{327}{334}
	1947
46.65	Drain, course NE.; asc. 40 ft. over an E. slope.
51.95	Spur, slopes N.; desc. 35 ft.over a W. slope.

hains	
58.55	Wash, 10 lks. wide, 2 ft. deep, course N. 10° W.;
69. 55	Wash, 10 lks. wide, 3 ft. deep, course N. 20° E.
70.45	Wash, 40 lks. wide, 6 ft. deep, course N. 30° E.
80.14	The cor. of secs.27,28, 33, and 34.
a a	Land, rolling. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses:
-	
	N. 0° 02' W., bet. secs. 27 and 28.
,	Over low rolling hills through medium dense desert growth.
3.50	Wash, 10 lks. wide, 3 ft. deep, course N. 30° E.; Asc. 45 ft.
19.00	Spur, slopes NE.; desc. 113 ft. over a N. slope.
40.00	Point for the 2 sec. cor. of secs. 27 and 28.
,	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	s 28 s 27
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
49.50	Wash, 20 lks. wide, 7 ft. deep, course N.30° E., asc. 25 ft.
61.50	Spur, slopes NE.; desc. 34 ft. along NE. slope.
80.00	Point for the cor. of secs. 21, 22, 27, and 28.
	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	. T7S R1W . S 21 S 22 S 28 S 27
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Tand, rolling. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	From the cor. of secs. 22, 23, 26, and 27.
	S. 89° 54' W., bet. secs. 22 and 27.
•	Over low rolling hills through medium dense desert growth.

	Chains.	
	1.30	Wash, 5 lks. wide, 1 ft. deep, course N. 10° E.
	9.00	Wash, 20 lks. wide, 2 ft. deep, course N.; asc. 29 ft. over an E. slope.
	12.70	Spur, slopes N.; thence along S. slope of hill near top.
	20.70	Wash, 10 lks. wide, 1 ft. deep, course N. 10° E; asc. 60 ft. overNE. slope of hill.
	26 . 90	Top of ascent on N. slope of low hill, near top; desc. 63 ft. over NW. slope.
	32.80	Wash, 20 lks. wide, 2 ft. deep, course N. 30° E.
	40.06	Point for the 2 sec. cor. of secs. 22 and 27.
•		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		. \frac{1}{4} \frac{S}{S} \frac{22}{27}
		1947
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,
	45.50	Wash, 40 lks. wide, 5 ft. deep, course N.
	57.90	Wash, 15 lks. wide, 3 ft. deep, course N. 30° E.
	66.00	Wash, 20 lks. wide, 2 ft. deep, course N. 2 0° E.; asc. 50 ft. over E. slope.
	75.65	Top of Low hill; desc. 37 ft. over a W. slope.
	80,12	The cor. of secs. 21, 22, 27, and 28.
	•	Land, rolling. Soil, sandy to rocky. Timber paloverde and ironwood; undergrowth, creosote brush ocotillo and cactuses.
	s	
		N. 0° 02' W., bet. secs. 21 and 22.
		Over rolling land, through medium dense desert growth.
	4.20	Wash, 10 lks. wide, 1 ft. deep, course N. 60° W.
	5.20	Same wash, course N. 10° E.
	16.00	Wash, 30 lks. wide, 10 ft. W. bank, course N.E.; asc.slightly.
	40.00	Point for the 4 sec. cor. of secs. 21 and 22.
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	,	s 21 s 22 1947
		Raise a mound of stone 5 ft. base, 3 ft. high W.
	ļ	of cor. The cor. is at fork of spur, slopes N. and N. 20° E.; desc. a gradual N. slope.

Chains. Wash, 10 lks. wide, 1 ft. deep, course N. 30° W.; thence along a level spur extending N. 56.00 Top of knoll on the above spur, from which spurs extend, NW. and NE.; desc. 12 ft. over a $^{\rm N}$. slope. 78.30 Point for the cor. of secs. 15, 16, 21, and 22. 00.08 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd. Raise amound of stone, 3 ft. base, 2 ft. high, · W. of cor. and, rolling. Soil, sandy to rocky. 3rd. rate. Timber, paleverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses. From the cor. of secs. 14, 15, 22, and 23. s.89° 55' W., bet. secs. 15 and 22. Over rolling desert land, through medium dense desert growth. 4.00 Wash, 35 lks. wide, 5 ft. deep, course N. 10° E. 39.30 Wash, 35 lks. wide, 5 ft. deep, course M. 10° W. Point for the 4 sec. cor. of secs. 15 and 22. 40.02 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ $\frac{S}{S}$ $\frac{15}{22}$. Raise a mound of stone, 3 ft. base, 2 ft. high, of cor. Wash, 20 1ks. wide, 2 ft. deep, course N. 10° W.asc. 20 ft. **57.**50 • **65.**00 Low spur, slopes N.; desc. 20 ft. over a W. slope. Wash, 15 lks. wide, 3 ft. deep, course N. 20° E. 74.50 The cor. of secs. 15, 16, 21, and 22. 80.04 Land, rolling. Soil, 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.

u. s. government printing office 16—28520-1

N. 0° 02' W_{\bullet} , bet. secs. 15 and 16.

hains.	Over rolling land, thru medium dense desert growth.
19.39	Wash, 5 lks.wide, 2 ft. deep, course N. 60° W.
40.00	Point for the 4 sec. cor. of secs. 15 and 16 .
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	s 16 s 15
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
45.00	Drain, course N. for 1 ch. thence NW.
57.00	Wash, 20 lks. wide, 4 ft. deep, course N. 80° W.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S R1W S 9 S 10 S 16 S 15
	. 1947.
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Land, rolling. Soil, sandy to rocky, 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, and cactuses.
-	
	From the cor. of secs. 10, 11, 14, and 15,
	5. 89° 55' W., bet. secs. 10 and 15.
	Over rolling land, through medium dense desert growth.
3. 00	Wash, 160 lks. wide, 12 ft. W. bank, course N.
20.80	Drain, course NW.
26.80	Drain, course NE.
40.02	Point for the 4 sec. cor. of secs. 10 and 15.
•	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	½ S 10 S 15
* *	1947
	Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
44.00	Wash, 15 lks. wide, 3 ft. deep, course N. 10° E.

	Chains	
	62.00	Wash, 15 lks. wide, 5 ft. W. bank, course N.
	76.60	Wash, 25 lks. wide, 5 ft. E. bank, course N.
	77.50	Wash, 10 lks. wide, 5 ft. deep, course N. 10° E.
	79 • 94	Aerial gunnery range bdy. marker, bears south, 1 lks. dist.
٠	80.04.	The cor. of secs. 9, 10, 15, and 16.
	,	and, rolling. Soil, sandy and gravelly, 2nd and 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
		N. 0° 02 ' W., bet. secs. 9 and 10.
	·	Over rolling land through dense desert growth, along a wash, 30 lks. wide, 5 ft. deep, course N.
	18.90	Left bank of wash, 30 ks. wide, course N. 10° E.
	20.00	Enter same wash, course along line.
	27.70	Leave wash, course N. 15° E.
	32.20	Same wash, 15 lks. wide, 10 ft. N. bank, course N.30° W.
	40.00	Foint for the 4 sec. cor. of secs. 9 and 10.
		Set an iron post, 3 ft. long, 1 ins. diam., 30 ins. in the ground, with brass cap mkd.
		$\mathbf{s} \mathbf{g} \mathbf{s} 10$
	•	1947
		Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	42.00	(Approximate dist.) Drain, course NW.
	64.00	Wash, 15 lks. wide, 3 ft. deep, course NW.
	69.00	Drain, course NW.
	73.00	Drain, course NW.; asc. grad. Sw. slope.
	80.00	Point for the cor. of secs. 3,4, 9, and 10.
	·	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
		T7S RIW
		\$ 9 \$ 10
		1947
		Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.
		Land, rolling. Soil, sandy and gravelly, 3 rd. rate. Timber, paloverd and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
		U. S. GOVERNMENT PRINTING OFFICE 16—23520-1

Chains.	
	From the cor. of secs. 2, 3, 10, and 11,
	5. 89° 58' W., bet. secs. 3 and 10.
	Over level desert, through scattering timber.
6.50	Wash, 40 lks. wide, 3 ft. deep, course N. 30° W.
32.00	Wash, 170 lks. wide, 3 ft. deep, course N. 20° W.
40.02	Point for the 4 sec. cor. of secs. 3 and 10.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	½ <u>S 3</u> B 10
	1947
	Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.
41.10	Wash, 10 lks. wide, 2 ft. deep, course, N.
49.90	Wash, 5 lks. wide, 1 ft. deep, course N.
59.00	Wash, 15 lks. wide, 3 ft. deep, course N.
66.00	Wash, 15 lks. wide, 3 ft. deep, course N. 10° E.
76.10	Wash, 5 lks. wide, 1 ft.deep, course N. 20° E.
80.04	The cor. of secs. 3, 4, 9, and 10.
	Land, level and rolling. Soil, sandy and gravelly, 2nd. and 3rd. rate. Timber, paloverde and ironwood, some mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
·	
	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp, Ts/an tron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record. S. 0° 02' E., bet. secs. 3 and 4. Over rolling desert land, through deattering timber.
1.80	Wash, 20 lks. wide, 2 ft. deep, course S. 80° W.
4.00	Wash, 25 lks. wide, 1 ft. deep, course W.
7.30.	Wash, 30 lks. wide, 3 ft. deep, course N. 80° W.
24.90	Center-line of Arizona State Highway No. 84, bears generally S. 76°E. and N. 73½° W., in curve.
26.80	Wash, 15 1ks. wide, 2 ft. deep, course S. 80° W.
39.84	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	s 4 s 3 1947

40070 43**07**

=	Chains	•	
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,	
	40.50	Wash, 35 lks. wide, 2 ft. deep, course W.	
	52.00	Bender Wash, 80 lks. wide, 3 ft. deep, course N. 70° W.	٠.
	79.84	The cor. of secs. 3, 4, 9, and 10.	
		Land, rolling desert. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.	
		The cor. of secs. 4, 5, 32, and 33 on the S. bdy. of the Tp. 1s/an Iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base, 1½ ft. high, marked and witnessed as described in the official record.	
		N. 0° 02' W., bet. secs. 32 and 33.	-
		Over rolling hills, through dense desert growth along the washes.	
	,	Desc. 50 ft. over a NW. slope.	
	2.20	Wash, 25 lks. wide, 10 ft. deep, course N. 10° E.	
	10.00	(Approximate dist.) Spur, slopes NE.; desc. 60 ft.	
	22.00	Wash, 15 lks. wide, 3 ft. deep, course N. 10° E. from SW. Desc. 20 ft.	
	24.50	Same wash, course NW. at this point, general course N. along line.	
	28.90	Same wash, course NE.	
	30.15	Same wash, course NW.	
	35.00	Same wash, course NE. to junction with main wash.	
	3 6. 95	Main wash, 25 lks. wide, 10 ft. deep, course N. 50° E	
	40.00	Point for the 4 sec. cor. of secs. 32 and 33.	í I I
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.	
		s 32 s 33 1947	
		Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
	46.75	Recross main wash, 50 lks. wide, 12 ft. deep, course NW.	
	59 •7 5	Wash, 10 lks. wide, 3 ft. deep, course N. 10° W.	
	75.00	Wash, 10 lks. wide, 2 ft. deep, course N. 20° W.	
	79.00	Wash, 25 lks. wide, 8 ft. deep, course N. 20° E.	
	, !	į	

Chains	
80,00	
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap, mkd.
	T7S R1W S 29 S 28
	s 32 s 33
	1947
	Raise a mound of stone, 2½ ft. base, ½ ft. high, W. of cor.
	Land, rolling hills. Soil, gravelly, 3rd. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo, and cactuses.
	From the cor. of secs, 27, 28, 33, and 34,
	West, bet. secs. 28 and 33.
	Over rolling desert land, through medium dense desert growth.
4.60	Wash, 20 lks. wide, 6 ft. deep, course N.; asc. 29 ft.
7.85	Spur, slopes NE., thence over flat top of same.
17.00	Spur, near toe, slopes NE., desc. 11 ft.
18.50	Drain, course NE.
26.75	Wash, 60 lks. wide, 8 ft. deep, course N. 20° E.
33.00	Wash, 10 lks. wide, 3 ft. deep, course N. 10° E.; asc. 34 ft.
35.00	Spur, slopes N.; asc. 23 ft.
37.90	Drain, course N.
40.04	Point for the 4 sec. cor. of secs. 28 and 33.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	4 S 28 5 33
	1947
	Raise a mound of stone, 2½ ft. base, 1½ ft. high N. of cor.
	Asc. 18 ft. over an E. slope.
42.50	Spur, slopes N.; desc. 26 ft. over a NW. slope.
45.00	Foot of slope.
53.99	Wash, 40 lks. wide, 10 ft. deep, course N.
57.50	Wash, 25 lks. wide, 4 ft. deep, course N. 20° E.

RCOK 4367

Chains	
68.50	Wash, 10 lks. wide, 2 ft. deep, course N. 10° E.; asc. 46 ft.
75.00	Spur, slopes N.; desc. 40 ft.
79.20	Wash, 40 lks. wide, 10 ft. deep, course N. 10° E.
80.08	The cor. of secs. 28,29,32, and 33.
•	Land, rolling. Soil, gravelly, 3 rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
·	N. 0° 02' W., bet. secs. 28 and 29.
	Through low rolling hills and scattered timber. Ascend a radual SE. slope.
30.00	Foot of S. slope; asc. 20 ft.
34.20	Top of ascent, thence across top of low hill.
37.00	Desc. NW. slope 17 ft.
40.00	Point for the 4 sec. cor. of secs. 28 and 29.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	s 29 s 28
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Desc. 53 ft. along E. slope of spur, slopes N.
58.00	Wash, 25 lks. wide, 10 ft. deep, course NE.
69.50	Wash, 10 lks. wide, 2 ft. deep., course N.
70.00	Leave wash, course N. 20° W.
78.50	Recross wash, course N. 30° E.
80.00	Point for the cor. of secs. 20, 21, 28, and 29.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S R1W S 20 S 21 S 29 S 28
	1947
	Raise a mound of stone, 2 ft. base, 12 ft. high, w. of cor.
	Land, rolling. Soil, sandy and gravelly, 3rd. rate. Limber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cactuses.

Chains.	From the cor. of secs. 21, 22, 27, and 28.
•	S. 89° 59' W., bet. secs. 21 and 28
	Over rolling desert land thru scattering timber
6.50,	Wash, 15 lks. wide, l.ft. deep, course N.
8.00	Wash, 10 lks.wide, 2 ft. deep, course N. 10° E.
22.70	Wash, 30 lks. wide, 5 ft. deep, course N. 30° E.; asc. 52 ft.
33.50	Spur, slopes N., desc. 46 ft.
40.05	Point for the casec. cor. of secs. 21 and 28.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	± <u>S 21</u> S 28
	1947
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
42.05	Drain, course NE.; asc. 40 ft.
45.00	Top of ascent, thence over flat topped spur.
48.00	Descend 35 ft.
53.00	Wash, 1 ch. wide, 10 ft. deep, course N. 10° W.; asc. 52 ft. over an E. slope.
62.50	Spur, slopes N.; desc. 30 ft. over a W. slope.
67.50	Wash, 20 lks. wide, 6 ft. deep, course N.
73 • 50	Wash, 50 lks. wide, 10 ft. deep, course N. 10° E.
78.20	Wash, 10 lks. wide, 2 ft. deep, course N. 20° E.
80.10	The cor. of secs. 20, 21, 28, and 29.
	Land, rolling. Soil, gravelly, 3 rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses.
,	
	N. 0° 02' W., bet. secs. 20 and 21.
• .	Over rolling land through medium dense desert growth.
10.00	Drain, course NE.
21.75	Drain, course NE.
31.40	Drain, course NE.
36.75	Wash, 10 lks. wide, 3 ft. deep, course N. 10° E.
38.00	Wash, 15 1ks. wide, 9 ft. E. bank, course N. along line.
["]	

u. s. GOVERNMENT PRINTING OFFICE 16-28520-

Subdivision of T. 7 S., R. 1 W. Chains. Point for the 4 sec. cor. of secs. 20 and 21, in a wash, 15 lks. wide, 5 ft. deep, course NE. 40.00 Establish a witness 4 sec. cor. of secs. 20 and 21. 40.50 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground and in a mound of stone, 5 ft. base, to top, with brass cap mkd. s 20\s 21 1947 Thence along a low spur, slopes generally N. Point for the cor. of secs. 16, 17, 20, and 21. 80.00 Set an iron post, 2 ins. diam., 3ft. long, 30 ins. in the ground, with brass cap mkd. T7S R1W S 17 S 16 S 20 S 21 Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. and, rolling. poil, gravelly, 3rd. rate.
Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo and cactuses. From the cor. of secs, 15, 16, 21, and 22, S. 89° 59' W., bet. secs. 16 and 21. Over rolling land, through scattering timber. Asc. 13 ft. over a NE. slope. 1.45 Spur, slopes Nw.; desc. 40 ft. over a Sw. slope. 10.85 Foot of descent. 15.70 Begin ascent of 30 ft. over NE. slope. 20.70 Spur, spur, slopes NW.; desc. 20 ft. over a SW. slope. 24.30 Wash, 25 lks. wide, 5 ft. deep, course N. 37.40 Wash, 20 1ks. wide, 4 ft. deep, course N. 40.04 Point for the cor. of secs. 16 and 21. Det an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

S 16

1947

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of oor.

U. S. GOVERNMENT PRINTING OFFICE

Subdivision of T. 7 S., R. 1 $\mbox{W.}$

	Chains.	
		Asc. 70 ft. over an E. to NE. slope.
•	45.70	Spur, slopes N.; desc. 60 ft. over a W. slope.
	50.05	Wash, 25 lks. wide, 4 ft. deep, course N. 10° W.
	52.75	Wash, 20 lks. wide, 3 ft. deep, course N.
	60.20	Wash, 10 lks. wide, 2 ft. deep, course N.
	70.00 /	Spur slopes N. Desc. 35 ft. over a W. slope.
	76.95	Wash, 30 lks. wide, 5 ft. deep, course N.
	80.08	The cor. of secs. 16, 17, 20, and 21.
		Land, rolling. Soil, gravelly, 3 rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, credsote brush, ocotillo and cactuses.
•		N. 0° 02' W., bet. secs. 16 and 17.
		Over rolling desert through medium desert growth.
	18.00	Wash, 40 lks. wide, 4 ft. deep, course N. 20° W.; asc. 42 ft
	29.00	Spur, slopes NW. desc. 17 ft.
	40.00	Point for the 4 sec. cor. of secs. 16 and 17.
	٠	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		s 17 = 16 1947
	,	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
		Thence along a spur, slopes generally N.
	79•95	Desc. 29 over N. end of spur.
	80.00	Point for the cor. of secs. 8, 9, 16, and 17.
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
		T7S R1W S 8 S 9 S 17 S 16
		1947
	41	from which
	-	An ironwood, 10 ins. diam., bears S. 30° E., 15 lks. dist., mkd. T7S R1W S16 BT.
		An ironwood, 18 ins. diam., bears N. 514° W., 114 lks. dist., mkd. T7S R1W S8 BT.
		Raise a mound of stone, 2 ft. base, lift. high w. of cor.

\$2000 4002

Chains	Land, gravelly and sandy, 3rd. rate. imber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, and cactuses.
	From the cor. of secs. 9, 10, 15, and 16,
-	S. 89° 59! W., bet. secs. 9 and 16.
	Over rolling land through scattering desert timber.
6.05	Drain, course NW.
15.15	Wash, 20 lks. wide, 1 ft. deep, course N. 15° W.
30.00	Wash, 20 lks. wide, 3 ft. deep, course N. 10° E.
32.00	Wash, 15 lks. wide, 2 ft. deep, course N. 10° E.
40.03	Point for the 4 sec. cor. of secs. 9 and 16.
1	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	\$\sigma \frac{\sigma \fra
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
51.75	Wash, 40 lks. wide, 3 ft. deep, course N. 20° W.
54.80	Wash, 20 lks. wide, 2 ft. deep, course N. 30° W.
62.65	Wash, 10 lks. wide, 2 ft. deep, course N. 30° W.; asc. 20 ft. over an E. slope.
77.25	Spur, slopes N. 10° W.; desc. 48 ft. over a W. slope.
79 • 75	Wash, 15 lks. wide, 2 ft. deep, course N. 30° W.
79 • 99	Aerial gunnery range bdy. marker bears North, 2 lks. dist.
80.06	The cor. of secs. 8, 9, 16, and 17.
	Land, rolling, Poil, sandy to rocky, 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, ocotillo, creosote brush, cactuses, catclaw.
	N. 0° 02' W., bet. secs. 8 and 9.
	Over rolling land, through medium dense desert growth.
0.40	Wash, 15 lks.wide, 2 ft. deep, course NW.; asc. 20 ft. along a SW. slope.
11.10	Drain, course W.
18.00	Drain, course W.
23.00	Drain, course NW.
40:00	Point for the z sec. cor. of secs. 8 and 9.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Continue along W. side of spur, nearly level, bears N. & S.

55.00 Descend 30 ft. over NE. slope.

60.00 Foot of slope, thence over bottom land.

70.00 Drain, course NE.

72.00 Enter wash area, drains N. 10° W.

78.90 Main wash, 20 lks. wide, 3 ft. deep, course N. 10° W.

80.00 Point for the cor. of secs. 4, 5, 8, and 9.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly, 2nd. and 3rd. rates.
Timber, paloverde, ironwood, and mesquite.
Undergrowth, creosote brush, ocotillo, cactuses, catclaw.

From the cor. of secs. 3, 4, 9, and 10,

S. 89° 59' W., bet. secs. 4 and 9.

Over rolling land, through medium dense desert growth.

6.25 Wash, 10 lks. wide, 4 ft. deep, course N. 10° W.

31.55 Wash, 15 1ks. wide, 4 ft. deep, course N. 10° W.

35.50 Wash, area, 3 chs. wide, drains NW.; series small drains.

.37.55 Drain course N.

40.03 Point for the asec. cor. of secs. 4 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

1947

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

FOCK 6367

Chains	•
48.00	Drain, course NW.
51.85	Wash area, 150 lks. wide, drains N.
67.45	Wash, 15 lks. wide, 5 ft. deep, course N. 10° W.
79.65	Enter Wash, area, drains N. 10° W.
80.06	The cor. of secs. 4,5, 8, and 9.
•	Land, rolling. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, cactuses, catsclaw.
,	
	The cor. of secs. 4, 5, 32, and 33 on the N. bdy. of the Tp. is a point on the N. shoulder of Arizona State. Highway No. 84.
•	From this cor. the witness cor. of secs. 4, 5, 32, and 33, bears S. 89° 59' E., 3.00 chs. dist., marked with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
	S. 0° 03' E., bet. secs. 4 and 5.
•	Over nearly level land draining SW, through scattering desert timber.
0.09	N. edge of asphalt paving.
0.26	Center-line of Arizona State Highway No. 84, bears S. 72° 45' E., to Casa Grande, and N. 72° 45' W. to Gila Bend.
0.43	S. edge of asphalt paving.
18.60	Wash, 15 lks. wide, 1½ ft. deep, course SW.
. 20.00	Enter wash area, drains W. through medium dense growth of desert timber and undergrowth.
30.00	Bender Wash, 70 lks. wide, 3½ ft. deep, course W.
31.00	Leave wash area, drains W.
39.87	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
•	s 5 s 4. 1947
,	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
40.65	Wash, 15 lks. wide, 3 ft. deep, course N. 15° W.
66.85	Wash, 20 lks. wide, 3½ ft. deep, course N. 60° W.
75.00	Enter wash area, drains N. 10° W.
79.87	The cor. of secs. 4, 5, 8, and 9.

36.

Subdivision of T. 7 S., R. 1 W.

Chains. Land, nearly level. Soil, sandy, 2nd rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, cactuses, catsclaw. The cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp. is marked with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record. N. 0° 03' W., bet. secs. 31 and 32. Over broken hills through scattering desert growth. Asc. 141 ft. over a SE. slope. Short rocky spur, slopes E; thence along an E. slope. 12.40 Spur, slopes E. about 3 chs. then N.; desc. 323 ft. 20.90 along a broken NW. slope. 34.50 Drain, at head, course NW.; asc. slightly over a SW.slope. 40.00 Point for the 4 sec. cor. of secs. 31 and 32. Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top, with brass cap mkd. s 31 s 32 The cor. is on a short spur, slopes W.; desc. 143 ft. over a broken MW. slope. 58.30 Wash, 1 ch. wide, 10 ft. deep, course NW. Wash, 15 lks. wide, 3 ft. deep, course W.; asc. 123 ft. over a S. slope. 61.4071.30 Slope changes to E.; continue descent. 73.20 Spur, slopes E.; desc. 80 ft. over a broken N. slope. 80.00 Point for the cor . of secs. 29, 30, 31, and 32. Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T7S R1W S 30 S 29 1947

Land, broken hills.
Soil, rocky, 4th. rate.
Timber, paloverde, ironwood; undergrowth, creosote brush, ocotillo, and cactuses.

FOOK 4367

Subdivision of T. 7 S., R. 1 W.

Chain	s •
	From the cor. of secs. 28, 29, 32, and 33,
,	N. 89° 55' W., bet. secs. 29 and 32.
	Over rolling hills, through medium dense desert growth along the washes.
	Asc. 70 ft. over a SE. slope.
9.90	Spur, slopes SW. from Hill; desc. 20 ft. over NW. slope.
13.00	Drain, course NW.
18.00	Drain, 5 lks. wide, 2 ft. deep, course N. 10°E.
20.45	Desert road, bears N. to Bender Ranch, and S. to cabin.
21.21	From this point;
	The NE. cor. of a l2ft.xl2ft. wood frame cabin, bears S. 56° 47' W., 2.46 chs. dist.
	The SE. cor. of a saguaro rib corral, bears S. 59° 40' W. 181 lks. dist.
	A well, bears S. 47° 08' W., 4.90 chs. dist., 6x6 ft., 10 ft. deep to water surface, cribbed with wood plank. The well is in the bottom of a wash, 40 lks. wide, 12 ft. deep, course N., at the junction of washes from S. 10° E., and S. 10° W.; a seep in the wash is 1 ch. N. of the well.
24.80	Wash, 40 lks. wide, 12 ft. deep, course N. 5° E.; asc. 193 ft. over a NE. slope.
38.42	Spur, slopes SE.; desc. 25 ft. over SW. slope.
39•97	Point for the ½ sec. cor. of secs. 29 and 32.
a	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground and in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	\frac{1}{4} \frac{\text{S} \cdot 29}{\text{S} \cdot 32}
*	1947
	Asc. 31 ft. along broken S. slope.
44.65	Top of ascent, desc. 23 ft. along broken S. slope.
49.30	Foot of descent, asc. 23 ft. along a broken S. slope.
55.70	Spur, slopes S.; desc. 145 ft. over a broken W. slope.
63.85	Wash, 20 lks. wide, course N. 20° W.; asc. 40 ft. over a broken NE. slope.
68.10	Spur, slopes N., desc. 75 ft. over a W. slope.
71.15	Wash, 20 lks. wide, 6 ft. deep, course N. 10° W.; asc. 102 ft. over an E. slope.
79•94	The cor. of secs. 29,30,31, and 32.
	Land, rolling to broken hills. Soil, gravelly and rocky, 3rd. and 4th. rates. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.

U. S. GOVERNMENT PRINTING OFFICE

16-28520-1

	Chains.	
		The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp. is marked with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.
		N. 89° 56' E., bet. secs. 30 and 31.
•		Over broken hills, through scattering desert growth.
	5.20	Wash, 15 lks. wide, 3 ft. deep, course N.
	12.70	Junction of washes from S. and SE., 80 lks. wide, 10 ft. deep, course N. 10° W.
	21.40	Wash, 2 chs. wide, 10 ft. deep, course N. 50° W.
	35.70	Recross wash, 1 ch. wide, 15 ft. deep, course S. 60° W. Asc. 23 ft. over a SW. slope.
	38.68	Point for the 4 sec. cor. of secs. 30 and 31.
	•	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
-	•	½ \$\frac{3}{5} \frac{30}{5}
		1947
	· .	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
		Asc. 30 ft. over a SW. slope.
	45•30	Wash, 50 lks. wide, 20 ft. deep, course, SW.; asc. 76 ft. along broken SW. slope.
	58.40	Spur, slopes S.; continue to asc. 25 ft. over a S. slope.
	65.30	Slope changes from S. to SE.; desc. 18 ft.
	72.40	Drain, 10 lks. wide, 2 ft. deep, course S.; asc. 63 ft. over a W. slope.
	77.70	Spur, slopes N.
	78.68	The cor. of secs. 29, 30, 31, and 32.
		Land, broken hills. Soil, rocky, 4th. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	-	
		N. 0° 03' W., bet. secs. 29 and 30.
		Over broken hills, through scattering desert growth.
	0.50	
	7.25	Wash, 5 lks. wide, course NE.; asc. 92 ft. over a SE. slope.
	11.60	Spur, slopes NE.; desc. 148 ft. over a NW. slope.

	*	
	Chains	•
	16.90	Wash, 5 lks. wide, course NE.; asc. 184 ft.
	23.70	Saddle in spur, slopes NE.; desc. 298 ft. over a NW, slope.
	29.70	Spur, slopes NW.; continue descent over NE. slope.
	39.40	Wash, course SE. for 1 ch. thence NE; asc. 53 ft. over a general SE. slope.
	40.00	Point for the 4 sec. cor. of secs. 29 and 30.
		Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
		S 30 S 29
		From this cor., a concrete and masonry dam, bears N.65° E. 33 chs. dist.
		Asc. 27 ft. over a SE. slope.
.	42.60	Spur, slopes NE.; desc. 113 ft. over a broken NW. slope
	49.75	Spur, slopes W.; desc. 57 ft. over a N. slope.
	56 , 40	Wash, 30 lks. wide, 5 ft. deep, course N. 70° E.
	63.50	E. slope of small hill; desc. 23 ft.
	66.90	Recross wash, 35 lks. wide, 6 ft. deep, course N. 30° W.
	72.50	Wash, 10 lks. wide, course N. 80° W.; asc. 21 ft.
	76.50	Spur; slopes NW.; desc. 28 ft. over a N. slope.
	80.00	Point for the cor. of secs. 19, 20, 29, and 30.
	•	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
		T7S R1W S 19 S 20 S 30 S 29
		Land, broken. Soil, rocky, 4 th. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, and cactuses.

From the cor. of secs. 20, 21, 28, and 29,

N. 89° 56' W., bet. secs. 20 and 29.

Over rolling land, through medium dense desert growth along the washes.

Asc. 56 ft. over a SE. slope.

'7.00 Spur, slopes N; desc. 60 ft. over a 7. slope.

Chains.	
14.00	Wash; 90 lks. wide; 10 ft. deep, course N.
20:00	Desert road, bears S. to cabin and N. to Bender Ranch.
23.00	Wash; 15 lks. wide, 5 ft. deep, course N.; asc. 23 ft.
25.85	Spur, slopes N.; desc. 34 ft.
30.80	Wash, course M.; asc. 50 ft. over an E. slope.
35.75	Spur, slopes N. 10° W.; desc. 61 ft. over a W. slope.
39.50	Wash, 10 lks. wide, 3 ft. deep, course N. 20° W.
40.01	Point for the 4 sec. cor. of secs. 20 and 29.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	1947
3	Raise a mound of stone, 3 ft. base, $l\frac{1}{2}$ ft. high, N. of cor.
	Asa. 12 ft. over E. slope.
41.25	Spur, slopes N.; desc. 23 ft.
44.00	Wash, 25 lks. wide, 2 ft. deep, course N. 20° W.; asc. 34 ft.
50.40	Spur, slopes M.; desc. 35 ft.
59.10	Edge of E. cut-bank, 20 ft. high, bears N. and S.
60.00	Center of large wash, course N.
61.25	W. cut-bank, 25 ft. high, bears N. and S.
6 6.80	Wash, 10 Iks. wide, course N. 15° W.; asc. 17 ft.
71.55	Spur, slopes N. 25° w.; desc. 24 ft.
74.10	Wash, 15 lks. wide, course N. 10° W.
80.02	The cor. of secs. 19, 20, 29, and 30.
	Land, rolling. Soil, gravelly and sandy, 3 rd. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	The cor. of secs. 19, 24, 25, and 30 on the W. bdy. of the Tp. is marked with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, 1½ ft. high, to top, marked an witnessed as described in the official record.
	N. 89° 59' E., bet. secs. 19 and 30.
	Over low broken hills, through scattering desert growth.
1.30	Wash, 20 lks. wide, 3 ft. deep, course S. 80° W.; asc. 66 ft. over a S. slope.

	' '
Chain	5 •
10.90	Low saddle in rocky spur, bears N. and S.; desc. 69 ft. over an E. slope.
17.90	Wash, 80 lks. wide, 20 ft. E. bank, course N. 20° E.; asc. 57 ft. over a NW. alope.
23.60	Rocky spur, slopes S. 10° W. from small peak; desc. 77 ft. over a broken rocky SE. slope.
35.60	Drain, 10 lks. wide, course N. 10° E.
38.63	Point for the 4 sec. cor. of secs. 19 and 30.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
. ,	\$\frac{\sim 19}{\sigma}\$.
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Asc. 12 ft. over a W. slope.
39.50	Short spur, slopes N.
44.90	Drain, 10 lks. wide, course N.
47.60	Top of SE. slope; desc. 60 ft.
57.20	Wash, 125 lks. wide, 20 ft. right bank, course N. 65° E., Asc. 90 ft.
62.90	Wash, 10 lks. wide, 15 ft. deep, course N.
66.50	Wash, 50 lks. wide, 20 ft. deep, course NW. for 4 chs. then N.
73.60	Spur, slopes NW.; desc. 29 ft. over NE. slope.
7 8.63	The cor. of secs. 19, 20, 29, and 30.
· -	Land, broken and rolling. Soil, gravelly and rocky, 4 th. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	N. 0° 03' W., bet. secs. 19 and 20.
	Over low rolling gravel hills, through medium dense desert growth along the washes.
4.60	Spur, slopes N. 60° W.; desc. 34 ft. over a N. slope.
9.90	Wash, 15 lks. wide, course W.; asc. 41 ft. over a S. slope.
13.70	Wash, 20 lks. wide, course W.; continue ascent.
17.85	Spur, slopes N. 15° W.; desc. 71 ft. over a N. slope.
32.60	Wash, 25 lks. wide, course NW.; asc. 25 ft.
39•75	Spur, slopes W.

Chains.	
40.00	Point for the \$ sec. cor. of secs. 19 and 20.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
. *	S 19 S 20 1947
	from which
• •	An ironwood, 4 ins. diam., bears N. 35½° E., 53 lks. dist., mkd. ½ S20 BT.
	An ironwood, 7 ins. diam., bears N. 77½° W., 38 lks. dist., mkd. 4 S19 BT.
71.00	Beginning of descent; from this point a spur slopes NW. and another NE.; desc. 30 ft. along a NW. slope.
80.00	Point for the cor. of secs. 17, 18, 19, and 20.
.*	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T7S R1W 518 S 17 S 19 S 20 1947
,	from which
	A paloverde, 8 ins. diam., bears N. 824° E., 81 lks. dist., mkd. BT.
•	An ironwood, 3 ins. diam., bears S. 75% E., 33 lks. dist., mkd. BT.
·	An ironwood, 3 ins. diam., bears S 134° W., 26 lks. dist., mkd. BT.
·	An ironwood, 4 ins. diam., bears N. 334° W., 41 lks. dist., mkd. BT.
	Land, rolling. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde, and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	From the cor. of secs. 16, 17, 20, and 21,
	S. 89° 59' W., bet. secs. 17 and 20.
<u>-</u>	Over rolling land, through medium dense desert growth along the washes.
4.50	Wash, course N. 10° W., 15 lks. wide, 2 ft. deep.
5.90	Desc. 36 ft. over a W. slope.
13.25	Wash, 1 ch. wide, course N.
15.90	Wash, 20 lks. wide, course N. 30° E.; asc. 35 ft.
	40.00 71.00 80.00 5.90 13.25

E 4867

Subdivision of T. 7 S., R. 1 \mbox{W} .

-	Chains	
	18.50	Eow spur, slopes N.
	27.60	Wash, 25 lks. wide, 2 ft. deep, course N.
	,	
	30.30	Wash, 25 lks. wide, 3 ft. deep, course N.
	34.15	Road, bears N. to Bender Ranch and S. to cabin.
	38.25	Wash, 15 lks. wide, 3 ft. deep, course N.
	40.00	Point for the ‡ sec. cor. of secs. 17 and 20.
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	-	$\frac{1}{4} \frac{S}{S} \frac{17}{20}$
		1947
		from which
		An ironwood, 10 ins. diam., bears N. 11° E., 61 lks. dist., mkd. 4 S 17 BT.
		An ironwood, 10 ins. diam., bears S. 24° E., 99 lks. dist., mkd. ½ S20 BT.
	41.00	Wash, 120 lks. wide, course N.
	49.15	Wash, 20 lks. wide, course N.
	53.50	Wash, 20 lks. wide, course N. 10° E.
	69.90	Wash, 15 lks. wide, 3 ft. deep, course N.
	74.00	Wash, 80 lks. wide, 15 ft. E. bank, course N. 35° W. Asc. 17 ft.
	78.60	Spur, slopes N.; desc. 13 ft.
	80.00	The cor. of secs. 17, 18, 19, and 20.
		Tand, rolling, Soil, gravelly, 3rd. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo and cactuses.
	,	The cor. of secs. 13, 18, 19, and 24 on the W. bdy. of the Tp. is marked with an iron post, 2 ins. diam., 8 ins.
		above ground, firmly set, marked and witnessed as described in the official record.
		S. 89° 56 ' E., bet. secs. 18 and 19.
		Over rolling desert, through medium dense desert growth along the washes.
		Desc. 15 ft. over an E. slope.
	4•55	Wash, 30 lks. wide, 3 ft. deep, course N.; asc. 24 ft.
	7.90	Spur, slopes N.
	14.35	Wash, 35 lks. wide, course N. 20° E.
		•

		Data Tiblion of I. D., I. I II.
-	Chains.	
	17.05	Spur, slopes N.; desc. 14 ft.
	19.00	Wash, 120 lks. wide, 18 ft. E. bank, course N.
	30.90	Wash, 10 lks. wide, 4 ft. deep, course N. 20° E.
	35.40	Wash, 20 lks. wide, 6 ft. banks, course N. 10° E.
	38 . 57	Point for the ½ sec. cor. of secs. 18 and 19.
	!	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		\$\frac{18}{4} \text{ S 19} \\ 1947
	·	
	,	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
	55.15	Wash, 20 lks. wide, 15 ft. W. bank, course NE.
	56.05	Wash, 40 lks. wide, course NE.
	59 .7 5	Wash, 20 lks. wide, 5 ft. deep, course N. 10° W.
	63.35	Wash, 80 lks. wide, 15 ft. banks, course N.
	71.65	Wash, 25 lks. wide, course N.; asc. 35 ft.
	7 3•55	Spur, slopes N ;desc. 20 ft.
	78.57	The cor, of secs. 17, 18, 19, and 20.
	-	and, rolling. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde and ironwood; undergrowth, creosote brush, ocotillo, cats claw, and cactuses.
		N. 0° 03' W., bet. secs. 17 and 18.
	•	Over gently rolling land, through medium dense desert growth.
	14.20	Low spur, slopes NW.; desc. 23 ft.
	32.80	Wash, 1.50 chs. wide, course N. 20° W.
	35.50	Recross wash, course N. 30° E. for 2 chs. then N.
	40.00	Point for the 4 sec. cor. of secs. 17 and 18.
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		s 18 s 17 1947
	,	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	52.60	Wash, 15 lks. wide, course N. 30° E.; thence along wash area.
	,	

13.
18.
18.
18.
., 30 ins. in the
\mathbf{e} , $\mathbf{l}_{\mathbf{z}}^{\mathbf{l}}$ ft. high,
r, bears N. 71°
ates. ctuses,
esert growth.
Lope.
30° W.
ese N. 15° E.
rse II. 19 E.
-7•
30 ins. in the
, jo ins. in one
la ft. high,
20° E.
10° E.

Chains	
50.14	Road, bears N. to Bender Ranch, and S. to Cabin.
54.40	Wash, 15 lks. wide, 3 ft. deep, course N.
68.70	Wash, 80 lks. wide, course NW.
76.20	Wash, 5 lks. wide, 6 ft. deep, course N. 15° W.
79.98	The cor. of secs. 7, 8, 17, and 16.
	Land, rolling to nearly level. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, cactuses, eats claw.
	The cor. of secs. 7, 12, 13, and 10 on the W. bdy. of the Tp. is marked with an iron post, 2 ins. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record.
,	S. 89° 56' E., bet. secs. 7 and 18.
	Over rolling land, through medium dense desert growth.
5.25	Low spur, desc. 16:ft.
7.25	Wash, 80 lks; wide, course N.
21.65	Wash, 20 lks. wide, 5 ft. deep, course N.
22.95	Wash, 15 lks. wide, 5 ft. deep, course NW.; asc. 23 ft.
27.25	Low spur, slopes N.; desc. 25 ft.
33.65	Wash, 110 lks. wide, 20 ft. deep, course N. 70° E.
37.25	Wash, 10 lks. wide, 15 ft. deep, course N. 15° E.
38.54	Point for the 2 sec. cor. of secs. 7. and 18.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	½ <u>\$ 7</u> \$ 18
	1947
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
40.55	Wash, 20 lks. wide, 10 ft. deep, course N.
49 • 35	Enter wash bottom area.
50.80	Wash, course N.
53.00	Leave wash bottom area.
56.15	Wash, 30 lks. wide, 7 ft. deep, course N. 30° E.
60.75	Low spur, slopes N.
65.75	Wash, 25 lks. wide, course N.
73.65	Wash, 15 lks. wide, 3 ft. deep, course N.

	Chains.		
	7 7.85	Wash, 50 lks. wide, course N.	
	78.54	The cor. of secs. 7, 8, 17, and 18,	
•		Land, gently rolling. Soil, sandy and gravelly, 2nd and 3rd. rates. Timber, paloverde, ironwood, and mescuite. Undergrowth, creosote brush, ocotillo, cactuses, cats claw.	
		N. 0° 03' W., bet. secs. 7 and 8.	
		Over wash bottom area through dense desert growth.	į
	1.90	Wash, 1 ch. wide, course N. 20° E.	
	10.50	Drain, course NE.; leave wash area, continue over open nearly level land.	,
	35.20	Drain, 10 lks. wide, 1 ft. deep, course NW.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.	
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.	
	·	s 7 s 8	
,		1947	
		Raise a mound of stone, 2 ft. base, log ft. high, ". of cor.	
	49.60	Enter wash bottom area, drains NE.;	
	53.00	Wash, 30 lks. wide, course N. 35° E.	
	61.50	Recross wash, 40 lks. wide, course N. 30° W.	
•	77.40	Wash, 1 ch. wide, course NW. from S. 25° E.	•
	80.00	Foint for the cor. of secs. 5, 6, 7, and 8.	
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.	
		T7S R1W S 6 S 5 S 7 S 8	
		from which	
		A paloverde, 6 ins. diam., bears N. 252° E., 66 lks. dist, mkd. T7S RlW S5 BT.	
		An ironwood, 10 ins. diam., bears S. 823° E., 154 lks. dist., mkd. T7S R1W S8 BT.	
		An ironwood, 3 ins. diam., bears N. 52% W., 150 lks. dist., mkd. T7S RlW S6 BT.	
	,	Raise a mound of stone, 2 ft. base, l ₂ ft. high, W. of cor.	
		and, slightly rolling; Soil, 2nd. and 3rd rates. Timber, paloverde and ironwood; undergrowth, greasewood.	
		U. S. GOVERNMENT PRINTING OFFICE 16—28520—1	

Chains	
	From the cor. of secs. 4, 5, 8, and 9,
	S. 89° 56' W., bet. secs. 5 and 8.
	Over nearly level land, through scattering desert growth.
0.75	Wash, 20 lks. wide, 2 ft. deep, course N. 10° W.
11.00	Drain, course N.
22.50	Wash, 15 lks. wide, 4 ft. deep, course N. 20° W.
35.24	Dim desert road, bears N. and S.
40.03	Point for the 4 sec. cor. of secs. 5 and 8.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	4 <u>S 5</u>
	1947
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, $\tilde{\mathbf{N}}$. of cor.
44.00	Wash, 80 lks. wide, 10 ft. E. bank, course NW.
47.00	Wash, 30 lks. wide, course NW.
50.20	Wash, 25 lks. wide, course N. 25° W.
59.20	Wash, 25 lks. wide, course N. 30° W.
65.00	Wash, 20 lks. wide, 3 ft. deep, course N. 20° W.
72.40	Road, bears S. to cabin and N. to Bender Ranch.
78.70	Enter Wash bottom area, drains NW.
80.06	The cor. of secs. 5, 6, 7, and 8.
	Tand, level to slightly rolling. Soil, sandy and gravelly, 2nd. and 3rd. rates. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, cactuses, cats claw.
	The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp. is marked with an iron post, 2 ins. diam., 10 ins. above ground, firmly set, marked and witnessed as described in the official record.
4 - 4	S. 89° 59' E., bet. secs. 6 and 7.
,•	Over slightly rolling land, through medium dense desert growth.
8.20	Wash, 20 lks. wide, 4 ft. deep, course N.
13.80	Drain, 10 lks. wide, course N. 20° W.
18.50	Desert road, bears NE. to Bender Ranch, and SW.
29.10	Wash, 1.80 chs. wide, 7 ft. banks, course N.

7.36	ومنازعتها
. ,	1397

	Chains.	
	36.70	Wash, 12 lks. wide, 2 ft. deep, course N. 10° W.
	38.51	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		4 S 6 S 7
		1947
		Raiss a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	41.50	Low spur, slopes N.
	60.00	Enter wash bottom area, drains N. 25° W.
	64.00	Wash, 35 lks. wide, course NW.
	67.00	Wash, 60 lks. wide, course N.
	73.80	Wash, 75 lks. wide, course N. 35° W.
	77.00	Wash, 50 lks. wide, course N. 30° W.
•	78.51	The cor. of secs. 5, 6, 7, and 8.
		Land, slightly rolling. Soil, sandy and gravelly, 2nd. and 3rd. rate. Timber, paloverde, ironwood, and mesquite. Undergrowth, creosote brush, ocotillo, cactuses, cats claw.
•		The cor. of secs. 5, 6, 31, and 32 on the N. bdy. of the Tp. is marked with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record. S. 0° 03' E., bet. secs. 5 and 6.
	·	Over nearly levelland, through medium dense desert growth along the washes.
	6.50	Bender Wash, 1 ch. wide, 4 ft. N. bank, course M. 70° W.
	10.70	Leave wash area, drains N. 70° W.
	35.50	Prain, 5 lks. wide, course NW.
	39.98	Point for the ½ sec. cor. of secs. 5 and 6.
		Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		s 6 5 5 1947
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	42.30	Wash, 15 lks. wide, course NW.
	46.10	Desert road, bears S. 10° E. to cabin, and N.20° W. to
		Bender Ranch.

BOOK 4867

Subdivision of T. 7 S., R. 1 W.

Chains.	
56.00	Drain, 10 lks. wide, course N. 30° W.
65.00	Wash, 30 lks. wide, course N. 15° W.
74.80	Enter Wash, area, drains NW.

79.98 The cor. of secs. 5, 6, 7, and 8.

Land, nearly level to slightly rolling.
Soil, sandy to gravelly, 2nd. and 3rd. rates.
Timber, paloverde, ironwood, and mesquite.
Undergrowth, creosote brush, ocotillo, cactuses, catsclaw.

FINAL TEST OF SOLAR ATTACHMENTS.

March 15; At the station in sec. 6, T. 7 S., R. 1 W., at 9h 00m a.m. app. t., make the proper settings on the latitude and declination arcs and orient the instruments with the solars. The lines of sight agree with the meridian established by Polaris observation.

At 3h 00m p.m., app. t., repeat the tests of the solars. The lines of sight agree with the meridian established by Polaris observation.

March 15, 1947.

GENERAL DESCRIPTION

T. 7 S., R. 1 W. embraces almost the entire width of the floor of a desert valley and extends southward up a gradual slope and a mile into the foot hills of the higher mountains. The eastern tier of secs. lies on the E. side of a very low drainage divide that diverts, at the N. tier of secs., the general northerly drainage of the Tp. to the E. by one main wash, and to the W. through Bender Wash. The mean elevation is about 2500 ft. above sea level, the southern portion nearing 3000 ft. and the northern portion lowering to approximately 2000 ft. at the lowest point in sec. 6.

The soil varies from sandy loam, in the most level of the N. portion; through gravelly and rocky on the rolling spurs and low hills of the central portion; to decomposed granite, loose rock, and igneous outcroppings in the higher S. portion.

A medium heavy stand of paloverde blankets the Tp. except for the creosote brush flats in secs. 2 and 11. The margins of the washes and the wider wash areas support a medium dense growth of paloverde, ironwood, mesquite, and cats claw, many trees attaining near maximum size.

The undergrowth, varying in density with the steepness of the slope, consists of creosote brush, ocotillo, cactuses, and a relatively excellent growth of native grasses and amuals. The latter were in a dormant state due to a complete lack of winter rainfall.

The Tp. affords good desert grazing for its only industry cattle raising.

The only natural occurring water found was a seep, in sec. 32, used by the javali that seem to be plentiful in this area. A shallow dug well is near the seep. The only other developed water in the Tp. is another well at the Bender Ranch, unoccupied, in sec. 6, and two small run-off reservoirs, one in sec. 2 and the other in sec. 29.

Arizona State Highway No. 84 bears easterly through the Tp. from the cor. of secs. 4, 5, 32, and 33 on the N. bdy. leaving at approximately 20 chains N. of the cor. of secs. 1, 6, 7, and 12 on the E. bdy.

There are no patented mineral claims in the Tp., some past prospecting is evident and a few mineral claim location monuments were seen.

4-680 (Revised May 1934)

BCCK 4367

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

CAPACITY
Engineering Aide.
Principal Assistant.
Principal Assistant.
Chainman.
Cha nman.
Flagman.
Flagman.
Moundsman.
Moundsman.
Moundsman.
Axman.
Axman.
Axman.
·

CERTIFICATE OF SURVEYOR

I, G. Marvin Litz	HEREBY CERT	IFY upon honor that, in
pursuance of special instructions bearing date of the	lst. day of Decem	nber , 193,7
received from the district cadastral engineer for	· 	with assignment
instructions dated February 18,1947, I hav	surveyed the subdivi	sion of
T. 7 S., R	. 1 W.,	-
of the Gila and Salt River Meridian		
represented in the foregoing field notes as having bee	n executed by me and under my	direction; and that said
survey has been made in strict conformity with said	instructions, the Manual of Ins	tructions for the Survey
of the Public Lands of the United States, and in the	specific manner described in the	e foregoing field notes.
Glendale, California.	I. Maro	in Lik
May 13, 1947.	Cadastral E	nginear
	Bureau of Land Mana Office of Surenvison of Washington, D. C.	Sunver s,
The foregoing field notes of the survey oft	Office of Surravisor of Washington, D. C.	SURVETS, 1 SEP 1 5 1949 19 19 19 19 19 19 19 19 19 19 19 19 19 1
T. 7 S.,	Office of S urravisor of Washington, D. C. ne subdivision of R. 1 W.,	SUNVETS, [13FP 1 5 1949 , 19
executed by	Office of Surravisor of Washington, D. C. ne subdivision of R. 1 W.,	SURVETS, 1 3 FP 1 5 1949 , 19 , and assignment
executed by G. Marvin Litz under special instructions dated December 1,	Office of Surravisor of Washington, D. C. ne subdivision of R. 1 W.,	SURVETS, 1 3 FP 1 5 1949 , 19 , and assignment
executed by G. Marvin Litz under special instructions dated December 1, instructions dated February 18, 1947	Office of Surenvison of Washington, D. C. ne subdivision of R. 1 W.,	SUNVETS, 1 SEP 1 5 1949, 19, 19, and assignment critically examined, and
executed by	Office of Surenvison of Washington, D. C. ne subdivision of R. 1 W.,	SUNVETS, 1 SEP 1 5 1949, 19, 19, and assignment critically examined, and
executed by	Washington, D. C. The subdivision of R. 1 W., 1937	SUNVETS, 1 SEP 1 5 1949 , 19 , and assignment critically examined, and
executed byG. warvin Litz	Washington, D. C. The subdivision of R. 1 W., 1937	, and assignment critically examined, and eld notes, and the survey
executed byG. warvin Litz	Office of Surravison of Washington, D. C. The subdivision of R. 1 W., 1937 ———————————————————————————————————	, and assignment critically examined, and eld notes, and the survey