



UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Area 2
Post Office Box No. 659
Salt Lake City 10, Utah

IN REPLY REFER TO:

E
4392

BOOK 4392



DATE RECORDED 7/25 INITIALS ECR 1954
RCC July 20, 1954

STATE SUPV. _____
ADM. ASST. _____
REC. & EXP. _____ ACTION _____
LAND SECTION _____ COMMENTS _____
PROPERTY _____ INFORM _____
E. ASST. _____
RETURN TO _____

Memorandum

To: Office Cadastral Engineer E. H. Kimmell
Through BLM State Supervisor for Arizona

From: Cadastral Engineering Staff Officer

Subject: Exchange Survey No. 678, Arizona

Further reference is made to your memorandum of July 12, 1954, concerning the original field notes of Tract C, Exchange Survey No. 678.

We have gone through the Arizona files that were brought to Salt Lake City last May. We found no original field notes of the above-described tract. The only record that appears is contained in a microfilm roll. Duplicate copies thereof are enclosed.

If these copies are insufficient for your needs, I would suggest that you write the Director and request a certified copy.

BOOK 4392

Leo M. Petersen
Leo M. Petersen
Cadastral Engineering
Staff Officer

Enclosure

The attached are a copy of a portion of the notes of the survey of Tract C - HES 678

The original (complete) in file HES-678

4392

Chains

The smaller legal subdivisions of the S. half of sec. 12, which were required to establish the boundaries of Tract C were executed in accordance with the Manual of Surveying Instructions. The following field notes are the record of only those portions of the legal subdivisions which are boundaries of the tract. The corners of the subdivision were not monumented except for those corners which are angle points of the tract.

Survey of Tract C

Beginning at the point for Angle Point 1 of Tract C, at the intersection of the south line of U. S. Highway No. 89-A right-of-way and the S-S-S 1/256 sec. line, at a point which bears N. 89° 39' W., 4.68 chs. dist. from the C-S-S-SE 1/256 cor. of sec. 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

A P 1
T R C
S 12
T17N R5E
1949

N. 81° 10' W., on N. bdy. of Tract C and along the S. line of the highway right-of-way.

42.12 Point for Angle Point 2 of Tract C.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

A P 2
T R C
1949

N. 82° 52' W., continuing along S. line of highway right-of-way.

2.605 Point for Angle Point 3 of Tract C, at the intersection of the S. line of the highway right-of-way and the W-W 1/64 sec. line.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T17N
R5E A P 3
S 12 T R C
1949

S. 0° 08' W., on W. bdy. of Tract C, and along the W-W 1/64 sec. line.

1.58 Point for the SW-SW 1/64 sec. cor. of sec. 12 designated as Angle Point 4 of Tract C.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

BOOK 4892

Chains	
	<p style="text-align: center;">S 12 SW-SW 1/64 1949</p> <p>S. 89° 41' E., along the S-S 1/64 sec. line.</p>
4.896	<p>Point for the C-E-SW-SW-1/256 sec. cor. of sec. 12, designated as Angle Point 5 of Tract C.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 12 C-E-SW-SW 1/256 1949</p> <p>S. 0° 14' W., along the E-W-W-1/256 sec. line.</p>
9.882	<p>The E-W-W 1/256 sec. cor. of secs. 12 and 13, designated as Angle Point 6 of Tract C.</p> <p>S. 89° 37' E., on S. bdy. of Tract C, and along the line bet. secs. 12 and 13.</p>
14.635	<p>The E-W 1/64 sec. cor. of secs. 12 and 13, designated as Angle Point 7 of Tract C.</p> <p>N. 0° 32' E., along the E-W 1/64 sec. line.</p>
4.95	<p>Point for the C-S-SE-SW 1/256 sec. cor. of sec. 12, designated as Angle Point 8 of Tract C.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 12 C-S-SE-SW 1/256 1949</p> <p>S. 89° 39' E., along the S-S-S 1/256 sec. line.</p>
9.791	<p>Point for the center S-S-S 1/256 sec. cor. of sec. 12.</p>
24.68	<p>Angle Point 1 of Tract C, and point of beginning.</p> <p>Area of Tract C: 19.38 acres.</p>

Chains

The smaller legal subdivisions of the S. half of sec. 12, which were required to establish the boundaries of Tract C were executed in accordance with the Manual of Surveying Instructions. The following field notes are the record of only those portions of the legal subdivisions which are boundaries of the tract. The corners of the subdivision were not monumented except for those corners which are angle points of the tract.

Survey of Tract C

Beginning at the point for Angle Point 1 of Tract C, at the intersection of the south line of U. S. Highway No. 89-A right-of-way and the S-S-S 1/256 sec. line, at a point which bears N. 89° 39' W., 4.68 chs. dist. from the C-S-S-SE 1/256 cor. of sec. 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

A P 1
T R C
S 12
T17N R5E
1949

N. 81° 10' W., on N. bdy. of Tract C and along the S. line of the highway right-of-way.

42.12 Point for Angle Point 2 of Tract C.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

A P 2
T R C
1949

N. 82° 52' W., continuing along S. line of highway right-of-way.

2.605 Point for Angle Point 3 of Tract C, at the intersection of the S. line of the highway right-of-way and the W-W 1/64 sec. line.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T17N
R5E A P 3
S 12 T R C
1949

S. 0° 08' W., on W. bdy. of Tract C, and along the W-W 1/64 sec. line.

1.58 Point for the SW-SW 1/64 sec. cor. of sec. 12 designated as Angle Point 4 of Tract C.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

Chains	
	<p style="text-align: center;">S 12 SW-SW 1/64 1949</p> <p>S. 89° 41' E., along the S-S 1/64 sec. line.</p>
4.896	<p>Point for the C-E-SW-SW-1/256 sec. cor. of sec. 12, designated as Angle Point 5 of Tract C.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 12 C-E-SW-SW 1/256 1949</p> <p>S. 0° 14' W., along the E-W-W-1/256 sec. line.</p>
9.882	<p>The E-W-W 1/256 sec. cor. of secs. 12 and 13, designated as Angle Point 6 of Tract C.</p> <p>S. 89° 37' E., on S. bdy. of Tract C, and along the line bet. secs. 12 and 13.</p>
14.635	<p>The E-W 1/64 sec. cor. of secs. 12 and 13, designated as Angle Point 7 of Tract C.</p> <p>N. 0° 32' E., along the E-W 1/64 sec. line.</p>
4.95	<p>Point for the C-S-SE-SW 1/256 sec. cor. of sec. 12, designated as Angle Point 8 of Tract C.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 12 C-S-SE-SW 1/256 1949</p> <p>S. 89° 39' E., along the S-S-S 1/256 sec. line.</p>
9.791	<p>Point for the center S-S-S 1/256 sec. cor. of sec. 12.</p>
24.68	<p>Angle Point 1 of Tract C, and point of beginning.</p> <p>Area of Tract C: 19.38 acres.</p>