

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey of South and East Boundaries

and

Portion of West Boundary and Portion of Subdivision

and

Retracement Portion of Subdivision of Township 14 South, Range 31 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Clarence E. Bilbray, Cadastral Engineer

Under special instructions dated November 1, 1951, which provided
for the surveys included under Group No. 280, approved November 20, 1951
and assignment instructions dated January 25, 1952

Survey commenced March 10, 1952

Survey completed April 10, 1952

Book No 4405

BOOK 4405

INDEX DIAGRAM

Township 14 S, Range 31 E.

10 6 40	40 5	34 4	30 3 29	23 2 23	16 1 4 16
9 7 39	8	9	29 10 28	22 11 22	15 12 4 15
9 18 38	39 17 38	33 16 33	27 15 27	21 14 20	14 13 3 14
8 19 36	37 20 36	32 21 32	26 22 26	19 23 19	13 24 3 12
30 35	35 29 35	31 28 31	25 27 24	18 26 18	11 25 2 11
31 8	34 32 7	30 33 7	23 34 6	17 35 6	11 36 1 5

T. 14 S., R. 31 E.

E201 446

The dependent resurvey of Township 14 South, Range 31 East, of the Gila and Salt River Meridian, Arizona. The boundaries and subdivision were originally surveyed by R.C. Powers, Deputy Surveyor, in 1883. The west boundary was resurveyed by John F. Hesse, U.S. Surveyor, in 1913. Sections 8 and 9 was resurveyed by B.J. Kinsey in 1940.

The resurvey was made at the request of the Division of Range Management.

A description of instrumental equipment, of observations and tests made, and methods employed, is given in the field notes of the resurvey of T. 13 S., R. 31 E.

The geographic position of the southeast corner of the township as computed through ties made in T. 13 S., R. 31 E., to (San Simon Coal Chute) U.S. Coast and Geodetic triangulation station is Latitude $32^{\circ} 09' 47.5''$ N. Longitude $109^{\circ} 07' 23.8''$ W.

Chains

Dependent Resurvey of East Boundary of T. 14 S., R. 31 E.

(Restoring the survey made by R.C. Powers in 1883)

The corner of Ts. 14 and 15 S., Rs. 31 and 32 E., is determined from intersection of roads, bearing N., S. and E., and a dim road bearing S. $89^{\circ} 00'$ W., this is the position for the cor. according to residents who stated the roads were constructed through the corner position, accepted as the best existing evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.

T14S	
R31E	R32E
S36	S31
S 1	S 6
T15S	
1952	

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears N. 45° E., 60 lks. dist., with brass cap mkd. T14SR32E S31 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears S. 45° W., 60 lks. dist., with brass cap mkd. T15SR31E S1 RM 1952 and an arrow pointing to the true corner.

N. $0^{\circ} 08'$ W., bet. secs. 31 and 36.

Over nearly level land, along road.

40.36

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance, on the W. side of road; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependent Resurvey of East Boundary of T. 14 S., R. 31 E.

Chains

$\frac{1}{4}$
 S36 | S31
 1952

Continue along W. side of road.

45.30 Shallow wash, 14 lks. wide, drains NE.

80.73 Point for the corner of secs. 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T14S
 R31E | R32E
 S25 | S30
 S36 | S31

1952

Land, nearly level.

Soil, sandy loam:

No timber; undergrowth, greasewood and mesquite.

N. 0° 08' W., bet. secs. 25 and 30.

Over nearly level land, along W. side of road.

40.36 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, marked by an iron rod, 1 in. diam., 12 ins. above the ground, accepted as the best existing evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$
 S25 | S30
 1952

N. 0° 33' W., beginning new measurement.

Over nearly level land, through undergrowth.

40.46 Point for the corner of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T14S
 R31E | R32E
 S24 | S19
 S25 | S30

1952

Land, nearly level.

Soil, sandy loam and gravelly.

No timber, undergrowth, greasewood and mesquite.

Dependent Resurvey of East Boundary of T. 14 S., R. 31 E.

Chains	N. 0° 33' W., bet. secs. 19 and 24. Over nearly level land, through undergrowth. 1.50 San Simon Wash, 60 lks. wide, 5 ft. deep, drains NW. 30.50 Wash, 30 lks. wide, 4 ft. deep, drains SW. 40.46 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div><div><div>$\frac{1}{4}$</div><div>S24 S19</div><div>1952</div></div></div> 41.20 Wash, 30 lks. wide, 4 ft. deep, drains SW. 67.00 Wash, 25 lks. wide, 2 ft. deep, drains SW. 80.93 Point for the corner of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div><div><div>T14S R31E R32E S13 S18 S24 S19</div><div>1952</div></div></div> Land, nearly level, Soil, sandy loam and gravelly. No timber; undergrowth, greasewood and mesquite.
	N. 0° 33' W., bet. secs. 13 and 18. Over gently rolling land, through undergrowth. 15.60 Natural Gas line, bears N. 83° 05' E. and S. 83° 05' W. 34.00 Shallow wash, drains SW. 40.46 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div><div><div>$\frac{1}{4}$</div><div>S13 S18</div><div>1952</div></div></div> 80.93 Point for the corner of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

.Dependent.Resurvey of East Boundary of T. 14 S., R. 31 E.

Chains	<div>TL4S. R31E R32E S12 S 7 S13 S18 1952 raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. Land, gently rolling. Soil, sandy and garvelly. No timber; undergrowth, greasewood and mesquite.</div>
	<div>N. 0° 33' W., bet. secs. 7 and 12. Over gently rolling land, through undergrowth. 1.20 Shallow wash, 10 lks. wide, drains SW. 21.00 Wash, 15 lks. wide, 2 ft. deep, drains SW. 23.50 Wash, 15 lks. wide, 3 ft. deep, drains SW. 29.00 Shallow wash, drains SW. 40.46 Point for the ¼ sec, cor. of secs, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. ¼ S12 S 7 1952 raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. 45.00 Shallow wash, 10 lks. wide, drains SW. 73.50 Shallow wash, drains SW. 80.93 Point for the corner of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. TL4S R31E R32E S 1 S 6 S12 S 7 1952 raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor. Land, gently rolling. Soil, sandy and gravelly. No timber; undergrowth, greasewood.</div>
	<div>N. 0° 33' W., bet. secs. 1 and 6. Over gently rolling land, through undergrowth. 11.50 Shallow wash, 15 lks. wide, drains SW.</div>

. Dependent Resurvey of East Boundary of T. 14 S., R. 31 E.

Chains	
36.50	Underground telephone cable, bears N. 74° 50' W. and S. 74° 50' E
39.00	Shallow wash, drains SW.
40.46	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">$\frac{1}{4}$ S 1 S 6 1952</div> raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor,
45.50	Highway right-of-way fence, bears N. 74° 50' W. and S. 74° 50' E.
47.15	State Highway No. 86, bears N. 74° 50' W. and S. 74° 50' E.
49.65	Telegraph line, bears N. 74° 50' W. and S. 74° 50' E.
50.25	Southern Pacific Railroad, bears N. 74° 50' W. and S. 74° 50' E.
51.00	Telegraph line, bears N. 74° 50' W. and S. 74° 50' E.
51.90	Railroad right-of-way fence, bears N. 74° 50' W. and S. 74° 50' E.
80.93	The corner of Ts. 13 and 14 S., Rs. 31 and 32 E., marked by an iron post, 3 ins. diam., set, marked and witnessed as described in the official record. Land, gently rolling. Soil, sandy and gravelly. No timber; undergrowth, greasewood.

Dependent Resurvey of South Boundary of T. 14 S., R. 31 E.

(Restoring the survey made by R.C. Powers in 1883)

From the corner of Ts. 14 and 15 S., Rs. 31 and 32 E.

S. 89° 34' W., bet. secs. 1 and 36.

Over nearly level land, along N. side of old road.

13.00	Shallow wash, drains NNE.
20.00	Leave road; thence through undergrowth.
40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div style="text-align: center;">$\frac{1}{4}$ S 36 S 1 1952</div>
80.96	Point for the corner of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependent Resurvey of South Boundary of T. 14 S., R. 31 E

Chains

T14SR31E	
S35	S36
S 2	S 1

T15S
1952

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, greasewood and mesquite.

S. 89° 34' W., bet. secs. 2 and 35.

Over nearly level land, through undergrowth.

10.00 Wash, 10 lks. wide, drains NNE.

40.48 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 35
$\frac{1}{4}$	S 2

1952

80.96 Point for the corner of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T14SR31E	
S34	S35
S 3	S 2

T15S
1952

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, greasewood and mesquite.

S. 89° 34' W., bet. secs. 3 and 34.

Over nearly level land, through undergrowth.

40.48 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 34
$\frac{1}{4}$	S 3

1952

80.86 Center of graded road, bears N. and S.

80.96 Point for the corner of secs. 3, 4, 33, and 34, at proportionate distance; 10 lks. W. of center line of road; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd.

Dependent Resurvey of South Boundary of T. 14 S., R. 31 E.

Chains	<div>T14SR31E</div> <div>S33 S34</div> <div>S 4 S 3</div> <div>T15S</div> <div>1952</div> <div>from which</div> <div>An iron post, 28 ins. long, 2½ ins. diam., set 2¼ ins. in the ground, for a reference monument, bears N. 45° E., 100 lks. dist., with brass cap mkd. T14SR31E S34 RM 1952 and an arrow pointing to the true corner.</div> <div>An iron post, 28 ins. long, 2½ ins. diam., set 2¼ ins. in the ground, for a reference monument, bears S. 45° W., 100 lks. dist., with brass cap mkd. T15SR31E S4 RM 1952 and an arrow pointing to the true corner.</div> <div>Land, nearly level.</div> <div>Soil, sandy loam.</div> <div>No timber; undergrowth, mesquite.</div>
	<div>S. 89° 34' W., bet. secs. 4 and 33..</div> <div>Over nearly level land, through undergrowth.</div> <div>0.45 Fence, bears N. and S.</div> <div>40.48 Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>½ S 33</div><div>¼ S 4</div><div>1952</div></div> <div>74.50 Shallow wash, 10 lks. wide, drains NNE.</div> <div>80.96 Point for the corner of secs. 4, 5, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>T14SR31E</div><div>S32 S33</div><div>S 5 S 4</div><div>T15S</div><div>1952</div></div> <div>Land, nearly level.</div> <div>Soil, sandy loam.</div> <div>No timber; undergrowth, mesquite.</div>
	<div>S. 89° 34' W., bet. secs. 5 and 32.</div> <div>Over nearly level land, through undergrowth.</div> <div>38.00 Shallow wash, drains NNE.</div> <div>40.48 Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</div>

BOOK 4406

Dependent Resurvey of South Boundary of T. 14 S., R. 31 E.

Chains Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.

1 S 32
4 S 5
1952

60.50 Shallow wash, drains N.

80.96 Point for the corner of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.

TL1SR31E
S31 | S32
S 6 | S 5
T15S
1952

Land, nearly level.
Soil, sandy loam and gravelly.
No timber; undergrowth, greasewood and mesquite.

S. 89° 34' W., bet. secs. 6 and 31.

Over nearly level land, through undergrowth.

16:50 Shallow wash. 10 lks. wide, drains NE.

40.48 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.

1 S 31
4 S 6
1952

73:00 Shallow wash, 10 lks. wide, drains NE.

80.32 The corner of Ts. 14 and 15 S., Rs. 30 and 31 E., marked by an iron post, 3 ins. diam., set, marked and witnessed as described in the official record.

Land, nearly level.
Soil, sandy loam and gravelly.
No timber; undergrowth, greasewood and mesquite.

Dependent Resurvey Portion of West Boundary, T. 14 S., R. 31 E.

(Restoring the resurvey made by John F. Hesse in 1913)

From the ¼ sec. cor. of secs. 19 and 24, marked by an iron post, in. diam., set, marked and witnessed as described in the official record.

N. 0° 16' W., bet. secs. 19 and 24.


Over nearly level land, along W. side of road.

40.10 Point for the corner of secs. 13, 18, 19, and 24, at proportionate distance; there is no evidence of the 1913 resurvey monument.

Dependent Resurvey Portion of West Boundary, T. 14 S., R. 31 E.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.



from which

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 60 lks. dist., with brass cap mkd. T14SR31E S19 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 60 lks. dist., with brass cap mkd. T14SR30E S13 RM 1952 and an arrow pointing to the true corner.

Land, nearly level.
Soil, sandy loam and gravelly.
No timber; undergrowth, greasewood and mesquite.


N. 0° 16' W., bet. secs. 13 and 18.

Over level land, continue along W. side of road.

40.10

Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no evidence of the 1913 resurvey monument.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



67.95

Shallow wash, 20 lks. wide, drains NE.

80.20

The corner of secs. 7, 12, 13, and 18, marked by an iron post, 3 ins. diam., set, and marked as described in the official record.

Land, level.
Soil, sandy loam.
No timber; undergrowth, greasewood and mesquite.


N. 0° 16' W., bet. secs. 7 and 12.

Over level land, along W. side of road.

40.10

Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no evidence of the 1913 resurvey monument.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



Dependent Resurvey Portion of West Boundary, T. 14 S., R. 31 E.

Chains

80.20

Point for the corner of secs. 1, 6, 7, and 12, at proportionate distance, falls on W. shoulder of road; there is no evidence of the 1913 resurvey monument.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.

T14S	
R30E	R31E
S 1	S 6
S12	S 7

1952

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears N. 45° E., 60 lks. dist., with brass cap mkd. T14SR31E S6 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears S. 45° W., 60 lks. dist., with brass cap mkd. T14SR30E S12 RM 1952 and an arrow pointing to the true corner.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and mesquite.

N. 0° 16' W., bet. secs. 1 and 6.

Over level land, along W. side of road.

40.10

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance, falls on W. shoulder of road; there is no evidence of the 1913 resurvey monument.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.

$\frac{1}{4}$	
S 1	S 6
1952	

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears East, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S6 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears West, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S1 RM 1952 and an arrow pointing to the true corner.

80.20

The corner of Ts. 13 and 14 S., Rs. 30 and 31 E., marked by an iron post, $\frac{3}{4}$ ins. diam., set, and marked as described in the official record.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and mesquite.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.


Chains	<p>(Reestablishment of survey made by R. C. Powers, in 1882)</p> <p>From the corner of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.</p> <p>Over nearly level land, through undergrowth.</p> <p>N. 0° 25' W., bet. secs. 35 and 36.</p>
36.00	<p>Shallow wash, 10 lks. wide, drains NNE.</p>
40.50	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>$\frac{1}{4}$</div><div>S35 S36</div><div>1952</div></div>
81.01	<p>The corner of secs. 25, 26, 35, and 36, marked by a redwood stake, 44 ins., firmly set in the ground, accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>T14SR31E</div><div>S26 S25</div><div>S35 S36</div><div>1952</div></div> <p>Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite.</p>
40.61	<p>From the corner of secs. 25, 30, 31, and 36, on the E. bdy of the Tp.</p> <p>S. 89° 49' W., bet. secs. 25 and 36.</p> <p>Over nearly level land, through undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>$\frac{1}{4}$ S 25</div><div>$\frac{1}{4}$ S 36</div><div>1952</div></div>
65.95	<p>Wash, 20 lks. wide, 5 ft. deep, drains NNE.</p>
81.23	<p>The corner of secs. 25, 26, 35, and 36.</p> <p>Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.</p>
	<p>N. 0° 24' E., bet. secs. 25 and 26.</p> <p>Over nearly level land, through undergrowth.</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains
40.28

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.




80.57

The corner of secs. 23, 24, 25, and 26, determined from intersection of roads, bearing N. $0^{\circ} 40'$ W., N. $89^{\circ} 39'$ E. and S. $89^{\circ} 11'$ W., this point is recognized by residents as the corner, accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.



from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears S. 45° E., 65 lks. dist., with brass cap mkd. T14SR31E S25 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears N. 45° W., 65 lks. dist., with brass cap mkd. T14SR31E S23 RM 1952 and an arrow pointing to the true corner.

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, mesquite and greasewood.

From the corner of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp. S. $89^{\circ} 39'$ W., bet. secs. 24 and 25.

Over nearly level land, through scattering undergrowth.


20.00

Intersection of roads, bearing S. and S. $89^{\circ} 39'$ W., along line.

40.07

Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance, on center line of road; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.



from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears North, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S24 RM 1952 and an arrow pointing to the true corner.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 45 lks. dist., with brass cap mkd. ¼ S25 RM 1952 and an arrow pointing to the true corner.</p>
80.15	<p>The corner of secs. 23, 24, 25, and 26.</p> <p>Land, nearly level, Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.</p>
40.25	<p>N. 0° 40' W., bet. secs. 23 and 24.</p> <p>Over level land, along road.</p> <p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance, on center line of road; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., ¾ ins. in the ground, with brass cap mkd.</p> <div><div>¼</div><div>S23 S24</div><div>1952</div></div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 50 lks. dist., with brass cap mkd. ¼ S24 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 50 lks. dist., with brass cap mkd. ¼ S23 RM 1952 and an arrow pointing to the true corner.</p>
61.30	<p>Left bank of San Simon wash, drains WNW.</p>
64.50	<p>Right bank of wash.</p>
80.50	<p>The corner of secs. 13, 14, 23, and 24, on center line of road, bearing N. 0° 43' W. and S. 0° 40' E., and in line with property line fence to west, accepted as the best existing evidence of the position of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., ¾ ins. in the ground, with brass cap mkd.</p> <div><div>T14SR31E</div><div>S14 S13</div><div>S23 S24</div><div>1952</div></div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 45 lks. dist., with brass cap mkd. T14SR31E S24 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 45 lks. dist., with brass cap mkd. T14SR31E S14 RM 1952 and an arrow pointing to the true corner.</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	Land. level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	From the corner of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. S. 89° 20' W., bet. secs. 13 and 24. Over nearly level land, through undergrowth.
22.70	Shallow wash, 10 lks. wide, drains SW.
32.30	Wash, 15 lks. wide, 3 ft. deep, drains SW.
40.19	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div><div>S 13</div><div>$\frac{1}{4}$ S 24</div><div>1952</div></div>
80.38	The corner of secs. 13, 14, 23, and 24. Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	N. 0° 43' W., bet. secs. 13 and 14. Over level land, along road.
7.00	Natural Gas line, bears N. 83° 05' E. and S. 83° 05' W.
40.55	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate distance, on center line of road; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd. <div><div>$\frac{1}{4}$</div><div>S14 S13</div><div>1952</div></div> from which An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 60 lks. dist., with brass cap mkd. $\frac{1}{4}$ S13 RM 1952 and an arrow pointing to the true corner. An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 60 lks. dist., with brass cap mkd. $\frac{1}{4}$ S14 RM 1952 and an arrow pointing to the true corner.
44.70	Shallow wash, 20 lks. wide, drains WSW.
60.50	Shallow wash, 25 lks. wide, drains SW.
66.00	Shallow wash, drains WSW.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains 81.10	<p>The corner of secs. 11, 12, 13, and 14, at intersection of roads, marked by a redwood stake, 2 ins. square, this stake was shown me by interested property owners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>T14SR31E</div><div>S11S12</div><div>S14S13</div></div> <p>1952</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.</p>
	<p>From the corner of secs. 7, 12, 13, and 18, on the E. bdy of the Tp. S. 89° 30' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land, through undergrowth.</p>
1.70	Shallow wash, 15 lks. wide, drains SW.
22.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.
24.50	Wash, 50 lks. wide, 4 ft. deep, drains SW.
40.30	<p>Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>S 12</div><div>¼ S 13</div><div>1952</div></div>
44.20	Shallow wash, 10 lks. wide, drains SW.
63.50	Shallow wash, drains SW.
80.60	<p>The corner of secs. 11, 12, 13, and 14.</p> <p>Land, gently rolling. Soil, sandy loam and gravelly. No timber; undergrowth, greasewood and mesquite.</p>
	<p>N. 0° 50' W., bet. secs. 11 and 12.</p> <p>Over nearly level land, through undergrowth .</p>
3.60	Shallow wash, 10 lks. wide, drains SW.
40.61	<p>Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<p>distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div><div><div>$\frac{1}{4}$</div><div>S 2 S 1</div><div>1952</div></div></div> <p>raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
42.50	Wash, 30 lks. wide, 3 ft. deep, drains SW.
52.00	Shallow wash, 20 lks. wide, drains SW.
58.50	Underground telephone cable, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
61.20	Wash, 15 lks. wide, 2 ft. deep, drains SW.
68.00	Highway right-of-way fence, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
69.75	State Highway No. 86, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
71.95	Telegraph line, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
72.60	Southern Pacific Railroad, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
73.30	Telegraph line, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
74.20	Railroad right-of-way fence, bears N. $74^{\circ} 50'$ W. and S. $74^{\circ} 50'$ E.
79.60	Wash, 10 lks. wide, 2 ft. deep, drains SW.
81.30	<p>The corner of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., marked by an iron post, $2\frac{1}{2}$ ins. diam., set, marked and witnessed as described in the 1952 resurvey record of T. 13 S., R. 31 E.</p> <p>Land, gently rolling. Soil, sandy loam and gravelly. No timber; undergrowth, greasewood and mesquite.</p>
	<p>From the corner of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 27'$ W., bet. secs. 34 and 35.</p> <p>Over nearly level land, through undergrowth.</p>
40.27	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div><div>$\frac{1}{4}$</div><div>S 34 S 35</div><div>1952</div></div></div>
80.55	<p>Point for the corner of secs. 26, 27, 34, and 35, at prpportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains

T14SR31E
S27 | S26
S34 | S35

1952

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 25, 26, 35, and 36.

S. 89° 12' W., bet. secs. 26 and 35.

Over nearly level land, through undergrowth.

40.46 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

S 26
S 35
1952

80.93 The corner of secs. 26, 27, 34, and 35.

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, greasewood and mesquite.

N. 0° 01' E., bet. secs. 26 and 27, bet. secs.

Over nearly level land, through undergrowth.

40.27 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

$\frac{1}{4}$
S27 | S26
1952

60.15 Southwest corner of irrigation reservoir, approximately 2.00 chs. sq.

64.45 Enter cultivated land, bears E. and W.

80.05 Leave cultivation, bears E. and W.

80.55 The corner of secs. 22, 23, 26, and 27, determined longitudinally by proportionate measurement, and latitudinally by center line of road bearing N. 89° 11' E. and S. 89° 43' W.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd.

T14SR31E
S22 | S23
S27 | S26
1952

BOOK 100

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	from which
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 60 lks. dist., with brass cap mkd. T14SR31E S26 RM 1952 and an arrow pointing to the true corner.
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins., diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 60 lks. dist., with brass cap mkd. T14SR31E S22 RM 1952 and an arrow pointing to the true corner.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	From the corner of secs. 23, 24, 25, and 26.
	S. 89° 11' W., bet. secs. 23 and 26
	Over level land, along road.
15.00	Shallow wash, 20 lks. wide, drains NNE.
31.00	Shallow wash, 20 lks. wide, drains NNE.
32.50	Old road, bears NNE. and SSW.
40.70	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; on center line of road; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S } 23 \\ \hline \frac{1}{4} \text{ S } 26 \\ 1952 \end{array}$
	from which
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S23 RM 1952 and an arrow pointing to the true corner.
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S26 RM 1952 and an arrow pointing to the true corner.
	Continue along road, between fields.
64.00	Intersections of roads, bearing S., E. and W., along line.
81.40	The corner of secs. 22, 23, 26, and 27.
	Land; Level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	N. 0° 44' W., bet. secs. 22 and 23.
	Over level land, through cultivated field.
0.50	South side of irrigation reservoir, approximately 3.00 chs. square.
3.50	North side of reservoir.

Dependent Resurvey Subdivision, T. 14 S., R. 31 E.

Chains 40.10	Leave cultivated field, bears E. and W.
40.55	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>$\frac{1}{4}$</div><div>S22 S23</div><div>1952</div></div> <p>From this corner a windmill, bears N. 72° E., 1.85 chs. dist.</p> <p>Continue over level land, through undergrowth.</p>
49.00	Road, bears NW. and SE.
80.30	Graded road, bears E. and W.
81.11	<p>The corner of secs. 14, 15, 22, and 23, marked by a redwood stake, 2 ins. square, accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>T14SR31E</div><div>S15 S14</div><div>S22 S23</div><div>1952</div></div> <p>Land, level. Soil, sandy loam. No timber; undergrowth, mesquite.</p>
	<p>From the corner of secs. 13, 14, 23, and 24.</p> <p>S. 89° 33' W., bet. secs. 14 and 23.</p> <p>Over level land, along S. side cultivated field.</p>
24.60	Leave field; thence through scattering undergrowth.
27.00	Right bank of San Simon wash, 8 ft. deep, drains NW.
30.60	Left bank of wash.
40.76	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>$\frac{1}{4}$</div><div>S 14</div><div>S 23</div><div>1952</div></div>
41.05	Power line, bears N. and S.
42.00	Southeast corner of irrigation reservoir, approximately 1.50 chs. square.
44.25	A well, bears N. .01 lk. dist.

BOOK 400

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	
73.00	A house, bears N. approximately 1.30 chs. dist.
81.53	The corner of secs. 14, 15, 22, and 23. Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	N. 0° 43' W., bet. secs. 14 and 15. Over nearly level land, through undergrowth.
1.70	Natural Gas line, bears N. 62° 45' E. and S. 62° 45' W.
20.00	Enter cultivated field, bears E. and W.
35.00	Leave field, bears E. and W.
40.64	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd, <div style="text-align: center;">$\frac{1}{4}$ S15 S14 1952</div>
41.50	Left bank of San Simon wash, 6 ft. deep, drains WNW.
44.50	Right bank of wash.
45.50	Enter cultivated field, bears E. and W.
52.40	Leave field, bears E. and W.
67.00	Shallow wash, drains W.
81.28	The corner of secs. 10, 11, 14, and 15, determined from intersection of road, bearing N. 89° 43' E. and N. 0° 25' W.; accepted as the best existing evidence of the position of the original corner. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T14SR31E S10 S11 S15 S14 1952</div> from which An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 60 lks. dist., with brass cap mkd. T14SR31E S11 RM 1952 and an arrow pointing to the true corner. An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 0° 45' W., 60 lks. dist., with brass cap mkd. T14SR31E S15 RM 1952 and an arrow pointing to the true corner. Land, nearly level. Soil, sandy loam.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	No timber; undergrowth, mesquite.
	<p>From the corner of secs. 11, 12, 13, and 14.</p> <p>S. 89° 43' W., bet. secs. 11 and 14.</p> <p>Over level land, along road.</p>
40.74	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate distance, on center line road; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S\ 11 \\ \frac{1}{4} \\ \hline S\ 14 \\ 1952 \end{array}$ </div> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S11 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S14 RM 1952 and an arrow pointing to the true corner.</p> <p>Continue along road, bet. cleared fields.</p>
81.48	<p>The corner of secs. 10, 11, 14, and 15.</p> <p>Land. level.</p> <p>Soil, sandy loam.</p> <p>No timber; undergrowth, greasewood and mesquite.</p>
	<p>N. 0° 25' W., bet. secs. 10 and 11.</p> <p>Over level land, along road and W. side of cleared field.</p>
20.00	Leave field, bears S. and E.
41.30	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance, on center line road; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ S10 \mid S11 \\ 1952 \end{array}$ </div>
82.60	<p>The corner of secs. 2, 3, 10, and 11, at intersection of road bearing S. 0° 25' E. and S. 88° 40' W., marked by an iron pipe, 2 ins. diam., firmly set in the ground, accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p>

BOOK 4400

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<div>T14SR31E</div> <div>S 3 S 2</div> <div>S10 S11</div> <div>1952</div> <div>Land, level.</div> <div>Soil, sandy loam.</div> <div>No timber; undergrowth, scattering mesquite.</div>
14.50	<div>From the corner of secs. 1, 2, 11, and 12.</div> <div>N. 89° 17' W., bet. secs. 2 and 11.</div> <div>Over nearly level land, through undergrowth.</div> <div>Shallow wash, 10 lks. wide, drains SW.</div>
40.49	<div>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>1 S 2</div><div>4 S 11</div><div>1952</div></div>
45.00	<div>Wash, 15 lks. wide, drains SW.</div>
80.98	<div>The corner of secs. 2, 3, 10, and 11.</div> <div>Land, nearly level.</div> <div>Soil, sandy loam.</div> <div>No timber; undergrowth, greasewood and mesquite.</div>
30.90	<div>N. 0° 16' W., bet. secs. 2 and 3.</div> <div>Over nearly level land, through undergrowth.</div> <div>Shallow wash, 15 lks. wide, drains SW.</div>
40.15	<div>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>1</div><div>4</div><div>S 3 S 2</div><div>1952</div></div>
80.34	<div>The corner of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set marked and witnessed as described in the 1952 resurvey record of T. 13 S., R. 31 E.</div> <div>Land, nearly level.</div> <div>Soil, sandy loam and gravelly.</div> <div>No timber; undergrowth, greasewood and mesquite</div>
	<div>From the corner of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.</div> <div>N. 0° 23' W., bet. secs. 33 and 34.</div>


Chains

Over level land, along road.

40.32

Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance, on road; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.



from which


An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S34 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S33 RM 1952 and an arrow pointing to the true corner.

80.65

Point for the corner of secs. 27, 28, 33, and 34, at proportionate distance, on center line of road; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.



from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 75 lks. dist., with brass cap mkd. T14SR31E S27 RM 1952 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 75 lks. dist., with brass cap mkd. T14SR31E S33 RM 1952 and an arrow pointing to the true corner.

Land, level.
Soil, sandy loam.
No timber; undergrowth, mesquite.

From the corner of secs. 26, 27, 34, and 35.

S. $89^\circ 36'$ W., bet. secs. 27 and 34.

Over level land, through undergrowth.

40.41

Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependant Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<div><div><div><div><div><div></div><div>S 27</div></div><div><div><div>1</div><div>4</div></div><div>S 34</div></div><div>1952</div></div></div></div></div>
80.83	<div><div><div>The corner of secs. 27, 28, 33, and 34.</div><div>Land, level.</div><div>Soil, sandy loam.</div><div>No timber; undergrowth, mesquite.</div></div></div>
40.32	<div><div><div>N. 0° 27' W., bet. secs. 27 and 28.</div><div>Over level land, along road.</div><div>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance, on center line road; there is no remaining evidence of the original corner</div><div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.</div><div><div><div><div><div></div><div>$\frac{1}{4}$</div></div><div><div>S28</div><div>S27</div></div><div>1952</div></div></div></div></div><div><div>from which</div><div><div>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S27 RM 1952 and an arrow pointing to the true corner.</div><div>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S28 RM 1952 and an arrow pointing to the true corner.</div></div></div></div>
80.65	<div><div><div>The corner of secs. 21, 22, 27, and 28, determined by intersection of roads bearing N., S. and N. 89° 43' E.. This is the position for the cor. according to residents, who stated the road was constructed along the section line, accepted as the best available evidence of the position of the original corner.</div><div>At the corner point</div><div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.</div><div><div><div><div><div><div></div><div>T14SR31E</div></div><div><div>S21</div><div>S22</div></div><div><div>S28</div><div>S27</div></div></div></div><div>1952</div></div></div><div><div>from which</div><div><div>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 100 lks. dist., with brass cap mkd. T14SR31E S22 RM 1952 and an arrow pointing to the true corner.</div><div>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a rfeerence monument, bears S. 45° W., 100 lks. dist., with brass cap mkd. T14SR31E S28 RM 1952 and an arrow pointing to the true corner</div></div></div></div></div>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	Land, level. Soil, sandy loam. No timber; undergrowth, mesquite.
	From the corner of secs. 22, 23, 26, and 27. S. 89° 43' W., bet. secs. 22 and 27. Over level land, along road.
40.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance, on center line of road; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd. <div style="text-align: center;">$\frac{1}{4}$ S 22 $\frac{1}{4}$ S 27 1952</div> from which An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears North, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S22 RM 1952 and an arrow pointing to the true corner. An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears South, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S27 RM 1952 and an arrow pointing to the true corner.
81.51	The corner of secs. 21, 22, 27, and 28. Land, level... Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	N. 0° 23' W., bet. secs. 21 and 22. Over level land, along road, between fences.
40.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance, on center line of road; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd. <div style="text-align: center;">$\frac{1}{4}$ S21 S22 1952</div> from which An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears East, 75 lks. dist., with brass cap mkd. $\frac{1}{4}$ S22 RM 1952 and an arrow pointing to the true corner. An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears West, 75 lks. dist., with brass cap mkd. $\frac{1}{4}$ S21 RM 1952 and an arrow pointing to the true corner

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains 81.50	<p>The corner of secs. 15, 16, 21, and 22, determined by intersection of roads bearing N., S., E. and W. This is the point for the cor. according to residents, who stated the roads were constructed along the section lines, accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.</p> <div><div>T14SR31E</div><div><div>S16</div><div>S15</div></div><div>S21</div><div>S22</div></div> <p>1952</p> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 70 lks. dist., with brass cap mkd. T14SR31E S22 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 70 lks. dist., with brass cap mkd. T14SR31E S16 RM 1952 and an arrow pointing to the true corner.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.</p>
	<p>From the corner of secs. 14, 15, 22, and 23.</p> <p>S. $89^{\circ} 59'$ W., bet. secs. 15 and 22.</p> <p>Over level land, through undergrowth.</p>
3.80	Natural Gas line, bears N. $61^{\circ} 30'$ E. and S. $61^{\circ} 30'$ W.
11.80	Road, bears WNW. and ESE.
16.00	Leave undergrowth; thence along N. edge of field.
40.52	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance, on N. edge field; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glads, with brass cap mkd.</p> <div><div>$\frac{1}{4}$ S 15</div><div>S 22</div><div>1952</div></div>
43.30	Leave field, bears S. and E.; thence through scattering undergrowth.
64.00	Fence, bears ENE, and WSW.; thence along road.
81.05	<p>The corner of secs. 15, 16, 21, and 22.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, scattering greasewood and mesquite.</p>
	<p>N. $0^{\circ} 30'$ W., bet. secs. 15 and 16</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	Over level land, along road
40.38	<p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, determined latitudinally by proportionate measurement, and longitudinally by center line of road.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">$\frac{1}{4}$ S16 S15 1952</div> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears East, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S15 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears West, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S16 RM 1952 and an arrow pointing to the true corner.</p> <hr/> <p>N. 3° 20' W., beginning new measurement</p> <p>Along road.</p>
5.00	Leave road; thence through scattering undergrowth.
40.45	<p>The corner of secs. 9, 10, 15, and 16, marked by an iron post, 2 ins. diam., set, marked and witnessed as described in the field note record of the 1940 resurvey of sections 8 and 9</p> <p>Land, level.</p> <p>Soil, sandy loam.</p> <p>No timber; undergrowth, greasewood and mesquite.</p> <hr/>
	<p>From the corner of secs. 10, 11, 14, and 15.</p> <p>S. 89° 39' W., bet. secs. 10 and 15.</p> <p>Over level land, through undergrowth.</p>
4.00	Northwest corner of reservoir, bears S. 30 lks. dist., approximately 1.50 chs. square.
41.37	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div style="text-align: center;">$\frac{1}{4}$ S 10 S 15 1952</div>
57.20	Right bank of San Simon wash, 8 ft. deep, drains NW..
59.40	Left bank of wash.
63.00	Enter field, bears NW. and S.
80.20	Leave cultivation, bears N. and S..

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	
80.70	Road, bears N. and S.
81.10	Power line, bears N. and S.
82.75	The corner of secs. 9, 10, 15, and 16. Land, level. Soil, sandy loam. No timber; undergrowth, mesquite.
Retracement Between Sections 9 and 10, T. 14 S., R. 31 E.	
	N. 1° 09' E., bet. secs. 9 and 10. Over level land, through undergrowth..
20.50	Left bank San Simon wash, 8 ft. deep, drains NW.
24.00	Right bank wash.
41.81	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, marked by an iron post, 1 in. diam., set, and marked as described in the field note record of the 1940 resurvey of secs. 8 and 9.
	N. 0° 07' E., beginning new measurement. Continue through undergrowth, near road.
39.20	Road, bears E. and W.
39.37	The corner of secs. 3, 4, 9, and 10, marked by an iron post, 2 ins. diam., set, and marked as described in the field note record of the 1940 resurvey of sections 8 and 9. Land, level. Soil, sandy loam. No timber; undergrowth, mesquite.
Dependent Resurvey of Subdivision, T. 14 S., R. 31 E. From the cor. of secs. 2, 3, 10, and 11. S. 88° 40' W., bet. secs. 3 and 10.	
	Over level land, along N. side road.
0.40	Power line, bears S. and W.
20.00	Road, bears NW. and S.; continue along N. side road and S. side field.
40.60	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance, on N. side road, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div>S 3 $\frac{1}{4}$ S 10 1952</div>
80.60	Road, bears N. and S.
81.21	The corner of secs. 3, 4, 9, and 10. Land, level. Soil, sandy loam. No timber; undergrowth, scattering mesquite.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	N. 0° 04' W., bet. secs. 3 and 4.
	Over level land, along and near W. side road.
24.70	Shallow wash, 15 lks. wide, drains W.
33.60	Shallow wash, 10 lks. wide, drains WSW.
41.25	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \downarrow \\ S\ 4 \quad \quad S\ 3 \\ 1952 \end{array}$
	from which
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 80 lks. dist., with brass cap mkd. $\frac{1}{4}$ S3 RM 1952 and an arrow pointing to the true corner.
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 80 lks. dist., with brass cap mkd. $\frac{1}{4}$ S4 RM 1952 and an arrow pointing to the true corner.
	Continue along W. side road, and W. side cultivated field.
82.33	The corner of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., marked by an iron post, $2\frac{1}{2}$ ins. diam., set. marked and witnessed as described in the 1952 resurvey record of T. 13 S., R. 31 E.
	Land, level.
	Soil, sandy loam.
	No timber; undergrowth, scattering mesquite.
	From the corner of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.
	N. 0° 18' W., bet. secs. 32 and 33.
	Over nearly level land, through undergrowth.
40.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \downarrow \\ S32 \quad \quad S33 \\ 1952 \end{array}$
80.72	Point for the corner of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground Over a deposit of broken glass, with brass cap mkd.

2017 1900

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<div>T14SR31E</div> <div>S29 S28</div> <div>S32 S33</div> <div>1952</div> <div>Land, nearly level.</div> <div>Soil; sandy loam.</div> <div>No timber; undergrowth, greasewood and mesquite.</div>
40.38	<div>From the corner of secs. 27, 28, 33, and 34.</div> <div>S. 89° 33' W., bet. secs. 28 and 33.</div> <div>Over nearly level land, through undergrowth.</div> <div>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>S 28</div><div>1/4 </div><div>S 33</div><div>1952</div></div>
80.77	<div>The corner of secs. 28, 29, 32, and 33.</div> <div>Land, nearly level.</div> <div>Soil, sandy loam.</div> <div>No timber; undergrowth, mesquite.</div>
40.36	<div>N. 0° 28' W., bet. secs. bet. secs. 28 and 29.</div> <div>Over nearly level land, through undergrowth.</div> <div>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>1/4</div><div>S29 S28</div><div>1952</div></div>
80.72	<div>Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div>T14SR31E</div><div>S20 S21</div><div>S29 S28</div><div>1952</div><div>Land, nearly level.</div><div>Soil, sandy loam.</div><div>No timber; undergrowth, greasewood and mesquite.</div></div>
	<div>From the corner of secs. 21, 22, 27, and 28.</div>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	S. 89° 35' W., bet. secs. 21 and 28. Over nearly level land, through undergrowth.
40.38	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div>$\begin{array}{c} \frac{1}{4} \text{ S } 21 \\ \hline \frac{1}{4} \text{ S } 28 \\ 1952 \end{array}$</div>
52.20	Wash, 15 lks. wide, 2 ft. deep, drains NNW.
80.76	The corner of secs. 20, 21, 28, and 29. Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	N. 0° 42' W., bet. secs. 20 and 21. Over nearly level land, through undergrowth.
22.00	Shallow wash, drains NNE.
40.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. <div>$\begin{array}{c} \frac{1}{4} \\ \hline \text{S20} \quad \text{S21} \\ 1952 \end{array}$</div>
52.80	Natural Gas line, bears N. 80° 30' E. and S. 80° 30' W.
80.73	The corner of secs. 16, 17, 20, and 21, determined latitudinally by center line road, and longitudinally by proportionate measurement. At the corner point. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd. <div>$\begin{array}{c} \text{TL4SR31E} \\ \hline \text{S17} \quad \text{S16} \\ \hline \text{S20} \quad \text{S21} \\ 1952 \end{array}$</div> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 60 lks. dist., with brass cap mkd. TL4SR31E S16 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 60 lks. dist., with brass cap mkd. TL4SR31E S20 RM 1952 and an arrow pointing to the true corner.</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	Land, nearly level. Soil, sandy loam and gravelly. No timber; undergrowth, mesquite.
	From the corner of secs. 15, 16, 21, and 22. S. 89° 00' W., bet. secs. 16 and 21. Over level land, along road.
30.00	Shallow wash, 15 lks. wide, drains NNE., continue along road with cultivated land to the N.
40.57	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance, on center line road, there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $3\frac{1}{4}$ ins. in the ground, with brass cap mkd. <div style="text-align: center;">$\begin{array}{r} S\ 16 \\ \frac{1}{4} \\ S\ 21 \\ 1952 \end{array}$</div> from which An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears S. 45° E., 60 lks. dist., with brass cap mkd. $\frac{1}{4}$ S21 RM 1952 and an arrow pointing to the true corner. An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears N. 45° W., 60 lks. dist., with brass cap mkd. $\frac{1}{4}$ S16 RM 1952 and an arrow pointing to the true corner.
42.00	Continue along road, with cultivated land to N. and S.
45.00	Southwest cor. of reservoir, bears N. 40 lks. dist., 2.00 chs. square. Leave cultivated land to N. bears N. and E.
72.00	Shallow wash, drains NNE.
80.50	Leave cultivated land to S. continue along road.
81.14	The corner of secs. 16, 17, 20, and 21. Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.
	N. 1° 07' W., bet. secs. 16 and 17. Over nearly level land, through undergrowth.
40.15	Point for the $\frac{1}{4}$ sec. cor. of Secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd. <div style="text-align: center;">$\begin{array}{c} \frac{1}{4} \\ S17 \quad S16 \\ 1952 \end{array}$</div>
79.55	Graded road, bears E. and W.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains
80.31

The corner of secs. 8, 9, 16, and 17, marked by an iron post, 2 ins. diam., set, and marked as described in the 1940 resurvey record of sections 8 and 9.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 4, 5, 8, and 9, marked by an iron post, 2 ins. diam., set, marked, and witnessed as described in the 1940 resurvey record of sections 8 and 9.

N. 0° 18' W., bet. secs. 4 and 5.

Over nearly level land, through undergrowth.

31.70 Left bank San Simon wash, 12 ft. deep, drains WNW.

33.10 Right bank wash.

44.19 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$
 S 5 | S 4
 1952

88.34 The corner of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., marked by an iron post, $2\frac{1}{2}$ ins. diam., set, marked and witnessed as described in the 1952 resurvey record of T. 13 S., R. 31 E.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.

N. 0° 18' W., bet. secs. 31 and 32.

Over nearly level land, through undergrowth.

40.22 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$
 S 31 | S 32
 1952

80.44 Point for the corner of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<div>T14SR31E</div> <div>S30 S29</div> <div>S31 S32</div> <div>1952</div> <div>Land, nearly level. Soil, sandy loam and gravelly. No timber; undergrowth, greasewood and mesquite.</div>
25.00	<div>From the corner of secs. 28, 29, 32, and 33.</div> <div>S. 89° 20' W., bet. secs. 29 and 32.</div> <div>Over nearly level land, through undergrowth.</div> <div>Shallow wash, drains NNE.</div>
40.45	<div>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div><div><div><div><div></div><div>S 29</div></div><div><div></div><div>S 32</div></div></div><div><div></div><div>1952</div></div></div></div></div>
80.91	<div>The corner of secs. 29, 30, 31, and 32.</div> <div>Land, nearly level. Soil, sandy loam and gravelly. No timber; undergrowth; greasewood and mesquite.</div>
40.44	<div>S. 89° 23' W., bet. secs. 30 and 31.</div> <div>Over gently rolling land, through undergrowth.</div> <div>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</div> <div><div><div><div><div><div></div><div>S 30</div></div><div><div></div><div>S 31</div></div></div><div><div></div><div>1952</div></div></div></div></div>
56.50	<div>Shallow wash, 20 lks. wide, drains NE.</div>
75.20	<div>A dike, bears NW. and SE.</div>
80.21	<div>The corner of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., marked by an iron post, 3 ins. diam., set, marked and witnessed as described in the 1913 resurvey record.</div> <div>Land, gently rolling. Soil, sandy loam and gravelly. No timber; undergrowth, greasewood and mesquite.</div>
	<div>From the corner of secs. 29, 30, 31, and 32.</div> <div>N. 0° 19' W., bet. secs. 29 and 30.</div> <div>Over nearly level land, through undergrowth.</div>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains
40.22

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$
S30 | S29
1952

51.50

Shallow wash, 10 lks. wide; drains NE.

80.44

Point for the corner of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.

T14SR31E
S19 | S20
S30 | S29
1952

Land, nearly level.

Soil, sandy loam and gravelly.

No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 20, 21, 28, and 29

S. 89° 10' W., bet. secs. 20 and 29.

Over nearly level land, through undergrowth.

10.50

Shallow wash, drains NNE.

40.36

Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.

S 20
 $\frac{1}{4}$ S 29
1952

49.60

Shallow wash, 15 lks. wide, drains NE.

80.72

The corner of secs. 19, 20, 29, and 30.

Land, nearly level.

Soil; sandy loam and gravelly.

No timber; undergrowth; greasewood and mesquite.

S. 89° 10' W., bet. secs. 19 and 30.

Over gently rolling land, through undergrowth.

18.90

Shallow wash, 20 lks. wide, drains N.

22.60

Shallow wash, 15 lks. wide, drains NNE.

27.70

Shallow wash, 10 lks. wide, drains NE.

40.42

Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<p>distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.</p> <div><div>S 19</div><div>4 S 30</div><div>1952</div></div> <p>raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p>
46.90	Wash, 20 lks. wide. 2 ft. deep, drains NE.
71.50	Shallow wash, 10 lks. wide, drains NNE.
80.09	<p>The corner of secs, 19, 24, 25, and 30, on the W. bdy. of the Tp., marked by an iron post, 3 ins. diam., set, marked and witnessed as described in the 1913 resurvey record.</p> <p>Land, nearly level..</p> <p>Soil, sandy loam and gravelly.</p> <p>No timber; undergrowth, greasewood and mesquite.</p>
	<p>From the corner of secs. 19, 20, 29, and 30.</p> <p>N. 0° 58' W., bet. secs. 19 and 20.</p> <p>Over nearly level land, through undergrowth.</p>
40.23	<p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance, on gas line clearing, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div><div>¼</div><div>S19 S20</div><div>1952</div></div>
40.30	Natural Gas line, bears N. 80° 30' E. and S. 80° 30' W.
41.00	Shallow wash, drains NE.
80.46	<p>The corner of secs. 17, 18, 19, and 20, determined by intersection of roads bearing N., N. 89° 00' E. and S. 89° 00' W., accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., ¾ ins. in the ground, with brass cap mkd.</p> <div><div>T14SR31E</div><div>S18 S17</div><div>S19 S20</div><div>1952</div></div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 2¼ ins. in the ground, for a reference monument, bears N. 45° E., 90 lks. dist., with brass cap mkd. T14SR31E S17 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 2¼ ins. in the</p>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<p>ground, for a reference monument, bears S. 45° W., 90 lks. dist., with brass cap mkd. T14SR31E S19 RM 1952 and an arrow pointing to the true corner.</p> <p>Land, nearly level. Soil, sandy loam and gravelly. No timber; undergrowth, greasewood and mesquite.</p>
40.56	<p>From the corner of secs. 16, 17, 20, and 21.</p> <p>S. 89° 00' W., bet. secs. 17 and 20.</p> <p>Over level land, along road.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance, on center line road; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \text{ S } 17 \\ \hline \text{S } 20 \\ 1952 \end{array}$ </div> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S17 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S20 RM 1952 and an arrow pointing to the true corner.</p>
81.12	<p>The corner of secs. 17, 18, 19, and 20.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.</p>
6.90	<p>S. 88° 57' W., bet. secs. 18 and 19.</p> <p>Over level land, along road.</p> <p>Shallow wash, 10 lks. wide, drains NE.</p>
39.93	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance, on center line road, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \text{ S } 18 \\ \hline \text{S } 19 \\ 1952 \end{array}$ </div> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 40 lks. dist., with brass cap mkd. $\frac{1}{4}$ S18 RM 1952 and an arrow pointing to the true corner.</p>

BOOK 40

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains	<p>An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 2$\frac{1}{4}$ ins. in the ground, for a reference monument, bears South, 40 lks. dist., with brass cap mkd. $\frac{1}{4}$ S19 RM 1952 and an arrow pointing to the true corner.</p>
78.90	Read, bears N. and S.
79.04	<p>The corner of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and mesquite.</p>
	<p>From the corner of secs. 17, 18, 19, and 20.</p> <p>N. 0° 19' W., bet. secs. 17 and 18.</p> <p>Over level land, along road.</p>
39.91	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance, on center line of road; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., $\frac{3}{4}$ ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">$\frac{1}{4}$ S18 S17 1952</div> <p>from which</p> <p>An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 2$\frac{1}{4}$ ins. in the ground, for a reference monument, bears East, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S17 RM 1952 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 2$\frac{1}{4}$ ins. in the ground, for a reference monument, bears West, 45 lks. dist., with brass cap mkd. $\frac{1}{4}$ S18 RM 1952 and an arrow pointing to the true corner.</p>
79.83	<p>The corner of secs. 7, 8, 17, and 18, which falls in center line of road, from which the witness corner monument, bears West, 32 lks. dist., monumented by an iron post, 2 ins. diam., set marked and witnessed as described in the official record of the 1940 resurvey of secs. 8 and 9.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, mesquite.</p>
	<p>S. 89° 14' W., bet. secs. 7 and 18.</p> <p>Over level land, through undergrowth.</p>
39.90	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 2$\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <div style="text-align: center;">$\frac{1}{4}$ $\frac{87}{S18}$ 1952</div>

Dependent Resurvey of Subdivision, T. 14 S., R. 31 E.

Chains

67.00 Shallow wash, drains NE.
 78.75 Road, bears N. and S.
 78.94 The corner of secs. 7, 12, 13, and 18, marked by an iron post, 3 ins. diam., set and marked as described in the 1913 resurvey record.
 Land, level.
 Soil, sandy loam.
 No timber; undergrowth, mesquite.

From the true point for the corner of secs. 5, 6, 7, and 8, from which the witness corner, bears West, 32 lks. dist., marked by an iron post, 2 ins. diam., set and marked as described in the official record.

S. 89° 48' W., bet. secs. 6 and 7.

Over level land, through undergrowth.

39.81 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \quad 86 \\ \frac{1}{4} \quad 87 \\ \hline 1952 \end{array}$$

41.00 Shallow wash, drains NNE.

78.67 The corner of secs. 1, 6, 7, and 12, on the W. bdy of the Tp.

Land, level.
 Soil, sandy loam.
 No timber; undergrowth, greasewood and mesquite.

From the $\frac{1}{4}$ cor. of secs. 5 and 6, monumented by an iron post, 1 in. diam., set and marked as described in the official record.

N. 0° 05' E., bet. secs. 5 and 6. (3 $\frac{1}{2}$)

Over level land, through undergrowth.

15.00 Field, bears N. and E.

18.00 Southwest cor. of reservoir, approximately 1.50 chs. square.

25.00 Leave field, bears S. and E.

47.02 The corner of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., marked by an iron post, 2 $\frac{1}{4}$ ins. diam., set and marked as described in the 1952 resurvey record of T. 13 S., R. 31 E.

Land, level.
 Soil, sandy loam.
 No timber; undergrowth, greasewood and mesquite.

General Description

This township is gently rolling in the northeast portion and nearly level in the south and west portions. The general drainage in the northeast portion of the township is to the southwest and in the south and west portions to the north and northeast into San Simon wash which drains northwest. This wash enters the township on the east boundary near the corner of secs. 19, 24, 25, and 30, and leaves

the township on the north boundary of sec. 5. The soil is a sandy loam. There is no timber in the township. The township is covered with a heavy undergrowth of greasewood and mesquite. There is quiet a little farming in the east half of the township with irrigation from wells. The Southern Pacific Railroad and State Highway No. 86 enters the township on the east boundary of sec. 1 and leaves on the north boundary of sec. 2. The El Paso natural gas line enters the township on the east boundary of sec. 13 and leaves on the west boundary of sec. 19. There is approximately 25 miles of graded County roads in the township, the majority of which were constructed along the section lines.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BOOK 4405

FIELD ASSISTANTS

[illegible]

CERTIFICATE OF CADASTRAL ENGINEER

I, Clarence E. Bilbray, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 1st day of November, 1951,
I have ~~surveyed~~ independently resurveyed the south and east boundaries and portion of
west boundary and portion of subdivision and retraced portion of subdivision of
T. 14 S., R. 31 E.

Gila and Salt River
of the _____ Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Albuquerque, New Mexico

August 11, 1952

Clarence E. Bilbray
Clarence E. Bilbray
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., JUN 30 1953, 19____

re-
The foregoing field notes of the survey of south and east boundaries and portion of west
boundary and portion of subdivision and retracement of portion of subdivision of
T. 14 S., R. 31 E., of the Gila and Salt River Meridian, in the State of Arizona

executed by Clarence E. Bilbray, Cadastral Engineer

having been critically examined and found correct, are hereby approved.

Robert O. Clement
Assistant Chief, Division of Cadastral Engineering.

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in~~

~~is a true copy of the original field notes.~~

~~Chief, Division of Cadastral Engineering.~~