

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BOOK 4465

Original

# FIELD NOTES

of the Survey of

West Boundary

and

Partial Subdivision

of

Township 40 North, Range 1 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding-Cadastral Engineer

Under special instructions dated August 16, 1954, which provided  
for the surveys included under Group No. 294, approved Aug. 20, 1954  
and assignment instructions dated Oct. 4, 1954

Survey commenced Oct. 11, 1954

Survey completed Oct. 19, 1954

4465

4465

4465

1A

BOOK 4465

# INDEX DIAGRAM

Township 40 N., Range 1 W.

5 6	5	4	10 8	2	1
4 7	8	9	10 10	11	12
3 18	17	7 16	8 15	14	13
3 19	20	7 21	22	23	24
2 30	29	6 28	27	26	25
1 31	11 32	5 33	34	35	36

Partial Subdivision of T. 40 N., R. 1 W.

Chains

The north boundary of T. 40 N., R. 1 W. was surveyed by Andrew Nelson in 1911. The east boundary was surveyed by J. C. Thoma in 1914. The south boundary was surveyed by T. B. Mathews in 1916.

Special instructions provides for the survey of the secs. in which the State of Arizona has vested rights.

The survey was executed with a light mountain solar transit made by Buff and Buff, Serial No. 16724, constructed in accordance with standard instrumental specifications of the Bureau of Land Management. Horizontal circle is 4 1/2 inches in diameter with two double opposite verniers reading to single minutes. Vertical circle is 4 inches in diameter with one double vernier reading to single minutes. The instrument is equipped with an improved telescopic solar attachment, radii of latitude arc 3 inches and of declination arc 3 1/2 inches with vernier reading to single minutes. Instrument was in good condition and was placed in proper adjustment prior to the beginning of the survey.

The direction of all lines was determined by both the direct solar method and solar method and the measurements made by a Lufkin steel tape, 5 chains in length, graduated every one tenth link for the first 10 links, every link for the next 90 links, and every 10 links for the balance. The tape was tested by comparison with a standard tape and found correct. Measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment. The horizontal equivalents only are entered in this field note record.

The transit was checked from time to time on the meridian and the azimuth of the lines was checked by direct solar method as the survey progressed. The latitude of the SE. cor. of the township is 36°48'35" N.; longitude is 112°21'03" W. Magnetic declination is 16°00' E.

West Boundary of T. 40 N., R. 1 W.

From the cor. of secs. 1, 6, 31, and 36, Ts. 39 and 40 N., Rs. 1 and 2 W., set and marked as described in the official record.

North, bet. secs. 31 and 36.


Over rolling land, through dense sagebrush.

3.50 Draw, course SSW.; asc. 57 ft. over S. slope.

20.40 Road and ridge, bear E. and W.; desc. gradual N. slope.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.



1954

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

60.70 Road, track, bears SE. and NW.

80.00 Point for the cor. of secs. 25, 30, 31, and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.

## BOOK 4465

West Boundary of T. 40 N., R. 1 W.

Chains

T40N	
R2W	R1W
S25	S30
S36	S31
1954	

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay.  
Timber, none.  
Undergrowth, sagebrush.

North, bet. secs. 25 and 30.

Desc. 69 ft. over N. slope.

8.50 Wash, in draw, 15 lks. wide, 5 ft. deep, course NNE.; asc. 35 ft. over SE. slope.

13.00 Spur, flat, slopes NE.; desc. 80 ft. over NE. slope.

29.70 Wash, 30 lks. wide, 4 ft. deep, course NW.; asc. 40 ft. over SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$	
S 25	S 30

1954

Raise a mound of stone  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

Desc. 22 ft. over N. slope.

44.70 Wash, 10 lks. wide, 5 ft. deep, course W.

73.90 Telephone line, bears SE. and NW.

80.00 Point for the cor. of secs. 19, 24, 25, and 30.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T40N	
R2W	R1W
S24	S19
S25	S30
1954	

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
Soil, sandy clay.  
Timber, none.  
Undergrowth, sagebrush.

West Boundary of T. 40 N., R. 1 W.


Chains

North, bet. secs. 19 and 24.

Over gentle rolling land, through dense sagebrush.

40.00 Point for the 1/4 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.



1954

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.


57.30 Wash, 20 lks. wide, 3 ft. deep, course W.; asc. 44 ft. over S. slope.

65.90 Top of round hill; desc. 34 ft. over N. slope.

79.50 Road, track, bears E. and W.

80.00 Point for the cor. of secs. 13, 18, 19, and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, sagebrush.

North, bet. secs. 13 and 18.

Over gentle N. slope, through dense sagebrush.


6.00 Road, graded and graveled, bears SE. and NW.

22.40 Road, track, bears E. and W.

25.00 Spur, low and flat, slopes W.

40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



1954

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

43.00 Road, track, bears SE. and NW.

## BOOK 4465

West Boundary of T. 40 N., R. 1 W.

Chains											
64.60	Wash, 40 lks. wide, 4 ft. deep, course NW.; asc. over gentle S. slope.										
75.00	Ridge, low and flat, bears ESE. and WNW.										
80.00	Point for the cor. of secs. 7, 12, 16, and 18.										
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T40N</td></tr> <tr><td>R2W</td><td>R1W</td></tr> <tr><td>S12</td><td>S7</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1954</td></tr> </table>	T40N		R2W	R1W	S12	S7	S13	S18	1954	
T40N											
R2W	R1W										
S12	S7										
S13	S18										
1954											
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.										
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, sagebrush.										
	North, bet. 7 and 12.										
	Over gentle rolling land, through dense sagebrush.										
12.40	Road, track, and ridge, bear E. and W.; desc. over gradual N. slope.										
27.00	Wash, 30 lks. wide, 3 ft. deep, course NW.										
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 12.										
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2"><math>\frac{1}{4}</math></td></tr> <tr><td>S 12</td><td>  S 7</td></tr> <tr><td colspan="2">1954</td></tr> </table>	$\frac{1}{4}$		S 12	S 7	1954					
$\frac{1}{4}$											
S 12	S 7										
1954											
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.										
48.70	Wash, 20 lks. wide, 4 ft. deep, course WNW.										
65.00	Spur, low and flat, slopes W.										
69.20	Wash, 10 lks. wide, 2 ft. deep, course W.										
80.00	Point for the cor. of secs. 1, 6, 7, and 12.										
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T40N</td></tr> <tr><td>R2W</td><td>R1W</td></tr> <tr><td>S1</td><td>S6</td></tr> <tr><td>S12</td><td>S7</td></tr> <tr><td colspan="2">1954</td></tr> </table>	T40N		R2W	R1W	S1	S6	S12	S7	1954	
T40N											
R2W	R1W										
S1	S6										
S12	S7										
1954											
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.										
	Land, rolling. Soil, sandy clay. Timber, none. Underbrush, sagebrush.										

## West Boundary of T. 40 N., R. 1 W.

## Chains

North, bet. secs. 1 and 6.

Over rolling land, through dense sagebrush.

10.00 Ridge, low and flat, bears E. and W.; desc. 46 ft. over N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 1 | S 6

1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

58.50 Ridge, low and flat, bears E. and W.; desc. 34 ft. over N. slope.

78.50 Wash, 40 lks. wide, 2 ft. deep, course NNW.

81.20 Intersect the 10th Standard Parallel North.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T41NR1W

S31

S1 | S6

R2W | R1W

C | C

T40N

1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, S. of cor.

From above intersection point, the standard township cor. of Ts. 41 N., Rs. 1 and 2 W., bears West, 1.66 chs. dist.

Land, rolling.

Soil, sandy clay.

Timber, none.

Underbrush, sagebrush.

Beginning the partial subdivision of T. 40 N., R. 1 W., at the cor. of secs. 4, 5, 32, and 33 on the south boundary of the township.

N.  $0^{\circ} 02'$  W., bet. secs. 32 and 33.

Over rolling land, through dense sagebrush and scattered juniper.

26.20 Fence; bears NE. and SW.; leave scattered juniper; desc. 58 ft. over N. slope.

32.00 Center of dike; W. side of dirt tank, approximately 1 acre in size.

33.70 Draw, course WNW.; asc. 35 ft. over S. slope.

34.20 Fence, bears E. and W.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

Partial Subdivision of T. 40 N., R. 1 W.

Chains

$\frac{1}{4}$

S 32 | S 33

1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Asc. 25 ft. over rocky SW. slope.

57.10 Road, track, bears E. and W.; desc. 23 ft. over N. slope.

72.20 Wash, 20 lks. wide, 3 ft. deep, course NW.

80.00 Point for the cor. of secs. 28, 29, 32, and 33.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T40NR1W

S29 | S28

S32 | S33

1954

Land, rolling hills.

Soil, sandy clay.

Timber, scattered juniper.

Undergrowth, sagebrush.

N. 0° 02' W., bet. secs. 28 and 29.

Over rolling land, through dense sagebrush.

6.00 Wash, 20 lks. wide, 2 ft. deep, course W.

19.30 Enter scattered greasewood and juniper.

24.30 Wash, 10 lks. wide, 4 ft. deep, course NW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 29.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S 29 | S 28

1954

43.50 Wash, 10 lks. wide, 2 ft. deep, course W.

63.00 Road, track, bears E. and W.; desc. 48 ft. over N. slope.

69.00 Road, track, bears E. and W.

80.00 Point for the cor. of secs. 20, 21, 28, and 29.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

T40NR1W

S20 | S21

S29 | S28

1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

## Partial Subdivision of T. 40 N., R. 1 W.

Chains	
	<p>Land, rolling. Soil, sandy clay. Timber, scattered juniper. Undergrowth, sagebrush.</p>
	<p>N. 0° 02' W., bet. secs. 20 and 21.</p> <p>Over rolling land, through dense sagebrush and scattered juniper.</p>
10.80	Wash, 20 lks. wide, 5 ft. deep, course NW.
32.00	Leave scattered juniper.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 20   S 21</p> <p style="text-align: center;">1954.</p>
58.40	Wash, 30 lks. wide, 4 ft. deep, course WNW.
80.00	Point for the cor. of secs. 16, 17, 20, and 21.
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, with brass cap, mkd.</p> <p style="text-align: center;">T40NRIW S17   S16 S20   S21 1954</p> <p>Raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy clay. Timber, scattered juniper. Undergrowth, dense sagebrush.</p>
	<p>N. 0° 02' W., bet. secs. 16 and 17.</p> <p>Over rolling land, through dense sagebrush.</p>
10.00	Wash, 10 lks. wide, 3 ft. deep, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 17   S 16</p> <p style="text-align: center;">1954</p> <p>Raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of cor.</p>
54.00	Wash, 15 lks. wide, 3 ft. deep, course W.

## Partial Subdivision of T. 40 N., R. 1 W.

## Chains

80.00

Point for the cor. of secs. 8, 9, 16, and 17.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T40NR1W	
S8	S9
S17	S16
1954	

Land, rolling.  
Soil, sandy clay.  
Timber, none.  
Undergrowth, dense sagebrush.

From the cor. of secs. 16, 17, 20, and 21.

N. 89° 57' E., bet. secs. 16 and 21.

Over rolling land, through dense sagebrush.

Desc. 29 ft. over E. slope.

16.50

Wash, 20 lks. wide, 2 ft. deep, course NNW.

27.00

Wash, 15 lks. wide, 6 ft. deep, course WNW.; asc. 26 ft. over gentle W. slope.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

S 16	
$\frac{1}{4}$	—
S 21	
1954	

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

75.20

Road, track, bears N. and S.

80.00

Point for the cor. of secs. 15, 16, 21, and 22.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T40NR1W	
S16	S15
S21	S22
1954	

Cor. is set on the edge of a track road which bears NE. and SW.

Land, rolling.  
Soil, sandy clay.  
Timber, none.  
Underbrush, dense sagebrush.

N. 0° 02' W., bet. secs. 15 and 16.

Over rolling land, through dense sagebrush.

BOOK 4465

Partial Subdivision of T. 40 N., R. 1 W.

Chains

- 7.00 Small wash, course NW.
- 12.00 Road, track, bears SE and NW.
- 22.60 Desc. 22 ft. over gentle N. slope.
- 26.00 Wash, 10 lks. wide, 4 ft. deep, course NW.
- 35.00 Wash, 15 lks. wide, 4 ft. deep, course NW.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 16 | S 15

1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

- 50.40 Wash, 10 lks. wide, 3 ft. deep, course NW.

- 64.60 Small wash, course NW.

- 80.00 Point for the cor. of secs. 9, 10, 15, and 16.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

T40NR1W

S9 | S10

S16 | S15

1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
 Soil, sandy clay.  
 Timber, none.  
 Undergrowth, dense sagebrush.

S. 89° 51' W., bet. secs. 9 and 16.

Over rolling land, through dense sagebrush.

- 14.20 Wash, 15 lks. wide, 10 ft. deep, course N.

- 39.98 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 16.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

S 9

$\frac{1}{4}$

S 16

1954

- 41.20 Road, track, bears N. and S.

- 47.60 Wash, 15 lks. wide, 4 ft. deep, course NW.

## Partial Subdivision of T. 40 N., R. 1 W.

Chains	
60.00	Wash, 20 lks. wide, 6 ft. deep, course NW.
80.00	<p>The cor. of secs. 8, 9, 16, and 17,</p> <p>Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, dense sagebrush.</p>
	From the cor. of secs. 9, 10, 15, and 16.
	N. 0° 02' W., bet. secs. 9 and 10.
	Over rolling land, through dense sagebrush.
7.20	Wash, 10 lks. wide, 4 ft. deep, course WNW.
13.30	Desc. 40 ft. over N. slope.
18.30	Wash, 10 lks. wide, 4 ft. deep, course W.; asc. 50 ft. over rocky S. slope.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math></p> <p style="text-align: center;">S 9   S 10</p> <p style="text-align: center;">1954</p>
41.00	Ridge, low and flat, bears E. and W.; desc. 69 ft. over general NW. slope.
55.40	Wash, 10 lks. wide, 4 ft. deep, course NW.
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T40NR1W</p> <p style="text-align: center;">S4   S3</p> <p style="text-align: center;">S9   S10</p> <p style="text-align: center;">1954</p> <p>Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, dense sagebrush.</p>
	N. 0° 02' W., bet. secs. 3 and 4.
	Over rolling land, through dense sagebrush and scattered greasewood.
1.40	Small wash, course WNW.
9.50	Wash, 10 lks. wide, 3 ft. deep, course WNW.
26.40	Wash, 20 lks. wide, 4 ft. deep, course W.

Partial Subdivision of T. 40 N., R. 1 W.

Chains

40.00

Point for the 1/4 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4

S 4 | S 3

1954

Desc. 28 ft. over NE. slope.

44.00

Small wash, course WNW.

52.00

Rocky canyon, 5 chs. wide, 75 ft. deep, course W.

61.00

Enter scattered juniper.

62.00

Wash, 10 lks. wide, 3 ft. deep, course WSW.; asc. 40 ft. over S. slope.

66.00

Spur, low and flat, slopes W.

74.60

Wash, 10 lks. wide, 4 ft. deep, course WSW.

80.84

Intersect the 10th Standard Parallel North.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.

T41N

S34

S 4 | S 3

C | C

T40NR1W

1954

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of cor.

From above point, the Standard cor. of secs. 33 and 34, T. 41 N., R. 1 W., bears West, .6 lks. dist.

Land, rolling.

Soil, sandy clay.

Timber, scattered juniper.

Undergrowth, sagebrush and scattered greasewood.

From the cor. of secs. 5, 6, 31, and 32, on the south boundary of the township.

N. 0° 08' W., bet. secs. 31 and 32.

Over rolling land, through dense sagebrush and scattered juniper.

8.70

Telephone line, bears SE. and NW.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4

S 31 | S 32

1954

Partial Subdivision of T. 40 N., R. 1 W.

Chains

51.80

Road, track, bears E. and W.

80.00

Point for the cor. of secs. 29, 30, 31, and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T40MR1W  
S30 | S29  
S31 | S32  
1954

Land, rolling.  
Soil, sandy clay.  
Timber, scattered juniper.  
Undergrowth, dense sagebrush and scattered greasewood.

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 53' W., bet. secs. 29 and 32.

9.70

Wash, 20 lks. wide, 3 ft. deep, course NW.

17.00

Small wash, course N.

34.50

Wash, 10 lks. wide, 4 ft. deep, course N.

40.00

Spur, slopes NW.

40.06

Point for the ¼ sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

S 29

¼  
S 32

1954

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

Desc. 61 ft. over W. slope.

47.70

Road, track, bears SE. and NW.

48.75

Small wash, course NW.; asc. 30 ft. over E. slope.

55.00

Spur, slopes NW.; desc. 23 ft. over W. slope.

60.00

Wash, 20 lks. wide, 3 ft. deep, course NNW.; asc. 40 ft. over E. slope.

64.30

Road, graded and graveled, bears N. and S.

69.00

Road, track, bears N. and S.

80.00

The cor. of secs. 29, 30, 31, and 32.

Land, Rolling.  
Soil, sandy clay.  
Timber, scattered juniper.  
Undergrowth, dense sagebrush and scattered greasewood.

Partial Subdivision of T. 40 N., R. 1 W.

General Description

The east half of T. 40 N., R. 1 W., is covered with sagebrush, juniper, and sparse grass. The west half is mostly sagebrush and sparse grass. Most of the land is low rolling ridges with low breaks. The only water is man made tanks, The soil is third and fourth rate. The general drainage is to the northwest.



15

# CERTIFICATE OF CADASTRAL ENGINEER

50-217-4400

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of August, 1954,

I have surveyed the West Boundary and part of the subdivision of T. 40 N., R. 1 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

June 6, 1955

*Donald E. Harding*  
Donald E. Harding

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., OCT 25 1955, 1955

The foregoing field notes of the survey of the West Boundary and part of the subdivision of T. 40 N., R. 1 W., G & S R, Meridian of Arizona

executed by Donald E. Harding having been critically examined and found correct, are hereby approved.

*Earl G. Harrington*  
Chief, Division of Cadastral Engineering.  
Cadastral Engineering Staff Officer

## CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.~~

~~Chief, Division of Cadastral Engineering.~~