

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the Survey of

South Boundary

and

West Boundary

and

Partial Subdivision

of

Township 40 North, Range 2 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding - Cadastral Engineer

Under special instructions dated August 16, 1954, which provided
for the surveys included under Group No. 294, approved August 20, 1954
and assignment instructions dated October 4, 1954.

Survey commenced October 20, 1954.

Survey completed October 29, 1954.

1A

BOOK 4466

INDEX DIAGRAM

Township 40 North, Range 2 West

10 6	5	4	3	2	1
9 7	8	9	10	11	12
8 18	17	16	15	14	13
7 19	20	21	22	23	24
6 30	29	28	27	26	25
5 31	13 32	13 33	34	35	12 36
4	3	3	2	1	1

Partial Subdivision of T. 40 N., R. 2 W.

Chains

The north boundary of T. 40 N., R. 2 W., was surveyed by Nelson and Stumm in 1911. The east boundary was provided for under the survey of T. 40 N., R. 1 W.

For a check of the instruments and tapes see the notes for T. 40 N., R. 1 W.

The geographic position of the southeast corner of the township is latitude 36°48'55" N., longitude 112°27'32" W. The mean magnetic declination is 16°00' E.

South Boundary of T. 40 N., R. 2 W.

From the cor. of secs. 1, 6, 31, and 36, Ts. 39 and 40 N., Rs. 1 and 2 W., set and marked as described in the official record.

West, bet secs. 1 and 36.

Over rolling land, through dense sagebrush.

8.50 Draw, course SSW.; asc. gradual E. slope.

15.00 Road, track, bears N. and S.

35.00 Slope changes to SW.; descending into draw.

38.55 Small wash, course S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

S 36
 $\frac{1}{4}$ ———
S 1
1954

42.40 Across rolling breaks on N. side of draw.

78.70 Small wash, course S.

80.00 Point for the cor. of secs. 1, 2, 35, and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T40NR2W
S35|S36
S2|S1
T39N
1954

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, dense sage brush and sparse grass.

West, bet. secs. 2 and 35.

Over rolling breaks on N. side of draw, through dense sagebrush and scattered greasewood.

BOOK 4466

South Boundary of T. 40 N., R. 2 W.

Chains	
4.60	Road, track, bears NE. and SW.
9.10	Small wash, course S.
22.10	Road, track, bears ESE. and WNW.
38.00	Desc. SW. slope into draw.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd. <div>S 35 $\frac{1}{4}$ ——— S 2 1954</div>
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
44.20	Small wash, course S.
52.20	Wash, in draw, 15 lks. wide, 3 ft. deep, course WNW; asc. 87 ft. over NE. slope.
80.00	Point for the cor. of secs. 2, 3, 34, and 35. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div>T40NR2W S34 S35 S3 S2 T39N 1954</div>
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, dense sagebrush and sparse grass.
	West, bet. secs. 3 and 34. Over rolling land, through dense sagebrush.
25.00	Wash, 10 lks. wide, 4 ft. deep, course N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div>S 34 $\frac{1}{4}$ ——— S 3 1954</div>
41.80	Small wash, course N.
52.70	Small wash, course N.
58.90	Small wash, course N.
63.70	Wash, 10 lks. wide, 4 ft. deep, course N.

South Boundary of T. 40 N., R. 2 W.

Chains	
77.70	Road, track, bears ESE. and WNW.
80.00	Point for the cor. of secs. 3, 4, 33, and 34. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> T40NR2W S33 S34 S4 S3 T39N 1954 </div> Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, dense sagebrush and sparse grass.
	West, bet. secs. 4 and 33. Over rolling land, through dense sagebrush.
9.00	Wash, 15 lks. wide, 4 ft. deep, course NNW.
12.00	Road, track, bears N. and S.
21.00	Wash, 10 lks. wide, 2 ft. deep, course N.
34.20	Wash, 10 lks. wide, 2 ft. deep, course N.
34.40	Road, track, bears N. and S.
40.00	Point for the ¼ sec. cor. of secs. 4 and 33. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> S 33 ¼ ————— S 4 1954 </div>
50.00	Desc. over gradual NW. slope.
80.00	Point for the cor. of secs. 4, 5, 32, and 33. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T40NR2W S32 S33 S5 S4 T39N 1954 </div> Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor. Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, dense sagebrush and sparse grass.
	West, bet. secs. 5 and 32.

South Boundary of T. 40 N., R. 2 W.

Chains	Over broken N. slope on S. side of draw.
3.30	Wash, 10 lks. wide, 3 ft. deep, course N.; asc. 29 ft. over E. slope.
12.50	Desc. 80 ft. over ledges on NW. slope.
25.83	Wash, 20 lks. wide, 4 ft. deep, course NNW.; asc. 60 ft. over ledges on E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd. <div>S 32 $\frac{1}{4}$ S 5</div> 1954
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor. Asc. 30 ft. over gentle E. slope.
59.20	Desc. 114 ft. over ledges on NW. slope.
72.10	Enter wash, in bottom of draw, course W. from ENE.
77.10	Leave wash, course SW.
80.00	Point for the cor. of secs. 5, 6, 31, and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. <div>T40NR2W S31 S32 S6 S5 T39N 1954</div> Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, dense sagebrush and sparse grass.
	West, bet. secs. 6 and 31. Over rolling hills, through dense sagebrush.
4.00	Wash, 10 lks. wide, 4 ft. deep, course N.
9.80	Asc. 146 ft. over rocky NW. slope.
16.70	Across rolling top.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd. <div>S 31 $\frac{1}{4}$ S 6</div> 1954

South Boundary of T. 40 N., R. 2 W.

Chains Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
 Desc. over gradual W. slope.
 45.20 Wash, 10 lks. wide, 2 ft. deep, course N.
 54.00 Road, track, bears ESE. and WNW.
 76.81 Intersect the E. bdy. of T. 39 N., R. 3 W.
 Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 ins. in the ground,
 and in a mound of stone to top, with brass cap mkd.

T39N	T40N
R3W	R2W
S1	S31
	S6
	T39N

1954

From above intersection point, the cor. of secs. 1 and 36, Ts. 39 and 40 N., R. 3 W., bears North, 6.11 chs. dist., monumented with an iron post, .3 ins. in diam., properly set and marked as described below.

T40N	
R3W	R2W
S36	S31
S1	S6
T39N	

1914

I delete these markings and remark the iron post.

T40N	T40N
R3W	R2W
S36	S31
S1	
T39N	

1914

Land, rolling hills.
 Soil, sandy and rocky clay.
 Timber, none.
 Undergrowth, dense sagebrush and sparse grass.

Survey of the west boundary of T. 40 N., R. 2 W., and the establishment of the cors. for T. 40 N., R. 3 W., at regular intervals north of the cor. of Ts. 39 and 40 N., R. 3 W.

North, on the west bdy. of sec. 31.

Over rolling hills, through sagebrush.

6.11 The cor. of secs. 1 and 36, Ts. 39 and 40 N., R. 3 W.
 11.40 Desc. 80 ft. over N. slope.
 17.20 Wash, 10 lks. wide, 2 ft. deep, course W.; asc. 63 ft. over S. slope.
 21.00 Spur, slopes W.; desc. 66 ft. over N. slope.
 33.10 Wash, 40 lks. wide, 4 ft. deep, course W.
 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 31.
 Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

West Boundary of T. 40 N., R. 2 W.

Chains	<div><div><div><div><div></div><div>1/4</div><div>S 31</div></div><div>1954</div><div>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, E. of cor.</div></div><div><div>44.20</div><div>Wash, .5 ft. wide, 3 ft. deep, course SW.</div></div><div><div>46.11</div><div>Point for the 1/4 sec. cor. of sec. 36.</div><div>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</div></div><div><div><div><div><div></div><div>1/4</div><div>S 36</div></div><div>1954</div><div>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.</div></div><div><div>54.00</div><div>Road, track, bears E. and WNW.</div></div><div><div>71.10</div><div>Wash, 10 lks. wide, 3 ft. deep, course SW.</div></div><div><div>80.00</div><div>Point for the cor. of secs. 30 and 31.</div><div>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</div></div><div><div><div><div><div><div>T40N</div><div>R3W</div><div>S36</div></div><div><div>S30</div><div>S31</div><div>R2W</div></div></div><div>1954</div><div>Land, rolling hills.</div><div>Soil, sandy and rocky clay.</div><div>Timber, none.</div><div>Undergrowth, scattered sagebrush, cacti, and sparse grass.</div></div></div></div></div></div></div></div>
	<div><div>North, on the W. bdy. of sec. 30.</div><div>Asc. 37 ft. over S. slope.</div><div><div>6.00</div><div>Fence, bears E. and W., on spur sloping W.</div></div><div><div>6.11</div><div>Point for the cor. of secs. 25 and 36.</div><div>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</div></div><div><div><div><div><div><div>T40N</div><div>R2W</div><div>S25</div></div><div><div>S36</div><div>S30</div><div>R3W</div></div></div><div>1954</div><div>14.00</div><div>Canyon, 30 ft. deep, 100 ft. wide, course WNW.</div></div></div></div></div>

West Boundary of T. 40 N., R. 2 W.

Chains	
23.80	Desc. over NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 30. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div><div>$\frac{1}{4}$</div><div>S 30</div></div> 1954 Over level ground.
46.11	Point for the $\frac{1}{4}$ sec. cor. of sec. 25. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div><div>$\frac{1}{4}$</div><div>S 25</div></div> 1954
47.00	Wash, 10 lks. wide, 2 ft. deep, course NW.
60.60	Wash, 10 lks. wide, 4 ft. deep, course NW.
68.30	Wash, 15 lks. wide, 4 ft. deep, course NW.
80.00	Point for the cor. of secs. 19 and 30. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd. <div><div>T40N R3W R2W S25 S19 S30</div><div>1954</div></div> Land, rolling. Soil, sandy and rocky clay. Timber, none. Undergrowth, scattered greasewood, cacti, and sparse grass.
6.11	North on the W. bdy. of sec. 19. Over flats; through sagebrush. Point for the cor. of secs. 24 and 25. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd. <div><div>T40N R3W R2W S24 S19 S25</div><div>1954</div></div> Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

West Boundary of T. 40 N., R. 2 W.

Chains

12.10 Wash, 10 lks. wide, 4 ft. deep, course NW.

15.20 Wash, 50 lks. wide, 6 ft. deep, course W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S 19

1954

46.11 Point for the $\frac{1}{4}$ sec. cor. of sec. 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 24

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

80.00 Point for the cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T40N

R3W | R2W

S24 | S18

S19

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

Land, flat.

Soil, sandy clay.

Timber, none.

Undergrowth, scattered sagebrush and sparse grass.

North, on the W. bdy. of sec. 18.

Over flats, through sagebrush and wheat grass.

6.11 Point for the cor. of secs. 13 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T40N

R3W | R2W

S13 | S18

S24

1954

Deposit a stone 4x3x1 ins. marked with an "X" at the base of the post, for witness.

BOOK 4466

West Boundary of T. 40 N., R. 2 W.

Chains	
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
16.10	Wash, 20 lks. wide, 4 ft. deep, course W.
37.40	Johnson Wash, 2 chs. wide, 25 ft. deep, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 7 falls on the bank of a wash.
40.50	Point for the witness $\frac{1}{4}$ sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<div><div><div><div><div></div><div>$\frac{1}{4}$</div><div>S 7</div><div>W C</div></div><div>1954</div></div></div></div>
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.
46.11	Point for the $\frac{1}{4}$ sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<div><div><div><div><div></div><div>$\frac{1}{4}$</div><div>S 12</div></div><div>1954</div></div></div></div>
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
80.00	Point for the cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.
	<div><div><div><div><div>T40N</div><div>R3W R2W</div><div>S12 S6</div><div>S7</div></div><div>1954</div></div></div></div>
	Deposit a stone 4x3x1 ins., marked with an "X" at the base of the post, for witness.
	Land, flats.
	Soil, sandy clay.
	Timber, none.
	Undergrowth, sāgebrūsh and wheat grass.
	North on the W. bdy.. of sec. 6.
	Over flats, through sagebrush and wheat grass.
5.00	Wash, 10 lks. wide, 6 ft. deep, course SW.
6.11	Point for the cor. of secs. 1 and 12.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.

BOOK 4466

West Boundary of T. 40 N., R. 2 W.

Chains	
	<div>T40N</div> <div>R3W R2W</div> <div>S1 S6</div> <div>S12</div> <div>1954</div> <div>Deposit a stone, 4x3x1 ins., marked with an "X" at the base of the post, for witness.</div>
7.40	Road, track, bears NE. and SW.
40.00	<div>Point for the $\frac{1}{4}$ sec. cor. of sec. 6.</div> <div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</div> <div><div>$\frac{1}{4}$</div><div>S 6</div></div> <div>1954</div> <div>Deposit a stone, 5x4x2 ins., mkd. with an "X" at the base of the post, for witness.</div>
46.11	<div>Point for the $\frac{1}{4}$ sec. cor. of sec. 1</div> <div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</div> <div><div>$\frac{1}{4}$</div><div>S 1</div></div> <div>1954</div> <div>Deposit a stone, 5x4x2 ins., marked with an "X" at the base of the post, for witness.</div>
67.30	Wash, 60. lks. wide, 20 ft. deep, course SW.
80.43	<div>Intersect the 10th Standard Parallel N.</div> <div>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</div> <div><div>T41NR2W</div><div>S31</div><div>S 1 S 6</div><div>R3W R2W</div><div>C C</div><div>T40N</div><div>1954</div><div>Deposit broken glass alongside the iron post, for witness.</div><div>From above point, the standard witness cor. of Ts. 41 N., Rs. 2 and 3 W., bears West, 3.30 chs. dist.</div><div>Land, flats.</div><div>Soil, sandy clay.</div><div>Timber, none.</div><div>Undergrowth, sagebrush and wheat grass.</div></div>

Partial Subdivision of T. 40 N., R. 2 W.

Chains	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township.</p> <p>N. 0° 01' W., bet. secs. 35 and 36.</p> <p>Over rolling land, through sagebrush and scattered greasewood.</p> <p>4.20 Road, track, bears E. and W..</p> <p>13.60 Small wash, course WNW.</p> <p>24.60 Wash, 10 lks. wide, 4 ft. deep, course W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <div>$\frac{1}{4}$ S 35 S 36 1954</div> <p>80.00 Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <div>T40NR2W S26 S25 S35 S36 1954</div> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, sagebrush and scattered greasewood.</p>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the township.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling land, through sagebrush and sparse grass.</p> <p>8.00 Road, track, bears N. and S.</p> <p>40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <div>$\frac{1}{4}$ S 25 S 36 1954</div> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.</p> <p>70.00 Desc. over gentle W. slope.</p>

BOOK 4466

Partial Subdivision of T. 40 N., R. 2 W.

Chains	
80.02	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, sagebrush and greasewood.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the township.</p> <p>N. 0° 02' W., bet. secs. 32 and 33.</p> <p>Over rolling hills, through dense sagebrush and sparse grass.</p>
2.20	Wash, 20 lks. wide, 4 ft. deep, course W.; asc. 82 ft. over S. slope.
21.10	Road, track, bears E. and W.
29.50	Ridge, flat, bears E. and W.; desc. 105 ft. over N. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 32 S 33</p> <p style="text-align: center;">1954</p>
	Desc. 92 ft. over N. slope.
72.50	Wash, 10 lks. wide, 4 ft. deep, course W.
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40NR2W S29 S28 S32 S33 1954</p>
	<p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy and rocky clay. Timber, none. Undergrowth, sagebrush, scattered greasewood and sparse grass.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the township.</p> <p>N. 0° 03' W., bet. secs. 31 and 32.</p> <p>Over rolling hills, through sagebrush, scattered greasewood, and sparse grass.</p> <p>Asc. 102 ft. over S. slope.</p>

BOOK 4466

Partial Subdivision of T. 40 N., R. 2 W.

Chains	
18.50	Ridge, flat, bears E. and W.
34.50	Wash, 10 lks. wide, 3 ft. deep, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 31 S 32 1954 Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
50.00	Desc. 109 ft. over NW. slope.
76.00	Road, track, bears NE. and SW.
77.20	Wash, 20 lks. wide, 2 ft. deep, course SW.
80.00	Point for the cor. of secs. 29, 30, 31, and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T4ONR2W S30 S29 S31 S32 1954 Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, sagebrush and scattered greasewood.
	From the cor. of secs. 28, 29, 32, and 33. N. 89° 57' W., bet. secs. 29 and 32. Over rolling land, through sagebrush and sparse grass. Asc. 20 ft. over NE. slope.
10.00	Desc. W. slope.
17.90	Wash, 20 lks. wide, 3 ft. deep, course NW.; asc. 35 ft. over NE. slope.
23.00	Spur, low and flat, slopes NW.; desc. 67 ft. over NMW. slope.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 29 S 32 1954 Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Partial Subdivision of T. 40 N., R. 2 W.

Chains	
55.40	Road, track, bears N. and S.
58.70	Wash, 10 lks. wide, 3 ft. deep, course WNW.
65.00	Wash, course SW.
66.80	Road, track, bears NE. and SW.
79.86	The cor. of secs. 29, 30, 31, and 32.
	Land, rolling.
	Soil, sandy clay.
	Timber, none.
	Undergrowth, sagebrush and scattered greasewood.
General Description	
T. 40 N., R. 2 W., is low rolling ridges and flats covered with dense sagebrush, scattered greasewood, and sparse grass. There is no water within the boundaries, no farming and no one living within the township. The general drainage is to the West into Kanab Wash. Soil is third and fourth rate, only good for grazing.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BOOK 4466

FIELD ASSISTANTS

[illegible]

19
BOOK 4466

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 16th day of August, 1954,
I have surveyed the South Boundary, the West Boundary and part of the subdivision
of T. 40 N., R. 2 W.

of the G & S R Meridian, in the State of Arizona; which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

June 8, 1955

Donald E. Harding
Donald E. Harding

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., OCT 25 1955, 19

The foregoing field notes of the survey of the South Boundary, the West Boundary and
part of the subdivision of T. 40 N., R. 2 W., G & S R Meridian of Arizona

executed by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Chief, Division of Cadastral Engineering.
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in~~
~~_____ is a true copy of the original field notes.~~

~~Chief, Division of Cadastral Engineering~~