UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT ORIGINAL

FIELD NOTES

OF THE	SURVEY	
Ol	3	
A PORTION OF THE	HE SUBDIVISION	
I		·
TOWNSHIP 35 NOR		
JON CC TIMENWOI	in, RANGE J WEST	
	·	
Of the Gila and	d Salt River	. Meridian,
In the State ofA	rizona	
E X E C U T		
EXECU	IED BY	
Donald A. Cannon -	Cadastral Survey	vor
	·	
Under special instructions dated	ctober 9	, 1958, which provided
for the surveys included under Group No	329 , appr	oved October 13, 1958
and assignment instructions dated	February 26	, 1959
Survey commenced	February 2	, 1959
Survey completed	April 7	. 1959

U. S. GOVERNMENT PRINTING OFFICE 16-56770-1

BOOK 4572 INDEX DIAGRAM

Towns	ship	35	North	ı	, <i>F</i>	<i>Kange</i>	5_W	lest		
6	32	5	23	4	17	3		2		1
31	_	31		22		16				6
7	30	8	22	9	16	10	11	11	6	12
30		29		21		15		10		5
18	28	17	21	16	15	15	10	14	5	13
28	_	27		20		14		9		4
19 26	27	20	20	21 19	14	22 13	9	23	3	24 3
30	25	29	19	28	13	27	8	26	2	25
24		24		18		12		7		2
31	23	32	18	38	11	34	7	35	1	36
										1656770-1

Township 35 North, Range 5 West

Chains

The west boundary was surveyed by W. E. Hiester in 1923. The south, east and north boundaries and a portion of the subdivision were surveyed by H. G. Parker in 1954. The west 1 mile of the north boundary was resurveyed by D. A. Cannon in 1958.

The following field notes are a survey of the completion of the subdivisional lines in Township 35 North, Range 5 West.

The survey was executed with a W. and L. E. Gurley solar transit, serial No. 541331, conforming to the standard specifications of the Bureau of Land Management. The instrument was maintained in good adjustment throughout the progress of the survey.

The directions of all lines of the survey were determined from meridians established by observations upon the sun and Polaris during the survey.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by the random and true method, but for simplification of the record, the random lines are omitted from these field notes.

Measurements were made with a narrow steel tape, 8 chains in length, graduated every link for the first chain and thereafter at intervals of every 10 links. The tape was tested by comparison with a standard steel tape, one chain in length, and found to be correct. All measurements were made on the slope and the vertical angle of each interval determined by use of a clinometer in good adjustment; the horizontal equivalents only are entered in the field note record.

The lengths of all lines in this survey were determined by chaining wherever possible. The inaccessible lines were run by traverses or triangulation methods. The details of such traverses and triangulations have been thoroughly verified and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The geographic position for the southeast corner of the township is latitude 36° 22' 58.5" N. and longitude 112° 46' 12.5" W., as computed from U.S.G.S. triangulation station "Cedar" located in sec. 33.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be $15\,^\circ$ E.

Portion of the Subdivision, T. 35 N., R. 5 W.

Beginning at the true point for the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township which is witnessed W. 10.00 chs. dist by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 35 and 36.

Asc. abruptly 1000 ft. over ledges facing SW.

Rim of S. B. Canyon, a ledge about 20 ft. high, bears NW. and SE.; continue over rolling land, through medium growth of timber interspersed by open railed areas.

40.00 Point for the \(\frac{1}{2} \) sec. cor. of secs. 35 and 36.

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

		
Ch	nains	T35N R5W
		\$35 \sqrt{\$36} 1959
	. 1	Deposit glass at base of iron post.
		Continue over gently rolling land.
70	6.60	Road, bears NW. and SE.
80	0.00	Point for the cor. of secs. 25, 26, 35 and 36.
		Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T35N R5W S26 S25 S35 S36 1959 Deposit glass at base of iron post.
		Land, gently rolling table land.
		Soil, sandy loam. Timber, medium juniper and pinon, interspersed with railed areas. Undergrowth, thinly scattered buck brush, Mormon tea and Spanish daggers.
	`	
		From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
		N. 89° 56' W., bet. secs. 25 and 36.
,	*	Over rolling table land, through medium growth of timber, interspersed with open railed areas.
3	1.40	Fence, bears N. and S.
3	6.50	Wash, 10 1ks. wide, 2 ft. deep, drains SE.
4	0.17	Point for the 1/2 sec. cor. of secs. 25 and 36.
	•	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.
		T35N R5W
		335 S36 1959
		Continue over rolling land
5	8.80	Unimproved road, bears NE. and SW.
8	0.34	The cor. of secs. 25, 26, 35 and 36.
		Land, rolling. Soil, sandy loam. Timber, medium to dense juniper and pinon.
	•	N. 0° 01' W., bet. secs. 25 and 26.
		Over rolling land, through medium to dense timber interspersed with railed areas.

Portion of	the Subdiv	ision, T.	35	Ν.,	R.	5 W	

i	
Chains	
40.00	Point for the ½ sec. cor. of secs. 25 and 26.
-	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$26 \$25 1959
	Deposit glass at base of iron post.
	Continue over rolling table land.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W S23 S24
	S26 S25 1959
	Deposit glass at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, medium juniper and pinon. Undergrowth, sage, bitter brush and buck brush.
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	N. 89° 53' W., bet. secs. 24 and 25.
	Over rolling land, through medium timber interspersed with railed areas.
40.08	Point for the ½ sec. cor. of secs. 24 and 25.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$\frac{\frac{1}{4} \cdot \frac{\frac{1}{2} \cdot \frac{1}{2}}{\frac{1}{2} \frac{1}{2}}} \tag{1959}
	Deposit glass at base of post.
49.50	Unimproved road, bears NW. and SE.
52.00	Wash, bears NW. and SE.
54.50	Fence, bears N. and S.
80.16	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, sandy loam.
	Timber, juniper and pinon. Undergrowth, sage, bitter brush and oak brush.
	N. 0° 01' W., bet. secs. 23 and 24.
	Over rolling table land, through medium timber interspersed with railed areas.
Ì	

Chains 40.00	Point for the k see cor of secs 23 and 24
40.00	Point for the ½ sec. cor. of secs. 23 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground,
	with brass cap mkd.
	T35N R5W
	\$23 \$24 1959
	Deposit glass at base of cor.
	Continue over rolling land.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	<u>\$14 \ \$13 \ </u>
	1959
	Deposit glass at base of cor.
	Land, rolling. Soil, sandy loam.
	Timber, pinon and juniper. Undergrowth, sage, bitter brush and oak brush.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24.
	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
4.00	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed
4.00 27.40	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas.
	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE.
27.40	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
27.40	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W
27.40	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
27.40	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the $\frac{1}{2}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W T35N R5W S13 S24
27.40	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the ½ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W 1 S13 T35N R5W 1 S13 T35N R5W
27.40 40.00	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the ½ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \(\frac{1}{2} \frac{\text{S13}}{\text{S24}} \) \(\frac{1}{2} \frac{\text{S24}}{\text{1959}} \) Continue over rolling land.
27.40 40.00	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the $\frac{1}{2}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W 1 S13 2 S24 1959 Continue over rolling land. Fork of Robinson Wash, drains N. 10° W. Unimproved road, bears N. and S. Fence, bears N. 20° W. and S. 20° E.
27.40 40.00 63.00 65.00	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the $\frac{1}{2}$ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \frac{1}{2} \frac{513}{524} 1959 Continue over rolling land. Fork of Robinson Wash, drains N. 10° W. Unimproved road, bears N. and S.
27.40 40.00 63.00 65.00 78.60	township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 56' W., bet. secs. 13 and 24. Over rolling land, through medium timber interspersed with railed areas. Small wash, drains SW. from NE. Robinson Wash, drains NW. Point for the ½ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W 1 S13 2 S24 1959 Continue over rolling land. Fork of Robinson Wash, drains N. 10° W. Unimproved road, bears N. and S. Fence, bears N. 20° W. and S. 20° E.

Portion of	the	Subdivision,	Т.	35	Ν.,	R.	. 5	W	•
------------	-----	--------------	----	----	-----	----	-----	---	---

Chains	N. 0° 01' W., bet. secs. 13 and 14.
	Over rolling land, through medium timber interspersed with railed areas.
4.40	Fence, bears N. 20° W. and S. 20° E.
17.80	Fork of Robinson Wash, drains NE.
30.50	Unimproved road, bears N. 30° W. and S. 30° E.
35.00	Robinson Wash, drains NW.
40.00	Point for the 2 sec. cor. of secs. 13 and 14.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$\\\\\$14\\\$13\\\\\\\\\\\\\\\\\\\\\\\\\\\
	Deposit glass at base of iron post.
	Continue over rolling land.
45.40	Unimproved road, bears N. 40° E. and S. 40° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W S11 S12 S14 S13 1959
	Deposit glass at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, bitter brush, buck brush and oak brush.
	From the cor. of secs. 6, 7, 12 and 13 on the E. bdy. of the township monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	N. 89° 55' W., bet. secs. 12 and 13.
	Over rolling land, through medium growth of timber interspersed with railed areas.
8.70	Unimproved road, bears N. 40° W. and S. 40° E.
11.50	Wash, drains NW.
26.20	Unimproved road, bears N. 10° W. and S. 10° E.
31.10	Unimproved road, bears N. 30° E. and S. 30° W.
39.99	Point for the ½ sec. cor. of secs. 12 and 13.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Portion of the	Subdivision,	T.	35	Ν.,	R.	5	W.	

	!
Chains	T35N_R5W
	\$12 \$13 1959
	Deposit glass at base of iron post.
	Continue over rolling land.
79.98	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, bitter brush, buck brush and oak brush.
	N. 0° 01' W., bet. secs. 11 and 12.
	Over rolling land, through medium timber interspersed with railed areas.
40.00	Point for the ½ sec. cor. of secs. 11 and 12.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$11 S12 1959
56.00	Wash, 6 lks. wide, 1 ft. deep, drains SE.
56.90	Unimproved road, bears NW. and SE.
58.80	Unimproved road, bears NW. and SE.
80.00	The cor. of secs. 1, 2, 11 and 12, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, sage, bitter brush, buck brush and oak brush.
	T
	From the cor. of secs. 1, 6, 7 and 12.
	N. 89° 59' W., bet. secs. 1 and 12. Over rolling land, through medium timber interspersed with railed
3.00	Road, bears S. 10° W.
39.96	Point for the ½ sec. cor. of secs. 1 and 12.
39 . 90	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W 2 S1 3 S12 1959
	Continue over rolling land.

Portion	οf	the	Subd	ivision,	, T.	35	Ν.,	, R.	5	W

,	Total of the Bushington, It 35 Mt, Mt 5 M
Chains	
79.92	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, sandy loam.
	Timber, juniper and pinon.
	Undergrowth, sage, bitter brush, buck brush and oak brush.
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	N. 0° 01' W.,bet. secs. 34 and 35.
	Over rolling land, through medium timber interspersed with railed areas.
5.50	Wash, drains SW.
38.60	Unimproved road, bears NE. and SW.
40.00	Point for the 表 sec. cor. of secs. 34 and 35.
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W
	\$34 \$35 1959
54.70	Wash, 21 1ks. wide, 1 ft. deep, drains N. 60° E.
55.90	Unimproved road, bears NE.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	. T35N R5W
	<u>\$27 \$26</u>
	S34 S35. 1959
	Deposit wood ashes at base of iron post.
	Land, rolling.
	Soil, sandy loam.
	Timber, juniper and pinon. Undergrowth, sage, bitter brush, buck brush and oak brush.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89° 56' W., bet. secs. 26 and 35.
	Over rolling land, through medium timber interspersed with railed area.
11.50	Road, unimproved, bears N. 85° W. and S. 85° E.
39.97	Point for the 1/2 sec. cor. of secs. 26 and 35.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Portion of the Subdivision, T. 35 N., R. 5 W.

		Totalon of the Subdivision, 1. 35 M., K. 5 W.
	Chains	
		T35N R5W 1. S26
		₹ S35
		1959
		Continue over rolling land.
	40.60	Wash, drains S. 40° E
	62.90	Unimproved road, bears NE. and SW.
	79.94	The cor. of secs. 26, 27, 34 and 35.
		Land, rolling. Soil, sandy loam. Timber, juniper and pinon.
		Undergrowth, sage, bitter brush, buck brush and oak brush.
		•
		N. 0° 01' W., bet. secs. 26 and 27.
		Over rolling land, through medium timber interspersed with railed area.
	16.30	Unimproved road, bears E. and W.
	40.00	Point for the ½ sec. cor. of secs. 26 and 27.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
		T35N R5W
		\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
		Raise a mound of stone W. of cor.
		Continue over rolling land.
	66.90	Shallow draw, drains N. 40° E.
	80.00	Point for the cor. of secs. 22, 23, 26 and 27.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
		T35N R5W
		S22 S23 S27 S26
		1959
		Deposit glass at base of iron post.
		Land, rolling. Soil, sandy loam.
		Timber, pinon and juniper. Undergrowth, sage, bitter brush, buck brush and oak brush.
		From the cor. of secs. 23, 24, 25 and 26.
		S. 89° 57' W., bet. secs. 23 and 26.
		Over rolling land, through medium growth of timber, interspersed with railed areas.
	39.99	Point for the ½ sec. cor. of secs. 23 and 26.
<u> </u>		

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	½ <u>S23</u>
	\$26 1959
	Continue over rolling land.
71.20	Shallow draw, drains NE. and SW.
79.98	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling.
	Soil, sandy loam. Timber, pinon and juniper.
	Undergrowth, sage, bitter brush, buck brush and oak brush.
	N. 0° 01' W., bet. secs. 22 and 23.
	Over rolling land, through medium timber interspersed with railed areas.
40.00	Point for the 2 sec. cor. of secs. 22 and 23.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	14 022 022
	S22 S23 1959
	Deposit charcoal at base of iron post.
	Continue over rolling land.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	<u>\$15 \$14 </u>
	S22 S23 1959
	Deposit charcoal at base of iron post.
	Land, rolling.
	Soil, sandy loam.
	Timber, juniper and pinon. Undergrowth, sage, bitterbrush, buck brush and oak brush.
	From the cor. of secs. 13, 14, 23 and 24.
	West, bet. secs. 14 and 23.
	Over rolling land, through medium timber interspersed with railed areas.
9.40	Shallow draw, drains NE.
40.00	Point for the ½ sec. cor. of secs. 14 and 23.
	Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

Portion	οf	the	Subdivision,	Т.	35	Ν.,	R.	5	W	•

Chains	
	T35N R5W 2 S14
	S23 1959
	Deposit glass at base of iron post.
	Continue over rolling land.
80.00	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling.
	Soil, sandy loam. Timber, pinon and juniper.
	Undergrowth, sage, bitter brush, buck brush and oak brush.
	N. 0° 01' W., bet. secs. 14 and 15.
	Over rolling land, through medium timber interspersed with railed areas.
40.00	Point for the ½ sec. cor. of secs. 14 and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$15 \$14 1959
	Deposit glass at base of cor.
	Continue over rolling land.
60.10	Unimproved road, bears S. 75° E. and N. 75° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W S10 S11
	S15 S14
	I and rolling
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
	Undergrowth, sage, bitter brush, buck brush and oak brush.
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89° 57' W., bet. secs. 11 and 14.
30.00	Fence, bears N. 20° W. and S. 20° E.
35.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 20° W.
40.01	Point for the ½ sec. cor. of secs. 11 and 14.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	T35N R5W 2 S11 S14 1959
	Deposit glass at base of iron post.
41.30	Unimproved road, bears NW. and SE.
80.02	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
•	N. 0° 01'W ., bet. secs. 10 and 11.
	Over rolling land, through medium timber interspersed with railed areas
19.00	Unimproved road, bears NE. and SW. in wash draining NE.
38.70	Unimproved road, bears E. and W.
40.00	Point for the ½ sec. cor. of secs. 10 and 11.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W 支 S10 S11 1959
	Deposit glass at base of iron post.
	Continue over rolling land.
43.10	Low spur, slopes S. 70° E.
47.30	Wash, 30 1ks. wide, 4 ft. deep, drains S. 70° E.
57.20	Low spur, slopes S. 50° W.
80.00	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, bitter brush, buck brush and oak brush.
-	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	N. 0° 02' W., bet. secs. 33 and 34.
	Over rolling land, through medium timberinterspersed with railed areas
13.30	Low ridge, bears E. and W.; desc. 60 ft. over gently rolling NE. slope
40.00	Point for the ½ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T35N R5W \$33 \$S34 1959 Continue over rolling land draining NE. Spur, slopes N. 30° E. from SE. Small wash, drains N. 30° E. Fence, bears E. and W. Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W \$28 S27 \$33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
S33 S34 1959 Continue over rolling land draining NE. Spur, slopes N. 30° E. from SE. Small wash, drains N. 30° E. Fence, bears E. and W. Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Continue over rolling land draining NE. Spur, slopes N. 30° E. from SE. Small wash, drains N. 30° E. Fence, bears E. and W. Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Spur, slopes N. 30° E. from SE. Small wash, drains N. 30° E. Fence, bears E. and W. Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 R33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Small wash, drains N. 30° E. Fence, bears E. and W. Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Fence, bears E. and W. Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Spur, slopes N. 70° E.; desc. N. slope. Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
with brass cap mkd. T35N R5W S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
S28 S27 S33 S34 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
Soil, sandy loam. Timber, pinon and juniper.
Undergrowth, sage, buck brush, Mormon tea and oak brush.
From the cor. of secs. 26, 27, 34 and 35.
N. 89° 49' W., bet. secs. 27 and 34.
Over rolling land, through medium timber interspersed with railed area
Unimproved road, bears N. and S.
Point for the ½ sec. cor. of secs. 27 and 34.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$\frac{\text{T35N R5W}}{\frac{1}{2}} = \frac{\frac{\text{S27}}{\text{S34}}}{\frac{1959}{}}$
Continue over rolling land.
Unimproved road, bears NE. and SW
Small wash, drains NE.
The cor. of secs. 27, 28, 33 and 34.
Land, rolling.

<u> </u>	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
	N. 0° 02' W., bet. secs. 27 and 28.
	Over rolling land draining E.
24.90	Center of flat drain, drains N. 70° E.
39.80	Spur, slopes N. 80° E.
40.00	Point for the 2 sec. cor. of secs. 27 and 28.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$28 \$27 1959
	Continue along rolling E. slope.
51.80	Spur, slopes E.
76.20	Wash, 10 1ks. wide, 1 ft. deep, drains N. 70° E.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground,
,	and in a collar of stone, with brass cap mkd.
,	T35N R5W S21 S22 S28 S27 1959
	Deposit glass at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89° 59' W., bet. secs. 22 and 27.
	Over rolling land, through medium timber interspersed with railed areas.
37.80	Unimproved road, bears N. 30° W. and S. 30° E.
39.93	Point for the ½ sec. cor. of secs. 22 and 27.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W 2 S22 S27 1959
	Continue over rolling land.
56.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.
69.60	Unimproved road, bears N. 30° W. and S. 30° E.

The cor. of secs. 21, 22, 27 and 28.

79.86

Chains	
	Land, rolling.
	Soil, sandy loam. Timber, juniper and pinon .
_	
	N. 0° 02' W., bet. secs. 21 and 22.
	Over rolling land, through medium timber interspersed with railed areas.
15.20	Unimproved road, bears N. 30° W. and S. 30° E.
40.00	Point for the ½ sec. cor. of secs. 21 and 22.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W
	\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	1959
	Continue over rolling land.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
-	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	S16 S15 S21 S22
	1959
	Land, rolling. Soil, sandy loam.
	Timber, juniper and pinon. Undergrowth, sage, Mormon tea and oak brush.
	offdergrowth, sage, formon ted did state.
	From the cor. of secs. 14, 15, 22 and 23.
	West, bet. secs. 15 and 22.
	Over rolling land, through medium timber interspersed with railed areas.
16.90	Wash, 4 lks. wide, 1 ft. deep, drains N. 15° W.
34.10	Wash, 12 lks. wide, 2 ft. deep, drains N. 40° E.
36.50	Unimproved road, bears NE. and SW.
39.93	Point for the ½ sec. cor. of secs. 15 and 22.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	$\frac{1}{4} \frac{\text{S15}}{\text{S22}}$
	1959
	Deposit glass at base of iron post.
	Continue over rolling land.
71.30	Unimproved road, bears N. 30° W. and S. 30° E.

	Portion of the Subdivision, T. 35 N., R. 5 W
Chains 79.86	The cor of sees 15 16 21 and 22
73.00	The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	N. 0° 02' W., bet. secs. 15 and 16.
	Over rolling land, through medium timber interspersed with railed areas.
40.00	Point for the ½ sec. cor. of secs. 15 and 16.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$16 \$15 1959
	Deposit glass at base of iron post.
	Continue over rolling land.
73.00	Unimproved road, bears N. 85° W. and S. 85° E.
76.10	Unimproved road, bears NW. and SE.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W S 9 S10 S16 S15 1959
	Deposit glass at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
·	From the cor. of secs. 10, 11, 14 and 15.
	S. 89° 57' W., bet. secs. 10 and 15.
	Over rolling land, through medium timber interspersed with railed areas.
7.00	Unimproved road, bears NE. from S.
7.50	Small wash, drains N. 60° E.
39.92	Point for the ½ sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd
	with brass cap mkd. T35N R5W $\frac{\$10}{\$15}$ 1959

Chains Deposit glass at base of iron post. Continue over rolling land. 79.84 The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. N. 0° 02' W., bet. secs. 9 and 10. Over rolling land, through medium timber interspersed with railed areas 3.50 Unimproved road, bears NE. and SW. 8.20 Wash, 10 lks. wide, 6 ins. deep, drains NW. Small wash, drains N. 35° E. 40.00 Point for the k sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2k ins. diam., 24 ins. in the ground, with brass cap mkd. T35N RW S 9 510 1959 Deposit glass at base of iron post. Continue over rolling land. 80.00 Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2k ins. diam., 24 ins. in the ground, with brass cap mkd. T35N RSW S 4 8 3 S 9 810 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the k sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2k ins. diam., 24 ins. in the ground, with brass cap mkd.		. Portion of the Subdivision, T. 35 N., R 5 W
Continue over rolling land. 79.84 The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. N. 0° 02' W., bet. secs. 9 and 10. Over rolling land, through medium timber interspersed with railed areas 3.50 Unimproved road, bears NE. and SW. 8.20 Wash, 10 lks. wide, 6 ins. deep, drains NW. 13.60 Small wash, drains N. 35° E. 40.00 Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W ½ S 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. 80.00 Point for the cor. of secs. 3, 4, 9 and 10, Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interapersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	Chains	
The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, sandy lowm. Timber, juniper and pinon. Undergrowth, sage, Normon tea, buck brush and oak brush. N. 0° 02' W., bet. secs. 9 and 10. Over rolling, land, through medium timber interspersed with railed areas 3,50 Unimproved road, bears NE. and SW. 8,20 Wash, 10 lks. wide, 6 ins. deep, drains NW. 13,60 Small wash, drains N. 35° E. 40,00 Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 9 \$10 1959 Deposit glass at base of iron post. Continue over rolling land. 80,00 Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 4 \$3 \$ 9 \$10 1359 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		Deposit glass at base of iron post.
Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. N. 0° 02' W., bet. secs. 9 and 10. Over rolling land, through medium timber interspersed with railed areas 3.50 Unimproved road, bears NE. and SW. 8.20 Wash, 10 lks. wide, 6 ins. deep, drains NW. 13.60 Small wash, drains N. 35° E. 40.00 Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 4 S 3		Continue over rolling land.
Soll, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. N. 0° 02' W., bet. secs. 9 and 10. Over rolling land, through medium timber interspersed with railed areas 3.50 Unimproved road, bears NE. and SW. Nash, 10 lks. wide, 6 ins. deep, drains NW. Small wash, drains N. 35° E. Point for the & sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 4 S 3 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59° W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the & sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	79.84	The cor. of secs. 9, 10, 15 and 16.
Over rolling land, through medium timber interspersed with railed areas 3.50 Unimproved road, bears NE. and SW. 8.20 Wash, 10 lks. wide, 6 ins. deep, drains NW. 13.60 Small wash, drains N. 35° E. 40.00 Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 9 310 1959 Deposit glass at base of iron post. Continue over rolling land. 80.00 Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 4 8 3 / 8 9 810 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. Prom the cor. of secs. 2, 3, 10 and 11. S. 89° 59¹ W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas. 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		Soil, sandy loam. Timber, juniper and pinon.
Over rolling land, through medium timber interspersed with railed areas 3.50 Unimproved road, bears NE. and SW. 8.20 Wash, 10 lks. wide, 6 ins. deep, drains NW. Small wash, drains N. 35° E. 40.00 Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 5 9 \$10 1959 Deposit glass at base of iron post. Continue over rolling land. 80.00 Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 4 8 3 / 8 9 \$10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59¹ W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
3.50 Unimproved road, bears NE. and SW. 8.20 Wash, 10 lks. wide, 6 ins. deep, drains NW. Small wash, drains N. 35° E. 40.00 Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W ½ S 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		N. 0° 02' W., bet. secs. 9 and 10.
8.20 Wash, 10 1ks. wide, 6 ins. deep, drains NW. Small wash, drains N. 35° E. 40.00 Point for the \$\frac{1}{2}\text{ sec. cor. of secs. 9 and 10.} Set an iron post, 30 ins. long, 2\frac{1}{2}\text{ ins. diam., 24 ins. in the ground, with brass cap mkd.} T35N R5W \$\frac{1}{2}\text{ \$\frac{1}{2}\text{ ins. diam., 24 ins. in the ground, with brass cap mkd.}} Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2\frac{1}{2}\text{ ins. diam., 24 ins. in the ground, with brass cap mkd.}} T35N R5W \$\frac{5}{2}\text{ 4 S 3} \text{ s 9 S10}} Deposit glass at base of iron post. Land, rolling. Soil, sandy loam Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interapersed with railed areas Point for the \$\frac{1}{2}\text{ sec. cor. of secs. 3 and 10.} Set an iron post, 30 ins. long, 2\frac{1}{2}\text{ ins. diam., 24 ins. in the ground,}		Over rolling land, through medium timber interspersed with railed areas
Small wash, drains N. 35° E. 40.00 Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. 80.00 Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59¹ W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas. 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	3.50	Unimproved road, bears NE. and SW.
Point for the ½ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 9 \$10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$ 4 \$ 3 \$ 9 \$10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. \$ 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	8.20	Wash, 10 lks. wide, 6 ins. deep, drains NW.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$\frac{1}{2}\$ S 9 \$10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W \$\frac{5}{4} \leq 3 \frac{3}{5} \leq \leq \leq 10} Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. \$\frac{5}{2}\$ 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the \frac{1}{2}\$ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground,	13.60	Small wash, drains N. 35° E.
T35N R5W S 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Foint for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	40.00	Point for the ½ sec. cor. of secs. 9 and 10.
S 9 S10 1959 Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T355N R5W 8 4 S 3 8 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas. 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
Deposit glass at base of iron post. Continue over rolling land. 80.00 Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		T35N R5W
Deposit glass at base of iron post. Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S4 S3 S9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89°59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		<u> </u>
Continue over rolling land. Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59 ' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		1959
Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S4 S3 S9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		Deposit glass at base of iron post.
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T35N R5W S4 S3 S9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		Continue over rolling land.
T35N R5W S 4 S 3 S 9 S10 1959 Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	80.00	Point for the cor. of secs. 3, 4, 9 and 10.
Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		T35N R5W
Deposit glass at base of iron post. Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		<u>S 4 S 3</u> <u>S 9 S 10</u>
Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		1959
Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		Deposit glass at base of iron post.
Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush. From the cor. of secs. 2, 3, 10 and 11. S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		Soil, sandy loam. Timber, juniper and pinon.
S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
S. 89° 59' W., bet. secs. 3 and 10. Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		From the cor. of secs. 2, 3, 10 and 11.
Over rolling land, through medium timber interspersed with railed areas 40.02 Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
Point for the ½ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,		
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,	40.02	
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground,

17

Chains	T35N R5W 1 S 3 2 S10
	Continue over rolling land.
74.80	Unimproved road, bears N. 35° W. and S. 35° E.
76.30	Small wash, drains NW.
80.04	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	North, bet. secs. 3 and 4.
	Over rolling land, through medium timber interspersed with railed areas.
4.40	Wash, 15 lks. wide, 1 ft. deep, drains NW.
8.00	Wash, 20 lks. wide, 3 ft. deep, drains NW.
8.50	Unimproved road, bears N. 25° W. and S. 25° E.
15.40	Unimproved road, bears N. 40° E. and S. 40° W.
33.50	Unimproved road, bears N. 40° W. and S. 40° E.
40.00	Point for the ½ sec. cor. of secs. 3 and 4.
•	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	s 4 s 3 1959
	Deposit broken glass at base of iron post.
	Continue over rolling land.
44.10	Spur, projects NW.
55.40	Unimproved road, bears N. 65° E. and S. 65° W.
61.50	Wash, drains NE. from SW., 4 1ks. wide and 1 ft. deep.
70.00	Fence, bears E. and W.
80.10	The cor. of secs. 3, 4, 33 and 34, Tps. 35 and 36 N., R. 5 W.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.

Chains	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy of the township, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	N. 0° 02' W., bet. secs. 32 and 33.
	Over rolling land, through medium timber interspersed with railed areas.
13.00	Unimproved road, bears NW. and SE.
40.00	Point for the ½ sec. cor. of secs. 32 and 33.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W \$32 S33 1959
	Raise a mound of stone W. of cor.
74.50	Wash, 4 lks. wide, 1½ ft. deep, drains N. 40° W.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	$\begin{array}{c c} \underline{\mathbf{S29}} \underline{\mathbf{S28}} \\ \underline{\mathbf{S32}} \underline{\mathbf{S33}} \end{array}$
	1959
	Deposit charcoal at base of iron post.
	From this point, U.S.G.S. triangulation station "Cedar" bears S. 8° 53' E., 16.21 chs. dist. The geographic position of this station is Latitude 36° 23' 40.235" N., Longitude 112° 50' 28.714" W. Land, rolling. Soil, sandy loam. Timber, pinon and juniper.
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89° 59' W., bet. secs. 28 and 33.
11.70	Over rolling land, through medium timber interspersed with railed areas. Fence, bears NW. and SW.
28.00	
40.08	
,,,,,,,	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground,
۰	with brass cap mkd: T35N R5W
	1 S28 4 S33 1959
	Raise a collar of stone around iron post.
	Continue over rolling land.
76.60	Low spur, slopes N. 15° E.
!	1

Portion of	the S	Subdivision,	T.	35 N.,	R.	5 W	

T T	
Chains	
80.16	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling.
	Soil, sandy loam. Timber, juniper and pinon.
	Undergrowth, sage, Mormon tea, buck brush and oak brush.
	N. 0° 02' W., bet. secs. 28 and 29.
	Over rolling land, through medium timber interspersed with railed areas; desc. gentle N. slope.
31.10	Fence, bears N. 65° W. and S. 60° E.
40.00	Point for the ½ sec. cor. of secs. 28 and 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground,
- '	and in a mound of stone to top, with brass cap mkd.
	T35N R5W
	\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	1959
50.60	Wash, 10 1ks. wide, 2 ft. deep, drains N. 40° E.
76.00	Wash, drains S. 75° E.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	<u>\$20 \$21 </u>
	\$29 \$28 1959
	Deposit glass at base of iron post.
	Land, rolling.
	Soil, sandy loam. Timber, pinon and juniper.
	Undergrowth, sage, Mormon tea, buck brush and oak brush.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89° 53' W., bet. secs. 21 and 28.
	Over rolling land, through medium timber interspersed with railed areas.
24.00	Wash, 30 1ks. wide, 1 ft. deep, drains N. 15° E.
40.12	Point for the ½ sec. cor. of secs. 21 and 28.
-	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	LS21
	⁴ S28 1959
	Continue over rolling land.
67.00	Wash, drains NE.
<u>-</u>	

Portion .	of	the	Subdivision,	т.	35	Ν.,	R.	5	W.	

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
80.24	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
-	N. 0° 02' W., bet. secs. 20 and 21.
	Over rolling land, through medium timber interspersed with railed areas.
18.00	Top of low ridge, bears N. 85° E. and S. 85° W.
40.00	Point for the 2 sec. cor. of secs. 20 and 21.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N_R5W
	\$20 \$21 1959
	Raise a collar of stone around cor.
	Continue over rolling land.
48.80	Bottom of swale, drains N. 80° E.
55°.50°.	Low spur, slopes E.; continue over numerous spurs and washes putting N.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a small mound of stone to top, with brass cap mkd.
	T35N R5W S17 S16 S20 S21 1959
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89° 52' W., bet. secs. 16 and 21.
	Over rolling land, through medium timber interspersed with railed areas.
8.80	Wash, drains NE.
11.10	Unimproved road, bears N. and S.
40.14	Point for the 2 sec. cor. of secs. 16 and 21.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground and in a mound of stone to top, with brass cap mkd.
	•

Chains	
Chams	T35N. R5W
	$\frac{1}{2} \frac{S16}{S21}$
	* S21 1959
	1939
-	Continue over rolling land.
64.70	Unimproved road, bears N. 60° W. and S 60° E. for about 3 chs., thence S. 40° E.
80.28	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	N. 0° 02' W., bet. secs. 16 and 17.
	Over rolling land, through medium growth of timber interspersed with railed areas.
3.30	Unimproved road, bears N. 60° W. and S. 60° E.
40.00	Point for the 1 sec. cor. of secs. 16 and 17.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	\$17\\$16 1959
	Raise a mound of stone W. of iron post.
	Continue over rolling land.
41.25	Unimproved road leading to dry tank, $9\frac{1}{2}$ chs. dist., bears N. 10° E. and S. 10° W.
42.30	Wash, 5 lks. wide, 1 ft. deep, drains N. 10° E.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam.,24 ins. in the ground, with brass cap mkd.
	T35N R5W
	<u>S 8 S 9</u> S17 S16
	1959
	Raise a mound of stone W. of iron post.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89° 51' W., bet. secs. 9 and 16.
	Over rolling land, through medium timber interspersed with railed areas.
	areas, remain memory medical medical and supplied by the control of the supplied areas.

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
4.50	Wash, drains N. from Gid Findlay Tank
5.00	Unimproved road, bears NE. and SW.
40.15	Point for the ½ sec. cor. of secs. 9 and 16.
v	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T35N R5W $\frac{S}{4} = \frac{S}{S16}$ Continue over rolling land.
73.00	Wash, drains N. from S.
80.30	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	N. 0° 02' W., bet. secs. 8 and 9.
	Over rolling land, through medium timber interspersed with railed areas.
40.00	Point for the ½ sec. cor. of secs. 8 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	s 8 s 9 1959
	Deposit charcoal at base of iron post.
	Continue over rolling land.
66.20	Fence, bears N. 20° E, and S. 20° W.
80.00	Point for the cor. of secs.4, 5, 8 and 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	<u>S 5 S 4</u> S 8 S 9
	1959
	Deposit charcoal at base of iron post.
·	Land, rolling. Soil, sandy loam. Timber, juniper and pinon. Undergrowth, sage, Mormon tea, buck brush and oak brush.
	From the cor of secs 3 / 9 and 10
	From the cor. of secs. 3, 4, 9 and 10. N. 89° 55' W., bet. secs. 4 and 9.
	Over gently rolling land, through medium timber interspersed with railed areas.

	Portion of the Subdivision, T.35 N., R. 5 W.
Chains	
40.12	Point for the ½ sec. cor. of secs. 4 and 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	$\frac{1}{4} \frac{\frac{S}{S} \frac{4}{9}}{1959}$
	Deposit charcoal at base of iron post.
	Continue over rolling land.
49.00	Wash, drains NE. from SW.
75.70	Fence, bears N. and S.
80.24	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling.
	Soil, sandy loam. Timber, juniper and pinon.
	Undergrowth, sage, Mormon tea, buck brush and oak brush.
	N. 0° 02' E., bet. secs. 4 and 5.
	Over gently rolling land, through medium growth of timber interspersed with railed areas.
20.10	Unimproved road, bears N. 80° W. and S. 80° E.
40.00	Point for the ½ sec. cor. of secs. 4 and 5.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W
-	S 5 S 4
	1959
	Continue over gently rolling land.
80.26	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, gently rolling. Soil, sandy loam.
	Timber, juniper and pinon.
	Undergrowth, sage and Mormon tea.
	Beginning at the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township.
	N. 0° 03' W., bet. secs. 31 and 32.
	Over rolling land, through medium growth of timber.
2.70	Wash, 1 ch. wide, 50 ft. deep, drains S. 30° W.; asc. 60 ft. over S. slope.
19.50	Spur, slopes N. 60° W.; desc. 60 ft. over N. slope.

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
34.00	Unimproved road, bears NW. and SE.
40.00	Point for the ½ sec. cor. of secs. 31 and 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W
	\$31 \$32 1959
	Asc. 50 ft. over SW. slope.
66.10	Top of ascent, slopes NW.; desc. 40 ft. over N. slope.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.
	T35N R5W S30 S29 S31 S32 1959
	Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, sage, buck brush and oak brush.
	From the cor. of secs. 28, 29, 32 and 33. West, bet. secs. 29 and 32.
7.00 33.50	Over rolling land, through medium timber; asc. 50 ft. over land draining S. Wash, drains NW. Spur, projects S.; desc. 40 ft. over gently rolling W. slope.
40.16	Point for the ½ sec. cor. of secs. 29 and 32.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a small mound of stone to top, with brass cap mkd.
	T35N R5W 2 S29 S32 1959
	Desc. 40 ft. over W. slope.
80.32	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon.
	N. 89° 49' W., bet. secs. 30 and 31.
	Over rolling land, through medium timber; desc. 30 ft. over W. slope.
6.00	Wash, 8 lks. wide, 1½ ft. deep, drains S. 75° W.; desc. 20 ft. over W. slope.

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
10.40	Unimproved road, bears N. and S
11.30	Wash, 10 1ks. wide, 2 ft. deep, drains N.; asc. 80 ft. over E. slope.
18.30	Top of ascent; spur projects N. 10° E.; desc. over series of small washes and minor spurs putting N.
40.00	Point for the ½ sec. cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W 2 S30 S31 1959
	Continue along series of small washes and minor drains putting N.
78.80	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, shallow sandy loam. Timber, pinon and juniper. Undergrowth, sage, buck brush and oak brush.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0° 03' W., bet. secs. 29 and 30.
	Over rolling land, draining W., through medium timber.
3.00	Wash, 10 1ks. wide, 1 ft. deep, drains SW.; asc. 20 ft. over W. slope.
21.00	Unimproved road, bears NE.
25.00	Unimproved road, bears NE.
40.00	Point for the ½ sec. cor. of secs. 29 and 30.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W
	S30 S29
	1959
	Continue over rolling land draining W.
71.40	Unimproved road, bears N. 70° W. and S. 70° E.
71.90	Fence, bears N. 70° W. for about 2 chs., thence N. 20° E. and S. 70°E.
77.10	Recross fence, bears N. 20° E. and S. 20° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins.diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W S19 S20 S30 S29
	1959

Portion	οf	the	Subdivi	sion,	Τ.	35	Ν.,	R.	5	W.

		rottion of the Subdivision, 1. 35 N., R. 5 W.
	Chains	
		Land, rolling. Soil, sandy loam.
		Timber, juniper and pinon.
		Undergrowth, sage, buck brush and oak brush.
		From the cor. of secs. 20, 21, 28 and 29.
		N. 89° 53' W., bet. secs. 20 and 29.
		Over rolling land, through medium timber.
	6.60	Wash, 15 1ks. wide, 2 ft. deep, drains S. 75° E.; asc. gentle E. slope
	40.10	Point for the ½ sec. cor. of secs. 20 and 29.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
		T35N R5W
	٠.	$\frac{1}{4} \frac{S20}{S29}$
		1959
		Continue to ascend gentle E. slope.
	43.60	Ridge, bears NE. and SW.; desc. W. slope.
	73.50	Unimproved road, bears N. and S.
	78.50	Fence, bears N. 35° E. and S. 35° W.
	80.20	The cor. of secs. 19, 20, 29 and 30.
P		Land, rolling. Soil, sandy loam. Timber, pinon and juniper. Undergrowth, sage, buck brush and oak brush.
		West, bet. secs. 19 and 30.
		Over gently rolling railed land.
	4.00	Begin descent of NW. slope; desc. 40 ft.
	13.10	Draw, drains S. 10° W.; asc. 30 ft. over rolling E. slope.
	20.70	Unimproved road, bears N. 35° W. and S. 35° E.
	26.40	Ridge, bears N. and S; desc. 40 ft. over W. slope.
	35.50	Draw, drains S. 15° E.; asc. E. slope.
	38.00	Unimproved road, bears NW. and SE
	40.00	Point for the 1/2 sec. cor. of secs. 19 and 30.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T35N R5W 1/4 S19 1/8 S30 1959
		Deposit charcoal at base of iron post.

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
	Continue ascent of 70 ft. over E. slope.
58.00	Spur, slopes S.; desc. 40 ft. over W. slope.
66.90	Small wash, drains S.; asc. 20 ft. over E. slope.
78.63	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, none.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0° 03' W.,bet. secs. 19 and 20.
	Over rolling land, through railed area.
40.00	Point for the ½ sec. cor. of secs. 19 and 20.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T35N_R5W
	\$19 \$20 1959
	Deposit glass at base of iron post.
,	Continue over rolling land.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
·	T35N R5W S18 S17 S19 S20 1959
	Deposit charcoal at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, a few juniper and pinon.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89° 59' W., bet. secs. 17 and 20.
	Over rolling land, through scattered timber.
27.00	Low spur, slopes N. 10° W.; desc. 40 ft. over N. slope.
32.50	Unimproved road, bears NE. and SW.
34.70	Center of draw, drains NE.; asc. 20 ft. over E. slope.
40.08	
70.00	Point for the ½ sec. cor. of secs. 17 and 20.

	Portion of the Subdivision, T. 35 N., R. 5 W.
Chains	
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins.in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W
	$\frac{1}{4} \frac{S17}{S20}$
	1959
40.20	Spur, slopes N.; asc. 90 ft. over rolling land draining N.
50.85	Fence, bears N. and S.
69.60	Ridge, bears N. 30° E. and S. 30° W.; desc. 60 ft. over SW. slope.
80.16	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, sandy loam. Timber, scattered juniper and pinon.
	N. 89° 43' W., bet. secs. 18 and 19.
	Over rolling land, through scattered timber.
3.00	Unimproved road, bears NE. and SW.
5.10	Draw, drains N.; asc. 90 ft. over SE. slope.
20.10	Spur, slopes S. 40° W.; asc. 20 ft. along S. slope.
40.00	Point for the ½ sec. cor. of secs. 18 and 19.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T35N R5W 表 S18 S19 1959
	Continue over nearly level land.
78.47	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Timber, scattered juniper and pinon. Soil, sandy loam.
·	From the cor. of secs. 17, 18, 19 and 20.
	N. 0° 03' W., bet. secs. 17 and 18.
	Over rolling land, through medium timber.
5.50	Unimproved road, bears NE. and SW.
20.90	Leave level land; asc. 60 ft. over SW. slope.
26.00	Spur, slopes N. 80° W.; desc. 70 ft. over NE. slope.
31.30	Road bears NE and SW; enter gently rolling land.

Chains	Portion of the Subdivision, T. 35 N., R. 5 W.
40.00	Point for the & sec. cor. of secs. 17 and 18.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
	T35N R5W
	\$18 \$17 1959
	Deposit charcoal at base of iron post.
	Continue over gently rolling land.
42.10	Low spur, slopes N. 80° E.
65.20	Low ridge, bears N. 80° E. and S. 80° W.; desc. 70 ft. over NE. slope
75.20	Wash, 6 1ks. wide, 1 ft. deep, drains N. 80° E.
78.30	Low spur, slopes E.; desc. gentle NE. slope.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set an iron post, 30 ins. long, 2½ ins.diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	$ \frac{s}{s18} \frac{7 s}{s17} $ 1959
	Deposit glass at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, scattered juniper and pinon.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89° 51' W., bet. secs. 8 and 17.
	Over gently rolling land, through scattered timber.
23.20	Fence, bears N. 20°E. and S. 20°W.
40.11	Point for the ½ sec. cor. of secs. 8 and 17.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T35N R5W 1/4 S 8 S 17 1959
	Continue over gently rolling land.
43.60	Rim, 10 ft. high, bears N. 10° W. and S. 10° E.; desc. 90 ft. over W slope.
52.20	Unimproved road, bears N. 5° W. and S. 5° E.; continue over nearly level land.
56.50	Wash, drains NW. from SE.
·	level land.

		Portion of the Subdivision, T. 35 N., R. 5 W.		
1				
	Chains 80.22	The cor. of secs. 7, 8, 17 and 18.		
		Land, rolling. Soil, sandy loam. Timber, scattered juniper and pinon.		
		N. 89° 49' W., bet. secs. 7 and 18.		
	•	Over rolling land, through scattered timber; asc. 80 ft. over E. slope.		
	16.40	Ridge, bears N. 5° E. and S. 5° W.; continue over nearly level top of ridge.		
	31.30	Desc. 70 ft. over W. slope.		
	40.00	Point for the ½ sec. cor. of secs. 7 and 18.		
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, and in a mound of stone to top, with brass cap mkd.			
		T35N R5W ½ S 7 S18		
		1959		
		Desc. 50 ft. over W. slope.		
	50.80	Draw, drains N. 10° E.; asc. 80 ft. over E. slope.		
	62 .6 0	Spur, slopes N. 20° E.; desc. 90 ft. over W. slope.		
78.30 The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the towns monumented by an iron post, 2 ins. diam., set, mkd. and witnes described in the official record.				
		Land, rolling. Soil, sandy loam. Timber, scattered juniper and pinon.		
		From the cor. of secs. 7, 8, 17 and 18.		
		N. 0° 03' W., bet. secs. 7 and 8.		
		Over rolling land draining NE., through scattered timber.		
	40.00	Point for the ½ sec. cor. of secs. 7 and 8.		
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins.diam., 24 ins. in the ground, with brass cap mkd.		
		T35N R5W		
		S 7 S 8 1959		
		Deposit glass at base of iron post.		
	. •	Continue over nearly level land.		
	58.70	Wash, bears NW. and SE.		
	63.20	Road, bears N. 60° W. and S. 60° E.		
	66.90	Unimproved road, bears N. 10° W. and S. 10° E.		

Portion	of	the	Subdivision,	Τ.	35	Ν.,	R.	5	W.

	Torcion of the subdivision, 1. 33 N., R. 3 W.
Chains	
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T35N R5W
	S 6 S 5 S 7 S 8
	1959
	Deposit glass at base of iron post.
	Land, rolling. Soil, sandy loam. Timber, scattered juniper and pinon.
	Timber, scattered juniper and pinon.
· ·	From the cor. of secs. 4, 5, 8 and 9.
	N. 89° 56' W., bet. secs. 5 and 8.
	Asc. 40 ft. over gently rolling E. slope.
40.15	Point for the ½ sec. cor. of secs. 5 and 8.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R5W
	½ S 5 S 8
	S 8 1959
	Deposit charcoal at base of iron post.
52.70	Wash, 5 lks. wide, 1 ft. deep, drains N. 10° E.
59.20	Low spur, slopes N.; desc. 30 ft. over gently rolling W. slope.
80.30	The cor. of secs. 5, 6, 7 and 8.
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon.
*	N. 89° 48' W., bet. secs. 6 and 7.
	Over rolling land, through scattered timber.
3.30	Unimproved road, bears N. 5° E. and S. 5° W.
8.50	Wash, drains NE. from SW.
10.00	Unimproved road, bears N. and S.
12.30	Unimproved road, bears N. 30° W. and S. 30° E.
40.00	Point for the 2 sec. cor. of secs. 6 and 7.
1	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	with brass cap mkd.

	Portion of the Subdivision, 1. 33 N., K. 3 W.				
Chains	Continue over gently rolling land.				
78.09					
	Land, rolling. Soil, sandy loam. Timber, juniper and pinon.				
	From the cor. of secs. 5, 6, 7 and 8.				
	N. 0° 03' E., bet. secs. 5 and 6.				
	Over gently rolling land draining SW., through scattered timber.				
3.40	Low ridge, bears NE. and SW.; desc. 30 ft. over gently rolling N. slope.				
24.50	Roade, bears NE. and SW.				
27.40	Draw, drains N. 30° E.; asc. 20 ft. over gentle SE. slope.				
31.60	Wash, 10 1ks. wide, 3 ft. deep, drains N. 25° E.				
40.00	Point for the 2 sec. cor. of secs. 5 and 6.				
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.				
	T35N R5W				
	s 6 s 5 1959				
	Deposit glass at base of iron post.				
	Continue over gently rolling land.				
80.35	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.				
	•				
GENERAL DESCRIPTION					
	The land in T. 35 N., R.5 W. is high table land of the Kanab Plateau. The altitude varies from 5500 ft. in the north to 5800 ft. in the south.				
	There are a number of roads running through the township, used principally by stockmen. The land is used mainly for stock grazing, although the south two miles of the township are included in the Grand Canyon National Monument.				
	The only water in the township is collected in tanks from runoff.				
	There are no settlements in the township.				
1					

4-680 (Feb., 1950)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Neil R. Forsyth	Chainman
Richard R. Brand	Chainman
William R. Savage	Axeman
Dee Von Thompson	Cornerman
Virgil D. Albrecht	Flagman
••••••	
	·
	·

16-53565-2

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald A. Cannon	, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing da	te of the 9th day of October ,1958,
	bdivision of Township 35 North, Range 5 West
of the Gila & Salt RiverMeridian, in the	State of, which are
represented in the foregoing field notes as h	aving been executed by me and under my direction; and that
said survey has been made in strict conform	nity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United S	tates, and in the specific manner described in the foregoing
field notes.	
July 9, 1959	Donald a. Camer
Salt Lake City, Utah	Donald A. Cannon, Cadastral Surveyor
CERTIF	ICATE OF APPROVAL
	BUREAU OF LAND MANAGEMENT,
	Washington, D. C., FER 3 1960, 19
The foregoing field notes of the survey of	f a portion of the subdivision of Township 35
North, Range 5 West, Gila and Salt	River Meridian, Arizona
·	
executed by Donald A. Cannon, Cada	stral Surveyor
having been critically examined and found	
having been efficiently enamined and resident	De la como
	Cadastral Engineering Staff Officer.
CERTIFI	CATE OF TRANSCRIPT
- LCERTIFY that the foregoing transcrip	t of the field notes of the above-described surveys in
	py of the original field notes.
	Cadastral Engineering Staff Officer