

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

NORTH FIVE AND ONE-HALF MILES OF THE WEST BOUNDARY

AND A PORTION OF THE SUBDIVISION

AND THE SURVEY

COMPLETING THE SUBDIVISION

OF

TOWNSHIP 6 SOUTH, RANGE 28 EAST

Of the *Gila And Salt River* ~~Salt Lake~~ Meridian,

In the State of *Arizona* ~~Utah~~

EXECUTED BY

Phil D. Smith, Cadastral Surveyor

Under special instructions dated November 16, 1954, which provided
and supplemental special instructions dated January 13, 1956 November 16, 1954
for the surveys included under Group No. 299, approved January 13, 1956

and assignment instructions dated January 13, 1960

Survey commenced December 11, 1957

Survey completed February 9, 1960

BOOK 4616

BOOK 4616

INDEX DIAGRAM

Township 6 South, Range 28 East

6	6	5	4	33 3	23 2	14 1
43			32	31	22	13
5	7	42 8	9	31 10	21 11	12 12
41	40			30	21	11
4	18	38 17	16	15	20 14	10 13
38	37			30	19	10
3	19	36 20	21	29 22	18 23	9 24
35			28	27	17	8
2	30	29	28	26 27	16 26	7 25
34			26	25	16	
1	31	32	33	24 34	15 35	36

Township 6 South, Range 28 East

Chains

The north boundary of T. 6 S., R. 28 E. (the First Standard Parallel South) and the south, east and west boundaries were originally surveyed by Philip Contzen in 1895. The south boundary and south one-half mile of the west boundary were resurveyed by C. E. Hunter in 1931. Sections 7 and 31 were surveyed by Philip Contzen in 1895; section 5 was surveyed by T. Y. White in 1947; sections 16, 29, 32 and 36, and the fourth meridional line were surveyed, and the east boundary was resurveyed by Horace G. Parker in 1955. The west five miles of the north boundary were resurveyed concurrently by Phil D. Smith and the east one mile was resurveyed by Vern E. Lane in 1960.

The following field notes are those of the dependent resurvey of the north five and one-half miles of the west boundary and sections 7 and 31, and the survey of the remaining subdivisional lines of T. 6 S., R. 28 E., which were requested by the State Supervisor of Arizona.

This survey was executed with a W. & L. E. Gurley solar transit, serial No. 491037, and a Buff and Buff light mountain solar transit, serial No. 23831. Both transits were constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition prior to the beginning of the survey and were maintained in proper adjustment throughout the progress of the survey.

The direction of the lines of the survey were determined by sustained angulation carried forward from an altitude observation on the sun for azimuth, and supplemented by numerous solar observations taken throughout the survey.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by the random and true method, but for simplification of the record the random lines are omitted from these notes.

Measurements were made with a Chicago steel tape, 8 chains in length, graduated every 1/10 link for the first link, every link for the next 99 links, and thereafter at intervals of 10 links. The tape was tested by comparison with a one-chain standard tape and found to be correct. Measurements were made on the slope, the vertical angle of each interval ascertained by two clinometers in good adjustment, and the horizontal equivalents only are entered in this field note record. All lines of this survey were run by direct methods where the lines were accessible; lines inaccessible to chaining were run by triangulation or traverse. The details of such triangulations and traverses have been thoroughly verified, and only the true line distances returned in the notes.

The geographic position of the southeast corner of the township is in latitude $32^{\circ} 51' 34.316''$ N. and longitude $109^{\circ} 25' 28.776''$ W., as determined from a tie to U.S.G.S. triangulation station "Bonit" located in section 7.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be $12^{\circ} 30'$ East.

 Dependent Resurvey of the West Boundary of T. 6 S., R. 28 E.

Reestablishment of the survey executed by Philip Contzen in 1895.

Beginning at the $\frac{1}{2}$ sec. cor. of secs. 31 and 36. Tps. 6 S., Rs. 27 and 28 E., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. of T. 6 S., R. 28 E.

Dependent Resurvey, W. Bdy., T. 6 S., R. 28 E.

Chains

N. 0° 12' W., bet. secs. 31 and 36.

Over rocky and rolling bench land.

Desc. 10 ft. over general N. slope.

36.40 Rut road, bears N. 70° E. and S. 70° W.

40.03 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

T6S

R27E R28E

S25 S30

S36 S31

1958.

Land, rocky, rolling benchland.

Soil, sandy clay.

Timber, none.

Undergrowth, moderate growth of native grasses, scattered cacti, and greasewood.

N. 0° 12' W., bet. secs. 25 and 30.

Over rocky, rolling hills.

Asc. 200 ft. over general S. slope to the ¼ sec. cor.

21.00 Four strand barb wire fence, bears N. 20° W. and S. 20° E.

39.82 Four strand barb wire fence, bears N. 20° W. and S. 20° E.

40.03 The original ¼ sec. cor. of secs. 25 and 30, mkd. by a lava stone, set, mkd. and witnessed as described in the official record.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 3½ ft. base, to cap, with brass cap mkd.

T6S

R27E R28E

S25 S30

1958.

Deposit original stone monument alongside the iron post.

N. 0° 10' W., beginning new measurement.

Asc. 45 ft. over general S. slope of rolling hills.

4.75 Four strand barb wire fence, bears N. 60° E. and S. 60° W.

7.25 Rut road, bears N. 60° E. and S. 60° W.

9.75 Top of ascent on spur of hill, from NE.; desc. 140 ft. over NW. slope.

Dependent Resurvey, W. Bdy., T. 6 S., R. 28 E.

Chains

- 24.60 Draw, drains SW.; asc. 25 ft. over SE. slope.
- 28.00 Spur, sloping SW.; desc. 20 ft. over NW. slope.
- 35.75 Wash, 30 lks. wide, 1 ft. deep, drains SW.; asc. 20 ft. over SE. slope.
- 40.38 The original cor. of secs. 19, 24, 25 and 30, mkd. by a Malpais stone, set, mkd. and witnessed as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S
R27E R28E
S24 | S19
S25 | S30
1958

Deposit original monument alongside iron post.

Land, rolling hills.

Soil, rocky, sandy clay.

Timber, none.

Undergrowth, scattered growth of greasewood, catclaw, cacti and native grasses.

N. 0° 11' W., bet. secs. 19 and 24.

Over rocky rolling hills.

Asc. 150 ft. over general SE. slope.

- 17.55 Rut road, bears N. 70° W. and N. 40° E.

- 31.90 Crest of spur, projecting SW.; desc. 20 ft. over rocky NW. slope.

- 39.55 The original ¼ sec. cor. of secs. 19 and 24, mkd. by a lava stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S
R27E R28E
¼
S24 | S19
1958

Deposit original monument alongside iron post.

N. 0° 12' W., beginning new measurement.

Desc. 10 ft. over NW. slope.

Dependent Resurvey, W. Bdy., T. 6 S., R. 28 E.

Chains

3.60 Wash, 70 lks. wide, 2 ft. deep, drains SW.; asc. 40 ft. over general S. slope.

16.00 Low spur, sloping E.; desc. 10 ft. over N. slope.

24.10 Recross wash, drains SE.; asc. 130 ft. over SW. slope.

39.98 The original cor. of secs. 13, 18, 19 and 24, mkd. by a malpais stone set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S
R27E R28E
S13|S18
S24|S19
1958

Deposit original monument alongside iron post.

Land, rolling hills.

Soil, rocky, sandy loam to sandy clay.

Timber, none.

Undergrowth, moderate to scattered greasewood, catclaw and native grasses.

N. 0° 07' W., bet. secs. 13 and 18.

Over rocky, rolling hills.

Asc. 125 ft. over SW. slope.

16.54 Crest of ridge, bears N. 40° W. and S. 40° E., and four-strand barb wire fence, bears N. 40° W. and S. 40° E. for 2 chs., thence S. 15° E.; desc. 255 ft. over NE. slope.

33.45 Wash, 60 lks. wide, 3 ft. deep, drains SE.; asc. 135 ft. over SW. slope.

39.64 The original ¼ sec. cor. of secs. 13 and 18, mkd. by a lava stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, with 3 ft. base, to top of post, with brass cap mkd.

T6S
R27E R28E
S13|S18
1958

Deposit original monument alongside iron post.

BOOK 4010

Dependent Resurvey, W. Bdy., T. 6 S., R. 28 E.

Chains

N. 0° 10' W., beginning new measurement.

Asc. 175 ft. over rocky SW. slope.

31.50 Crest of ridge, bears N. 45° W. and S. 45° E.; desc. 15 ft. over NE. slope.

36.10 Four strand barb wire fence, bears E. and W.

40.15 The original cor. of secs. 7, 12, 13 and 18, mkd. by a lava rock, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base, to top of post, with brass cap mkd.

T6S
R27E R28E

S12 | S 7

S13 | S18

1958

Deposit original monument alongside iron post.

Land, rolling hills.

Soil, rocky, sandy clay.

Timber, none.

Undergrowth, scattered greasewood, cacti and native grasses.

N. 0° 12' W., bet. secs. 7 and 12.

Over rocky rolling hills.

Desc. 95 ft. over NE. slope.

23.85 Wash, 30 lks. wide, 1 ft. deep, drains SE.; asc. 115 ft. over general SW. slope.

40.15 The original ¼ sec. cor. of secs. 7 and 12, mkd. by a malpais stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S
R27E R28E¼
S12 | S 7

1958

Deposit original monument alongside iron post.

Dependent Resurvey, W. Bdy., T. 6 S., R. 28 E.

Chains	
	N. 0° 11' W., beginning new measurement.
.10	Crest of spur, sloping SE.; desc. 65 ft. over rolling and broken NE. slope.
19.50	Wash, 30 lks. wide, 1 ft. deep, drains SE.; asc. 60 ft. over SW. slope.
26.60	Rut road, bears N. 75° W. and S. 50° E.
29.60	Crest of spur, bears NW. and SE.; desc. 115 ft. over NE. slope.
38.10	Wash, 40 lks. wide, 1 ft. deep, drains SE.; asc. 130 ft. over broken SW. slope.
40.04	The original cor. of secs. 1, 6, 7 and 12, mkd. by malpais stone, set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	T6S R27E R28E S 1 S 6 S12 S 7 1958
	Deposit original monument alongside iron post.
	From this cor. U.S.G.S. triangulation station "Bonit" bears S. 17° 15' E., 15.71 chs. dist. Its geographic position is latitude 32° 55' 45.995" N., longitude 109° 31' 35.092" W.
	Land, rolling to broken hills. Soil, rocky, sandy clay to sand. Timber, none. Undergrowth, moderate growth of greasewood, cacti and native grasses.
	N. 0° 06' W., bet. secs. 1 and 6.
	Over rocky, broken to rolling hills.
	Asc. 90 ft. over broken SW. slope.
8.20	Crest of spur, projecting SE.; desc. 85 ft. over NW. slope.
12.00	Slope changes to N.
17.05	Draw, drains E.; asc. 160 ft. over rocky S. slope.
26.25	Crest of spur, projects E.; desc. 100 ft. over broken general NE. slope.
31.54	Wash, 40 lks. wide, 2 ft. deep, drains SE.; asc. 155 ft. over SW. slope.
40.04	The original ¼ sec. cor. of secs. 1 and 6 mkd. by lava stone, set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

DOPN 4010

Dependent Resurvey, W. Bdy., T. 6 S., R. 28 E.

Chains

T6S
R27E R28E

S 1 | S 6

1958

Deposit original monument alongside iron post.

N. 0° 09' W., beginning new measurement.

Asc. 200 ft. over SW. slope.

5.60 Great of spur, projects SE.; desc. 70 ft. over general NE. slope.

25.65 Wash, 30 lks. wide, 2 ft. deep, drains SE.; asc. 110 ft. over SW. slope.

39.29 Intersect the First Standard Parallel South at the closing cor. of secs. 1 and 6, Tps. 6 S., Rs. 27 and 28 E., mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

Land, broken and rolling hills.

Soil, rocky and sandy clay.

Timber, none?

Undergrowth, scattered greasewood, cacti and native grasses.

From the above cor. the standard ¼ sec. cor. of sec. 36, T. 5 S., R. 27 E., bears West 89° 55' E., 0.20 lks. dist., mkd. by a malpais stone, set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

S C
T5S R27E

¼ S36

1958

Deposit the original cor. alongside iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of iron post.

From the same closing cor. the ¼ sec. cor. of sec. 6, T. 6 S., R. 28 E. bears N. 89° 55' E., 37.52 chs. dist., mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

Survey of the Subdivision of T. 6 S., R. 28 E.

From the cor. of secs. 25, 26, 35 and 36, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

Survey, Subdivision, T. 6 S., R. 28 E.

Chains	
	N. 0° 01' W., bet. secs. 25 and 26.
	Over rolling mountainous land.
	Asc. 110 ft. over rocky, general SW. slope.
15.20	Top of ascent, spur, sloping N. 30° W.; desc. 140 ft. over rocky NE. slope.
27.30	Wash, 10 lks. wide, 3 ft. deep, drains N. 35° W.; asc. 85 ft. over rocky SW. slope.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 25 and 26.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, $\frac{1}{4}$ ft. base, to top of post, with brass cap mkd.
	T6S R28E
	$\frac{1}{2}$
	S26 S25
	1957
	Cont. to asc. 30 ft. over SW. slope.
43.20	Spur, sloping N. 25° W.; desc. 260 ft. over rocky NE. slope.
58.95	Wash, 70 lks. wide, 3 ft. deep, drains N. 20° W.; asc. 90 ft. over S. slope.
65.00	Top of small rise; desc. 90 ft. over N. slope.
70.60	Draw, drains S. 40° W.; asc. 95 ft. over rolling rocky S. slope.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	T6S R28E
	S23 S24
	S26 S25
	1957
	Land, rolling, mountainous.
	Soil, rocky clay.
	Timber, none.
	Undergrowth, scattered greasewood, catclaw, locust brush, cacti and moderate native grasses.
	From the cor. of secs. 24 and 25 on the E. bdy. of the Tp., monumented by an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	S. 89° 50' W., bet. secs. 24 and 25.
	Over mountainous land.
	By triangulation, desc. 300 ft. over rocky rolling SW. slope.
25.25	Wash, 40 lks. wide, 3 ft. deep, drains S. 35° W.; asc. 375 ft. over rocky SE. slope.
40.12	Point for the $\frac{1}{2}$ sec. cor. of secs. 24 and 25.

BOOK 1010

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E ¼ S24 S25 1957</p> <p>Cor. is located on ridge, bears N. 40° E. and S. 40° W.</p> <p>Thence by chaining; desc. 355 ft. over rocky NW. slope.</p>
55.80	Rut road, bears N. 30° W. and S. 30° E.
72.35	Draw, drains S. 55° W.; asc. 120 ft. over rocky SE. slope.
75.80	Slope changes to S.
80.24	The cor. of secs. 23, 24, 25 and 26.
	<p>Land, mountainous.</p> <p>Soil, rocky clay.</p> <p>Timber, none.</p> <p>Undergrowth, scattered greasewood, catclaw, cacti and moderate native grasses.</p>
	<p>N. 0° 01' W., bet. secs. 23 and 24.</p> <p>Over mountainous land.</p> <p>Asc. 115 ft. over rocky S. slope.</p>
15.60	Slope changes to SE.; cont. to asc. 25 ft.
30.70	Rut road, bears N. 60° W. and S. 30° E.; asc. 25 ft.
31.60	High point of ascent; desc. 100 ft. along rocky E. slope.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E ¼ S23 S24 1958</p> <p>Cor. is located on low point of descent on E. slope.</p> <p>Asc. 20 ft. over rocky SE. slope.</p>
41.90	Spur, sloping N. 30° E.; desc. 105 ft. over broken NW. slope.
47.65	Wash, 40 lks. wide, 1 ft. deep, drains N. 15° W.; asc. 225 ft. over broken general S. slope.
52.00	Slope changes to SW.
64.65	Spur, sloping N. 30° W.; desc. 230 ft. over rocky broken NE. slope.
75.45	Draw, draining W.; asc. 145 ft. over broken S. slope.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

80.00 Point for the cor. of secs. 13, 14, 23 and 24.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E

S14 | S13

S23 | S24

1958

Land, broken, mountainous.
Soil, rocky.
Timber, none.
Undergrowth, scattered greasewood, catclaw, cacti and moderate native grasses.

From the true point for the cor. of secs. 13 and 24 on the E. bdy. of T. 6 S., R. 28 E., which is witnessed S. 3.21 chs. dist. by an iron post, $2\frac{1}{2}$ ins. diam., as described in the official record.

S. $89^{\circ}46'$ W., bet. secs. 13 and 24.

Over rough mountainous land.

By triangulation

4.60 Spur, sloping N. 35° W.; desc. abruptly 355 ft. over broken SW. slope.

32.30 Wash, 50 lks. wide, 3 ft. deep, drains N. 30° W.; asc. 260 ft. over rocky NE. slope.

40.14 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E

 $\frac{1}{4}$ S13

S24

1958

Thence by chaining.

Cont. to asc. 160 ft. over NE. slope.

62.70 High Point of ascent on slope; thence desc. 120 ft. along S. slope.

80.28 The cor. of secs. 13, 14, 23 and 24.

Land, mountainous.

Soil, rocky.

Timber, none.

Undergrowth, scattered greasewood, catclaw, cacti and native grasses.

N. $0^{\circ}01'$ W., bet. secs. 13 and 14.

Over mountainous land.

BOOK 4019

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
Asc. 55 ft. over rocky S. slope.	
3.50	Ridge, bears S. 25° E. and W.; desc. 165 ft. over a series of rolling hills, general NE. slope.
32.50	Canyon rim, bears N. 30° W. and S. 30° E.; desc. 60 ft. over sharp, rocky NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E S14 S13 1958
	Thence by triangulation; desc. 410 ft. over rocky NE. slope.
55.00	Canyon bottom, draining N. 30° W.; asc. 430 ft. over broken rocky SW. slope.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E S11 S12 S14 S13 1958
	Land, mountainous. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, catclaw, cacti and native grasses.
	From the cor. of secs. 12 and 13 on the E. bdy. of T. 6 S., R. 28 E., monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the official record. S. 89° 58' W., bet. secs. 12 and 13. Over broken mountainous land. By triangulation, desc. 410 ft. over sharp rocky SW. slope.
15.30	Wash, 35 lks. wide, 4 ft. deep, drains N. 25° W.; asc. 385 ft. over abrupt NE. slope.
33.00	Spur, sloping N. 30° W. Thence by chaining, desc. 65 ft. over rocky SW. slope.
34.65	Four strand barbed wire fence, bears N. 30° W. and S. 30° E.
40.10	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

Survey of the Subdivision, T. 26 S., R. 28 E.

Chains	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E ½ S12 ½ S13 1958</p> <p>Cont. to desc. 45 ft. over SW. slope.</p>
42.25	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 35° W.</p> <p>Thence over rolling benchland.</p>
73.55	<p>Canyon rim, bears N. 30° W. and S. 30° E.; desc. abruptly 180 ft. over SW. slope.</p>
80.20	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, mountainous. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, catclaw, cacti, locust brush and moderate native grasses.</p>
	<p>N. 0° 01' W., bet. secs. 11 and 12.</p> <p>Over mountainous land.</p> <p>Asc. 100 ft. over rocky SW. slope.</p>
7.05	<p>Canyon rim, bears N. 30° W. and S. 30° E.</p> <p>Thence by triangulation, desc. 100 ft. over rolling to broken hills, general NW slope.</p>
33.00	<p>Wash, 40 lks. wide, 3 ft. deep, drains N. 35° W.</p>
40.00	<p>Point for the ½ sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E ½ S11 ½ S12 1958</p>
	<p>Thence by chaining, asc. 15 ft.</p>
41.10	<p>Ridge, bears N. 35° W. and S. 25° E.; thence across ridge top.</p>
50.25	<p>Thence by triangulation, desc. abruptly 540 ft. over rocky NE. slope.</p>
65.00	<p>Left bank of Gila River, bears N. 70° W. and E.</p>
67.00	<p>Right bank of Gila River, bears N. 70° W. and E.; asc. 100 ft. over general S. slope through moderate willow growth.</p>

BOOK 7429

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

72.00

Leave willow growth and set iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground

80.00

Point for the cor. of secs. 1, 2, 11 and 12.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S R28E

S 2 S 1

S11 S12

1958

Land, mountainous.

Soil, rocky.

Timber, none.

Undergrowth, scattered to moderate greasewood, locust brush, cacti and native grasses.

From the cor. of secs. 1 and 12 on the E. bdy. of T. 6 S., R. 28 E., an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the field notes of T. 6 S., R. 29 E. surveyed concurrently under this same group.

S. 89° 54' W., bet. secs. 1 and 12.

Over broken SE. slope.

By traverse and triangulation.

5.00

Point of spur slopes SE. desc. over SW. slope.

16.50

Right bank of Gila River bears N. 50° W. and S. 50° E.

19.00

Left bank of Gila River bears N. 50° W. and S. 50° E.

Asc. over steep broken NE. slope.

32.90

Point selected for the witness 1/4 sec. cor. of secs. 1 and 12.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E

W S 1

C S12

1958

Cor. is located on rocky spur, projecting N. 15° W., approximately 6 chs. to end.

Desc. abruptly 300 ft. over rocky W. slope.

40.05

True point for the 1/4 sec. cor. of secs. 1 and 12 falls on abrupt loose W. slope, where it is impractical to set the monument.

47.00

Slope changes to NW.; cont. to desc. 395 ft.

56.10

Left bank of Gila River, bears N. 60° E. and S. 60° W.

59.60

Right bank of Gila River, bears N. 60° E. and S. 60° W.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

66.70 Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

W.P. 28
S. 1
S12
1958

Thence by chaining, asc. 95 ft. over SE. slope.

75.55 Spur, sloping S. 10° W.; desc. 35 ft. over rocky general W. slope.

77.30 Slope changes to SW.

78.50 Slope changes to S.

80.10 The cor. of secs. 1, 2, 11 and 12.

Land, broken, mountainous.

Soil, rocky.

Timber, none.

Undergrowth, none.

N. 0° 01' W., bet. secs. 1 and 2.

Over broken mountainous land; asc. 145 ft. over SE. slope.

24.00 Spur, projects SW.; desc. 45 ft. over broken NW. slope.

30.40 Draw, drains SW.; asc. 130 ft. over broken SE. slope.

36.50 Spur, projects SW.; desc. 60 ft. over NW. slope.

40.00 Point for the 1/4 sec. cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E
S 2 | S 1
1958

Desc. 300 ft. along broken NW. slope.

55.00 Draw, drains W.; asc. 120 ft. along ledgy SW. slope.

78.84 Intersect the First Standard Parallel South; point for the closing cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T5S R28E
S 2 | S 1
T6S R28E
C C
1958

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

X

From the above cor. point the true point for the standard 1/4 sec. cor. of sec. 35 bears S. 89° 57' W., 2.99 chs. dist., from which its witness cor. bears N. 89° 57' E., 4.85 chs. dist., mkd. by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the notes of the survey of T. 5 S., R. 28 E.

Land, broken, mountainous.
Soil, rocky.
Timber, none.
Undergrowth, scattered greasewood, cacti and widely scattered native grasses.

The point for the N. 1/4 sec. cor. of sec. 1 is at midpoint bet. the closing cor. of secs. 1 and 6 of T. 6 S., Rs. 28 and 29 E., and the closing cor. of secs. 1 and 2.

True point for the N. 1/4 sec. cor. of sec. 1 falls on the steep slope of a ledge, where the cor. cannot be perpetuated. Therefore, at a point S. 89° 52' E., 7.81 chs. dist.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

1/4 S 1
W C
T6S R28E

1958

From the true point for the 1/4 sec. cor. of sec. 1, the true point for the standard cor. of secs. 35 and 36 bears N. 89° 52' W., 2.79 chs. dist., from which its witness cor. bears S. 89° 52' E., 11.15 chs. dist.

From the cor. of secs. 34 and 35 on the S. bdy. of T. 6 S., R. 28 E., monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 34 and 35.

Asc. 60 ft. over S. slope.

5.90 Spur, sloping E., thence over rolling land.

27.55 Wash, 25 lks. wide, 1 ft. deep, drains S. 30° E.; asc. 50 ft. over gradual SE. slope.

40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E

1/4

S34 S35

1957

Cor. is located 4 lks. W. of barbed wire fence, bears N. and S.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
66.35	<p>Cont. over rolling land.</p> <p>Wash, 30 lks. wide, 1 ft. deep, drains N. 25° E.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.</p>
	<p>T6S R28E S27 S26 S34 S35 1957</p>
	<p>Land, rolling.</p> <p>Soil, rocky.</p> <p>Timber, none.</p> <p>Undergrowth, scattered greasewood, catclaw, some locust brush and cacti, moderate native grasses.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36, hereinbefore described.</p> <p>N. 89° 52' W., bet. secs. 26 and 35.</p>
26.50	<p>Over rolling land.</p> <p>Four strand barbed wire fence, bears N. and S., 30 lks.; thence N. 80° E. and S. 80° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p>
	<p>T6S R28E S26 S35 1957</p>
	<p>Cor. is located 4 lks. N. of barbed wire fence, bears N, 80° E. and S. 80° W.</p>
	<p>Desc. 80 ft. over rolling, general W. slope.</p>
71.65	<p>Wash, 50 lks. wide, 1 ft. deep, drains N. 35° W.</p>
80.00	<p>The cor. of secs. 26, 27, 34 and 35.</p>
	<p>Land, rolling.</p> <p>Soil, rocky.</p> <p>Timber, none.</p> <p>Undergrowth, scattered greasewood, cacti, moderate native grasses.</p>
	<p>N. 0° 01' W., bet. secs. 26 and 27.</p>
	<p>Over rolling land.</p> <p>Desc. 140 ft. over general NE. slope.</p>
8.05	<p>Wash, 50 lks. wide, 1 ft. deep, drains N. 35° W.</p>

Survey of the Subdivision, T6S R. 28 E.

Chains	
17.15	Ridge, bears N. 30° W. and S. 30° E.
31.50	Top of ledge, facing NE., 75 ft. high.
32.80	Base of descent in wash, 60 lks. wide, 4 ft. deep, draining N. 50° W.; asc. 120 ft. over rocky S. slope.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E 1/4 S27 S26 1958
	Cont. to asc. 105 ft. over S. slope.
45.00	Slope changes to SE.
49.75	Ridge, bears N. 40° E. and S. 40° W.; desc. 145 ft. over rocky NW. slope.
60.20	Wash, 50 lks. wide, 2 ft. deep, drains S. 35° W.; asc. 180 ft. over broken S. slope.
73.00	Ridge, bears E. and W.; desc. 85 ft. over rocky N. slope.
74.65	Four strand barbed wire fence, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E S22 S23 S27 S26 1958
	Land, rolling. Soil, rocky. Timber, none. Undergrowth, very scattered catclaw, locust brush, scattered to moderate native grasses and cacti.
	From the cor. of secs. 23, 24, 25 and 26. N. 89° 57' W., bet. secs. 23 and 26. Over rolling to broken land. Asc. 95 ft. over general SE. slope to the 1/4 sec. cor.
11.95	Wash, 30 lks. wide, 1 ft. deep, drains S. 25° E.
22.55	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.
33.55	Four strand barbed wire fence, bears N. 10° W. and S. 10° E.
39.98	Point for the 1/4 sec. cor. of secs. 23 and 26.

Survey of the Subdivision, T. 6 S., R. 28 E.,

Chains	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	<p style="text-align: center;">T6S R28E $\frac{1}{4}$ S23 $\frac{1}{4}$ S26 1958</p> <p>Cor. is located on ridge, bears N. 30° E. and S. 30° W. Desc. 170 ft. over NW. slope.</p>
51.95	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.; asc. 95 ft. over SE. slope.
61.40	Spur, sloping S. 30° W.; desc. 90 ft. over NW. slope.
70.75	Four strand barbed wire fence, bears N. 60° E. and S. 60° W.
72.00	Slope changes to N.
79.96	The cor. of secs. 22, 23, 26 and 27. Land, rolling, broken. Soil, rocky. Timber, none. Undergrowth, scattered catclaw, cacti and native grasses.
	<p>N. 0° 01' W., bet. secs. 22 and 23. Over rolling land. Desc. 85 ft. over rocky N. slope.</p>
5.20	Wash, 30 lks. wide, 1 ft. deep, drains W.; asc. 130 ft. over S. slope.
12.00	Spur, sloping W.; desc. 215 ft. over rocky N. slope.
27.15	Wash, 70 lks. wide, 2 ft. deep, drains S. 75° W.; asc. 160 ft. over SE. slope.
34.35	Rut road, bears N. 60° E. and S. 60° W.; cont. to asc. 65 ft.
37.55	Ridge, bears N. 55° E. and S. 55° W.; desc. 35 ft. over NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	<p style="text-align: center;">T6S R28E $\frac{1}{4}$ S22 $\frac{1}{4}$ S23 1958</p> <p>Thence over mountainous land. Desc. 195 ft. over NW. slope.</p>
47.20	Wash, 35 lks. wide, 2 ft. deep, drains W.; asc. 200 ft. over S. slope.

BOOK 4016

Survey of the Subdivision, T. 16 S., R. 28 E.

Chains																	
56.05	Spur, sloping W.; desc. 105 ft. along rocky, broken NW. slope.																
59.05	Four strand barbed wire fence, bears N. 80° W. and S. 80° E.																
64.65	Thence by triangulation; desc. 75 ft.																
71.00	Left bank of Gila River, bears S. 30° W. and N. 20° E.																
72.80	Right bank of Gila River, bears S. 30° W. and N. 20° E.																
80.00	Point for the cor. of secs. 14, 15, 22 and 23.																
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.																
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="4" style="text-align: center;">T6S R28E</td></tr> <tr><td style="border-right: 1px solid black; border-bottom: 1px solid black;">S15</td><td style="border-bottom: 1px solid black;">S14</td><td colspan="2"></td></tr> <tr><td style="border-right: 1px solid black;">S22</td><td>S23</td><td colspan="2"></td></tr> <tr><td colspan="4" style="text-align: center;">1958</td></tr> </table>	T6S R28E				S15	S14			S22	S23			1958			
T6S R28E																	
S15	S14																
S22	S23																
1958																	
	<p>Land, south half, rolling; north half, mountainous. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, cacti and native grasses.</p>																
	From the cor. of secs. 13, 14, 23 and 24.																
	S. 89° 46' W., bet. secs. 14 and 23.																
	Over mountainous land.																
	By triangulation, desc. 170 ft. over rocky, rolling to broken land, general drainage to W.																
20.00	Wash, 40 lks. wide, 4 ft. deep, drains N. 40° W.																
31.95	Spur, sloping N. 40° W.; desc. 85 ft. over rocky SW. slope.																
39.96	Point for the ¼ sec. cor. of secs. 14 and 23.																
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.																
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="4" style="text-align: center;">T6S R28E</td></tr> <tr><td colspan="2"></td><td style="border-right: 1px solid black; border-bottom: 1px solid black;">S14</td><td></td></tr> <tr><td colspan="2"></td><td style="border-right: 1px solid black;">S23</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">1958</td></tr> </table>	T6S R28E						S14				S23		1958			
T6S R28E																	
		S14															
		S23															
1958																	
	Cont. to desc. 175 ft. over SW. slope.																
49.60	Wash, 60 lks. wide, 3 ft. deep, drains N. 40° W; asc. 265 ft. over rocky, general E. slope.																
59.15	Spur, sloping N.; desc. 215 ft. over rocky W. slope.																
74.65	Left bank of Gila River, bears N. 30° E. and S. 20° W.																

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
76.45	Right bank of Gila River, bears N. 30° E. and S. 20° W.; asc. 50 ft. over general E. slope.
79.92	The cor. of secs. 14, 15, 22 and 23. Land, mountainous. Soil, rocky. Timber, none. Undergrowth, scattered native grasses and cacti, moderate greasewood.
	N. 0° 01' W.; bet. secs. 14 and 15. Over mountainous land. By triangulation, desc. 40 ft. along general E. slope.
12.00	Right bank of Gila River, bears N. 60° W. and S. 60° E.
13.80	Left bank of Gila River, bears N. 60° W. and S. 60° E.; asc. 85 ft. over rolling to broken land, general SW. slope.
32.00	Slope changes to W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E $\frac{1}{4}$ S15 S14 1958 Cor. is located on W. slope, 8 chs. E. of Gila River. Desc. 55 ft. along W. slope.
48.00	Left bank of Gila River, bears N. 45° E. and S. 45° W.
50.00	Right bank of Gila River, bears N. 45° E. and S. 45° W.; thence asc. 60 ft. along broken, rocky SE. slope.
78.20	Spur, sloping E.; desc. 25 ft. over broken, rocky N. slope.
79.50	Point selected for the witness cor. of secs. 10, 11, 14 and 15. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E W. C. S. 11 S10 S11 S15 S14 1958 Cont. to desc. 30 ft. over broken N. slope.
80.00	True point for the cor. of secs. 10, 11, 14 and 15 falls on a ledge, 100 ft. high, facing N., where the monument cannot be perpetuated.

BOOK 4070

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	<p>Land, mountainous. Soil, rocky. Timber, heavy growth of juniper and willow along river banks. Undergrowth, scattered greasewood, cacti, native grasses.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14. S. 89° 50' W., bet. secs. 11 and 14. Over mountainous land. By triangulation, desc. 510 ft. over broken SW. slope of canyon.</p>
27.05	Canyon bottom, draining N. 35° W.; asc. 305 ft. over broken NE. slope of canyon.
40.02	True point for the $\frac{1}{2}$ sec. cor. of secs. 11 and 14 falls on a broken ledge, 65 ft. high, facing NE., where the monument cannot be perpetuated.
41.75	Point selected for the witness $\frac{1}{2}$ sec. cor. of secs. 11 and 14. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. <div style="text-align: center;"> <p>T6S R28E S11 W S14 C 1958</p> </div>
	<p>Cor. is located on rim of canyon, bears N. 35° W. and S. 35° E., 210 ft. below the cor. of secs. 11, 12, 13 and 14. Desc. 140 ft. over broken SW. slope.</p>
53.00	Left bank of Gila River, bears N. 20° W. and S. 20° E.
55.00	Right bank of Gila River, bears N. 20° W. and S. 20° E.; asc. 50 ft. along broken N. slope through heavy willow growth.
80.04	The true point for the cor. of secs. 10, 11, 14 and 15. Land, mountainous. Soil, rocky. Timber, moderate growth of juniper along river banks. Undergrowth, scattered greasewood, cacti, native grasses, heavy willow growth along river banks.
	<p>N. 0° 01' W., bet. secs. 10 and 11. Over mountainous land. By triangulation, desc. 60 ft. over broken N. slope.</p>
7.00	Right bank of Gila River, bears N. 80° W. and N. 60° E.
9.00	Left bank of Gila River, bears N. 80° W. and N. 60° E.; asc. 175 ft. over rolling to broken general S. slope.
33.35	Spur, sloping W.; desc. 155 ft. over broken N. slope.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 10 and 11.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E $\frac{1}{2}$ S10 S11 1958</p> <p>Cor. is located at base of broken N. slope.</p>
47.00	Left bank of Gila River, bears N. 75° E. and S. 75° W.
49.50	Right bank of Gila River, bears N. 75° E. and S. 75° W.; asc. 285 ft. over rolling to broken SW. slope.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E S3 S2 S10 S11 1958</p> <p>Land, rolling to broken, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, scattered cacti, native grasses, moderate willow growth along river banks.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89° 53' W., bet. secs. 2 and 11.</p> <p>Over broken mountainous land.</p> <p>By triangulation, desc. 150 ft. along S. slope.</p>
4.50	Slope changes to SW.; desc. 250 ft.
10.00	Right bank of Gila River, course N.
12.00	Left bank of river; thence by chaining, asc. 500 ft. over broken general E. slope.
28.85	Spur, sloping N.; desc. 350 ft. over broken W. slope.
35.85	Point selected for the witness ¼ sec. cor. of secs. 2 and 11.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E $\frac{1}{4}$ sec. cor. W S 2 C S11 1958</p>
38.00	Left bank of Gila River, course S. 45° W.
	Thence by triangulation across river.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
40.04	True point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11 falls in the Gila River.
41.00	Right bank of river; thence by chaining, asc. 315 ft. over rolling to broken E. slope.
60.00	Slope changes to NE.
70.50	Spur, sloping S. 30° E.; desc. 295 ft. over broken SW. slope.
80.08	The cor. of secs. 2, 3, 10 and 11. Land, broken to rolling mountains. Soil, rocky clay. Timber, none. Undergrowth, scattered greasewood, cacti and native grasses.
	N. $0^{\circ} 01'$ W., bet. secs. 2 and 3. Over mountainous land. Asc. 505 ft. over rocky, broken SW. slope.
37.85	Spur, sloping S. 35° E.; desc. 20 ft. over rocky NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E S 3 S 2 1958
	Thence by triangulation, desc. 450 ft. over rocky NE. slope.
54.85	Wash, 40 lks. wide, 3 ft. deep, drains S. 35° E.; asc. 400 ft. along broken W. slope.
79.09	Intersect the First Standard Parallel South. Point for the closing cor. of secs. 2 and 3. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T5S R28E S34 S 3 S 2 C.C T6S R28E 1958
	From the above cor. point the true point for the standard $\frac{1}{4}$ sec. cor. of sec. 34 bears S. $89^{\circ} 57'$ W., 2.72 chs. dist., from which its witness cor. bears S. $89^{\circ} 57'$ W., 11.06 chs. dist. mkd. by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the notes of the survey of T. 5 S., R. 28 E.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

Land, broken, mountainous.
Soil, rocky.
Timber, none.
Undergrowth, scattered greasewood, cacti and native grasses.

The point for the N. 1/4 sec. cor. of sec. 2 is at midpoint bet. the closing cor. of secs. 1 and 2 and the closing cor. of secs. 2 and 3.

The true point for the N. 1/4 sec. cor. of sec. 2 falls on a steep, broken NE. slope where the cor. cannot be perpetuated; therefore, at a point S. 89° 57' W., 5.06 chs. dist.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

W
S 2 C
T6S R28E
1958

From the true point for the above witness cor. the true point for the standard cor. of secs. 34 and 35 bears S. 89° 57' W., 2.85 chs. dist., from which its witness cor. bears S. 89° 57' W., 1.04 chs. dist., mkd. by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the notes of the survey of T. 5 S., R. 28 E.

From the cor. of secs. 33 and 34, on the S. bdy. of T. 6 S., R. 28 E., monumented by an iron post, 2 1/2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 33 and 34.

Over rolling land.

Asc. 150 ft. over rocky general S. slope.

35.00 Wash, 30 lks. wide, 1 ft. deep, drains S. 50° W.; asc. 85 ft. over rocky S. slope.

40.00 Point for the 1/4 sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S R28E
1/4
S33 | S34
1957

Asc. 40 ft. over S. slope.

42.40 Ridge, bears E. and W.; desc. 170 ft. over rocky general N. slope.

50.00 Slope changes to NE.

57.30 Wash, 25 lks. wide, 1 ft. deep; drains N. 25° W.

62.85 Wash, 35 lks. wide, 1 ft. deep, drains N. 50° W.; asc. 190 ft. over broken SE. slope.

Survey of the Subdivision, T. 6 S., R. 28 E.,

Chains	
77.90	Spur, sloping N. 35° E.; desc. 70 ft. over rocky NW. slope.
80.00	Point for the cor. of secs. 27, 28, 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	T6S R28E S28 S27 S33 S34 1957
	Land, rolling to broken. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, catclaw, locust brush, cacti, moderate native grasses.
	From the cor. of secs. 26, 27, 34 and 35. S. 89° 57' W., bet. secs. 27 and 34. Over rolling land. Asc. 25 ft. over general SE. slope.
7.30	Small rise, bears N. 25° E. and S. 25° W.; desc. 100 ft. over NW. slope.
11.30	Wash, 40 lks. wide, 1 ft. deep, drains N.; asc. 80 ft. over E. slope.
15.65	Small rise, bears N. and S.; desc. 80 ft. over general W. slope.
18.65	Draw, draining N. 30° E.; asc. 150 ft. over rocky E. slope.
28.70	Rut road, bears N. and S.; slope changes to NE.
34.70	Ridge, bears N. 35° W. and S. 35° E.; desc. 75 ft. over rocky SW. slope.
40.04	Point for the ¼ sec. cor. of secs. 27 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	T6S R28E S27 ¼ S34 1957
	Desc. 325 ft. over rolling land; general SW. slope.
70.65	Wash, 120 lks. wide, 4 ft. deep, drains N. 40° W.; asc. 130 ft. over E. slope.
74.50	Slope changes to SE.
77.90	Spur, sloping N. 20° E.; desc. 45 ft. over rocky NW. slope.
80.08	The cor. of secs. 27, 28, 33 and 34.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, scattered catclaw, locust brush, cacti and native grasses.

N. 89° 55' W., bet. secs. 28 and 33.

Over rolling land.

Desc. 30 ft. over rocky NW. slope.

1.00 Small wash, drains N. 15° E.; asc. 140 ft. over rocky NE. slope.

7.60 Ridge, bears N. 30° W. and S. 20° E.; desc. 155 ft. over rocky SW. slope.

13.45 Draw, drains N. 35° W.; asc. 110 ft. over NE. slope.

17.75 Spur, sloping N. 30° W.; desc. 230 ft. over SW. slope.

32.70 Wash, 60 lks. wide, 2 ft. deep, drains N. 30° W.; asc. 160 ft. over NE. slope.

40.12 Point for the $\frac{1}{2}$ sec. cor. of secs. 28 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E

S28

$\frac{1}{2}$ S33

1957

Asc. 15 ft. over NE. slope.

41.70 Ridge, bears N. 30° W. and S. 30° E.; desc. 175 ft. over rocky SW. slope.

53.25 Wash, 25 lks. wide, 1 ft. deep, drains N. 25° W.; thence over a series of spurs and washes, sloping and draining NW.; desc. 35 ft.

68.25 Wash, 30 lks. wide, 1 ft. deep, drains N. 30° W.

75.55 Rut road, bears N. 30° W. and S. 40° E.

80.24 The cor. of secs. 28, 29, 32 and 33 monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, rocky.

Timber, none.

Undergrowth, scattered cacti, catclaw, moderate greasewood and native grasses.

N. 0° 02' W., bet. secs. 27 and 28.

Over rolling to broken land.

Desc. 60 ft. over NW. slope.

1.70 Draw, drains N. 15° E.; cont. to desc. 255 ft.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
22.40	Wash, 2 chs. wide, 3 ft. deep, drains N. 30° W.; asc. 40 ft. over S. slope.
25.00	Spur, sloping W.; desc. 40 ft. over N. slope.
26.70	Wash, 1½ chs. wide, 2 ft. deep, drains W.; asc. 125 ft. over S. slope.
32.30	Spur, sloping W.; desc. 85 ft. over N. slope.
39.45	Wash, 25 lks. wide, 2 ft. deep, drains W.; asc. 15 ft. over S. slope.
40.00	Point for the ¼ sec. cor. of secs. 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	T6S R28E ¼ S28 S27 1958
	Cont. to asc. 30 ft. over S. slope.
42.20	Spur, sloping W. Thence by triangulation, desc. 245 ft. over rocky N. slope.
44.00	Slope changes to NW.
52.00	Base of descent, thence across bottom land.
65.30	Left bank of Gila River, bears N. 50° E. and S. 50° W.
67.00	Right bank of Gila River, bears N. 50° E. and S. 50° W.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	T6S R28E S21 S22 S28 S27 1958
	Cor. is located 3 chs. W. of right bank of Gila River, bears N. 30° W. and S. 30° E. Land, rolling to broken. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, native grasses, heavy growth of willow along river banks.
	From the cor. of secs. 22, 23, 26 and 27. N. 89° 56' W., bet. secs. 22 and 27. Over rolling land.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	Desc. 20 ft. along rocky N. slope.
6.00	Head of wash, drains N. 10° E.; slope changes to NE.
11.00	Slope changes to E.; asc. 40 ft.
19.80	Spur, sloping N.; desc. 155 ft. over rocky W. slope.
32.50	Draw, drains N. 20° W.; asc. 40 ft. over NE. slope.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	T6S R28E $\frac{1}{4}$ $\frac{S22}{S27}$ 1958
	Asc. 60 ft. over NE. slope.
47.50	Slope changes to N.; asc. 20 ft.
47.90	Four strand barbed wire fence, bears N. 20° W. and S. 20° E.
49.60	Top of ascent on N. slope.
	Thence by triangulation, desc. 485 ft. over rocky general SW. slope.
75.26	Left bank of Gila River, bears N. 15° W. and S. 15° E.
76.95	Right bank of Gila River, bears N. 15° W. and S. 15° E.
80.06	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling to broken. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, cacti and native grasses.
	N. 89° 57' W., bet. secs. 21 and 28.
	Over broken to rolling land.
	By triangulation, asc. 75 ft. over rolling, rocky general E. slope, through heavy willow growth.
14.10	Rut road, bears N. and S.
	Thence by chaining, asc. 80 ft. over NE. slope.
40.13	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	T6S R28E $\frac{1}{4}$ $\frac{S21}{S28}$ 1958
	Thence over rolling hills, general drainage SE.; desc. 130 ft. to sec. cor.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
64.90	Wash, 40 lks. wide, 2 ft. deep, drains S.
80.26	The true point for the cor. of secs. 20, 21, 28 and 29 which is witnessed N. 0° 02' W., 0.50 chs. dist. by a 2½ in. iron post as described in the official record. Land, broken to rolling. Soil, rocky. Timber, none. Undergrowth, scattered cacti, native grasses, moderate greasewood.
	From the cor. of secs. 21, 22, 27 and 28. N. 0° 14' W., bet. secs. 21 and 22. By triangulation.
4.00	Right bank Gila River, bears N. 30° W. and S. 30° E.
6.00	Left bank Gila River, bears N. 30° W. and S. 30° E. Asc. 50 ft.
20.00	Spur, sloping W.; desc. 55 ft. over N. slope.
27.00	Left bank Gila River, bears N. 45° E. and S. 45° W.
29.00	Right bank Gila River, bears N. 45° E. and S. 45° W.; asc. 95 ft. over steep SE. slope.
36.00	Slope changes to E.
39.97	Point for the ¼ sec. cor. of secs. 21 and 22. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E S21 S22 1958 Desc. 25 ft. along E. slope.
61.55	Wash, 40 lks. wide, 2 ft. deep, drains S. 20° E.; asc. 105 ft. over general S. slope.
77.95	Wash, 35 lks. wide, 2 ft. deep, drains S. 15° E.
79.94	The cor. of secs. 15, 16, 21 and 22, monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the official record. Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered greasewood, cacti, native grasses.

BOOK 4616

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89° 59' W., bet. secs. 15 and 22.
	Asc. 370 ft. over rolling SE. slope of benchland.
12.65	Draw, draining S. 30° E.
40.14	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	<p style="text-align: center;">T6S R28E $\frac{1}{4}$ $\frac{S15}{S22}$ 1958</p>
	Thence over rolling hills, general W. slope; desc. 180 ft.
80.28	The cor. of secs. 15, 16, 21 and 22, hereinbefore described.
	Land, east half, rolling bench; west half, rolling hill land.
	Soil, rocky.
	Timber, none.
	Undergrowth, scattered cacti, native grasses, moderate greasewood.
	<hr/>
	From the true point for the cor. of secs. 10, 11, 14 and 15.
	S. 89° 54' W., bet. secs. 10 and 15.
	Asc. 220 ft. along broken N. slope.
13.65	Thence over rolling benchland; desc. 145 ft., general W. slope.
40.16	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	<p style="text-align: center;">T6S R28E $\frac{1}{4}$ $\frac{S10}{S15}$ 1958</p>
	Cor. is located 15 lks. N. of wash, 30 lks. wide, 1 ft. deep, drains S. 20° W.
	Cont. over rolling bench land, general drainage SW.
70.00	Wash, 30 lks. wide, 1 ft. deep, drains S. 40° W.
80.32	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the official record.
	Land, rolling benchland.
	Soil, rocky.
	Timber, none.
	Undergrowth, scattered cacti, native grasses, moderate greasewood.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	N. 0° 02' W., bet. secs. 9 and 10. Over rolling benchland; asc. 165 ft., general SE. slope.
28.80	Rut road, bears N. 70° E. and S. 70° W.
30.00	Ridge, bears N. 35° E. and S. 35° W.; desc. 65 ft. over rocky NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E S 9 S10 1958
	Thence by triangulation, desc. 105 ft. over NW. slope.
40.20	Rut road, bears N. 30° E. and S. 30° W.
53.00	Wash, 40 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 210 ft. over rocky SE. slope.
56.00	Rut road, bears N. 60° E. and S. 60° W.
66.00	Rut road, bears N. 40° E. and S. 40° W.
67.00	Four strand barbed wire fence, bears N. 60° E. and S. 60° W.
70.00	Spur, sloping S. 40° W.; desc. 20 ft. over NW. slope.
80.00	Point for the cor. of secs. 3, 4, 9 and 10. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E S 4 S 3 S 9 S10 1958
	Land, south half, rolling benchland; north half, high rolling land. Soil, rocky. Timber, none. Undergrowth, scattered cacti, native grasses, moderate greasewood.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89° 55' W., bet. secs. 3 and 10.
	Over mountainous land.
	By triangulation, desc. 330 ft. over rocky SW. slope.
8.00	Wash, 30 lks. wide, 2 ft. deep, drains S. 25° W.; asc. 470 ft. over NE. slope.
29.70	Rut road, bears N. 10° E. and S. 30° W.; thence over rolling ridge top; asc. 15 ft.
40.15	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

BOOK 4810

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S R28E.

S 3

¼ S10

1958

Cor. is located on ridge; top, bears N. 35° W. and S. 30° E.

- 44.00 Desc. 375 ft. over rocky NW. slope.
- 52.30 Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 465 ft. over rocky, broken SE. slope.
- 62.55 Four strand barbed wire fence, bears N. 45° E. and S. 45° W.
- 67.30 Spur, sloping S. 30° W.
- Thence by chaining, desc. 110 ft. over rocky NW. slope, heavy native grasses.
- 68.55 Rut road, bears N. 30° E. and S. 30° W.
- 80.30 The cor. of secs. 3, 4, 9 and 10.

Land, mountainous.
Soil, rocky.
Timber, none.
Undergrowth, scattered to heavy native grasses, scattered cacti, moderate greasewood.

S. 89° 44' W., bet. secs. 4 and 9.

Over mountainous land,

Desc. 180 ft. over NW. slope.

- 13.10 Wash, 30 lks. wide, 2 ft. deep, drains S. 35° W.; asc. 155 ft. over rocky E. slope.
- 22.60 Spur, slopes S.; desc. 195 ft. over rocky W. slope.
- 38.90 Draw, drains S. 10° W.; asc. 20 ft. over SE. slope.
- 40.16 Point for the ¼ sec. cor. of secs. 4 and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T6S R28E

¼ S 4

S 9

1958

Cont. to asc. 15 ft. over SE. slope.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
42.50	Spur, slopes S. 15° W.; desc. 55 ft. over NW. slope.
45.15	Wash, 40 lks. wide, 2 ft. deep, drains S. 10° W.; asc. 140 ft. over general E. slope.
52.00	Slope changes to NE.
64.00	Spur, slopes S. 15° E.; desc. 165 ft. over SW. slope.
80.32	The cor. of secs. 4, 5, 8 and 9 monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the official record.
	Land, mountainous. Soil, rocky clay. Timber, none. Undergrowth, scattered cacti, scattered to moderate greasewood and native grasses.
	From the cor. of secs. 3, 4, 9 and 10. N. 40° 02' W., bet. secs. 3 and 4. Over mountainous land, over medium dense undergrowth. By triangulation, desc. 85 ft. over NW. slope.
12.50	Wash, 40 lks. wide, 3 ft. deep, drains S. 45° W.; asc. 215 ft. over rocky S. slope.
19.00	Slope changes to SW.
40.00	Point for the ¼ sec. cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E S 4 S 3 1958
	Thence by chaining, asc. 95 ft. over SW. slope.
43.50	Rut road, bears N. 60° W. and S. 60° E.
49.60	Ridge, bears N. 30° W. and S. 20° E.; desc. 335 ft. over NE. slope.
67.25	Wash, 60 lks. wide, 2 ft. deep, drains S. 30° E.; asc. 140 ft. along rocky SW. slope.
79.34	Intersect the First Standard Parallel South. Point for the closing cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) cut on solid limestone and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

T5S R28E

S33

S 4 | S 3

C C

T6S R28E

1958

From the above cor. the standard $\frac{1}{4}$ sec. cor. of sec. 33 bears N. 89° 57' W., 2.59 chs. dist., mkd. by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the notes of T. 5 S., R. 28 E.

Land, mountainous.

Soil, rocky clay.

Timber, none.

Undergrowth, scattered greasewood, cacti and native grasses.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3 is at midpoint bet. the closing cor. of secs. 2 and 3 and the closing cor. of secs. 3 and 4.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) on bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

 $\frac{1}{4}$ S. 3

T6S R28E

1958

From the above cor. the standard cor. of secs. 33 and 34 bears N. 89° 54' W., 2.66 chs. dist.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 4 is at midpoint bet. the closing cor. of secs. 3 and 4 and the closing cor. of secs. 4 and 5.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) cut on bedrock and in a mound of stone, $3\frac{1}{2}$ ft. base, to top of post, with brass cap mkd.

 $\frac{1}{4}$ S 4

T6S R28E

From the above cor. the standard cor. of secs. 32 and 33 bears W. 2.34 chs. dist.

Dependent Resurvey of a Portion of the Subdivision, T. 6 S., R. 28 E.

From the cor. of secs. 29, 30, 31 and 32, monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. 89° 57' W., bet. secs. 30 and 31.

Through river bottom.

By triangulation.

Dependent Resurvey, Portion of Subdivision, T. 6 S., R. 28 E.

Chains

- 4.00 Left bank Gila River, bears N. 20° E. and S. 40° W.
- 5.50 Right bank Gila River, bears N. 20° E. and S. 40° W.; asc. 110 ft. over rocky, rolling benchland, general SE. slope and drainage.
- 24.05 Thence by chaining.
- 40.03 The original $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented by a malpais stone, firmly set, mkd. and witnessed as described in the official record of 1895.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
- T6S R28E
 $\frac{1}{4}$ S30
 S31
 1958
- Deposit original stone monument alongside iron post.
-
- S. 89° 54' W., beginning new measurement.
- 1.00 Top of ascent on benchland; desc. 50 ft. general W. slope and drainage.
- 16.00 Rut road, bears N. 70° E. and S. 70° W.
- 22.00 General slope and drainage changes to N.
- 38.05 Four strand barbed wire fence, bears N. 20° W. and S. 20° E.
- 38.13 Intersect W. bdy. of Tp. at the cor. of secs. 25, 30, 31 and 36, hereinbefore described.
- Land, benchland.
 Soil, rocky.
 Timber, none.
 Undergrowth, scattered cacti, native grasses, scattered to moderate greasewood.
-
- Survey of the Subdivision of T. 6 S., R. 28 E.
-
- From the cor. of secs. 19, 20, 29 and 30, monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the official record.
- N. 89° 46' W., bet. secs. 19 and 30.
- Over rolling land.
- Asc. 145 ft. along general N. slope.
- 15.00 Slope changes to NE.
- 19.50 Slope changes to E.
- 23.30 Ridge, bears N. and S.; desc. 155 ft. over rocky W. slope.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
39.20	Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 20 ft. over SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd. T6S R28E $\frac{1}{4}$ $\frac{S19}{S30}$ 1958 Cor. is located on small spur, sloping S. Desc. 30 ft. over W. slope.
42.35	Wash, 30 lks. wide, 2 ft. deep, drains S. 15° W.; asc. 70 ft. over rocky general SE. slope.
45.35	Rut road, bears N. 40° E. and S. 40° W.
59.85	Four strand barbed wire fence, bears N. 60° W. and S. 60° E.
60.30	Spur, sloping S. 25° W.; desc. 110 ft. over general NW. slope.
77.05	Wash, 30 lks. wide, 1 ft. deep, drains S. 20° W.; asc. 20 ft. over SE. slope.
78.31	Intersect W. bdy. of Tp. at the cor. of secs. 19, 24, 25 and 30, hereinbefore described. Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered cacti, native grasses, scattered to moderate greasewood.
	From the cor. of secs. 19, 20, 29 and 30, hereinbefore described. N. 0° 03' W., bet. secs. 19 and 20. Over rolling land. Desc. 40 ft. over NE. slope.
3.35	Draw, drains S. 20° E.; asc. 90 ft. over SW. slope.
20.90	Ridge, bears N. 30° W. and S. 30° E.; desc. 210 ft. over rocky NE. slope.
23.65	Rut road, bears N. 35° W. and S. 35° E.
38.00	Wash, 50 lks. wide, 4 ft. deep, drains S. 40° E.; asc. 85 ft. over rocky SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	<p style="text-align: center;">T6S R28E $\frac{1}{4}$ S19 S20 1958</p>
	Cont. to asc. 45 ft. over SW. slope.
42.10	Spur, sloping S. 25° E.; desc. 145 ft. over NE. slope.
45.50	Wash, 40 lks. wide, 2 ft. deep, drains S. 30° E.
50.00	Same wash, drains S. 20° W.
54.75	Same wash, drains S. 30° E.; asc. 250 ft. over broken SW. slope.
74.40	Four strand barbed wire fence, bears E. and W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.
	<p>T6S R28E S18 S17 S19 S20 1958</p>
	Land, rolling.
	Soil, rocky.
	Timber, none.
	Undergrowth, scattered cacti, greasewood, native grasses.
	From the cor. of secs. 16, 17, 20 and 21, monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the official record.
	N. 89° 58' W., bet. secs. 17 and 20.
	Over rolling land.
	Asc. 105 ft. over NE. slope.
21.15	Ridge, bears N. 40° W. and S. 40° E.; desc. 135 ft. over SW. slope.
34.40	Rut road, bears N. 60° E. and S. 20° W.
40.00	Point for the ¼ sec. cor. of secs. 17 and 20.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.
	<p>T6S R28E $\frac{1}{4}$ S17 S20 1958</p>
	Cont. to desc. 95 ft. over SW. slope.
43.30	Wash, 40 lks. wide, 4 ft. deep, drains S.; asc. 170 ft. over E. slope.
51.30	Spur, sloping S.; desc. 220 ft. over W. slope.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
63.60	Wash, 50 lks. wide, 5 ft. deep, drains S. 20° E.; asc. 320 ft. over NE. slope.
66.80	Four strand barbed wire fence, bears N. 70° E. and S. 70° W.
75.85	Rut road on ridge, bears N. 30° W. and S. 30° E.; desc. 40 ft. over SW. slope.
79.12	The cor. of secs. 17, 18, 19 and 20. Land, rolling. Soil, rocky. Timber, none. Undergrowth, scattered cacti, greasewood, native grasses.
	S. 89° 57' W., bet. secs. 18 and 19. Over rolling land. Desc. 235 ft. over SW. slope.
9.65	Wash, 40 lks. wide, 2 ft. deep, drains S. 30° E.; asc. 215 ft. over NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E $\frac{1}{4}$ $\frac{S18}{S19}$ 1958 Cont. to asc. 60 ft. over NE. slope.
55.00	Spur, projects SE.; desc. 75 ft. along SW. slope.
68.10	Wash, 50 lks. wide, 2 ft. deep, drains S. 75° E.; asc. 55 ft. over NE. slope.
68.20	Rut road, bears N. 30° W. and S. 30° E.
69.40	Barbed wire fence, bears NW. and SE.
69.90	Ridge, bears N. 30° W. and S. 30° E.; desc. 75 ft. over rocky SW. slope.
78.50	Intersect the W. bdy. of the Tp. at the cor. of secs. 13, 18, 19 and 24, hereinbefore described. Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, scattered cacti, greasewood and native grasses.
	From the cor. of secs. 17, 18, 19 and 20, hereinbefore described. N. 0° 03' W., bet. secs. 17 and 18. Over rolling land.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains	
	Asc. 40 ft. over SW. slope.
5.80	Rut road, bears N. 40° W. and S. 30° E.
6.00	Ridge, bears N. 30° W. and S. 30° E.; desc. 190 ft. over NE. slope.
7.80	Four strand barbed wire fence, bears N. 60° W. and S. 60° E.
21.90	Wash, 50 lks. wide, 4 ft. deep, drains S. 30° E.
28.00	Same wash, drains S. 40° W. and N. 25° E.
32.55	Same wash, drains S. 20° E. from N. 35° W.; asc. 65 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E S18 S17 1958 Cor. is located 1.50 chs. E. of wash, 30 lks. wide, 2 ft. deep, draining S. 25° E. Asc. 215 ft. over general SW. slope.
79.55	Intersect the S. bdy. of sec. 8. Point for the closing cor. of secs. 17 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd. T6S R28E S 8 S18 S17 C C 1958 Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, moderate cacti, greasewood and native grasses.

From the above cor. the original cor. of secs. 7, 8, 17 and 18 bears S. 89° 40' W., 1.43 chs. dist., mkd. by a malpais stone, set, mkd. and witnessed as described in the official record. This cor. now refers to secs. 7 and 8 only.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

Survey of the Subdivision, T. 6 S., R. 28 E.

Chains

T6S R28E

S 7 | S 8

S18

1958

Deposit the original cor. alongside iron post.

From the cor. of secs. 8, 9, 16 and 17 mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

S. 89° 40' W., bet. secs. 8 and 17.

Over rolling mountainous land, through scattered undergrowth.

Asc. 310 ft. over E. slope.

20.35 Four strand barbed wire fence, bears N. and S.

22.15 Rut road, bears N. 15° E. and S. 30° W.

22.95 Spur, projects S.; desc. 130 ft. over general NW. slope.

28.95 Draw, drains S. 30° W.; asc. 175 ft. over general E. slope.

40.00 Point for the ¼ sec. cor. of sec. 17.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

¼ S17

T6S R28E

1958

40.18 Point for the ¼ sec. cor. of sec. 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S R28E

¼ S 8

1958

Desc. 35 ft. over W. slope.

41.60 Wash, 30 lks. wide, 1 ft. deep, drains S.; asc. 110 ft. over E. slope.

50.10 Spur, projects S. 10° E.; desc. 130 ft. over SW. slope.

58.25 Wash, 35 lks. wide, 2 ft. deep, drains S. 15° E.; asc. 165 ft. over NE. slope.

71.00 Ridge, bears N. 20° W. and S. 20° E.; desc. 10 ft. over SW. slope.

78.93 The closing cor. of secs. 17 and 18.

Cont. to desc. 10 ft. over SW. slope.

80.36 The cor. of secs. 7 and 8.

Land, high, rolling.

Soil, rocky clay.

Timber, none.

Undergrowth, moderate cacti, greasewood, native grasses.

Dependent Resurvey, Portion of Subdivision, T. 6 S., R. 28 E.

Chains

Dependent Resurvey of a Portion of the Subdivision, T. 6 S., R. 28 E.

Reestablishment of the survey executed by Philip Contzen in 1895.

S. 89° 49' W., bet. secs. 7 and 18.

Over rolling land.

Desc. 190 ft. over rocky SW. slope.

10.10 Wash, 50 lks. wide, 4 ft. deep, drains S. 15° E.; asc. 250 ft. over general NE. slope.

14.95 Four strand barbed wire fence, bears N. 70° E. and S. 70° W.

36.60 Rut road, bears N. 20° E. and S. 20° W.

38.57 Point for the 1/4 sec. cor. of sec. 18, at 40 chs. in longitude W. of the closing cor. of secs. 17 and 18.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

1/4 S18
T6S R28E
1958

39.71 The original 1/4 sec. cor. of secs. 7 and 18, monumented by a malpais stone, firmly set, mkd. and witnessed as described in the official record.

This monument now refers to sec. 7 only.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S R28E
1/4 S 7
1958

Deposit original stone monument alongside iron post.

Cor. is located on spur top, sloping S. 20° E.

S. 89° 42' W., beginning new measurement.

Desc. 135 ft. over general SW. slope.

11.40 Wash, 30 lks. wide, 1 ft. deep, drains S. 15° E.; asc. 250 ft. over general NE. slope.

BOOK 4616

Dependent Resurvey, Portion of Subdivision, T. 6 S., R. 28 E.

Chains	
37.53	Intersect W. bdy. of Tp. at the cor. of secs. 7, 12, 13 and 18.
	<p>Land, rolling. Soil, rocky. Timber, none. Undergrowth, moderate cacti, greasewood and native grasses.</p>
	<p>From the cor. of secs. 7 and 8, hereinbefore described.</p>
	<p>N. 0° 07' E., bet. secs. 7 and 8.</p>
	<p>Over high rolling land.</p>
	<p>Asc. 45 ft. over SW. slope.</p>
7.90	Spur, sloping S. 30° E.; desc. 30 ft. over rocky general NE. slope.
23.00	Rut road, bears N. 60° W. and S. 60° E.
25.00	Small wash, drains S. 20° E.; asc. 50 ft. over rocky general SW. slope.
27.25	Spur, slopes S. 25° E.; desc. 70 ft. over rocky NE. slope.
40.08	The original $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented by a malpais stone, firmly set, mkd. and witnessed as described in the official record.
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.</p>
	<p style="text-align: center;">T6S. R28E</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S 7 S 8</p>
	<p style="text-align: center;">1958</p>
	<p>Deposit original stone monument alongside iron post.</p>
	<hr/>
	<p>N. 0° 09' E., beginning new measurement.</p>
	<p>Desc. 45 ft. over NE. slope.</p>
20.60	Wash, 35 lks. wide, 1 ft. deep, drains S. 30° E.; asc. 150 ft. over rocky general SW. slope.
40.08	The cor. of secs. 5, 6, 7 and 8, monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.
	<p>Land, rolling.</p>
	<p>Soil, rocky.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, moderate cacti, greasewood and native grasses.</p>

Dependent Resurvey, Portion of Subdivision, T. 6 S., R. 28 E.

Chains

- From the cor. of secs. 5, 6, 7 and 8, hereinbefore described.
 N. 89° 48' W., bet. secs. 6 and 7.
 Over rolling, mountainous land.
 Desc. 100 ft. over rolling to broken, general SW. slope.
 9.40 Wash, 30 lks. wide, 2 ft. deep, drains S. 20° E.; asc. 150 ft. over rocky NE. slope.
 22.80 Ridge, bears N. 30° W. and S. 30° E.; desc. 140 ft. over SW. slope.
 40.00 The original $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented by a malpais stone, firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground and in a mound of stone, 3 ft. base, to top of post, with brass cap mkd.

T6S R28E

$\frac{1}{4}$ $\frac{S 6}{S 7}$

1958

Deposit original stone monument alongside iron post.

N. 89° 48' W., beginning new measurement.

Desc. 35 ft. over SW. slope.

- 5.60 Wash, 60 lks. wide, 2 ft. deep, drains S. 20° E.; asc. 215 ft. over NE. slope.
 26.45 Spur, sloping S. 25° E.; desc. 75 ft. over broken SW. slope.
 37.48 Intersect W. bdy. of Tp. at the cor. of secs. 1, 6, 7 and 12.

Land, rolling, mountainous.

Soil, rocky.

Timber, none.

Undergrowth, scattered cacti, moderate greasewood and native grasses.

General Description

The general elevation of T. 6 S., R. 28 E. ranges from approximately 3,000 ft. above sea level to approximately 4,500 feet above sea level.

The north and east portions of the township are mountainous. The central, south and west portions are rolling land, and the soil within the township is very shallow. The soil along the banks of the Gila River is of a silty and sandy clay loam nature.

There is little timber in the township; however, there is a heavy growth of mesquite, willow and moderate cottonwood along the Gila River and the Bonita Creek.

BOOK 4616

Township 6 South, Range 28 East

Chains

The Gila River enters the township near the center of section one on the east boundary, flows southwest through the township, leaving in the southwest portion of section 31 on the south boundary of the township.

There are a number of dirt roads in the central and east portions of the township. There is a ranch in section 16, and some stock-grazing throughout the township. This stock-grazing is limited mostly to the central and northwest portions of the township as the rest of the land, being rough and rocky, is not suitable for grazing. There is a sufficient amount of rainfall to produce a moderate growth of native grasses. Some settlers live in sections 29 and 31 where the land is cultivated. There are several deep irrigation wells in section 31 and an earth tank in the central south portion of section 24.

CERTIFICATE OF CADASTRAL ENGINEER

I, Phil D. Smith, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 16th day of November, 1954,
and supplemental special instructions dated 13th day of January, 1956
I have ~~surveyed~~ independently resurveyed a portion of the west boundary and a portion
of the subdivision; and completed the survey of the subdivision of T. 6 S., R.
28 E.

of the Gila And Salt River ~~Salt Lake~~ Meridian, in the State of Utah ~~Arizona~~, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Salt Lake City, Utah
August 3, 1960

Phil D. Smith
Phil D. Smith - Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., FEB 1 1962, 19

The foregoing field notes of the ~~survey of~~ independent resurvey of a portion of the west
boundary and a portion of the subdivision; and completion of the survey of the
subdivision of T. 6 S., R. 28 E., ~~Salt Lake Meridian, Utah~~ Gila And Salt River
Meridian, Arizona

executed by Phil D. Smith, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

Lee Livingston
Cadastral Engineering Staff Officer,
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

Cadastral Engineering Staff Officer