

Antoni 1
30m

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

SURVEY

of the

East Boundary

and a

COMPLETION SURVEY

of the

North Boundary

and the

Subdivisional Lines

of

Township 5 North, Range 6 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leonard W. Murphy, Cadastral Surveyor

Under special instructions dated October 11, 1962, which provided
for the surveys included under Group No. 383, approved October 16, 1962
and assignment instructions dated November 29, 1962

Survey commenced November 29, 1962

Survey completed January 24, 1963

1A

BOOK 4661

INDEX DIAGRAM

Township 5 North, Range 6 East

	1	2	3	4	5
6	5 34 33	4 27 33	3 21 26	2 16 21	1 10 15
7	8 32 32	9 25 31	10 20 25	11 14 19	12 9 14
18	17 30 30	16 24 29	15 19 23	14 13 18	13 8 13
19	20 29 28	21 23 28	22 18 23	23 12 17	24 7 12
30	29 27	28 22	27 16	26 11	25 7 11
31	32	33	34	35	36 6 1

16-56770-1

Township 5 North, Range 6 East, G&SR Meridian, Arizona

18

Chains

The south boundary, the First Standard Parallel North, was surveyed in 1867 by W. H. Pierce and resurveyed in 1919 by S. E. Blout. The west 5 miles were retraced in 1959 by H. G. Parker. The west boundary was surveyed in 1919 by S. E. Blout. Sections 6, 7, 18, 19, and 30 through 35 were surveyed in 1959 by H. G. Parker.

The following field notes are those of the survey of the east boundary and a completion survey of the north boundary and the subdivisional lines of Township 5 North, Range 6 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the Manual of Surveying Instructions, 1947, and the Special Instructions dated October 11, 1962.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude, 33°43'37" N. and Longitude 111°40'55" W. as determined by computation from U.S.C. and G.S. Triangulation Station "Line." The mean magnetic declination was found to be 13°30' E.

Retracement of a Portion of the
First Standard Parallel North in Range 6 East

Retracing the Survey by S. E. Blout in 1919

From the cor. of T. 5 N., Rgs. 6 and 7 E., monumented by an iron post as described in the official record.

S. 89°49' W., on the S. bdy. of sec. 36.

3.31 The closing cor. of T. 4 N., Rgs. 6 and 7 E., monumented by an iron post as described in the official record.

40.02 The Stan. ¼ sec. cor. of sec. 36, monumented by an iron post as described in the official record.

80.03 The Stan. sec. cor. of secs. 35 and 36, monumented by an iron post as described in the official record.

North Boundary of T. 5 N., R. 6 E., Arizona

From the cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township, monumented by an iron post as described in the official record.

Note: The north boundary was established by running east from this point for 400 chains, setting the quarter section and section corners at 40 and 80 chain intervals.

East, bet. secs. 5 and 32.

Over rolling land, through sparse timber and undergrowth.

Chains	
2.10	Head of small wash, 10 lks. wide, course SE.
8.50	Desc. E. slope.
13.00	Wash, 40 lks. wide, drains SSE.; asc. SW. slope.
23.70	Spur, slopes SW.; desc. NE. slope.
28.00	Enter Camp Creek Wash area, thence over level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32. Set the iron post 24 ins. in the ground, cap mkd.
	T6N R6E $\frac{1}{4}$ S 32 $\frac{1}{4}$ S 5 T5N R6E 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of the cor.
54.50	Camp Creek Wash, course irregularly SE.; jeep road in wash.
63.00	Leave wash area; asc. rocky SW. slope.
72.40	Crest of spur, slopes S.; desc. SE. slope.
76.10	Ravine, course S.; asc. W. slope.
78.50	Small spur, slopes S.; desc. SE. slope.
79.90	Ravine, course S.; asc. SW. slope to cor.
80.00	Point for the cor. of secs. 4, 5, 32 and 33. Set the iron post 24 ins. in the ground, cap mkd.
	T6N R6E S32 S33 S 5 S 4 T5N R6E 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Land, rolling. Soil, sandy and gravelly clay loam. Timber, palo verde, mesquite and saguaro. Undergrowth, mesquite and catclaw.
	East, bet. secs. 4 and 33. Over rolling land, through sparse timber and undergrowth. Asc. SW. slope.
2.90	Small spur, slopes S.; desc. S. slope.
9.50	Wash, drains SW.; asc. W. slope.
15.10	Spur, slopes SW.; desc. SE. slope.
19.40	Small wash, drains SW.; asc. W. slope.

Chains	
25.30	Narrow spur, slopes S.; desc. SE. slope.
31.70	Enter wash area.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33.
	Set the iron post 19 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T6N R6E $\frac{1}{4}$ $\frac{S\ 33}{S\ 4}$ T5N R6E 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	Cor. located in wash area not subject to flood.
40.60	Main wash, drains S.
44.00	Leave wash area; asc. NW. slope.
54.30	Ridge, bears irregularly NW. and SE.; desc. NE. slope.
64.70	Wash, drains SE.; asc. W. slope.
76.00	Spur, slopes SE.; desc. NE. slope.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.
	Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T6N R6E $\frac{S33}{S\ 4}$ $\frac{S34}{S\ 3}$ T5N R6E 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Cor. located on NE. rocky slope.
	Land, rolling. Soil, sandy and rocky. Timber, none. Undergrowth, cactus, creosote brush and catclaw.
	East, bet. secs. 3 and 34.
	Over rolling land, through sparse undergrowth, no timber.
	Desc. NE. slope.
5.30	Wash, 15 lks. wide, drains SSE.; asc. small spur.
17.10	Wash, 15 lks. wide, drains irregularly SSE.; asc. SW. slope.
28.10	Spur, slopes SE.; desc. NE. slope.
34.60	Wash, 10 lks. wide, drains SE.; asc. SW. slope.
38.20	Spur, slopes SE.; desc. NE. slope.

BOOK 4661

4

N. Bdy., T. 5 N., R. 6 E., Arizona

4.

Chains	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34.</p> <p>Set the iron post 16 ins. in the ground to bedrock, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T6N R6E $\frac{1}{4} \frac{S \ 34}{S \ 3}$ T5N R6E 1962</p> <p>Cor. located on SE. slope.</p>
41.50	Wash, 10 lks. wide, drains SE.; asc. SW. slope.
55.10	Long spur, slopes SSE.; desc. NE. slope.
75.50	Small wash, drains SSE.; asc. SW. slope.
79.40	Spur, slopes SE.; desc. steep ENE. slope.
80.00	<p>Point for the cor. of secs. 2, 3, 34 and 35.</p> <p>Set the iron post 19 ins. in the ground, small collar of stone to top, cap mkd.</p> <p style="text-align: center;">T6N R6E <u>S34</u> <u>S35</u> S 3 S 2 T5N R6E 1962</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p> <p>Cor. falls on steep ENE. slope.</p> <p>Land, rolling. Soil, sandy and rocky. Timber, none. Undergrowth, cactus and catclaw.</p>
	East, bet. secs. 2 and 35.
	Over rolling and broken land, through sparse undergrowth, no timber.
	Desc. steep ENE. slope.
4.10	Wash, 60 lks. wide, drains SE.; asc. steep SW. slope.
9.30	Spur, slopes irregularly SE.; thence over gently rolling land sloping to SE.
35.50	Small wash, drains SE.
38.90	Small ravine, course SW.; asc. SW. slope to cor.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T6N R6E $\frac{1}{4} \frac{S \ 35}{S \ 2}$ T5N R6E 1962</p>

Chains	
	Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of cor. Cor. falls on SW. slope.
40.20	Small spur, slopes SE.
45.60	Wash, 15 lks. wide, drains SE.
75.50	Wash, 50 lks. wide, drains SSE.
78.00	Small wash, drains SW.; asc. WSW. slope to cor.
80.00	Point for the cor. of secs. 1, 2, 35 and 36. Set the iron post 22 ins. in the ground, cap mkd.
	T6N R6E <u>S35 S36</u> S 2 S 1 T5N R6E 1962
	Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor. Cor. falls on gentle WSW. slope. Land, rolling and broken. Soil, rocky. Timber, none. Undergrowth, cactus and catclaw.
	East, bet. secs. 1 and 36. Over gently rolling land, through scattered timber and undergrowth.
15.80	Wash, 40 lks. wide, drains SW.
16.20	Concrete and rock dam, 90 lks. long, 15 lks. high, 4 lks. wide, across small wash, bears SW., 10 lks. dist.; asc. rocky NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 1 and 36. Set the iron post 24 ins. in the ground, cap mkd.
	T6N R6E ¼ <u>S 36</u> S 1 T5N R6E 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Cor. falls on NW. slope.
40.60	Crest of spur, slopes N.; desc. steep rocky NE. slope.
56.00	Leave steep NE. slope, thence over rolling land.
73.00	Wash, 200 lks. wide, drains irregularly SE.; asc. small spur.
76.00	Small spur, slopes SSW.; desc. SE. slope.
77.70	Small rocky wash, drains S.; asc. broken WNW. slope to cor.
80.00	Point for the cor. of secs. 1, 6, 31 and 36, Ts. 5 and 6 N., Rs. 6 and 7 E.

Chains

Set the iron post 22 ins. in the ground, cap mkd.

T6N
R6E R7E
S36 | S31
S 1 | S 6
T5N
1962

Raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

Cor. falls on rocky NW. slope.

Land, rolling and broken.
Soil, sandy and rocky.
Timber, scattered palo verde.
Undergrowth, cactus.

East Boundary of T. 5 N., R. 6 E., Arizona

From the Standard Corner of secs. 31 and 36, First Standard Parallel North, T. 5 N., Rs. 6 and 7 E., monumented by an iron post as described in the official record.

from which

The closing corner of secs. 1 and 6, T. 4 N., Rs. 6 and 7 E., bears S. 89°49' W., 3.31 chs. dist.

N. 0°02' W., bet. secs. 31 and 36.

Over nearly level land, through medium dense timber and undergrowth.

1.70 Road, unimproved, bears E. and W.

18.40 Wash, 40 lks. wide, drains SSE.

36.10 Wash, 15 lks. wide, drains SE.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set the iron post 24 ins. in the ground, cap mkd.

T5N
R6E R7E
1/4
S36 | S31
1962

44.00 Wash, 15 lks. wide, drains E.

75.00 Road, unimproved, bears E. and W.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set the iron post 21 ins. in the ground, cap mkd.

T5N
R6E R7E
S25 | S30
S36 | S31
1962

Chains	
	<p>No bearing trees available.</p> <p>Land, level. Soil, sandy and gravelly loam clay. Timber, palo verde and mesquite. Undergrowth, catclaw and cactus.</p> <hr/> <p>N. 0°02' W., bet. secs. 25 and 30.</p> <p>Over level land, through dense timber and undergrowth.</p>
35.30	Wash, 30 lks. wide, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E R7E $\frac{1}{4}$ S25 S30 1962
52.00	Wash, 100 lks. wide, drains SE.
55.50	Wash, 100 lks. wide, drains SE.
80.00	Point for the cor. of secs. 19, 24, 25 and 30.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E R7E S24 S19 S25 S30 1962
	<p>Land, level. Soil, sandy, gravelly loam clay. Timber, palo verde and mesquite. Undergrowth; cactus.</p> <hr/> <p>N. 0°02' W., bet. secs. 19 and 24.</p> <p>Over nearly level land, through scattered timber and undergrowth.</p>
.90	Wash, 80 lks. wide, drains E.
7.20	Road, unimproved, bears E. and W.
9.30	S. bank of dry wash, drains E.
17.40	N. bank of same wash.
28.20	Wash, 30 lks. wide, drains SE.
38.60	Wash, 15 lks. wide, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24.
	Set the iron post 18 ins. in the ground to bedrock, mound with stones to top, cap mkd.

Chains	
	T5N R6E R7E $\frac{1}{2}$ S24 S19 1962
43.10	Wash, 50 lks. wide, drains E.
51.10	Wash, 300 lks. wide, drains SE.
68.60	Small ravine, course E.
79.85	Small ravine, course E.
80.00	Point for the cor. of secs. 13, 18, 19 and 24. Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E R7E S13 S18 S24 S19 1962
	Cor. falls on gentle S. slope. Raise mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, nearly level. Soil, sandy and gravelly. Timber, scattered palo verde and mesquite. Undergrowth, cactus and catclaw.
	N. 0°02' W., bet. secs. 13 and 18. Over nearly level land, through medium dense timber and undergrowth. Asc. S. slope.
2.25	Low ridge, slopes E.
19.70	Road, unimproved, bears E. and W.
24.70	Ravine, course SE.
38.60	Low ridge, slopes E.; desc. N. slope.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 13 and 18. Set the iron post 18 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T5N R6E R7E $\frac{1}{2}$ S13 S18 1962
	Cor. falls on N. slope. Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
40.30	Ravine, 25 lks. wide, course E.; asc. S. slope.
41.80	Low spur, bears E. and W.

Chains	
61.80	Wash, 30 lks. wide, drains SE.
68.00	Low spur, bears E. and W.
71.00	Ravine, 40 lks. wide, course SE.
78.80	Desc. N. slope of mesa.
80.00	Point for the cor. of secs. 7, 12, 13 and 18.
	Set the iron post 16 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T5N R6E R7E S12 S 7 S13 S18 1962
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.
	Cor. falls on NE. slope overlooking Camp Creek Wash.
	Land, nearly level. Soil, rocky. Timber, scattered palo verde and mesquite. Undergrowth, creosote brush and cactus.
	N. 0°02' W., bet. secs. 7 and 12.
	Over gently rolling land, through sparse timber and undergrowth.
	Desc. over N. slope.
4.00	S. bank of Camp Creek Wash, drains SE.
6.00	N. bank of Camp Creek Wash; asc. S. slope.
16.60	Over rolling mesa.
39.20	Wash, 35 lks. wide, 4 ft. deep, drains SE.; asc. gentle S. slope.
40.00	Point for the ¼ sec. cor. of secs. 7 and 12.
	Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd.
	T5N R6E R7E ¼ S12 S 7 1962
	Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Cor. located on gentle S. slope.
48.30	Road, unimproved, bears NW. and SE.
58.00	Arizona Public Service power line, bears N. 71° E. and S. 71° W.
60.60	Ravine, 30 lks. wide, course irregularly SE.; asc. S. slope over rocky ledge.
80.00	Point for the cor. of secs. 1, 6, 7 and 12.

Chains

Set the iron post 10 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T5N
R6E R7E
S 1 | S 6
S 12 | S 7
1962

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Cor. falls on gentle NE. slope.

Land, gently rolling, draining to SE.
Soil, gravelly and rocky.
Timber, sparse palo verde.
Undergrowth, creosote brush and cactus.

N. 0°02' W., bet. secs. 1 and 6.

Over gently rolling land, through sparse timber and undergrowth.

Desc. gentle NE. slope.

- 2.10 Ravine, 25 lks. wide, course irregularly SE.; asc. gentle S. slope.
7.50 Ridge, bears E. and W., road on ridge.
14.60 Ravine, 30 lks. wide, course SE.
37.70 Fence, barbed wire, bears N. 65° E. and S. 65° W.
40.00 Point for the ¼ sec. cor. of secs. 1 and 6.

Set the iron post 6 ins. in the ground to bedrock, mound with stone to top, cap mkd.

T5N
R6E R7E
¼
S 1 | S 6
1962

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Cor. falls on ridge bearing E. and W.

- 56.25 Desc. NE. slope.
62.10 Wash, 50 lks. wide, drains irregularly SE.
66.15 Road, unimproved, bears SE. and W.
71.00 Wash, 15 lks. wide, 2 ft. deep, drains SE.; asc. rocky SW. slope.
78.91 The cor. of secs. 1, 6, 31 and 36, Ts. 5 and 6 N., Rs. 6 and 7 E.

Land, gently rolling.
Soil, rocky.
Timber, scattered palo verde and mesquite.
Undergrowth, cactus and creosote brush.

Chains	
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the township.
	S. 89°50' W., bet. secs. 25 and 36.
	Over level land, through medium dense timber and undergrowth.
34.80	Road, graded, bears irregularly E. and W.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.
	Set the iron post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T5N R6E $\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$ 1962 </div>
68.10	Small wash, 20 lks. wide, drains irregularly SE.
79.94	The cor. of secs. 25, 26, 35 and 36, monumented by an iron post, as described in the official record.
	Land, level. Soil, gravelly and sandy clay loam. Timber, palo verde and mesquite. Undergrowth, cactus, creosote brush and saguaro.
	N. 0°03' W., bet. secs. 25 and 26.
	Over nearly level land, through medium dense timber and undergrowth.
3.20	Small wash, 20 lks. wide, drains irregularly E.
8.80	Road, bladed, bears E. and W.
28.00	Wash, 20 lks. wide, 2 ft. deep, drains E.
36.70	Wash, 20 lks. wide, 2 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
	Set the iron post 24 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T5N R6E $\frac{1}{4}$ S26 S25 1962 </div>
46.10	Small wash, 20 lks. wide, drains E.
78.50	Wash, 20 lks. wide, 2 ft. deep, drains SE.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 22 ins. in the ground, cap mkd.
	<div style="text-align: center;"> T5N R6E S23 S24 S26 S25 1962 </div>
	Land, nearly level. Soil, gravelly and sandy clay loam. Timber, palo verde and mesquite. Undergrowth, creosote bush, cactus and catclaw.

Chains	
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the township.
	S. 89°49' W., bet. secs. 24 and 25.
	Over nearly level land, through scattered timber and undergrowth.
	Asc. gentle slope, draining SE. toward the Verde River.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S 24}{S 25}$ 1962
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
	Continue over nearly level land.
42.60	Wash, 10 lks. wide, 1 ft. deep, drains SSE.
79.96	The cor. of secs. 23, 24, 25 and 26.
	Land, nearly level.
	Soil, gravelly and sandy clay loam.
	Timber, scattered palo verde and mesquite.
	Undergrowth, creosote bush, cactus and catclaw.
	<hr/>
	N. 0°03' W., bet. secs. 23 and 24.
	Over nearly level land, through scattered timber and undergrowth.
.85	Road, unimproved, bears S. 80° E. and N. 80° W.
7.60	Wash, 150 lks. wide, 2 ft. deep, drains E.
15.40	Wash, 100 lks. wide, 1 ft. deep, drains SE.
23.30	Wash, 15 lks. wide, 1 ft. deep, drains SE.
38.10	Small wash, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
	Set the iron post 21 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ S23 S24 1962
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
43.50	Wash, 50 lks. wide, 1 ft. deep, drains E.
54.50	Wash, 70 lks. wide, 1 ft. deep, drains SE.
73.50	Wash, 30 lks. wide, 1 ft. deep, drains E.
78.40	Wash, 10 lks. wide, 1 ft. deep, drains NE.
79.60	Wash, 10 lks. wide, 1 ft. deep, drains SE.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.

Subdivision, T. 5 N., R. 6 E., Arizona

Chains

Set the iron post 22 ins. in the ground, cap mkd.

T5N R6E
S14|S13
S23|S24
1962

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Corner falls on gentle S. slope.

Land, nearly level.

Soil, gravelly and sandy clay loam.

Timber, scattered palo verde and mesquite.

Undergrowth, cactus, yucca and ocotillo.

From the cor. of secs. 13, 18, 19 and 24.

S. 89°49' W., bet. secs. 13 and 24.

Over nearly level land, through scattered timber and undergrowth.

.30 Wash, 10 lks. wide, 1 ft. deep, drains SE.

13.00 Wash, 15 lks. wide, 1 ft. deep drains S.

35.80 Enter wash area, drains to SE.

39.98 Point for the ¼ sec. cor. of secs. 13 and 24.

Set the iron post 24 ins. in the ground, cap mkd.

T5N R6E
¼ S 13
S 24
1962

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

Corner falls in wash area not subject to flood.

40.80 Leave wash area.

69.00 Wash, 10 lks. wide, 2 ft. deep, drains SSE.

79.96 The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, cactus, catclaw and ocotillo.

N. 0°03' W., bet. secs. 13 and 14.

Over gently rolling land, through scattered timber and undergrowth.

35.50 Wash, 40 lks. wide, 1 ft. deep, drains SE.

40.00 Point for the ¼ sec. cor. of secs. 13 and 14.

Set the iron post 20 ins. in the ground, cap mkd.

T5N R6E
¼
S14|S13
1962

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Chains	
	Cor. falls on gentle SW. slope.
44.70	Wash, 10 lks. wide, 2 ft. deep, drains SE.
49.35	Road, unimproved, bears E. and W.
74.70	Wash, 10 lks. wide, 1 ft. deep, drains ESE.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.
	Set the iron post 22 ins. in the ground, cap mkd.
	T5N R6E S11 S12 S14 S13 1962
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.
	Land, gently rolling.
	Soil, gravelly and rocky.
	Timber, scattered palo verde and mesquite.
	Undergrowth, cactus, creosote bush and yucca.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the township.
	S. 89°49' W., bet. secs. 12 and 13.
	Over gently rolling land, through scattered timber and undergrowth.
11.80	Wash, 40 lks. wide, 1 ft. deep, drains SE.
35.30	Wash, 10 lks. wide, 2 ft. deep, drains SE.
37.20	Small spur, slopes irregularly SE.
40.00	Point for the ¼ sec. cor. of secs. 12 and 13.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E ¼ S12 S13 1962
	Raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	Cor. falls on SW. slope.
40.30	Wash, 10 lks. wide, 2 ft. deep, drains SE.
75.20	Wash, 100 lks. wide, 1 ft. deep, drains SSE.
80.00	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling.
	Soil, gravelly and rocky.
	Timber, scattered palo verde.
	Undergrowth, cactus, creosote bush and catclaw.
	N. 0°03' W., bet. secs. 11 and 12.
	Over rolling land, through sparse timber and undergrowth.
9.60	Wash, 150 lks. wide, 1 ft. deep, drains SE.

Chains	
27.30	Road, graded, serves as access to power line under construction at time of survey; bears generally NE. and SW.
28.40	Power line, bears NE. and SW.
30.50	Power line, bears NE. and SW.
31.50	Service road for power line, parallels power line.
38.50	Wash, 60 lks. wide, 2 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set the iron post 20 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ S11 S12 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.
	Cor. falls on rocky S. slope.
48.70	S. rim of Camp Creek Wash, projects ESE.; desc. NE. slope.
66.70	Camp Creek Wash, used as road, drains SE.
68.00	Asc. steep SW. sandstone slope.
73.00	Leave sandstone cliff, thence over rolling mesa.
80.00	Point for the cor. of secs. 1, 2, 11, and 12.
	Set the iron post 20 ins. in the ground, cap mkd.
	T5N R6E <u>S 2 S 1</u> S11 S12 1962
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.
	Cor. falls on S. slope.
	Land, rolling and broken. Soil, sandy and rocky. Timber, sparse palo verde. Undergrowth, cactus and catclaw.
	From the cor. of secs. 1, 6, 7, and 12, on the east boundary of the township.
	S. $89^{\circ}50'$ W., bet. secs. 1 and 12.
	Over gently rolling land, through sparse timber and undergrowth.
31.00	Fence, barbed wire, bears N. 10° E. and S. 10° W.
32.60	Road, unimproved, bears irregularly S. and NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ S 1 S12 1962

Chains	
	Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of cor. Cor. falls on gentle W. slope.
52.40	Wash, 60 lks. wide, 3 ft. deep, drains S.
71.20	Road, unimproved, bears irregularly SSE. and NNW.
78.90	Road, unimproved, bears S. and NW.; leads to powerline.
80.00	The cor. of secs. 1, 2, 11 and 12. Land, gently rolling. Soil, sandy and gravelly. Timber, scattered palo verde. Undergrowth, cactus and catclaw.
	N. 0°03' W., bet. secs. 1 and 2. Over gently rolling land, through sparse timber and undergrowth.
1.15	Road, unimproved, bears SE. and NW.; leads to powerline.
29.70	Road, unimproved, bears ESE. and NW.
40.00	Point for the ¼ sec. cor. of secs. 1 and 2. Set the iron post 4 ins. in the ground to bedrock, mound with earth and stone to top, cap mkd. T5N R6E ¼ S2 S1 1962
	Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor. Cor. falls on E. slope.
45.60	Road, unimproved, bears irregularly E. and W.
67.00	Wash, 50 lks. wide, 2 ft. deep, drains SE.
79.15	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the township. Land, gently rolling. Soil, sandy and rocky. Timber, sparse palo verde and mesquite. Undergrowth, cactus, yucca and catclaw.
	From the cor. of secs. 26, 27, 34 and 35, monumented by an iron post as described in the official record. N. 0°03' W., bet. secs. 26 and 27. Over nearly level land, through dense timber and undergrowth.
4.30	Road, graded, bears irregularly E. and W.; leads to Verde River and Ft. McDowell.
21.50	Wash, 50 lks. wide, 1 ft. deep, drains E.
34.30	Wash, 20 lks. wide, 1 ft. deep, drains E.
40.00	Point for the ¼ sec. cor. of secs. 26 and 27.

Chains	
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ S27 S26 1962
	No suitable bearing trees available.
64.50	Wash, 15 lks. wide, 1 ft. deep, drains E.
79.30	Road, unimproved, bears irregularly E. and W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E S22 S23 S27 S26 1962
	From which
	Anacacia, 6 ins. diam., bears S. 58° W., 72 lks. dist., mkd. S 27 BT.
	A palo verde, 6 ins. diam., bears N. 2° W., 73 lks. dist., mkd. S 22 BT.
	Land, level.
	Soil, sandy and gravelly clay loam.
	Timber, palo verde, joshua and mesquite.
	Undergrowth, cactus, yucca and sagebrush.
	<hr/>
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°50' W., bet. secs. 23 and 26.
	Over level land, through dense timber and undergrowth.
20.00	Road, unimproved, bears irregularly E. and W.
34.20	Same road, bears irregularly E. and W.
38.20	Same road, bears irregularly E. and W.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	Set the iron post 22 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ 1962
	Cor. located 40 lks. N. of road bearing irregularly E. and W.
64.00	Road, unimproved, bears irregularly E. and W.
69.70	Same road, same general bearing.
75.30	Same road, same general bearing.
78.70	Same road as described previously.
79.94	The cor. of secs. 22, 23, 26 and 27.

Chains

Land, nearly level.
Soil, gravelly and sandy clay loam.
Timber, palo verde, joshua and mesquite.
Undergrowth, cactus, sage brush and ocotillo.

N. 0°03' W., bet. secs. 22 and 23.

Over nearly level land, through medium dense timber and undergrowth.

24.00 Wash, 250 lks. wide, 1 ft. deep, drains ESE.

36.00 Wash, 30 lks. wide, 1 ft. deep, drains ESE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

Set the iron post 24 ins. in the ground, cap mkd.

T5N R6E
 $\frac{1}{4}$
S22|S23
1962

Cor. falls in sandy wash area not subject to flood.

73.30 Wash, 40 lks. wide, 1 ft. deep, drains ESE.

79.40 Wash, 150 lks. wide, 1 ft. deep, drains ESE.

80.00 Point for the cor. of secs. 14, 15, 22 and 23.

Set the iron post 24 ins. in the ground, cap mkd.

T5N R6E
S15|S14
S22|S23
1962

from which

A palo verde, 6 ins. diam., bears S. 64° E., 93 lks. dist.,
mkd. S 23 BT.

A palo verde, 6 ins. diam., bears S. 67° W., 43 lks. dist.,
mkd. S 22 BT.

Land, nearly level.
Soil, gravelly and sandy clay loam.
Timber, palo verde and mesquite.
Undergrowth, catclaw, black brush and cactus.

From the cor. of secs. 13, 14, 23 and 24.

S. 89°50' W., bet. sec. 14 and 23.

Over nearly level land, through medium dense timber and undergrowth.

39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set the iron post 24 ins. in the ground, cap mkd.

T5N R6E
 $\frac{1}{4}$ $\frac{S 14}{S 23}$
1962

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Chains	
65.00	Wash, 30 lks. wide, 2 ft. deep, drains SE.
79.94	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, nearly level. Soil, sandy. Timber, palo verde and mesquite. Undergrowth, cactus.</p>
11.60	<p>N. 0°03' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land, through medium dense timber and undergrowth.</p>
40.00	Wash, 30 lks. wide, 1 ft. deep, drains ESE.
48.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{1}{4}$ S15 S14 1962</p>
48.00	<p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.</p> <p>Cor. falls on gentle NE. slope.</p>
76.30	Wash, 150 lks. wide, 1 ft. deep, drains SE.
78.30	Wash, 10 lks. wide, 1 ft. deep, drains SE.
80.00	Powerline, bears S. 70°50' W. and N. 70°50' E.
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E S10 S11 S15 S14 1962</p>
4.90	<p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p> <p>Cor. falls on small spur, slopes SE, under powerline bearing S. 70°50' W. and N. 70°50' E.</p> <p>Land, gently rolling. Soil, sandy and rocky. Timber, palo verde and mesquite. Undergrowth, cactus.</p>
39.00	<p>From the cor. of secs. 11, 12, 13 and 14.</p>
39.98	<p>S. 89°50' W., bet. secs. 11 and 14.</p>
4.90	<p>Over gently rolling land, through sparse timber and undergrowth.</p>
39.00	Wash, 20 lks. wide, 1 ft. deep, drains SE.
39.00	Wash, 10 lks. wide, 1 ft. deep, drains SE.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Chains	
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{1}{4}$ $\frac{S\ 11}{S\ 14}$ 1962</p> <p>Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of cor. Cor. falls on gentle NE. slope.</p>
49.20	Wash, 20 lks. wide, 2 ft. deep, drains SE.
54.40	Road, unimproved, bears NW. and SE.
74.60	Powerline, bears N. 70°50' E. and S. 70°50' W.
79.96	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, gently rolling. Soil, gravelly and rocky. Timber, scattered palo verde and mesquite. Undergrowth, cactus, yucca and black brush.</p> <hr/> <p>N. 0°03' W., bet. secs. 10 and 11.</p> <p>Over rolling land, through sparse timber and undergrowth.</p>
1.60	Powerline road, bladed, bears irregularly N. 70° E., and S. 70° W.
18.10	Road, unimproved, bears N. 80° W. and S. 80° E.
37.40	Wash, 10 lks. wide, 1 ft. deep, drains E.
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{1}{4}$ S10 S11 1962</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor. Cor. falls on crest of low spur, slopes S. 80° E.</p>
42.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 80° E.
78.60	Wash, 10 lks. wide, 1 ft. deep, drains E.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{S\ 3}{S10}$ $\frac{S\ 2}{S11}$ 1962</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, gravelly and rocky. Timber, scattered palo verde and mesquite. Undergrowth, cactus, ocotillo and catclaw.</p> <hr/>

Chains	
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89°51' W., bet. secs. 2 and 11.
	Over rolling and broken land, through sparse timber and undergrowth.
2.30	Leave rolling mesa; desc. over rocky SW. slope.
6.00	End desc., thence along Camp Creek Wash.
6.90	Camp Creek Wash, used as jeep road.
20.00	Camp Creek Wash, drains irregularly E. to SE.
23.50	Camp Creek Wash, course E.
29.00	Camp Creek Wash.
29.50	Leave Camp Creek Wash area; asc. over steep, sandstone N. slope.
31.40	Mesa top, thence over gently rolling land.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	Set the iron post 20 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S \ 2}{S \ 11}$ 1962
	Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
49.90	Wash, 10 lks. wide, 1 ft. deep, drains SE.
79.98	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling and broken. Soil, sandy and rocky. Timber, sparse palo verde and joshua. Undergrowth, cactus.
	N. 0°05' W., bet. secs. 2 and 3.
	Over rolling and broken land, through sparse timber and undergrowth.
2.20	Leave mesa top, begin desc. over broken, rocky N. slope.
10.50	Camp Creek Wash, course irregularly SE.
14.80	Leave Camp Creek Wash area; asc. broken S. slope.
17.70	N. rim of wash; thence over series of ridges sloping to SW.
22.70	Ravine, 15 lks. wide, course irregularly SW.
39.40	Same ravine, 20 lks. wide, 20 ft. deep, drains S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set a brass tablet, 3 $\frac{1}{2}$ ins. diam., 3 $\frac{1}{2}$ ins. stem, in a drilled hole, surrounded by concrete, with brass cap mkd.

Chains	
	<p style="text-align: center;">T5N R6E $\frac{1}{4}$ S 3 S 2 1962</p> <p>Cor. falls on steep, rocky sandstone S. slope. Asc. S. slope.</p>
68.30	Thence over mesa.
77.00	Desc. along gentle NE. slope.
79.31	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the township.</p> <p>Land, rolling and broken. Soil, rocky. Timber, scattered mesquite. Undergrowth, cactus and catclaw.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, monumented by an iron post as described in the official record.</p> <p>N. 0°04' W., bet. secs. 27 and 28.</p> <p>Over level land, through medium dense timber and undergrowth.</p>
6.30	Wash, 30 lks. wide, 1 ft. deep, drains E.
14.40	Road, graded, leads to Verde River and Ft. McDowell.
17.60	Wash, 25 lks. wide, 2 ft. deep, drains E.
38.40	Wash, 50 lks. wide, 2 ft. deep, drains E.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{1}{4}$ S28 S27 1962</p>
51.50	Wash, 30 lks. wide, 2 ft. deep, drains SE.
70.80	Wash, 20 lks. wide, 2 ft. deep, drains E.
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E <u>S21 S22</u> <u>S28 S27</u> 1962</p> <p>Land, level. Soil, sandy and clay loam. Timber, palo verde and mesquite. Undergrowth, cactus.</p> <hr/>

Chains	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°50' W., bet. secs. 22 and 27.</p> <p>Over level land, through medium dense timber and undergrowth.</p>
33.70	Road, unimproved, bears irregularly NW. and SE.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$ 1962</p>
80.12	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, level. Soil, gravelly and sandy clay loam. Timber, palo verde and mesquite. Undergrowth, cactus, yucca, ocotillo, catclaw and creosote bush.</p>
	<p>N. 0°04' W., bet. secs. 21 and 22.</p> <p>Over level land, through medium dense timber and undergrowth.</p>
13.80	Wash, 30 lks. wide, 2 ft. deep, drains E.
21.00	Road, unimproved, bears NW. and SE.
27.40	Wash, 40 lks. wide, 2 ft. deep, drains SE.
34.80	Wash, 60 lks. wide, 2 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{1}{4}$ $\frac{S21}{S22}$ 1962</p>
72.70	Wash, 30 lks. wide, 1 ft. deep, drains SE.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E $\frac{S16}{S21}$ $\frac{S15}{S22}$ 1962</p>
	<p>Land, level. Soil, sandy and gravelly. Timber, palo verde, mesquite and ironwood. Undergrowth, creosote bush and cactus.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°48' W., bet. secs. 15 and 22.</p> <p>Over nearly level land, through medium dense undergrowth.</p>

Chains	
1.05	Small wash, drains S. 30° E.
11.70	Wash, 60 lks. wide, 2 ft. deep, drains S. 45° E.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S\ 15}{S\ 22}$ 1962
41.50	Road, unimproved, bears S. and N. for 2 chains leading to stock watering tank known locally as the Buckhorn Tank of the Box Bar Ranch.
79.80	Wash, 30 lks. wide, 1 ft. deep, drains S. 65° E.
80.16	The cor. of secs. 15, 16, 21 and 22.
	Land, nearly level. Soil, gravelly clay loam. Timber, palo verde, mesquite and joshua. Undergrowth, cactus and catclaw.
	N. 0°04' W., bet. secs. 15 and 16.
	Over nearly level land, through medium dense undergrowth and timber.
.60	Small wash, drains S. 45° E.
19.40	Wash, 30 lks. wide, 2 ft. deep, drains S. 30° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.
	Set the iron post 22 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ S16 S15 1963
44.30	Wash, 3 ft. deep, 70 lks. wide, drains S. 30° E.
47.80	Arizona Public Service powerline, bears N. 69°30' E. and S. 69°30' W.
48.25	Maintenance road for powerline, unimproved, same bearing as above.
50.15	Arizona Public Service powerline, bears N. 69°30' E. and S. 69°30' W.
55.30	Wash, 70 lks. wide, 1 ft. deep, drains S. 35° E.
79.70	Small wash, drains S. 30° E.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set the iron post 22 ins. in the ground, cap mkd.
	T5N R6E S 9 S10 S16 S15 1963

Chains	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, palo verde and mesquite. Undergrowth, cactus, black brush and catclaw.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°48' W., bet. secs. 10 and 15.</p> <p>Over level land, through scattered timber and undergrowth.</p>
3.70	Maintenance road for powerline, bears N. 6° E. and S. 6° W.
10.60	Wash, 70 lks. wide, 2 ft. deep, drains S. 7° E.
27.90	Wash, 120 lks. wide, 1 ft. deep, drains S. 20° E.
40.09	Point for the ¼ sec. cor. of secs. 10 and 15.
	<p>Set the iron post 20 ins. in the ground, collar of stone to top, cap mkd.</p> <p style="text-align: center;">T5N R6E ¼ $\frac{S\ 10}{S\ 15}$ 1962</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
44.30	Wash, 30 lks. wide, 2 ft. deep, drains S. 73° E.
53.30	Wash, 100 lks. wide, 3 ft. deep, drains S. 25° E.
80.18	The cor. of secs. 9, 10, 15 and 16.
	<p>Land, level. Soil, sandy and gravelly clay loam. Timber, scattered palo verde and mesquite. Undergrowth, cactus and black brush.</p> <hr/> <p>N. 0°04' W., bet. secs. 9 and 10.</p> <p>Over rolling mesa, through sparse timber and undergrowth.</p>
11.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° E.
30.60	Wash, 30 lks. wide, 2 ft. deep, drains S. 40° E.
40.00	Point for the ¼ sec. cor. of secs. 9 and 10.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T5N R6E ¼ S 9 S 10 1963</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. falls on level land.</p>
42.00	Fence, barbed wire, bears generally E. and W.

Chains	
43.40	Leave mesa; desc. over N. slope.
55.50	Thence over level bottom land.
67.45	Road, unimproved, bears N. 35° W. and S. 35° E. for approximately 4 chs. to a stock watering reservoir.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{S}{S} \frac{4}{9} \frac{S}{S} \frac{3}{10}$ 1963
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of cor.
	No suitable bearing trees available; cor. falls 250 lks. S. of Camp Creek Wash.
	Land, rolling. Soil, sandy and gravelly. Timber, scattered palo verde and mesquite. Undergrowth, catclaw and cactus.
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89°47' W., bet. secs. 3 and 10.
	Over rolling and broken land, through patches of undergrowth.
	Over nearly level mesa.
7.70	Desc. steep NW. slope.
30.00	S. bank of Camp Creek Wash.
30.30	Middle of Camp Creek Wash, drains E.; used as jeep road.
34.30	N. bank of Camp Creek Wash, asc. along broken S. slope.
40.13	Point for the ¼ sec. cor. of secs. 3 and 10.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4} \frac{S}{S} \frac{3}{10}$ 1963
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
	Cor. falls on gentle SE. slope in dense undergrowth.
62.00	N. bank of Camp Creek Wash.
68.60	Middle of Camp Creek Wash, drains irregularly E., used as jeep road.
75.10	S. bank of Camp Creek Wash; asc. gentle slope to cor.
80.26	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Soil, sandy and gravelly. Timber, scattered palo verde and mesquite along Camp Creek Wash. Undergrowth, dense catclaw along Camp Creek Wash.

Chains	
	N. 0°05' E., bet. secs. 3 and 4. Over mountainous land, through sparse undergrowth and timber.
2.50	S. bank of Camp Creek Wash.
4.50	N. bank of Camp Creek Wash, used as jeep road; asc. broken S. slope.
33.25	Spur, bears E. and W.; desc. along steep E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set the iron post 24 ins. in the ground, cap mkd. T5N R6E $\frac{1}{4}$ S4 S3 1963
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
42.80	Ravine, 25 lks. wide, 1 ft. deep, course S. 30° E.; asc. along broken E. slope.
53.25	Wash, 125 lks. wide, 1 ft. deep, drains S. 25° E.; asc. S. slope.
58.70	Ridge, bears N. 30° W. and S. 30° E., desc. along E. slope.
61.25	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° E., asc. SW. slope.
74.50	Ridge, bears N. 45° W. and S. 45° E.; desc. along NE. slope.
79.67	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township. Land, mountainous. Soil, clay with rock. Timber, palo verde and mesquite. Undergrowth, catclaw, yucca and ocotillo.
	From the cor. of secs. 28, 29, 32 and 33, monumented by an iron post as described in the official record.
	N. 0°04' W., bet. secs. 28 and 29. Over level land, through dense timber.
7.70	Road, graded, leads to Verde River and Fort McDowell, bears E. and W.
25.90	Wash, 30 lks. wide, 1 ft. deep, drains E.
38.90	Wash, 30 lks. wide, 2 ft. deep, drains S. 30° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29. Set the iron post 18 ins. in the ground to bedrock, collar of stone to top, cap mkd. T5N R6E $\frac{1}{4}$ S29 S28 1963
46.50	Stock watering reservoir, bears W., about 3 chs. dist.
71.75	Fence, barbed wire, bears S. 70° E. and N. 70° W.

28

Chains	
75.50	Wash, 20 lks. wide, 1 ft deep, drains S. 28° E.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E <u>S20 S21</u> <u>S29 S28</u> 1963
	Land, level. Soil, sandy loam. Timber, palo verde and mesquite. Undergrowth, black brush, catclaw, yucca and cactus.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°51' W., bet. secs. 21 and 28.
	Over nearly level land, through dense timber.
28.30	Wash, 30 lks. wide, 3 ft. deep, drains S. 70° E.
30.70	Road, unimproved, bears generally N. and S.
31.80	Fence, barbed wire, bears N. and S.
39.97	Point for the ¼ sec. cor. of secs. 21 and 28.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E ¼ <u>S 21</u> <u>S 28</u> 1963
54.10	Wash, 100 lks. wide, 1 ft. deep, drains S. 32° E.
61.50	Road, unimproved, bears generally N. and S.
65.40	Wash, 30 lks. wide, 4 ft. deep, drains S. 45° E.
79.94	The cor. of secs. 20, 21, 28 and 29.
	Land, nearly level. Soil, sandy and gravelly. Timber, palo verde and mesquite. Undergrowth, black brush, catclaw and cactus.
	S. 89°48' W., bet. secs. 20 and 29.
	Over level land, through scattered timber and undergrowth.
26.40	Fence, barbed wire, bears N. 70° W. and S. 70° E.
30.40	Wash, 15 lks. wide, 2 ft. deep, drains S. 40° E.
40.06	Point for the ¼ sec. cor. of secs. 20 and 29.
	Set the iron post 20 ins. in the ground, cap mkd.
	T5N R6E ¼ <u>S 20</u> <u>S 29</u> 1963

Chains	
	No bearing trees available; cor. falls on level land.
63.50	Small wash, 30 lks. wide, drains S. 70° E.
80.12	The cor. of secs. 19, 20, 29 and 30, monumented by an iron post as described in the official record.
	Land, level. Soil, sandy. Timber, palo verde and mesquite. Undergrowth, black brush, catclaw, yucca and cactus.
<hr/>	
	From the cor. of secs. 20, 21, 28 and 29.
	N. 0°04' W., bet. secs. 20 and 21.
	Over level land, through scattered timber and undergrowth.
3.80	Wash, 20 lks. wide, 4 ft. deep, drains E.
24.90	Road, unimproved, bears N. 60° W. and S. 60° E.
36.80	Wash, 40 lks. wide, 2 ft. deep, drains S. 45° E.
40.00	Point for the ¼ sec. cor. of secs. 20 and 21.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E ¼ S20 S21 1963
41.20	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° E.
55.70	Wash, 150 lks. wide, 4 ft. deep, drains S. 70° E.
79.70	Wash, 10 lks. wide, 1 ft. deep, drains S. 65° E.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E S17 S16 S20 S21 1963
	Land, nearly level. Soil, sandy and gravelly. Timber, palo verde and mesquite. Undergrowth, black brush and catclaw.
<hr/>	
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°52' W., bet. secs. 16 and 21.
	Over nearly level land, through scattered timber and undergrowth.
6.30	Road, unimproved, bears S. and N. 50° W. for 5 chs., thence W.
19.50	Wash, 25 lks. wide, 1 ft. deep, drains S. 80° E.
29.70	Road, unimproved, bears generally N. and S.
30.00	Fence, barbed wire, bears N. and S.

Chains	
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$ 1963
42.70	Small wash, drains S. 30° E.
66.50	Wash, 30 lks. wide, 3 ft. deep, drains S. 45° E.
79.92	The cor. of secs. 16, 17, 20 and 21.
	Land, nearly level. Soil, sandy and gravelly. Timber, dense palo verde and mesquite. Undergrowth, cactus, black brush and catclaw.
	S. 89°48' W., bet. secs. 17 and 20.
	Over nearly level land, through medium dense timber and undergrowth.
.50	Small wash, drains S. 65° E.
31.50	Wash, 70 lks. wide, 2 ft. deep, drains S. 30° E.
37.60	Wash, 60 lks. wide, 2 ft. deep, drains S. 40° E
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S\ 17}{S\ 20}$ 1963
51.00	Arizona Public Service powerline, bears N. 70° E. and S. 70° W.
67.40	Access road for powerline, bladed, bears same as above.
80.02	The cor. of secs. 17, 18, 19 and 20, monumented by an iron post as described in the official record.
	Land, nearly level. Soil, sandy and gravelly clay loam. Timber, palo verde and mesquite. Undergrowth, saguaro, yucca, Spanish bayonet and cholla.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 0°04' W., bet. secs. 16 and 17.
	Over nearly level land, through scattered timber and undergrowth.
7.00	Wash, 40 lks. wide, 1 ft. deep, drains S. 60° E.
17.60	Powerline, bears N. 70° E. and S. 70° W.
17.80	Access road to powerline, bears N. 70° E. and S. 70° W.

Chains	
19.60	Powerline, bears N. 70° E. and S. 70° W.
28.90	Wash, 30 lks. wide, 2 ft. deep, drains S. 58° E.
40.00	Point for the ¼ sec. cor. of secs. 16 and 17.
	Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4}$ S17 S16 1963
43.20	Wash, 30 lks. wide, 3 ft. deep, drains S. 70° E.
70.20	Wash, 30 lks. wide, 1 ft. deep, drains S. 50° E.
77.90	Fence, barbed wire, bears E. and W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set the iron post 22 ins. in the ground, cap mkd.
	T5N R6E S 8 S 9 S17 S16 1963
	Land, nearly level. Soil, sandy and gravelly clay loam. Timber, palo verde and mesquite. Undergrowth, black brush, catclaw, saguaro and cholla.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°49' W., bet. secs. 9 and 16.
	Over level land, through medium dense timber and undergrowth.
20.70	Wash, 40 lks. wide, 1 ft. deep, drains S. 30° E.
29.00	Fence, barbed wire, bears N. and S.
35.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 30° E.
39.93	Point for the ¼ sec. cor. of secs. 9 and 16.
	Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.
	T5N R6E $\frac{1}{4}$ $\frac{S 9}{S 16}$ 1963
40.40	Wash, 40 lks. wide, 3 ft. deep, drains S. 30° E.
69.60	Wash, 30 lks. wide, 3 ft. deep, drains S. 30° E.
79.86	The cor. of secs. 8, 9, 16 and 17.
	Land, level. Soil, sandy and gravelly clay loam. Timber, palo verde and mesquite. Undergrowth, cactus and catclaw.

Chains

S. 89°45' W., bet. secs. 8 and 17.

Over level land, through scattered timber and undergrowth.

34.70 Wash, 30 lks. wide, 3 ft. deep, drains S. 30° E.

39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.

Set the iron post 18 ins. in the ground, collar of stone to top, cap mkd.

T5N R6E
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{8}{17}$
 1963

Raise a small mound of stone to N. of cor.

50.40 Wash, 20 lks. wide, 1 ft. deep, drains S. 45° E.

59.90 Wash, 20 lks. wide, 2 ft. deep, drains S. 45° E.

79.94 The cor. of secs. 7, 8, 17 and 18, monumented by an iron post as described in the official record.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, cactus, black brush and catclaw.

From the cor. of secs. 8, 9, 16 and 17.

N. 0°04' W., bet. secs. 8 and 9.

Over broken land, through sparse timber and undergrowth.

25.10 Wash, 50 lks. wide, 1 ft. deep, drains S. 80° E.

38.70 Wash, 70 lks. wide, 1 ft. deep, drains S. 60° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set the iron post 24 ins. in the ground, cap mkd.

T5N R6E
 $\frac{1}{4}$
 S8|S9
 1963

Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.

53.90 Leave nearly level mesa top; desc. steep N. slope.

58.20 Thence over level wash area.

66.30 Asc. steep S. slope.

69.75 Crest of ridge, bears E. and W.; desc. N. slope.

75.55 Ravine, course N. 80° E.; asc. SE. slope.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set the iron post 22 ins. in the ground, collar of rock to top, cap mkd.

Chains	
	T5N R6E $\frac{S5}{S8} \frac{S4}{S9}$ 1963
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor. Cor. falls on E. slope. Land, broken. Soil, rocky. Timber, scattered palo verde. Undergrowth, catclaw and cactus.
	From the cor. of secs. 3, 4, 9 and 10. S. $89^{\circ}50'$ W., bet. secs. 4 and 9. Over gently rolling land, through sparse timber and undergrowth.
6.40	S. bank of Camp Creek Wash, bears N. 75° E. and S. 75° W.; used as jeep road.
11.00	N. bank of Camp Creek Wash, bears N. 75° E. and S. 75° W.
32.40	Asc. along S. slope of ridge.
34.10	Spur, slopes S.
39.40	Spur, slopes S.; desc. along S. slope.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9. Set the iron post 24 ins. in the ground, cap mkd.
	T5N R6E $\frac{1}{4} \frac{S 4}{S 9}$ 1963
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, N. of cor. Cor. falls on S. slope.
40.95	Low spur, slopes S.; desc. W. slope.
45.00	N. bank of Camp Creek Wash, bears S. 15° E.; jeep road in center.
49.40	S. bank of Camp Creek Wash, bears S. 15° E.; thence over level bottom land.
75.70	Asc. steep E. slope.
79.88	The cor. of secs. 4, 5, 8 and 9. Land, gently rolling. Soil, sandy and gravelly. Timber, mesquite and palo verde. Undergrowth, mesquite brush, catclaw and cactus.
	S. $89^{\circ}46'$ W., bet. secs. 5 and 8. Over rolling hills, through scattered timber and undergrowth. Asc. steep E. slope.

Chains	
1.90	Top of spur, bears E. and W.; thence along crest of spur.
12.60	Desc. SW. slope.
21.90	Enter area of several small washes.
30.80	Leave wash area; asc. E. slope.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8. Set the iron post 12 ins. in the ground to bedrock, mound with stone to top, cap mkd. <div style="text-align: center;"> T5N R6E $\frac{1}{4}$ $\frac{S\ 5}{S\ 8}$ 1963 </div> Cor. falls on E. slope.
46.40	Ravine, course SE.; thence over nearly level land.
79.88	The cor. of secs. 5, 6, 7 and 8, monumented by an iron post as described in the official record. Land, rolling. Soil, gravelly clay loam. Timber, sparse palo verde and mesquite. Undergrowth, black brush, ocotillo, yucca and catclaw.
	From the cor. of secs. 4, 5, 8 and 9. N. 0°06' E., bet. secs. 4 and 5. Over rolling and broken land. Desc. along E. slope.
3.80	Thence over level land, through dense undergrowth.
7.00	Wash, 70 lks. wide, 2 ft. deep, drains E.
16.00	Asc. S. slope.
16.90	Small spur, slopes SE.; thence over series of small rolling hills.
37.40	Desc. steep N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5. Set the iron post 24 ins. in the ground, cap mkd. <div style="text-align: center;"> T5N R6E $\frac{1}{4}$ S5 S4 1963 </div> Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of cor. Cor. falls on steep N. slope.
41.30	S. bank of Camp Creek Wash, bears S. 45° E. and N. 45° W.; jeep road in center.

Chains	
51.60	N. bank of Camp Creek Wash, same general bearing; asc. gentle S. slope.
70.50	Wash, 120 lks. wide, 2 ft. deep, drains S. 45° W.
79.73	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the township.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, scattered mesquite and palo verde.

Undergrowth, catclaw, ocotillo, yucca and cactus.

General Description

The area included in this survey lies within the Tonto National Forest. The west and south boundaries of the township constitute portions of the west and south boundaries of the National Forest.

The area covered by this survey is generally flat or gently rolling, and slopes eastward at the rate of 100 to 200 feet per mile, towards the Verde River, which flows southward through Township 5 North, Range 7 East. Elevations over the area vary from about 1,750 feet above sea level along the east boundary of section 36 to about 2,700 feet above sea level at the northwest corner of section 6.

The entire area is forested with a more or less dense growth of non-commercial desert trees such as palo verde, mesquite and acacia. There is also a general cover of undergrowth, which consists of desert plants such as cactus, desert sage, yucca, sotol, ocotillo, and century plant. Also many members of the chaparral family, including scrub mesquite, palo verde, catclaw, crucifixion thorn and creosote bush.

There are no settlers living within the area and the only improvements consist of considerable fencing to control stock grazing distribution. During the progress of this survey, Arizona Public Service Company has been erecting a powerline network across the northern portion of the township, entering in section 19 and leaving the township in section 12. There are numerous roads throughout the township, mostly unimproved. The area is principally used for stock grazing, with watershed protection and erosion control by the U. S. Forest Service.

37

CERTIFICATE OF CADASTRAL SURVEYOR

I, Leonard Wesley Murphy, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11 day of October, 19 62.

I have surveyed the east boundary and completion survey of the north boundary and subdivisional lines of Township 5 North, Range 6 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

January 28, 1963
(Date)

Leonard W. Murphy
Leonard W. Murphy (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., MAY 24 1963, 1963

The foregoing field notes of the survey of Township 5 North, Range 6 East G & SR Meridian Arizona

executed by Leonard W. Murphy, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

[Signature]
(Cadastral Engineering Staff Officer)
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Cadastral Engineering Staff Officer)