### FIELD NOTES

	DEPENDENT	RESURVEY			
	Sections	3 and 4			
					·
	SURV	/EY	****		
	Subdivi	isions			
	Sections	3 and 4			
	Township 22 South	n, Range	22 East		
and the second s					
					····
Of the	Gila and S	alt River	<u> </u>		Meridian,
In the State of	Ariz	ona			·
	FXFCI	JTED BY	<i>(</i>		
			•		
Paul	G. Bauer, Carto	graphic S	Surveying	g Aid	
	Boyd S. Owens, C	Cadastral	Surveyor	:	
Under special instructions da	ted <u>April 4</u>		, 19 <u>63</u> ,	which provided	for the surveys
included under Group Number					
and assignment instructions da	May 3 April 8		1963 , 19 <u>63</u> .		American Mariante
<u> </u>					· · · · · · · · · · · · · · · · · · ·

Survey commenced April 11 , 19 63

Survey completed \_\_\_\_\_\_\_, 19 63

BOOK 4664

### INDEX DIAGRAM

Township22 Sou		outh	, Range	2 East	······································
6	8	13\4 3 13\4 9	1 8	9	1
7	8	13(½) 9	10	11	12
18	17	16	15	14	13
19	20	21	22	28	24
30	29	28	27	26	25
31	32	88	84	35	36

Subdivisions of Secs. 3 and 4, see pages 14-22

#### FIELD NOTE PAPER

 $_1\mathcal{B}$ 

CHAINS

Sections 3 and 4

Township 22 South, Range 22 East, Arizona

The north boundary of sections 3 and 4 was surveyed in 1909 by J. B. Wright. The west boundary of section 4 is the east boundary of the San Rafael Del Valle Private Land Claim and was surveyed in 1879 by S. M. Allis and retraced in 1916 by S. E. Blout. The remaining boundaries of sections 3 and 4 were surveyed in 1916 by S. E. Blout.

The following notes are those of a dependent resurvey of the boundaries and a survey of subdivisions, sections 3 and 4, Township 22 South, Range 22 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 4, 1963.

Bathey Markers described herein are "T" iron stakes, 24 inches long, with aluminum caps.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes.

The geographic position of the southeast corner of section 3 is: Latitude 31°32'26.5" N., and Longitude 110°05'15.9" W.

The magnetic declination was found to be 13°00' East.

Reestablishment of the 1909 Survey

By J. B. Wright

The cor. of secs. 2, 3, 34 and 35, Ts. 21 and 22 S., R. 22 E., is monumented by sandstone,  $20 \times 15 \times 10$  ins., set 20 ins. below ground, mkd. with 2 notches on the E. and 4 notches on the W., from which

Old B.T., a mesquite, 8 ins. diam., bears S. 28°30' W., 26 lks. dist., mkd. T22SR22E S3 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in ground, brass cap mkd.

Bury the original cor. stone alongside of iron post.

Build a mound of stone, 2 ft. base, 1 ft. high to the W. of iron post.

Set a 4  $\times$  4 ins. wood post, 5 ft. long, 18 ins. in the ground and alongside iron post.

S. 89°58' W., bet. secs. 3 and 34.

N. Bdy., Secs. 3 and 4, T. 22 S., R. 22 E., Arizona 2.

<del> </del>	No Buyer, Book. 5 and 4, 1. 22 Bey Re 22 Bey MIZORE 22
CHAINS	Over rolling hills, through thick mesquite with series of small washes draining NW.
10.03	Set Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	6 5
	Set a 2 x 2 ins. wood post, 4 ft. long, 18 ins. in ground alongside of marker.
20.06	Point for the E. 1/16 cor., secs. 3 and 34.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
	T21S R22E
	E $1/16 \frac{S}{S} \frac{34}{3}$
	Lot Lot
	145 6
	T22S 1963
	1905
	Set a 4 x 4 ins. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
30.00	Bladed road, bears NE. and SW.
30.09	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	146 145
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground, alongside marker.
40.12	The ½ sec. cor. of secs. 3 and 34, monumented by a sandstone, 18 x 10 x 10 ins. mkd. ½ on N. face.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
	T21S R22E . S 34
	½ S 34 S 3
	Lot <sub>T22S</sub> Lot 22 1963 <sup>146</sup>
	Bury the original corner stone alongside iron post.
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
	S. 89°56' W., beginning new measurement.
10.03	Set a Bathey marker 24 ins. long, 20 ins. in ground, cap mkd.
	23   22
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
20.06	Point for the W. 1/16 cor. of secs. 3 and 34.

### FIELD NOTE PAPER

	3.
N. Bdy., Secs. 3 and 4, T. 22 S., I	R. 22 E., Arizona
Set an iron post, 30 ins. long, $2\frac{1}{2}$ insins. in ground, cap mkd.	s. diam., 26
T21S R22E	
W $1/16 \frac{S}{S} \frac{34}{3}$ Lot Lot	
32 T22S 23 1963	
Set a 4 x 4 in. wood post, 5 ft. long ground alongside iron post.	, 18 ins. in
26.60 Wash, 22 lks. wide, 3 ft. deep, drain	s NW.
30.09 Set Bathey marker, 24 ins. long, 20 in cap mkd.	ns. in the ground,
33 32	
Set a 2 x 2 ins. wood post, 4 ft. longround alongside of marker.	g, 18 ins. in
The cor. of secs. 3, 4, 33 and 34, more 4 x 4 in. wood stake, 2 ft. long and ground with a few stones tamped along	3 ins. below
At the cor. point	
Set an iron post, 30 ins. long, $2\frac{1}{2}$ in in ground, cap mkd.	s. diam., 26 ins.
T21S R22E S33 S34	
Lot S 4 S 3 Lot	
25 T22S 25 1963 33	
Set a 4 x 4 in. wood stake, 5 ft. lon ground alongside iron post.	g, 18 ins. in
Land, low, rolling hills.	
Soil, sandy and rocky. Timber, none; undergrowth, greasewood mesquite and chaparral.	, white thorn,
S. 89°56' W., bet. secs. 4 and 33.	
Over low rolling hills, through heavy	brush.
Set a Bathey marker, 24 ins. long, 20 cap mkd.	ins. in ground,
26   25	
Set a 2 x 2 in. wood post, 4 ft. long ground alongside of marker.	g, 18 ins. in
20.06 Point for the E. 1/16 cor. of secs. 4	and 33.

N. Bdy., Secs. 3 and 4, T. 22 S., R. 22 E., Arizona 4.

CHAINS	1. 22 J., 1. 22 J., 1. 12 J., 1. 12 J., 1. 12 J.
CHAINS	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
,	T21S R22E E $1/16 \frac{S}{S} \frac{33}{4}$
	Lot T22S Lot 33 1963 26
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
30.09	Set a Bathey marker 24 ins. long, 20 ins. in ground, cap mkd.
	34   33
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
31.00	Old barbed wire fence, bears NE. and SW.
37.60	Wash, 30 lks. wide, 3 ft. deep, drains NE.
38.85	Gully, 5 lks. wide, 3 ft. deep, drains NW.
40.12	The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented by a granite stone, 24 x 12 x 10 ins. mkd. $\frac{1}{4}$ on N. face.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
	T21S R22E  2 S 33 S 4
	Lot 11 Lot 34 T22S 1963
	Bury the original corner stone alongside iron post.
	S. 89°40' W., beginning new measurement.
10.02	Set a Bathey marker 24 ins. long, 20 ins. in ground, cap mkd.
	43 11
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
17.20	Track road, bears NE. and SW.
17.80	Track road, bears N. 14° W. and S. 14° E.
18.04	The closing cor. of secs. 4 and 33 on the E. bdy. of the San Rafael Del Valle Private Land Claim, monumented by a granite stone, 24 x 15 x 10 ins., mkd. CC R22E on E. face, SRDV on W. face and 6 grooves on N. and S. faces; in a fence.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in ground, cap mkd.

Form 4-673b (January 1963)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD NOTE PAPER

CHAINS N. Bdy. Secs. 3 and 4, T. 22 S., R. 22 E., Arizona S T21S R R22E D <u>S 33</u> C V S 4 C T22S 1963 Bury the original cor. stone alongside iron post. From the C.C. the 3 mile marker, a stone as described in the official record, bears N.  $13^{\circ}30^{\circ}$  W., 37.98 chs. dist., and the  $3\frac{1}{2}$  mile marker bears S.  $13^{\circ}30^{\circ}$  E., 2.16 chs. dist. Land, low rolling hills. Soil, sandy and rocky. Timber, none; undergrowth, greasewood, white thorn, catclaw, mesquite and chaparral. Resurvey, Sections 3 and 4 Township 22 South, Range 22 East, Arizona Reestablishment of the 1916 Survey by S. E. Blout The cor. of secs. 2, 3, 10 and 11 is monumented by an iron post as described in the official record. marks Lot 144 to NW. cor. of cap. Build a collar of stone around the iron post and set a 4  $\times$  4 in. wood post, 6 ft. long, 18 ins. in ground alongside. Build a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, to west of iron post. N.  $0^{\circ}06$ 'E., bet. secs. 2 and 3. Over low rolling hills, through thick brush. 5.00 Set a Bathey marker, 24 ins. long, 18 ins. in the ground, cap mkd. Set a  $2 \times 2$  in. wood post, 4 ft. long, 18 ins. in ground alongside marker. Gully, 50 lks. wide, 5 ft. deep, drains W. 9.20 10.00 Set a Bathey marker, 24 ins. long, 22 ins. in ground, cap mkd. Set a  $2 \times 2$  in. wood post, 4 ft. long, 18 ins. in ground alongside marker.

	Resurvey, Secs. 3 and 4, 1. 22 S., R. 22 E., Arizona 6.
CHAINS	
15.00	Set a Bathey marker 24 ins. long, 22 ins. in ground, cap mkd.
	86
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground and alongside marker.
20.00	Point for the S. 1/16 cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in ground, cap mkd.
	S 1/16 S3   S2
	Lot 86 1963
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
20.10	R-O-W fence, bears N. 79°38' W. and S. 79°38' E.
21.63	Arizona State Highway No. 90, bears N. 79°38' W. and S. 79°38' E.
22.50	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	<u>80</u> 86
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
23.15	R-O-W fence, bears N. 79°38' W., and S. 79°38' E.; thence along old fence.
24.75	Track road, bears E. and W.
30.00	Set a Bathey marker, 24 ins. long, 22 ins. in ground, cap mkd.
	79 80
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
35.00	Set a Bathey marker, 24 ins. long, 22 ins. in ground, cap mkd.
	<u>76</u> 79
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
40.00	The ½ sec. cor. of secs. 2 and 3, monumented by an iron post as described in the official record. Added marks so cap reads
	Lot ½ 75 s 3 s 2
	Lot
	76 1916
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.

	FIELD NOTE PAPER 7.
CHAINS	Resurvey, Secs. 3 and 4, T. 22 S., R. 22 East, Arizona
	N. 0°09' E., beginning new measurement.
5.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	72 75
,	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
7.00	Old fence, bears S. and N. 5° W.; thence along a track road.
10.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	71 72
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
15.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	<u>68</u> 71
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
19.12	Wash, 25 lks. wide, 3 ft. deep, drains N. 50° W.
20.00	Point for the N. 1/16 cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
	Lot N 1/16 12 S 3 S 2
	Lot 68 1963
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
25.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	9 12
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
25.60	Track road, bears NW. and SE.
30.00	Set a Bathey marker, 24 ins. long, 20 ins. in the ground, cap mkd.
	8 9

	FIELD NOTE PAPER 9	•
CHAINS		
į	Resurvey, Secs. 3 and 4, T. 22 S., R. 22 E., Arizona	
	S. 89°57' W., beginning new measurement.	
10.02	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	128 129	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
19.80	Dam, bears SE. and NW. for 50 lks. then curves SW. to old railroad bed; thence over N. edge of dry reservoir.	
20.04	Point for the W. $1/16$ cor. of secs. 3 and 10.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.	
	Lot Lot 121 128	
	W 1/16 S 3 S 10 1963	
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.	
22.07	Old railroad bed, bears N. 46° W. and S. 46° E.	
30.06	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	120 121	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
40.08	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post as described in the official record. Added marks Lot 104 to NW. cor. and Lot 120 to NE. cor. of cap.	
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.	
	Land, low rolling hills. Soil, sandy and rocky. Timber, none; undergrowth, greasewood, mesquite, catclaw, white thorn and chaparral.	
·	North, bet. secs. 3 and 4.	
	Over rolling land, through thick brush.	
5.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	$     \begin{array}{c c}                                    $	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	

		BOOK 4664
<u> </u>	CHAINS	Resurvey, Secs. 3 and 4, T. 22 S., R. 22 E., Arizona 10.
	10.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		100   116 101   119
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	15.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		97   115 100   116
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	16.00	Wash, 75 lks. wide, 4 ft. deep, drains W.
	19.11	Old railroad bed, bears N. 46° W. and S. 46° E.
	20.00	Point for the S. 1/16 cor. of secs. 3 and 4.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
		Lot Lot 76 112
		S 1/16 Lot S4   S3 Lot
		97 115
		1963
		Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
	25.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		73   111 76   112
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	30.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		72   108 73   111
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	35.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		69 107 72 108
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	40.00	The ½ sec. cor. of secs. 3 and 4, monumented by an iron post as described in the official record. Added marks Lot 68 to NW. cor., Lot 47 to NE. cor., Lot 107 to SE. cor. and Lot 69 to SW. cor. of cap.
		Set a 5 x 5 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.

		FIELD NOTE PAPER	
Ī	CHAINS		
		Resurvey, Secs. 3 and 4, T. 22 S., R. 22 E., Arizona	
		N. 0°01' E., beginning new measurement.	
	5.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
		66 68 47	
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
	8.40	R-O-W fence, bears N. 76° W. and S. 76° E.	
	9.95	Arizona State Highway No. 90, bears N. 76° W. and S. 76° E.	
	10.00	Set a railroad spike flush with pavement, top mkd.	
	,	59 43 66 47	
		from which	
		An iron R-O-W marker, bears S. 23°28' E., 1.97 chs. dist., mkd.  HWY R of W 491 + 76.89	
		An iron R-O-W marker, bears N. 52°15' E., 1.88 chs. dist., mkd.  HWY R of W  491 + 76.89	
	11.50	R-O-W fence, bears N. 76° W. and S. 76° E.	
	12.41	Old highway, bears N. 77°38' W. and S. 77°38' E.	
	17.37	Old fence, bears E. and W.	
	20.00	Point for the N. 1/16 cor. of secs. 3 and 4.	
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.	
	·	Lot Lot  32 N 1/16  S4   S3  Lot Lot  59 1963	
		Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.	
	25.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
		29 37 32 38	
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
	1		1

-	Resurvey, Secs. 3 and 4, T. 22 S., R. 22 E., Arizona 13
30.00	Set a Bathey marker, 24 ins. long, 12 ins. in ground,
	cap mkd.
	28 34 29 37
	Set a 2 x 2 in. wood post 4 ft. long, 12 ins. in ground alongside marker.
34.60	Leave dredged area.
35.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	25 33 28 34
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
40.97	The cor. of secs. 3, 4, 33 and 34 on the N. bdy.
	Land, low rolling hills. Soil, sandy and rocky. Timber, none; undergrowth, greasewood, white thorn, blackbrush, mesquite and chaparral.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°57' W., bet. secs. 4 and 9.
	Over a series of small gullies draining NW., through thick undergrowth.
10.01	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	103 104
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
20.02	Point for the E. 1/16 cor. of secs. 4 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
	Lot Lot 96 103
	$W 1/16 \frac{S}{S} \frac{4}{9}$
	1963
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
30.03	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	95 96
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
30.60	Gully, 10 lks. wide, 4 ft. deep, drains NW.
38.68	The closing cor. of secs. 4 and 9 on the E. bdy. of the San Rafael Del Valle Private Land Claim, monumented by an iron post as described in the official record. Add marks Lot 95 to NE. on cap. Iron post is in a fence.
	<b>f</b>

### FIELD NOTE PAPER

	CHAINS	Resurvey, Secs. 3 and 4, T. 22 S., R. 22 E., Arizona
		From the C. C., the 5 mile marker on the S.R.D.V. Claim, monumented by a stone as described in the official record, bears S. 13°32' E., 39.52 chs. dist. and the 4½ mile marker bears N. 13°32' W., 0.72 chs. dist.
	40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, not monumented.
		Land, low rolling hills. Soil, sandy and rocky. Timber, none; undergrowth, greasewood, white thorn, catclaw, mesquite and chaparral.
		The $4\frac{1}{2}$ mile marker on the E. bdy. of the San Rafael Del Valle Private Land Claim is monumented by a granite stone 18 x 10 x 6 ins. mkd. $4\frac{1}{2}$ M on S. face, PL on E. face and SRDV on W. face.
		At the 4½ mile point
		Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
		S T22S
		R R22E D S 4
		V 4⅓M
		1963
		Bury the original stone marker alongside iron post.
		N. 13°31' W., bet. the E. bdy. and sec. 4.
		Over rolling land, through thick brush, along bdy. fence.
۱	7.78	Wash, 15 1ks. wide, 10 ins. deep, drains S. 80° W.
	22.08	Wash, 70 lks. wide, 6 ft. deep, drains NW.; enter mesquite grove.
	40.16	The 4 mile marker, monumented by a granite stone, $18 \times 12 \times 10$ ins. mkd 4M on S. face, PL on E. face and SRDV on W. face.
		At the 4 mile point
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
		S T22S R R22E D S 4
		V
		4M 1963
		Bury the original stone marker alongside iron post.
		•

		DOOK 100			
	CHAINS	Resurvey, Secs. 3 and 4, T. 22 S., R. 22 E., Arizona 14.			
		N. 13°34' W., beginning new measurement.			
	4.10	4.10 Leave mesquite grove.			
	22.70	R-O-W fence, bears N. 76° W. and S. 76° E.; end of bdy. fence.			
	24.37	Arizona State Highway No. 90, bears N. 76° W. and S. 76° E.			
	25.86	R-O-W fence, bears N. 76° W. and S. 76° E.; thence along bdy. fence.			
	40.15	The 3½ mile marker, monumented by a stone, 18 x 12 x 8 ins. mkd. 3½ M on S. face, PL on E. face and SRDV on W. face.			
	At the $3\frac{1}{2}$ mile point				
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in ground, cap mkd.			
		S T22S			
		R R22E D S 4			
		v			
		3½M 1963			
Bury the original stone marker alongside iron post.					
Subdivisions of Secs. 3 and 4.					
From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.		From the ½ sec. cor. of secs. 3 and 10.			
N. 0°02' E., on the N-S center line of sec. 3.  Over rolling land, through thick undergrowth.		N. 0°02' E., on the N-S center line of sec. 3.			
			5.00 Set a Bathey marker, 24 ins. long, 18 ins. in ground, cap mkd.		
		126   135 129   136			
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
	7.35	Wash, 50 1ks. wide, 6 ft. deep, drains NW.			
	7.80	Wash, 50 lks. wide, 7 ft. deep, drains W.			
	10.00	Set a Bathey marker, 24 ins. long, 6 ins. in ground, mound with stone to top, cap mkd.			
		125   132 126   135			
		Set a 2 x 2 in. wood post, 4 ft. long, 6 ins. in ground alongside marker.			
15.00 Set a Bathey marker, 24 ins. long, 20 ins. i cap mkd.		Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
		122 131 125 132			
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
	20.00	Point for the CS 1/16 cor. of sec. 3.			

	FIELD NOTE PAPER	
CHAINS	Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in ground, cap mkd.	
	Lot C Lot $105   96$ S $\frac{1}{16}$ S3 Lot Lot $122   C   131$ $1963$	
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground and alongside iron post.	
25.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	102 90 105 96	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside of marker.	
30.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	$\begin{array}{c c} 101 \\ \hline 102 \end{array} 90$	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
31.61	R-O-W fence, bears N. 63°58' W. and S. 64°16' E.	
32.50	Set a Bathey marker, 24 ins. long, 23 ins. in ground, cap mkd.	
	101 89 90	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
33.28	Arizona State Highway No. 90, bears N. 63°58' W. and S. 64°16' E.	
34.98	R-O-W fence, bears N. 63°58' W. and S. 64°16' E.	
35.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	97 89	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
40.00	Point for the C ½ cor. of sec. 3.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in ground, cap mkd.	

Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz. 16.

	Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz. 10			
CHAINS				
	T22S R22E Lot Lot			
	<sup>59</sup> c ½ s 3 <sup>66</sup>			
	Lot Lot 97 89			
	1963			
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.			
45.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
55 65 59 66				
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
45.15	Gully, 10 lks. wide, 4 ft. deep, drains N. 60° W.			
50.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
	54 62 55 65			
·	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground and alongside marker.			
55.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
	51 61 54 62			
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
56.08	Gully, 10 lks. wide, 4½ ft. deep, drains NW.			
60.00	Point for the CN 1/16 cor. of sec. 3.			
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.  Lot $C$ Lot $C$			
	51 C 61 1963 61			
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.			
60.75	Old fence, bears E. and W.			
65.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
	149 19 150 20			
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
70.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
148   147 149   19				

FIELD NOTE PAPER 17.		
	CHAINS	Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz.
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	70.72	Bladed road, bears SW. and NE.
	<b>74.</b> 42	Gully, 5 lks. wide, 4 ft. deep, drains N. 80° W.
	75.00	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		22   146   148   147
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground, alongside marker.
	80.97	The ½ sec. cor. of secs. 3 and 34 on the N. bdy.
		From the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
		S. 89°56' W., on the E-W center line of sec. 3.
		Over rolling land, through heavy undergrowth.
	10.01	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		74   75 77   76
		Set a 2 x in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	20.02	Point for the CE 1/16 cor. of sec. 3.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in ground, cap mkd.
		$ \begin{array}{c} \text{Lot} & \text{Lot} \\ 67 & \frac{1}{\text{E}} & \frac{74}{16} \\ \text{C} & \frac{16}{\text{S} & 3} & \text{C} \end{array} $
		Lot Lot 87 77 1963
		Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
	28.03	Gully, 15 lks. wide, 4 ft. deep, drains N. 60° W.
	30.03	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		66 67 88 87
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	33.70	Dim track road, bears NW. and SE.
	35.03	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
		66 89   88

Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz. 18.

		Subdivisions, Secs. 3 and 4, 1. 22 5., K. 22 E., Aliz. 10			
	CHAINS				
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
	40.04	The C ½ sec. cor. of sec. 3.			
	45.05	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
		58 <u>59</u> 97			
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
	49.60	R-O-W fence, S. 62° E. and N. 62° W.			
	50.06	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
		57 98 58			
		from which			
		A R-O-W marker bears S. 7°03' E., 3.43 chs. dist., mkd. HIGHWAY R of W 513 + 13.			
		A R-O-W marker bears S. 68°25' E., 1.90 chs. dist., mkd. HIGHWAY R of W 513 + 13.			
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			
	52.82	Arizona State Highway No. 90 bears S. 62° E. and N. 62° W.			
	55.07	Set a Bathey marker, 24 ins. long, 23 ins. in ground, cap mkd.			
		50   57 98			
	·	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground and alongside marker.			
	56.19	R-O-W fence, bears S. 62° E. and N. 62° W.			
	60.08	Point for the CW 1/16 cor. of sec. 3.			
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, cap mkd.			
Lot 50 W 1/16 C - S3 C Lot S3 Lot 106 1963					
		Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.			
	65.09	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.			
		49 50 106			
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.			

### FIELD NOTE PAPER

	FIELD NOTE PAPER	19.
CHAINS		
	Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz.	_
70.10	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	48 49 107 106	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
75.11	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	<u>47   48</u> 107	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
80.12	The ½ sec. cor. of secs. 3 and 4.	
	S. 89°57' W., on the E-W center line of sec. 4.	
	Over rolling land, through heavy brush.	
10.02	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	67 68 70 69	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
19.80 Track road, bears NW. and SE.  20.04 Point for CE 1/16 cor. of sec. 4.		
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.	
	Lot Lot	
	58 <u>1</u> 67	
	$c = \frac{16}{24}$	
	Lot S4 Lot	
	1963 70	
	from which	
	A U.S.G.S. bench mark, a brass tablet set in a granite stone 10 x 15 ins., 18 ins. of it above ground, mkd.  4194 FEET DATUM NOGLS	
	bears S.38°17' E., 11.36 chs. dist.	
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.	
30.06	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	57 58 78 77	
	78 77 Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in	
	ground alongside marker.	

	Subdivisions, Secs. 3 and 4, 1. 22 S., R. 22 E., Ariz. 20
40.08	Point for the C ½ cor. of sec. 4.
40.00	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.
	Lot Lot
	$\begin{array}{cc} 24 & 57 \\ \text{Lot} & \text{Lot} \end{array}$
	85 <sub>1963</sub> 78
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.
48.30	Intersect the E. bdy. of the San Rafael Del Valle Private Land Claim.
	Set a Bathey marker, 20 ins. in ground, cap mkd.
	S R 24 85
	D 85 V
	from which
	The iron post set at the 4th mile on the E. Bdy. of the San Rafael Del Valle Private Claim bears S. 13°34' E., 0.24 chs. dist.
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
	From the ½ sec. cor. of secs. 4 and 33 on the N. bdy.
	S. 0°04' E., on the N-S center line of sec. 4.
	Over rolling land, through thick brush.
5.98	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	11 34 12 35
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
10.98	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	12 35 45 38
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
15.98	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.
	45 38 39
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.
18.20	
19.43	
19.70	Old railroad bed, bears NW. and SE.
1	

### FIELD NOTE PAPER

		FIELD NOTE PAPER	21.
	CHAINS		T
		Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz.	_
	20.98	Arizona State Highway No. 90, bears S. 76° E. and N. 76° W.	
	20.98	Point for the CN 1/16 cor. of sec. 4.	
		Set a railroad spike flush with pavement, top mkd.	
		Lot Lot $ \begin{array}{c c}  & & & & \\  & 45 \\  & & 16 \\ \hline  & & 16 \\ \hline  & & 16 \\ \hline  & & 50 \\ \hline  & & 1963 \end{array} $ Lot	
	22.52	R-O-W fence, bears S. 76° E. and N. 76° W.	
	25.98	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	:	<u>50</u> 53	
		Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
	30.98	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
		22 53 23 56	
		Set a 2 $\times$ 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
	35 <b>.9</b> 8	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
		23   56 24   57	
		Set a 2 $\times$ 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
	40.98	The center ½ cor. of sec. 4.	
	45 <b>.9</b> 8	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
		85 <u>78</u> 86 <del>79</del>	
		Set a $2 \times 2$ in. wood post, $4 \text{ ft. long}$ , $18 \text{ ins. in}$ ground alongside marker.	
	50 <b>.9</b> 8	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
		86 79 87 82	
		Set a $2 \times 2$ in. wood post, $4 \text{ ft. long}$ , $18 \text{ ins. in}$ ground alongside marker.	
	54.80	Wash, 80 lks. wide, 4 ft. deep, drains SE.	
			-

	BOOK 4664	
	Subdivisions, Secs. 3 and 4, T. 22 S., R. 22 E., Ariz. 22.	
CHAINS		
55.98	Set a Bathey marker, 24 ins. long, 20 ins. in ground, cap mkd.	
	87 82 88 83	
	Set a 2 x 2 in. wood post, 4 ft. long, 18 ins. in ground alongside marker.	
60.98	Point for the CS 1/16 cor. of sec. 4.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in ground, cap mkd.	
	$ \begin{array}{c c} \text{Lot} & \text{C} & \text{Lot} \\ 88 & \text{S} \frac{1}{16} & \text{S4} \end{array} $	
	Lot 90 1963	
	Set a 4 x 4 in. wood post, 5 ft. long, 18 ins. in ground alongside iron post.	
75.39	Intersect the E. bdy. of the San Rafael Del Valle Private Land Claim.	
80.98	The point for the ½ sec. cor. of secs. 4 and 9, on private land.	
The remaining subdivisions of sections 3 and 4 as shown on the plat of this survey were surveyed and the corner monuments set. The plat gives the true bearing and distances and the legend indicates the kind of marker set at the corners.		

### BOOK 4664

Form 4-680 (January 1963)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

### FIELD ASSISTANTS

NAMES	CAPACITY
Wallace Ott	Transitman
Alan Crockett	Notekeeper
Dennis Twitchell	Chainman
Ken Herman	Flagman
Tom D. Carter	Cornerman
Walter Mitchell	Axeman
Larry Carson	Cornerman
<del></del>	<del></del>

#### 4664 BOOK



#### CERTIFICATE OF SURVEY

Paul G. Bauer I. Boyd S. Owens , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of April , 1963, I have resurveyed the boundaries and surveyed subdivisions, sections 3 and 4, Township 22 South, Range 22 East

of the Gila and Salt River Arizona , which Meridian, in the State of are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Saul D. Banes (Cadastral Surveyor) June 14, 1963 (Date) Boy of S Cwelly (Cadastral Surveyor) June 14, 1963 (Date)

#### CERTIFICATE OF APPROVAL Bureau of Land Management

The foregoing field notes of the resurvey of the boundaries and survey of subdivisions, sections 3 and 4, Township 22 South, Range 22 East, Gila and Salt River Meridian, Arizona

Paul G. Bauer, Surveying Technician Boyd S. Owens, Cadastral Surveyor executed by

having been critically examined and found correct, are hereby approved. Washington, D. C. JUN 26 1963 of Engine (Date)

#### CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes. (Date) (Chief, Division of Engineering)