#### FIELD NOTE PAPER

18

CHAINS

Dependent Resurvey of Township 10 South,
Range 28 East, Arizona

The south boundary, the Second Standard Parallel South, was surveyed in 1882 by T. F. White. The east half mile was retraced and the Stan.  $\frac{1}{4}$  sec. cor. of sec. 36 was remonumented in 1952 by C. E. Bilbray. The east, west, and north boundaries were surveyed in 1884 by L. Wolfley. The subdivisional lines were surveyed in 1885 by J. C. Smith. The north half mile of the east boundary was dependently resurveyed in 1921 by W. H. Thorn and the south  $5\frac{1}{2}$  miles of the east boundary were dependently resurveyed in 1935 by H. M. Muscott.

The following notes are those of the dependent resurvey of the north and west boundaries, the south boundary, the Second Standard Parallel South, and the subdivisional lines; the establishment of the closing corners and the  $\frac{1}{4}$  section corners for T. 11 S., R. 28 E. on the Second Standard Parallel South.

Executed in accordance with the special instructions dated August 10, 1960 and the specifications set forth in the Manual of Surveying Instructions, 1947.

Only the true line bearings and the horizontal distances for the surveyed lines are given in these notes. Unless described, all corners were monumented with standard iron posts, 30 inches long,  $2\frac{1}{2}$  inches in diameter, flanged at the bases and with brass caps riveted to the tops.

The geographic position for the southeast corner of the township is in latitude 32° 30'  $l_45.87$ " M. and longitude 109° 25' 26.85" W., as determined by section line ties to U.S.C. & G.S. triangulation station TAN located in section 36, T. 9 S., R. 27 E.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be 13° East.

Dependent Resurvey, 2nd Stan. Par. South, R. 28 E., Arizona

Reestablishment of the Survey in 1882 by T. F. White

From the Stan. Cor. of T. 10 S., Rs. 28 and 29 E., monumented by an iron post as described in the official record.

S. 89° 58' W., on the S. bdy. of sec. 35.

Over nearly level land, through scattered undergrowth.

28.30 Low sand ridge; desc. W. slope.

The closing cor. of secs. 1 and 6, T. 11 S., Rs. 28 and 29 E., marked by an iron post as descirbed in the official record.

|       | BOOK 4667  |
|-------|--|
| 2     | Resurvey, 2nd Stan. Par. S., R. 28 E., Arizona 2.  |
| 39.6  |  |
| 40.7  |  |
|       | S. 89° 48' W., beginning new measurement.  |
|       | Asc. gentle E. slope.  |
| 1.40  | Low sand ridge; desc. W. slope.  |
| 25.40 | Wash, 40 lks. wide, drains SW.   |
| 34•25 | Point for the $\frac{1}{4}$ sec. cor. of sec. 1, at midpoint bet. the closing corners for sec. 1.                              |
|       | Set the iron post 26 ins. in the ground, cap mkd.  |
|       | T 11 S R 28 E<br>1960  |
| 40.23 | The Stan. cor. of secs. 35 and 36, monumented by a wood stake as described in the official record.                             |
|       | At the corner point  |
|       | Set the iron post 21 ins. in the ground, cap mkd.  |
|       | SC<br>Tlos R28E<br>S35 S36   |
|       | Land, nearly level. Soil, sandy. Timber, none: Undergrowth, cactus and mesquite.   |
|       | N. 89° 51' W., on the S. bdy. of sec. 35.  |
|       | Over nearly level land, through scattered undergrowth.   |
| 4.80  | Drainage ditch, 50 lks. wide, drains S.  |
| 29.10 | Fence, barbed wire, bears N. and S.  |
| 34.40 | Jeep road, bears N. and S.   |
| 34.50 | Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. |
|       | Set the iron post 28 ins. in the ground, cap mkd.  |
|       | S2   SI<br>C C<br>T11S R28E<br>1960  |
|       |  |
|       |  |
|       |  |
|       |  |
|       |  |
|       |  |

Form 4-673b (January 1963)

### UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

|   |        | FIELD NOTE PAPER 3.   |
|---|--------|---|
|   | CHAINS | Resurvey, 2nd Stan. Par. S., R. 28 E., Arizona  |
| , | 40.00  | The Stan. ½ sec. cor. of sec. 35, monumented by a wood post as described in the official record.  |
|   |        | At the corner point   |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | SC<br>T10S R28E<br>- ½ S 35<br>1960   |
|   |        | Deposit glass at base of iron post.   |
|   |        | S. 89°57' W., beginning new measurement.  |
|   | 6.90   | San Simon Wash, 100 1ks. wide, drains N.  |
|   | 15.20  | Jeep road, bears NW. and SE.  |
|   | 26.50  | Wash, 10 lks. wide, drains N.   |
|   | 29.60  | Asc. E. slope of a bench, bears N. and S.   |
|   | 34.38  | Point for the ½ sec. cor. of sec. 2, at midpoint bet. the closing corners of sec. 2.              |
|   |        | Set the iron post 24 ins. in the ground, mound with stone to top, cap mkd.                        |
|   |        | え S 2<br>T11S R28E<br>1960  |
|   |        | Corner falls on rocky E. slope of mesa.   |
|   | 39.44  | The Stan. cor. of secs. 34 and 35, monumented by a wood post as described in the official record. |
|   |        | At the corner point   |
|   |        | Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.                        |
|   |        | SC<br>T10S R28E<br><u>S34   S35</u><br>1960   |
|   |        | Land, level. Soil, sandy. Timber, none; undergrowth, mesquite and catclaw.                        |
|   |        | S. 89°58' W., on the S. bdy. of sec. 34.  |
|   |        | Over rolling land, through scattered undergrowth.   |
|   | 7.50   | Draw, drains NE.  |
|   | 16.80  | Wash, 100 lks. wide, drains NE.   |
|   |        |   |

|   | CHAINS | Resurvey, 2nd Stan. Par. S., R. 28 E., Arizona 4.  |
|---|--------|--|
|   | 34.81  | The closing cor. of secs. 2 and 3, monumented by a wood post as described in the official record.  |
|   |        | At the corner point  |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.  |
|   |        | S3   S2<br>CC  |
|   |        | T11S R28E<br>1960  |
|   | 40.03  | The ½ sec. cor. of sec. 34, monumented by a wood post as described in the official record.   |
|   |        | At the corner point  |
|   |        | Set the iron post 15 ins. in the ground, mound with stone to top, cap mkd.   |
|   |        | SC<br>T10S R28E  |
|   |        | ½ S34  |
|   |        | 1960   |
|   |        | N. 89°50' W., beginning new measurement.   |
| l | 6.60   | Road, bears N. and S.  |
|   | 26.00  | Wash, 150 1ks. wide, drains N.   |
|   | 28.00  | Desc. W. slope of a bench, bears SW. and N.  |
|   | 35.29  | Point for the ½ sec. cor. of sec. 3, at midpoint bet. the closing corners of sec. 3 and falling in the bottom of a wash, 50 lks. wide, drains N. |
|   | 35.49  | Point selected for the witness 1/2 sec. cor. of sec. 3.  |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.  |
|   |        | ₩<br>½ S3 C  |
|   |        | T11S R28E<br>1960  |
|   |        |  |
|   |        | Raise a mound of stones N. of corner.  |
|   | 39.00  | Point selected for the witness Stan. Cor. of secs. 33 and 34.  |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.  |
|   |        | SC<br>T10S R28E<br>W S33 S34<br>C 1960   |
|   |        | Deposit glass at base of iron post.  |
|   | 40.00  | The Stan. cor. of secs. 33 and 34, monumented by a wood stake as described in the official record, falling in an unsafe place.                   |
|   |        | Land, rolling. Soil, gravelly. Timber, none: Undergrowth, mesquite and creosote.   |
|   |        |  |
| ı | i      | ı  |

### FIELD NOTES

| · · · · · · · · · · · · · · · · · · · | of the             |                          |
|---------------------------------------|--------------------|--------------------------|
| DEPEN                                 | DENT RESURVEY      |                          |
|                                       | of the             |                          |
| Second Standard Paralle               | 1 South through    | Range 28 East            |
|                                       |                    | -                        |
| North an                              |                    |                          |
| •                                     |                    |                          |
|                                       |                    |                          |
| Subdiv                                | risional Lines     |                          |
|                                       | of                 |                          |
| Township 10                           | South, Range 28 Ea | st                       |
|                                       |                    |                          |
|                                       | ·                  |                          |
|                                       | ·                  | <b>:</b>                 |
| Of theGila a                          | nd Salt River      |                          |
| In the State of                       | Arizona            |                          |
| EXE                                   | CUTED BY           |                          |
|                                       |                    |                          |
| Dell Cazier,                          | Cadastral Survey   | or                       |
| Glen B. Hatch,                        | Surveying Techni   | cian                     |
| A. D. Griffin                         | , Surveying Aide   | ×                        |
| Under special instructions dated      | August 10          | , 19.60., which provided |
| for the surveys included under Group  | o No351            | approved August 16, 1960 |
| and assignment instructions dated     |                    |                          |
| una assignimenti instructions auteu   |                    | , 10                     |
|                                       |                    |                          |
| Survey commenced                      | December 2         | , <i>19</i> 60           |
| Survey completed                      | January 23         | . 19 61                  |

BOOK 4667

### INDEX DIAGRAM

|    | Towns | hip_     | 10 5 | South |    | , F | Range | 28 | East |    |    |
|----|-------|----------|------|-------|----|-----|-------|----|------|----|----|
|    | 17    |          | 16   |       | 15 |     | 14    |    | 14   |    | 13 |
| 12 | 6     | 51       | 5    | 43    | 4  | 36  | 8     | 30 | 2    | 23 | 1  |
|    | 51    | -        | 50   |       | 42 |     | 36    | _  | 29   |    | 23 |
| 11 | 7     | 50       | 8    | 42    | 9  | 35  | 10    | 28 | 11   | 22 | 12 |
|    | 49    | -        | 49   |       | 41 |     | 35    | _  | 28   |    | 21 |
| 10 | 18    | 48       | 17   | 41    | 16 | 34  | 15    | 27 | 14   | 21 | 18 |
|    | 48    | <u>.</u> | 47   |       | 40 |     | 33    |    | 27   |    | 20 |
|    |       |          |      |       |    |     |       |    |      |    |    |
| 10 | 19    | 47       | 20   | 39    | 21 | 33  | 22    | 26 | 28   | 19 | 24 |
|    | 46    | -        | 46   |       | 39 |     | 32    | _  | 26   |    | 19 |
|    |       | 1        |      |       |    |     |       |    |      |    |    |
| 9  | 80    | 45       | 29   | 38    | 28 | 31  | 27    | 25 | 26   | 18 | 25 |
|    | 45    | _        | 44   |       | 38 |     | 31    |    | 24   |    | 18 |
|    |       |          |      |       |    |     |       |    |      |    |    |
| 8  | 81    | 43       | 82   | 37    | 88 | 30  | 84    | 24 | 85   | 17 | 86 |
|    | 7     |          | 6    | -     | 5  |     | 3     |    | 2    |    | 1  |

GPQ 866119

Form 4-673b (January 1963)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

| ,   |                | FIELD NOTE PAPER 5.   |
|-----|----------------|---|
|     | CHAINS         | Resurvey, 2nd Stan. Par. S., R. 28 E., Arizona  |
|     |                | N. 89° 37' W., on the S. bdy. of sec. 33.   |
|     |                | Over level to rolling land, through scattered undergrowth   |
|     | 2.00           | Wash, 250 lks. wide, drains NE.   |
|     | <b>5.</b> 30   | Wash, 100 lks. wide, drains E.  |
|     | 27.20          | Road, bears N. and S.   |
|     | 35 <b>.</b> 80 | Point for the closing cor. of secs. 3 and 4 at proportionate distance; there is no remaining evidence of the original corner. |
|     |                | Set the iron post 26 ins. in the ground, cap mkd.   |
|     |                | C C<br>SL  S3<br>T11S R28E<br>1960  |
|     |                | Deposit glass at base of iron post.   |
|     | 40.92          | The Stan. $\frac{1}{4}$ sec. cor. of sec. 33, monumented by a wood post as described in the official record.                  |
|     |                | At the corner point   |
|     |                | Set the iron post 14 ins. in the ground, mound with stone to top, cap mkd.  |
|     |                | SC<br>TIOS R28E<br>   |
|     |                |   |
|     |                | N. 89° 52' W., beginning new measurement.   |
|     | 8.00           | Asc. E. slope of ridge, bears NE. and SE.   |
|     | 22.00          | Draw, drains NE.  |
|     | 26.00          | Ridge, bears NE. and SW.  |
|     | 32.40          | Wash, 30 lks. wide, drains NE.  |
|     | 35.30          | Point for the $\frac{1}{4}$ sec. cor. of sec. 4, at midpoint bet. the closing corners of sec. 4.                              |
| j.  |                | Set the iron post 26 ins. in the ground, cap mkd.   |
|     |                | 1/4 S 4<br>T11S R28E<br>1960  |
| . • |                | Deposit glass at base of iron post.   |
|     | 38.90          | Ridge, bears N. and S.; desc. W. slope.   |
|     | 40.03          | The Stan. cor. of secs. 32 and 33, monumented by a wood post as described in the official record.                             |
| •   |                |   |

|     | T      | Resurvey, 2nd Stan. Par. S., R. 28 E., Arizona 6.  |
|-----|--------|--|
|     | CHAINS | At the corner point  |
|     |        | Set the iron post 22 ins. in the ground, cap mkd.  |
|     | ,      | SC<br>Tlos R28E<br>S32 S33<br>1960   |
|     |        | Deposit glass at base of iron post.  |
|     |        | Land, level to rolling. Soil, sandy to gravelly. Timber, none: Undergrowth, creosote and mesquite.   |
|     |        | N. 89° 53' W., on the S. bdy. of sec. 32.  |
|     |        | Over gently rolling land, through scattered undergrowth.   |
|     | 1.50   | Wash, 10 lks. wide, drains S.  |
|     | 16.00  | Desc. W. slope.  |
|     | 35.70  | The closing cor. of secs. 4 and 5, monumented by a wood post as described in the official record.  |
|     |        | At the corner point  |
|     |        | Set the iron post 26 ins. in the ground, cap mkd.  |
|     |        | S5 S4<br>T11S R28E<br>C C<br>1960  |
|     |        | Deposit glass at base of iron post.  |
|     | 38.69  | Point selected for the witness Stan. ½ sec. cor. of sec. 32.   |
|     |        | Set the iron post 26 ins. in the ground, cap mkd.  |
|     |        | SC<br>TIOS R28E<br>W 1/4 S32<br>C 1960   |
| l   |        | Deposit glass at base of iron post.  |
|     | 40.19  | Point for the Stan. $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner; falling in a wash, 300 lks. wide, 1 ft. deep, draining NE. |
|     | 49.40  | Wash, 30 lks. wide, drains NE.   |
|     | 51.20  | Wash, 30 lks. wide, drains NE.   |
|     | 52.30  | Asc. E. slope of ridge.  |
|     | 57.10  | Top of ridge, projects NE. and SW.; desc. over rolling land.   |
|     | 66.00  | Wash, 30 lks. wide, drains NE.   |
|     | 76.13  | Point for the $\frac{1}{4}$ sec. cor. of sec. 5, at midpoint bet. the closing corners of sec. 5.   |
|     |        |  |
|     |        |  |
| - 1 | 4      |  |

7.

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

|   |        | TILLUNOTE TALER 7.  |
|---|--------|---|
|   | CHAINS | Dependent Resurvey, 2nd Stan. Par. S., R. 28 E.   |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.   |
|   |        | 1/4 S 5<br>T11S R28E<br>1960  |
|   |        | Deposit glass at base of iron post.   |
|   | 80.39  | Point for the Stan. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.                              |
|   |        | Set the iron post 20 ins. in the ground, cap mkd.   |
|   |        | SC<br>T10S R28E<br><u>S31 S32</u><br>1960   |
|   |        | Deposit glass at base of iron post.   |
|   |        | Land, rolling. Soil, sandy. Timber, none; undergrowth, mesquite and creosote brush.   |
|   |        | N. 89°53' W., on the S. bdy. of sec. 31.  |
|   |        | Over rolling land, through scattered undergrowth.   |
|   | 8.10   | Ridge, bears NE. and SW.; desc. W. slope.   |
|   | 16.10  | Wash, 20 lks. wide, drains NE.  |
|   | 32.50  | Wash, 140 1ks. wide, drains NE.   |
| · | 36.17  | Point for the closing cor. of secs. 5 and 6, at proportionate distance; falls in a wash, 50 lks. wide. 2 ft. deep, drains NE.; unable to perpetuate corner. |
|   | 36.57  | Point selected for the witness closing cor. of secs. 5 and 6.   |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.   |
|   |        | CC W<br>S6 S5C<br>T11S R28E<br>1960   |
|   |        | Deposit glass at base of iron post.   |
| · | 40.19  | Point for the Stan. ½ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.                               |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.   |
|   |        | SC<br>T10S R28E   |
|   |        | 1103 K26E<br>- 1/4 S31<br>1960  |
|   |        | Deposit glass at base of iron post.   |

| 8 |        | BOOK 4667   |
|---|--------|---|
|   | CHAINS | Dependent Resurvey, 2nd Stan. Par. S., R. 28 E.   |
|   |        |   |
|   | 64.40  | Wash, 10 1ks. wide, drains NE.  |
|   | 76.35  | Point for the ½ sec. cor. of sec. 6 at proportionate distance based upon the theoretical position for the ½ sec. cor. as originally being 40.00 chs. W. of the closing cor. of secs. 5 and 6. |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.   |
|   |        | · · · · · · · · · · · · · · · · · · ·   |
|   |        | Deposit glass at base of iron post.   |
|   | 80.39  | The cor. of T. 10 S., Rs. 27 and 28 E., monumented by a wood post, as described in the official record.   |
|   |        | At the corner point   |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | SC<br>T10S  |
|   |        | R27E R28E   |
|   |        | S36   S31<br>1960   |
|   |        | Deposit glass at base of iron post.   |
|   |        | Land, gently rolling. Soil, sandy to gravel. Timber, none; undergrowth, creosote, mesquite and mescal.  |
|   |        | Dependent Resurvey of the West Boundary, T. 10 S., R. 28 E., G&SRM, Arizona   |
|   |        | Reestablishment of the Survey Executed by L. Wolfley in 1884  |
|   |        | From the Stan. cor. of secs. 31 and 36, T. 10 S., Rs. 27 and 28 E.  |
|   |        | N. 0°12' W., bet. secs. 31 and 36.  |
|   |        | Over nearly level land, through scattered undergrowth.  |
|   | 4.00   | Fence, barbed wire, bears NE. and SW.   |
|   | 23.00  | Shallow wash, 20 lks. wide, drains E.   |
|   | 33.40  | Shallow wash, 20 lks. wide, drains E.   |
|   | 40.26  | Point for the ½ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.   |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.   |
|   |        | TIOS  |
|   |        | R27E R28E   |
|   | ,      | S36 S31<br>1960   |
|   |        | Deposit glass at base of iron post.   |
|   |        |   |

|        | BUREAU OF LAND MANAGEMENT   |
|--------|---|
|        | FIELD NOTE PAPER 9.   |
| CHAINS | Resurvey, W. Bdy., T. 10 S., R. 28 E.   |
| 53.20  | Wash, 30 lks. wide, drains NE.  |
| 53.80  | Wash, 70 lks. wide, drains NE.  |
| 58.30  | Wash, 40 lks. wide, drains E.   |
| 80.52  | The cor. of secs. 25, 30, 31 and 36, monumented by a wood post as described in the official record.                             |
|        | At the corner point   |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |
|        | T10S<br>R27E R28E<br>S25 S30<br>S36 S31<br>1960   |
|        | Deposit glass at base of iron post.   |
|        | Land, nearly level. Soil, gravelly, sandy. Timber, none; undergrowth, cactus, mesquite and creosote brush.                      |
|        | N. 0°06' W., bet. secs. 25 and 30.  |
|        | Over level land, through scattered undergrowth.   |
| 15.50  | Shallow wash, 20 lks. wide, drains NE.  |
| 25.90  | Wash, 30 lks. wide, drains NE.  |
| 31.90  | Wash, 30 1ks. wide, drains NE.  |
| 35.30  | Wash, 30 lks. wide, drains E.   |
| 40.07  | Point for the ½ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S<br>R27E R28E   |
|        | \$25\\ \$30<br>1960   |
|        | Raise a mound of stone N. of corner.  |
| 53.00  | Wash, 20 1ks. wide, drains NE.  |
| 73.80  | Wash, 30 1ks. wide, drains E.   |
| 80.14  | The cor. of secs. 19, 24, 25 and 30, monumented by a wood post as described in the official record.                             |
|        | At the corner point   |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |
|        | •   |

| CHAINS         | 10.   |
|----------------|---|
|                | Resurvey, W. Bdy., T. 10 S., R. 28 E.   |
|                |   |
|                | T10S<br>R27E R28E   |
|                | S24 S19   |
|                | \$25 \$30   |
|                | 1960<br>Land, level.  |
|                | Soil, sandy.  |
|                | Timber, none; undergrowth, cactus and mesquite.   |
|                | N. 0°05' W., bet. secs. 19 and 24.  |
|                | Over level land, through scattered undergrowth.   |
| 14.80          | Wash, 20 1ks. wide, drains NE.  |
| 30.60          | Wash, 20 1ks. wide, drains NE.  |
| 33.20          | Wash, 10 1ks. wide, drains NE.  |
| 40.52          | Point for the 1/2 sec. cor. of secs. 19 and 24, at pro-   |
|                | portionate distance; there is no remaining evidence of the original corner.                         |
|                | Set the iron post 26 ins. in the ground, cap mkd.   |
|                | T10S<br>R27E R28E   |
|                | 1 2   |
|                | S24 S19<br>1960   |
|                | Deposit glass at base of iron post.   |
| 47.70          | Wash, 30 lks. wide, drains NE.  |
| 54.10          | Wash, 30 1ks. wide, drains NE.  |
| 60.70          | Wash, 20 1ks. wide, drains NE.  |
| 62.90          | Wash, 40 lks. wide, drains NE.  |
| 81.04          | The cor. of secs. 13, 18, 19 and 24, monumented by a wood post as described in the official record. |
|                | At the corner point   |
|                | Set the iron post 24 ins. in the ground, cap mkd.   |
|                | T10S  |
|                | R27E R28E<br>S13 S18  |
|                | S24 S19   |
|                | 1960  |
|                | Deposit glass at base of iron post  |
|                | Land, level. Soil, sandy. Timber, none; undergrowth, mesquite, cactus and creosote brush.           |
|                | N. 0°25' W., bet. secs. 13 and 18.  |
|                | Over level land, through scattered undergrowth.   |
| 22 <b>.9</b> 0 | Wash, 20 lks. wide, drains NE.  |
| 24.40          | Wash, 20 lks. wide, drains NE.  |

|     | FIELD NOTE PAPER |   |  |  |  |
|-----|------------------|---|--|--|--|
|     | CHAINS           | To a Company Andrews  |  |  |  |
|     |                  | Resurvey, W. Bdy., T. 10 S., R. 28 E., Arizona  |  |  |  |
|     | 33.40            | Wash, 70 1ks. wide, drains NE.  |  |  |  |
|     | 39.89            | Point for the ½ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. |  |  |  |
|     |                  | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |  |
|     |                  | T10S<br>R27E R28E   |  |  |  |
|     |                  | \$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\   |  |  |  |
|     |                  | Deposit glass at base of iron post.   |  |  |  |
|     | 79.78            | The cor. of secs. 7, 12, 13 and 18, monumented by a wood post as described in the official record.                              |  |  |  |
|     |                  | At the corner point   |  |  |  |
|     |                  | Set the iron post 24 ins. in the ground, cap mkd.   |  |  |  |
|     |                  | T10S  |  |  |  |
|     |                  | R27E R28E<br>S12 S 7  |  |  |  |
|     |                  | S13 S18<br>1960   |  |  |  |
|     |                  | Deposit charcoal at base of iron post.  |  |  |  |
|     |                  | Land, level. Soil, sandy. Timber, none; undergrowth, mesquite, cactus and creosote.   |  |  |  |
|     |                  | N. 0°21' W., bet. secs. 7 and 12.   |  |  |  |
|     |                  | Over level land, through scattered undergrowth.   |  |  |  |
|     | 15.00            | Wash, 30 1ks. wide, drains E.   |  |  |  |
|     | 24.70            | Road, unimproved, bears E. and W.   |  |  |  |
|     | 26.10            | Fence, barbed wire, bears E. and W.   |  |  |  |
| -   | 40.14            | Point for the ½ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.  |  |  |  |
|     |                  | Set the iron post 24 ins. in the ground, cap mkd.   |  |  |  |
|     |                  | T10S<br>R27E R28E   |  |  |  |
|     |                  | 1/2   |  |  |  |
|     |                  | S12   S 7<br>1960   |  |  |  |
|     |                  | Deposit charcoal at base of iron post.  |  |  |  |
|     | 47.60            | Wash, 10 1ks. wide, drains E.   |  |  |  |
| •   | 67.20            | Wash, 30 1ks. wide, drains NE.  |  |  |  |
| . • | 80.28            | Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.   |  |  |  |
| •   |                  |   |  |  |  |

|   | CHAINS     |   |  |  |  |
|---|------------|---|--|--|--|
|   | CHIMING    | Resurvey, W. Bdy., T. 10 S., R. 28 E., Arizona  |  |  |  |
|   |            | Set the iron post 25 ins. in the ground, cap mkd.   |  |  |  |
|   |            | T10S  |  |  |  |
|   |            | R27E R28E<br>S 1 S 6  |  |  |  |
|   |            | S12 S 7   |  |  |  |
|   |            | Deposit store 7.5.2 : 1.5 mm  |  |  |  |
|   |            | Deposit stone, 7x5x3 ins., mkd. "X" at base of iron post.   |  |  |  |
|   |            | Land, level. Soil, sandy.   |  |  |  |
|   |            | Timber, none; undergrowth, creosote, mesquite and cactus.   |  |  |  |
|   |            | N. 0°21' W., bet. secs. 1 and 6.  |  |  |  |
|   |            | Over level land, through scattered undergrowth.   |  |  |  |
|   | 10.30      | Wash, 20 lks. wide, drains NE.  |  |  |  |
|   | 40.14      | Point for the ½ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.                                     |  |  |  |
|   |            | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |  |
|   |            | T10S  |  |  |  |
|   |            | R27E R28E   |  |  |  |
|   |            | S 1 S 6<br>1960   |  |  |  |
|   | from which |   |  |  |  |
|   |            | A fence cor. post bears S. 61°28' E., 4.10 chs. dist.   |  |  |  |
|   | 45.20      | Wash, 30 lks. wide, drains NE.  |  |  |  |
|   | 51.40      | Wash, 70 1ks. wide, drains NE.  |  |  |  |
|   | 59.40      | Wash, 110 lks. wide, drains NE.   |  |  |  |
|   | 71.50      | San Simon Wash, 250 lks. wide, drains irregularly N.  |  |  |  |
|   | 80.28      | Point for the cor. of secs. 1, 6, 31 and 36, Ts. 9 and 10 S., Rs. 27 and 28 E., at proportionate distance; there is no remaining evidence of the original corner. |  |  |  |
|   |            | Set the iron post 24 ins. in the ground, cap mkd.   |  |  |  |
|   |            | T9S<br>R27E R28E  |  |  |  |
|   |            | S36 S31   |  |  |  |
|   |            | S 1 S 6<br>T10S   |  |  |  |
|   |            | 1960  |  |  |  |
|   |            | from which  |  |  |  |
|   |            | U.S. Coast & Geodetic triangulation station TAN, bears N. 64°34'31" W., 70.85 chs. dist.  |  |  |  |
|   |            | The cor. of secs. 25, 30, 31 and 36, T. 9 S., Rs. 27 and 28 E., bears N. 0°16' E., 80.28 chs. dist., described in the field notes of T. 9 S., R. 27 E.            |  |  |  |
| The cor. of secs. 1, 2, 35 and 36, Ts. 9 an R. 27 E., bears S. 89°57' W., 80,60 chs. di |            | The cor. of secs. 1, 2, 35 and 36, Ts. 9 and 10 S., R. 27 E., bears S. 89°57' W., 80,60 chs. dist., described in the field notes of T. 10 S., R. 27 E.            |  |  |  |
| The ½ sec. cor. of secs. 31 and 6, T  |            | The ½ sec. cor. of secs. 31 and 6, Ts. 9 and 10 S.,   |  |  |  |
|   |            | R. 28 E., bears S. 89°41' E., 39.60 chs. dist., described in the field notes hereinafter.   |  |  |  |
|   |            | and little hotes hereihalter.   |  |  |  |
|   | - 1        |   |  |  |  |

FIELD NOTE PAPER 13. CHAINS Resurvey, W. Bdy., T. 10 S., R. 28 E. Land, level. Soil, sandy. Timber, none; undergrowth, cactus, and mesquite. Dependent Resurvey of the North Boundary, T. 10 S., R. 28 E., G&SRM, Arizona Reestablishment of the Survey Executed by L. Wolfley in 1884 From the cor. of Ts. 9 and 10 S., R. 28 E., only; a stone as described in the official record. S. 89°55' W., bet. secs. 1 and 36. Over nearly level land, through scattered undergrowth. Wash, 80 1ks. wide, drains SW. 22.00 Wash, 10 1ks. wide, drains SW. 23.50 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, monumented with a 40.28 volcanic stone as described in the official record. At the corner point Set the iron post 18 ins. in the ground, cap mkd. T9S R28E Bury original cor. stone alongside the iron post. N.  $89^{\circ}58^{\circ}$  W., beginning new measurement. 6.50 Wash, 30 1ks. wide, drains SW. The cor. of secs. 1, 2, 35 and 36, monumented with a 40.44 volcanic stone as described in the official record. At the corner point Set the iron post 6 ins. in the ground, mound with stone to top, cap mkd. T9S R28E S35 S36 S 2 S 1 T10S 1960 Bury original cor. stone alongside iron post. Land, nearly level. Soil, sandy. Timber, none; undergrowth, cactus.

| T      | 14   |  |  |  |  |
|--------|--|--|--|--|--|
| CHAINS | Resurvey, N. Bdy., T. 10 S., R. 28 E.  |  |  |  |  |
|        | West, bet. secs. 2 and 35.   |  |  |  |  |
|        | Over nearly level land, through scattered undergrowth.   |  |  |  |  |
| 40.26  | The ½ sec. cor. of secs. 2 and 35, monumented by a stone as described in the official record.          |  |  |  |  |
|        | At the corner point  |  |  |  |  |
|        | Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.                              |  |  |  |  |
|        | T9S R28E   |  |  |  |  |
|        | ½ S 35<br>X 2<br>T10S  |  |  |  |  |
|        | 1960   |  |  |  |  |
|        | Bury original cor. stone alongside iron post.  |  |  |  |  |
|        | N. 86°49' W., beginning new measurement.   |  |  |  |  |
| 18.70  | Ravine, drains S.; thence enter onto level mesa top.   |  |  |  |  |
| 27.90  | Leave mesa top.  |  |  |  |  |
| 29.50  | Wash, 20 1ks. wide, drains SW.   |  |  |  |  |
| 39.66  | The cor. of secs. 2, 3, 34 and 35, monumented by a volcanic rock as described in the official record.  |  |  |  |  |
|        | At the corner point  |  |  |  |  |
|        | Set the iron post 24 ins. in the ground, cap mkd.  |  |  |  |  |
|        | T 9S R28E<br>S34 S35   |  |  |  |  |
|        | S 3 S 2  |  |  |  |  |
| !      | T10S<br>1960   |  |  |  |  |
|        | Bury original cor. stone alongside iron post.  |  |  |  |  |
|        | Land, nearly level. Soil, sandy gravelly. Timber, none; undergrowth, cactus and creosote brush.        |  |  |  |  |
|        | N. 89°28' W., bet. secs. 3 and 34.   |  |  |  |  |
|        | Over nearly level land, through scattered undergrowth.   |  |  |  |  |
| 0.40   | Wash, 10 lks. wide, drains SW.   |  |  |  |  |
| 17.10  | Small ravine, drains S.  |  |  |  |  |
| 37.30  | Small ravine, drains SW.   |  |  |  |  |
| 39.90  | The ½ sec. cor. of secs. 3 and 34, monumented by a volcanic stone as described in the official record. |  |  |  |  |
|        | At the corner point  |  |  |  |  |
|        | Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.                              |  |  |  |  |
|        | T9S R28E   |  |  |  |  |
|        | $\frac{1}{4} \frac{\text{S34}}{\text{S3}}$   |  |  |  |  |
|        | T10S<br>1960   |  |  |  |  |
| 1      | 1  |  |  |  |  |

#### FIELD NOTE PAPER

|   | CHAINS | Resurvey, N. Bdy., T. 10 S., R. 28 E.   |
|---|--------|---|
|   |        | Bury original cor. stone alongside iron post.   |
| - |        | S. 89°48' W., beginning new measurement.  |
| , | 1.00   | Low spur, slopes S.   |
|   | 1.60   | Small draw, drains S.   |
|   | 37.60  | Wash, 20 1ks. wide, drains SW.  |
|   | 39.89  | The cor. of secs. 3, 4, 33 and 34, monumented by a volcanic rock as described in the official record. |
|   |        | At the corner point   |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | T 9S R28E  S33   S34  S 4   S 3  T10S  1960   |
| - |        | Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.                  |
|   |        | Bury original cor. stone alongside the iron post.   |
| • |        | Land, nearly level. Soil, sandy, gravelly. Timber, none; undergrowth, creosote brush and cactus.      |
|   |        | N. 89°21' W., bet. secs. 4 and 33.  |
|   |        | Over nearly level land, through scattered undergrowth.  |
|   | 2.00   | Wash, 30 1ks. wide, drains SW.  |
|   | 17.20  | Wash, 20 1ks. wide, drains SW.  |
|   | 33.50  | Road, unimproved, bears NE. and SW.   |
|   | 40.00  | The ½ sec. cor. of secs. 4 and 33, monumented by a stone as described in the official record.         |
| • |        | At the corner point   |
|   |        | Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.                            |
|   |        | T9S R28E  1/4 S 33 S 4  |
|   |        | <sup>4</sup> <del>S</del> 4<br>T10S   |
|   |        | 1960  |
| • |        | Bury original cor. stone alongside iron post.   |
| • |        | S. 89°54' W., beginning new measurement.  |
| • | 0.50   | Asc. along W. slope.  |
|   | 1      | 1   |

| T Greature | 16.   |  |  |
|------------|---|--|--|
| CHAINS     | Resurvey, N. Bdy., T. 10 S., R. 28 E.   |  |  |
| 13.00      | Road, unimproved, bears SE. and NW.; end asc.   |  |  |
| 40.10      | Point for the corner of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.                                |  |  |
|            | Set the iron post 14 ins. in the ground, mound with stone to top, cap mkd.  |  |  |
|            | T 9S R28E  S32 S33 S 5 S 4  T10S  1960  |  |  |
|            | Land, nearly level. Soil, sandy. Timber, none; undergrowth, mesquite, creosote bush and cactus.   |  |  |
|            | S. 89°54' W., bet. secs. 5 and 32.  |  |  |
|            | Over level land, through scattered undergrowth.   |  |  |
| 10.34      | Road, unimproved, bears NE. and SW.   |  |  |
| 24.20      | Road, unimproved, bears NW. and SE.   |  |  |
| 39.90      | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 5 and 32.   |  |  |
|            | Set the iron post 6 ins. in the ground, mound with stone to top, cap mkd.   |  |  |
|            | T 9S R28E  W S 32  C 4 S 5  T10S 1960   |  |  |
| 40.10      | True point for the ½ sec. cor. of secs. 5 and 32, at proportionate distance, falls in dry wash, 10 lks. wide, drains SW., where the cor. cannot be perpetuated. |  |  |
| 41.30      | Fence, barbed wire, bears NW. and SE.   |  |  |
| 66.30      | Road, unimproved, bears N. and S.   |  |  |
| 80.21      | Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.                                  |  |  |
|            | Set the iron post 12 ins. in the ground, mound with stone to top, cap mkd.  |  |  |
|            | T 9S R28E S31 S32 S 6 S 5 T10S 1960   |  |  |
|            | Land, level. Soil, sandy, gravelly. Timber, none; undergrowth, cactus.  |  |  |
|            |   |  |  |

BUREAU OF LAND MANAGEMENT FIELD NOTE PAPER 17. **CHAINS** Resurvey, N. Bdy., T. 10 W., R. 28 E. S. 89°54' W., bet. secs. 6 and 31. Over nearly level land, through scattered undergrowth. Road, unimproved, bears N. and S. 0.60 Low spur, slopes SW. 13.30 The  $\frac{1}{4}$  cor. of secs. 6 and 31, monumented by a volcanic 40.10 stone as described in the official record. At the corner point Set the iron post 12 ins. in the ground, mound with stone to top, cap mkd. T 9S R28E **T10S** 1960 N. 89°41' W., beginning new measurement. Wash, 230 1ks. wide, drains SW. 17.00 The cor. of secs. 1, 6, 31 and 36, Ts. 9 and 10 S., 39.60 Rs. 27 and 28 E. Land, nearly level. Soil, gravelly and rocky. Timber, none; undergrowth, creosote brush and cactus. Resurvey, Subdivisions, T. 10 S., R. 28 E., Ariz. Reestablishment of the Survey Executed by J. C. Smith in 1885 From the Stan. Cor. of secs. 35 and 36 on the S. bdy. of the township. N.  $0^{\circ}50^{\circ}$  E., bet. secs. 35 and 36. Over level land, through scattered undergrowth. Fence, barbed wire, bears NE. and SW. 21.30 Road, unimproved, bears NE. and SW. 28.10 Enter into area of swampy land with dense growth of 36.80 tamarisk brush. Fence, barbed wire, bears E. and W. 39.70 Point for the  $\frac{1}{4}$  cor. of secs. 35 and 36, at proportion-40.11 ate distance; there is no remaining evidence of the original corner. Set the iron post 24 ins. in the ground, cap mkd.

| CHAINS | , 18.   |  |  |  |
|--------|---|--|--|--|
|        | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |  |  |  |
|        | T10S_R28E   |  |  |  |
|        | \$\\\\\$35\\\$36\\\\\\\\\$1960  |  |  |  |
| 42.90  | Leave area of dense tamarisk growth.  |  |  |  |
| 44.70  | Road, unimproved, bears E. and W.   |  |  |  |
| 45.60  | Road, unimproved, bears E. and W.   |  |  |  |
| 80.22  | Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.                            |  |  |  |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |  |  |  |
|        | T10S R28E<br><u>S26</u> S25<br>S35 S36<br>1960  |  |  |  |
|        | Land, nearly level. Soil, sandy. Timber, none; undergrowth, mesquite, tamarisk and greasewood.  |  |  |  |
|        | From the cor. of secs. 25, 30, 31 and 36, Rs. 28 and 29 E., on the E. bdy. of the township, monumented by an iron post as described in the official record. |  |  |  |
|        | N. 89°45' W., bet. secs. 25 and 36.   |  |  |  |
|        | Over nearly level land, through scattered undergrowth.  |  |  |  |
| 40.08  | Point for the $\frac{1}{4}$ cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.                      |  |  |  |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |  |
|        | T10S R28E  2 S 25 S 36 1961   |  |  |  |
| 43.10  | Fence, barbed wire, bears N. 50° W. and S. 50° E.   |  |  |  |
| 80.17  | The cor. of secs. 25, 26, 35 and 36.  |  |  |  |
|        | Land, nearly level. Soil, sandy. Timber, none; undergrowth, catclaw and greasewood.   |  |  |  |
|        | North, bet. secs. 25 and 26.  |  |  |  |
|        | Over level land, through scattered undergrowth.   |  |  |  |
| 35.40  | Fence, barbed wire, bears NW. and SE.   |  |  |  |
| 40.11  | Point for the ½ cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.                                  |  |  |  |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |  |
|        | T10S R28E   |  |  |  |
|        | \$26   \$25<br>1960   |  |  |  |
| +      | <b>}</b>  |  |  |  |

|        | FIELD NOTE PAPER 19.  |
|--------|---|
| CHAINS | Resurvey, Subdivisions, T. 10 S ., R. 28 E.   |
| 63.00  | Wash, 80 lks. wide, drains SW.; begin gentle asc.   |
| 73.00  | Low ridge, slopes NE.; gentle desc.   |
| 79.00  | Draw, drains W.   |
| 80.21  | Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.          |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |
|        | T10S R28E<br><u>S23</u> <u>S24</u><br><u>S26</u> <u>S25</u><br>1960   |
|        | Land, level. Soil, sandy, gravelly. Timber, none; undergrowth, mesquite, cactus and creosote brush.                                       |
|        | From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the township, monumented by an iron post as described in the official record. |
|        | N. 89°24' W., bet. secs. 24 and 25.   |
|        | Over nearly level land, through scattered undergrowth.  |
| 23.70  | Top of sandy knob; desc.  |
| 35.50  | Wash, 160 lks. wide, 1 ft. deep, drains SW.   |
| 40.21  | Point for the ½ cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.                |
|        | Set the iron post 16 ins. in the ground, mound with stone to top, cap mkd.  |
|        | T10S R28E  2 S 24  S 25  1960   |
|        | Deposit glass at base of iron post.   |
| 43.80  | Wash, 15 lks. wide, 1 ft. deep, drains SW.  |
| 50.00  | Sandy ridge, bears NE. and SW.; desc.   |
| 80.42  | The cor. of secs. 23, 24, 25 and 26.  |
|        | Land, level. Soil, sandy. Timber, none; undergrowth, creosote brush and cactus.   |
|        | N. 0°05' E., bet. secs. 23 and 24.  |
|        | Over nearly level land, through scattered undergrowth.  |
|        |   |

|  | 20.   |  |
|--|---|--|
| CHAINS   | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |  |
| 40.11  | Point for the ½ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.                             |  |
|  | Set the iron post 26 ins. in the ground, cap mkd.   |  |
|  | T10S_R28E   |  |
|  | \$23   \$24<br>1960   |  |
|  | Deposit glass at base of iron post.   |  |
| 80.21 Point for the cor. of secs. 13, 14, 23 and 24, at portionate distance; there is no remaining eviden the original corner. |   |  |
|  | Set the iron post 24 ins. in the ground, cap mkd.   |  |
|  | T10S R28E<br>S14 S13  |  |
|  | \$23 \$24<br>1960   |  |
|  | Deposit glass at base of iron post.   |  |
|  | Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of the corner.   |  |
|  | Land, nearly level. Soil, sandy. Timber, none; undergrowth, mesquite, cactus and greasewood.  |  |
|  | From the cor. of secs. 13, 18, 19 and 24, Rs. 28 and 29 E., on the E. bdy. of the township, monumented by an iron post as described in the official record. |  |
|  | N. 89°12' W., bet. secs. 13 and 24.   |  |
|  | Over gently rolling land, through scattered undergrowth.  |  |
| 14.40  | Wash, 10 lks. wide, l ft. deep, drains NW.; desc. along W. slope of sandy ridge.  |  |
| 40.37  | Point for the ½ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.                             |  |
|  | Set the iron post 24 ins. in the ground, cap mkd.   |  |
|  | T10S R28E   |  |
|  | $\frac{1}{4} = \frac{S + 13}{S + 24}$ 1961  |  |
|  | Cor. located on sandy SW. slope.  |  |
|  | Gentle desc. from cor.  |  |
| 68.60  | End desc.; begin as. over E. slope.   |  |
| 73.00  | Sandy ridge, slopes NW.; desc. to cor.  |  |
| 80.73  | The cor. of secs. 13, 14, 23 and 24.  Land, gently rolling.  Soil, sandy.  Timber, none; undergrowth, mesquite, cactus and greasewood.                      |  |
|  |   |  |

### FIELD NOTE PAPER

|   | CHAINS     |   |
|---|------------|---|
|   | <b>0.1</b> | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|   |            | N. 0°36' E., 13 and 14.   |
| • |            | Over nearly level land, through scattered undergrowth.  |
| • | 1.70       | Wash, 100 1ks. wide, drains SW.   |
|   | 36.70      | Low spur, slopes W.   |
|   | 40.11      | The ½ sec. cor. of secs. 13 and 14, monumented by a malpais stone as described in the official record.  |
| : |            | At the corner point   |
|   |            | Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.  |
|   |            | T10S R23E   |
|   |            | \$14   \$13<br>1960   |
|   |            | N. 0°35' E., beginning new measurement.   |
|   | 9.50       | Wash, 100 lks. wide, drains SW.   |
|   | 38.25      | Ridge, bears N. and S.; desc. N. slope.   |
|   | 40.18      | The cor. of secs. 11, 12, 13 and 14, monumented by a malpais stone as described in the official record.   |
| - |            | At the corner point   |
| • | ·          | Set the iron post 14 ins. in the ground, mound with stone to top, cap mkd.  |
| • |            | T10S R28E  S11 S12  S14 S13   |
|   |            | 1960  |
|   |            | Land, nearly level. Soil, sandy and gravelly. Timber, none; undergrowth, cactus, mesquite and greasewood.   |
|   |            | From the true point for the cor. of secs. 12 and 13 only, on the E. bdy. of the township. The W. C. bears N. 2°16' W., 0.40 chs. dist., monumented by an iron post as described in the official record. |
|   |            | N. 89°33' W., bet. secs. 12 and 13.   |
|   |            | Over gently rolling land, through scattered undergrowth.  |
|   | 2.30       | Wash, 15 lks. wide, drains irregularly SW.  |
|   | 37.00      | Wash, 40 lks. wide, drains SW.  |
|   | 39.38      | Point for the 2 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.   |
|   |            | Set the iron post 12 ins. in the ground, mound with stone to top, cap mkd.  |
|   |            |   |
| • |            | •   |

| CHAINS |   |  |  |
|--------|---|--|--|
|        | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |  |  |
|        | T10S R28E   |  |  |
|        | $\frac{1}{4} \frac{S}{S} \frac{12}{13}$   |  |  |
|        | 1961  |  |  |
| 54.00  | Wash, 30 lks. wide, 2 ft. deep, drains SW.  |  |  |
| 65.30  | Wash, 20 lks. wide, 2 ft. deep, drains SW.  |  |  |
| 77.40  | Wash, 15 lks. wide, 2 ft. deep, drains SE.  |  |  |
| 78.76  | The cor. of secs. 11, 12, 13 and 14.  |  |  |
|        | Land, gently rolling. Soil, gravelly and rocky. Timber, none; undergrowth, mesquite, cactus, greasewood and creosote brush. |  |  |
|        | N. 0°21' W., bet. secs. 11 and 12.  |  |  |
|        | Over rolling land, through scattered undergrowth.   |  |  |
| 2.30   | Draw, drains E.   |  |  |
| 3.00   | Draw, drains SE.; asc. S. slope of mesa.  |  |  |
| 14.50  | Mesa top, thence over gentle desc.  |  |  |
| 21.70  | Wash, 10 lks. wide, drains W.   |  |  |
| 38.50  | Low spur, slopes W.   |  |  |
| 40.04  | The ½ sec. cor. of secs. 11 and 12, monumented by a malpais stone as described in the official record.                      |  |  |
|        | At the corner point   |  |  |
|        | Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.  |  |  |
|        | T10S R28E   |  |  |
|        | S11 S12<br>1960   |  |  |
|        | N. 5°34' W., beginning new measurement.   |  |  |
| 6.00   | Wash, 100 1ks. wide, drains SW.   |  |  |
| 19.10  | Fence, barbed wire, bears W. and SE.  |  |  |
| 40.42  | The cor. of secs. 1, 2, 11 and 12, monumented by a malpais stone as described in the official record.                       |  |  |
|        | At the corner point   |  |  |
|        | Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.  |  |  |
|        | T10S R28E  S 2 S 1  S11 S12  1960   |  |  |
|        | Land, rolling. Soil, rocky. Timber, none; undergrowth, mesquite, creosote brush and cactus.                                 |  |  |

### FIELD NOTE PAPER

|   |        | 23.   |
|---|--------|---|
|   | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
| • |        | From the cor. of secs. 1 and 12 only, R. 28 E., on the E. bdy. of the township, monumented by an iron post as described in the official record. |
| • |        | N. 89°25' W., bet. secs. 1 and 12.  |
|   |        | Over gently rolling land, through sparse undergrowth.   |
|   | 2.20   | Wash, 100 1ks. wide, 1 ft. deep, drains SW.   |
|   | 39.70  | The ½ sec. cor. of secs. 1 and 12, monumented by a malpais stone, as described in the official record.  |
|   |        | At the corner point   |
|   |        | Set the iron post 20 ins. in the ground, mound with stone to top, cap mkd.  |
|   |        | T10S R28E  2 S 1  S 12  1961  |
|   |        | N. 89°24' W., beginning new measurement.  |
|   | 18.50  | Wash, 100 lks. wide, 1 ft. deep, drains approx. S. $10^{\circ}$ W.  |
|   | 41.13  | The cor. of secs. 1, 2, 11 and 12.  |
| • |        | Land, gently rolling. Soil, gravelly and rocky. Timber, none; undergrowth, cactus and mesquite.   |
|   |        | N. 0°43' W., bet. secs. 1 and 2.  |
|   |        | Over level land, through scattered undergrowth.   |
|   | 2.50   | Shallow wash, 20 lks. wide, drains W.   |
|   | 23.10  | Shallow wash, 20 lks. wide, drains SW.  |
|   | 35.70  | Wash, 220 1ks. wide, 2 ft. deep, drains SW.   |
|   | 39.74  | The ½ sec. cor. of secs. 1 and 2, monumented by a malpais stone as described in the official record.  |
|   |        | At the corner point   |
|   |        | Set the iron post 5 ins. in the ground, mound with stone to top, cap mkd.   |
|   |        | T10S R28E   |
|   |        | S2   S1<br>1960   |
|   |        | N. 0°54' W., beginning new measurement.   |
|   | 10.70  | Wash, 10 1ks. wide, drains SW.  |
|   | 39.51  | The cor. of secs. 1, 2, 35 and 36, Ts. 9 and 10 S., on the N. bdy. of the township.   |
| • |        |   |

| <del></del> | 24.  |  |  |
|-------------|--|--|--|
| CHAINS      | Resurvey, Subdivisions, T. 10 S., R. 28 E.   |  |  |
|             | Land, nearly level. Soil, sandy. Timber, none; undergrowth, mesquite, cactus and creosot brush.                                    |  |  |
|             | From the Stan. Cor. of secs. 34 and 35 on the S. bdy. of the township.   |  |  |
|             | N. 0°08' E., bet. secs. 34 and 35.   |  |  |
|             | Over gently rolling land, through scattered undergrowth.   |  |  |
| 16.80       | Wash, 30 lks. wide, 1 ft. deep, drains N. 40° E.   |  |  |
| 17.80       | Road, unimproved, bears generally E. and W.  |  |  |
| 25.60       | Wash, 20 lks. wide, 1 ft. deep, drains E.  |  |  |
| 38.90       | Small ravine, drains NE.   |  |  |
| 40.18       | Point for the ½ sec. cor. of secs. 34 and 35, at proportionate distance; there being no remaining evidence of the original corner. |  |  |
|             | Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.   |  |  |
|             | T10S R28E  |  |  |
|             | S34 S35<br>1961  |  |  |
|             | Corner located on rocky NW. slope of low ridge.  |  |  |
| 59.80       | Wash, 30 lks. wide, 2 ft. deep, drains NE.   |  |  |
| 68.70       | San Simon Wash, 80 lks. wide, 5 ft. deep, drains W.  |  |  |
| 80.35       | Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.   |  |  |
|             | Set the iron post 24 ins. in the ground, cap mkd.  |  |  |
|             | T10S R28E<br><u>S27   S26</u><br><u>S34   S35</u><br>1961  |  |  |
|             | Deposit glass at base of iron post.  |  |  |
|             | Land, gently rolling. Soil, rocky. Timber, none; undergrowth, creosote brush and cactus.   |  |  |
|             |  |  |  |
|             | From the cor. of secs. 25, 26, 35 and 36.  |  |  |
|             | N. 89°47' W., bet. secs. 26 and 35.  |  |  |
|             | Over nearly level land, through scattered undergrowth.   |  |  |
| 33.80       | Wash, 20 1ks. wide, 1 ft. deep, drains SW.   |  |  |
| 40.16       | Point for the ½ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.    |  |  |
|             |  |  |  |

#### FIELD NOTE PAPER

|   | CHAINS |   |
|---|--------|---|
| - | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | T10S R28E $\frac{5.26}{5.35}$   |
|   |        | <sup>3</sup> S 35<br>1960   |
|   | 50.30  | Fence, barbed wire, bears S. $20^{\circ}$ E. and N. $20^{\circ}$ W.   |
|   | 60.20  | Wash, 10 lks. wide, drains SW.  |
|   | 80.33  | The cor. of secs. 26, 27, 34 and 35.  |
|   |        | Land, nearly level. Soil, rocky. Timber, none; undergrowth, cactus and catclaw.   |
|   |        | N. 0°04' W., bet. secs. 26 and 27.  |
|   |        | Over nearly level land, through scattered undergrowth.  |
|   | 11.00  | Wash, 40 lks. wide, 3 ft. deep, drains NW.  |
|   | 14.00  | Wash, 15 lks. wide, 2 ft. deep, drains W.   |
|   | 31.60  | Wash, 20 1ks. wide, 2 ft. deep, drains SW.  |
| • | 35.20  | Wash, 30 1ks. wide, 3 ft. deep, drains SW.  |
| • | 40.17  | True point for the ½ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Corner point falls in shallow wash where it cannot be perpetuated. Wash drains SW. |
|   | 40.87  | Point selected for witness $\frac{1}{4}$ sec. cor. of secs. 26 and 27.  |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | T10S R28E   |
|   |        | S27 S26<br>W C  |
|   |        | 1961  |
|   | 50.05  | Fence, barbed wire, bears NW. and SE.   |
|   | 60.00  | Road, unimproved, bears NW. and SE.   |
|   | 76.20  | Wash, 10 1ks. wide, 1 ft. deep, drains SW.  |
|   | 80.35  | Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.  |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | T10S R28E<br><u>S22</u> <u>S23</u><br>S27 <u>S26</u><br>1961  |
| • |        |   |

| - | CHAINS |  |
|---|--------|--|
|   | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.   |
|   |        | Land, nearly level.  |
|   |        | Soil, sandy clay. Timber, none; undergrowth, cactus and catclaw.   |
|   |        |  |
|   |        | From the cor. of secs. 23, 24, 25 and 26.  |
|   |        | N. 89°42° W., bet. secs. 23 and 26.  |
|   |        | Over level land, through scattered undergrowth.  |
|   | 21.90  | Fence, 4 strand barbed wire, bears NW. and SE.   |
|   | 40.21  | Point for the ½ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.  |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.  |
|   |        | T10S R28E  |
|   |        | ½ <u>\$ 23</u><br>\$ 26  |
|   |        | 1961   |
|   |        | Continue over nearly level land.   |
|   | 80.41  | The cor. of secs. 22, 23, 26 and 27.   |
|   |        | Land, level. Soil, sandy clay. Timber, none; undergrowth, greasewood and cactus.   |
|   |        | N. 0°12 W., bet. secs. 22 and 23.  |
|   |        | Over level land, through sparse undergrowth.   |
|   | 22.90  | Fence, barbed wire, bears SE. and NW.  |
|   | 26.20  | Wash, 80 lks. wide, 5 ft. deep, drains SW.   |
|   | 40.17  | Point for the ½ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.  |
|   |        | T10S R28E  |
|   |        | \$22 \big  \$23<br>1961  |
|   | 54.50  | Wash, 10 1ks. wide, 1 ft. deep, drains SW.   |
|   | 67.50  | Wash, 60 lks. wide, 2 ft. deep, drains W.  |
|   | 69.80  | Wash, 50 1ks. wide, 2 ft. deep, drains W.  |
|   | 80.35  | Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.  |
|   |        | T10S R28E <u>S15   S14</u> S22   S23  1961   |
|   |        |  |
|   | 1      | ı  |

#### FIELD NOTE PAPER

|   |        | 27.   |
|---|--------|---|
|   | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|   |        | Land, level.  |
|   |        | Soil, sandy. Timber, none; undergrowth, cactus.   |
|   |        | From the cor. of secs. 13, 14, 23 and 24.   |
|   |        | N. 89°32' W., bet. secs. 14 and 23.   |
|   |        | Over nearly level land, through scattered undergrowth.  |
|   | 3.30   | Wash, 60 lks. wide, 5 ft. deep, drains SW.  |
|   | 16.20  | Wash, 180 lks. wide, 2 ft. deep, drains SW.   |
|   | 40.38  | Point for the 4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.   |
|   |        | T10S R28E   |
|   |        | ½ S 14<br>S 23<br>1961  |
|   |        | Deposit glass at base of iron post.   |
|   | 41.90  | Wash, 20 lks. wide, 2 ft. deep, drains SE.  |
| - | 63.90  | Wash, 30 lks. wide, 1 ft. deep, drains SW.  |
|   | 80.77  | The cor. of secs. 14, 15, 22 and 23.  |
|   |        | Land, nearly level. Soil, sandy. Timber, none; undergrowth, catclaw and cactus.   |
|   |        | N. 0°41 E., bet. secs. 14 and 15.   |
|   |        | Over nearly level land, through sparse undergrowth.   |
|   | 2.10   | Wash, 20 lks. wide, 1 ft. deep, drains SW.  |
|   | 30.00  | Wash, 20 1ks. wide, 1 ft. deep, drains SW.  |
| - | 34.10  | Wash, 20 1ks. wide, 2 ft. deep, drains SW.  |
|   | 40.18  | Point for the % sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. |
|   |        | Set the iron post 25 ins. in the ground, cap mkd.   |
|   |        | T10S R28E   |
|   |        | 玄<br>S15 S14<br>1961  |
|   | ·      | Asc. S. slope of low spur.  |
| • | 48.90  | Low spur, bears NE. and SW.   |
| • | 54.60  | Wash, 10 lks. wide, drains SW.  |
|   |        |   |

|        | 28.   |
|--------|---|
| CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
| 76.40  | Wash, 15 lks. wide, drains NW.  |
| 80.35  | Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.                                      |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E  S10   S11  S15   S14  1961   |
|        | Land, nearly level. Soil, sandy clay. Timber, none; undergrowth, desert vegetation.   |
|        | From the cor. of secs. 11, 12, 13 and 14.   |
|        | N. 89°25 W., bet. secs. 11 and 14.  |
|        | Over rolling land, through undergrowth.   |
| 4.70   | Top of mesa, bears N. and S.  |
| 8.70   | Wash, 20 lks. wide, 1 ft. deep, drains S.   |
| 14.90  | Spur, slopes SE.  |
| 21.60  | Wash, 10 lks. wide, 2 ft. deep, drains SE.  |
| 40.25  | Point for the $\frac{1}{4}$ sec. cor. of sec. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.                            |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E  2 S 11 S 14 1961   |
|        | Raise a mound of stone N. of cor.   |
| 80.50  | The cor. of secs. 10, 11, 14 and 15.  |
|        | Land, rolling. Soil, sandy and rocky. Timber, none; undergrowth, catclaw, creosote, yucca and cactus.   |
|        | N. 2°30' W., bet. secs. 10 and 11.  |
|        | Over rolling land, through desert undergrowth.  |
| 0.23   | Wash, 10 lks. wide, 1 ft. deep, drains SW.  |
| 13.60  | Wash, 30 lks. wide, 1 ft. deep, drains W.   |
| 16.00  | Wash, 60 lks. wide, 2 ft. deep, drains NW.  |
| 33.00  | Wash, 5 lks. wide, 1 ft. deep, drains W.  |
| 40.22  | Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Falls in wash, drains SW. |
| 40.42  | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 10 and 11.  |

#### FIELD NOTE PAPER

| · |        | FIELD NOTE PAPER   | 29. |
|---|--------|--|-----|
|   | CHAINS | Resurvey, Subdivisions, T . 10 S., R. 28 E.  |     |
|   |        | Set the iron post 24 ins. in the ground, cap mkd.  |     |
|   |        | T10S_R28E  |     |
|   |        | $\begin{array}{c} S10 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$   |     |
|   |        | 1961   |     |
|   |        | Raise a mound of stone N. of corner.   |     |
|   | 61.60  | Wash, 60 lks. wide, 1 ft. deep, drains W.  |     |
|   | 65.10  | Fence, bears E. and W.   |     |
|   | 69.20  | Wash, 40 lks. wide, 3 ft. deep, drains S. 60° W.   |     |
|   | 75.40  | Wash, 50 lks. wide, 3 ft. deep, drains W.  |     |
|   | 80.43  | Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. | f   |
|   |        | Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.   |     |
|   |        | T10S R28E  S 3 S 2  S10   S11  1961  |     |
|   |        | Corner falls on the S. slope of mesa.  |     |
|   |        | Land, rolling. Soil, rocky. Timber, none; undergrowth, creosote, catclaw, yucca and greasewood.                                |     |
|   |        | From the cor. of secs. 1, 2, 11 and 12.  |     |
|   |        | N. 89°21' W., bet. secs. 2 and 11.   |     |
|   | 1      | Over rolling land, through scattered undergrowth.  |     |
|   | 40.15  | The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented by a stone, as described in the official record.                     |     |
|   |        | At the corner point  |     |
|   |        | Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.   |     |
|   |        | T10S R28E  |     |
|   |        | ½ S 2<br>S 11<br>1961  |     |
|   |        | 1701   |     |
| : |        | N. 89°04' W., beginning new measurement.   |     |
|   | 39.68  | The cor. of secs. 2, 3, 10 and 11.   |     |
|   |        | Land, rolling.<br>Soil, sandy clay and rocky.  |     |
|   |        | Timber, none; undergrowth, sagebrush and wormwood.   |     |
|   |        |  |     |

|        | 300   |
|--------|---|
| CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|        | N. 0°51 W., bet. secs. 2 and 3.   |
|        | Over rolling land, through desert undergrowth.  |
| 10.70  | Wash, 10 1ks. wide, 1 ft. deep, drains NW.  |
| 11.20  | Wash, 40 lks. wide, 2 ft. deep, drains W.   |
| 12.10  | Wash, 10 1ks. wide, 1 ft. deep, drains SW.  |
| 27.40  | Wash, 10 1ks. wide, 2 ft. deep, drains W.   |
| 38.20  | Wash, 10 1ks. wide, 3 ft. deep, drains W.   |
| 40.18  | Point for the ½ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.   |
|        | Set the iron post 22 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | S3   S2<br>1961   |
|        | Raise a mound of stones W. of corner.   |
| 46.10  | Top of knoll, bears S. 45° W., desc. N. slope.  |
| 52.10  | Wash, 25 lks. wide, 3 ft. deep, drains NW.  |
| 54.90  | Wash, 60 lks. wide, 3 ft. deep, drains W.   |
| 60.40  | Wash, 60 lks. wide, 2 ft. deep, drains W.; asc. S. slope over rolling ridges.   |
| 80.22  | The cor. of secs. 34, 35, 2 and 3, on the N. bdy. of the township.  |
|        | Land, rolling. Soil, rocky. Timber, none; undergrowth, creosote, catclaw and cactus.  |
|        | From the true point of secs. 33 and 34, on the S. bdy. of the township.   |
|        | N. 0°09' W., bet. secs. 33 and 34.  |
|        | In the bottom of Gold Gulch   |
| 8.30   | NW. rim of Gold Gulch, 380 lks. wide, 15 ft. deep, drains irregularly N.; continue along W. edge of Gold Gulch.                 |
| 29.00  | Gold Gulch wash, 400 lks. wide, 15 ft. deep, drains irregularly N.  |
| 40.18  | Point for the ½ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | \$33 \$34<br>1961   |
|        | Deposit glass at base of iron post.   |

| 2 | 1 |
|---|---|
| _ | 1 |
| _ | _ |

|   |        | 31.   |
|---|--------|---|
|   | CHAINS | Resurvey, Subdivisions, T. 10 S ., R. 28 E.   |
| • | 49.50  | Drainage ditch, 8 lks. wide, 1 ft. deep, drains NW.   |
| • | 74.37  | Point selected for the witness cor. of secs. 27, 28, 33 and 34.   |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.   |
|   |        | T10S R28E<br><u>\$28</u>   \$27<br><del>\$33</del>   \$34<br>1961   |
|   |        | Deposit glass at base of iron post.   |
|   | 80.37  | Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; fall in Gold Gulch Wash, not suitable for permanent monument. |
|   |        | Land, level and eroded. Soil, clay and loam. Timber, none; undergrowth, catclaw, yucca, greasewood and creosote brush.                  |
|   |        | From the cor. of secs. 26, 27, 34 and 35.   |
| - |        | N. 89°50' W., bet. secs. 27 and 34.   |
| • |        | Over level to rolling land, through scattered under-<br>growth.   |
|   | 18.50  | Center of San Simon Wash, 550 lks. wide, 4 ft. deep, drains NW.   |
|   | 30.90  | Wash, 150 lks. wide, 6 ft. deep, drains NE.   |
|   | 40.14  | Point for the ½ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.         |
|   |        | Set the iron post 24 ins. in the ground, mound with stone to top, cap mkd.  |
|   |        | T10S R28E  2 S 27  S 34  1961   |
|   | 55.20  | Enter bare clay flat; nearly level.   |
|   | 78.00  | E. bank of Gold Gulch, bears N. 15° E. and S. 15° W.  |
|   | 80.29  | True point for the cor. of secs. 27, 28, 33 and 34.   |
|   |        | Land, level to rolling. Soil, sandy and clay. Timber, none; undergrowth, creosote brush.  |
|   |        | N. 0°08' W., bet. secs. 27 and 28.  |
|   |        | Over level to rolling land, through desert undergrowth.   |
|   | 3.00   | Leave Gold Gulch Wash, drains NE.   |
|   | 7.47   | Fence, bears E. and W.  |
| • |        |   |

| 1                       |  |
|-------------------------|--|
| CHAINS                  | Resurvey, Subdivisions, T. 10 S., R. 28 E.   |
| 16.40                   | Enter rolling hills.   |
| 18.40                   | Spur, bears E. and W.  |
| 30.20                   | Wash, drains NE.   |
| 33.40                   | Top of spur, projects E. and W.  |
| 40.18                   | Point for the ½ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.  |
|                         | Set the iron post 22 ins. in the ground, cap mkd.  |
|                         | T10S_R28E  |
|                         | S28   S27<br>1961  |
|                         | Deposit glass at base of iron post.  |
| 49.80                   | Center of San Simon Wash, 160 lks. wide, drains W.   |
| 66.50<br>77.00<br>80.37 | Fence, bears NE. and SW. Fence, bears NW. and SE. Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. |
|                         | Set the iron post 20 ins. in the ground, cap mkd.  |
|                         | T10S R28E  S21 S22  S28 S27  1961  |
|                         | Deposit glass at base of iron post.  |
|                         | Land, level to rolling, badly eroded. Soil, clay and sand. Timber, none; undergrowth, catclaw, greasewood and willows.   |
|                         | From the cor. of secs. 22, 23, 26 and 27.  |
|                         | N. 89°53' W., bet. secs. 22 and 27.  |
|                         | Over nearly level land, through scattered undergrowth.   |
| 35.90                   | Road, unimproved, bears NW. and SE.  |
| 40.18                   | Point for the ½ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.  |
|                         | Set the iron post 24 ins. in the ground, cap mkd.  |
|                         | T10S R28E  1/4 S 22  |
|                         | Deposit glass at base of iron post.  |
| 80.36                   | The cor. of secs. 21, 22, 27 and 28.   |
|                         |  |

#### FIELD NOTE PAPER

| CHAINS | Resurvey, Subdivisions, T. 10 S. R. 28 E.  |
|--------|--|
|        | Land, nearly level. Soil, sand and clay. Timber, none; undergrowth, catclaw, greasewood and yucca.                               |
|        | N. 0°25 W., bet. secs. 21 and 22.  |
|        | Over nearly level land, through scattered undergrowth.   |
| 34.50  | Fence, bears NE. and SW.   |
| 39.10  | Road, unimproved, bears E. and W.  |
| 40.18  | Point for the ½ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.  |
|        | Set the iron post 20 ins. in the ground, cap mkd.  |
|        | T10S_R28E  |
|        | \$21<br> \$22<br>1961  |
|        | Deposit glass at base of iron post.  |
| 42.80  | Wash, 10 lks. wide, 1 ft. deep, drains SW.   |
| 44.80  | Wash, 10 lks. wide, 1 ft. deep, drains SW.   |
| 64.40  | Wash, 10 lks. wide, 1 ft. deep, drains SW.   |
| 80.37  | Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 26 ins. in the ground, cap mkd.  |
|        | T10S R28E  S16 S15  S21 S22  1961  |
|        | Deposit glass at base of iron post.  |
|        | Land, nearly level.  |
|        | Soil, clay. Timber, none; undergrowth, greasewood, Spanish bayonet.  |
|        | From the cor. of secs. 14, 15, 22 and 23.  |
|        | N. 89°50' W., bet. secs. 15 and 22.  |
|        | Over nearly level land, through scattered undergrowth.   |
| 40.32  | Point for the ½ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.  |
|        | Set the iron post 26 ins. in the ground, cap mkd.  |
|        |  |
| i      | 1  |

| CHAINS |   |
|--------|---|
|        | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|        | #10C P00E   |
|        | T10S R28E  1 S 15 2 S 22  |
|        | <sup>4</sup> S 22<br>1961   |
|        | Deposit glass at base of iron post.   |
| 58.30  | Wash, 20 lks. wide, 1 ft. deep, drains SW.  |
| 80.65  | The cor. of secs. 15, 16, 21 and 22.  |
|        | Land, nearly level.   |
|        | Soil, sandy. Timber, none; undergrowth, yucca, catclaw.   |
|        |   |
|        | N. 0°49' E., bet. secs. 15 and 16.  |
|        | Over gently rolling land, through dense undergrowth.  |
| 29.00  | Top of spur, slopes SW.   |
| 40.19  | Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 22 ins. in the ground, cap mkd.   |
|        | T10S_R28E   |
|        | \$16   \$15<br>1961   |
|        | Deposit glass at base of iron post.   |
|        | Raise a mound of stone W. of corner.  |
| 44.10  | Wash, 10 lks. wide, 1 ft. deep, drains W.   |
| 48.90  | Spur, slopes W.   |
| 61.00  | Wash, 20 lks. wide, 1 ft. deep, drains SW.  |
| 68.90  | Spur, slopes SW.  |
| 77.90  | Wash, 100 1ks. wide, 2 ft. deep, drains SW.   |
| 80.38  | The cor. of secs. 9, 10, 15 and 16, monumented by a stone as described in the official record.  |
|        | At the corner point   |
|        | Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.   |
|        | T10S R28E<br>S 9 S10  |
|        | S16 S15<br>1961   |
|        | Land, gently rolling.<br>Soil, sandy and clay.  |
|        | Timber, none; undergrowth, creosote, catclaw, cactus and yucca.   |
|        |   |
|        |   |

### FIELD NOTE PAPER

| CHAINS |   |
|--------|---|
|        | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|        | From the cor. of secs. 10, 11, 14 and 15.   |
|        | N. 89°53' W., bet. secs. 10 and 15.   |
| 7.50   | Spur, slopes S.   |
| 39.83  | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 10 and 15.  |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E  2  |
|        | Deposit glass at base of iron post.   |
| 40.28  | Point for the ½ sec. cor. of secs. 10 and 15, at proportionate distance; falls in a small wash draining irregularly SW. Not monumented. |
| 47.90  | Wash, 20 lks. wide, 1 ft. deep, drains SW.  |
| 55.20  | Spur, slopes S.   |
| 63.40  | Ridge, bears NE. and SW.  |
| 74.10  | Wash, 130 lks. wide, 4 ft. deep, drains S. 70° W.   |
| 80.56  | The cor. of secs. 9, 10, 15 and 16.   |
|        | Land, rolling. Soil, sandy and rocky. Timber, none; undergrowth, catclaw, creosote, greasewood, yucca and cactus.                       |
|        | N. 0°12' E., bet. secs. 9 and 10.   |
|        | Over gently rolling land, through desert undergrowth.   |
| 16.50  | Wash, 30 lks. wide, 1 ft. deep, drains SW.  |
| 40.06  | The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented by a stone, as described in the official record.                              |
|        | At the corner point   |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | s 9 s 10<br>1961  |
|        | N. 3°32" W., beginning new measurement.   |
| 0.50   | Wash, 15 lks. wide, 1 ft. deep, drains SE.  |
|        | Top of knoll.   |

| T      | j  |
|--------|--|
| CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.   |
| 25.00  | Wash, 15 lks. wide, 1 ft. deep, drains NW.   |
| 32.70  | Sandstone spur, slopes W.  |
| 40.23  | Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.  |
|        | Set the iron post 26 ins. in the ground, cap mkd.  |
|        | T10S R28E <u>S 4   S 3</u> S 9   S 10  196 1   |
|        | Land, gently rolling. Soil, sandy. Timber, none; undergrowth, yucca, creosote, greasewood and catclaw.                         |
|        | From the cor. of secs. 2, 3, 10 and 11.  |
|        | N. 89°52' W., bet. secs. 3 and 10.   |
|        | Over gently rolling land, through desert undergrowth.  |
| 6.20   | Wash, 100 lks. wide, 2 ft. deep, drains NW.  |
| 10.10  | Wash, 40 lks. wide, 2 ft. deep, drains SW.   |
| 14.80  | Wash, 30 lks. wide, 2 ft. deep, drains NW.   |
| 34.00  | Wash, 20 1ks. wide, 1 ft. deep, drains NW.   |
| 39.71  | Point for the ½ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 22 ins. in the ground, mound with stone to top, cap mkd.   |
|        | T10S R28E  |
|        | 1 S 3 S 10   |
|        | 1961   |
| 68.30  | Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.   |
| 74.10  | Fence, bears N. 55° W. and S. 55° E.   |
| 79.42  | The cor. of secs. 3, 4, 9 and 10.  |
|        | Land, gently rolling. Soil, sand and clay. Timber, none; undergrowth, sagebrush, greasewood and yucca.                         |
|        | N. 0°58' W., bet. secs. 3 and 4.   |
|        | Over rolling land, through scattered undergrowth.  |
| 0.50   | Wash, 15 lks. wide, 1 ft. deep, drains W.  |
| 2.90   | Fence, bears NW. and SE.   |
| 10.20  | Wash, 15 lks. wide, 1 ft. deep, drains irregularly W.  |
|        |  |

FIELD NOTE PAPER 37. **CHAINS** Resurvey, Subdivisions, T. 10 S., R. 28 E. 20.70 Wash, 10 1ks. wide, 1 ft. deep, drains NW. 40.16 Point for the 4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 26 ins. in the ground, cap mkd. T10S R28E ½ S4|S3 41.60 Wash, 30 1ks. wide, 1 ft. deep, drains NW. Wash, 230 lks. wide, 2 ft. deep, drains W. 47.30 65.80 Top of mesa. 79.00 Wash, 20 lks. wide, 3 ft. deep, drains irregularly W. The cor. of secs. 33, 34, 3 and 4, on the N. bdy. of 80.42 the township. Land, rolling. Soil, sandy. Timber, none; undergrowth, yucca, catclaw, greasewood, cactus, creosote and Spanish bayonet. From the cor. of secs. 32 and 33, on the S. bdy. N.  $0^{\circ}20^{\circ}$  E., bet. secs. 32 and 33. Over gently rolling land, through desert undergrowth. 22.30 Wash, 10 1ks. wide, 1 ft. deep, drains SW. 35.60 Wash, 20 1ks. wide, 1 ft. deep, drains SW. The  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, monumented by a 40.25 stone, as described in the official record. At the corner point Set the iron post 20 ins. in the ground, cap mkd. T10S R28E S32 S33 1961 N.  $0^{\circ}13$ ' E., beginning new measurement. 6.10 Wash, 10 1ks. wide, 1 ft. deep, drains W. 26.20 Wash, 100 lks. wide, 1 ft. deep, drains S. 30° W. 40.18 The cor. of secs. 28, 29, 32 and 33, monumented by a wood post as described in the official record. At the corner point Set the iron post 20 ins. in the ground, cap mkd.

| CHAINS |   |
|--------|---|
|        | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|        | T10S R28E<br><u>S29   S28</u><br><u>S32   S33</u><br>1961   |
|        | Land, gently rolling. Soil, sandy and rocky. Timber, none; undergrowth, creosote and yucca.   |
|        | From the true point for the cor. of secs. 27, 28, 33, 34.   |
|        | N. 89°37' W., bet. secs. 28 and 33.   |
|        | Over rolling land, through desert undergrowth.  |
|        | Asc. E. slope of mesa.  |
| 19.00  | Edge of mesa.   |
| 34.40  | Wash, 20 1ks. wide, 2 ft. deep, drains N.   |
| 40.14  | Point for the 2 sec. cor. of secs. 28 and 33, at proproportionate distance; there is no remaining evidence of the original corner.  |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | $\frac{1}{4} = \frac{S}{S} = \frac{28}{33}$   |
|        | 1961  |
|        | Deposit glass at base of iron post.   |
| 64.10  | Wash, 40 lks. wide, 2 ft. deep, drains N.   |
| 76.90  | Wash, 20 lks. wide, 1 ft. deep, drains N.   |
| 80.29  | The cor. of secs. 28, 29, 32 and 33.  |
|        | Land, gently rolling. Soil, sandy. Timber, none; undergrowth, creosote.   |
|        | N. 0°06' W., bet. secs. 28 and 29.  |
|        | Over gently rolling land, through scattered undergrowth.  |
| 6.40   | Wash, 20 lks. wide, 1 ft. deep, drains NE.  |
| 11.00  | Enter wash area, drains N. from SW., continue in wash area.   |
| 27.00  | Leave wash area, drains NE. from S.   |
| 33.50  | Wash, 20 1ks. wide, 3 ft. deep, drains NE.  |
| 37.90  | Fence, bears N. 70° W. and S. 70° E.  |
| 40.10  | The 4 sec. cor. of secs. 28 and 29, monumented by a wood stake as described in the official record.   |
|        | At the corner point   |
|        | Set the iron post 20 ins. in the ground, cap mkd.   |
|        | See the 11th past to the company of |

|        | FIELD NOTE PAPER  |
|--------|---|
| CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|        | T10S R28E   |
|        | \$\frac{1}{2}\$\$\$S29\S28\$\$\$1961  |
|        | Deposit glass at base of iron post.   |
|        | N. 0°12' W., beginning new measurement.   |
| 10.10  | Wash, 20 1ks. wide, 1 ft. deep, drains N. 30° E.  |
| 38.71  | Wash, 200 1ks. wide, 20 ft. deep, drains N. 20° E.  |
| 40.04  | The cor. of secs. 20, 21, 28 and 29, monumented by a stone as described in the official record. Point falls on edge of large wash, not suitable for permanent monument. |
|        | Land, gently rolling. Soil, rocky and sandy. Timber, none; undergrowth, creosote and yucca.   |
|        | From the cor. of secs. 21, 22, 27 and 28.   |
|        | N. 89°51' W., bet. secs. 21 and 28.   |
|        | Over gently rolling land, through dense undergrowth.  |
| 3.80   | Fence, bears NW. and SE.  |
| 36.40  | San Simon Wash, main channel, 200 1ks. wide, 3 ft. deep, drains NW.; continue in flood area.  |
| 40.17  | Point for the ½ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.   |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E  2 S 21 S 28 1961   |
|        | Deposit glass at base of iron post.   |
|        | Raise a mound of stone N. of corner.  |
|        | Continue in flood bottom land.  |
| 80.34  | The true point for corner of secs. 20, 21, 28 and 29.   |
|        | Land, level and eroded. Soil, clay and sand. Timber, none; undergrowth, willows and greasewood.   |
|        | N. 0°03' E., bet. secs. 20 and 21.  |
|        | Over gently rolling land, through desert undergrowth.   |
| 1.00   | Point selected for the witness cor. of secs. 20, 21, 28 and 29.   |
|        | Set the iron post 22 ins. in the ground, mound with stone to top, cap mkd.  |

| CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|--------|---|
|        | T10S R28E   |
|        | \$20   \$21   |
|        | S29 S28   |
|        | wc  |
| 18.00  | Thence along W. bank of a wash.   |
| 24.20  | Wash, 150 lks. wide, 20 ft. deep, drains N. 30° E.  |
| 35.90  | San Simon Wash, 200 lks. wide, 20 ft. deep, drains<br>N. 30° W.   |
| 41.51  | The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented by a wood stake as described in the official record. |
|        | At the corner point   |
|        | Set the iron post 20 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | 12  |
|        | S20 S21<br>1961   |
|        |   |
|        | N. 1°48' W., beginning new measurement.   |
| 13.50  | Road, unimproved, bears SE. and NW.   |
| 19.40  | Wash, 30 1ks. wide, 1 ft. deep, drains SW.  |
| 39.96  | The cor. of secs. 16, 17, 20 and 21, monumented by  |
|        | stone and stake, as described in the official record.   |
|        | At the corner point   |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | <u>S17 S16</u><br>S20 S21   |
|        | 1961  |
|        | Land, rolling. Soil, sand, clay and rocks. Timber, none; undergrowth, creosote and yucca.                       |
|        |   |
|        | From the cor. of secs. 15, 16, 21 and 22.   |
|        | N. 86°41' W., bet. secs. 16 and 21.   |
|        | Over rolling land, through scattered undergrowth.   |
| 11.10  | Wash, 10 lks. wide, 1 ft. deep, drains SW.  |
| 40.38  | The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented by a stone, as described in the official record.     |
|        | At the corner point   |
|        | Set the iron post 24 ins. in the ground, mound with stone to top, cap mkd.                                      |
|        | T10S R28E   |
|        | ½ <u>S16</u><br>S21   |
|        | 1961  |
|        |   |
|        | S. 88°29' W., beginning new measurement.  |
| 25.10  | Wash, 30 1ks. wide, 1 ft. deep, drains SW.  |
| 40.69  | The cor. of secs. 16, 17, 20 and 21.  |
|        | Land, rolling.  |
|        | Soil, sandy.  |
|        | Timber, none; undergrowth, creosote and yucca.  |
|        |   |
| 1      |   |

### FIELD NOTE PAPER

| <del></del> |        |  |
|-------------|--------|--|
|             | CHAINS | Resurvey, Subdivisions, T. 10 S ., R. 28 E.  |
|             |        | N. 0°40' W., bet. secs. 16 and 17.   |
|             |        | Over rolling land, through scattered undergrowth.  |
|             | 39.83  | The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented by a wood stake, as described in the official record.               |
|             |        | At the corner point  |
|             |        | Set the iron post 24 ins. in the ground, cap mkd.  |
|             |        | T10S_R28E  |
|             |        | \$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\  |
|             |        | N. 3°38' E., beginning new measurement.  |
|             | 21.00  | Wash, 100 1ks. wide, 3 ft. deep, drains S. 80° W.  |
|             | 39.66  | The cor. of secs. 8, 9, 16 and 17, monumented by a stone and stake, as described in the official record.                       |
|             |        | At the corner point  |
|             |        | Set the iron post 24 ins. in the ground, cap mkd.  |
|             |        | T10S R28E<br>S 8 S 9<br>S17 S16  |
|             |        | 1961   |
|             |        | Land, rolling. Soil, sandy and rocky. Timber, none; undergrowth, creosote and yucca.   |
|             |        | From the cor. of secs. 9, 10, 15 and 16.   |
|             |        | N. 89°45' W., bet. secs. 9 and 16.   |
|             | 15.10  | Over rolling land, through desert undergrowth. Wash, 40 lks. wide, 1 ft. deep, drains S.                                       |
|             | 40.04  | Point for the ½ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. |
|             |        | Set the iron post 26 ins. in the ground, cap mkd.  |
|             |        | T10S R28E  2 S 9  S 16  1961   |
|             |        | Deposit glass at base of iron post.  |
|             | 56.40  | Wash, 20 lks. wide, l ft. deep, drains SW.   |
|             | 76.10  | Spur, slopes SW.   |
|             | 80.08  | The cor. of secs. 8, 9, 16 and 17.   |
|             |        |  |
|             | 1      |  |

| CHAINS         |   |
|----------------|---|
|                | Resurvey, Subdivisions, T. 10 S ., R. 28 E.   |
|                | Land, rolling. Soil, rocky and sandy. Timber, none; undergrowth, catclaw, creosote, greasewood.   |
|                | N. 1°18' W., bet. secs. 8 and 9.  |
|                | Over gently rolling land, through desert undergrowth.   |
| 40.15          | Point for the ½ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.   |
|                | Set the iron post 24 ins. in the ground, cap mkd.   |
|                | T10S R28E   |
| 44.90          | Wash, 20 lks. wide, 1 ft. deep, drains NW.  |
| 48.00          | Wash, 20 lks. wide, l ft. deep, drains N. 80° W.  |
| 73.50          | Wash, 10 lks. wide, l ft. deep, drains N. 30° W.  |
| 80.30          | The cor. of secs. 4, 5, 8 and 9, monumented by a stone and stake, as described in the official record.  |
|                | At the corner point   |
|                | Set the iron post 24 ins. in the ground, cap mkd.   |
|                | T10S R28 <b>E</b><br>S5 S4  |
|                | \$8 \$9<br>1961   |
|                | '   |
|                | 1961 Land, rolling. Soil, sandy.  |
|                | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  |
|                | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  |
| 39.80          | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  N. 89°34' W., bet. secs. 4 and 9.   |
| 39.80          | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  N. 89°34' W., bet. secs. 4 and 9.  Over gently rolling land, through desert undergrowth.  Point for the ½ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of  |
| 39.80          | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  N. 89°34' W., bet. secs. 4 and 9.  Over gently rolling land, through desert undergrowth.  Point for the ½ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.   |
| 39.80<br>77.30 | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  N. 89°34' W., bet. secs. 4 and 9.  Over gently rolling land, through desert undergrowth.  Point for the ½ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.  Set the iron post 26 ins. in the ground, cap mkd.  T10S R28E  ½ S 4/S 9  |
|                | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  N. 89°34' W., bet. secs. 4 and 9.  Over gently rolling land, through desert undergrowth.  Point for the ½ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.  Set the iron post 26 ins. in the ground, cap mkd.  TIOS R28E  ½ \$\frac{5}{5}\frac{9}{1961}  |
| 77.30          | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote and yucca.  From the cor. of secs. 3, 4, 9 and 10.  N. 89°34' W., bet. secs. 4 and 9.  Over gently rolling land, through desert undergrowth.  Point for the ½ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.  Set the iron post 26 ins. in the ground, cap mkd.  TIOS R28E  ½ \$ 4 / \$ 9 / \$ 9 / \$ 1961  Wash, 20 1ks. wide, 1 ft. deep, drains S. 30° W. |

### FIELD NOTE PAPER

|   |        | 73.   |
|---|--------|---|
|   | CHAINS | N. 0°12' E., bet. secs. 4 and 5.  |
| • |        | Over rolling land, through desert undergrowth.  |
| • | 9.00   | Ridge, bears E. and W.; desc. NE. slope.  |
|   | 40.07  | The ½ sec. cor. of secs. 4 and 5, monumented by a wood stake, as described in the official record.                              |
|   |        | At the corner point   |
|   |        | Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.  |
|   |        | T10S R28E   |
|   |        | \$5<br>  \$5<br>  \$4<br>  1961   |
|   |        | N. 2°43' W., beginning new measurement.   |
|   | 6.20   | Wash, 30 lks. wide, 1 ft. deep, drains NE.  |
|   | 18.70  | Fence, bears E. and W.  |
|   | 22.00  | Wash, 100 lks. wide, 2 ft. deep, drains W.  |
|   | 29.40  | Wash, 30 lks. wide, 2 ft. deep, drains SW.  |
|   | 34.00  | Ridge, bears E. and W.; desc. N. slope.   |
| • | 40.30  | The corner of secs. 32, 33, 4 and 5, on the N. bdy. of the township.  |
|   |        | Land, rolling. Soil, sandy. Timber, none; undergrowth, creosote brush.  |
|   |        | From the cor. of secs. 31 and 32, on the S. bdy. of the township.   |
|   |        | N. 0°07' W., bet. secs. 31 and 32.  |
|   |        | Over gently rolling land, through desert undergrowth.   |
|   | 7.80   | Wash, 20 1ks. wide, 1 ft. deep, drains NE.  |
|   | 40.22  | Point for the ½ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. |
|   |        | Set the iron post 22 ins. in the ground, cap mkd.   |
|   |        | T10S_R28E   |
|   |        | S31 S32<br>1961   |
|   |        | Deposit glass at base of iron post.   |
|   | 44.10  | Wash, 10 lks. wide, 1 ft. deep, drains N. 20° E.  |
| • | 50.90  | Wash, 50 lks. wide, 2 ft. deep, drains N., continue in flood area.  |
| • |        |   |
|   | 4      |   |

| T      | 500% 4001 44.   |
|--------|---|
| CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
| 67.10  | Fence, bears NE.  |
| 73.80  | Wash, 50 lks. wide, 3 ft. deep, drains NE.; leave flood area.   |
| 80.45  | The cor. of secs. 29, 30, 31 and 32, monumented by a marked stone, as described in the official record.                         |
|        | At the corner point   |
|        | Set the iron post 24 ins. in the ground, mound with stone to top, cap mkd.  |
|        | T10S R28E   |
|        | S30 S29   |
|        | S31 S32<br>1961   |
|        | 1701  |
|        | Land, rolling.<br>Soil, rocky.  |
|        | Timber, none; undergrowth, creosote and yucca.  |
|        | From the cor. of secs. 28, 29, 32 and 33.   |
|        | N. 89°49' W., bet. secs. 29 and 32.   |
|        | Over gently rolling land, through desert undergrowth.   |
| 5.80   | Wash, 60 lks. wide, 1 ft. deep, drains NE.  |
| 13.90  | Wash, 20 lks. wide, 1 ft. deep, drains NE.  |
| 30.40  | Wash, 40 lks. wide, 1 ft. deep, drains N.   |
| 40.45  | Point for the ½ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | $\frac{1}{4} \frac{S}{S} \frac{29}{32}$   |
|        | 1961  |
|        |   |
|        | Deposit glass at base of iron post.   |
| 43.70  | Wash, 30 lks. wide, 2 ft. deep, drains NW., continue in flood area.   |
| 50.10  | Wash, 50 lks. wide, 3 ft. deep, drains NE.  |
| 63.60  | Fence, bears NE. and SW.  |
| 65.90  | Wash, 100 lks. wide, 2 ft. deep, drains NE.   |
| 71.80  | Leave flood area.   |
| 80.90  | The cor. of secs. 29, 30, 31 and 32.  |
| İ      | Land, gently rolling.   |
|        | Soil, sandy. Timber, none; undergrowth, catclaw, mesquite and creosote.   |
|        |   |
|        |   |

## FIELD NOTE PAPER

|   | <del></del> |  |
|---|-------------|--|
| • | CHAINS      | Resurvey, Subdivisions, T. 10 S., R. 18 E.   |
| _ |             | N. 89°49' W., bet. secs. 30 and 31.  |
|   |             | Over gently rolling land, through scattered undergrowth.   |
|   | 8.60        | Wash, 60 lks. wide, 1 ft. deep, drains N.  |
|   | 16.90       | Wash, 15 1ks. wide, 1 ft. deep, drains N.  |
|   | 36.10       | Wash, 20 1ks. wide, 1 ft. deep, drains NW.   |
|   | 40.22       | Point for the ½ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.  |
|   |             | Set the iron post 26 ins. in the ground, cap mkd.  |
|   |             | T10S R28E  1/4 S 30 S 31 1961  |
|   |             | Deposit glass at base of iron post.  |
|   | 43.50       | Wash, 50 lks. wide, 2 ft. deep, drains NE.   |
|   | 53.10       | Wash, 40 lks. wide, 1 ft. deep, drains N.  |
|   | 80.35       | The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township.   |
|   |             | Land, gently rolling. Soil, sandy. Timber, none; undergrowth, cactus, catclaw, creosote.   |
|   |             | From the cor. of secs. 29, 30, 31 and 32.  |
|   |             | N. 0°03' W., bet. secs. 29 and 30.   |
|   |             | Over gently rolling land, through desert undergrowth.  |
|   | 21.00       | Wash, 15 lks. wide, 1 ft. deep, drains NE.   |
|   | 40.17       | Point for the ½ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.  |
|   |             | Set the iron post 26 ins. in the ground, cap mkd.  |
|   |             | T10S_R28E  |
|   |             | S30 S29<br>1961  |
|   | 51.00       | Wash, 15 lks. wide, 1 ft. deep, drains N. 80° E.   |
|   | 80.34       | Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner. |
|   |             | Set the iron post 26 ins. in the ground, cap mkd.  |
|   |             |  |
|   | ]           |  |

| T GYLATYS | 40.   |
|-----------|---|
| CHAINS    | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|           | T10S R28E   |
|           | S 19 S 20   |
|           | \$30 \$29   |
|           | 1961  |
|           | Deposit glass at base of iron post.   |
|           | Land, gently rolling. Soil, sandy and rocky. Timber, none; undergrowth, creosote, yucca.  |
|           | From the true point for the cor. of secs. 20, 21, 28 and 29.  |
|           | N. 89°41' W., bet. secs. 20 and 29.   |
| 1.20      | Leave wash; thence over gently rolling land, through desert undergrowth.  |
| 12.60     | Wash, 120 1ks. wide, 20 ft. deep, drains N. 20° E.  |
| 22.10     | Wash, 20 1ks. wide, 2 ft. deep, drains N.   |
| 40.29     | Point for the ½ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner. |
|           | Set the iron post 26 ins. in the ground, cap mkd.   |
|           | T10S R28E   |
|           | $\frac{1}{4} = \frac{S}{S} = \frac{20}{29}$   |
|           | S 29<br>1961  |
|           | Deposit glass at base of iron post.   |
| 75.20     | Wash, 20 1ks. wide, 2 ft. deep, drains N.   |
| 80.58     | The cor. of secs. 19, 20, 29 and 30.  |
|           | Land, gently rolling.   |
|           | Soil, sandy. Timber, none; undergrowth, creosote, yucca and cactus.   |
|           | West, bet. secs. 19 and 30.   |
|           | Over gently rolling land through desert undergrowth.  |
| 40.33     | Point for the ½ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. |
|           | Set the iron post 26 ins. in the ground, cap mkd. T10S R28E $\frac{1}{4} = \frac{\text{S } 19}{\text{S } 30}$ 1961              |
|           | Deposit glass at base of iron post.   |
| 80.56     | The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township.  |
|           | Land, gently rolling. Soil, sandy and rocky. Timber, none; undergrowth, creosote, cactus and yucca.                             |
|           |   |

### FIELD NOTE PAPER

|        | FIELD NOTE PAPER  |
|--------|---|
| CHAINS |   |
|        | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |
|        | From the cor. of secs. 19, 20, 29 and 30.   |
|        | N. 0°25' W., bet. secs. 19 and 20.  |
|        | Over gently rolling land, through desert undergrowth.   |
| 40.17  | Point for the ½ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.             |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | \$19   \$20<br>1961   |
|        | Deposit glass at base of iron post.   |
| 80.34  | The cor. of secs. 17, 18, 19 and 20, monumented by a marked stone, as described in the official record.                                     |
|        | At the corner point   |
|        | Set the iron post 24 ins. in the ground, cap mkd.   |
|        | T10S R28E <u>S18 S17</u> S19 S20  1961  |
|        | Land, rolling. Soil, sandy. Timber, none; undergrowth, sagebrush.   |
|        | From the cor. of secs. 16, 17, 20 and 21.   |
|        | S. 89°32' W., bet. secs. 17 and 20.   |
|        | Over gently rolling land, through scattered undergrowth.  |
| 10.90  | Road, unimproved, bears N. and S.   |
| 18.80  | San Simon Wash, 200 lks. wide, 10 ft. deep, drains NW.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. |
|        | Set the iron post 26 ins. in the ground, cap mkd.   |
|        | T10S R28E   |
|        | $\frac{1}{4} = \frac{S}{S} = \frac{17}{20}$ 1961  |
|        |   |
|        | Deposit glass at base of iron post.   |
| 67.00  | Deposit glass at base of iron post.  Wash, 30 lks. wide, 2 ft. deep, drains N.  |

| CHAINS  |  |  |   |
|---|--|--|---|
| Resurvey, Subdivisions, T. 10 S., R. 28 E.  |  |  |   |
|   | Land, level to gently rolling.   |  |   |
|   | Soil, clay, sandy and rocky.   |  |   |
|   | Timber, none; undergrowth, creosote.   |  |   |
|   | N. 89°34' W., bet. secs. 18 and 19.  |  |   |
|   | Over gently rolling land, through scattered undergrowth.   |  |   |
| 40.07   | Point for the 1/2 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.        |  |   |
|   | Set the iron post 24 ins. in the ground, cap mkd.  |  |   |
| T10S R28E   |  |  |   |
| -   | ½ S 18<br>S 19   |  |   |
|   | 1961   |  |   |
|   | Deposit glass at base of iron post.  |  |   |
| 44.50   | Wash, 100 lks. wide, 3 ft. deep, drains N.   |  |   |
| 60.90   | Wash, 50 lks. wide, 3 ft. deep, drains NE.   |  |   |
| 80.00 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the township.  Land, gently rolling. Soil, sandy. Timber, none; undergrowth, sagebrush and wormwood. |  |  |   |
|   |  |  | From the cor. of secs. 17, 18, 19 and 20. |
| N. 0°08' E., bet. secs. 17 and 18.  |  |  |   |
|   | Over nearly level land, through scattered undergrowth.   |  |   |
| 36.30   | San Simon Wash, 210 lks. wide, 15 ft. deep, drains NW.   |  |   |
| 40.08   | Point for the 2 sec. cor. of secs. 17 and 18, at proportionate distance; falls in deep erosion cut, not suitable for permanent monument. |  |   |
| 42.08   | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 17 and 18.   |  |   |
|   | Set the iron post 24 ins. in the ground, cap mkd.  |  |   |
|   | T10S R28E  |  |   |
|   | S18 S17  |  |   |
|   | W C<br>1961  |  |   |
|   | Raise a mound of stone, N. of corner.  |  |   |
| 68.10   | Road, unimproved, bears NW. and SE.  |  |   |
|   |  |  |   |
| 80.16   | The cor. of secs. 7, 8, 17 and 18, monumented by a wood stake and marked stone, as described in the official record.                     |  |   |
|   | At the corner point  |  |   |
|   | Set the iron post 24 ins. in the ground, cap mkd.  |  |   |
|   |  |  |   |

### FIELD NOTE PAPER

| FIELD NOTE PAPER 49. |        |  |   |  |  |
|----------------------|--------|--|---|--|--|
|                      | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.   |   |  |  |
| •                    |        | T10S R28E  S 7   S 8  S18   S17  1961  | - |  |  |
| ,                    |        | Land, nearly level. Soil, sandy and clay. Timber, none; undergrowth, catclaw, greasewood, yucca, cactus and creosote.          |   |  |  |
|                      |        | From the cor. of secs. 8, 9, 16 and 17.  |   |  |  |
|                      |        | N. 89°55' W., bet. secs. 8 and 17.   |   |  |  |
|                      |        | Over nearly level land, through scattered undergrowth.   |   |  |  |
|                      | 40.92  | Point for the ½ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. |   |  |  |
|                      |        | Set the iron post 26 ins. in the ground, cap mkd.  |   |  |  |
|                      |        | T10S_R28E  |   |  |  |
|                      |        | ½ S 8<br>S 17<br>1961  |   |  |  |
| -<br>-               |        | Deposit marked stone.  |   |  |  |
| ~                    | 47.30  | Wash, 30 1ks. wide, 3 ft. deep, drains NW.   |   |  |  |
| •                    | 81.84  | The cor. of secs. 7, 8, 17 and 18.   |   |  |  |
|                      |        | Land, nearly level. Soil, sandy and clay. Timber, none; undergrowth, catclaw, greasewood, yucca and cactus.                    |   |  |  |
|                      |        | S. 89°58' W., bet. secs. 7 and 18.   |   |  |  |
|                      |        | Over nearly level land, through scattered undergrowth.   |   |  |  |
|                      | 9.30   | Road, unimproved, bears SE. and NW.  |   |  |  |
|                      | 22.50  | San Simon Wash, 400 lks. wide, 8 ft. deep, drains NW.; continue over small deep washes draining NE.                            |   |  |  |
|                      | 40.50  | Point for the ½ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. |   |  |  |
|                      | -      | Set the iron post 24 ins. in the ground, cap mkd.  |   |  |  |
|                      |        | T10S_R28E  |   |  |  |
|                      |        | $\frac{1}{4} \frac{S}{S} \frac{7}{18}$ 1961  |   |  |  |
| •                    |        | Deposit mkd. stone at base of iron post.   |   |  |  |
| •                    | 80.59  | The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the township.  |   |  |  |
|                      |        |  |   |  |  |

| T   |   |  |  |
|---|---|--|--|
| CHAINS  | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |  |  |
|   | Land, nearly level. Soil, sandy. Timber, none; undergrowth, yucca and greasewood.   |  |  |
|   | From the cor. of secs. 7, 8, 17 and 18.   |  |  |
|   | N. 0°29' W., bet. secs. 7 and 8.  |  |  |
| Over nearly level land, through desert undergrowt   |   |  |  |
| 40.15   | Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. |  |  |
|   | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |
|   | T10S_R28E   |  |  |
|   | \$7   \$8<br>1961   |  |  |
|   | Deposit stone at base of iron post.   |  |  |
| 72.00   | Wash, 50 lks. wide, 2 ft. deep, drains W.   |  |  |
| Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence the original corner. |   |  |  |
|   | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |
|   | T10S R28E  S6   S5  S7   S8  1961   |  |  |
|   | Deposit marked stone.   |  |  |
|   | Land, nearly level. Soil, sandy. Timber, none; undergrowth, catclaw.  |  |  |
|   | From the cor. of secs. 4, 5, 8 and 9.   |  |  |
|   | N. 89°54' W., bet. secs. 5 and 8.   |  |  |
|   | Over nearly level land, through desert undergrowth.   |  |  |
| 11.30   | Wash, 20 lks. wide, 1 ft. deep, drains S. approx. 3 chs., thence SW.  |  |  |
| 23.20   | Spur, slopes S. approx. 2 chs.; desc. gentle W. slope.  |  |  |
| 40.38   | Point for the ½ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.             |  |  |
|   | Set the iron post 26 ins. in the ground, cap mkd.   |  |  |
|   | T10S R28E  1/4 S 5/S 8  1961  |  |  |
|   | Deposit mkd. stone.   |  |  |
| 52.20   | Spur, slopes SE., desc. W. slope.   |  |  |
| 80.76   | The cor. of secs. 5, 6, 7 and 8.  |  |  |

## FIELD NOTE PAPER

|   |        | 51.  |
|---|--------|--|
|   | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.   |
| • |        | Land, gently rolling. Soil, sandy. Timber, none; undergrowth, creosote.  |
|   |        | N. 89°55' W., bet. secs. 6 and 7.  |
|   |        | Over nearly level land, through desert undergrowth.  |
|   | 8.60   | Road, bladed, bears N. and S.  |
|   | 33.92  | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 6 and 7.   |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.  T10S R28E  W 1 S 6  C 4 S 7  1961   |
|   |        | Deposit marked stone at base of iron post.   |
|   | 35.50  | E. bank of San Simon Wash, bears N. and S.   |
|   | 40.40  | Point for the ½ sec. cor. of secs. 6 and 7, at proportional distance; there is no remaining evidence of the original corner; falls in San Simon Wash, draining NW. |
|   | 46.00  | W. bank of San Simon Wash, bears SE. and NW.   |
|   | 50.50  | Wash, 30 1ks. wide, 4 ft. deep, drains N.  |
|   | 56.50  | Fence, bears N. and S.   |
|   | 80.47  | The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the township.  |
|   |        | Land, nearly level. Soil, sandy and clay. Timber, none; undergrowth, mesquite and creosote.  |
|   |        | From the cor. of secs. 5, 6, 7 and 8.  |
|   |        | N. 0°46' W., bet. secs. 5 and 6.   |
|   |        | Over nearly level land, through scattered undergrowth.   |
|   | 26.00  | Wash, 10 lks. wide, 2 ft. deep, drains SW.   |
|   | 34.20  | Road, bears N. 25° E. and S. 25° W.  |
|   | 40.15  | Point for the ½ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.                                      |
|   |        | Set the iron post 26 ins. in the ground, cap mkd.  |
| 4 |        | T10S R28E<br><sup>1</sup> 4<br>S6   S5<br>1961   |
|   |        | Deposit marked stone at base of iron post.   |

|  |        | BOOK 4667 5   |  |
|--|--------|---|--|
|  | CHAINS | Resurvey, Subdivisions, T. 10 S., R. 28 E.  |  |
| 46.50 Wash, 70 lks. wide, 1 ft. deep, drains SW. |        |   |  |
| Land, level to rolling. Soil, sandy.             |        | Wash, 300 1ks. wide, 3 ft. deep, drains SW.   |  |
|  |        | The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the township.  |  |
|  |        |   |  |
|  |        | General Description   |  |
|  |        | Township 10 South, Range 28 East, is located in Graham County approximately 22 miles southeast of the city of Safford, Arizona. |  |

The land within the township is mostly rolling hills with relatively low relief. The highest elevation, about 3900 feet above sea level, is located in the NE $\frac{1}{4}$  of section 1 on the southwest flank of the Whitlock Mountains. The lowest elevation is along the bottom of San Simon Wash in the NW $\frac{1}{4}$  of section 6.

The drainage of the township consists of San Simon Wash, an intermittent stream which drains from the SE% to the northwest corner of the township, and numerous washes which drain northeast and southwest to the San Simon. This drainage system is a rejuvenated system and the San Simon and its tributaries are young streams with steep banks. The banks of the San Simon average around 20 feet high, which makes it impossible to cross except at two places which are man-made crossings.

The soil of the township can be divided into two classes: a well developed loam along the stream valleys and a shallow, rocky, sandy clay soil on the hills and ridges. The vegetative cover is composed of mesquite, tamarisk, creosote brush, cacti and grasses. The creosote brush and cactus cover the entire area, while the mesquite grows along the drainage, with the tamarisk along the bottom of the San Simon Wash.

The main access road into the township enters at the west boundary, bearing east approximately one-half mile where it turns southeast and roughly follows the east bank of San Simon Wash in a southeasterly direction to a junction at an artesian well in section 36, with a road bearing east to the east boundary and southwest to a point near the corner of sections 34 and 35 where it leaves the township. These roads are mostly track roads, but access to the area is no problem since a 4-wheel drive vehicle can be taken almost anywhere in the area.

The artesian well is a highly mineralized warm water well, located in section 36, and was the only source of water noted during this survey. The only other improvements noted were some stock watering ponds scattered throughout the township.

There are several apparently abandoned mining claims scattered throughout the township, but at the present time there is no activity in the area except grazing and feeding livestock. Feeding consists of placing cottonseed at watering places to supplement available forage.

Form 4-680 (January 1963)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

### FIELD ASSISTANTS

| TILLU AGGISTANTO   |            |  |  |
|--|------------|--|--|
| NAMES  | CAPACITY   |  |  |
| Alburn D. Griffin  | Crew Chief |  |  |
| Glen B. Hatch  | Crew Chief |  |  |
| Wallace R. Ott   | Notekeeper |  |  |
| Gary W. Rutledge   | Notekeeper |  |  |
| Rex J. Edwards   | Chainman   |  |  |
| Gordon Shurtz  | Chainman   |  |  |
| Wayne Fisher   | Flagman    |  |  |
| Parley Pratt   | Flagman    |  |  |
|  |            |  |  |
|  |            |  |  |
| Alexander de la companya del companya del companya de la companya  |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |
| Proposition of the second of t |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |
|  |            |  |  |

#### CERTIFICATE OF SURVEY

We, Glen B. Hatch A. D. Griffin

, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 10th ay of August

. 19 60 .

We have made a DEPENDENT REUSRVEY of the Second Standard Parallel South through Range 28 East, the North and West Boundaries and the Subdivisional Lines of Township 10 South, Range 28 East

of the Gila & Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jan 23, 1961
(Date)
Jan. 23, 1961
Jan. 23, 1961
(Date)

(Cadastral Surveyor)

B. Hatch Surveying Technician

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the DEPENDENT REUSRVEY of the Second Standard Parallel South, the North and West Boundaries and the Subdivisional Lines of Township 10 South, Range 28 East of the Gila and Salt River Meridian, Arizona

Dell Cazier, Cadastral Surveyor Glen B. Hatch, Surveying Technician

executed by Glen B. Hatch, Sun

A. D. Griffin, Surveying Aide

having been critically examined and found correct, are hereby approved.

Washington, D. C.

**JUL 24 1963** 

(Date)

(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

is a true copy of the original field notes.

(Date) (Chief, Division of Engineering)