

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of

A Portion of the East Boundary

A Portion of the South Boundary

SURVEY

of a

Portion of the Subdivisional Lines

of

Township 37 North, Range 5 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Paul G. Bauer, Surveying Technician

Wallace R. Ott, Surveying Aid

Under special instructions dated June 20, 19 62, which provided for the surveys  
included under Group Number 376, approved June 26, 1962,  
and assignment instructions dated October 12, 19 62.

Survey commenced October 17, 19 62

Survey completed October 23, 19 62

1A

# INDEX DIAGRAM

Township 37 North, Range 5 West

				13( $\frac{1}{4}$ )	10( $\frac{1}{4}$ )
6	5	4	3 12	2 9	1
				11	8
7	8	9	10 11	11 8	12
				10	7
18	17	16	15	14 7	13
					6
19	20	21	22	23 6	24
					5
30	29	28	27	26 4	25
					3
					4
31	32	33	34	35 3	36
					2
					1

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 37 North, Range 5 West  
Gila and Salt River Meridian, Arizona

The south boundary, which is the Ninth Standard Parallel North, was surveyed in 1915 by T. B. Matthews. The east mile, south boundary of section 36, was dependently resurveyed in 1958 by Yundt and Cannon. The east boundary, which is the First Guide Meridian West, was surveyed in 1914 by J. C. Thoma. The west boundary was surveyed in 1924 by W. E. Hiester. The north boundary was surveyed in 1924 by W. E. Hiester. Section 32 was surveyed in 1954 by D. E. Harding.

The following notes are those of a dependent resurvey of a portion of the east boundary and a portion of the south boundary and the survey of a portion of the subdivisional lines of Township 37 North, Range 5 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated June 20, 1962.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude, 36°33'23.06 North and Longitude 112°46'21.47" West.

The magnetic declination was found to be 15° East.

Dependent Resurvey of a Portion of the South Boundary  
Township 37 North, Range 5 West

Reestablishment of the Resurvey in 1958  
by Yundt and Cannon

From the cor. of T. 37 N., Rs. 4 and 5 W., monumented by an iron post as described in the official record.

N. 89°51' W., along the S. bdy. of sec. 36.

Over broken land through scattered timber.

2.20 Small draw, drains S. 80° E.

6.50 Top of high spur, projects NE.; thence, by triangulation, topography as taken from U.S.G.S. topographic sheet; desc. over steep, ledgy W. slope.

31.00 Bottom of deep canyon, drains N.; asc. over steep, ledgy E. slope.

37.72 Point for the Standard ¼ sec. cor. of sec. 36, at 40.00 chs. in easting from the Stan. cor. of secs. 35 and 36.

CHAINS	
	<p>Set the iron post on solid ledge, mound with stones to top, cap mkd.</p> <p style="text-align: center;">SC T37NR5W <u>½ S36</u> 1962</p> <p>Remove and destroy the witness ¼ sec. cor. set in 1915 by T. B. Mathews as per instructions; end of triangulation.</p>
61.00	Spur, projects N. 30° E.; thence over rolling land through moderate timber.
68.35	The closing cor. of secs. 1 and 2, T. 36 N., R. 5 W., monumented by an iron post as described in the official record.
77.72	The Standard cor. of secs. 35 and 36, monumented by an iron post as described in the official record.
	<p>Land, mountainous. Soil, rocky and exposed sandstone. Timber, scattered to moderate pinon and juniper. Undergrowth, shadscale and cactus.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the East Boundary Township 37 North, Range 5 West</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey in 1914 by J. C. Thoma</p> <hr/> <p>From the ¼ sec. cor. of secs. 31 and 36 on the E. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 0°05' E., bet. secs. 31 and 36.</p> <p>Desc. over N. slope; topography as taken from U.S.G.S. topographic sheet.</p>
21.00	Wash, drains NE.; thence, over bottom of Hack Canyon.
37.40	Point selected for the witness cor. of secs. 25, 30, 31 and 36.
	<p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T37N R5W R4W <u>S25   S30</u> <u>S36   S31</u> WC 1962</p>
40.03	<p>Point for the cor. of secs. 25, 30, 31 and 36 at proportionate distance. There is no remaining evidence of the original corner; point falls in Hack Canyon Wash, 300 lks. wide, 5 ft. banks, drains East.</p> <p>Land, mountainous. Soil, exposed sandstone and sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, shadscale and cactus.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	East Bdy., T. 37 N., R. 5 W.
	N. 0°05' E., bet. secs. 25 and 30.
15.00	Draw, drains SW.; asc. over general S. slope.
40.03	The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by an iron post as described in the official record.
	Survey of a Portion of the Subdivisional Lines Township 37 North, Range 5 West
	From the Standard cor. of secs. 35 and 36 on the S. bdy. of the township.
	North, on a Sectional Guide Meridian, bet. secs. 35 and 36.
	Over mountainous land through moderate to scattered timber.
	By triangulation, topography as taken from U.S.G.S. topographic sheet; desc. over NW. slope.
23.00	Bottom of canyon, drains N. 70° E.; asc. over steep SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.  Set the iron post on solid rock, mound with stones to top, cap mkd.
	T37NR5W $\frac{1}{4}$ S35 S36 1962
	End of triangulation; asc. over S. slope.
45.90	Spur top, projects N. 30° E.; desc. along NW. slope.
64.50	S. rim of Hack Canyon, bears irregularly SE. and SW.; by triangulation desc. over steep, ledgy NW. slope.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.  Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T37NR5W S26 S25 S35 S36 1962
	Land, steep and broken. Soil, rocky, exposed sandstone and shallow sand. Timber, moderate to scattered scrub juniper and pinon. Undergrowth, shadscale and brigham tea.
	From the true point for the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township.

CHAINS	
	<p>N. 89°51' W., bet. secs. 25 and 36.</p> <p>Leave Hack Canyon Wash; asc. along the S. side of canyon floor.</p>
37.76	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at 40.00 chs. in easting from the cor. of secs. 25, 26, 35 and 36.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T37NR5W ¼ <math>\frac{S\ 25}{S\ 36}</math> 1962</p> <p>Raise a mound of stone N. of the cor.</p> <p>Thence, by traverse, topography as taken from U.S.G.S. topographic sheet; asc. over steep ledgy NE. slope.</p>
70.00	<p>Ledgy spur, sloping sharply N.; desc. over steep, broken NW. slope.</p>
77.76	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, steep and broken on W. ½ mile, rolling on remainder. Soil, rocky, exposed sandstone and sandy. Timber, scattered scrub juniper and pinon. Undergrowth, shadscale, weeds and cactus.</p> <hr/> <p>North, on a Sectional Guide Meridian, bet. secs. 25 and 26.</p> <p>Desc. over steep broken NW. slope.</p>
3.70	<p>Bottom of draw, drains N. 30° E.; asc. along broken E. slope.</p>
10.00	<p>Rocky spur, slopes sharply NE.; by triangulation, descend over steep ledgy NE. slope.</p>
27.00	<p>S. bank of Hack Canyon Wash, bears SE. and NW.; thence in wash draining irregularly SE.; end of triangulation.</p>
38.60	<p>N. bank of wash, bears E. and N. 80° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 25 and 26.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T37NR5W ¼ S26 S25 1962</p> <p>By triangulation, asc. over steep slope and ledges facing S.</p>
59.40	<p>N. rim of Hack Canyon, bears S. 70° E. and N. 70° W.; thence over point projecting W.</p>
72.10	<p>Desc. over N. slope.</p>
73.10	<p>Canyon rim, bears S. 80° E. and N. 80° W.; desc. over steep, broken N. slope.</p>
80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Set the iron post on solid rock, mound with stones to top, cap mkd.

T37NR5W  
S23|S24  
S26|S25  
1962

from which

A cabin in the bottom of Hack Canyon bears S. 80°19' W., 41.38 chs. dist. as calculated from traverse.

Land, steep and broken.  
Soil, rocky, exposed sandstone and shallow sand.  
Timber, scattered scrub juniper and pinon.  
Undergrowth, shadscale, brigham tea and cactus.

From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, monumented by an iron post as described in the official record.

N. 89°57' W., bet. secs. 24 and 25.

Desc. over W. slope.

- 6.20 Draw, about 4.00 chs. from head, drains N. 20° E.; asc. over E. slope.
- 9.00 E. edge of small mesa, bears N. and S.
- 16.30 W. edge of mesa, bears NE. and SW.; desc. over steep W. slope.
- 22.60 Draw, near head, drains N. 30° W.
- 27.00 Small spur, slopes N. 30° W.
- 34.20 Wash, 10 lks. wide, 1 ft. deep, drains NW.
- 37.95 Point for the  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, at 40.00 chs. in easting from the cor. of secs. 23, 24, 25 and 26.  
  
Set the iron post on broken bedrock, mound with stones to top, cap mkd.  
  
T37NR5W  
 $\frac{1}{4}$  S 24  
S 25  
1962  
  
Cor is located on rolling NW. slope.  
  
By traverse, topography as taken from U.S.G.S. topographic sheet.
- 50.00 Bottom of canyon, nearly vertical walls, drains SW. circling to W.; thence along N. side of canyon.
- 74.00 Bottom of same canyon, drains N. 70° W.; asc. along steep N. slope.
- 77.95 The cor. of secs. 23, 24, 25 and 26.

CHAINS

Land, rolling and broken.  
Soil, rocky, exposed sandstone and sandy clay loam.  
Timber, scattered scrub juniper and pinon.  
Undergrowth, shadscale, cactus and brigham tea.

North, on a Sectional Guide Meridian, bet. secs. 23 and 24.

Over steep broken mountainous land through scattered timber.

By triangulation, topography as taken from U.S.G.S. topographic sheet; desc. over N. slope.

2.00 Wash in canyon bottom, drains N. 70° W.; asc. over steep, ledgy SW. slope.

11.40 End of triangulation on point projecting W. about 3.00 chs. to end. Desc. over N. slope.

16.80 Bottom of draw, drains W. circling to S.

24.40 Point, projects S. 70° W.

28.40 Small wash in bottom of draw, drains irregularly SW.; asc. over S. slope.

40.00 Point for the ¼ sec. cor. of secs. 23 and 24.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T37NR5W  
¼  
S23|S24  
1962

40.00 Rim, bears N. 80° E. and W.; thence, along rolling W. edge of Sunshine Point.

47.00 Wash, 20 lks. wide, 1 ft. deep, drains SW.

64.10 Desc. over steep NW. slope.

71.40 Wash, 20 lks. wide, 1 ft. deep, drains S. 70° W.; asc. over steep SE. slope.

78.50 Top of spur, slopes SW.; thence over Sunshine Point.

80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set the iron post 9 ins. in the ground, mound with stones to top, cap mkd.

T37NR5W  
S14|S13  
S23|S24  
1962

Land, mountainous.  
Soil, rocky, exposed sandstone and sandy clay loam.  
Timber, scattered scrub juniper.  
Undergrowth, shadscale, brigham tea and cactus.

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, monumented by an iron post as described in the official record. Note: This cor. is located on fence line bearing N. and S.

N. 89°58' W., bet. secs. 13 and 24.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p style="text-align: center;">Subdivision, T. 37 N., R. 5 W.</p> <hr/>
	<p>Over rolling land on Sunshine Point.</p>
<p>38.01</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24, at 40.00 chs. in easting from the cor. of secs. 13, 14, 23 and 24.</p> <p>Set the iron post 3 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T37NR5W <math>\frac{1}{4}</math> <math>\frac{S\ 13}{S\ 24}</math> 1962</p>
<p>46.60</p>	<p>Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W. circling to SW.</p>
<p>61.80</p>	<p>Same wash, drains SW.</p>
<p>78.01</p>	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, sandy. Timber, scattered scrub juniper. Undergrowth, sage, blackbrush, brigham tea and cactus.</p> <hr/>
	<p>North, on a Sectional Guide Meridian, bet. secs. 13 and 14.</p>
	<p>Over gently rolling land through scattered scrub juniper.</p>
<p>40.00</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T37NR5W <math>\frac{1}{4}</math> S14 S13 1962</p>
<p>80.00</p>	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T37NR5W <math>\frac{S11 S12}{S14 S13}</math> 1962</p> <p>Land, rolling. Soil, rocky sandy loam. Timber, scattered scrub juniper. Undergrowth, cactus and brush.</p> <hr/>
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>N. 89°59' W., bet. secs. 12 and 13.</p>

## CHAINS

Over rolling land through scattered juniper and pinon.

2.70 Wash, 30 lks. wide, 1 ft. deep, drains N. circling to NE.

38.06 Point for the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, at 40.00 chs. in easting from the cor. of secs. 11, 12, 13 and 14.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T37NR5W

$\frac{1}{4}$   $\frac{S\ 12}{S\ 13}$

1962

69.70 Unimproved dirt road, bears SE. and NW.

72.00 Small wash, drains N. 20° W.

78.06 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.

Soil, sandy.

Timber, scattered juniper and pinon.

Undergrowth, sage, brigham tea and cactus.

North, on a Sectional Guide Meridian, bet. secs. 11 and 12.

Over rolling land.

4.80 Small wash, drains NW.

5.80 Unimproved dirt road, bears N. 60° W. and S. 60° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T37NR5W

$\frac{1}{4}$  S11|S12

1962

78.40 Small wash, drains N. 30° E.

80.00 Point for the sec. cor. of secs. 1, 2, 11 and 12.

Set the iron post on solid rock, mound with stones to top, cap mkd.

T37NR5W

S 2 | S 1  
S11 | S12

1962

Land, gently rolling hills.

Soil, rocky and shallow sand.

Timber, scrub juniper.

Undergrowth, brush, brigham tea and cactus.

From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township, monumented by an iron post as described in the official record.

S. 89°58' W., bet. secs. 1 and 12.

4003  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 37 N., R. 5 W.
	Over rolling land, through moderate scrub junipers.
4.10	Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.
27.50	Wash, 25 lks. wide, 1 ft. deep, drains N.
38.14	Point for the 1/4 sec. cor. of secs. 1 and 12, at 40.00 chs. in easting from the cor. of secs. 1, 2, 11 and 12.  Set the iron post 3 ins. in the ground, mound with stones to top, cap mkd.
	T37NR5W 1/4 S 1 S 12 1962
57.90	Wash, 10 lks. wide, 1 ft. deep, drains N.
65.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° E.
65.70	Trail, bears N. 10° E. and S. 10° W.
74.00	Small wash, drains NW. circling to N.
76.60	Small wash, drains NE.
78.14	The cor. of secs. 1, 2, 11 and 12.  Land, rolling. Soil, rocky and sandy. Timber, moderate scrub juniper. Undergrowth, brigham tea, weeds and cactus.
	North, on a Sectional Guide Meridian, bet. secs. 1 and 2.
	Over rolling hills through scattered junipers.
17.20	Track road, bears NE. and SW.
20.00	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° E.
30.80	Barbed wire fence, bears N. 81°50' W. for about 8.00 chs.; thence, NW. and S. 81°50' E. for about 1.00 chain; thence SE.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.  Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T37NR5W 1/4 S 2   S 1 1962
80.13	Intersect the S. bdy. of T. 38 N., R. 5 W.  Point for the closing cor. of secs. 1 and 2.

CHAINS

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T38N  
S 36  
 S 2 | S 1  
 T37NR5W  
 CC  
 1962

The cor. originally set as the cor. of secs. 1, 2, 35 and 36, bears N. 89°59' W., 1.91 chs. dist., monumented by an iron post as described in the official record. This cor. now functions as the cor. of secs. 35 and 36, T. 38 N., R. 5 W., only, remarked

T38NR5W  
S35 | S36  
 S 2  
 T37N  
 62  
 1925

Land, gently rolling hills.  
 Soil, rocky and sandy.  
 Timber, scattered scrub juniper.  
 Undergrowth, black brush, cactus and brigham tea.

The point for the ¼ sec. cor. of sec. 1 is on the N. bdy. at 40.00 chs. S. 89°59' E. of the closing cor. of secs. 1 and 2.

Set the iron post 26 ins. in the ground, cap mkd.

T38N  
¼ S 1  
 T37NR5W  
 1962

Raise a mound of stone S. of the cor.

The cor. originally set as the ¼ sec. cor. of secs. 1 and 36 bears N. 89°59' W., 1.91 chs. dist., monumented by an iron post as described in the official record. This cor. now functions as the ¼ sec. cor. of sec. 36, T. 38 N., R. 5 W., only, remarked

¼ S 36  
          
 62  
 1925

From the cor. of secs. 11, 12, 13 and 14.

West, bet. secs. 11 and 14, parallel to the S. bdy. of the township.

Over gently rolling land, through scattered timber.

25.70 Track road, bears SW. and N. 60° E.

40.00 Point for the ¼ sec. cor. of secs. 11 and 14.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 37 N., R. 5 W.
	T37NR5W $\frac{1}{4}$ $\frac{S\ 11}{S\ 14}$ 1962
72.10	Track road, bears NW. and SE.
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set the iron post 20 ins. in the ground, cap mkd.
	T37NR5W $\frac{S10}{S15}$   $\frac{S11}{S14}$ 1962
	Raise a mound of stone W. of cor. Land, gently rolling. Soil, gravel and sandy clay. Timber, scattered juniper and pinon. Undergrowth, black brush, brigham tea and cactus.
	N. 0°01' W., bet. secs. 10 and 11. Over gently rolling land through scattered timber.
6.60	Track road, bears NW. and SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11. Set the iron post 18 ins. in the ground, mound with stone to top, cap mkd.
	T37NR5W $\frac{1}{4}$ $\frac{S10}{S11}$ 1962
65.00	Small wash, drains N. 70° E.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T37NR5W $\frac{S\ 3}{S10}$   $\frac{S\ 2}{S11}$ 1962
	Land, gently rolling. Soil, gravel and sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, black brush, brigham tea and cactus.
	From the cor. of secs. 1, 2, 11 and 12. West, bet. secs. 2 and 11. Over rolling land, through scattered timber.

CHAINS

20.70 Track road, bears N. and S.

21.50 Wash, 30 lks. wide, 1 ft. deep, drains N.

40.02 Point for the 1/4 sec. cor. of secs. 2 and 11.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T37NR5W

1/4 S 2 / S 11

1962

65.40 Track road, bears N. 15° W. and S. 15° E.

80.04 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.  
Soil, rocky sandy loam.  
Timber, scattered scrub juniper.  
Undergrowth, sage, brigham tea and cactus.

N. 0°01' W., bet. secs. 2 and 3.

Over nearly level land through scattered juniper and pinon.

32.60 Fence, bears irregularly E. and W.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 3.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T37NR5W

1/2 S 3 | S 2

1962

51.70 Bottom of small draw, drains N. 75° E. for about 4.00 chs., thence N.

61.20 Draw, drains NE. circling to N.

80.18 Intersect the S. bdy. of T. 38 N., R. 5 W.

Point for the closing cor. of secs. 2 and 3.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

S 3 | S 2

T37NR5W

CC

1962

The cor. of secs. 2, 3, 34 and 35 bears N. 89°59' W., 1.96 chs. dist., monumented by an iron post as described in the official record. This cor. now functions as the cor. of secs. 34 and 35, T. 38 N., R. 5 W., only, remarked

T38NR5W

S34 | S35

S 3

T37N

62

1925

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Township 37 North, Range 5 West, Arizona

Land, gently rolling.  
Soil, rocky sandy loam.  
Timber, scattered juniper and pinon.  
Undergrowth, sage, brigham tea and cactus.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 2 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{4}$  S 2  
T37NR5W  
1962

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 35 bears N.  $89^{\circ}59'$  W., 1.93 chs. dist., monumented by an iron post as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 35, T. 38 N., R. 5 W., only, remarked

$\frac{1}{4}$  S 35  
62  
1925

General Description

The land surveyed in T. 37 N., R. 5 W., varies from steep and broken in sections 24, 25 and 36 to gently rolling in the remainder. The soil is of a rocky sandy loam with sandy clay and broken ledges along Hack Canyon.

Scattered to moderate juniper and pinon are found over most of the area, with blackbrush, sage, brigham tea, grass and cactus the predominating undergrowth. The land is, at present, primarily used for limited grazing of livestock.

Mining has been carried on in Hack Canyon but there is no activity on a commercial scale at the present time.

Form 4-680  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Alan R. Crockett	Note Keeper
Harold Chemas	Front Chainman
Tom Carter	Flagman
Albert Emett	Cornerman
Jimmie Schmutz	Axeman
Gary Oviatt	Transitman
Dan Bauer	Front Chainman
Robert Monasmith	Flagman
George Chemas	Cornerman
Gordon Black	Axeman



15

CERTIFICATE OF SURVEY

We, Boyd S. Owens  
Paul G. Bauer  
Wallace R. Ott, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 20th day of June, 1962,

We have independently resurveyed a portion of the south boundary and a portion of the east boundary, and surveyed a portion of the subdivisional lines of Township 37 North, Range 5 West

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~<sup>us</sup> and under ~~my~~<sup>our</sup> direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 23, 1963  
(Date)

April 23, 1963

April 23, 1963  
(Date)

Boyd S. Owens  
(Cadastral Surveyor)  
Paul G. Bauer  
Surveying Technician  
Wallace R. Ott  
Surveying (Cadastral Surveyor) Aid

CERTIFICATE OF APPROVAL

Bureau of Land Management

The foregoing field notes of the dependent resurvey of a portion of the south boundary and a portion of the east boundary, and survey of a portion of the subdivisional lines of Township 37 North, Range 5 West, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens, Cadastral Surveyor  
Paul G. Bauer, Surveying Technician  
Wallace R. Ott, Surveying Aid

having been critically examined and found correct, are hereby approved.

Washington, D. C.

AUG 29 1963  
(Date)

[Signature]  
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_ is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)