

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

Section 3

SURVEY

Subdivisions Section 3

Township 1 North, Range 8 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Paul G. Bauer, Surveying Technician

Under special instructions dated June 6, 1963, which provided for the surveys included under Group Number 400, approved June 10, 1963, and assignment instructions dated June 10, 1963.

Survey commenced June 11, 1963

Survey completed July 5, 1963

1A

BOOK 4678

INDEX DIAGRAM

Township 1 North, Range 8 East
10 9

6	5	4	7 14 5	12 8 11	4 13 3	2	1
7	8	9	2	1	10	11	12
18	17	16	15	14	13	12	11
19	20	21	22	23	24	25	26
30	29	28	27	26	25	24	23
31	32	33	34	35	36	37	38

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

16

CHAINS

Township 1 North, Range 8 East, G&SRM, Arizona

The boundaries of section 3 were surveyed in 1924 by Averill and Wilson.

The following field notes are those of a dependent resurvey of the boundaries of section 3, and a survey of the subdivision of section 3.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 6, 1963.

Only the true line bearings and distances for the surveyed lines are given in these notes. The Bathey markers are "T" iron stakes, 24 inches long, with aluminum caps.

The geographic position of the southeast corner of section 3 is: Latitude 33°27'05" North, and Longitude 111°30'39" West, as determined from the Apache Junction Quadrangle, Arizona, by the U. S. Geological Survey.

The magnetic declination was found to be 14°30' East.

Dependent Resurvey, Section 3, T. 1 N., R. 8 E.

Reestablishment of the Survey executed in 1924
by Averill and Wilson

Beginning at the corner of secs. 2, 3, 10 and 11, an iron post as described in the official record.

S. 89°58' W., bet. secs. 3 and 10.

Over nearly level land, through palo verde and cacti.

- 1.40 Transmission line, bears N. 77° E. and S. 77° W.
- 3.90 Wash, 30 lks. wide, 1 ft. deep, drains SW.
- 6.30 Wash, 15 lks. wide, 2 ft. deep, drains SW.
- 6.40 Transmission line, bears N. 72° E. and S. 72° W.
- 9.80 Access road, parallel to transmission line.
- 10.16 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 13.95 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 20.024 Point for the E. 1/16 cor. of secs. 3 and 10.
- Set an iron post 30 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, 1½ ft. diam., cap of post mkd.

T1N R8E

LOT

204

E 1/16 $\frac{S 3}{S 10}$

1963

Deposit glass.

CHAINS																						
25.03	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd. <u>203 204</u>																					
25.17	Wash, 10 lks. wide, 1 ft. deep, drains SE.																					
30.036	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd. <u>202 203</u>																					
34.86	Wash, 15 lks. wide, 1 ft. deep, drains SW.																					
35.042	Set a Bathey marker 19 ins. in the ground, in a collar of stone, cap mkd. <u>201 202</u>																					
37.90	Bladed road, bears N. 30° E. and S. 30° W.																					
40.048	The ¼ sec. cor. of secs. 3 and 10, monumented by an iron post as described in the official record. Remarked the cor. to read <div style="text-align: center;"> <table border="0"> <tr> <td>L</td> <td>T1N</td> <td>R8E</td> <td>L</td> </tr> <tr> <td>188</td> <td>¼</td> <td><u>S 3</u></td> <td>201</td> </tr> <tr> <td></td> <td></td> <td>S10</td> <td></td> </tr> <tr> <td></td> <td></td> <td>63</td> <td></td> </tr> <tr> <td></td> <td></td> <td>1924</td> <td></td> </tr> </table> </div> <hr/>	L	T1N	R8E	L	188	¼	<u>S 3</u>	201			S10				63				1924		
L	T1N	R8E	L																			
188	¼	<u>S 3</u>	201																			
		S10																				
		63																				
		1924																				
	S. 89°59' W., beginning new measurement.																					
	Over nearly level land.																					
.16	Wash, 25 lks. wide, 2 ft. deep, drains SW.																					
1.65	Bladed road, bears N. 20° E. and S. 20° W.																					
5.001	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd. <u>187 188</u>																					
10.002	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd. <u>186 187</u>																					
15.003	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd. <u>185 186</u>																					
18.40	Wash, 40 lks. wide, 2 ft. deep, drains SW.																					
20.004	Point for the W. 1/16 cor. of secs. 3 and 10. Set an iron post 30 ins. long, 2½ ins. diam., 23 ins. in the ground, mound with stone to top, 2 ft. base, cap mkd.																					

BOOK 4870
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS											
	Dependent Resurvey, Sec. 3, T. 1 N., R. 8 E., Arizona										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">LOT</td> <td style="text-align: center;">LOT</td> </tr> <tr> <td style="text-align: center;">172</td> <td style="text-align: center;">185</td> </tr> <tr> <td style="text-align: center;">W $\frac{1}{16}$</td> <td style="text-align: center;">S $\frac{3}{10}$</td> </tr> <tr> <td colspan="2" style="text-align: center;">1963</td> </tr> </table>	LOT	LOT	172	185	W $\frac{1}{16}$	S $\frac{3}{10}$	1963			
LOT	LOT										
172	185										
W $\frac{1}{16}$	S $\frac{3}{10}$										
1963											
	Deposit glass										
22.80	Bladed road, bears N. and S.										
25.005	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.										
	<u>171 172</u>										
29.10	Wash, 15 lks. wide, 1 ft. deep, drains S.										
30.006	Set a Bathey marker, 19 ins. in the ground, in a collar of stone, cap mkd.										
	<u>170 171</u>										
35.007	Set a Bathey marker 21 ins. in the ground, in a collar of stone, cap mkd.										
	<u>169 170</u>										
35.800	Wash, 10 lks. wide, 1 ft. deep, drains S.										
39.700	Track road, bears N. and S.										
39.820	Fence, barbed wire, bears irregularly N. and S.										
40.008	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post as described in the official record.										
	Remarked the cor. to read										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T1N R8E</td> <td style="text-align: center;">LOT</td> </tr> <tr> <td style="text-align: center;">S 4 S 3</td> <td style="text-align: center;">169</td> </tr> <tr> <td style="text-align: center;">S 9 S 10</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">63</td> </tr> <tr> <td colspan="2" style="text-align: center;">1924</td> </tr> </table>	T1N R8E	LOT	S 4 S 3	169	S 9 S 10		63		1924	
T1N R8E	LOT										
S 4 S 3	169										
S 9 S 10											
63											
1924											
	Land, nearly level. Soil, sandy and gravelly. Timber, palo verde and ironwood. Undergrowth, greasewood and cacti.										
	From the cor. of secs. 2, 3, 10 and 11.										
	N. 0°07' W., bet. secs. 2 and 3.										
	Over nearly level land, through palo verde and cacti.										
.310	Transmission line, bears N. 77° E. and S. 77° W.										
1.970	Transmission line, bears N. 72° E. and S. 72° W.										
2.200	Access road, parallel to transmission line.										

CHAINS		
3.200	Wash, 15 lks. wide, 1 ft. deep, drains SW.	
10.007	Set a Bathey marker, 16 ins. in the ground, in a collar of stone, cap mkd.	
15.010	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	
16.500	Wash, 15 lks. wide, 1 ft. deep, drains SW. from N. 5° E.	
19.400	Transmission line, bears N. 50°45' W. and S. 50°45' E.	
20.013	Point for the S. 1/16 cor. of secs. 2 and 3. Set an iron post 30 ins. long 2½ ins. diam., 30 ins. in the ground, with brass cap mkd.	
25.016	Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.	
29.280	Intersect the S. bdy. of Survey No. 4598 Bulldog #2 lode claim. Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.	
34.500	Top of low knoll.	
40.026	The ¼ sec. cor. of secs. 2 and 3, monumented by an iron post, as described in the official record. N. 0°04' W., beginning new measurement. Over gently rolling land.	

212

205
212

LOT
108 S $\frac{1}{16}$
S3|S2
LOT
205
1963

Deposit glass

This cor. is in the center of a power line access road.

101
108

101

from which

Cor No. 1 of the Bulldog #2 and Cor. No. 1 of the Enterprise #2 lode claims, Mineral Survey No. 4598, Arizona, monumented by an iron post 1 inch diam., projecting 18 ins. above ground, bears S. 83°10'20" W., 0.178 chs. dist., with brass cap mkd.

MS4598
E2 BD2
1 | 1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

5.

CHAINS	
	Dependent Resurvey, Sec. 3, T. 1 N., R. 8 E., Arizona
10.840	Track road, bears NW. and SE.
12.300	Wash, 30 lks. wide, 2 ft. deep, drains S. 70° W.
17.100	Wash, 15 lks. wide, 5 ft. deep, drains S. 70° W.
19.400	Shaft, 25 ft. deep.
19.982	Point for the N. 1/16 cor. of secs. 2 and 3.
	Set an iron post 30 ins. long, 2½ ins. diam., 11 ins. in the ground, mound with stone to cap, 2 ft. base, cap mkd.
	$N \frac{1}{16}$ $S3 S2$ 1963
	Deposit glass
22.300	Bladed road, bears NE. and SW.
26.100	Same road, bears NW. and SE.
40.084	The cor. of secs. 2, 3, 34 and 35, monumented by an iron post as described in the official record.
	from which
	Cor. No. 1 of Mineral Survey No. 4598 Bull Dog #1 lode claim bears S. 37°02'45" E., 5.79 chs. dist.
	Land, gently rolling. Soil, gravelly. Timber, palo verde and ironwood. Undergrowth, greasewood and cacti.
	From the cor. of secs. 3, 4, 9 and 10.
	N. 0°02' W., bet. secs. 3 and 4.
	Over nearly level land.
.510	Power line, bears S. 89°53' W. and terminates 50 lks. N. 89°53' E.
.600	Enter wash, 30 lks. wide, 1 ft. deep, drains S. 2° W.
2.200	Leave same wash.
3.900	Reenter same wash.
4.993	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.
	$\frac{168}{169}$
	from which
	An irregular N-W fence line bears E., 0.67 chs. distant.
5.010	Reenter same wash, drains S. 10° W., from N.

6

CHAINS			
7.500	Leave wash.		
9.986	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	$\begin{array}{r} 161 \\ 168 \end{array}$	
	from which		
	Same N-S fence line bears E., 1.02 chs. dist.		
14.980	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	$\begin{array}{r} 160 \\ 161 \end{array}$	
	from which		
	Same N-S fence line bears E., 1.28 chs. dist.		
19.973	Point for the S. 1/16 cor. of secs. 3 and 4.		
	Set an iron post 30 ins. long, 2½ ins. in diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.	<p>T1N R8E S $\frac{1}{16}$ LOT 153 S4 S3 LOT 160 1963</p>	
	Deposit glass		
	from which		
	Same N-S fence line bears E., 1.50 chs. dist.		
23.750	Wash, 15 lks. wide, 1 ft. deep, drains SE.		
24.966	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	$\begin{array}{r} 152 \\ 153 \end{array}$	
	from which		
	Same N-S fence line bears E., 1.62 chs. dist.		
29.960	Set a Bathey marker 18 ins. in the ground, in a collar fo stone, cap mkd.	$\begin{array}{r} 145 \\ 152 \end{array}$	
30.330	Reenter same wash, 10 lks. wide, 1 ft. deep, drains S.		
32.250	Leave wash, drains S.		
34.953	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	$\begin{array}{r} 144 \\ 145 \end{array}$	
	from which		
	Same N-S fence line bears E., 0.635 chs. dist.		

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Dependent Resurvey, Sec. 3, T. 1 N., R. 8 E., Arizona
39.947	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented by an iron post as described in the official record.</p> <p>Remarked the cor. to read</p> <div style="text-align: center;"> $\frac{1}{4}$ LOT 65 S 4 S 3 LOT 144 63 1924</div> <hr style="width: 20%; margin: auto;"/> <p>N. 0°03' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
4.991	<p>Iron pin, $\frac{1}{2}$ in. diam., projecting 3 ins. above the ground.</p>
4.993	<p>Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.</p>
	<div style="text-align: center;"> $\frac{64}{65}$ </div>
	<p>from which</p>
	<p style="padding-left: 40px;">Same N-S fence line bears E., 0.295 chs. dist.</p>
9.981	<p>An iron pin, $\frac{1}{2}$ in. in diam., projecting 2 ins. above the ground.</p>
9.986	<p>Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.</p>
	<div style="text-align: center;"> $\frac{57}{64}$ </div>
	<p>from which</p>
	<p style="padding-left: 40px;">Same N-S fence line bears E., 0.276 chs. dist.</p>
10.150	<p>Bladed road, bears N. and W.</p>
14.979	<p>Set a Bathey marker 30 ins. in the ground, level with road surface, cap mkd.</p>
	<div style="text-align: center;"> $\frac{56}{57}$ </div>
	<p>From which</p>
	<p style="padding-left: 40px;">An iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., set 16 ins. in the ground, for a reference monument, bears N. 41°50' E., 0.682 chs. dist., with brass mkd. RM S3 45 ft. 1963 and an arrow pointing to the true cor.</p>
	<p style="padding-left: 40px;">An iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., set 16 ins. in the ground, for a reference monument, bears S. 48°33' E., .61 chs. dist., with brass cap mkd. RM S3 40.24 ft. 1963 and an arrow pointing to the true cor.</p>

CHAINS		
19.973	<p>Same N-S fence line bears E., 0.254 chs. dist.</p> <p>Point for the N. 1/16 cor. of secs. 3 and 4 falls in same road.</p>	
	<p>Set a "Copperweld," a copper coated steel rod, 24 ins. long, 5/8 ins. diam., cut back to 16 ins. long and set 22 ins. in the ground, cap mkd.</p>	
		<p>BLM N $\frac{1}{16}$ S 4 S 3 1963</p>
	<p>from which</p>	
	<p>An iron post 30 ins. long, 2½ ins. diam., set 16 ins. in the ground, for a reference monument, bears N. 40°46' E., 0.697 chs. dist., with brass cap mkd. RM S3 45.96 ft. 1963 and an arrow pointing to the true cor.</p>	
	<p>An iron post 30 ins. long, 2½ ins. diam., set 16 ins. in the ground, for a reference monument, bears S. 49°37' E., 0.599 chs. dist., with brass cap mkd. RM S3 39.55 ft. 1963 and an arrow pointing to the true cor.</p>	
	<p>Same N-S fence line bears E., 0.238 chs. dist.</p>	
20.270	<p>Intersection of bladed roads, N., S. and W.</p>	
24.960	<p>An iron pin, ½ in. diam., projecting 2 ins. above the ground.</p>	
24.966	<p>Set a Bathey marker 16 ins. in the ground, in a collar of stone, on W. edge of road, cap mkd.</p>	
		<p> 48 49</p>
	<p>from which</p>	
	<p>Same N-S fence line bears E., 0.254 chs. dist.</p>	
25.830	<p>Leave road, bears N. 30° W. and S.</p>	
29.957	<p>An iron pin, ½ in. diam., projecting 5 ins. above the ground.</p>	
29.959	<p>Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.</p>	
		<p> 41 48</p>
	<p>from which</p>	
	<p>Same N-S fence line bears E., 0.259 chs. dist.</p>	
31.476	<p>Fall 0.006 chs. E. of a ½ in. galvanized pipe, projecting 2 ins. above the ground.</p>	
34.953	<p>Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.</p>	
		<p> 40 41</p>
	<p>from which</p>	
	<p>Same N-S fence line bears E., 0.254 chs. dist.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS															
	Dependent Resurvey, Sec. 3, T. 1 N., R. 8 E., Arizona														
40.086	<p>The cor. of secs. 3, 4, 33 and 34, monumented by an iron post as described in the official record.</p> <p>Remarked the cor. to read</p> <div style="text-align: center;"> <table border="0"> <tr><td>T2N</td><td>R8E</td></tr> <tr><td><u>S33</u></td><td><u>S34</u></td></tr> <tr><td>S 3</td><td>S 3</td></tr> <tr><td>T1N</td><td>LOT</td></tr> <tr><td></td><td>40</td></tr> <tr><td></td><td>63</td></tr> <tr><td></td><td>1924</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">An E-W fence line bears North, 0.03 chs. dist.</p> <p>Land, nearly level. Soil, shallow, gravelly. Timber, palo verde and ironwood. Undergrowth, greasewood and cacti.</p>	T2N	R8E	<u>S33</u>	<u>S34</u>	S 3	S 3	T1N	LOT		40		63		1924
T2N	R8E														
<u>S33</u>	<u>S34</u>														
S 3	S 3														
T1N	LOT														
	40														
	63														
	1924														
	<p>From the cor. of secs. 2, 3, 34 and 35.</p> <p>S. 89°56' W., bet. secs. 3 and 34.</p> <p>Over rolling and mountainous land.</p>														
13.270	Wash, 10 lks. wide, 2 ft. deep, drains SE.														
19.955	<p>Point for the E. 1/16 cor. of secs. 3 and 34.</p> <p>Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone to cap, 2½ ft. base, cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>E</td><td><u>1</u></td><td><u>S34</u></td></tr> <tr><td></td><td>16</td><td>S 3</td></tr> <tr><td></td><td></td><td>1963</td></tr> </table> </div> <p>Deposit glass</p> <p>from which</p> <p style="padding-left: 40px;">An E-W fence line bears North, 0.01 chs. dist.</p> <p>Asc. steep E. slope.</p>	E	<u>1</u>	<u>S34</u>		16	S 3			1963					
E	<u>1</u>	<u>S34</u>													
	16	S 3													
		1963													
27.800	Top of N. edge of rocky knoll, descend steep W. slope.														
32.500	Land levels.														
34.400	Descend steep W. slope over cliffs.														
38.750	Base of cliffs.														
39.911	<p>The ¼ sec. cor. of secs. 3 and 34, monumented by an iron post as described in the official record.</p> <p>Remarked the cor. to read</p>														

CHAINS

T2N R8E
 $\frac{1}{4}$ $\frac{S\ 34}{S\ 3}$
 LOT T1N
 21 63
 1924

S. 89°56' W., beginning new measurement.

Over rolling land.

4.250 Wash, 10 lks. wide, 1 ft. deep, drains SW.

5.008 Set a Bathey marker 12 ins. in the ground, in a collar of stone, cap mkd.

22|21

from which

An E-W fence line bears North, 0.06 chs. dist.

7.000 Wash, 20 lks. wide, 3 ft. deep, drains S., asc. SE. slope.

10.017 Set a Bathey marker 15 ins. in the ground, in a collar of stone, cap mkd.

23|22

from which

An E-W fence line bears North, 0.07 chs. dist.

15.025 Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.

24|23

from which

An E-W fence line bears North, 0.035 chs. dist.

20.034 Point for the W. 1/16 cor. of secs. 3 and 34.

Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, 2 ft. base, cap mkd.

T2N R8E
 $\frac{1}{16}$ $\frac{S34}{S\ 3}$
 W
 LOT T1N LOT
 37 1963 24

Deposit glass

from which

An E-W fence line bears North, 0.01 chs. dist.

20.300 Same fence, bears S. 89°53' W.

21.400 Desc. SW. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Dependent Resurvey, Sec. 3, T. 1 N., R. 8 E., Arizona
25.042	Set a Bathey marker 16 ins. in the ground, in a collar of stone, in an E-W fence, cap mkd.
	$\frac{38}{37}$
30.051	Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.
	$\frac{39}{38}$
	from which
	An E-W fence line bears North, 0.02 chs. dist.
32.000	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
35.059	Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.
	$\frac{40}{39}$
	from which
	An E-W fence line bears North, 0.015 chs. dist.
35.200	Power line, bears N. 50°45' W., and S. 50°45' E.
35.400	Access road to power line.
39.840	N-S fence line.
40.068	The cor. of secs. 3, 4, 33 and 34.
	Land, steep and mountainous.
	Soil, rocky.
	Timber, scattered palo verde and ironwood.
	Undergrowth, greasewood and cacti.
	Subdivision, Sec. 3, T. 1 N., R. 8 E., Arizona
	From the $\frac{1}{2}$ sec. cor. of secs. 3 and 10.
	N. 0°00'30" E., on the N. and S. center line of sec. 3.
	Over nearly level land, up a wash, 20 lks. wide, 1 ft. deep.
4.999	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.
	$\frac{181}{188} \frac{200}{201}$
5.300	Leave wash.
7.300	Bladed road, bears NE. and SW.
9.998	Set a Bathey marker 19 ins. in the ground, in a collar of stone, cap mkd.
	$\frac{180}{181} \frac{193}{200}$

CHAINS		
14.997	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 173 & 192 \\ \hline 180 & 193 \end{array}$
16.200	Wash, 10 lks. wide, 1 ft. deep, drains SW.	
19.997	Point for the CS 1/16 cor. of sec. 3.	
	Set an iron post 30 ins. long, 2½ ins. diam., 26 ins. in the ground, mound of stone to cap, 1½ ft. base, cap mkd.	
		<p>LOT LOT 140 121</p> <p>C-S $\frac{1}{16}$ S3</p> <p>LOT LOT 173 192</p> <p>1963</p>
	Deposit glass.	
24.996	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 133 & 120 \\ \hline 140 & 121 \end{array}$
29.996	Set a Bathey marker 22 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 132 & 113 \\ \hline 133 & 120 \end{array}$
34.995	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 125 & 112 \\ \hline 132 & 113 \end{array}$
39.995	Point for the C¼ cor. of sec. 3.	
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.	
		<p>LOT LOT 84 97</p> <p>C $\frac{1}{4}$ S 3</p> <p>LOT LOT 125 112</p> <p>1963</p>
	Deposit glass.	
44.989	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 77 & 96 \\ \hline 84 & 97 \end{array}$
46.180	Bladed road, bears N. 75° W. and S. 75° E.	
49.984	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 76 & 89 \\ \hline 77 & 96 \end{array}$

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, Sec. 3, T. 1 N., R. 8 E., Arizona
51.400	Power line, bears N. 50°45' W. and S. 50°45' E.
51.900	Access road, parallel to power line.
54.978	Set a Bathey marker 21 ins. in the ground, in a collar of stone, cap mkd.
	$\begin{array}{r l} 69 & 88 \\ \hline 76 & 89 \end{array}$
59.973	Point for the CN 1/16 cor. of sec. 3.
	Set an iron post 30 ins. long, 2½ ins. diam., 28 ins. in the ground, in a collar of stone, 2 ft. diam., with brass cap mkd.
	<p>LOT 36</p> <p style="margin-left: 40px;">N $\frac{1}{16}$</p> <p style="margin-left: 40px;">C</p> <p style="margin-left: 40px;"> </p> <p style="margin-left: 40px;">C</p> <p style="margin-left: 40px;">S3</p> <p>LOT LOT</p> <p>69 88</p> <p>1963</p>
	Deposit glass.
64.000	Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.
64.967	Set a Bathey marker, 6 ins. in the ground, mound of stone to cap, 3 ft. base, cap mkd.
	$\begin{array}{r l} 29 & \\ \hline 36 & \end{array}$
65.400	Wash, 10 lks. wide, 2 ft. deep, drains SW.
67.200	Wash, 10 lks. wide, 1 ft. deep, drains SW.
68.700	Wash, 15 lks. wide, 2 ft. deep, drains SW.
69.962	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.
	$\begin{array}{r l} 28 & \\ \hline 29 & \end{array}$
74.956	Set a Bathey marker 12 ins. in the ground, mound of stone to cap, 2 ft. base, cap mkd.
	$\begin{array}{r l} 21 & \\ \hline 28 & \end{array}$
76.300	Wash, 20 lks. wide, 2 ft. deep, drains S. 75° W.
80.082	The ¼ sec. cor. of secs. 3 and 34, on the N. bdy. of the township.
	<hr/> <p>From the ¼ sec. cor. of secs. 2 and 3.</p> <p>S. 89°55'30" W. on the E. and W. center line of sec. 3.</p>

CHAINS		
	Over nearly level ground.	
3.100	Wash, 45 lks. wide, 1 ft. deep, drains SW.	
7.000	Bladed road, bears N. 31° E. and S. 31° W.	
12.200	Wash, 15 lks. wide, 1 ft. deep, drains S.	
19.980	Point for the CE 1/16 cor. of sec. 3.	
	Set an iron post 30 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, 1½ ft. diam., with brass cap mkd.	
		LOT E 1 100 16 C — C S3 LOT 109 1963
	Deposit glass.	
23.800	Bladed road, bears N. 30° E. and S. 30° W.	
24.975	Set a Bathey marker, 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 99 & 100 \\ \hline 110 & 109 \end{array}$
29.970	Set a Bathey marker 20 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 98 & 99 \\ \hline 111 & 110 \end{array}$
30.140	Access road parallel to power line.	
30.840	Power line, bears N. 50°50' W. and S. 50°50' E.	
34.965	Set a Bathey marker 22 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 97 & 98 \\ \hline 112 & 111 \end{array}$
39.960	The C ¼ cor. of sec. 3.	
44.963	Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 83 & 84 \\ \hline 126 & 125 \end{array}$
49.967	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 82 & 83 \\ \hline 127 & 126 \end{array}$
51.460	Wash, 50 lks. wide, 4 ft. deep, drains S. 30° W.	
53.400	Track road, bears NE. and SW.	
54.970	Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.	
		$\begin{array}{r l} 81 & 82 \\ \hline 128 & 127 \end{array}$
59.974	Point for the CW 1/16 cor. of sec. 3.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Subdivision, Sec. 3, T. 1 N., R. 8 E., Arizona

Set an iron post 30 ins. long, 2½ ins. diam, 24 ins. in the ground, in a collar of stone, 1½ ft. diam. with brass cap mkd.

LOT	LOT
68	81
W $\frac{1}{16}$	
C ——— C	
S3	
LOT	LOT
141	128
1963	

Deposit glass.

62.500 Wash, 15 lks. wide, 1 ft. deep, drains S.

64.977 Set a Bathey marker 18 ins. in the ground, in a collar of stone, cap mkd.

67	68
142	141

69.981 Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.

66	67
143	142

74.100 Wash, 15 lks. wide, 1 ft. deep, drains S.

74.984 Set a Bathey marker 16 ins. in the ground, in a collar of stone, cap mkd.

65	66
144	143

79.643 Fence, barbed wire, bears irregularly N. and S.

79.988 The ¼ sec. cor. of secs. 3 and 4.

The remaining subdivisions of section 3 as shown on the plat of this survey were surveyed and the corner monuments set. The plat gives the true bearings and distances and the legend indicates the kind of marker set at the corners.

General Description

The general elevation of section 3 is from about 1910 to 2000 feet above sea level. The north central portion is rough and stony, and the remainder is nearly level to gently rolling. The soil is sandy and gravelly. The general drainage is to the south. There is a medium growth of palo verde and ironwood trees, with numerous sahuaro cactus throughout the section.

17

BOOK 4073

CERTIFICATE OF SURVEY

I, Paul G. Bauer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of June, 1963, I have dependently resurveyed the boundaries of section 3 and surveyed subdivisions in section 3, Township 1 North, Range 8 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

(Date)

July 5, 1963

(Date)

(Cadastral Surveyor)

Paul G. Bauer

~~Subordinate Surveyor~~
Surveying Technician

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the dependent resurvey of the boundaries and survey of subdivisions in section 3, Township 1 North, Range 8 East, Gila and Salt River Meridian, Arizona

executed by Paul G. Bauer, Surveying Technician

having been critically examined and found correct, are hereby approved.
Washington, D.C.

SEP 11 1963

(Date)

Clark J. Lumm

Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)