Form 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY
Subdivisional Lines
Township 41 North, Range 11 West
Of the Gila and Salt River Meridian
In the State of Arizona
EXECUTED BY
Boyd S. Owens, Cadastral Surveyor
Wallace R. Ott, Surveying Aid
Under special instructions datedJune 22, 19 62_, which provided for the survey
included under Group Number 377, approved July 2, 1962
and assignment instructions dated <u>August 31</u> , 19 <u>62</u> .
Survey commenced September 4 1962

October 8

Survey completed ___

_____, 19 62

4675

INDEX DIAGRAM

Township41 N			l Noi	rth		, Range_	11	West		,
6	39	5	28	4	. 21	8	14	2	7	1
38		38		27		20		13		7
7	37	8	27	9	20		13	11	6	12
36		36		26		19		12	 -	6
18	35		26	16	19	18	12	14	5	13
35		34		25	-	18		11		4
19	33	20	24	21	17	22	10	28	4	24
32		32		24		17		10		3
30	31	29	23	28	16	27	9	26	2	25
30		30		22		15		8		2
31	29	82	22	88	15	84	8	85	1	36

FIELD NOTE PAPER

1. B

	CHAINS	
		Township 41 North, Range 11 West
		Gila and Salt River Meridian, Arizona
•		The south boundary, which is the Tenth Standard Parallel North, was surveyed in 1939 by Muscott, Warner and Motch. The west boundary was surveyed in 1921 by J. P. Davis and dependently resurveyed in 1956 by P. K. Russell.
		The north and east boundaries were surveyed in 1956 by P. K. Russell.
	,	The following notes describe a survey of the subdivision- al lines of Township 41 North, Range 11 West, Gila and Salt River Meridian, Arizona.
		This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 22, 1962.
		Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base and with a brass cap riveted to the top.
		The geographical position of the southeast corner of the township is: Latitude, 36°54'13.61" North and Longitude, 113°25'28.77" West.
	·	The magnetic declination was found to be 16° East.
		Survey of the Subdivisional Lines
		Township 41 North, Range 11 West
•		
		From the Standard Corner of secs. 35 and 36 on the S. bdy. of the township, monumented by an iron post as described in the official record.
		N. 0°01' W., bet. secs. 35 and 36.
		Desc. over rocky NW. slope.
	4.90	Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. over SE. slope.
	9.80	Spur, slopes N. 30° E.; desc. along rolling E. slope.
	17.80	Spur, slopes irregularly N.
	34.20	Bank of wash, about 30 ft. high.
	36.60	Wash, 70 lks. wide, 4 ft. deep, drains N. 10° W.; asc. along rolling W. slope.
	40.00	Point for the ½ sec. cor. of secs. 35 and 36.
		Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
		T41N R11W
•		\$35 \$\frac{1}{5}\$36 1962

4575

CVAVVO	1
55.00	Asc. over S. slope.
64.40	Spur, slopes SE.
74.90	Wash, 10 1ks. wide, 2 ft. deep, drains SE.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	Set the iron post on solid rock, mound with stones to top, cap mkd.
	T41N R11W <u>S26 S25</u> S35 S36 1962
	Land, rolling and slightly broken. Soil, rocky sandy loam. No timber; undergrowth, scattered sage and bunch grass.
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township, monumented by an iron post as described in the official record.
	N. 89°58' W., bet. secs. 25 and 36.
	Desc. over rolling W. slope.
24.70	Wash, 30 lks. wide, 2 ft. deep, drains SW.; thence, over gently rolling land.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T41N R11W 1/4 S 25 S 36 1962
	Raise a mound of stone N. of the post.
48.00	Sunshine Trail, bears N. 15° W. and S. 15° E.
57.70	Wash, 20 lks. wide, 1 ft. deep, drains S.; asc. over rolling E. slope.
69.00	Desc. over gentle SW. slope.
80.08	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling. Soil, gravel. No timber; undergrowth, sage, bunch grass and cactus.
	N. 0°01' W., bet. secs. 25 and 26.
	Over gently rolling W. slope.
30.40	Small wash, drains S. 70° W.
40.00	Point for the 4 sec. cor. of secs. 25 and 26.
	Set the iron post 24 ins. in the ground, cap mkd.
	T41N R11W
	S26 S25 1962

FIELD NOTE PAPER

	CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona	
		Raise a mound of stone W. of post.	
•	·	The cor. is located in small basin draining N. 70° W.	
.	44.00	Wash, 15 lks. wide, 2 ft. deep, drains W.	
	52.40	Wash, 10 lks. wide, 1 ft. deep, drains SW.	
	71.00	Wash, 10 1ks. wide, 1 ft. deep, drains N. 60° W. from SE.	
	78.80	Sunshine Trail, bears N. 10° W. and S. 10° E.	
	80.00	Point for the cor. of secs. 23, 24, 25 and 26.	
		Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.	
		T41N R11W <u>\$23</u> <u>\$24</u> <u>\$26</u> <u>\$25</u> 1962	
		Land, gently rolling. Soil, rocky sandy loam. No timber; undergrowth, scattered sage, cactus and grass.	
		From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, monumented by an iron post as described in the official record.	
•		N. 89°58' W., bet. secs. 24 and 25.	
		Asc. over steep NE. slope.	
	12.10	Small bench, about 2.00 chs. wide, 6.00 chs. long on side of slope; asc.	
	19.80	Point on East Mesa, projects N. 15° W.; thence, over top of point.	
	27.20	West rim of point, bears N. and S.; by triangulation, topography as taken from U.S.G.S. topographic sheet. Desc. over steep W. slope.	
•	33.50	Bottom of canyon, drains irregularly N.; asc. over steep E. slope.	
	39.00	Mesa rim, bears N. 20° W. and S. 20° E.; thence, over mesa top; end of triangulation.	
	40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.	
		Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		1/4 S 24 S 25 1962	
•	55.80	Mesa rim, bears irregularly NW. and S. 20° E.; desc. over steep SW. slope.	

_	CHAINS		·
	80.16	The cor. of secs. 23, 24, 25 and 26.	
		Land, rolling and broken. Soil, rocky sandy loam.	
		No timber; undergrowth, black brush and cactus.	
		N. 0°01' W., bet. secs. 23 and 24.	
		Asc. over steep, rocky SW. slope.	
	17.20	Mésa rim, bears NW. and SE.; thence, over point of mesa.	
	20.00	Mesa rim, bears S. 80° E. and N. 80° W.; desc. over steep N. slope, by triangulation; topography as taken from U.S.G.S. topographic sheet.	
	28.00	Bottom of draw, drains N. 70° W.; asc. over steep SW. slope.	
	35.00	Mesa rim, bears NW. and SE.; thence, along W. slope of mesa.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.	
		Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		S23 S24 1962	
		End of triangulation.	
	43.60	Desc. over steep N. slope.	
	68.30	Wash, 15 lks. wide, 2 ft. deep, drains N. 70° E. circling to NE.; thence along spur sloping NE.	
	74.50	Sunshine Trail, bears N. 20° E. and S. 60° W.; desc. over N. slope.	
	80.00	Point for the cor. of secs. 13, 14, 23 and 24.	
		Set the iron post on solid rock, mound with stones to top, cap mkd.	
		T41N R11W <u>S14 S13</u> S23 S24 1962	
		Land, rolling and broken. Soil, rocky sandy loam. Timber, none; undergrowth, black brush, sage, cactus and bunch grass.	
		From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, monumented by an iron post as described in the official record.	
		N. 89°58' W., bet. secs. 13 and 24.	
		Over rolling land, NW. drainage and exposure.	
	7.70	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.	
	28.40	Draw, drains N. 60° W.	
	40.03	Point for the ½ sec. cor. of secs. 13 and 24, falls in wash draining N. 20° E.	
	1		

FIELD NOTE PAPER

CHAINS Subdivision, T. 41 N., R. 11 W., Arizona Point selected for the witness 1/4 sec. cor. of secs. 41.06 13 and 24. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S 13 W S 24 C Draw, drains N. 70° E. 42.80 47.10 Small draw, drains N. S. end of fence, bears N. 10° W. for about 10.00 chs.; 54.60 thence NW. Small wash, drains NE. 55.30 Wash, 20 1ks. wide, 2 ft. deep, drains N. 15° E.; asc. 62.80 over steep E. slope. Bladed dirt road, bears N. 15° W. and S. 15° E. 76.50 The cor. of secs. 13, 14, 23 and 24. 80.06 Land, rolling and broken. Soil, gravelly. No timber; undergrowth, black brush, sage and cactus. N. 0°01' W., bet. secs. 13 and 14. Desc. over N. slope. Enter gently rolling land. 20.60 Road, bears NW. and SE. 34.50 Fence, bears NW. and SE. 34.70 Wash, 30 lks. wide, 2 ft. deep, drains NW. 39.20 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. 40.00 Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S14 S13 Low spur, slopes NW. about 2.00 chs. to end. 55.60 Wash, 15 lks. wide, 1 ft. deep, drains N. 30° W. 59.90 West point of low rim; bears irregularly N. and S. 75.50 Point for the cor. of secs. 11, 12, 13 and 14. 80.00 Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

	Subdivision, T. 41 N., R. 11 W., Arizona 6.
CHAINS	
	T41N R11W S11 S12 S14 S13 1962
	Land, gently rolling on N. 60 chs., moderate N. slope on remainder. Soil, gravelly. No timber; undergrowth, black brush and cactus.
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township, monumented by an iron post as described in the official record.
	S. 89°59' W., bet. secs. 12 and 13.
	Asc. over steep E. slope.
14.60	N. end of high, isolated, lava rock mesa; desc. over steep, ledgy W. slope.
40.01	Point for the 2 sec. cor. of secs. 12 and 13.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W 1/4 S 12 S 13 1962
	Desc. over gentle W. slope.
58.20	Wash, 25 1ks. wide, 2 ft. deep, drains N.; thence, over gentle rolling land.
80.02	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling and broken. Soil, rocky and gravelly. No timber; undergrowth, black brush and cactus.
	N. 0°01' W., bet. secs. 11 and 12.
	Over gently rolling land.
9.80	Low spur, slopes W.
40.00	Point for the ½ sec. cor. of secs. 11 and 12.
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W
	S11 S12 1962
45.50	Desc. over gentle N. slope.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W S 2 S 1 S11 S12 1962

24,000 4070

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

	CHAINS	
		Subdivision, T. 41 N., R. 11 W., Arizona
		Land, gently rolling.
•		Soil, gravelly. No timber; undergrowth, black brush and cactus.
		No timber, didenglower, second second
•		From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township, monumented by an iron post as described in the official record.
		N. 89°57' W., bet. secs. 1 and 12.
		Over gently rolling land.
	24.00	Small wash, drains NW.
	39.98	Point for the ½ sec. cor. of secs. 1 and 12.
		Set the iron post 18 ins. in the ground, cap mkd.
		T41N_R11W
		$\begin{array}{c c} \frac{1}{4} & \frac{S}{S} & \frac{1}{12} \\ & 1962 & & & & & & & & & & & & & & & & & & &$
		Raise a mound of stone N. of post.
	46.00	Wash, 60 lks. wide, 1 ft. deep, drains N. 30° W.
	52.20	Wash, 50 1ks. wide, 4 ft. deep, drains N.
-	77.60	Wash, 10 1ks. wide, 2 ft. deep, drains N. circling to NW.
•	79.96	The cor. of secs. 1, 2, 11 and 12.
		Land, gently rolling. Soil, rocky sandy loam. No timber; undergrowth, black brush and cactus.
		N. 0°02' W., bet. secs. 1 and 2.
		Desc. over rolling N. slope.
	5.20	Wash, 40 lks. wide, 1 ft. deep, drains N. 30° W. circling to NE.
	10.30	Low spur, slopes W. 1.00 chain to end.
	18.30	Same wash as one at 5.20, drains irregularly N.
	31.80	Same wash.
	39.30	Same wash, drains N. 30° W.
	40.00	Point for the ½ sec. cor. of secs. 1 and 2.
		Set the iron post 18 ins. in the ground, cap mkd.
		T41N R11W
•		S 2 S 1 1962
•		Raise a mound of stone W. of the post.

	Subdivision, T . 41 N., R. 11 W., Arizona 8.
CHAINS	Continue over nearly level level
80.02	Continue over nearly level land. The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township, monumented by an iron post as described in the official record.
	Land, nearly level. Soil, gravelly. No timber; undergrowth, black brush and cactus.
	From the Standard Corner of secs. 34 and 35 on the S. bdy. of the township, monumented by an iron post as described in the official record.
	N. 0°01' W., bet. secs. 34 and 35.
	Over rolling hills and washes.
2.80	Spur, projects W.; desc. NW. slope.
10.30	Wash, 50 lks. wide, nearly vertical banks about 60 ft. high, drains N. 70° E.
30.10	Draw, drains E.
39.30	Draw, drains irregularly E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W
	\$34 \$35 1962
53.90	Wash, 30 1ks. wide, 1 ft. deep, drains irregularly E.
63.00	Draw, drains E. circling to NE.
70.00	Small knoll; desc. over N. slope.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 20 ins. in the ground, cap mkd.
	T41N R11W <u>S27 S26</u> S34 S35 1962
	Raise a mound of stone W. of the post.
	Land, rolling and slightly broken. Soil, rocky and gravelly. No timber; undergrowth, black brush, cactus and brigham tea.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°57' W., bet. secs. 26 and 35.
	Over gently rolling land.
15.10	Wash, 10 1ks. wide, 1 ft. deep, drains S.
23.80	Small wash, drains S. 20° E.
28.30	Spur, slopes S. 20° E.; desc. over W. slope.
-	

FIELD NOTE PAPER

		FIELD NOTE PAPER	9.
	CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona	
	40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35 falls on ledge where corner cannot be perpetuated.	
	40.18	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 26 and 35.	
		Set the iron post on solid rock, mound with stones to top, cap mkd.	
		T41N R11W \[\frac{1}{4} \] \frac{S 26 W}{S 35 C} 1962	
	43.40	Bottom of Dutchman Draw, 80 lks. wide, 4 ft. deep, drains N.; asc. over ledgy E. slope.	
	49.50	Spur, slopes N.; desc. W. slope.	
	62.30	Wash, 10 1ks. wide, 1 ft. deep, drains N.	
	67.50	Draw, drains N.; thence, over rolling N. slope.	
	80.16	The cor. of secs. 26, 27, 34 and 35.	
		Land, rolling and broken. Soil, rocky and gravelly. No timber; undergrowth, black brush, cactus and brigham tea.	
-		N. 0°01' W., bet. secs. 26 and 27.	
•		Desc. over N. slope.	
	1.10	Wash, 15 lks. wide, 2 ft. deep, drains N. 70° E.; asc. over S. slope.	
	10.30	Top of low knoll; desc. over steep N. slope.	
,	19.10	Desc. over nearly vertical canyon wall, about 70. ft. high, faces N.	
	20.60	Wash in bottom of Dutchman Draw, 50 lks. wide, 3 ft. deep, drains NW.; asc. over ledges facing S.	
	31.00	Spur, projects W.	
	32.90	Desc. over canyon wall and steep slope facing N.	
	37.00	Wash in bottom of Dutchman Draw, 50 lks. wide, 4 ft. deep, drains E. circling to N.	
	39.00	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 26 and 27.	
		Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
•		₩C S27 S26 1962	
		1702	

	r		·
	CHAINS		
	40.00	True point for the ½ sec. cor. of secs. 26 and 27 falls in bottom of Dutchman Draw, drains W.	
		By triangulation, asc. over ledgy S. slope.	
	58.30	End of triangulation on spur, sloping S. 20° W.	
	71.90	Spur, slopes N. 10° W.; desc. over N. slope.	
	78.80	Fence, bears N. 30° W. and S. 30° E.	
	80.00	Point for the cor. of secs. 22, 23, 26 and 27.	
		Set the iron post 18 ins. in the ground, collar with stones, cap mkd.	
		T41N R11W <u>S22 S23</u> <u>S27 S26</u> 1962	
ŀ		Raise a mound of stone W. of the post.	
		Land, rolling and broken. Soil, rocky and gravelly. No timber; undergrowth, black brush and cactus.	
		From the cor. of secs. 23, 24, 25 and 26.	
		S. 89°59' W., bet. secs. 23 and 26.	
		Over rolling land.	
	6.30	Wash, 20 1ks. wide, 1 ft. deep, drains N. 15° W.	
	36.00	Wash, 10 1ks. wide, 1 ft. deep, drains SW.	
	40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.	
		Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W 1/4 S 23 S 26 1962	
	65.90	Wash, 20 lks. wide, l ft. deep, drains N.	
l	68.30	Small spur, slopes N.; desc. over NW. slope.	
	80.06	The cor. of secs. 22, 23, 26 and 27.	
		Land, rolling. Soil, gravelly. No timber; undergrowth, black brush and cactus.	
		N. 0°01' W., bet. secs. 22 and 23.	
		Desc. over N. slope.	
	7.20	Slope changes to W.	
	20.80	Sunshine Trail, bears E. and W.	
	21.50	Wash, 10 lks. wide, 2 ft. deep, drains irregularly S. 70° W.; asc. over rolling SW. slope.	
	34.10	Draw, drains S. 10° W.	•
		• • • • • • • • • • • • • • • • • • •	

FIELD NOTE PAPER

CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona
40.00	Point for the ½ sec. cor. of secs. 22 and 23.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W
	S22 S23 1962
	Asc. over SW. slope.
48.90	Spur, slopes W. from Joe Blake Hill; desc. over NW. slope.
56.90	Head of wash, drains S. 60° W.
80.00	Point for the sec. cor. of secs. 14, 15, 22 and 23.
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W S15 S14 S22 S23 1962
,	Land, rolling and broken. Soil, rocky, gravelly. No timber; undergrowth, sage, black brush and greasewood.
	From the cor. of secs. 13, 14, 23 and 24.
	S. 89°54' W., bet. secs. 14 and 23.
	Along rolling N. slope of Joe Blake Hill.
17.00	Draw, drains N.
25.00	Spur, slopes N.
40.07	Point for the 4 sec. cor. of secs. 14 and 23.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W
	$\frac{1}{4} \frac{S}{S} \frac{14}{23}$
	4 S 23 1962
	Raise a mound of stone N. of the post.
60.10	Wash, 30 1ks. wide, 1 ft. deep, drains N. from SE.
80.14	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling and broken. Soil, rocky sandy clay loam. No timber; undergrowth, black brush, creosote brush and cactus.

	CHAINS	
	CHAINS	N. 0°01' W., bet. secs. 14 and 15.
		Desc. over NW. slope.
	14.00	Enter nearly level land.
	27.00	Sunshine Trail, bears N. 30° E. and S. 30° W.
	37.50	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.
	40.00	Point for the ½ sec. cor. of secs. 14 and 15.
		Set the iron post 20 ins. in the ground, cap mkd.
		T41N R11W
		\$15 S 14 1962
		Raise a mound of stone W. of the post.
	49.80	Wash, 10 lks. wide, 1 ft. deep, drains irregularly N.
-	65.60	Wash, 20 lks. wide, 1 ft. deep, drains N. 10° W.
	80.00	Point for the cor. of secs. 10, 11, 14 and 15.
		Set the iron post 24 ins. in the ground, cap mkd.
		T41N R11W S10 S11 S15 S14 1962
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, gravelly. No timber; undergrowth, black brush, cactus and creosote brush.
		From the cor. of secs. 11, 12, 13 and 14.
		S. 89°54' W., bet. secs. 11 and 14.
		Over gently rolling land.
	14.30	Wash, 20 lks. wide, 2 ft. deep, drains N.
	40.06	Point for the 4 sec. cor. of secs. 11 and 14.
		Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
		T41N R11W
		½ S 11
		1962
	42.60	Desc. over ledge facing W.; thence over gently rolling land.
	58.10	Intersection of two washes, drains N.
	74.80	Sunshine Trail, bears N. 15° W. and S. 15° E.
	79.30	Small wash, drains N. circling to W.
	80.12	The cor. of secs. 10, 11, 14 and 15.

FIELD NOTE PAPER 13. CHAINS Subdivision, T. 41 N., R. 11 W., Arizona Land, gently rolling. Soil, gravelly. No timber; undergrowth, black brush, creosote and cactus. N. 0°01' W., bet. secs. 10 and 11. Desc. over gentle N. slope. Small wash, drains NW. 3.30 Wash, 30 1ks. wide, 1 ft. deep, drains N. 30° W. from 13.60 S. 80° E. Wash, 10 1ks. wide, 3 ft. deep, drains irregularly NW. 31.60 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11. 40.00 Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S10 S11 Bladed road, bears SW. from E. 40.40 49.00 Draw, drains E. Wash, 30 1ks. wide, 1 ft. deep, drains NW. 58.60 Spur, slopes W. about 3.00 chs. to end. 62.00 Wash, 10 1ks. wide, 3 ft. deep, drains W. 66.90 Wash, 10 lks. wide, 1 ft. deep, drains W. 71.90 Point for the cor. of secs. 2, 3, 10 and 11. 80.00 Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S 3 S 2 S10 S11 1962 Land, rolling. Soil, gravelly. No timber; undergrowth, scattered brush and cactus. From the cor. of secs. 1, 2, 11 and 12. S. 89°52' W., bet. secs. 2 and 11. Over rolling land draining N.; by triangulation, topography as taken from U.S.G.S. topographic sheet. Wash, drains N. 23.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. 40.09

		Subdivision, T. 41 N., R. 11 W., Arizona 14.	•
	CHAINS	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		$\frac{1}{4} \frac{S}{S} \frac{2}{11}$	
		1962	
		End of triangulation.	
	56.60	Low hill, bears N. and S.	•
	62.80	Sunshine Trail, bears N. 20° W. and S. 15° E.	
	80.18	The cor. of secs. 2, 3, 10 and 11.	
		Land, rolling. Soil, rocky sandy loam. No timber; undergrowth, brush and cactus.	
		N. 0°06' E., bet. secs. 2 and 3.	
		Over rolling land, through scattered undergrowth.	
1	6.50	Wash, 10 1ks. wide, 1 ft. deep, drains NW.	
	7.90		
		Sunshine Trail, bears NW. and SE.	
	21.50	Asc. over steep S. slope.	
	26.20	Mesa rim, bears NW. and SE.	
	34.70	Mesa rim, bears S. 60° W. and N. 60° E.; desc. over general N. slope.	
	40.00	Point for the ½ sec. cor. of secs. 2 and 3.	
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	•
		T41N R11W	-
		s 3 s 2 1962	
		Continue over rolling land.	
	53.40	Low mesa rim, bears E. and irregularly NW.; thence over gently rolling land.	
l	74.00	Asc. over SW. slope.	
	78.90	Rim, bears E. and N. 30° W.	
	80.29	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township, monumented by an iron post as described in the official record.	
		Land, rolling and slightly broken. Soil, rocky sandy loam. No timber; undergrowth, scattered sage, creosote and cactus.	
		From the Standard Corner of secs. 33 and 34 on the S. bdy. of the township, monumented by an iron post as described in the official record.	
		N. 0°02' W., bet. secs. 33 and 34.	•
		Over low rolling hills and washes.	
			•

William William

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

15. CHAINS Subdivision, T. 41 N., R. 11 W., Arizona Bladed road, bears N. 70° E. and S. 70° W. .50 Wash, 30 1ks. wide, 1 ft. deep, drains N. 70° E. 1.20 curving to NE. 17.50 Spur, slopes E. Road, bears N. 20° W. curving to N. and SE. 24.90 25.60 Same road, bears irregularly N. 38.60 Draw, drains W. about 2.00 chs. to Quail Draw. 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34. Set the iron post 20 ins. in the ground, cap mkd. T41N R11W S33 S34 Raise a mound of stone W. of the post. Quail Draw, 30 1ks. wide, 5 ft. deep, drains NE. from S. 54.20 64.20 Bladed road, bears irregularly SW. and N. Same road. 69.00 Same road, bears N. 15° E. 72.75 Wash, 20 lks. wide, 1 ft. deep, drains N. 50° E. 75.80 80.00 Point for the cor. of secs. 27, 28, 33 and 34. Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S28 S27 S33 S34 1962 from which Steel water tank, $18 \times 7 \times 2\frac{1}{2}$ ft. with water piped in, bears S.61°10' E., 19.31 chs. dist. Land, rolling and broken. Soil, rocky sandy clay loam. No timber; undergrowth, sage, black brush and cactus. From the cor. of secs. 26, 27, 34 and 35. S. 89°59' W., bet. secs. 27 and 34. Over rolling land through scattered undergrowth. Wash, 15 lks. wide, 1 ft. deep, drains NE. 3.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 15° E. 7.30 curving to E.

	CHAINS		Γ
	24.00	Low hill, bears NW. and SE.; desc. over SW. slope.	
	31.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W.; asc. over NE. slope.	
	40.06	Point for the ½ sec. cor. of secs. 27 and 34.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T41N R11W	
		½ S 27 S 34	
		1962	
		Raise a mound of stone N. of the post.	
	40.40	Spur, slopes N. 30° W.; desc. over broken W. slope.	
	57.90	Quail Draw, 60 lks. wide, 3 ft. deep, drains irregularly N. 10° W. from SW.	
	76.60	Wash, 20 1ks. wide, 2 ft. deep, drains N. 50° E. curving to E.	
	78.20	Blade road, bears N. 20° E. and S. 20° W.	
	80.12	The cor. of secs. 27, 28, 33 and 34.	ļ. [
		Land, rolling and slightly broken. Soil, gravelly and clay loam. No timber; undergrowth, black brush, cactus and creosote brush.	
		N. 0°02' W., bet. secs. 27 and 28.	
	,	Over low rolling hills and washes.	
	11.10	Spur, slopes E.	
	19.50	Wash, 20 lks. wide, 1 ft. deep, drains E.	
	22.00	Spur, slopes S. 70° E.	
	24.10	Blade road, bears NW. and S. 30° E.	
	27.80	Wash, 20 1ks. wide, 2 ft. deep, drains S. 50° E.	
	30.40	Draw, drains S.; asc. S. slope.	
	40.00	Point for the 4 sec. cor. of secs. 27 and 28.	
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		\$28 \$27 1962	
	48.90	Ridge, bears irregularly NE. and SW.	
	65.00	Spur, slopes N. 10° W.	
	71.60	Wash, 10 1ks. wide, 2 ft. deep, drains NW.	
	78.90	Wash, 10 lks. wide, l ft. deep, drains irregularly N. 10° E.	
	80.00	Point for the cor. of secs. 21, 22, 27 and 28.	
,	i	<u>.</u>	

FIELD NOTE PAPER 17. CHAINS Subdivision, T. 41 N., R. 11 W., Arizona Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S21 S22 S28 S27 1962 Land, rolling and broken. Soil, rocky sandy clay loam. No timber; undergrowth, brush, brigham tea and cactus. From the cor. of secs. 22, 23, 26 and 27. N. 89°59' W., bet. secs. 22 and 27. Over rolling and broken N. slope by triangulation; topography as taken from U.S.G.S. topographic sheet. 25.00 Desc. over steep W. slope. Quail Draw, drains NE. curving to E.; asc. over 30.00 rolling land facing E. Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27. 40.10 Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W ½ S 22 S 27 End of triangulation. Ridge top, bears irregularly NE. and SW. 50.30 Wash, 15 lks. wide, 2 ft. deep, drains N. 60.50 Wash, 10 lks. wide, 2 ft. deep, drains N. 10° E. 61.50 67.60 Draw, drains N. The cor. of secs. 21, 22, 27 and 28. 80.20 Land, rolling and broken. Soil, rocky sandy clay loam. No timber; undergrowth, scattered brush, brigham tea and cactus. N. 0°02' W., bet. secs. 21 and 22. Desc. over N. slope. Blade road, bears E. and W.; wash, drains E. 10.70 Spur, slopes E. 15.40 Wash, 30 1ks. wide, 1 ft. deep, drains N. 30° E. 26.10 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22. 40.00

Set the iron post 6 ins. in the ground, mound with

	Subdivision, T. 41 N., R. 11 W., Arizona	.8.
CHAINS		
	stones to top, cap mkd.	
	T41N R11W	
	S21 S22 1962	
71.00	Desc. over steep N. slope.	
79.00	Draw, drains N. 20° E.	
80.00	Point for the cor. of secs. 15, 16, 21 and 22.	
	Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.	
	T41N R11W S16 S15 S21 S22 1962	
	Land, rolling hills and washes.	
	Soil, sandy clay loam. No timber; undergrowth, brush, brigham tea and cactus.	
	From the cor. of secs. 14, 15, 22 and 23.	•
	N. 89°54' W., bet. secs. 15 and 22.	
	By triangulation, topography as taken from U.S.G.S. topographic sheet; desc. over steep W. slope.	
23.00	Sunshine Trail, bears NE. and SW. curving to S.; asc. over rolling E. slope.	
40.09	Point for the 4 sec. cor. of secs. 15 and 22.	
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.	
	T41N R11W 1/4 S 15 S 22 1962	
	from which	
	NW. cor. of pond bears S. 36°04' E., 22.74 chs. dist.	
	End of triangulation; thence across the top of hill.	
51.60	Desc. over W. slope.	
64.90	Dutchman Draw, drains N. 10° W.; asc. over E. slope.	
76.50	Spur, slopes NE.	
79.20	Small wash, drains N. 20° E. circling to E.	
79.60	Small wash, drains N. 15° E.	
80.18	The cor. of secs. 15, 16, 21 and 22.	
	Land, rolling hills. Soil, sandy clay loam and rocky. No timber; undergrowth, scattered brush, brigham tea and cactus.	
		-

FIELD NOTE PAPER

		FIELD NOTE PAPER	19.
	CHAINS	N 00000 II hat area 15 and 16	
		N. 0°02' W., bet. secs. 15 and 16.	
		Over low rolling hills and washes.	
-	9.30	Wash, 20 lks. wide, 1 ft. deep, drains SE.; asc. over S. slope.	
	16.90	Small spur, slopes W., 1.00 chain to end.	
	19.90	Small spur, slopes NW. about 4.00 chs. to end.	
	24.90	Wash, 20 lks. wide, 2 ft. deep, drains E. curving to NE	•
	29.00	Spur, slopes E.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.	
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		\$ 16 S 15 1962	
,	42.30	Wash, 20 1ks. wide, 1 ft. deep, drains E.	
	45.30	Top of ledge, 25 ft. high, bears E. and W.	
	59.80	Desc. over N. slope.	
	70.00	Bottom of Dutchman Draw, drains NW. on curve to NE.; thence over end of point sloping from the E.	
•	79.00	Point selected for the witness cor. of secs. 9, 10, 15 and 16.	
•		Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W WC	
		S 9 S10	
		\$16 \$15 1962	
	80.00	Point for the cor. of secs. 9, 10, 15 and 16 falls in bottom of Dutchman Draw, about 100 ft. banks, 2.00 chs. wide, drains NE.	•
		Land, rolling and broken. Soil, rocky sandy clay loam. No timber; undergrowth, small brush, brigham tea and cactus.	
			-
		From the cor. of secs. 10, 11, 14 and 15.	
		N. 89°55' W., bet. secs. 10 and 15.	
		Over gently rolling land.	
•	7.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.	
	35.90	Wash, 10 1ks. wide, 1 ft. deep, drains N. 10° W.	
÷			

G** A ****G	Total Title
40.08	Point for the ½ sec. cor. of secs. 10 and 15.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W ½ S 10 S 15
	1962
	Asc. over rolling E. slope.
68.50	Ridge bears N.; desc. along spur, sloping W.
80.16	True point for the cor. of secs. 9, 10, 15 and 16.
	Land, rolling and broken. Soil, rocky and sandy clay loam. No timber; undergrowth, black brush, shadscale and brigham tea.
	N. 0°02' W., bet. secs. 9 and 10.
	By triangulation, topography as taken from U.S.G.S. topographic sheet; asc. over canyon wall facing SE.
10.00	Spur, projects NE.
14.00	Desc. over steep N. slope.
20.50	Bottom of Dutchman Draw, drains N. 70° W.; thence, over rolling W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T41N, R11W
	S 9 S 10 1962
	End of triangulation; thence, over rolling land; W. drainage and exposure.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W S 4 S 3 S 9 S 10 1962
	Land, rolling and slightly broken. Soil, rocky clay loam. No timber; undergrowth, shadscale, black brush and brigham tea.
	From the cor. of secs. 2, 3, 10 and 11.
	2 110
	N. 89°55' W., bet. secs. 3 and 10.
	N. 89°55' W., bet. secs. 3 and 10. Asc. over low rolling hills and gullies.

BUREAU OF LAND MANAGEMENT FIELD NOTE PAPER 21. **CHAINS** Subdivision, T. 41 N., R. 11 W., Arizona Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. $\begin{array}{ccc} T41N & R11W \\ \frac{1}{4} & \frac{S}{S} & \frac{3}{10} \end{array}$ 42.20 Desc. over W. slope. Wash, 20 1ks. wide, 2 ft. deep, drains NW.; thence, 47.30 over gently rolling land. Blade road, bears irregularly W. 48.60 53.70 Same road. Same road. 59.80 74.60 Same road. Wash, 20 1ks. wide, 1 ft. deep, drains N. 30° W. 74.90 Same road, bears N. 10° W. 77.60 The cor. of secs. 3, 4, 9 and 10. 80.16 Land, rolling. Soil, rocky clay loam. No timber; undergrowth, brush and brigham tea. N. $0^{\circ}09$ ' E., bet. secs. 3 and 4. Over nearly level land. Blade road, bears NE. and SW. .95 Same road. 7.20 Wash, 30 1ks. wide, 1 ft. deep, drains W. 7.80 Wash, 30 1ks. wide, 3 ft. deep, drains N. 70° W. 24.50 Point for the 1/2 sec. cor. of secs. 3 and 4. 40.00 Set the iron post 24 ins. in the ground, cap mkd. T41N R11W $\begin{array}{c|c}
 & \frac{1}{4} \\
 & 4 & 3
\end{array}$ Raise a mound of stone W. of the cor. Wash, 15 lks. wide, 6 ft. deep, drains S. 30° E. 79.80 The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of 80.32 the township, monumented by an iron post as described in the official record. Land, nearly level.

Soil, rocky clay loam.

No timber; undergrowth, creosote brush and brigham tea.

	Subdivision, 1. 41 N., R. 11 W., Arizona 22.
CHAINS	From the Standard Corner of secs. 32 and 33 on the S. bdy. of the township, monumented by an iron post as described in the official record.
	N. 0°03' W., bet. secs. 32 and 33.
	Over rolling and broken land; desc. along spur sloping N.
12.80	Quail Draw, drains SE. from SW.; asc. over S. slope.
25.00	Top of ascent, bears N. and E.
40.00	Point for the ½ sec. cor. of secs. 32 and 33.
	Set the iron post 22 ins. in the ground, cap mkd.
	T4 1N R1 1W
	\$ 32 \$ 33
•	1962
E0 00	Raise a mound of stone W. of the post.
52.80	Wash, 30 1ks. wide, 1 ft. deep, drains E.
57.20	Narrow rocky hill, bears N. 75° E. and W.; desc. over N. slope.
60.00	Small wash, drains N. 75° E.
68.50	Low ridge, bears NE. and SW.; desc. over N. slope.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W <u>\$29</u> <u>\$28</u> \$32 \$33 1962
	Land, rolling and slightly broken.
	Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush.
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89°57' W., bet. secs. 28 and 33.
	Asc. over E. slope.
14.50	Ledge, 6 ft. high, forming the N. bank of wash draining S. 70° E. from S. 70° W.; asc. SE. slope.
32.00	Top of ascent, bears N. and S.
37.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 15° E.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W 1/4 S 28 S 33 1962

1-345 (4075

FIELD NOTE PAPER

Subdivision, T. 41 N., R. 11 W., Arizona Small wash, drains NE. 45.60 Same wash, drains from N. 70° W. 68.00 Draw, drains N. 69.60 Small spur, slopes N. 79.96 The cor. of secs. 28, 29, 32 and 33. Land, rolling, slightly broken. Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush. N. 0°03' W., bet. secs. 28 and 29. Desc. over broken N. slope. Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the & sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$2.29 \$28 1962 Wash, 10 lks. wide, 2 ft. deep, drains E. Wash, 10 lks. wide, 3 ft. deep, drains E. Spur, slopes NW.; desc. over N. slope. 75.50 Spur, slopes NW.; desc. over N. slope. Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$2.0 \$221 \$2.9 \$28 1962	_			
45.60 Same wash, drains from N. 70° W. 68.00 Draw, drains N. 69.60 Small spur, slopes N. 79.96 The cor. of secs. 28, 29, 32 and 33. Land, rolling, slightly broken. Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush. N. 0°03' W., bet. secs. 28 and 29. Desc. over broken N. slope. 4.60 Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 5pur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$\frac{1}{2}\$\fr		CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona	
Draw, drains N.		43.30	Small wash, drains NE.	
69.60 Small spur, slopes N. 79.96 The cor. of secs. 28, 29, 32 and 33. Land, rolling, slightly broken. Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush. N. 0°03' W., bet. secs. 28 and 29. Desc. over broken N. slope. 4.60 Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the & sec. cor. of secs, 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 S28 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 S21 \$29 S28		45.60	Same wash, drains from N. 70° W.	
The cor. of secs. 28, 29, 32 and 33. Land, rolling, slightly broken. Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush. N. 0°03' W., bet. secs. 28 and 29. Desc. over broken N. slope. 4.60 Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 S28 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 S21 \$29 S28		68.00	Draw, drains N.	
Land, rolling, slightly broken. Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush. N. 0°03' W., bet. secs. 28 and 29. Desc. over broken N. slope. 4.60 Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 5pur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the k sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29\subseteq \text{S28} \\ 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$22\subseteq \text{S21} \\ \text{S20} \subseteq \text{S21} \\ \text{S20} \subseteq \text{S21} \\ \text{S29} \subseteq \text{S20} \\ \text{S21} \subseteq \text{S20} \subseteq \text{S21} \\ \text{S20} \subseteq \text{S21} \\ \text{S29} \subseteq \text{S20} \subseteq \text{S21} \\ \text{S29} \subseteq \text{S22} \subseteq \text{S21} \\ \text{S21} \subseteq \text{S21} \subseteq \text{S21} \\ \text{S21} \subseteq S2		69.60	Small spur, slopes N.	·
Soil, rocky. No timber; undergrowth, creosote brush, cactus and black brush. N. 0°03' W., bet. secs. 28 and 29. Desc. over broken N. slope. 4.60 Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$229 \$528 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$521 \$220 \$521 \$229 \$528		79.96	The cor. of secs. 28, 29, 32 and 33.	
Desc. over broken N. slope. Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$28 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$21 \$20 \$21 \$29 \$28 \$20 \$21 \$29 \$28 \$20 \$21 \$29 \$28 \$20 \$21 \$29 \$28 \$20 \$21 \$29 \$28 \$20 \$21 \$29 \$28 \$20 \$			Soil, rocky. No timber; undergrowth, creosote brush, cactus and	
### Accordance Rim, bears NE. and SW. 12.40 Blade road, bears NE. and SW. 13.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. #### ### ### ### ### ### ### ### ###			N. 0°03' W., bet. secs. 28 and 29.	
Blade road, bears NE. and SW. Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$528 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$521 \$29 \$528			Desc. over broken N. slope.	
13.10 Wash, 10 1ks. wide, 1 ft. deep, drains N. 30° E.; asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 1ks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$S28 1962 42.90 Wash, 10 1ks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 1ks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$S21 \$29 \$S28		4.60	Rim, bears NE. and SW.	
asc. over SE. slope. 16.20 Spur, slopes NE. 21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$28 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$21 \$29 \$28		12.40	Blade road, bears NE. and SW.	
21.80 Draw, drains E. 23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W 28.29 S28 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28		13.10		
23.00 End of spur, sloping from W. 26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. 38.00 Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T4 IN R11W \$29 \$528\$ 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$21\$ \$29 \$28\$		16.20	Spur, slopes NE.	
26.20 Wash, 20 lks. wide, 1 ft. deep, drains E. Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$528 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$521 \$29 \$528		21.80	Draw, drains E.	
Rocky spur, projects SE. 40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$28 1962 42.90 Wash, 10 1ks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 1ks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$21		23.00	End of spur, sloping from W.	
40.00 Point for the ½ sec. cor. of secs. 28 and 29. Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$28 1962 42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$21 \$29 \$28		26.20	Wash, 20 lks. wide, 1 ft. deep, drains E.	
Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$29 \$528 1962 42.90 Wash, 10 1ks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 1ks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W \$20 \$521 \$29 \$528		38.00	Rocky spur, projects SE.	
### Stones to top, cap mkd. ### T41N R11W S29 S28		40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.	
S29 S28 1962			•	
42.90 Wash, 10 lks. wide, 2 ft. deep, drains E. 54.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28	ļ		T4 1N R1 1W	·
54.20 Wash, 10 1ks. wide, 3 ft. deep, drains S. 20° E. 69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28				
69.00 Desc. along W. slope. 75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28		42.90	Wash, 10 1ks. wide, 2 ft. deep, drains E.	•
75.50 Spur, slopes NW.; desc. over N. slope. 80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28		54.20	Wash, 10 1ks. wide, 3 ft. deep, drains S. 20° E.	
80.00 Point for the cor. of secs. 20, 21, 28 and 29. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28		69.00	Desc. along W. slope.	•
Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S20 S21 S29 S28		75.50	Spur, slopes NW.; desc. over N. slope.	`
stones to top, cap mkd. T41N R11W S20 S21 S29 S28		80.00	Point for the cor. of secs. 20, 21, 28 and 29.	
<u>\$20 \$21</u> <u>\$29 \$28</u>				
			S20 S21 S29 S28	

_		Subdivision, 1. 41 N., R. II W., Arizona 24.
	CHAINS	Land, rolling and broken. Soil, rocky sandy clay loam. No timber; undergrowth, scattered brush and brigham tea.
		From the cor. of secs. 21, 22, 27 and 28.
		N. 89°59' W., bet. secs. 21 and 28.
	,	Over rolling land, numerous small washes.
	11.60	Wash, blade road in bottom, drains N. 20° E.
	23.00	Wash, 20 1ks. wide, 1 ft. deep, drains N. 30° E.
	40.01	Point for the ½ sec. cor. of secs. 21 and 28.
		Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
		T41N R11W 1/4 S 21 S 28 1962
	47.50	Wash, 20 1ks. wide, 1 ft. deep, drains N. 20° E. from S. 70° W.
	57.20	Spur, slopes N.
	67.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 30° E. curving to N.
	75.10	Spur, slopes N.; desc. over NW. slope.
	80.02	The cor. of secs. 20, 21, 28 and 29.
		Land, rolling. Soil, rocky sandy clay loam. No timber; undergrowth, creosote brush, black brush and brigham tea.
		N. 0°03' W., bet. secs. 20 and 21.
		Desc. over NW. slope.
	. 10	Small wash, drains N. 30° W.
	1.50	Ledge, 75 ft. high, bears NE. and SW.; desc.
	4.00	Base of steep desc.; thence, along broken W. slope.
	15.50	Spur, slopes N. 60° W.; desc. along broken W. slope.
	30.00	Desc. over steep N. slope.
	39.00	Wash, 10 1ks. wide, 2 ft. deep, drains N. 75° W.
	40.00	Point for the 2 sec. cor. of secs. 20 and 21.
		Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
		T41N R11W 表 S20 S21 1962
		Desc. along gentle NW. slope.
	l	

FIELD NOTE PAPER

	TIELD NOTE PAPER 25
CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona
50.10	Blade road, bears S. 10° W. and N. 20° E.
71.00	Small wash, drains W.; asc. along W. slope of black mesa.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W S17 S16 S20 S21 1962
	Land, broken on S. ½ mile, rolling on remainder. Soil, rocky, sandy clay loam. No timber; undergrowth, brush, shadscale and brigham tea.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°53' W., bet. secs. 16 and 21.
	Over rolling hills cut by numerous washes and gullies; asc. E. slope.
11.00	Spur, slopes N. 10° E.
18,00	Low ridge, bears NW. and SE.
27.60	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° W.
34.20	Wash, 30 lks. wide, 1 ft. deep, drains N.; asc. gentle E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	$ \begin{array}{c} $
	Desc. over gentle W. slope.
51.60	Small spur, projects N.; desc. over broken, ledgy W. slope.
64.70	Bottom of draw, drains N. 15° E.; asc. E. slope.
73.00	Top of small black mesa, bears N. and S.
74.30	Desc. over W. slope.
80.00	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling and broken. Soil, rocky clay loam. No timber; undergrowth, small brush and scattered brigham tea.

	Subdivision, 1. 41 N., R. II W., MIZONA 20.
CHAINS	46 1.17
	N. 0°03' W., bet. secs. 16 and 17.
	Along broken W. slope of black mesa.
4.00	Desc. over NW. slope.
19.00	Over bottom of shallow draw draining W.
32.50	Asc. over SW. slope.
40.00	Point for the k sec. cor. of secs. 16 and 17.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T4 1N R1 1W
	S17 S 16 1962
	Asc. along W. slope.
43.30	Desc. over NW. slope.
56.70	Enter nearly level land.
66.10	Small wash, drains N. 20° E.
67.10	Small wash, drains N. 20° E.
76.70	Small wash, drains N. 20° E.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set the iron post 24 ins. in the ground, cap mkd.
	T41N R11W <u>S 8 S 9</u> S17 S16 1962
	Raise a mound of stone W. of the post.
	Land, rolling and slightly broken on S. 56.00 chs., nearly level on remainder. Soil, rocky clay loam. No timber; undergrowth, creosote brush, shadscale and scattered brigham tea.
	From the true point for the cor. of secs. 9, 10, 15 and 16.
	N. 89°49' W., bet. secs. 9 and 16.
	By triangulation, asc. over ledges and steep E. slope of Dutchman Draw.
9.20	End of triangulation on point projecting irregularly NE.; thence over draw, high sloping walls, drains N. bending to W.
15.00	West side of draw on small point sloping sharply N.; desc. W. slope.
24.70	Wash, 10 1ks. wide, 2 ft. deep, drains N.; desc.
33.40	Wash, 10 lks. wide, 2 ft. deep, drains N.; base of steep W. slope; continue over nearly level land.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.
i	1

FIELD NOTE PAPER

27

Subdivision, T. 41 N., R. 11 W., Arizona	,
Set the iron post 16 ins. in the ground, mound with	
stones to top, cap mkd.	
T41N R11W 1 S 9 4 S 16	
4 S 16 1962	
45.60 Wash, drains N.	
56.90 Wash, drains N.	
78.20 Wash, 20 lks. wide, 1 ft. deep, drains N. 15° E.	
80.04 The cor. of secs. 8, 9, 16 and 17.	,
Land, broken on E. 34.00 chs., nearly level on remain Soil, rocky, clay loam. No timber; undergrowth, scattered creosote and shadso	
N. 0° 03' W., bet. secs. 8 and 9.	
Over nearly level land through scattered undergrowth.	к
5.50 Small wash, drains NE.	
16.50 Wash, 30 lks. wide, 4 ft. deep; drains N. 50° E.	
40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.	
Set the iron post 21 ins. in the ground, cap mkd.	
THIN RILW	
s 8 s 9 1962	
No accessories available.	
78.50 Small wash, drains NE.	•
80.00 Point for the cor. of secs. 4, 5, 8 and 9.	,
Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.	r
TAIN RIIW	٢
\$.5 S 4 \$.8 S0	e
1962	
Land, nearly level. Soil, clay loam. No timber; undergrowth, scattered creosote brush and shadscale.	
From the cor. of secs. 3, 4, 9 and 10.	
N. 89° 49' W., bet. secs. 4 and 9.	
Over nearly level land, through scattered undergrowth.	ı^
2.10 Bladed road, bears N. 20° E. and S. 20° W.	9
	a
	n

_	T		
	7.20	Wash, 30 lks. wide, 3 ft. deep, drains N.	
	9.80	Wash, drains N.	
	16.30	Wash, 40 lks. wide, 2 ft. deep, drains N.	
	24.40	Dutchman Draw, drains N.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.	
		Set the iron post, 14 ins. in the ground, mound with stones to top, cap mkd.	
		TLIN RIIW	
		1 S 4 5 9 1962	
	40.50	Wash, 40 lks. wide, 5 ft. deep, drains N.	
	44.90	Wash, 20 lks. wide, 5 ft. deep, drains N. 15° E.	
	45.40	Asc. E. slope.	
	55.90	Top of small black knoll; desc. W. slope.	
	65.00	Base of hill, thence over nearly level land.	
	78.90	Small wash, drains NE.	
	80.00	The cor. of secs. 4, 5, 8 and 9.	
		Land, nearly level with exception of small knoll. Soil, rocky clay and loam. No timber; undergrowth; creosote and shadscale.	
		N. 0° 10' E., bet. secs. 4 and 5.	
		Over gentle S. slope, through creosote brush.	
	2.10	Wash, 5 lks. wide, 1 ft. deep, drains NE.	
	8.90	Bladed road, bears NE. and S. 30° W.	
	18.70	Bladed road, bears NE. and SW.	
	23.80	Bladed road, bears irregularly NE. and SW.	
	30•20	Bladed road, bears E. and W.	
	140.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.	
		Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.	en.
		T41N R 11W	
		s 5 [†] s 4 1962	
	47.90	Wash, 10 lks. wide, 2 ft. deep, drains SE.	
	57.70	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.,; asc. over steep, ledgy S. slope.	
	66.00	Top of ledge, 50 ft. high, bears SE. and W.; asc. over SW. slope.	
	80,22	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the township, monumented by an iron post as described	•
- 1		, I	

FIELD NOTE PAPER

		FIELD NOTE PAPER	29.
	CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona	
		in the official record.	
		Land, nearly level on S. 55.00 chs., broken on remainder. Soil, clay loam and rocky. No timber; undergrowth, creosote brush and shadscale.	
		From the Standard Corner of secs. 31 and 32 on the S. bdy. of the township, monumented by an iron post as described in the official record.	
		N. 0°03' W., bet. secs. 31 and 32.	
		Desc. over NE. slope.	
	2.50	Bottom of draw, drains SE.; asc. over SW. slope.	
	12.10	Top of hill, bears NW. and SE.; desc. over NE. slope.	
	19.70	Wash, 5 1ks. wide, 3 ft. deep, drains SE.	
	28.10	Draw, drains E. curving to SE.	
	32.20	Desc. over steep N. slope.	
	35.40	Draw, drains N. 20° E.; desc. along W. side of draw.	
	40.00	Point for the 2 sec. cor. of secs. 31 and 32.	
•		Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.	
•		T41N R11W	
		S31 S32 1962	
	49.30	Wash, 15 1ks. wide, 1 ft. deep, drains S. 15° E. on curve from SW.	
	53.20	Wash, 10 1ks. wide, 1 ft. deep, drains E.; asc. over S. slope.	
	66.50	Top of steep ascent; thence, over nearly level land.	
	80.00	Point for the cor. of secs. 29, 30, 31 and 32.	
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W S30 S29	
		S31 S32 1962	
		Cor. is located on flat mountain top.	
		Land, mountainous. Soil, rocky and clay loam. No timber; undergrowth, black brush, shadscale and cactus.	
			l

GYVAYNO	
CHAINS	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over mountainous land.
1.20	Small draw, drains N. 15° E.
5.80	Spur, slopes sharply N.
6.50	Desc. over ledge about 100 ft. high and steep slope facing NW.
29.90	Wash, 30 1ks. wide, 2 ft. deep, drains N.; asc. steep NE. slope.
35.50	Finger spur, slopes NE.
38.70	Wash, 10 1ks. wide, 3 ft. deep, drains NE.
40.10	Point for the ½ sec. cor. of secs. 29 and 32.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T4 IN R1 IW 2 S 29 5 32 1962
	Asc. steep E. slope.
63.70	Top of steep ascent, bears NW. and SE.; thence over gently sloping mountain top.
80.20	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. Soil, rocky and clay loam. No timber; undergrowth, small brush and cactus.
	N. 89°56' W., bet. secs. 30 and 31.
	Over mountain top.
5.30	Ledge, bears N. and S.; by triangulation, desc. over steep broken land facing W.; topography as taken from U.S.G.S. topographic sheet.
25.00	Draw, drains NW.
34.00	Spur, slopes NW.; desc. over gentle W. slope.
40.00	Point for the 4 sec. cor. of secs. 30 and 31.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W 2 S 30 S 31 1962
	Continue by triangulation; desc. W. slope.
44.30	Wash, drains N.; thence over gently rolling land, N. drainage and exposure.
55.50	Draw, drains N.

FIELD NOTE PAPER

31. CHAINS Subdivision, T. 41 N. R. 11 W., Arizona 65.50 Draw, drains N.; asc. E. slope. 75.70 End of triangulation on spur sloping NE. from S.; desc. over W. slope. Point for the 1/16 cor. of secs. 30 and 31. 80.00 Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd. $1/16 \frac{s}{s} \frac{30}{31} 80$ Continue over rolling land, N. drainage. The cor. of secs. 30 and 31 on the W. bdy. of the 99.99 township, monumented by an iron post as described in the official record. Land, mountainous. Soil, rocky and clay loam. No timber; undergrowth, black brush, shadscale and cactus. From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Asc. over S. slope on mountain top bearing NE. and SW. 10.30 Desc. over steep rolling land facing NW. 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30. Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd. T41N R11W s30 | s29 Cor. is located on the W. slope of spur sloping sharply N. Desc. over steep N. slope. Wash, 10 lks. wide, 1 ft. deep, steep sloping banks, 77.00 drains N. 20° E. Point for the cor. of secs. 19, 20, 29 and 30. 80.00 Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd. T41N R11W S19 | S20 S30 S29 1962

1	CHAINS	
		Land, mountainous. Soil, rocky clay loam. No timber; undergrowth, scattered black brush, shadscale and brigham tea.
		From the cor. of secs. 20, 21, 28 and 29.
		N. 89°57' W., bet. secs. 20 and 29.
		Asc. along N. slope.
	5.30	Desc. over rocky ledge facing W.
	8.30	Wash, 20 1ks. wide, 6 ft. deep, drains NW. from S. 15° E.; desc. over rolling and broken NW. slope.
	24.30	Base of steep descent, bears NE. and SW.; thence across mouth of canyon draining N.
	25.70	Wash, 60 lks. wide, 3 ft. deep, drains N. 20° W.
	29.40	Wash, 30 lks. wide, 6 ft. banks, drains N.; asc. gentle NE. slope.
	40.10	Point for the 4 sec. cor. of secs. 20 and 29.
		Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.
		T41N R11W 1/4 S 20 S 29 1962
	45.10	Spur, near end, slopes from the S.; thence along rolling N. slope.
	62.80	Small wash, drains N.
	73.10	Wash, 15 1ks. wide, 3 ft. deep, drains N.
	74.30	Low spur, slopes N. 15° E.
	77.90	Wash, 15 lks. wide, 4 ft. banks, drains N. 20° E.; asc. gentle SE. slope.
	80.20	The cor. of secs. 19, 20, 29 and 30.
		Land, mountainous. Soil, rocky clay loam. No timber; scattered creosote brush and shadscale.
		N. 89°55' W., bet. secs. 19 and 30.
		Over rolling, slightly broken land, by triangulation; topography as taken from U.S.G.S. topographic sheet.
	10.00	Spur, slopes N.
	15.50	Bottom of draw, drains N.
	28.00	Small draw, drains NE.
	40.00	Point for the ½ sec. cor. of secs. 19 and 30.
		Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.

FIELD NOTE PAPER 33. CHAINS Subdivision, T. 41 N., R. 11 W., Arizona T41N R11W ½ S 19 S 30 End of triangulation. 41.00 Bottom of draw, drains N. 46.50 Spur, slopes N. Wash, 15 1ks. wide, 1 ft. deep, drains NW. 52.80 Wash, 30 lks. wide, 2 ft. deep, high, nearly vertical 69.10 walls, drains NW. curving to W. 76.90 Desc. over steep, broken NW. slope. Point selected for the witness 1/16 sec. cor. of 79.70 secs. 19 and 30. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. $\frac{1}{16} \frac{\text{WC S } 19}{\text{S } 30} 80$ True point for the 1/16 cor. falls on ledge where cor. 80.00 cannot be perpetuated. Fence, around water tank, bears NW. and SE. 80.70 83.00 Base of steep descent, bears NE. and SW.; thence, over nearly level land. 99.85 The cor. of secs. 19 and 30 on the W. bdy. of the township, monumented by an iron post as described in the official record. from which A water tank, rock and mortar, 12 ft. x 20 ft. x 2 ft., bears N. 81°44' E., 18.12 chs. dist. Land, mountainous. Soil, rocky clay loam. No timber; undergrowth, brush and cactus. From the cor. of secs. 19, 20, 29 and 30. N. $0^{\circ}03$ ' W., bet. secs. 19 and 20. By triangulation over rolling mountainous land; N. drainage and exposure. Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20. 40.00 Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.

CHAINS	•
	T41N R11W
	\$19 \$20 1962
	End of triangulation.
48.60	Wash, 20 lks. wide, 1 ft. deep, drains N. 20° W.
67.30	Blade road, bears N. 60° W. and S. 60° E.; enter nearly level land.
76.70	Wash, 10 lks. wide, 1 ft. deep, drains NW. curving to NE.
79.60	Same wash, drains NE,
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W S18 S17 S19 S20 1962
	Land, rolling and broken on S. 67.00 chs., nearly level on remainder. Soil, rocky clay loam. No timber; undergrowth, scattered brush and cactus.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89°59' W., bet. secs. 17 and 20.
	Desc. over W. slope.
15.90	Wash, 30 lks. wide, 2 ft. deep, drains irregularly N. 30° E.; thence, over gently rolling land.
19.40	Blade road, bears N. and S.
30.60	Wash, 5 lks. wide, 1 ft. deep, drains N.
34.60	Small wash, drains N.
40.10	Point for the 1/2 sec. cor. of secs. 17 and 20.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T41N R11W 1/4 S 17 S 20 1962
	Cor. is located on gentle NE. slope.
43.90	Low spur, slopes N.
79.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° E.
80.20	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling. Soil, clay loam and rocky. No timber; undergrowth, scattered shadscale, brush and cactus.

FIELD NOTE PAPER

		FIELD NOTE PAPER	35.
	CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona	
			-
		N. 89°51' W., bet. secs. 18 and 19.	
		Over nearly level land.	
	1.30	Blade road, bears NE. and SW.	
	6.60	Wash, 30 lks. wide, 1 ft. deep, drains N. 30° E.	
	40.00	Point for the ½ sec. cor. of secs. 18 and 19.	
		Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		$\begin{array}{c c} \frac{1}{4} & \frac{S}{S} & \frac{18}{19} \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & \\ & & \\ & & \\ & & \\ & \\ & & \\ & & \\ & \\ & & \\ & \\ & & \\ & \\ & & \\ & & \\ & \\ & & \\ & \\$	
	62.90	Fence, bears N. and S.	
	80.00	Point for the 1/16 cor. of secs. 18 and 19.	
		Set the iron post 24 ins. in the ground, cap mkd.	
		$\frac{1}{16} \frac{S}{S} \frac{18}{19} 80$	
		1962	
		Raise a mound of stone N. of the cor.	
•	87.80	Wash, 10 lks. wide, 1 ft. deep, drains N. 15° E.	
	93.50	Top of low rise, bears NE. and SW.	
	99.68	The cor. of secs. 18 and 19 on the W. bdy. of the township, monumented by an iron post as described in the official record.	
		Land, nearly level. Soil, gravelly clay. No timber; undergrowth, scattered brush and shadscale.	
•		From the cor. of secs. 17, 18, 19 and 20.	
		N. 0°03' W., bet. secs. 17 and 18.	
		Over nearly level land.	
	.90	Blade road, bears NE. and SW.	
	26.30	Wash, 15 lks. wide, 1 ft. deep, drains N. 15° W.	
	30.40	Small wash, drains N. 60° W.; asc. along W. slope of small black hill.	
	40.00	Point for the ½ sec. cor. of secs. 17 and 18.	
		Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.	
-			
	i i		- 1

Subdivision, T. 41 N., R. 11 W., Arizona

_		Subdivision, 1. 41 N., N. II N., MIZONA
	CHAINS	T41N R11W
		戈 S18 S17
		1962
	59.20	Desc. over gentle NW. slope.
	79.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
	80.00	Point for the cor. of secs. 7, 8, 17 and 18.
		Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
		T41N R11W S 7 S 8 S18 S17 1962
		Land, rolling. Soil, clay loam and lava rock. No timber; undergrowth, creosote brush and cactus.
		From the cor. of secs. 8, 9, 16 and 17.
-		S. 89°57' W., bet. secs. 8 and 17.
		Over gently rolling land.
	5.30	Wash, 10 lks. wide, 3 ft. deep, drains N.
	8.90	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.
	15.90	Wash, 30 1ks. wide, 2 ft. deep, drains N. 60° E.
	25.50	Road, bears NE. and SW.; asc. over gentle E. slope.
	40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
		Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
		T4 IN R1 IW \(\frac{1}{4} \) \frac{S}{S} \frac{8}{17} \\ 1962
-		Asc. along spur sloping E.
	64.10	Crest of low hill, bears N. 30° E. and S. 30° W.; desc. over NW. slope.
	78.30	Wash, 10 1ks. wide, 1 ft. deep, drains SW.
	80.16	The cor. of secs. 7, 8, 17 and 18.
		Land, gently rolling. Soil, sandy clay and gravel. No timber; undergrowth, scattered creosote and cactus.
		N. 89°50' W., bet. secs. 7 and 18.
		Over gently rolling land.
	16.60	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.
	21.70	Wash, 15 lks. wide, 2 ft. deep, drains N.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.

FIELD NOTE PAPER

		FIELD NOTE PAPER	37.
	CHAINS		
	4	Subdivision, T. 41 N., R. 11 W., Arizona	
		Set the iron post 24 ins. in the ground, cap mkd.	
		T41N R11W	
	,	½ <u>S 7</u> S 18	
		1962	
		Raise mound of stone N. of post.	
	58.40	Fence, bears N. and S.	
	80.00	Point for the 1/16 sec. cor. of secs. 7 and 18.	
		Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.	
		1 S 7 80	
		$ \frac{1}{16} \frac{S}{S} \frac{7}{18} 80 \\ 1962 $	
	99.66	The cor. of secs. 7 and 18 on the W. bdy. of the township, monumented by an iron post as described in the official record.	
		Land, gently rolling. Soil, clay loam and gravel. No timber; undergrowth, scattered creosote brush, shadscale and cactus.	
		From the cor. of secs. 7, 8, 17 and 18.	
		N. 0°03' W., bet. secs. 7 and 8.	
		Asc. over gentle S. slope.	
	29.30	Top of small black mesa, bears E. and W. about 3.00	chs.
	31.70	Desc. over NW. slope.	
	37.30	Small draw, drains N. 60° W.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.	1
		Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R11W	
		S 7 S 8 1962	
	48.00	Enter nearly level land.	
	52.30	Road, bears NE. and SW.	
	72.50	Bladed road, bears N. 60° W. and S. 60° E.	
	80.00	Point for the sec. cor. of secs. 5, 6, 7 and 8.	
•		Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.	
,			
•			

	passarvision, 4, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,		
CHAINS	T41N R11W S 6 S 5 S 7 S 8 1962		
	Land, rolling on S. ½ mile, nearly level on remainder. Soil, rocky sandy clay loam. No timber; undergrowth, scattered creosote brush, shadscale and cactus.		
	From the cor. of secs. 4, 5, 8 and 9.		
	S. 89°57' W., bet. secs. 5 and 8.		
	Over nearly level land.		
2.70	Wash, 10 1ks. wide, 1 ft. deep, drains NE.		
6.50	Wash, 10 1ks. wide, 1 ft. deep, drains NE.		
14.30	Bladed road, bears N. and S.		
21.20	Narrow dirt road, bears NE. and SW.		
33.40	Wash, 5 lks. wide, 1 ft. deep, drains N.		
40.09	Point for the 4 sec. cor. of secs. 5 and 8.		
	Set the iron post 20 ins. in the ground, collar with stones, cap mkd.		
	T41N R11W 2 S 5 S 8 1962		
55.20	Small wash, drains NW.		
60.20	Wash, 15 1ks. wide, 1 ft. deep, drains NE.		
80.18	The cor. of secs. 5, 6, 7 and 8.		
	Land, nearly level. Soil, clay and gravel. No timber; undergrowth, scattered shadscale and creosote brush.		
	N. 89°46' W., bet. secs. 6 and 7.		
	Over nearly level land.		
10.00	Narrow dirt road, bears N. 20° E. and S. 20° W.		
40.00	Point for the 4 sec. cor of secs. 6 and 7.		
	Set the iron post 24 ins. in the ground, cap mkd.		
	T41N R11W		
	$\frac{1}{4} \frac{S}{S} \frac{6}{7}$ 1962		
	Raise a mound of stone N. of the post.		
59.00	Fence, bears N. and S.		
67.00	Wash, 10 1ks. wide, 2 ft. deep, drains N.		
80.00	Point for the 1/16 sec. cor. of secs. 6 and 7.		

FIELD NOTE PAPER

	7
CHAINS	Subdivision, T. 41 N., R. 11 W., Arizona
	Set the iron post 20 ins. in the ground, collar with stones, cap mkd.
	T41N R11W 1 S 6 S 7 80 1962
99.51	The cor. of secs. 6 and 7, on the W. bdy. of the township, monumented by an iron post as described in the official record.
	Land, nearly level. Soil, clay and gravel. No timber; undergrowth, scattered creosote brush and shadscale.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°14' E., bet. secs. 5 and 6.
	Over nearly level land.
9.20	Road, bears S. 70° E. and N. 70° W. for 1.00 chain, thence W.
11.60	Small wash, drains N. 25° W.
16.00	Small wash, drains W.
40.00	Point for the ½ sec. cor. of secs. 5 and 6.
	Set the iron post 24 ins. in the ground, cap mkd.
	T4 1N R1 1W
	S 6 S 5 1962
68.10	Wash, 10 1ks. wide, 1 ft. deep, drains NW.
80.39 The cor. of secs. 5, 6, 31 and 32 on the N. bdy. the township, monumented by an iron post as descrin the official record.	
	Land, nearly level. Soil, clay loam and gravel. No timber; undergrowth, scattered creosote brush and shadscale.
	General Description
	The land in Township 41 North, Range 11 West, varies from steep broken mountains cut by numerous washes and draws in the south and central part to nearly level in the northwest and rolling in the northeast. Dutchman Draw, Quail Draw and their tributaries drain the township northerly, emptying into Fort Pierce Wash.

CHAINS

The elevation varies from about 4850 feet above sea level in section 31 to 2800 feet above sea level in sections 2 and 6. Sunshine Trail extends southerly through the eastern part of the township with several roads branching off to water holes and mineral locations. A blade road with numerous side roads branching off extends northeasterly through the township along the base of the mountains.

There is fair grass and undergrowth at the higher elevations with livestock grazing being the present predominating interest. No active mining was noted in the township, although many location markers were in evidence.

200K 4075

Form 4-680 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

TILLU ASSISTANTS				
NAMES	CAPACITY			
Gary Oviatt	Transitman			
Daniel R. Bauer	Note Keeper			
Gordon Black	Front Chainman			
Robert Monasmith	Flagman			
George Chemas	Cornerman			
· · · · · · · · · · · · · · · · · · ·				

CERTIFICATE OF SURVEY We Boyd S. Owens Wallace R. Ott , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of , 19 62 , surveyed the subdivisional lines of Township 41 North, Range 11 I/have West of the Gila and Salt River Meridian, in the State of , which Arizona are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes. May 1, 1963 (Date) May 1, 1963 / CERTIFICATE OF APPROVAL Bureau of Land Management The foregoing field notes of the subdivisional lines of Township 41 North, Range 11 West, Gila and Salt River Meridian, Arizona. Boyd S. Owens, Cadastral Surveyor Wallace R. Ott, Surveying Aid executed by having been critically examined and found correct, are hereby approved. Washington, D.C. DEC 5 1963 of Enginee CERTIFICATE OF TRANSCRII I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

, is a true copy of the original field notes.

(Chief. Division of Engineering)