Form 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY
North, South, East and West Boundaries
and the
Subdivisional Lines
Township 15 North, Range 26 East
Township 15 North, Range 20 Base
<u> </u>
Of the Gila and Salt River Meridian,
In the State ofArizona
EXECUTED BY
Boyd S. Owens, Cadastral Surveyor
Paul G. Bauer, Cadastral Surveyor
Wallace R. Ott, Cadastral Surveyor
Under special instructions dated March 13 , 1963 , which provided for the surveys
sincluded under Group Number 389 , approved March 18, 1963 ,
and assignment instructions dated <u>November 26</u> , 19 63.
Survey commenced November 26, 19 63

Survey completed ______January 31

____, 19 <u>64</u>

BCC1/ 4703

INDEX DIAGRAM

	Т	ownsl	nip <u>15</u>	Nor	th		, Range	2	6 East		······	
	15		16		. 17		17		18		18	
14	6	56	5	47	4	40	8	33	2	25	1	10
	55		55		46		40		33		25	
14	7	54		45	9	39	10	32		24	12	9
	54		53		45		38		31		24	_
13	18	53	17	44	16	38	15	31	14	23	13	9
	52		52		44		37		30		22	
12	19	51	20	43	21	36	22	29	28	22	24	6
	50		50		43		36		29		21	
12	80	49	29	42	28	35	27	28	26	20	25	7
	49		48		41		34		27		20	
11	31	47	32	41	33	34	84	26	35	19	36	6
	1		2		3		3		4		5	

Township 15 North, Range 26 East Gila and Salt River Meridian, Arizona

10

CHAINS

The south boundary was surveyed in 1875 by C. B. Foster and dependently resurveyed in 1882 by O. D. Wheeler. The boundary was retraced in 1944 by Forrest and Warner. The north, east and west boundaries and the subdivisional lines were surveyed in 1882 by O. D. Wheeler.

The following notes are those of a dependent resurvey of the south, east, north and west boundaries and the subdivisional lines of Township 15 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 13, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base and with a brass cap riveted to the top. Original corner monuments, unless described otherwise, were deposited alongside the new monuments.

The geographic position of the southeast corner of the township is: Latitude, 34°39'37" North, and Longitude, 109°31'37.9 " West.

The magnetic declination was found to be 14° East.

Dependent Resurvey of the South Boundary Township 15 North, Range 26 East

Reestablishment of the Survey by O. D. Wheeler in 1882

The cor. of Tsl4&15N, Rs25&26E, monumented by a mound of stone. I accept this as the best remaining evidence of the cor. position.

At the corner point

Set an iron post 20 ins. in the ground, cap mkd.

T15N R25E R26E S36 S31 S1 S 6 T14N 1963

Raise a mound of stone S. of the cor.

Topography as adjusted from random lines.

N. $83^{\circ}22^{\circ}$ E., bet. secs. 6 and 31.

Asc. over gently rolling land.

Spur, slopes irregularly S. 60° W. from North.

Small spur, slopes S.

17.50

2	Pogumyou Couth Boundame TIEN DOCE
CHAINS	Resurvey, South Boundary, T15N, R26E, Arizona
28.80	Wash, 30 lks. wide, 4 ft. banks, drains S. 25° W.; thence over gently rolling range land.
46.00	Wash, 20 1ks. wide, 4 ft. banks, drains S. 15° W.
75.69	Point for the ½ sec. cor. of secs. 6 and 31 at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set an iron post 20 ins. in the ground and in a collar of stone, cap mkd.
	T15N R26E 1/4 S 31 T14N R26E 1963
115.74	The cor. of secs. 5, 6, 31 and 32, monumented by a sandstone $16 \times 12 \times 2$ ins. marked with 5 grooves on E. and 1 groove on W. edge.
,	At the cor. point
	Set the iron post 20 ins. in the ground, cap mkd.
	T15N R26E S31 S32 S6 S5 T14N R26E 1963
	Raise a mound of stone W. Land, gently rolling. Soil, sand and clay. Timber, widely scattered juniper on spur. Undergrowth, sagebrush and weeds.
	N. 84°36' E., bet. secs. 5 and 32.
	Over gently rolling range land.
12.20	Fence, barbed wire, bears NW. and SE.
39.69	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 20 ins. in the ground, cap mkd.
	T15N R26E 1/4 S 32 1/4 S 5 T14N R26E
	1963
	Raise a mound of stone north of the cor.
47.30	Small spur, slopes S.
59.70	Wash, 30 1ks. wide, course S.
63.80	Wash, 10 lks. wide, course SW.
79.38	The cor. of secs. 4, 5, 32 and 33, monumented by an old cedar stake, dimly mkd., in a small mound of stone. I accept this as the best remaining evidence
	of the cor.

Resurvey, South Boundary, T15N, R26E, Arizona

	CHAINS	·
1		At the cor. point
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
		T15N R26E <u>S32 S33</u> S 5 S 4 T14N R26E 1963
		Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, scattered sagebrush and weeds.
		N. 83°20' E., bet. secs. 4 and 33.
		Over gently rolling range land.
	40.56	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33 at proportionate dist.; unable to find any remaining evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		$\frac{1}{4} \frac{S}{S} \frac{33}{4}$
		T14N R26E 1963
		Raise a mound of stone North of the cor.
	EQ 00	
	58.20	Road, bears N. and S.
	62.50	Fence, barbed wire, bears N. 15° E. and S. 15° W.
•	64.00	Asc. over broken land, NW. drainage and exposure.
	81.12	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 18 ins. in the ground, cap mkd.
		T15N R26E S33 S34 S4 S3 T14N R26E 1963
		Cor. falls on spur sloping W.
		Land, nearly level on W. 62.00 chs., mountainous on remainder. Soil, sandy clay loam. Timber, none. Undergrowth, scattered sagebrush and weeks.
		N. 83°20' E., bet. secs. 3 and 34.
		Asc. over broken W. slope of North Mountain.

		BOOK 4703	
	7	Resurvey, South Boundary, T15N, R26E, Arizona 4	•
	CHAINS		
	27.50	Top of asc. on crest of spur sloping SE.; desc. over rolling and broken E. slope.	
	40.56	The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented by a sandstone $18x12x4$ ins. in a small mound of stone, mkd. $\frac{1}{4}$ on N. face, with mound of stone North.	
		At the cor. point	
		Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.	
		T15N R26E	
		$\frac{1}{4} \frac{s}{s} \frac{34}{3}$	
		T14N R26E 1963	
		N. 84°17' E., beginning new measurement.	
		Desc. over broken E. slope of North Mountain.	
	9.70	Spur, slopes S. 10° W.	
	15.00	Wash, 10 1ks. wide, 2 ft. deep, drains S.	
	40.13	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; unable to find any remaining evidence of the original cor.	
		Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
		T15N R26E <u>S34 S35</u> S 3 S 2 T14N R26E 1963	
		The cor. falls on S. slope of spur sloping SE.	
		Land, mountainous. Soil, sandy clay loam. Timber, scattered junipers. Undergrowth, scattered sage.	
		N. 84°17' E., bet. secs. 2 and 35.	
		Desc. along general S. slope.	
	5.00	Base of mountain, bears irregularly N. and SW.; thence, over nearly level land.	
	7.70	Old road, bears S. 20° W. and N. 20° E.	
:	18.10	Wash, 50 lks. wide, 2 ft. banks, drains S. 25° W.	
	22.00	Asc. over west slope of low rolling hills.	
	31.90	Top of ascent, bears N. 10° E., and S. 10° W.	
	40.13	The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented by a sandstone 14x14x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N. face.	
		<i>[</i>	

	CHAINS	
	CHAINS	At the cor. point
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		$\frac{1}{4} \frac{\text{S } 35}{\text{S } 2}$
	1	T14N R26E 1963
		Raise a mound of stone N. of the cor.
		N. 83°48' E., beginning new measurement.
		Over gently rolling land.
	2.60	Spur, slopes S. 35° E.
	28.90	Wash, 2.00 chs. wide, 3 ft. banks, drains S. 20° W.; thence over bottom of valley.
	35.00	Fence, barbed wire, bears N. and S.
	40.56	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; unable to find any remaining evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		<u>S35 S36</u> S 2 S 1
		T14N R26E
		1964
.		Raise a small mound of stone W. of the cor.
		Land, gently rolling. Soil, sandy clay loam. Timber, widely scattered junipers. Undergrowth, sagebrush.
		N. 83°48' E. bet. secs. 1 and 36.
		Over gently rolling land.
	11.90	Dirt dike, 20 lks. wide, about 18 chs. long, bears N. 55° W. and S. 55° E.
İ	20.90	Road, bears N. 20° E. and S. 20° W.
	33.60	Asc. over gentle W. slope.
	38.50	Small spur, slopes SW.
	40.57	Point for the ½ sec. cor. of secs. 1 and 36 at proportionate dist.; unable to find any remaining evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		$\frac{1}{4} \frac{S}{S} \frac{36}{1}$
		T14N R26E
I		1963

6		Dep. Resurvey, E. Bdy., T15N, R26E, Arizona 6.
<u> </u>	CHAINS	
		Raise a mound of stone N. of the cor.
	41.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.; asc. over low rolling hills, SW. drainage and exposure.
	58.60	Crest of low ridge, bears S. 25° W. and N. 25° E.
	68.30	Wash, 20 1ks. wide, 4 ft. deep, drains S. 10° W.
	74.80	Spur, slopes S. 30° W.
·	81.14	The cor. of Ts14&15 N., Rs26&27 E., monumented by an old deteriorated cedar stake, set in a small mound of scattered stone. After considerable retracement I accept this as the best remaining evidence of the township cor.
		At the cor. point
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E R27E S36 S31 S1 S 6 R26E R27E T14N 1963
		Raise a mound of stone S. of the cor.
		From this cor. the cor. of secs. 1, 6, 7 and 12, T14N, Rs26&27E, bears S. 3°55' W., 104.01 chs. dist., monumented by an old cedar stake, firmly set and dimly marked. The position does not fit the topography as recorded in the original survey.
		From the township cor. the cor. of secs. 3, 4, 33 and 34, Ts14&15N, R27 E., bears N. 89°55' E., 247.28 chs. dist., monumented by an old cedar stake dimly mkd. with 5 ft. cedar post set alongside.
		Land, gently rolling. Soil, sandy. Timber, widely scattered juniper. Undergrowth, sage and black brush.
		Dependent Resurvey of the East Boundary Township 15 North, Range 26 East
		Reestablishment of the Survey in 1882 by O. D. Wheeler
		From the township cor. of Ts14&15 N., Rs. 26 and 27 E.
		N. 0°45' E. bet. secs. 31 and 36.
		Over low rolling hills through moderate blackbrush.
ì		Asc. over S. slope.
	9.50	Ridge, bears NE. and SW.

BOOK 4703

	_ 5 5 2 2 1100
· r	Dep. Resurvey, E. Bdy., T15N, R26E, Arizona
23.00	Ridge, bears NE. and SW.; thence along rolling W. slope
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36 at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N
	R26E R27E
	S36 S31 1963
	Raise a mound of stone W. of the cor.
46.50	Small spur, slopes N. 85° W.
58.90	Spur, slopes N. 80° W.
69.40	Spur, slopes W.
80.44	Point for the cor. of secs. 25, 30, 31 and 36 at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E R27E
	\$25 S30 \$36 S31 1963
	Raise a mound of stone West of the cor.
	Land, low rolling hills. Soil, sandy clay loam. No timber; undergrowth, black brush and sage.
	N. 0°45' E., bet. secs. 25 and 30.
	Over low rolling hills through moderate undergrowth.
.40	Small wash, drains $^{ extsf{NW}}$.
9.40	Wash, 1.00 chain wide, 5 ft. banks, drains W.; thence over rolling land, W. drainage and exposure.
36.00	Spur, slopes S. 85° W.
40.22	Point for the ½ sec. cor. of secs. 25 and 30 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T 15N R26E R27E ½
	S25 S30 1963
	Raise a small mound of stone West of the cor.
†	

	BCOK 4703
8	Dep. Resurvey, E. Bdy., T15N, R26E, Arizona 8.
CHAINS	
54.10	Wash, 90 lks. wide, 5 ft. banks, drains S. 65° W.
56.70	Spur, slopes S. 40° W.
64.90	Wash, 25 lks. wide, 3 ft. deep, drains SW.
80.44	Point for the cor. of secs. 19, 24, 25 and 30 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N
	R26E R27E S24 S19
	\$25 \$30 1963
	Raise a mound of stone W. of the cor.
	Land, low rolling hills. Soil, sandy loam.
	Timber, widely scattered junipers.
	Undergrowth, blackbrush and sage.
	N. 0°45' E., bet. secs. 19 and 24.
	Over low rolling hills.
37.00	Fence, barbed wire, bears N. 41°58' W. and S. 41°58' E.
37.20	Road, parallels fence.
40.22	Point for the ½ sec. cor. of secs. 19 and 24 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E R27E
	524 S 19
	1963
	from which
	A windmill bears N. 42°21' W., 7.02 chs. dist.
ŀ	Raise a mound of stone West of the cor.
	Continue over nearly level land through moderate undergrowth and widely scattered timber.
48.50	Old road, bears NW. and SE.
80.44	Point for the cor. of secs. 13, 18, 19 and 24 at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E R27E <u>S13 S18</u> S24 S19
	1963

a

	Gr. A raya	
	CHAINS	Raise a mound of stone West of cor.
		Land, gently rolling.
		Soil, sandy. Timber, scattered to widely scattered junipers. Undergrowth, moderate black brush.
	:	
		N. 0°45' E., bet. secs. 13 and 18.
		Over gently rolling land through scattered timber and moderate brush.
	21.10	Ascend over gentle S. slope.
	40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18 at proportionate distance; unable to find any remaining evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E R27E
-		
		S13 S18 1963
		Raise a mound of stone West of the cor.
		Enter moderate timber, bears irregularly E. and W.
	80.44	Point for the cor. of secs. 7, 12, 13 and 18 at proportionate distance; unable to locate any evidence of the original cor.
		Set the iron post 20 ins. in the ground, cap mkd.
		T15N
		R26E R27E S12 S7
		S13 S18
		1963
:		from which
		A juniper, 6 ins. diam., bears N. 7°45' E., 11 lks. dist., mkd. S7BT
		Raise a mound of stone West of the cor.
		Land, gently rolling. Soil, sandy loam.
		Timber, scattered juniper on S $\frac{1}{2}$ mile, moderate on remainder.
		Undergrowth, moderate sage.
		N. 0°45' E., bet. secs. 7 and 12.
		Asc. gentle S. slope through moderate timber.
	40.22	Point for the ½ sec. cor. of secs. 7 and 12 at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		•

U	Dep. Resurvey, E. Bdy., 115N, R26E, Ar1zona	1
CHAINS		
	T15N	
	R26E R27E	
	S12 S 7	
	1963	
	Raise a mound of stone West of the cor.	
80.44	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T15N	
	R26E R27E	
	<u>S 1 S 6</u> S12 S 7	
	1963	
	from which	
	A juniper, 8 ins. diam., bears N. 62° E., 58 lks. dist., mkd. T15NR27ES6BT	
	Raise a mound of stone West of the Cor.	
	Land, gently rolling.	
	Soil, sandy loam.	
	Timber, moderate to heavy juniper. Undergrowth, black brush.	
Fedi		_
	N. 0°45' E., bet. secs. 1 and 6.	
	Over nearly level land through moderate to heavy timber.	
40.22	Point for the ½ sec. cor. of secs. 1 and 6 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T15N R26E R27E	
7	S 1 S 6 1963	
	from which	
	A juniper, 12 ins. in diam., bears N. 19°20' E., 77 lks. dist., mkd. ½S6BT	
	A juniper, 10 ins. diam., bears S. 89°30' W., 63 lks. dist., mkd. ½S1BT	
	Raise a mound of stone W. of the cor.	
80.44	Point for the cor. of Ts15&16N, Rs26&27E, at proportionate dist.; unable to find any evidence of the original township cor.	
	Set the iron post 24 ins. in the ground, cap mkd.	
}		

Den.	Resurvey.	W.	Bdv.	T15N.	R26E.	Arizona

,	CHAINS	
		T16N R26E R27E S36 S31 S 1 S 6 T15N 1963
		from which
		The cor. of Ts15&16N, Rs27&28E, bears S. 89°32' E., 479.20 chs. dist., monumented by an iron post as described in the survey notes of T15N, R28E.
		The closing cor. of T16N, Rs26&27E, bears N. 1°06' W., 407.69 chs. dist., monumented by an iron post as described in the survey notes of T16N, R26E, surveyed concurrently and under this same group number.
		An intersection of fences bearing N. 3° E., S. 3° W. and S. 87°40' E., bears S. 23°31' W., 19.34 chs. dist.
		A fence cor. of fence bearing N. 3° E. and S. 84° 20' W., bears S. 20°11' W., 22.97 chs. dist.
		Land, nearly level. Soil, sandy. Timber, moderate juniper. Undergrowth, black brush.
		Dependent Resurvey of the West Boundary Township 15 North, Range 26 East
		Reestablishment of the Survey in 1882 by O. D. Wheeler
		From the cor. of Ts14&15N, Rs25&26E, hereinbefore described.
		N. 0°12' E., bet. secs. 31 and 36.
		Over nearly level range land through scattered undergrowth.
	40.33	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36 at proportionate dist.; unable to locate any evidence of the original cor.
:		Set the iron post 22 ins. in the ground, cap mkd.
		T15N R25E R26E
		\$36 \$31 1963
		Raise a mound of stone West of the cor.
	80.10	Fence, bears S. 55° E. and N. 55° W. for 3.00 chs. to N-S fence line.

de.	Dep. Resurvey, W. Bdy., 115N, R26E, Arizona
CHAIN	
80.66	Point for the cor. of secs.25, 30, 31 and 36 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 20 ins. in the ground, cap mkd.
	T15N
	R25E R26E S25 S30
	S36 S31
	1963
	Raise a mound of stone West of the cor.
	Land, nearly level.
	Soil, sandy loam.
	No timber; undergrowth, scattered brush.
	N. 0°12' E., bet. secs. 25 and 30.
	Over nearly level range land.
39.20	Wash, 20 1ks. wide, 2 ft. deep, drains S. 80° W.
40.33	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T15N
	R25E_R26E
	S25 S30
	1963
80.66	Point for the cor. of secs. 19, 24, 25 and 30 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
į	T15N
	R25E R26E
	S24 S19
	\$25 \$30 1963
	I and magning lovel
	Land, nearly level. Soil, sandy loam.
	No timber; undergrowth, scattered brush.
	N. 0°12' E., bet. secs. 19 and 24.
	Over nearly level land.
40.33	Point for the ½ sec. cor. of secs. 19 and 24 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 21 ins. in the ground, cap mkd.
1	l l

Den.	Resurvey.	W.	Bdv	T15N.	R26E.	Arizona

	= = = = = = = = = = = = = = = = = = = =
	Dep. Resurvey, W. Bdy., T15N, R26E, Arizona
CHAINS	
	T15N R25 E R26E
	14.
	S24 S 19
	1963
	Raise a mound of stone West of the cor.
80.66	Point for the cor. of secs. 13, 18, 19 and 24 at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N
·	R25E R26E
	<u>S13 S18</u> <u>S24 S19</u>
	1963
	Raise a mound of stone West of the cor.
	Land, nearly level range land.
	Soil, sandy loam. No timber; undergrowth, scattered brush.
	N. 0°12' E., bet. secs. 13 and 18.
	Over gently rolling grassland.
18.00	Leave grass land, enter low rolling barren clay hills.
40.33	Point for the ½ sec. cor. of secs. 13 and 18 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N
	R25 E R26 E ½
	S13 S18
	1963
	Raise a mound of stone West of the cor.
80.66	The cor. of secs. 6, 12, 13 and 18, monumented by a sandstone $12x6x4$ ins., dimly mkd. as described in the official record.
	At the cor. point
	Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.
ĺ	T15N
	R25E R26E
	S12 S 7
	\$\frac{\overline{\sigma}}{\sigma} \frac{\overline{\sigma}}{1963}
	Land, gently rolling.
	Soil, sandy clay on south 18 chs., clay loam on
	remainder. No timber; undergrowth, scattered brush.
1	

<i></i>	7	Dep. Resurvey, W. Bdy., TIDN, R26E, Arizona	14
	CHAINS		1
		N. 2°21' E., bet. secs. 7 and 12.	
		Over low rolling barren clay hills.	
	4.30	Leave barren clay land, enter nearly level grass land.	
	39.83	Point for the ½ sec. cor. of secs. 7 and 12 at proportionate dist.; unable to locate any evidence of the original cor.	
		Set the iron post 20 ins. in the ground, cap mkd.	
	,	T15N R25 E R26 E	
		S12 S 7 1963	
	54.70	Wash (Surprise Creek), 1.30 chs. wide, 4 ft. deep, drains S. 85° W.	
	79.66	Point for the cor. of secs. 1, 6, 7 and 12 at proportionate dist.; unable to find any evidence of the original cor.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T15N R25E R26E <u>S1 S6</u> S12 S7 1963	
		from which	
		N-S fence line bears West, 7.05 chs. dist.	
		Raise a mound of stone West of the cor.	
		Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, yellow brush.	•
		N. 2°21' E., bet. secs. 1 and 6.	
		Over nearly level grass land.	
	30.90	Wash, 20 1ks. wide, 3 ft. deep, drains irregularly S. 70° W.	
	39.83	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 at proportionate dist.; unable to find any evidence of the original cor.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T15N R25E R26E	
		S 1 S 6 1963	
		Raise a mound of stone West of the cor.	

		BOOK 4703	
		Dep. Resurvey, N. Bdy., T15N, R26E, Arizona 15.	
	CHAINS		
	71.50	Low ridge, bears N. 30° E., and S. 30° W.	
:	75.30	Fence, bears N. 84° E. and S. 84° W.	
	79.66	Point for the cor. of Ts15&16N, Rs25&26E, at proportionate dist.; unable to find any evidence of the original cor.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T16N R25E R26E <u>S36 S31</u> S 1 S 6 1963	
		from which	
		The cor. of Ts15&16N, Rs24&25E, bears S. 89°07' W., 485.74 chs. dist., monumented by an iron post as described in the official record.	
		The closing cor. of T16N, Rs25&26E, bears N. 1° 27' W., 457.92 chs. dist., monumented by an iron post described in the survey of T16N, R26E.	
•		A N-S fence line bears West, 10.29 chs. dist.	
		Raise a mound of stone S. of the cor.	
,		Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, scattered yellow brush.	
,		Dependent Resurvey of the North Boundary Township 15 North, Range 26 East	
		Reestablishment of the Survey in 1882 by O. D. Wheeler	
		From the cor. of Ts15&16N, Rs25&26E.	
		N. 83°42' E., bet. secs. 6 and 31.	
		Over gently rolling land.	
	9.20	Low rolling ridge, bears SW. and NE.; thence over nearly level range land.	
	75 . 95	Point for the ½ sec. cor. of secs. 6 and 31 at proportionate dist.; unable to locate any evidence of the original cor.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T16N R26E 1/4 S 31 S 6	
	•	⁴ S 6 T15N 1963	
		Raise a mound of stone N. of the cor.	

Pocuryon	N	Rdv	T 15N	R26E.	Arizona	17

	Dep. Resurvey, N. Bdy., T15N, R26E, Arizona	17.
CHAINS		
	N. 83°42' E., bet. secs. 4 and 33.	
	Over gently rolling range land.	
15.80	Wash, 90 lks. wide, 3 ft. deep, drains SW.	
40.08	Point for the ½ sec. cor. of secs. 4 and 33, at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T16N R26E 1/4 S 33 S 4 T15N 1963	
	Raise a mound of stone North of the cor.	
46.90	Wash, 1.00 chain wide, 3 ft. deep, drains irregularly SW.; thence across bend of wash and over level land.	
80.16	Point for the cor. of secs. 3, 4, 33 and 34 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T16N R26E S33 S34 S4 S 3 T15N 1963	
	Raise a mound of stone West of the cor.	
	Land, nearly level. Soil, sandy clay. No timber; undergrowth, yellow brush and shadscale.	
	N. 83°42' E., bet. secs. 3 and 34.	
	Over nearly level range land.	
22.70	Wash, 90 lks. wide, 1 ft. deep, drains NW.	
40.08	Point for the ½ sec. cor. of secs. 3 and 34 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	T16N R26E 1/4 S 34 T15N 1963	
	Raise a mound of stone N. of the cor.	
57.90	Small wash, drains NW.	
70.60	Fence, barbed wire, bears N. 15°40' W. and S. 15°40' E	
1		l

18	Dep. Resurvey, N. Bdy., T15N, R26E, Arizona 1
CHAINS	
74.60	Leave valley; asc. over blue clay hills.
80.16	Point for the cor. of secs. 2, 3, 34 and 35 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 20 ins. in the ground, cap mkd.
	T16N R26E S34 S35 S3 S2 T15N 1963
	Raise a mound of stone West of the cor.
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, yellow brush.
	N. 83°42' E., bet. secs. 2 and 35.
	Asc. over steep broken clay hills.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T16N R26E 1/4 S 35 S 2 T15N 1963
56.30	Enter scattered timber.
66.50	Leave clay hills; asc. over general W. slope.
80.16	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 20 ins. in the ground, and in a collar of stone, cap mkd.
	T16N R26E S35 S36 S 2 S 1 T15N 1963
	Deposit glass in the hole.
	Land, rolling and broken. Soil, clay loam. Timber, scattered juniper on E. 24.00 chs. Undergrowth, black brush and shadscale.
	N. 83°42' E., bet. secs. 1 and 36.
	Asc. over W. slope through scattered timber.

		300k 4703
		Dep. Resurvey, Subdivision, T15N, R26E, Arizona 19.
	CHAINS 14.40	Rim of bluff, bears NW. and SE.; thence over nearly
	40.08	Point for the ½ sec. cor. of secs. 1 and 36, at proportionate dist.; unable to locate any evidence of
		the original cor. Set the iron post 20 ins. in the ground, cap mkd.
		T16N R26E
,		T 15N 1963
		Raise a mound of stone N. of the cor.
	·	Enter scattered timber.
	68.00	Road bears N. 48° E. and S. 48° W.
	80.16	The cor. of Ts15&16N, Rs26&27E.
		Land, nearly level on E. 66.00 chs. Soil, sandy loam.
		Timber, scattered junipers. Undergrowth, sage and yellow brush.
		Dependent Resurvey of the Subdivisional Lines Township 15 North, Range 26 East
		Reestablishment of the Survey in 1882 by O. D. Wheeler
	·	From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township.
		N. 0°35' W., bet. secs. 35 and 36.
		Over nearly level grass land.
	6.40	Wash, 150 lks. wide, 6 ft. banks, drains SW.
'	37.25	Point for the ½ sec. cor. of secs. 35 and 36, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		S35 S36 1964
		Raise a mound of stone W. of the cor.
	48.20	Asc. gradual S. slope.
	61.50	Small spur, slopes W.
	74.50	The cor. of secs. 25, 26, 35 and 36, monumented by a sandstone 12x8x6 ins., lying loose upon the ground, mkd. as described in the official record.

		Dep. Resurvey, Subdivision, T15N, R26E, Arizona	20.
· *** *** *** *** *** ***	CHAINS		T
		At the cor. point	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T15N R26E <u>S26 S25</u> S35 S36	
		1964	
		Raise a mound of stone West of the cor.	
		Land, nearly level. Soil, sandy clay loam. Timber, widely scattered juniper. Undergrowth, scattered sage.	
		From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township.	
		S. 79°55' W., bet. secs. 25 and 36.	
		Over gently rolling land.	
	22.40	Wash, 30 lks. wide, 4 ft. banks, drains S. circling SW.	
	25.70	Wash, 45 lks. wide, 4 ft. banks, drains S.; asc. gentle E. slope.	
	40.00	Top of asc., bears N. and S.; desc. gentle W. slope.	
	41.85	Point for the ½ sec. cor. of secs. 25 and 36 at proportionate dist.; unable to find any evidence of the original cor.	
		Set the iron post 24 ins. in the ground, mound with stones to top, cap mkd.	
1		T15N R26E	
		$\frac{1}{4} \frac{S \ 25}{S \ 36}$	
		1964	
	46.90	Road, bears N. and S.	
	54.80	Wash, 30 1ks. wide, 4 ft. banks, drains S.	
	63.80	Wash, 10 1ks. wide, 3 ft. deep, drains S. 10° E.	
:	72.50	Wash, 100 1ks. wide, 2 ft. deep, drains SE.	
	83.70	The cor. of secs. 25, 26, 35 and 36.	
		Land, gently rolling. Soil, clay loam and hardpan. Timber, very widely scattered junipers. Undergrowth, scattered yellow brush and sage.	
		N. 1°25' E., bet. secs. 25 and 26.	
		Asc. over gently rolling range land.	
	6.40	Top of ascent, bears SE. and S. 80° E. from W.	1
	10.50	Dry wash, 100 lks. wide, 2 ft. deep, drains irregularly SE.; thence along side of wash draining irregularly S. from N.	

Dep. Resurvey, Subdivision, T15N, R26E, Arizona CHAINS 40.44 Point for the ½ sec. cor. of secs. 25 and 26 at proportionate dist.; unable to find any evidence of the	2
40.44 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26 at proportionate dist.; unable to find any evidence of the	
original cor.	
Set the iron post 24 ins. in the ground, cap mkd.	
T15N R26 E \$26 S25 1964	
Raise a mound of stone W. of the cor.	
68.00 Top of low clay hill.	
80.88 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; unable to find any evidence of the original cor.	
Set the iron post 24 ins. in the ground, cap mkd.	
T15N R26E <u>S23</u> <u>S24</u> <u>S26</u> <u>S25</u> 1964	
Raise a mound of stone West of the cor.	
Land, gently rolling. Soil, sandy clay loam. Timber, few junipers. Undergrowth, scattered sage brush.	
From the cor. of secs. 19, 24, 25 and 30 on the E. bdy of the township.	
S. 80°05' W., bet. secs. 24 and 25.	
Over gently rolling land.	
6.50 Wash, 15 1ks. wide, 3 ft. deep, drains S. 10° W.	
13.10 Low ridge, bears irregularly NW. and S.	
24.90 Road, bears N. 10° E. and S.	
28.80 Wash, 40 1ks. wide, 7 ft. banks, drains S. 15° E.	
Point for the ½ sec. cor. of secs. 24 and 25 at proportionate dist.; unable to find any evidence of the original cor.	
Set the iron post 24 ins. in the ground, cap mkd.	
T15N R26E 1/4 S 24 S 25 1964	
Raise a mound of stone N. of the cor.	
Continue over gently rolling land.	
65.60 Wash, 15 1ks. wide, 1 ft. deep, drains S.	

	bep, Resulvey, Subulvision, 1131, 1223, 1212ona
CHAINS	
82.68	The cor. of secs. 23, 24, 25 and 26.
	Land, gently rolling.
	Soil, sandy clay loam. Timber, widely scattered junipers.
	Undergrowth, sage and yellow brush.
	N. 1°20' W., bet. secs. 23 and 24.
	Over gently rolling land.
8.60	Asc. over broken clay hills.
40.44	The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented by a sandstone, $12x6x4$ ins., mkd. $\frac{1}{4}$ on W. face.
	At the cor. point
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T15N R26E
	S23 [₹] S24
	1964
	N. 3°48' E., beginning new measurement.
	Over low rolling clay hills.
26.60	Wash, 30 lks. wide, 4 ft. deep, drains S. 50° E.
31.10	South rim of ridge, bears S. 75° E, and N. 80° W.; enter scattered timber.
40.98	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26 E
	<u>S14 S13</u> S23 S24
	1964
	Raise a mound of stone West of the cor.
	Land, gently rolling.
	Soil, clay and sandy loam. Timber, widely scattered to scattered juniper. Undergrowth, black brush and shadscale.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township.
	S. 80°37' W., bet. secs. 13 and 24.
	Over nearly level land, through scattered junipers.
34.10	Road, bears NW. and SE.

BCCK 4703

	2001% 4100
	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 23.
CHAINS	
34.30	Fence, barbed wire, bears N. 42°10' W. and S. 42°10' E.
37.70	Road, bears NW. and SE.
40.88	Point for the ½ sec. cor. of secs. 13 and 24.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	$\frac{1}{4} \frac{S}{S} \frac{13}{24}$
	1964
	Raise a mound of stone North of the cor.
51.90	Wash, 10 1ks. wide, 3 ft. deep, drains S.
81.76	The cor. of secs. 13, 14, 23 and 24.
	Land, gently rolling.
	Soil, sandy loam. Timber, scattered juniper.
	Undergrowth, black brush and sage.
	N. 0°52' E., bet. secs. 13 and 14.
	Over gently rolling land, through scattered junipers.
19.80	Road, bears S. 84°10' E. and N. 84°10' W.; asc. gentle S. slope.
23.80	Enter moderate to dense juniper, bears N. 75° E. and SW.; thence over nearly level land.
40.89	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S 14 S 13 1964
	from which
	A juniper, 8 ins. diam., bears N. 25°45' E., 86 lks. dist., mkd. \ddash513BT.
	Raise a mound of stone West of the cor.
51.90	Road, bears S. 85° E. and N. 50° W.
62.60	Fence, barbed wire, bears N. 54°10' W. and S. 54°10' E.
81.78	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E S11 S12 S14 S13
	1964

`/	Dep. Reput vey, Bubut vibion, 115th, 115th, 115th
CHAIN	5
	from which
	A juniper, 14 ins. diam., bears S. 51°05' E., 169 lks. dist., mkd. S13BT
	A juniper, 8 ins. diam., bears N. 79°30' W., 181 lks. dist.; mkd. S11BT
ŀ	Raise a mound of stone West of the cor.
	Land, gently rolling. Soil, sandy loam. Timber, scattered to dense juniper. Undergrowth, sagebrush.
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township.
	S. 81°31' W., bet. secs. 12 and 13.
	Over gently rolling land through moderate timber.
40.65	Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E 1/4 S 12 S 13 1964
	from which
	A juniper, 8 ins. diam., bears N. 19°54' E., 65 lks. dist., mkd. ½S12BT
	Raise a mound of stone N. of the cor.
73.60	Road, bears irregularly N. and S.
81.30	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling. Soil, sandy loam. Timber, moderate to dense junipers. Undergrowth, sage and blackbrush.
	N. 1° E., bet. secs. 11 and 12.
	Asc. gradually through dense junipers.
28.60	
40.89	Point for the ½ sec. cor. of secs. 11 and 12, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S11 S12 1964
1	

CHAINS	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
CHAINS	from which
	A juniper, 16 ins. diam., bears N. 7°50' E., 49 lks. dist., mkd. ½S12BT
,	Raise a mound of stone West of the cor.
51.10	Road, bears N. 20° E. and S. 20° W.
81.78	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	<u>S 2 S 1 </u>
	1964
	Raise a mound of stone W. of the cor.
	Land, gently rolling.
	Soil, sandy loam. Timber, dense on S $\frac{1}{2}$ mile, scattered on remainder.
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy.
	of the township.
	S. 82°25' W., bet. secs. 1 and 12.
	Over nearly level land through moderate timber.
40.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	$\frac{1}{4} \frac{S}{S} \frac{1}{12}$
	1964
	Raise a mound of stone N. of the cor.
68.60	Road, bears N. 39° E., and S. 34° W.
80.74	The cor. of secs. 1, 2, 11 and 12.
	Land, nearly level. Soil, sandy loam. Timber, moderate to dense juniper.
	Undergrowth, sagebrush.
	N. 0°57' E., bet. secs. 1 and 2.
	Over rolling land through scattered timber.
6.50	N. rim of ridge, bears irregularly N. 15° E. and S. 80° W.; desc. over broken clay hills.
٠ (

_	<u> </u>	
	CHAINS	
	33.00	Wash, with road along bottom, drains S. 80° W.
i	34.80	Fence, barbed wire, bears N. 40° E. and S. 25° W.
		Asc. over rolling hills, S. drainage and exposure.
	40.89	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		S 2 S 1 1964
1		Raise a mound of stone West of the cor.
	49.50	Rim of mesa, bears E. and W.; thence over nearly level land through heavy timber.
	53.30	Fence, barbed wire, bears S. 29° W. and N. 29° E.
		Desc. over broken N. slope.
	65.50	Fence, bears N. 59°20' W. and S. 59°20' E.
	74.40	Wash, 35 1ks. wide, 2 ft. deep, drains N. 70° W.
	82.36	The cor. of secs. 1, 2, 35 and 36.
		Land, rolling and slightly broken. Soil, sandy and clay. Timber, moderate juniper. Undergrowth, sagebrush.
	,	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township.
		N. 0°08' W., bet. secs. 34 and 35.
		Over rolling E. side of North Mountain.
		Asc. S. slope.
	8.00	Spur, slopes S. 85° E.
	15.10	Spur, slopes S. 50° E.
	16.20	Wash, 10 lks. wide, 7 ft. deep, drains irregularly East.
	17.80	Spur, slopes E.
	23.10	Wash, 25 lks. wide, 2 ft. deep, drains irregularly East.
	25.70	Wash, 20 lks. wide, 1 ft. deep, drains N. 75° E.; thence along E. slope.
	37.79	Point for the ½ sec. cor. of secs. 34 and 35, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		<u>-</u>

CHAINS	T15N R26E
	\$ \$34 \$35
	1964
	Raise a mound of stone West of the cor.
39.30	Draw, drains S. 10° E. from NW.; asc. over steep clay hills putting S.
60.80 66.10	Crest of spur, slopes E. Narrow ridge, bears N. 80° E. and N. 80° W.; thence over steep clay hills draining N.
75.58	The cor. of secs. 26, 27, 34 and 35, monumented by a sandstone, 12x9x4 ins., lying loose on top of the ground, mkd. 1 notch on S. and 2 notches on E. face.
	At the cor. point
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E <u>S27 S26</u> S34 S35 1964
	from which
	U.S.G.S. Triangulation station HARPER bears S. 65°33' W., 40.43 chs. dist., monumented by a bronze tablet mkd. HARPER 1954
	Raise a mound of stone West of the cor.
	Land, rolling and broken E. slope of North Mountain. Soil, clay and rocky. Timber, scattered junipers. Undergrowth, scattered black brush and shadscale.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 84°37' W., bet. secs. 26 and 35.
e	Asc. over broken clay hills.
4.20	Fence, 4 strand barbed wire, bears S. 0°10' W. and N. 0°10' E.
19.00	Spur, slopes S.
40.39	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented by a sandstone, $10x8x8$ ins., dimly mkd. $\frac{1}{4}$ on face with scattered mound of stone North.
	At the cor. point
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	$\frac{1}{4} \frac{\text{S } 26}{\text{S } 35}$
	1964
	Raise a mound of stone North of the cor.

)		Dep. Resurvey, Subdivision, T15N, R26E, Arizona
C	CHAINS	
		S. 84°53' W., beginning new measurement.
18	3.30	Spur, slopes N. 85° E.
39	.64	The cor. of secs. 26, 27, 34 and 35.
		Land, mountainous.
		Soil, clay. Timber, widely scattered juniper.
		Undergrowth, scattered sage.
		N. 0°17' E., bet. secs. 26 and 27.
		Over low rolling clay hills.
2	.20	Draw, drains NE.
5	.90	Top of low clay hill.
30	.20	Wash, 10 1ks. wide, 1 ft. deep, drains irregularly SE.; thence over gently rolling land.
40	.40	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by a sandstone, $12 \times 12 \times 3$ ins., dimly mkd. with $\frac{1}{4}$, lying
		loose upon the ground.
		At the cor. point
		Set the iron post 10 ins. in the ground and in a mound of stone to top, cap mkd.
		T15N R26E
		\$27 \s26
		1964
		N. 0°12' E., beginning new measurement.
		Over gently rolling land.
15	.40	Old road, bears N. 40° E. and S. 40° W.
	.40	
		Asc. over barren clay hills cut by numerous deep gullies.
40	.64	The cor. of secs. 22, 23, 26 and 27, monumented by an old squared cedar stake lying loose upon the ground, dimly mkd. but partially legible.
		At the cor. point
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		S22 S23 S27 S26 1964
		The cor. is located on clay spur sloping S. and set in clay hardpan; no accessories available.
		Land, rolling.
		Soil, sandy and clay. Timber, widely scattered juniper.
		Undergrowth, scattered brush.

BCOK 4703

Dep.	Resurvey,	Subdivision,	T15N,	R26E,	Arizona	29

•	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 29.
CHAINS	
	From the cor. of secs. 23, 24, 25 and 26.
	S. 84°56' W., bet. secs. 23 and 26.
	Over low and broken clay hills, numerous gullies, general SE. drainage.
6.70	Fence, barbed wire, bears S. and N. curving to N. 35° W.
40.81	Point for the ½ sec. cor. of secs. 23 and 26, at proportionate dist.; unable to locate any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E ¹ / ₄ S 23/S 26 1964
	No accessories available.
54.00	Wash, 60 lks. wide, 1 ft. deep, drains S. 10° E.
81.62	The cor. of secs. 22, 23, 26 and 27.
	Land, low clay hills cut by numerous deep gullies. Soil, shallow clay and clay hardpan. No timber; scarce vegetation.
	N. 1°47' E., bet. secs. 22 and 23.
	Asc. over barren clay hills cut by deep gullies.
17.50	Gully, 100 lks. wide, about 35 ft. deep, drains S. 85° West.
27.80	Gully, 300 lks. wide, 35 ft. deep, steep sloping sides, drains SW.
38.00	Spur, slopes S. 20° W.
40.42	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 18 ins. in the ground and in a collar of stone, cap mkd.
	T15N R26 E
	S22 S23 1964
62.50	South rim of mesa, bears irregularly NE. and SW.; thence over gently rolling land through moderate timber.
72.90	Enter clearing, bears N. 65° E. and S. 85° W.
77.90	Road, bears N. 58° E. and S. 58° W.
80.50	Enter heavy timber bearing N. 60° E. and S. 60° W.
	, I

<i>50</i>	Dep. Resurvey, Subdivision, T15N, R26E, Arizona	30
CHAINS		\neg
80.84	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T15N R26E <u>S15 S14</u> <u>S22 S23</u> 1964	
	Raise a mound of stone West of the cor.	
	Land, clay hills on S. 60 chs., gently rolling range on remainder. Soil, clay and sandy loam. Timber, moderate juniper on N. 20 chs. Undergrowth, sagebrush on N. 20 chs.	
	From the cor. of secs. 13, 14, 23 and 24.	
	S. 84°31' W., bet. secs. 14 and 23.	
	Asc. over gently rolling land.	
10.90	Enter dense juniper bearing NE. and SW.	
25.40	Enter clearing bearing NE. and SW.	
40.42	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate dist.; unable to find any evidence of the original corner.	
	Set the iron post 24 ins. in the ground, cap mkd.	ŀ
	T15N R26E 1/4 S 14 S 23 1964	
	from which	
	A juniper, 6 ins. diam., bears S. 25° W., 65 lks. dist., mkd. $\frac{1}{4}$ S23BT	
	Raise a mound of stone N. of the cor.	
	Over nearly level land through moderate timber.	
61.40	Enter clearing, bears NE. and SW.	
64.40	Fence, bears S. 36° E. and N. 36° W.	
73.50	Enter heavy timber, bears S. 80° W. and NE.	
80.84	The cor. of secs. 14, 15, 22 and 23.	
	Land, nearly level. Soil, sandy loam. Timber, heavy to scattered juniper. Undergrowth, sagebrush.	
·		

	200K 4708
	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
CHAINS	N. 2°09' E., bet. secs. 14 and 15.
,	Over nearly level land through heavy timber.
8.20	Asc. over gentle S. slope.
21.80	Low ridge, bears N. 70° E. and S. 70° W.; desc. gradually.
40.43	The ½ sec. cor. of secs. 14 and 15, monumented by an old cedar stake, plainly mkd. ½, lying loose upon the ground; I accept it as best evidence of cor. position.
	At the cor. point
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S 15 S 14 1964
	N. 0°24' W., beginning new measurement.
•	Desc. over barren clay hills, numerous gullies.
24.50	Enter small stand of juniper timber and gently rolling land.
30.00	Wash, 80 lks. wide, 1 ft. deep, drains N. 85° W.
40.79	Point for the cor. of secs. 10, 11, 14 and 15 at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E <u>S10 S11</u> S15 S14 1964
	Raise a mound of stone West of the cor.
	Land, clay hills and gently rolling range. Soil, clay and sand. Timber, dense juniper on S ½, scattered on remainder. Undergrowth, scattered sage.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 84°05' W., bet. secs. 11 and 14.
	Over nearly level land, through moderate timber.
21.30	Road, bears N. 40° W. and S. 40° E. (Approximate dist.)
21.60	Fence, barbed wire, bears N. 53°20' W. and S. 53°20' E. (Approximate dist.)
35.30	Desc. gradual W. slope.
40.40	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14 at proportionate dist.; unable to locate any evidence of the original cor.
	the original cor.

32	Dep. Resurvey, Subdivision, T15N, R26E, Arizona	32.
CHAINS	Set the iron post 24 ins. in the ground, cap mkd.	
	T15N R26E	
	½ S 11 S 14	
	S 14 1964	
	Raise a mound of stone North of the cor.	
54.10	Desc. over slightly broken land, SW. drainage.	
61.50	Wash, 10 1ks. wide, 3 ft. deep, drains SW.	
80.80	The cor. of secs. 10, 11, 14 and 15.	
	Land, nearly level on E. 54.00 chs., rolling on remainder. Soil, sandy loam. Timber, heavy to scattered juniper. Undergrowth, scattered sagebrush.	
	N. 1°03' E. bet. secs. 10 and 11.	
	Asc. over gently rolling hills.	
4.80	Small wash, drains S. 65° W.	
27.90	South rim of low ridge bears irregularly NE. and NW.	
	Enter moderate timber.	ŀ
40.80	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate dist.; unable to find any evidence of the original corner.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T15N R26E	
	S10 S11 1964	
	Raise a mound of stone West of the cor.	
76 . 00	North edge of ridge, bears irregularly NE. and SW.; desc. over broken clay hills.	
81.60	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; unable to locate any evidence of the original cor.	
	Set the iron post 18 ins. in the ground, cap mkd.	
	T15N R26E S 3 S 2	
	\$3 \$2 \$10 \$11 1964	
	No accessories available.	,
	Land, rolling. Soil, sandy and clay. Timber, moderate to scattered junipers. Undergrowth, scattered sage.	
•		ı

BOOK 4703

Den.	Resurvey.	Subdivision,	T15N.	R26E.	Arizona	33
Dep.	Resurvey,	Dubui vi bioni	112119	112029	111 1 50110	20.

	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
CHAINS	
	From the cor. of secs. 1, 2, 11 and 12.
	S. 83°54' W., bet. secs. 2 and 11.
	Over gently rolling land through moderate timber.
4.20	Fence, bears N. 10° E., and S. 10° W. (Dist. as adjusted from random.)
40.40	Point for the ½ sec. cor. of secs. 2 and 11 at proportionate dist.; unable to find any evidence of the original corner.
	Set the iron post 22 ins. in the ground, cap mkd.
-	T15N R26E 1/4 S 2 S 11 1964
	Raise a mound of stone N. of the cor.
50.60	Desc. over broken clay hills.
80.80	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling, slightly broken. Soil, sandy loam and clay. Timber, moderate to scattered junipers. Undergrowth, sagebrush.
	N. 1°28' E., bet. secs. 2 and 3.
	Desc. over rolling clay hills.
3.00	Enger gently rolling range land.
4.90	Wash, 150 1ks. wide, 2 ft. deep, drains S. 85° W.
16.40	Wash, 40 lks. wide, 1 ft. deep, drains N. 80° W.
24.40	Enter broken clay hills.
29.00	Clay ridge, bears N. 75° E. and S. 75° W.
40.80	Point for the ½ sec. cor. of secs. 2 and 3 at proportionate dist., falls on steep N. slope of clay hill where cor. cannot be perpetuated.
41.20	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T15N R26E S 3 \int S 2 WC 1964
46.00	Wash, 50 1ks. wide, 2 ft. deep, drains W.
53.90	Wash, 30 1ks. wide, 2 ft. deep, drains N. 85° W.
	1

Dep.	Resurvey,	Subdivision,	T15N,	R26E,	Arizona
					

<u>ر</u>	<u>/</u>	Jep. Reservey, Bushivision, 115N, R20B, M120Na 54,			
	CHAINS				
	62.90	Wash, 65 lks. wide, 1 ft. deep, drains N. 65° W.			
	76.34	Fence, barbed wire, bears N. 71.20' W. and S. 71°20' E. (As calculated from random.)			
	82.09	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township.			
		Land, rolling and broken. Soil, clay loam and sandy. Timber, scattered juniper. Undergrowth, scattered sage.			
		From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township.			
		N. 0°43' W., bet. secs. 33 and 34.			
		Over rolling clay hills on West slope of North Mountain.			
	2.80	Deep gully, drains W.			
	6.20	Spur, slopes W.			
	9.00	Deep gully, drains W.; continue over spurs and gullies putting W.			
	38.41	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate dist.; unable to find any evidence of the original cor.			
		Set the iron post 20 ins. in the ground, cap mkd.			
		T15N R26E			
		S33 S34 1963			
		The cor. is on SW. slope of clay spur.			
	41.60	Spur, slopes S. 80° W.			
	76.82	The cor. of secs. 27, 28, 33 and 34, monumented by a sandstone, 18x15x8 ins., plainly mkd. with 3 notches on E. and 1 notch on S. face - scattered mound alongside.			
		At the cor. point			
		Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.			
		T15N R26E <u>S28 S27</u> S33 S34 1963			
		Land, broken W. slope of North Mountain. Soil, clay loam. Timber, scattered junipers. Undergrowth, scattered sage and shadscale.			
		From the cor. of secs. 26, 27, 34 and 35.			
		S. 84°45' W., bet. secs. 27 and 34.			

BOOK 4703

	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 3
CHAINS	
	Ascend along broken N. slope of North Mountain.
40.70	Point for the 4 sec. cor. of secs. 27 and 34.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	$\begin{array}{c} \frac{1}{4} \frac{\text{S } 27}{\text{S } 34} \\ \end{array}$
	1964
	The cor. is located on E. slope of clay spur sloping N.
81.40	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling and broken. Soil, clay.
	Timber, widely scattered junipers. Undergrowth, scattered brush and shadscale.
	N. 0°27' E., bet. secs. 27 and 28.
	Over rolling clay hills.
7.90	Spur, slopes NW.
12.50	Spur, slopes W.
16.50	Wash bottom, about 6.00 chs. wide, drains S. 80° W.
24.70	Wash, 20 1ks. wide, 1 ft. deep, drains S. 15° W.
30.60	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.
33.10	Same wash, drains from NE.
37.90	Wash, 40 lks. wide, 1 ft. deep, drains S. 30° W.
40.48	Point for the ½ sec. cor. of secs. 27 and 28, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26 E
	S20 S27 1963
	Raise a mound of stone W. of the cor.
	Over gently rolling land.
63.50	Fence, barbed wire, bears N. 50°50' W., and S. 50°50' E.
67.40	Wash, 20 1ks. wide, 1 ft. deep, drains S. 30° W.
74.10	Wash, 10 1ks. wide, 1 ft. deep, drains S. 25° W.; asc. over S. slope of clay hill.
80.96	Point for the cor. of secs. 21, 22, 27 and 28 at proportionate dist.; unable to find any evidence of the original cor.

CYLATIVE	
CHAINS	Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.
	T15N R26E S21 S22 S28 S27 1964
	Land, rolling, slightly broken. Soil, clay and sandy. Timber, widely scattered juniper. Undergrowth, scattered sagebrush.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 84°45' W., bet. secs. 22 and 27.
	Over broken clay hills.
20.20	Wash, 40 lks. wide, 2 ft. deep, drains S. 65° W.
25.60	Wash, 30 lks. wide, 1 ft. deep, drains S. 60° W.
40.50	Point for the ½ sec. cor. of secs. 22 and 27 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26 E 1/4 S 22 S 27 1964
59.80	Wash, 35 1ks. wide, 3 ft. deep, drains S. 50° W.
81.00	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling and broken clay hills. Soil, clay. No timber; scant undergrowth.
	N. 2° E., bet. secs. 21 and 22.
	Over rolling clay hills.
23.50	S. end of low ridge, bears NE.; thence over gently rolling land.
31.20	Enter scattered juniper trees.
40.51	Point for the ½ sec. cor. of secs. 21 and 22 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E 2 S21 S22 1964
	Raise a mound of stone West of the cor.
1	1

CHAINS	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
64.40	Old road, bears N. 80° E. and S. 80° W.
81.02	Point for the cor. of secs. 15, 16, 21 and 22 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S16 S15 S21 S22 1964
	from which
	A juniper, 6 ins. diam., bears S.11°30' E., 1.05 chs. dist., mkd. S22BT
	A juniper, 12 ins. diam., bears S. 48°15' W., 1.55 chs. dist., mkd. S21BT
	Raise a mound of stone W. of the cor.
	Land, rolling on S. 23.00 chs. nearly level on remainder. Soil, clay and sand.
	Timber, scattered to moderate juniper. Undergrowth, sagebrush.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 84°52' W., bet. secs. 15 and 22.
	Over nearly level land, through moderate to heavy timber.
37.30	Enter clearing, bears NE. and SW.
40.35	Point for the ½ sec. cor. of secs. 15 and 22 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
_	1 S 15 S 22 1964
	from which
	A juniper, 14 ins. diam., bears S. 18° E., 14 lks. dist.; mkd. ${}^{1}\!$
	Raise a mound of stone N. of the cor.
:	Continue over nearly level land through moderate timber.
80.70	The cor. of secs. 15, 16, 21 and 22.
	Land, nearly level to gently rolling. Soil, sandy clay loam. Timber, scattered to dense juniper.

3		Dep. Resurvey, Subdivision, T15N, R26E, Arizona	38.
	CHAINS	N. 0°42' E., bet. secs. 15 and 16.	
		Over nearly level range land, through scattered to moderate timber.	
	10.10	North edge of ridge, bears irregularly NE. and SW.; leave timber, desc. over broken N. slope.	
	16.90	Enter bottom land, bears E. and W.	
	28.40	Wash, 10 lks. wide, l ft. deep, drains N. 85° W.	
	34.50	Wash, 10 lks. wide, 1 ft. deep, drains West.	
	40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16 at proportionate dist.; unable to find any evidence of the original cor.	
		Set the iron post 24 ins. in the ground, cap mkd.	
		T15N R26E	
		S16 S15 1964	
		Raise a mound of stone West of the Cor.	
	60,50	Road, bears N. 68° W. and S. 68° E.	
	63.70	Wash, 60 lks. wide, 4 ft. deep, drains N. 65° W.	
	68.60	Wash, 60 lks. wide, 3 ft. deep, drains S. 85° W.	ŀ
		Asc. over low rolling clay hills.	
	80.96	Point for the cor. of secs. 9, 10, 15 and 16 at proportionate dist.; unable to find any evidence of the original cor.	
		Set the iron post 24 ins. in the ground, cap mkd.	
		T15N R26E S 9 S10 S16 S15 1963	
	•	from which	
		Dike on pond, "White Tank", bears S. 70°53' W., 12.77 chs. dist.	
:		Raise a mound of stone West of the cor.	
		Land, moderately level - rolling. Soil, sandy and clay loam. Timber, scattered junipers. Undergrowth, sagebrush.	
		From the cor. of secs. 10, 11, 14 and 15.	
	; ;	S. 84°46' W., bet. secs. 10 and 15.	
		Over rolling clay hills through scattered timber.	:
	7.20	Crest of clay hill, bears N. and S.	

	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 39.
CHAINS	
34.60	Wash, 25 lks. wide, 4 ft. deep, drains S. 60° W.
40.51	Point for the ½ sec. cor. of secs. 10 and 15 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E 1/4 S10 S15 1964
	Raise a mound of stone North of the cor.
81.02	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling.
	Soil, clay. Timber, scattered junipers. Undergrowth, sagebrush and shadscale.
	N. 1°21' E., bet. secs. 9 and 10.
	Asc. over low rolling clay hills.
15.10	Wash, 50 lks. wide, 2 ft. deep, drains S. 25° W.
35.60	South rim of low ridge, bears irregularly SE. and SW.; thence over gently rolling land.
40.49	Point for the ½ sec. cor. of secs. 9 and 10 at proportionate dist.; unable to find any evidence of the original corner.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S 9 S 10 1964
	Raise a mound of stone West of the cor.
56.30	North rim of ridge, bears irregularly NE. and SW.
	Desc. over broken clay hills.
71.30	Enter gently rolling range land.
80.98	Point for the cor. of secs. 3, 4, 9 and 10 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E <u>S4 S3</u> S9 S10
	1964
	Raise a mound of stone West of the cor.
1	

<u>U</u>	
CHAINS	Land, rolling to nearly level. Soil, sandy and clay loam. Timber, scattered junipers. Undergrowth, scattered sage brush.
	From the cor. of secs. 2, 3, 10 and 11.
	S. 84°15' W., bet. secs. 3 and 10.
	Over rolling and broken clay hills, N. drainage and exposure.
40.36	Point for the ½ sec. cor. of secs. 3 and 10, at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 18 ins. in the ground, cap mkd.
	T15N R26E \[\frac{1}{4} \frac{S}{S} \frac{3}{10} \\ 1964
	No accessories available.
69.70	Wash, 300 lks. wide, 1 ft. deep, drains NW.; thence over nearly level range land.
80.72	The cor. of secs. 3, 4, 9 and 10.
	Land, steep rolling and broken clay hills. Soil, clay and clay hard-pan. No timber; undergrowth, scant shadscale.
	N. 1°57' E., bet. secs. 3 and 4.
	Over gently rolling range land.
8.70	Wash, 35 1ks. wide, 2 ft. deep, drains W.
37.80	Wash, 10 1ks. wide, 1 ft. deep, drains N. 70° W.
40.50	Point for the ½ sec. cor. of secs. 3 and 4, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	S 4 S 3 1963
	Raise a mound of stone West of the cor.
46.80	Wash, 30 1ks. wide, 1 ft. deep, drains West.
77.75	Fence, barbed wire, bears irregularly N. 83° E. and S. 83° W.
81.39	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the township.
	Land, nearly level range land. Soil, sandy clay loam. No timber; undergrowth, scattered sagebrush.
1	

BOOK 4703

,	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 41.
CHAINS	
	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township.
	N. 0°07' E., bet. secs. 32 and 33.
	Over gently rolling range land.
21.10	Wash, 10 lks. wide, 1 ft. deep, drains SW.
32.00	Asc. gentle S. slope.
40.22	Point for the ½ sec. cor. of secs. 32 and 33 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	S32 S33 1963
	Raise a mound of stone West of the cor.
	Asc. gentle S. slope through scattered timber.
48.30	Crest of knoll; desc. over N. slope.
52.50	Leave timber, enter nearly level range land.
80.44	Point for the cor. of secs. 28, 29, 32 and 33 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S29 S28 S32 S33
	. 1963
	Raise a mound of stone West of the cor.
	Land, gently rolling. Soil, sandy. Timber, scattered timber on knoll.
	Undergrowth, sagebrush.
	From the cor. of secs. 27, 28, 33 and 34.
	S. 85°51' W., bet. secs. 28 and 33.
	Over gently rolling land.
25.20	Road, bears N. 20° E. and S. 20° W.
31.80	Road, bears N. 40° W. and S. 40° E.; wash, 40 lks. wide, 1 ft. deep, drains S. 25° W.
35.20	Wash, 200 1ks. wide, 3 ft. deep, drains S. 50° W.
39.82	Point for the ½ sec. cor. of secs. 28 and 33 at proportionate dist.; unable to find any evidence of the original cor.

Dep.	Resurvey,	Subdivision,	T15N,	R26E,	Arizona
------	-----------	--------------	-------	-------	---------

42.

	bep. Resulvey, Subdivision, 115N, R202, M120Ra 42
CHAINS	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	$\begin{array}{c} \frac{1}{4} \frac{S}{S} \frac{28}{33} \end{array}$
	1964
	Raise a mound of stone North of the cor.
68.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.
79.64	The cor. of secs. 28, 29, 32 and 33.
	Land, gently rolling. Soil, sandy clay loam. Timber, widely scattered junipers. Undergrowth, sagebrush.
	N. 0°17' W., bet. secs. 28 and 29.
	Asc. over gently rolling range land.
.80	Wash, 10 1ks. wide, 1 ft. deep, drains S. 35° W.
40.22	Point for the ½ sec. cor. of secs. 28 and 29 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S29 S28 1963
	from which
	A dam, bet. two stock ponds, bears N. 80°39' E., 4.77 chs. dist.
42.30	Road, bears SE. and NW.
44.20	Asc. over steep broken SE. slope through moderate timber.
64.10	Rim of bluff, bears SW. and N. 65° E.
65.50	Track road, bears N. 60° E. and S. 60° W.; thence over rolling land.
71.70	Spur, slopes W.; desc. along rolling W. slope.
80.44	Point for the cor. of secs. 20, 21, 28 and 29 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E <u>S20 S21</u> <u>S29 S28</u> 1963
	Raise a mound of stone West of the cor.

CHAINS	1
	Land, rolling. Soil, sandy, clay loam. Timber, scattered juniper. Undergrowth, brush.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 85°29' W., bet. secs. 21 and 28.
	Over broken clay hills.
4.90	Wash, 10 1ks. wide, 1 ft. deep, drains S. 40° W.
40.35	Point for the ½ sec. cor. of secs. 21 and 28 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 20 ins. in the ground and in a collar of stone, cap mkd.
	T15N R26E S 21
	$\frac{1}{4} \frac{\frac{S}{S} \frac{21}{28}}{1964}$
45.00	Ridge, bears N. 70° E. and S. 70° W.; desc. gradually through scattered juniper trees.
80.70	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling and slightly broken. Soil, clay hard-pan and sandy loam. Timber, scattered junipers on W. 30 chs. Undergrowth, sage brush.
	N. 1°57' E., bet. secs. 20 and 21.
	Over gently rolling land through scattered timber.
1.10	Wash, 70 1ks. wide, 2 ft. deep, drains SW. circling to W.; asc. gentle S. slope.
20.60	Spur, slopes W.; thence over gently rolling land.
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	\$20 \$21 1963
	Raise a mound of stone West of the cor.
48.30	Wash, 15 1ks. wide, 3 ft. deep, drains W.
57.80	Wash, 25 1ks. wide, 3 ft. deep, drains NW.
65.70	Wash, 20 1ks. wide, 2 ft. deep, drains W.

44	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
CHAINS	
79.70	Wash, 80 lks. wide, 4 ft. deep, drains S. 80° W.
80.48	Point for the cor. of secs. 16, 17, 20 and 21 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E S17 S16 S20 S21 1964
	Land, gently rolling. Soil, sandy and clay loam. Timber, scattered junipers. Undergrowth, sagebrush.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 85°04' W., bet. secs. 16 and 21.
	Over rolling land through scattered timber.
40.43	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E ¹ / ₄ S 16 S 21 1964
	Raise a mound of stone North of the cor.
57.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.; thence over gently rolling land, several small washes, SW. drainage.
80.86	The cor. of secs. 16, 17, 20 and 21.
	Land, gently rolling. Soil, sandy clay loam. Timber, scattered junipers. Undergrowth, sagebrush.
	N. 0°23' E., bet. secs. 16 and 17.
	Asc. over gentle S. slope.
28.10	Desc. over steep rolling clay hills.
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
1	

	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 45.
CHAINS	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 45.
	Raise a mound of stone W. of the cor.
43.00	Leave clay hills; desc. over gentle N. slope through scattered timber.
70.90	Wash, 140 1ks. wide, 4 ft. deep, drains West.
	Asc. gentle S. slope.
80.44	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E <u>S 8 S 9</u> S17 S16 1964
	Raise a mound of stone West of the cor.
	Land, rolling. Soil, sandy and clay loam. Timber, scattered juniper. Undergrowth, sagebrush.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 84°44' W., bet. secs. 9 and 16.
	Over nearly level range land.
21.00	Road, bears N. 56° W. and S. 56° E.
40.62	Point for the ½ sec. cor. of secs. 9 and 16 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	$\begin{array}{c} \frac{1}{4} \frac{S}{S} \frac{9}{16} \\ \end{array}$
	1964
	Raise a mound of stone North of the cor.
	Continue over rolling land, numerous small washes and gullies draining south and SW.
81.24	The cor. of secs. 8, 9, 16 and 17.
	Land, gently rolling. Soil, sandy loam and clay. Timber, widely scattered junipers; undergrowth, sagebrush.
	N. 1°32' E., bet. secs. 8 and 9.
	Asc. over gentle S. slope through widely scattered junipers.
19.90	Top of asc., bears E. and W.; thence over rolling land.

16	>	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 46.
	CHAINS	
1	29.70	Wash, 100 lks. wide, 4 ft. deep, drains S. 55° W.
	40.23	Point for the 4 sec. cor. of secs. 8 and 9, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 22 ins. in the ground, cap mkd.
		T15N R26E S8 S 9 1964
		Raise a mound of stone West of the cor.
	56.90	Road, bears S. 83° E. and N. 83° W.
	59.80	Desc. over N. slope.
	67.70	Enter nearly level range land.
	78.00	Old road, bears N. 85° W. and S. 85° E.
	80.46	Point for the cor. of secs. 4, 5, 8 and 9 at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 22 ins. in the ground, cap mkd.
		T15N R26E S 5 S 4 S 8 S 9 1964
		from which
		A dike on a pond bears N. 51°44' W., 36.52 chs. dist.
		Raise a mound of stone West of the cor.
	,	Land, rolling to nearly level. Soil, sandy loam. Timber, widely scattered junipers. Undergrowth, sagebrush.
		From the cor. of secs. 3, 4, 9 and 10.
		S. 84°20' W., bet. secs. 4 and 9.
		Over nearly level land.
	40.51	Point for the ½ sec. cor. of secs. 4 and 9 at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 22 ins. in the ground, cap mkd.
		T15N R26E 1/4 S 4 S 9 1964

Raise a mound of stone North of the cor.

CHAINS	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
	Continue over gently rolling range land, NW. drainage and exposure.
81.02	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, scattered brush.
	N. 2°38' E., bet. secs. 4 and 5.
	Over nearly level range land.
20.60	Wash, 10 lks. wide, 1 ft. deep, drains N. 85° W.
40.26	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	S 5 \sqrt{S 4} 1964
	Raise a mound of stone West of the cor.
	Continue over nearly level range land.
53.50	Wash, 100 lks. wide, 4 ft. deep, drains S. 75° W. (Surprise Creek)
63.30	Wash, 250 lks. wide, 4 ft. deep, drains N. 80° W.
77.05	Fence, barbed wire, bears N. 83°50' E. and S. 83°50' W.
80.61	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the township.
	Land, moderately level. Soil, sandy clay loam. No timber; undergrowth, sagebrush.
	From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township.
	N. 1°54' W., bet. secs. 31 and 32.
	Over gently rolling land.
6.60	Fence, barbed wire, bears N. 55° W. and S. 55° E.
10.40	Spur, slopes S. 80° W.; thence over low rolling hills, SW. drainage.
41.45	The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented by an old squared cedar stake, markings not legible. I accept this as the best remaining evidence of the original cor.
	At the cor. point
1	

_	0	Dep. Resulvey, Subdivision, 1131, 1151,
	CHAINS	
•		T15N R26E
		S31 S32
		1963
	:	Raise a mound of stone West of the cor.
		Cor. is located on gentle SE. slope.
		N. 1°30' E., beginning new measurement.
		Over gently rolling hills through moderate undergrowth.
	39.95	Point for the cor. of secs. 29, 30, 31 and 32 at proportionate dist.; unable to find any evidence of the original cor.
	·	Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		S30 S29 S31 S32
		1963
		Raise a mound of stone West of the cor.
		Land, rolling. Soil, sandy clay loam.
		Timber, scattered juniper.
		Undergrowth, moderate sagebrush.
		From the cor. of secs. 28, 29, 32 and 33.
		S. 85°17' W., bet. secs. 29 and 32.
		Over nearly level land.
	2.10	Wash, 20 lks. wide, 3 ft. deep, drains S. 10° W.
	31.80	Road, bears North and South.
	32.60	Wash, 30 lks. wide, 4 ft. banks, drains S.
	39.89	Point for the ½ sec. cor. of secs. 29 and 32 at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E
		½ S 29 S 32
		1964
		Raise a mound of stone N. of the cor.
	54.20	Low ridge, bears N. and S.
	76.60	Wash, 30 1ks. wide, 5 ft. banks, drains S.
	79.78	The cor. of secs. 29, 30, 31 and 32.
		Land, gently rolling.
		Soil, sandy loam. Timber, widely scattered junipers.
		Undergrowth, sagebrush.

	- CON 4703
CHAINS	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 4
CHAINS	S. 83°01' W., bet. secs. 30 and 31.
	Over gently rolling range land.
15.20	Wash, 10 lks. wide, 4 ft. banks, drains S. 10° E.
26.10	Wash, 15 lks. wide, 3 ft. deep, drains S.
39.92	Point for the ½ sec. cor. of secs. 30 and 31 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E 1/4 S 30 S 31 1964
	Raise a mound of stone North of the cor.
49.50	Low ridge, bears N. 10° E. and S. 10° W.
115.26	The cor. of secs. 25, 30, 31 and 36 on the west boundary of the township.
	Land, gently rolling. Soil, sandy and clay hardpan. Timber, widely scattered junipers. Undergrowth, moderate sage.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°45' W., bet. secs. 29 and 30.
	Over gently rolling hills; asc. gentle S. slope.
15.20	Enter moderate stand of timber.
24.70	Spur, slopes S. 80° W.; thence, over gently rolling land, W. drainage.
39.94	Pointfor the $\frac{1}{4}$ sec. cor. of secs. 29 and 30 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	\$30 \$29 1963
	Raise a mound of stone West of the cor.
46.10	Wash, 15 lks. wide, 2 ft. deep, drains West.
50.50	Wash, 40 lks. wide, 4 ft. banks, drains S. 75° W.
59.70	Crest of low ridge, bears E. and W.; desc. over gentle N. slope.
79.88	Point for the cor. of secs. 19, 20, 29 and 30 at proportionate dist.; unable to find any evidence of the original corner.

portionate dist.; unable to find any evidence of the

original cor.

		200K 4703
Dep. Resurvey, Subdivision, T15N, R26E, Arizona 51		
	CHAINS	
		Set the iron post 24 ins. in the ground, cap mkd.
	·	T15N R26E \[\frac{1}{4} \frac{\text{S } 19}{\text{S } 30} \\ 1964
		Raise a mound of stone N. of the cor.
	44.60	Spur, slopes N. 30° W.
	98.10	Wash, 40 lks. wide, 5 ft. deep, drains S.
	113.81	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township.
		Land, gently rolling. Soil, sandy, clay and clay hardpan. Timber, widely scattered juniper. Undergrowth, scattered sage.
		From the cor. of secs. 19, 20, 29 and 30.
		N. 1°43' E., bet. secs. 19 and 20.
		Over gently rolling hills.
	3.40	Wash, 150 lks. wide, 4 ft. deep, drains N. 75° W.
	5.30	Wash, 20 1ks. wide, 3 ft. deep, drains W.
	13.00	Ridge, bears E. and W.; desc. N. slope.
	24.40	Wash, 20 1ks. wide, 3 ft. deep, drains W.
	39.96	Point for the ½ sec. cor. of secs. 19 and 20, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26 E
		S 19 S 20 1963
		Raise a mound of stone West of the cor.
	49.20	Wash, 40 lks. wide, 4 ft. banks, drains irregularly West.
	79.92	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; unable to find any evidence of the original cor.
		Set the iron post 24 ins. in the ground, cap mkd.
		T15N R26E <u>S18 S17</u> S19 S20 1963
		Raise a mound of stone West of the cor.
t		

52.

CHAINS	
	Land, nearly level. Soil, clay.
	Timber, scattered junipers. Undergrowth, scattered brush and weeds.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 84°32' W., bet. secs. 17 and 20.
	Over gently rolling land.
4.10	Wash, 25 lks. wide, 4 ft. deep, drains S. 20° W.
15.50	Low ridge, bears NE. and SW.; desc. over gentle W. slope.
40.37	Point for the ½ sec. cor. of secs. 17 and 20 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	$ \begin{array}{c} \frac{1}{4} & \frac{S}{S} & \frac{17}{20} \\ 1964 \end{array} $
	Raise a mound of stone N. of the cor.
41.10	Road, bears N. 3° W. and S. 3° E.
54.80	Low ridge, bears NW. and SE.
80.74	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling. Soil, sandy and clay loam. No timber; undergrowth, sagebrush.
	S. 83°50' W., bet secs. 18 and 19.
	Over nearly level land.
31.20	Low rise, bears N. and S.
40.34	Point for the ½ sec. cor. of secs. 18 and 19 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E 1/4 S 18 1/4 S 19 1964
	Raise a mound of stone North of the cor.
44.10	Wash, 60 lks. wide, 4 ft. deep, drains S. 25° W.
58.00	Wash, 100 lks. wide, 4 ft. deep, drains S. 80° W.
115.83	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township.

BCOK 4703

	DCOK 4100
_	Dep. Resurvey, Subdivision, T15N, R26E, Arizona
CHAINS	Land, nearly level. Soil, clay loam. No timber; undergrowth, scattered sage.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°12' E., bet. secs. 17 and 18.
	Over nearly level range land.
39.94	Point for the ½ sec. cor. of secs. 17 and 18 at proportionate dist.; find no remaining evidence of original corner.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E
	S18 S17 1964
	Raise a mound of stone West of cor.
60.10	Dike on small reservoir.
73.30	Crest of low ridge, bears N. 75° E. and S. 75° W.; desc. over gentle N. slope.
77.10	Road, bears SE. and NW.
79.88	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T15N R26E S 7 S 8 S 18 S 17
	1963
	Raise a mound of stone West of the cor.
	The cor. is located on S. edge of reservoir.
	Land, nearly level.
	Soil, clay and sand. No timber; undergrowth, scattered sage.
	From the cor. of secs. 8, 9, 16 and 17.
	S. 84°13' W., bet. secs. 8 and 17.
	Over nearly level land.
21.20	Wash, 200 lks. wide, 4 ft. deep, drains irregularly S. 84° W.; thence cross and recross wash.
40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N_R26E
	½ <u>S 8</u> S 17
	1964
	Raise a mound of stone North of cor.
	•

	BOOK 4703
	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 55.
CHAINS	
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	<u>s 6 [†]s 5</u>
	S7 S8 WC
	1963
	Raise a mound of stone West of the post.
79.92	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., falls in wash (Surprise Creek) 200 lks. wide, 2 ft. deep, draining South for 2.00 chs. thence West; unable to find any evidence of the original cor.
	Land, nearly level.
	Soil, sandy clay loam. No timber; undergrowth, scattered brush.
	and Tamber, and Table, Scattered Drush,
	From the cor. of secs. 4, 5, 8 and 9.
	S. 83°46' W., bet. secs. 5 and 8.
	Over gently rolling range land.
40.26	Point for the ½ sec. cor. of secs. 5 and 8, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	1 S 5 S 8 1964
	Raise a mound of stone North of the cor.
48.80	Road, bears N. 29° E. and S. 29° W.
80.52	The cor. point for secs. 5, 6, 7 and 8.
	Land, nearly level.
	Soil, sandy clay loam. No timber; undergrowth, scattered brush.
	S. 84°03' W., bet. secs. 6 and 7.
	Along N. side of wash draining W.
11.00	Wash, drains N. 20° W.; thence over gently rolling land.
40.20	Point for the ½ sec. cor. of secs. 6 and 7, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	$\frac{1}{4} \frac{S 6}{S 7}$
	1964
	· ·

56	Dep. Resurvey, Subdivision, T15N, R26E, Arizona 56.
CHAINS	Raise a mound of stone North of the cor.
68.30	Recross same wash as one at 11.00, drains S. 30° W.
115.19	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township.
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, scattered sagebrush.
	From the point for the cor. of secs. 5, 6, 7 and 8.
	N. 2°51' E., bet. secs. 5 and 6.
	Along Surprise Creek, draining from N.
17.00	Creek drains from NE.; thence over rolling land.
39.99	Point for the ½ sec. cor. of secs. 5 and 6, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	T15N R26E
	S 6 S 5 1963
	Raise a mound of stone West of the cor.
76.90	Fence, barbed wire, bears N. 83°40' E. and S. 83°40' W.
80.52	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township.
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, scattered to moderate brush.
	General Description
	The land in Township 15 North, Range 26 East, varies from nearly level range land to rolling clay hills cut by deep gullies to steep and broken North Mountain. The soil is mostly clay loam and clay hardpan, with sand on the mesas and sandy clay on the nearly level range land.
	Moderate junipers are found in the northeast corner of the township, extending southwesterly along the higher elevations. The grazing of livestock is the primary interest as there is good grass throughout the township. Windmills and reservoirs afford a continual water supply.
	Only a small percentage of the original corners were found during this survey (usually where the terrain was rough), due partly to the time elapsed since the original survey and, according to some local sources, corners were purposely removed and destroyed by some of the early settlers. All evidence such as bearing trees and buildings given in the original survey notes seems to have been thoroughly removed.

Form 4-680 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Party Chief
Crew Chief and Cornerman
Transit Man
Note Keeper
Front Chainman
F1agman
Crew Chief and Transitman
Note Keeper
Front Chainman
F1 agman
Cornerman

CERTIFICATE OF SURVEY

Boyd S. Owens Paul G. Bauer We Wallace R. Ott X,

, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 13 day of March , 1963, khave dependently resurveyed the boundaries and subdivisional lines of Township 15 North, Range 26 East

Meridian, in the State of Arizona , which Gila and Salt River of the are represented in the foregoing field notes as having been executed by max and under may direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 3, 1964 (Date) April 3, 1964 April 3, 1964

CERTIFICATE OF APPROVAL Bureau of Land Management

The foregoing field notes of the dependent resurvey of the boundaries and subdivisional lines of Township 15 North, Range 26 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens, Paul G. Bauer, and Wallace R. Ott,

having been critically examined and found correct, are hereby approved. Washington, D.C.

AUG 31 1964 (Date)

(Chief, Division of Engineer

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field no	otes of the above-described surveys in
	, is a true copy of the original field notes
	, is a true copy of the original field notes

(Date)	(Chief, Division of Engineering)