F<sub>orm</sub> 4-679 (January 1963)

#### BOOK 4720 UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## FIELD NOTES

	<del></del>	REMONUMEN	TED			
	CADA	STRAL SURVE	Y CORNER	S		
	Township	15 North,	Range 8	East,		
			······································			
-	<u>-</u>			***		· · · · · · · · · · · · · · · · · · ·
	·					
					·	
	***************************************			****		
Of the	Gila	a and Salt F	River		Ме	ridian.
in the State of						
						•
		EXECUT	ED BY			
	Boyd S.	Owens, Cad	lastral S	Surveyor		
		April 23				
Jnder special instructions						
ncluded under Group Numb					1964	······································
and assignment instruction	s dated	May 15	, 1	19		
		34				
Sur	vev commence	May 1	Lβ	19 <sup>64</sup>		

\_\_\_\_\_, 19 \_\_\_\_

June 26

Survey completed \_\_\_\_\_

## BOOK 4720

## INDEX DIAGRAM

Townsh	ip 15 Nor	th	, Range8	East	<del></del> ,
6		4	8	2	1
<b>7</b>	2 2	9	10	11	12
18	2 2 2 2 2	16	15	14	18
19	20	21	22	23	24
30	29	28	27	26	25
31	82	38	84	85	36

#### CHAINS

The north and east boundaries were surveyed in 1881 by T. F. White, Girand and Latimer resurveyed the north boundary and a portion of the east boundary and surveyed the Auxiliary Base Line west, a portion of the west boundary and a portion of the subdivisional lines in 1902. The south boundary, a portion of the west boundary and remaining subdivisional lines were surveyed by F. Rodolf in 1911.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The Assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 15 North, Range 8 East, Arizona

The cor. of secs. 5, 6, 31 and 32, Tps. 15 and 16 N., R. 8 E., is monumented by a malpais stone,  $20 \times 12 \times 4$  ins., firmly set, mkd. with 5 notches on E. and 1 notch on W., from which, the remaining original bearing trees

A ponderosa pine, 24 ins. diam., bears N. 59° E., 172 lks. dist., mkd. with an overgrown blaze. Fence is stapled to the tree on the side facing the cor. Unable to remark.

A ponderosa pine stump, bears S. 66° E., 164 lks. dist. No mks. visible.

A ponderosa pine, 28 ins. diam., bears S. 23° W., 88 lks. dist., mkd. T15N R8E S6 BT. The blaze has recently been opened to reveal the scribe mks.

A ponderosa stump, bears N. 31° W., 210 1ks. dist. No mks. visible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T16N R8E S31 S32 S6 S5 T15N 1964

from which

A ponderosa pine, 10 ins. diam., bears S.  $80^{\circ}45'$  E. 84 1ks. dist., mkd. T15N R8E S5 BT.

A ponderosa pine, 10 ins. diam., bears N. 34° W., 41 lks. dist., mkd. T16N R8E S31 BT.

## Remonumentation

Township 15 North, Range 8 East, Gila and Salt River Meridian, Arizona

CHAINS

Bury the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The 1/2 sec. cor. of secs. 17 and 18, is monumented by a malpais stone, 20 x 14 x 12 ins., firmly set, mkd. } on W., from which, the original bearing trees

A juniper, 20 ins. diam., bears S. 42° E., 329 lks. dist., mkd. ½ S17 BT. (Note: record calls for S. 42° E., 56 lks.)

A juniper, 28 ins. diam., bears N. 64° W., 291 lks. dist., mkd. ½ S18 BT. (Note: record calls for N. 64° W., 78 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

--- T15N R8E 支 S18 S17

Bury the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The cor. is located 4 lks. N. of old E-W fence line and about 5 chs. south of a tank.

The cor. of secs. 7, 8, 17 and 18, is monumented by a malpais stone,  $18 \times 18 \times 12$  ins., firmly set, mkd. with 4 notches on the  $\mathbf{S}$ . and 5 notches on  $\mathbf{E}$ ., with a mound of stones W., from which, the original bearing tree

A juniper, 16 ins. diam., bears S. 21° W., 182 1ks. dist., mkd. T15N R8E S18 BT.

At the cor. point.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

> T15N R8E S7 | S8 S18 S17 1964

Raise a mound of stones W. of the iron post and deposit the original cor. stone in mound.

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, is monumented by a malpais stone, 20 x 12 x 4 ins., firmly set, mkd.  $\frac{1}{4}$  on N., with a scattered mound of stones N., from which, the original bearing tree

A juniper, 36 ins. diam., bears N. 21° E., 162 lks. dist., mkd. with overgrown blaze. Remarked T15N R8E & S8 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

#### Remonumentation

Township 15 North, Range 8 East, Gila and Salt River Meridian, Arizona

3.

CHAINS

T15N R8E

½ <u>S8</u> S17

1964

Bury the original cor. stone alongside the iron post.

Rebuild the mound of stones N. of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, is monumented by a malpais stone, 18 x 14 x 8 ins., firmly set, mkd.  $\frac{1}{4}$  on N., from which, the original bearing trees

A juniper, 36 ins. diam., bears N. 13°45' E., 139 lks. dist., mkd. by overgrown blaze. I remarked T15N R8E ½ S7 BT.

A juniper, 22 ins. diam., bears S. 7° W., 302 1ks. dist., mkd. 1/2 S18 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T15N R8E

₹ <del>S7</del> S18 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stones N. of the iron post.

### **BOOK** 4720

Form 4-680 (June 1963)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD ASSISTANTS

NAMES	CAPACITY
Joe M. Sisneros	Forest Service Cadastral Surveyor
Ben D. Mahaffey	Forest Service District Forester
	•

## BOOK 4720

#### CERTIFICATE OF SURVEY

I, Boyd S. Owens	, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the	23 day of April , 19 64,
I have remonumented cadastral survey corners	s in Township 15 North, Range
8 East,	
of the Gila and Salt River Meridian, in the	State of Arizona , which
are represented in the foregoing field notes as having been	en executed by me and under my direction;
and that said survey has been made in strict conformity	with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of	the United States, and in specific manner
described in the foregoing field notes.	
Relamana 2/ 1065	3 1 0 0
February 24, 1965 (Date)	Boyd & Owens ((Cadastral Surveyor)
	-
(Date)	(Cadastral Surveyor)
CERTIFICATE OF AP	PROVAL
SUBMITTED FOR APPROVAL	
DateFEB 2 5 1965	Bureau of Land Management, Washington, D. C.
The foregoing field notes of the remonumented cad	dastral survey corners in
Township 15 North, Range 8 East, of the 0	Gila and Salt River Meridian,
Arizona,	,
·	
executed by Boyd S. Owens, Cadastral Surve	eyor,
having been critically examined and found correct, are h	nereby approved.
JUL 6 1965	CEK. +
(Date)	(Chief, Division of Engineering)
CERTIFICATE OF TRA	ANSCRIPT
I CERTIFY That the foregoing transcript of the field no	tes of the above-described surveys in
	, is a true copy of the original field notes.
(Date)	(Chief, Division of Engineering)