

BOOK 4725
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 14 North, Range 5 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 23, 19 64, which provided for the surveys
included under Group Number 415, approved April 23, 1964,
and assignment instructions dated May 15, 19 64.

Survey commenced May 18, 19 64

Survey completed June 26, 19 64

1A

BOOK 4725 INDEX DIAGRAM

Township 14 North, Range 5 East,

	6	5	4	3	2	1
				3		
	7	8	9	10	11	12
3						
	18	17	16	15	14	13
2						
	19	20	21	22	23	24
2						
	30	29	28	27	26	25
	4					
	31	32	3 33	34	35	36
1						
			1			

CHAINS

Part of the S. bdy. was surveyed in 1873 by C. B. Foster, who also surveyed a portion of the W. bdy., surveyed the N. bdy. and part of the subdivisional lines in 1877. The remainder of the W. bdy. and a portion of the S. bdy. and subdivisional lines were surveyed by D. Drummond in 1892.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service, remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

 Remonumentation, Township 14 North, Range 5 East, Arizona

The cor. of Tps. 13 and 14 N., Rs. 4 and 5 E., is monumented by a granite stone, 26 x 14 x 6 ins., firmly set, mkd. with 6 notches on each edge, with a mound of stones alongside.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T14N
R4E R5E
S36 S31
S 1 S 6
T13N
1964

from which

A fence cor. bears N., 7 lks. dist., fences bearing N. and W.

An "X" chiseled on E. end of cattle guard (cement), bears S. 76¼° W., 24½ lks. dist.

Bury the original cor. stone alongside the iron post.

Build a mound of stones S. of the iron post.

The cor. of secs. 4, 5, 32 and 33, Tps. 13 and 14 N., R. 5 E., is monumented by a limestone, 22 x 16 x 8 ins., firmly set, mkd. with 2 notches on W. edge, with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

BOOK 4725

Remonumentation, Township 14 North, Range 5 East, Arizona

2

2.

CHAINS

T14N R5E
 S32|S33
 S 5|S 4
 T13N
 1964

Deposit the original cor. stone in a mound of stones W. of the iron post.

The cor. is located at a fence cor., from which fences bear S. and W.

The cor. of secs. 25, 30, 31 and 36, T. 14 N., Rs. 4 and 5 E., is monumented by a stone, 24 x 16 x 8 ins., firmly set in a small mound of stones, mkd. with 1 notch on S. and 5 notches on N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T14N
 R4E R5E
 S25|S30
 S36|S31
 1964

Bury the original cor. stone alongside the iron post.

Raise a small mound of stones W. of the iron post.

The ¼ sec. cor. of secs. 19 and 24, T. 14 N., Rs. 4 and 5 E., is monumented by a malpais stone, 24 x 12 x 10 ins., firmly set, mkd. with ¼ on S. face, with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T14N
 R4E R5E
 ¼
 S24|S19
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the mound of stones W. of the iron post.

The cor. is located on old fence line, fences bearing W. and E., 11½ lks. to end.

The cor. of secs. 13, 18, 19 and 24, T. 14 N., Rs. 4 and 5 E., is monumented by a malpais stone, 16 x 14 x 12 ins., firmly set, mkd. with 3 notches on the N. and S. edges, with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

CHAINS

T14N
R4E R5E
S13 | S18
S24 | S19
1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

An 8 in. square wooden stake, set 5 ft. above the ground, bears N., 4 lks. dist.

The cor. of secs. 7, 12, 13 and 18, T. 14 N., Rs. 4 and 5 E., is monumented by a limestone, 18 x 14 x 8 ins., firmly set, mkd. with 2 notches on N. and 4 notches on S., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T14N
R4E R5E
S12 | S 7
S13 | S18
1964

Bury the original cor. stone alongside the iron post.

Rebuild the mound of stones W. of the iron post.

The cor. of secs. 3, 4, 9 and 10, is monumented by a malpais stone, 18 x 12 x 6 ins., firmly set, mkd. with 3 notches on E. and 5 notches on S., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, mound with stones to top, brass cap mkd.

T14N R5E
S 4 | S 3
S 9 | S10
1964

Deposit the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

A N-S fence line bears E., 48 lks. dist.

The ¼ sec. cor. of secs. 32 and 33, is monumented by a malpais stone, 18 x 12 x 4 ins., firmly set, mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound with stones to top, brass cap mkd.

BOOK 4725

Remonumentation, Township 14 North, Range 5 East, Arizona

4

4.

CHAINS

T14N R5E

$\frac{1}{4}$
S32 | S33
1964

Deposit the original cor. stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, is monumented by a malpais stone, 18 x 12 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stones, brass cap mkd.

T14N R5E

$\frac{1}{4}$ $\frac{S30}{S31}$
1964

Bury the original cor. stone alongside the iron post.

A N-S fence bears W., $3\frac{1}{2}$ lks. dist.

BOOK 4725
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Joe M. Sisneros	Forest Service Cadastral Surveyor
Ben D. Mahaffey	Forest Service District Forester

BOOK 4725
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 23 day of April, 19 64,
I have remonumented cadastral survey corners in Township 14 North,
Range 5 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 24, 1965
(Date)

Boyd S. Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 14 North, Range 5 East, of the Gila and Salt River Meridian,
Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JUL 6 1965
(Date)

[Signature]
(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~_____~~, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)