

Form 4-679  
(January 1963)

BOOK 4726  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 14 North, Range 4 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 23, 19 64, which provided for the surveys  
included under Group Number 415, approved April 23, 1964,  
and assignment instructions dated May 15, 19 64.

Survey commenced May 18, 19 64

Survey completed June 26, 19 64

10A

# BOOK 4726 INDEX DIAGRAM

Township 14 North, Range 4 East,  
3 3 2 2 2 1 1

6	5	4 5	3	2	1
7	8	9	10	11	12
18	17	16	15	14 4	13
19	20	21	22	23 4	4 24 3
30	29	28	27	26	25 3
31	32	33	34	35	36

CHAINS

The north boundary, a portion of the east and west boundaries and part of the subdivisional lines were surveyed by C. B. Foster in 1877. The subdivisional lines within the abandoned Camp Verde Military Reservation were surveyed in 1893 by D. Drummond.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 14 North, Range 4 East, Arizona

The cor. of secs. 1, 2, 35 and 36, Tps. 14 and 15 N., R. 4 E., is monumented by a limestone, 20 x 10 x 5 ins., firmly set, mkd. with 1 notch on E. and 5 notches on W., with a scattered mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound with stones to top, brass cap mkd.

T15N R4E	
S35	S36
S 2	S 1
T14N	
1964	

Deposit the original cor. stone alongside the iron post.

The cor. is located on a S. slope, approximately 1.00 ch. N. of large wash, draining W.

The cor. of secs. 2, 3, 34 and 35, Tps. 14 and 15 N., R. 4 E., is monumented by a limestone, 24 x 16 x 8 ins., firmly set, mkd. with 2 notches on E. and 4 notches on W., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R4E	
S34	S35
S 3	S 2
T14N	
1964	

Bury the original cor. stone alongside the iron post.

Rebuild the mound of stones W. of the iron post.

BOOK 4726

Remonumentation, Township 14 North, Range 4 East, Arizona

2

2.

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, Tps. 14 and 15 N., R. 4 E., is monumented by a limestone, 14 x 10 x 8 ins., firmly set, mkd.  $\frac{1}{4}$  on E. face, with a mound of stones N. Pits visible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R4E

$\frac{1}{4}$   $\frac{S34}{S3}$

1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stones N. of the iron post.

The cor. of secs. 3, 4, 33 and 34, Tps. 14 and 15 N., R. 4 E., is monumented by a limestone, 24 x 12 x 10 ins., firmly set, mkd. with 3 notches on E. and 3 notches on W., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R4E

$\frac{S33}{S4} | \frac{S34}{S3}$

T14N

1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

The cor. of secs. 4, 5, 32 and 33, Tps. 14 and 15 N., R. 4 E., is monumented by a limestone, 16 x 14 x 3 ins., firmly set, mkd. with 4 notches on the E. and 2 notches on the W., with a mound of stones N., from which the remains of the original bearing tree

A juniper stump, 5 ft. high, 16 ins. diam., bears S.  $89^\circ$  E., 91 lks. dist., mkd. T14N R4E S4 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R4E

$\frac{S32}{S5} | \frac{S33}{S4}$

T14N

1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, Tps. 14 and 15 N., R. 4 E., is monumented by a granite stone, 10 x 8 x 6 ins., firmly set, mkd.  $\frac{1}{4}$  on the N. with a mound of stones N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T15N R4E  
 $\frac{1}{4}$   $\frac{S32}{S5}$   
 T14N  
 1964

Bury the original cor. stones alongside the iron post.

Rebuild the original mound of stones N. of the iron post.

The cor. of secs. 5, 6, 31 and 32, Tps. 14 and 15 N., R. 4 E., is monumented by a granite stone, 16 x 14 x 10 ins., firmly set, mkd. with 5 notches on the E. and 1 notch on the W., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, brass cap mkd.

T15N R4E  
 $\frac{S31}{S6} | \frac{S32}{S5}$   
 T14N  
 1964

Deposit the original cor. stone in the mound of stones W. of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, is monumented by a malpais stone, 20 x 14 x 10 ins., firmly set in a mound of stones, mkd.  $\frac{1}{4}$  on W. face.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T14N R4E  
 $\frac{1}{4}$   $\frac{S25}{S36}$   
 1964

Bury the original cor. stones alongside the iron post.

Raise a mound of stones N. of the iron post.

The cor. of secs. 23, 24, 25 and 26, is monumented by a malpais stone, 20 x 8 x 6 ins., firmly set, mkd. with 2 notches on the S. and 2 notches on the E., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, brass cap mkd.

BOOK 4726

Remonumentation, Township 14 North, Range 4 East, Arizona

4

4.

CHAINS

T14N R4E  
 $\frac{1}{4}$   $\frac{S23}{S26}$  |  $\frac{S24}{S25}$   
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 23 and 24, is monumented by a malpais stone, 20 x 14 x 8 ins., firmly set, mkd.  $\frac{1}{4}$  on W., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T14N R4E  
 $\frac{1}{4}$   
 $\frac{S23}{S24}$   
 1964

Bury the original cor. stone alongside the iron post.

Rebuild mound of stones W. of the iron post.

A fence bearing E. and W., bears N., 6 lks. dist.

The  $\frac{1}{4}$  sec. cor. of secs. 23 and 26, is monumented by a malpais stone, 20 x 10 x 4 ins., firmly set in a mound of stones, mkd.  $\frac{1}{4}$  on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, brass cap mkd.

T14N R4E  
 $\frac{1}{4}$   $\frac{S23}{S26}$   
 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stones N. of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, is monumented by a malpais stone, 24 x 14 x 4 ins., firmly set in a mound of stones, mkd.  $\frac{1}{4}$  on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, brass cap mkd.

T14N R4E  
 $\frac{1}{4}$   $\frac{S14}{S23}$   
 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stones N. of the iron post.

CHAINS

The  $\frac{1}{2}$  sec. cor. of secs. 4 and 9, is monumented by a granite stone, 20 x 12 x 8 ins., firmly set, mkd. with  $\frac{1}{2}$  on N., with a mound of stones N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, brass cap mkd.

T14N R4E

$\frac{1}{2}$   $\frac{S4}{S9}$

1964

Bury the original cor. stone alongside the iron post.

Rebuild original mound of stones N. of the iron post.

A fence cor. bears N., 6 lks. dist., from which fences bear S. and W.



1

BOOK 4726  
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,  
in pursuance of special instructions bearing date of the 23 day of April, 1964,  
I have remonumented cadastral survey corners in Township 14 North,  
Range 4 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
are represented in the foregoing field notes as having been executed by me and under my direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual  
of Instructions for the Survey of the Public Lands of the United States, and in specific manner  
described in the foregoing field notes.

February 24, 1965  
(Date)

*Boyd S. Owens*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in  
Township 14 North, Range 4 East, of the Gila and Salt River Meridian,  
Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,  
having been critically examined and found correct, are hereby approved.

JUL 6 1965  
(Date)

*E. L. Remington*  
(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~  
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)