

BOOK 4731

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(1)

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 17 North, Range 4 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 23, 19 64, which provided for the surveys included under Group Number 415, approved April 23, 1964, and assignment instructions dated May 15, 19 64.

Survey commenced May 18, 19 64

Survey completed June 26, 19 64

10

BOOK 4731

INDEX DIAGRAM

Township 17 North, Range 4 East
5 4 4 4 3 3 3 2

2	6	15 5	13 4	8	2	7 1
1		14 15	13			7 7
	7	14 8	13 9	10	11	12
1		14	12	12 12	9	
	18	17	16	11 15	14	18
				10 11	8	
	19	20	21	10 22	8 23	24
				9 10	8	6
	30	29	28	27	26	6 25
						6 5
	31	32	33	34	35	36

CHAINS

The south boundary, the 4th standard parallel north, and the east boundary were surveyed in 1885 by John G. Smith, the north and west boundaries and subdivisional lines were surveyed in 1904 by Edgar G. Dietrich. The 4th standard parallel north was retraced in 1916 by W. H. Richards.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The Assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 17 North, Range 4 East, Arizona

The cor. of secs. 7, 12, 13 and 18, Tps. 17 N., Rs. 3 and 4 E., is monumented by a calcareous stone, 20 x 6 x 3 ins., firmly set, mkd. 2 notches on N. and 4 notches on S. edge, from which an original bearing tree

A cedar, 10 ins. diam., bears S. 66½° E., 300 lks. dist., mkd. T17N R4E S18 BT.

Other bearing trees have been destroyed.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N
R3E R4E
S12 S7
S13 S18
1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The cor. of secs. 1, 6, 7 and 12, Tps. 17 N., Rs. 3 and 4 E., is monumented by a sandstone, 20 x 12 x 6 ins., firmly set, mkd. 1 notch on N. and 5 notches on S.

The original bearing trees have been destroyed, with a stump remaining at record bearing and distance in SW quadrant.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

CHAINS

T17N
R3E R4E
S1 | S6
S12 | S7
1964

from which

A juniper, 6 ins. diam., bears N. 35° E.,
114 lks. dist., mkd. T17N R4E S6 BT.

No other trees within limits.

Raise a mound of stones W. of the iron post, and deposit
the original corner stone in the mound.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, Tps. 17 N., Rs. 3 and
4 E., is monumented by a squared cedar stake with
Forest Service boundary marker nailed to it, with pieces
of the original stone alongside, mkd. $\frac{1}{4}$, with a mound
of stones W., from which the original bearing trees

A cedar, 10 ins. diam., bears S. 65 $\frac{1}{2}$ ° E.,
318 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

A cedar stump, 10 ins. diam., 5 ft. high, bears
S. 50° W., 285 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T17N
R3E R4E
 $\frac{1}{4}$
S1 | S6
1964

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

Cor. is located 1 lk. E. of a N-S fence.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, Tps. 17 and 18 N.,
R. 4 E., is monumented by a stone, 16 x 8 x 4 ins.,
firmly set, mkd. $\frac{1}{4}$ on N., from which the original bearing
trees

A cedar, 12 ins. diam., bears S. 41 $\frac{1}{2}$ ° E.,
72 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A cedar, 8 ins. diam., bears N. 15 $\frac{1}{2}$ ° W.,
28 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins.
in the ground to bedrock, mound with stones to top,
with brass cap mkd.

T18N R4E
 $\frac{1}{4}$ S36
S1
T17N
1964

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona 3.

CHAINS

Bury the original corner stone alongside the iron post.

Raise a mound of stones N. of the iron post.

The cor. of secs. 1, 2, 35 and 36, Tps. 17 and 18 N., R. 4 E., is monumented by a conglomerate stone, 22 x 10 x 6 ins., firmly set in a mound of stones, mkd. with 1 notch on E. and 5 notches on W., with a mound of stones W., from which the original bearing trees

A cedar, 10 ins. diam., bears S. 29½° E., 109 lks. dist., mkd. with a partly grown over blaze, remarked S2 BT.

A cedar, 10 ins. diam., bears S. 7° W., (record S. 10½° W.) 170 lks. dist., blaze has partly grown over, remarked S1 BT.

A cedar, 12 ins. diam., bears N. 74½° W., 151 lks. dist., mkd. T18N R4E S35 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T18N R4E	
S35	S36
S2	S1
T17N	
1964	

from which

A cedar, 6 ins. diam., bears N. 43° E., 19 lks. dist., mkd. S36 BT.

Bury the original corner stone alongside the iron post.

Rebuild the original mound of stones, W. of the iron post.

A N-S fence bears E., 2 lks. dist.

The cor. of secs. 2, 3, 34 and 35, Tps. 17 and 18 N., R. 4 E., is monumented by a sandstone, 18 x 8 x 6 ins., firmly set, mkd. with 2 notches on E. and 4 notches on W., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T18N R4E	
S34	S35
S3	S2
T17N	
1964	

Rebuild the original mound of stones W. of the iron post and deposit the original corner stone in the mound.

The cor. of secs. 3, 4, 33 and 34, Tps. 17 and 18 N., R. 4 E., is monumented by a sandstone, 20 x 10 x 4 ins., firmly set, mkd. with 3 notches on E. and W., with mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona 4.

4

CHAINS

T18N R4E

S33	S34
S4	S3

T17N
1964

Bury the original corner stone alongside the iron post.
Rebuild the original mound of stones W. of the iron post.

The cor. of secs. 4, 5, 32 and 33, Tps. 17 and 18 N., R. 4 E., is monumented by a sandstone, 16 x 8 x 6 ins., firmly set, mkd. with 4 notches on E. and 2 notches on W., with mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T18N R4E

S32	S33
S5	S4

T17N
1964

Bury the original corner stone alongside the iron post.
Rebuild the original mound of stones W. of the iron post.

A fence cor. bears NW., 8½ lks. dist., fences bearing N. 65° W. and S. 12° E.

The ¼ sec. cor. of secs. 5 and 32, Tps. 17 and 18 N., R. 4 E., is monumented by a stone, 16 x 10 x 8 ins., firmly set, mkd. ¼ on N., with a scattered mound of stones N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T18N R4E

¼ S32
¼ S5

T17N
1964

Bury the original corner stone alongside the iron post.
Rebuild the mound of stones N. of the corner.
A N-S fence bears W., 1 lk. dist.

The cor. of secs. 5, 6, 31 and 32, Tps. 17 and 18 N., R. 4 E., is monumented by a sandstone, 20 x 14 x 2 ins., firmly set in a mound of stones, mkd. 5 notches on E. and 1 notch on W., from which the remains of the original bearing trees

A cedar stump, 24 ins. diam., bears N. 66½° E., 175 lks. dist. (No mks. visible.)

A cedar, 30 ins. diam., bears S. 27½° E., 217 lks. dist. This tree has been partially destroyed and no mks. remain.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, mound with stones to top, with brass cap mkd.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona 5.

CHAINS

T18N R4E
S31 | S32
 S6 | S5
 T17N
 1964

from which

A cedar, 8 ins. diam., bears N. 85° E.,
 70½ lks. dist., mkd. T18N R4E S32 BT.

A cedar, 6 ins. diam., bears S. 12° E.,
 66½ lks. dist., mkd. S5 BT.

Deposit the original corner stone in the mound around
 the iron post.

An E-W fence bears N., 1 lk. dist.

The ¼ sec. cor. of secs. 6 and 31, Tps. 17 and 18 N.,
 R. 4 E., is at fence cor., fences bearing E., W. and S.
 This point has been accepted for years by R. E. Hardy
 and McCulley who are interested property owners and
 verified the position, from which the original bearing
 trees

A cedar, 14 ins. diam., bears N. 28¼° W., 61 lks.
 dist., mkd. ¼ S31 BT. (Tree partially grown over,
 blaze reopened.)

A cedar, 10 ins. diam., bears S. 21½° W., 113 lks.
 dist., mkd. ¼ S6 BT. (Note: record dist. given
 as 131 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
 in the ground, with brass cap mkd.

T18N R4E
 ¼ S31
 S6
 T17N
 1964

The ¼ sec. cor. of secs. 25 and 36, is monumented by a
 stone, 18 x 14 x 6 ins., firmly set, mkd. ¼ on N. face,
 with pits visible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T17N R4E
 ¼ S25
 S36
 1964

from which

A juniper, 4 ins. diam., bears S. 51°30' E.,
 56 lks. dist., mkd. ¼ S36 BT.

A juniper, 4 ins. diam., bears N. 41°30' W.,
 59 lks. dist., mkd. ¼ S25 BT.

Bury the original corner stone alongside the iron post.

Raise a mound of stones N. of the iron post.

BOOK 4731

6

Remonumentation, Township 17 North, Range 4 East, Arizona 6.

CHAINS

The cor. of secs. 25, 26, 35 and 36, is monumented by a sandstone, 14 x 8 x 6 ins., firmly set, mkd. with 1 notch on S. and E. edges. All bearing trees have been eradicated.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N R4E
 S26|S25
 S35|S36
 1964

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The ¼ sec. cor. of secs. 25 and 26 is monumented by a malpais stone, 18 x 12 x 6 ins., firmly set in a mound of stones, mkd. ¼ on W. face. The original bearing tree has been destroyed.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T17N R4E
 ¼
 S26|S25
 1964

Raise a mound of stones W. of the iron post and deposit the orig. corner stone in mound.

The cor. is located 10 lks. N. of an E-W fence.

The cor. of secs. 23, 24, 25 and 26, is monumented by a malpais stone, 18 x 8 x 6 ins., firmly set, mkd. with 2 notches on S. and 1 notch on E., from which the original bearing trees .

A juniper, 10 ins. diam., bears S. 85° E., 269 lks. dist., mkd. T17N R4E S25 BT. (Note: record calls for S 4½° E., 269 lks. dist.)

A juniper, 10 ins. diam., bears S. 24° W., 232 lks. dist., mkd. T17N R4E S26 BT. (Note: record calls for S. 17½° W., 232 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R4E
 S23|S24
 S25|S26
 1964

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

CHAINS

A fence cor. bears N. $64\frac{1}{2}^\circ$ W., 40 lks. dist., from which the fences bear E. and S. No new bearing trees within limits.

The cor. of secs. 1, 2, 11 and 12, is monumented by a sandstone, 18 x 12 x 4 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the E. edge, from which the remaining bearing trees

A pinon, 10 ins. diam., bears N. 54° E., 189 lks. dist., mkd. T17N R4E S1 BT.

A cedar, 10 ins. diam., bears S. $14\frac{1}{2}^\circ$ W., 88 lks. dist., mkd. T17N R4E S11 BT.

The other bearing trees have been destroyed.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, mound with stones to top, with brass cap mkd.

T17N R4E	
S2	S1
S11	S12
1964	

Deposit the original corner stone in the mound around the iron post.

The witness $\frac{1}{4}$ sec. cor. of secs. 1 and 12, is monumented by a sandstone, 20 x 16 x 14 ins., firmly set, mkd. WC $\frac{1}{4}$ on N. face, from which the original bearing trees

A cedar, 10 ins. diam., bears N. $80\frac{1}{2}^\circ$ E., 70 lks. dist., mkd. WC $\frac{1}{4}$ S1 BT.

A cedar, 9 ins. diam., bears S. $56\frac{1}{2}^\circ$ E., 33 lks. dist., mkd. WC $\frac{1}{4}$ S12 BT.

Both trees partially grown over. I reopen blaze on SE. tree.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, mound with stones to top, brass cap mkd.

T17N R4E		
$\frac{1}{4}$	S1	W
	S12	C
1964		

Deposit the original corner stone in the mound around the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, is monumented by a sandstone, 18 x 10 x 4 ins., firmly set in a small mound of stones, mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees

A cedar, 12 ins. diam., bears N. 31° E., 168 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A cedar, 10 ins. diam., bears S. $72\frac{1}{2}^\circ$ W., 57 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona

8

8.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound with stones to top, with brass cap mkd.

T17N R4E

½
S2|S1
1964

Deposit the original corner stone in the mound around the iron post.

The cor. of secs. 22, 23, 26 and 27, is monumented by a malpais stone, 20 x 10 x 8 ins., firmly set, mkd. with 2 notches on S. and E. edges, with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, mound with stones to top, with brass cap mkd.

T17N R4E

S22|S23
S27|S26
1964

Deposit the original corner stone in mound around the iron post.

The ¼ sec. cor. of secs. 22 and 23, is monumented by a malpais stone, 18 x 8 x 6 ins., firmly set, mkd. ¼ on W., with a mound of stones to the W., from which the original bearing tree

A dead cedar, 20 ins. diam., bears N. 10½° E., 202 lks. dist., mkd. ¼ S23 BT on 6 in. limb of the tree.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R4E

¼
S22|S23
1964

No new bearing trees available.

Deposit the original corner stone in mound of stones W. of the iron post.

The cor. of secs. 14, 15, 22 and 23 is monumented by a malpais stone, 20 x 10 x 6 ins., firmly set, mkd. with 3 notches on S. and 2 notches on E., with a mound of stone to the W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona

CHAINS

T17N R4E
S15 | S14
S22 | S23
 1964

No original bearing trees given and no new trees available.

Bury the original corner stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

The cor. of secs. 10, 11, 14 and 15, is monumented by a sandstone, 20 x 8 x 4 ins., firmly set in a mound of stones, mkd. with 4 notches on S. and 2 notches on E., with a mound of stones W., from which the original bearing trees

A cedar, 10 ins. diam., bears S. 65° E.,
 86 lks. dist., mkd. T17N R4E S14 BT.

A cedar, 10 ins. diam., bears S. 75½° W.,
 160 lks. dist., mkd. T17N R4E S15 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, mound with stones to top, with brass cap mkd.

T17N R4E
S10 | S11
S15 | S14
 1964

from which

A 6 in. limb on scrub cedar, 14 in. diam.,
 bears N. 3° W., 57 lks. dist., mkd. S10 BT.

No other suitable bearing trees available.

Deposit the original corner stone in mound around the iron post.

The cor. of secs. 21, 22, 27 and 28, is monumented by a malpais stone, 18 x 8 x 8 ins., firmly set, mkd. with 2 notches on S. and 3 notches on E., with scattered mound of stones W., from which the remains of original bearing trees

A cedar, 18 ins. diam., bears S. 70½° E.,
 318 lks. dist., mkd. T17N R4E S27 BT.

A cedar, 16 ins. diam., bears N. 51° E.,
 222 lks. dist., is dead and blown over.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, collar of stones to top, brass cap mkd.

T17N R4E
S21 | S22
S28 | S27
 1964

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona

10

10.

CHAINS

Bury the original corner stone alongside the iron post.
 Rebuild the mound of stones W. of iron post.
 No other suitable bearing trees available.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, is monumented by a malpais stone, 18 x 10 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on N. face, with a mound of stones N., from which the original bearing trees

A cedar, 30 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ E.,
 234 lks. dist., mkd. $\frac{1}{4}$ S27 BT. (Note: record
 was S. $53\frac{1}{2}^{\circ}$ W., 234 lks. dist.)

A cedar, 30 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ W.,
 382 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

Both trees legible but partly dead.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins.
 in the ground, mound with stones to top, with brass
 cap mkd.

T17N R4E
 $\frac{1}{4}$ $\frac{S22}{S27}$
 1964

Deposit original corner stone alongside the iron post.
 Rebuild the original mound of stone N. of the iron post.
 No other suitable bearing trees available.

The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, is monumented by a broken malpais stone, 18 x 8 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, with pits visible.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T17N R4E
 $\frac{1}{4}$
 S21 | S22
 1964

Bury the original corner stone alongside the iron post.
 Raise a mound of stones W. of the iron post.

The cor. of secs. 15, 16, 21 and 22, is monumented by a malpais stone, 14 x 8 x 6 ins., firmly set, mkd. with 17 on NE, 4 on SE., 3 notches on S. and E. edges, with small mound of stones W., from which the remains of original bearing trees

A cedar, 12 ins. diam., bears N. 56° E.,
 116 lks. dist., grown over blaze, remarked
 T17N R4E S15 BT.

A cedar stump, bears S. $24\frac{1}{2}^{\circ}$ E., 127 lks. dist.
 No mks. visible.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona 11.

CHAINS

A cedar, 14 ins. diam., bears S. 61° W.,
137 lks. dist., mkd. T17N R4E S21 BT.

(Note: Dist. to BT's are all slope dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T17N R4E
S16 | S15
S21 | S22
1964

from which

A cedar, 12 ins. diam., bears N. 24° W.,
97 lks. dist., mkd. S16 BT.

No other suitable bearing trees available.

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The witness ¼ sec. cor. of secs. 15 and 22, is monumented
by a malpais stone, 18 x 8 x 6 ins., firmly set, mkd.
WC ¼ on N. with scattered mound of stones N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T17N R4E
¼ S15 W
S22 C
1964

Bury the original corner stone alongside the iron post.

Rebuild the mound of stones N. of the iron post.

The ¼ sec. cor. of secs. 15 and 16, is monumented by a
sandstone, 14 x 6 x 4 ins., firmly set, mkd. ¼ on W.
face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T17N R4E
¼
S16 | S15
1964

from which

A cedar, 6 ins. diam., bears N. 88° E.,
37 lks. dist., mkd. ¼ S15 BT.

No other suitable bearing trees available.

Bury the original corner stone alongside the iron post.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona

12.

12

CHAINS

Raise a mound of stones W. of the iron post.

The cor. is located 75 lks. W. of a N-S road.

The cor. of secs. 9, 10, 15 and 16, is monumented by a sandstone, 20 x 6 x 4 ins., firmly set, mkd. 4 notches on S. and 3 notches on E., from which the original bearing tree

A cedar, 10 ins. diam., bears S. 30½° W., 371 lks. dist., mkd. T17N R4E S16 BT. (The tree is dead but still standing with mks. legible.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N R4E	
S9	S10
S16	S15
1964	

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The ¼ sec. cor. of secs. 10 and 15, is monumented by a sandstone, 18 x 8 x 4 ins., firmly set in a small mound of stones, mkd. ¼ on N. face, with mound of stones N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound with stones to top, with brass cap mkd.

T17N R4E	
¼ S10	
S15	
1964	

Deposit original corner stone in mound around the iron post.

Original mound of stones N. of the iron post.

The cor. of secs. 8, 9, 16 and 17, is monumented by a stone, 16 x 10 x 10 ins., firmly set, mkd. with 4 notches on S. and E. edges, with mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T17N R4E	
S8	S9
S17	S16
1964	

Deposit original corner stone in mound W. of the iron post.

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona 13.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, is monumented by a sandstone, 20 x 6 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T17N R4E

$\frac{1}{4}$
S8|S9
1964

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The cor. of secs. 4, 5, 8 and 9, is monumented by a sandstone, 20 x 10 x 8 ins., firmly set in a mound of stones, mkd. with 5 notches on S. and 4 notches on E., with mound of stones W., from which the remains of original bearing trees

A cedar stump, bears S. 59° E., 111 lks. dist.
(No mks. legible.)

A cedar, 10 ins. diam., bears N. 68° W.,
158 lks. dist. Part of tree has been cut down.
No mks. found.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, mound with stones to top, with brass cap mkd.

T17N R4E

S5|S4
S8|S9
1964

from which

A small scrub juniper with Forest Service "K"
tag nailed to trunk, bears NW. 66 lks. dist.

Deposit original corner stone in mound around the iron post.

No other suitable bearing trees within limits.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, is monumented by a sandstone, 20 x 6 x 4 ins., firmly set, dimly mkd. $\frac{1}{4}$ on W. face, with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R4E

$\frac{1}{4}$
S5|S4
1964

BOOK 4731

Remonumentation, Township 17 North, Range 4 East, Arizona 14.

14

CHAINS

Bury the original corner stone alongside the iron post.
 Rebuild the original mound of stones W. of the iron post.

The cor. of secs. 7, 8, 17 and 18, is monumented by a limestone, 18 x 8 x 6 ins., firmly set in a mound of stones, mkd. 4 notches on S. and 5 notches on E. edge, from which the original bearing trees

A cedar, 18 ins. diam., bears N. 52 $\frac{1}{2}$ ° E.,
 51 lks. dist., mkd. T17N R4E S8 BT.

A cedar, 24 ins. diam., bears S. 73° E.,
 18.6 lks. dist. (Note: record 186 lks.), mkd.
 T17N R4E S17 BT.

A cedar, 14 ins. diam., bears S. 86° W.,
 44 lks. dist., mkd. T17N R4E S18 BT.

A cedar, 20 ins. diam., bears N. 5° W.,
 33 lks. dist., mks. rotted out.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, mound with stones to top, with brass cap mkd.

T17N R4E	
S7	S8
S18	S17
1964	

Deposit the original corner stone in the mound around the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, is monumented by a sandstone, 20 x 10 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N R4E	
$\frac{1}{4}$	
S7	S8
1964	

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

Fence cor. bears NW., 7 lks. dist. Fences bearing E., W. and N.

The cor. of secs. 5, 6, 7 and 8, is monumented by a sandstone, 20 x 8 x 6 ins., firmly set, mkd. with 5 notches on S. and E.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS

T17N R4E
 $\frac{S6}{S7} | \frac{S5}{S8}$
 1964

Bury the original corner stone alongside the iron post.

Raise a mound of stones W. of the iron post.

A fence cor. bears S. 55° W., 11 lks. dist., fences bearing S., W. and NE. about 100 lks., thence N. and E.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, is monumented by a malpais stone, 20 x 10 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on N.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17N R4E
 $\frac{1}{4} \frac{S5}{S8}$
 1964

Bury the original corner stone alongside the iron post.

Raise a mound of stones N. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, is monumented by a sandstone, 20 x 8 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on W., with a mound of stones W.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T17N R4E
 $\frac{1}{4}$
 $S6 | S5$
 1964

Bury the original corner stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

An E-W fence bears N., 1 lk. dist.

17

BOOK 4731

CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23 day of April, 1964, I have remonumented cadastral survey corners in Township 17 North, Range 4 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 24, 1965
(Date)

Boyd S. Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 17 North, Range 4 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 6 1965
(Date)

E. S. Huntington
(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)