Form 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY	
of the	
East Boundary	
and the Subdivisional Lines	
Supurvisional Lines	
Township 1 North, Range 12 West	
·	
Of the Gila and Salt RiverMer	idian,
n the State of Arizona	
EXECUTED BY	
Boyd S. Owens, Cadastral Surveyor	
Under special instructions datedFebruary 11 , 19 63, which provided for the si	urveys
included under Group Number 388 , approved February 20, 1963	
and assignment instructions datedSeptember 15, 19	
Survey commenced September 24, 19 64	

October 22

Survey completed _

_, 19 ____

BOOK 4748

INDEX DIAGRAM

T	ownsł	1ip1	Nor	th		, Range		12 West			,
				İ	***************************************					1	
6	43	5	34	4	26	8	19	2	12	1	5
43		43		33		26		19		12	
1		,									
7	42	8	32	9	25	10	18	11	11	12	4
41		41		32		25		18		10	
											
18	40	17	31	16	24	18	17	14	10	13	3
						10	- '	14	10	18	ر
40		39		31		24		16		9	
				-						·	
19	38	20	30	21	23	22	16	23	8	24	2
38		37		29		23		15		8	
30	37	29	29	28	22	27	15	26	7	25	2
36		35		28		21		14		6	
						21		14		0	
31	34	32	27	88	20	84	12	6 ~	_		
01	74	02	41	00	20	34	13	85	5	36	1

Township 1 North, Range 12 West, G&SRM, Arizona

 $1 f_{i}^{d}$

=	CHAINS	
		The north and west boundaries were surveyed in 1941 by Hiester and White. The south boundary, the Base Line, was surveyed in 1914-16 by Abbey Gill Voight.
		The following field notes are those of the survey of the east boundary and the subdivisional lines of Township 1 North, Range 12 West.
		The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated February 11, 1963.
		Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches in diameter, flanged at the base and with a brass cap riveted to the top.
		The geographic position of the southeast corner of the township is: Latitude 33°22'38.3" North, and Longitude 113°26'17.5" West, as determined from U.S.G.S. Quadrangle Eagle Tail Mts, dated 1962.
		The mean magnetic declination was found to be 14°30' East.
		East Boundary, T. 1 N., R. 12 W., Arizona
		Beginning at the Std. corner of Townships 1 North, Ranges 11 and 12 West, monumented by an iron post 3 ins. diam., as described in the official record.
		North, bet. secs. 31 and 36.
		Over rolling desert land, through scattered palo verde, creosote brush and cacti.
	3.40	Rocky rim, bears SE. and NW., desc. NE. slope.
	7.50	Wash, 50 lks. wide, 1 ft. deep, drains SE.; thence over gently rolling land.
	40.00	Point for the ½ sec. cor. of secs. 31 and 36.
		Set the iron post 22 ins. in the ground, cap mkd.
		T 1 N
		R12W R11W
		\$36 \$31 1964
		Build a mound of stones W. of the iron post.
		Thence over rolling land.
	53.00	Track road, bears SE. and NW.
	80.00	Point for the cor. of secs. 25, 30, 31 and 36.
		Set the iron post 22 ins. in the ground, cap mkd.
:		

East	Boundary,	т.	1	Ν.,	R.	12	W.,	Arizona
------	-----------	----	---	-----	----	----	-----	---------

CHAINS	
	T 1 N R12W R11W S25 S30 S36 S31 1964
	Build a mound of stones W. of the iron post.
	Land, gently rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered cacti and creosote brush.
	North, bet. secs. 25 and 30.
	Over nearly level land, through scattered palo verde, creosote brush and cacti.
18.80	Track road, bears SE. and NW.
40.00	Point for the ½ sec. cor. of secs. 25 and 30.
:	Set the iron post 20 ins. in the ground, cap mkd.
	T 1 N R12W R11W \$\frac{1}{4}\$ S25 S30 1964
	Build a mound of stones W. of the iron post.
44.00	Wash, 8 1ks. wide, 1 ft. deep, drains S. 10° E.
74.90	Wash, 45 lks. wide, 1 ft. deep, drains SE.
80.00	Point for the cor. of secs. 19, 24, 25 and 30.
	Set the iron post 20 ins. in the ground, cap mkd.
	T 1 N R12W R11W <u>S24 S19</u> S25 S30 1964
	Land, nearly level. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	North, bet. secs. 19 and 24.
	Over gently rolling land, through scattered palo verde, creosote brush.
22.00	Wash, 35 lks. wide, 1 ft. deep, drains SW.
24.50	Wash, 35 lks. wide, 1 ft. deep, drains S. 30° W.
	Begin asc. over gentle SE. slope.
39.00	0 1 1 1 1 1 1 1 0 0 0 0 0 0 0 0 0 0 0 0

East Boundary, T. 1 N., R. 12 W., Arizona

3.

	CHAINS	
		Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.
		T 1 N R12W R11W
		\$24 \$19 1964
•		Build a mound of stones W. of the iron post.
	46.20	Crest of slope; desc. gentle NE. slope.
	51.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.
	66.70	Wash, 40 1ks. wide, 1 ft. deep, drains E.
	70.20	Asc. gentle SE. slope.
	76.70	Top of asc.; thence over nearly level land.
	80.00	Point for the cor. of secs. 13, 18, 19 and 24.
	·	Set the iron post 18 ins. in the ground, cap mkd.
		T 1 N R12W R11W
		<u>s13 s18</u>
		\$24 \$19 1964
		Build a mound of stones W. of the iron post.
		Land, gently rolling. Soil, rocky and gravelly. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		North, bet. secs. 13 and 18.
		Over gently rolling land, through scattered creosote brush and cacti.
	9.40	Small draw, drains E.
	21.60	Wash, 20 1ks. wide, 1 ft. deep, drains SE.; asc. gentle S. slope.
	27.40	Spur, slopes E.; desc. gentle N. slope.
	31.50	Small draw, drains E.; asc. gentle S. slope.
	39.00	Top of ascent; thence over nearly level land.
	40.00	Point for the ½ sec. cor. of secs. 13 and 18.
•	·	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
		T 1 N R12W R11W
	·	\$13 \$18 1964
	ļ	

East	Boundary,	Τ.	1	Ν.,	R.	12	W.,	Arizona
------	-----------	----	---	-----	----	----	-----	---------

	East Boundary, T. I N., R. 12 W., Arizona	4.
CHAINS		7
46.40	Track road, bears NE. and SW.	
58.60	Small wash, 10 lks. wide, 1 ft. deep, drains W.	
73.90	Small wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.	
80.00	Point for the cor. of secs. 7, 12, 13 and 18.	
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.	
	T 1 N R12W R11W S12 S 7 S13 S18	
	1964	
	Land, rolling and broken. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.	
	North, bet. secs. 7 and 12.	-
	Over rough rolling land, through scattered creosote brush and cacti; asc. S. slope.	
7.60	Spur, slopes SW.; desc. NW. slope.	
19.40	Wash, 20 1ks. wide, 1 ft. deep, drains W.	
20.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.	
34.90	Same wash, drains S. 15° E.; begin asc. over S. slope of broken mountainous land.	
39.50	Small wash, drains SW.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.	
	Set the iron post 8 ins. in the ground, mound of stones to top, cap mkd.	
	T 1 N R12W R11W	
	\$12 S 7 1964	
41.20	Small spur, slopes SW.	
45.00	Saddle, bears E. and W.; desc. N. slope.	
59.50	Wash, 10 1ks. wide, 1 ft. deep, drains N. 70° W.	
61.30	Wash, 10 1ks. wide, 1 ft. deep, drains SW.	
71.20	Wash, 10 1ks. wide, with 5 ft. banks, drains W.; asc. gentle S. slope.	
80.00	Point for the cor. of secs. 1, 6, 7 and 12.	
	Set the iron post 12 ins. in the ground, mound of stones to top, cap mkd.	

BOOK 4748

East Boundary, T. 1 N., R. 12 W., Arizona

5.

 T-2	1
CHAINS	
	T 1 N R12W R11W S 1 S 6 S12 S 7 1964
	Land, rolling and broken. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	North, bet. secs. 1 and 6.
	Over rolling land, asc. S. slope through scattered undergrowth.
9.60	Rocky draw, drains SW.; asc. steep and rocky S. slope.
23.70	Top of knob; desc. N. slope.
26.00	Saddle bet. knobs; asc. S. slope.
32.80	Top of knob; desc. N. slope.
40.00	Point for the 4 sec. cor. of secs. 1 and 6.
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.
	T 1 N R12W R11W
	s 1 s 6 1964
41.20	Wash, 20 1ks. wide with 4 ft. banks, drains N. 80° W.; asc. S. slope.
57.30	Rocky spur, slopes W.; desc. N. slope.
75.50	Wash, 80 1ks. wide, 1 ft. deep, drains W.
80.25	The cor. of Ts. 1 and 2 N., Rs. 11 and 12 W., monumented by an iron post 3 ins. diam., as described in the official record.
	Land, mountainous. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote brush and cacti.
	Subdivision, T. 1 N., R. 12 W., Arizona
	From the Std. cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., as described in the official record.
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling land, through scattered palo verde, greasewood and cacti.
1	1

	
CHAINS	
6.30	Wash, 10 1ks. wide, 1 ft. deep, drains NE.
16.30	Wash, 35 1ks. wide, 1 ft. deep, drains E.
23.90	Asc. over S. slope.
24.90	Ridge, bears S. 85° E. and N. 85° W.; desc. NE. slope.
33.00	Wash, 50 1ks. wide, 2 ft. deep, drains N. 60° E.
40.00	Point for the ½ sec. cor. of secs. 35 and 36.
	Set the iron post 24 ins. in the ground, cap mkd.
	T1NR12W
	塚 S35 S36
ą	1964
	Build a mound of stones W. of the iron post.
40.90	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. S. slope.
50.60	Spur, slopes SW.; desc. NW. slope.
53.20	Wash, 20 lks. wide, 1 ft. deep, drains NE.
60.70	Spur, slopes NE.; desc. N. slope.
70.50	Wash, 30 1ks. wide, 1 ft. deep, drains SE.; asc. S. slope.
77.90	Top of ascent, bears NW. and SE.; desc. over NE. slope.
	Point for the cor. of secs. 25, 26, 35 and 36.
, .	Set the iron post 24 ins. in the ground, cap mkd.
	T1NR12W
	<u>\$26</u> <u>\$25</u> \$35 <u>\$</u> 36
•	1964
•	Build a mound of stones W. of the iron post.
	Land, rolling.
	Soil, rocky clay loam. Timber, scattered palo verde.
	Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
	S. 89°58' W., bet. secs. 25 and 36.
	Over gently rolling land, through scattered undergrowth; asc. gentle E. slope.
20.00	Top of asc.; begin desc. over gentle W. slope.
•	
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

ECCK 4748

CHAIÑS	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	$\frac{1}{4} \frac{S25}{S36}$
	1964
	Build a mound of stones N. of the iron post.
44.90	Wash, 30 1ks. wide, 2 ft. deep, drains SW.; asc. E. slope.
50.00	Top of asc.; thence over rolling land.
57.00	Wash, 10 1ks. wide, 1 ft. deep, drains SE.
68.90	Wash, 12 1ks. wide, 1 ft. deep, drains SE.
73.00	Wash, 100 1ks. wide, 3 ft. deep, drains S.
76.20	Begin asc. over NE. slope.
80.10	The cor. of secs. 25, 26, 35 and 36.
	Land, gently rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	N. 0°01' W., bet. secs. 25 and 26.
	Over rolling land, through scattered palo verde, creosote brush and cacti.
6.00	Desc. NE. slope.
11.00	Wash, 30 lks. wide, with 3 ft. banks, drains SE.; continue over gently rolling land.
39.00	Wash, 40 1ks. wide, 1 ft. deep, drains SW.
40.00	Point for the ½ sec. cor. of secs. 25 and 26 falls in a wash subject to flash floods.
40.38	Point selected for the witness ½ sec. cor. of secs. 25 and 26.
	Set the iron post 22 ins. in the ground, mound of stones to top, cap mkd.
•	T1NR12W
	W C
	S25 S26
	1964
43.90	Wash, 30 1ks. wide, 1 ft. deep, drains W. from NE.
80.00	Point for the cor. of secs 124, 25 and 26.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W <u>S23 S24</u> <u>S26 S25</u> 1964

3		Subdivision, T. 1 N., R. 12 W., Arizona
	CHAINS	
		Build a mound of stones W. of the iron post.
		Land, rolling.
		Soil, rocky clay loam. Timber, scattered palo verde and mesquite.
		Undergrowth, scattered creosote brush and cacti.
		Example on a final state of the
		From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
		S. 89°58' W., bet. secs. 24 and 25.
		Over gently rolling land, through scattered undergrowth.
	4.50	Wash, 20 1ks. wide, 6 ins. deep, drains SE.; asc. gentle E. slope.
	12.40	Begin desc. over gentle W. slope.
	17.40	Begin asc. over gentle E. slope.
	40.05	Point for the 4 sec. cor. of secs. 24 and 25.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W
		$\frac{1}{4} \frac{\text{S24}}{\text{S25}}$
		1964
	57.90	Begin desc. over gentle W. slope.
	70.30	Wash, 20 1ks. wide, 1 ft. deep, drains S. 30° W.
	73.30	Wash, 12 lks. wide, with 4 ft. banks, drains SE. from N. 5° E.; asc. E. slope.
	78.00	Spur, slopes S.; desc. W. slope.
	80.10	The cor. of secs. 23, 24, 25 and 26.
		Land, rolling.
		Soil, rocky clay loam. Timber, scattered palo verde.
		Undergrowth, scattered creosote brush and cacti.
		N 00011 TV 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		N. 0°01' W., bet. secs. 23 and 24.
		Over rolling land, through moderate undergrowth.
	15.80	Wash, 40 lks. wide, 1 ft. deep, drains SW. from N. 10° E.
	22.90	Wash, 40 1ks. wide, 1 ft. deep, drains S. 5° E. from NE.; asc. over SE. slope.
	34.70	Ridge, bears NE. and SW.; continue over rolling land.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.

:	CHAINS	Set the iron post 22 ins. in the ground, cap mkd.
	,	T1NR12W
		. 1 2
		S23 S24 1964
		Build a mound of stones W. of the iron post.
•	42.10	Wash, 15 lks. wide, 1 ft. deep, drains SW.; thence over nearly level land.
	59.20	Begin desc. over NW. slope.
	61.70	Draw, drains SW.; asc. SE. slope.
	67.20	Top of asc., bears NE. and SW.; thence over nearly level land.
	80.00	Point for the cor. of secs. 13, 14, 23 and 24.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W
		<u>S14 S13</u> S23 S24
		1964
* 0		Build a mound of stones W. of the iron post.
		Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and ironwood. Undergrowth, moderate creosote brush and cacti.
		From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
		S. 89°59' W., bet. secs. 13 and 24.
		Over gently rolling land, through scattered undergrowth.
	17.30	Draw, drains SE.; asc. E. slope.
	22.10	E. rim of mesa, bears S. 20° E. and N. 20° W.; thence over nearly level land.
	40.05	Point for the ½ sec. cor. of secs. 13 and 24.
		Set the iron post 20 ins. in the ground, cap mkd.
		T1NR12W
		1/4 S13 S24 1964
		Build a mound of stones N. of the iron post.
-		Thence over nearly level land.
*	59.70	Small draw, drains SW.; continue over nearly level land.
	80.10	The cor. of secs. 13, 14, 23 and 24.

		BOOK 4748
10 -		Subdivision, T. 1 N., R. 12 W., Arizona
	CHAINS	Land, gently rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered cacti and creosote brush.
		N. 0°01' W., bet. secs. 13 and 14.
		Over nearly level land, through scattered undergrowth; desc. gentle N. slope.
	15.20	Wash, 20 1ks. wide, 1 ft. deep, drains W.; asc. S. slope.
	22.00	Low spur, slopes S. 70° W.; thence over nearly level land.
	35.10	Low spur, slopes W.
	40.00	Point for the 4 sec. cor. of secs. 13 and 14.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W
		\$14 s13 1964
		Build a mound of stones W. of the iron post.
	48.00	Desc. gentle N. slope.
	60.50	Draw, drains W.; asc. S. slope.
	68.70	Low spur, slopes S. 70° W.; thence over nearly level land.
	80.00	Point for the cor. of secs. 11, 12, 13 and 14.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W <u>S11 S12</u> <u>S14 S13</u> 1964
		Build a mound of stones W. of the iron post.
		Land, gently rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
		N. 89°56' W., bet. secs. 12 and 13.
		Over gently rolling land, through scattered undergrowth.
		Asc. gentle SE. slope.
	10.00	Top of asc., bears NE. and SW.; thence over gently rolling land.

CHAINS 25.20	Draw, drains N.
40.05	Point for the ½ sec. cor. of secs. 12 and 13.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T1NR12W 2 S12 S13 1964
	Build a mound of stones N. of the iron post.
47.30	Begin gentle desc. along N. slope.
72.00	Begin asc. over E. slope.
77.00	Top of asc., bears S. 5° E. and N. 5° W.; desc. W. slope.
80.10	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling. Soil, rocky clay loam. Timber, scattered palo verde.
	Undergrowth, scattered creosote brush and cacti.
	N. 0°01' W., bet. secs. 11 and 12.
	Over rolling land, through scattered undergrowth.
9.30	Left bank of wash, bears S. 85° E. and N. 80° W.
11.60	Right bank of same wash, bears S. 85° E. and N. 85° W.; thence over nearly level land.
25.30	Left bank of wash, bears NE. and SW.
28.40	Main channel of wash, 40 lks. wide, 2 ft. deep, drains SW.
28.60	Right bank of wash, bears NE. and SW.; thence over nearly level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	S11 S12 1964
	Build a mound of stones W. of the iron post.
51.10	Wash, 5 lks. wide, 1 ft. deep, drains SW.; thence over nearly level land.
70.20	Begin gentle asc. along E. slope of a hill.
72.70	Low spur, slopes E.; desc. along gentle E. slope.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.

CHAINS	
CHAINS	Sot the image made 22 to 1
	Set the iron post 22 ins. in the ground, cap mkd.
-	T1NR12W S 2 S 1
	$\begin{array}{c c} \underline{S} & \underline{Z} & \underline{S} & \underline{1} \\ \underline{S}11 & \underline{S}12 \end{array}$
	1964
	Build a mound of stones W. of the iron post.
	Land, gently rolling.
	Soil, rocky clay loam. Timber, scattered palo verde.
	Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy
	of the Tp. S. 89°56' W., bet. secs. 1 and 12.
	Over gently rolling land.
11.90	
18.00	Wash, 10 1ks. wide, 1 ft. deep, drains SW.
40.03	Wash, 30 1ks. wide, 1 ft. deep, drains S. 15° W.
40.03	Point for the 1/2 sec. cor. of secs. 1 and 12.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W 1 S 1
	₹ <u>S12</u>
	1964
	Build a mound of stones N. of the iron post.
57.20	Wash, 4 lks. wide, 1 ft. deep, drains S.
64.80	Wash, 12 lks. wide, 1 ft. deep, drains S. 30° E.
69.80	Wash, 40 1ks. wide, 2 ft. deep, drains S. 30° E.
80.06	The cor. of secs. 1, 2, 11 and 12.
	Land, gently rolling.
	Soil, rocky clay loam. Timber, scattered palo verde.
	Undergrowth, moderate creosote brush.
	N. 0°01' W., bet. secs. 1 and 2.
	Over gently rolling land, through moderate undergrowth
14.70	Wash, 25 1ks. wide, 6 ins. deep, drains S. 70° W., from N. 80° E.
29.60	Track road, bears N. 60° E. and S. 60° W.
38.00	Wash, 5 1ks. wide, 6 ins. deep, drains SW.
40.00	Point for the ½ sec. cor. of secs. 1 and 2.

T	CHAINS		
		T1NR12W	
	4	s 2 s 1	
		1964	
İ		Build a mound of stones W. of the iron post.	
		Asc. gentle S. slope.	
	50.90	Asc. SW. slope of a rocky hill.	
	61.90	Begin gentle asc. along W. slope.	
	72.20	Spur, slopes W., desc. along W. slope.	
	80.32	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.	
		Land, gently rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, moderate to scattered creosote brush.	
		From the Std. cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., as described in the official record.	い
		N. 0°01' W., bet. secs. 34 and 35.	
		Over rolling land, desc. N. slope through scattered undergrowth.	
	11.50	Draw, drains SE.	
	34.00	Begin asc. over SW. slope.	
	37.70	Ridge, bears S. 75° E. and N. 75° W.; desc. NE. slope.	
	40.00	Point for the ½ sec. cor. of secs. 34 and 35.	
		Set the iron post 24 ins. in the ground, cap mkd.	
		T1NR12W	
		\$34\\$35 1964	
		Build a mound of stones W. of the iron post.	
	42.50	Draw, drains NE.; asc. S. slope.	
	44.80	Spur, slopes E.; thence over rough, rolling land.	
	59.10	Wash, 40 1ks. wide, 3 ft. deep, drains SE.	
	64.70	Begin asc. over SE. slope.	
	67.50	Ridge, bears E. and W.; desc. NW. slope.	
	69.10	Draw, drains N. 20° W.	
	74.00	Draw, drains N. 60° E.	

CHAINS	
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W S27 S26 S34 S35 1964
	Build a mound of stones W. of the iron post.
	Land, rough and rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°57' W., bet. secs. 26 and 35.
	Over rough, rolling land, through scattered undergrowth.
	Asc. NE. slope.
3.00	Low ridge, bears SE. and NW.; desc. SW. slope.
7.20	Wash, 40 lks. wide, 2 ft. deep, drains SW. 1 chain, thence curves to SE.
8.60	Wash, 5 lks. wide, 6 ins. deep, drains SE.
21.70	Wash, 6 lks. wide, 6 ins. deep, drains N. 85° E.
34.60	Wash, 40 lks. wide, 1 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
·	Set the iron post 22 ins. in the ground, cap mkd.
-	T1NR12W 4 S26 S35 1964
	Build a mound of stones N. of the iron post.
41.00	Enter wash, 6 1ks. wide, 6 ins. deep, drains irregularly East.
46.40	Leave same wash; thence over rough, rolling land.
66.40	Draw, drains NE.; asc. E. slope.
71.10	Low ridge, bears S. 20° E. and N.; desc. W. slope.
76.90	Wash, 8 lks. wide, 6 ins. deep, drains N.
80.00	The cor. of secs. 26, 27, 34 and 35.
	Land, broken and rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.

,		,	15.
	CHAIÑS	N. 0°01' W., bet. secs. 26 and 27.	
		Over rough, rolling land, through moderate undergrowth.	
	1.30	Begin desc. along E. slope.	
	18.30	Wash, 10 1ks. wide, 2 ft. deep, drains NW.; continue	
	10.50	over rough, rolling land.	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.	
		Set the iron post 22 ins. in the ground, cap mkd.	
		T1NR12W	
		s27 s26	
		1964	
		Build a mound of stones W. of the iron post.	
	41.40	Begin desc. over N. slope.	
	46.00	Wash, 20 1ks. wide, 2 ft. deep, drains irregularly N.	
	49.40	Leave same wash, drains NE.	
	62.80	Wash, 15 1ks. wide, with 3 ft. banks, drains SE.	
	80.00	Point for the cor. of secs. 22, 23, 26 and 27.	
		Set the iron post 22 ins. in the ground, cap mkd.	
		T1NR12W <u>S22 S23</u> S27 S26 1964	
		Build a mound of stones W. of the iron post.	
		Land, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, moderate creosote brush and cacti.	
		From the cor. of secs. 23, 24, 25 and 26.	
		N. 89°55' W., bet. secs. 23 and 26.	
	•	Over rolling land.	
	11.60	Wash, 12 1ks. wide, 1 ft. deep, drains S. 25° W.	
	18.10	Wash, 10 1ks. wide, 1 ft. deep, drains S. 20° E.	
	34.90	Draw, drains N. 20° W.; thence along N. slope with numerous draws draining N.	
	39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.	
		Set the iron post 22 ins. in the ground, cap mkd.	
		T1NR12W 1 S23 S26 1964	

-			17.
	CHAINS		
	39.99	Point for the ½ sec. cor. of secs. 14 and 23.	
		Set the iron post 22 ins. in the ground, cap mkd.	
		T1NR12W	
		$\frac{1}{4} \frac{\text{S}14}{\text{S}23}$	
		1964	
		Build a mound of stones N. of the iron post.	
		Continue over nearly level land.	
	79.98	The cor. of secs. 14, 15, 22 and 23.	
		Land, nearly level. Soil, shallow and stony. Timber, scattered palo verde and ironwood. Undergrowth, moerate creosote brush and cacti.	
		N. 0°01' W., bet. secs. 14 and 15.	
		Over nearly level land, through moderate undergrowth.	
	18.00	Desc. gentle N. slope.	
·	21.20	Wash, 20 lks. wide, 2 ft. deep, drains irregularly W.	
	29.40	Begin desc. over gentle NW. slope.	
	30.70	Wash, 20 lks. wide, 1 ft. deep, drains SW.	
	35.60	Wash, 40 lks. wide, with 3 ft. banks, drains irregularly SW.	
	40.00	Point for the ½ sec. cor. of secs. 14 and 15.	
		Set the iron post 22 ins. in the ground, cap mkd.	
		TLNR12W	
		な 	
	•	1964	
		Build a mound of stones W. of the iron post.	
·	41.80	Begin asc. over gentle SE. slope.	
	42.50	Thence over gently rolling land.	
	80.00	Point for the cor. of secs. 10, 11, 14 and 15.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T1NR12W <u>\$10</u> \$11 <u>\$15</u> \$14 1964	
		Build a mound of stones W. of the iron post.	
		Land, gently rolling. Soil, shallow and stony. Timber, scattered palo verde and ironwood Undergrowth, moderate creosote brush and cacti.	
	•		

18		Subdivision, T. 1 N., R. 12 W., Arizona
10	CHAINS	
		From the cor. of secs. 11, 12, 13 and 14.
		N. 89°55' W., bet. secs. 11 and 14.
		Over gently rolling land, through scattered undergrowth.
	1.10	Draw, drains N. 15° W.; asc. gentle E. slope.
	12.90	Low spur, slopes S.; desc. gentle SW. slope.
	30.50	Low spur, slopes S.; desc. gentle W. slope.
	40.00	Point for the ½ sec. cor. of secs. 11 and 14.
		Set the iron post 20 ins. in the ground, cap mkd.
		T1NR12W
		½ <u>S11</u> S14
		1964
		Build a mound of stones N. of the iron post.
	45.70	Wash, 15 1ks. wide, 2 ft. deep, drains SW.
	50.00	Wash, 35 1ks. wide, 1 ft. deep, drains SW.
	71.60	Track road, bears NE. and SW.
	80.00	The cor. of secs. 10, 11, 14 and 15.
		Land, gently rolling. Soil, shallow and stony. Timber, scattered palo verde and ironwood. Undergrowth, moderate creosote brush and cacti.
		N. 0°01' W., bet. secs. 10 and 11.
		Over nearly level land, through scattered undergrowth.
	3.90	Track road, bears NE. and SW.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.
		Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
		T1NR12W
		\$10 \$11
		1964
		Build a mound of stones W. of the iron post.
	48.00	Begin asc. over gentle SE. slope.
	54.00	Low spur, slopes SW.; desc. gentle NW. slope.
	60.50	End of desc.; thence over nearly level land.
	74.00	Track road, bears NE. and SW.
	80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	1	

CHAINS	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W <u>S 3 S 2</u> S10 S11 1964
	Build a mound of stones W. of the iron post.
:	Land, gently rolling. Soil, shallow and stony. Timber, scattered palo verde and ironwood. Undergrowth, moderate creosote brush and cacti.
-	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°54' W., bet. secs. 2 and 11.
	Over gently rolling land, through scattered undergrowth.
8.70	Wash, 10 1ks. wide, 1 ft. deep, drains N. 30° E.; asc. SE. slope.
16.70	Low ridge, bears S. and N. 30° W.
23.50	Small draw, drains NW.; desc. W. slope.
36.40	Begin asc. over NE. slope.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T1NR12W
	$\frac{5.2}{4.511}$
	1964
40.50	Low spur, slopes N. 30° W.; desc. gentle W. slope.
48.60	Track road, bears NE. and SW.
80.02	The cor. of secs. 2, 3, 10 and 11.
	Land, gently rolling. Soil, shallow and stony. Timber, scattered palo verde and ironwood. Undergrowth, scattered to moderate creosote brush and cacti.
	and Cacti.
	N. 0°01' W., bet. secs. 2 and 3.
	Over nearly level land, through moderate undergrowth.
4.10	Wash, 10 lks. wide, 1 ft. deep, drains irregularly W.; asc. gentle S. slope.
17.30	Wash, 12 lks. wide, 1 ft. deep, drains SW.
31.50	Wash, 20 lks. wide, 6 ins. deep, drains irregularly W.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 2 and 3.

Subdivision, T $_{ullet}$ 1 N., R. 12 W., Arizona

	basarvision, 1. I w., R. 12 w., Allzona	20
 CHAINS		20.
	Set the iron post 22 ins. in the ground, cap mkd.	
	T1NR12W	
	s 3 s 2 1964	
	Build a mound of stone W. of the iron post.	
40.80	Wash, 10 1ks. wide, 2 ft. deep, drains SW.	
43.40	Wash, 30 1ks. wide, 2 ft. deep, drains S. 30° W.	
45.10	Wash, 25 1ks. wide, 2 ft. deep, drains SW	
80.13	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.	
	Land, gently rolling. Soil, shallow and rocky. Timber, scattered palo verde and ironwood. Undergrowth, moderate creosote brush and cacti.	
	From the Std. cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented by an iron post as described in the official record.	
	N. 0°02' W., bet. secs. 33 and 34.	
	Over rolling and hilly land, through scattered undergrowth.	
6.30	Track road, bears SE. and N. 60° W.	
9.00	Cabin, bears W., 2.00 chs. dist.	
11.40	Draw, drains SW.; asc. gentle S. slope.	
26.60	Wash, 15 lks. wide, 1 ft. deep, drains W.; asc. S. slope.	
32.70	Small knoll on spur sloping S.; desc. N. slope.	
37.30	Begin asc. over steep SW. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.	
	Set the iron post 18 ins. in the ground, cap mkd.	
	T1NR12W	
	な S33[S34 1964	
	Build a mound of stones W. of the iron post.	
43:30	Spur, slopes W.; desc. NW. slope.	
45.30	Spur, slopes N. 80° W.	
45.80	Draw, drains SW.; asc. steep SW. slope.	
56.90	Ridge, bears SE. and NW.; desc. NE. slope.	

		<u> </u>	1 ·
	CHAINS		
6	57.80	Base of steep desc.; thence over rough, rolling land.	
7	76.80	Begin desc. over NW. slope.	
8	30.00	Point for the cor. of secs. 27, 28, 33 and 34.	
		Set the iron post 10 ins. in the ground, collar of stones to top, 3 ft. diam., cap mkd.	
	·	T1NR12W <u>S28 S27</u> S33 S34	
		1964	
		Land, mountainous. Soil, shallow and stony. Timber, scattered palo verde and ironwood in low areas. Undergrowth, scattered creosote brush and cacti.	
		From the cor. of secs. 26, 27, 34 and 35.	
		S. 89°58' W., bet. secs. 27 and 34.	
		Over rolling land, through scattered undergrowth.	
		Asc. E. slope.	
	2.20	Top of asc.; thence over rough, rolling land.	
	6.40	Low ridge, bears SE. and NW.	
1	15.50	Wash, 30 lks. wide, with 4 ft. banks, drains NE.	
2	29.80	Begin asc. over E. slope.	
3	32.70	Spur, slopes N. 10° W.; desc. W. slope.	
4	40.02	Point for the ½ sec. cor. of secs. 27 and 34.	
		Set the iron post 20 ins. in the ground, cap mkd.	
		T1NR12W 2 S27 S34	
		1964	
		Build a mound of stones N. of the iron post.	
4	41.00	Draw, drains NW.	
4	47.80	Wash, 25 lks. wide, 1 ft. deep, drains N.; asc. E. slope.	
-	53.60	Spur, slopes N.; desc. W. slope.	
-	57.50	Wash, 30 lks. wide, 1 ft. deep, drains N. 20° E.	l
	60.00	Wash, 10 1ks. wide, 1 ft. deep, drains N. 30° E.; asc. E. slope.	
	66.00	Begin desc. along top of spur sloping W.	
	72.60	Begin asc. over S. slope.	
	75.50	Low ridge, bears N. and S.; desc. broken W. slope.	
	2		

	80.04	The cor. of secs. 27, 28, 33 and 34.
		Land, broken and rolling.
		Soil, shallow and stony.
		Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		N. 0°02' W., bet. secs. 27 and 28.
		Over rolling land, through scattered undergrowth.
	0.30	Draw, drains NE.
	9.00	Spur, slopes NE.; desc. NW. slope.
	11.70	Draw, drains NE.; desc. over rolling land.
	22.40	Wash, 25 lks. wide, 1 ft. deep, drains NW.; asc. SW. slope.
	31.70	Spur, slopes N. 70° W.; desc. NE. slope.
	33.20	Draw, drains NW.; asc. SW. slope.
	38.20	Spur, slopes NW.; desc. N. slope.
	40.00	Point for the ½ sec. cor. of secs. 27 and 28.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W
		\$28 \$27 1964
		Build a mound of stones W. of the iron post.
	42.00	Bottom of desc.; thence over rough, rolling land.
	48.80	Wash, 15 lks. wide, with 4 ft. banks, drains irregularly North.
	55.40	Leave same wash, drains NW.
	61.30	Wash, 10 1ks. wide, 1 ft. deep, drains N. 75° W.
	66.10	Wash, 30 lks. wide, 1 ft. deep, drains W. for 1 chain, thence curves irregularly S.; asc. broken S. slope.
	73.40	Slope changes to rolling E.
	80.00	Point for the cor. of secs. 21, 22, 27 and 28.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W
	,	S21 S22 S28 S27 1964
		Build a mound of stones W. of the iron post.
		Land, rough, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.

CHAINS	From the cor. of secs. 22, 23, 26 and 27.		
	S. 89°58' W., bet. secs. 22 and 27.		
	Over gently rolling land, through scattered undergrowth.		
16.00			
16.00	Draw, drains SE.; asc. gentle E. slope.		
40.02	Point for the k sec. cor. of secs. 22 and 27.		
	Set the iron post 22 ins. in the ground, cap mkd.		
	T1NR12W 1/4 S22 S27		
	1964		
	Build a mound of stones N. of the iron post.		
60.00	Draw, drains N.		
75.00	Draw, drains S.		
80.04	The cor. of secs. 21, 22, 27 and 28.		
	Land, nearly level. Soil, stony loam. Timber, scattered palo verde. Undergrowth, scattered to moderate creosote brush and		
	cacti.		
	N. 0°02' W., bet. secs. 21 and 22.		
	Over gently rolling land, through moderate undergrowth; asc. gentle SE. slope.		
2.20	Low ridge, bears NE. and SW.; desc. NW. slope.		
5.20	Small draw, drains NE.		
7.70	Small draw, drains NW.		
8.50	Wash, 15 1ks. wide, 1 ft. deep, drains W.		
16.10	Wash, 80 lks. wide, with 4 ft. banks, drains W.		
25.30	Begin asc. over SE. slope.		
27.10	Top of asc.; thence over nearly level land.		
40.00	Point for the 1/2 sec. cor. of secs. 21 and 22.		
	Set the iron post 22 ins. in the ground, cap mkd.		
	T1NR12W		
	S21 S22 1964		
	Build a mound of stones W. of the iron post.		
48.90	Gully, 5 lks. wide, 4 ft. deep, drains SSE.		

	24.
CHAINS	
54.50	Same gully, 10 lks. wide, 2 ft. deep, drains SSW; asc. gentle SE. slope.
67.20	Top of asc., bears NE. and SW.; thence over nearly level land.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W S16 S15 S21 S22 1964
	Build a mound of stones W. of the iron post.
	Land, gently rolling. Soil, stony loam. Timber, scattered palo verde. Undergrowth, scattered to moderate creosote brush
	and cacti.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89°58' W., bet. secs. 15 and 22.
	Over nearly level land, through scattered undergrowth.
40.01	Point for the ½ sec. cor. of secs. 15 and 22.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W 1
	Build a mound of stones N. of the iron post.
46.80	Left bank of wash, bears N. 30° E. and S. 30° W.
47.10	Main channel of wash, 40 lks. wide, 2 ft. deep, drains S. 40° W.
53.30	Right bank of wash area, bears NE. and SW.; asc. gentle E. slope.
73.30	Low spur, slopes N. 10° E.
80.02	The cor. of secs. 15, 16, 21 and 22.
	Land, nearly level. Soil, stony loam. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	N. 0°02' W., bet. secs. 15 and 16.
	Over nearly level land, through scattered undergrowth.
16.00	Enter medium growth of creosote brush.
40.00	Point for the ½ sec. cor. of secs. 15 and 16.
1	

	CHAINS	Set the iron post 20 ins. in the ground, cap mkd.		
		T1NR12W		
		14		
		\$16 \$15 1964		
		Build a mound of stones W. of the iron post.		
		Continue over nearly level land, through medium growth of creosote brush.		
	80.00	Point for the cor. of secs. 9, 10, 15 and 16.		
		Set the iron post 22 ins. in the ground, cap mkd.		
T1NR12W S 9 S10 S16 S15 1964				
		Build a mound of stones W. of the iron post.		
		Land, nearly level. Soil, fine, sandy clay. Timber, none. Undergrowth, medium creosote brush, scattered cacti.		
		From the cor. of secs. 10, 11, 14 and 15.		
	,	S. 89°59' W., bet. secs. 10 and 15.		
		Over nearly level land, through medium creosote brush.		
	3.80	Track road, bears NE. and SW.		
	40.00	Point for the ½ sec. cor. of secs. 10 and 15.		
		Set the iron post 22 ins. in the ground, cap mkd.		
		T1NR12W 1 S10 4 S15		
		\$\frac{4}{\sum \sqrt{\sq}}}}}}}}}}}\signtimes\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sq}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}		
		Build a mound of stones N. of the iron post.		
		Continue over nearly level land, through medium creosote brush.		
	80.00	The cor. of secs. 9, 10, 15 and 16.		
		Land, nearly level. Soil, fine, sandy clay. Timber, scattered ironwood. Undergrowth, medium creosote brush.		
	N. 0°02' W., bet. secs. 9 and 10.			
		Over nearly level land, through medium creosote brush.		
	40.00	Point for the ½ sec. cor. of secs. 9 and 10.		

CHAINS	
CHAINS	Set the iron post 22 ins. in the ground, cap mkd
	T1NR12W
	\$ 9 \$10 1964
	Build a mound of stones W. of the iron post.
62.90	Wash, 15 1ks. wide, 2 ft. deep, drains SW.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W S 4 S 3 S 9 S10 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, fine, sandy clay. Timber, scattered ironwood. Undergrowth, medium creosote brush.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°59' W., bet. secs. 3 and 10.
	Over nearly level land, through medium creosote brush.
15.50	Wash, 12 1ks. wide, with 3 ft. banks, drains S. 75° W.
23.00	Wash, 7 lks. wide, 2 ft. deep, drains SW.
39.80	Wash, 10 1ks. wide, 2 ft. deep, drains S. 60° E., curving to SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set the iron post 18 ins. in the ground, cap mkd.
	T1NR12W 1 S 3 1 S10 1964
	Build a mound of stones N. of the iron post.
	Continue over nearly level land, through dense creosote brush.
80.00	The cor. of secs. 3, 4, 9 and 10.
	Land, nearly level. Soil, fine, sandy clay. Timber, scattered ironwood. Undergrowth, medium to dense creosote brush.
·	N. 0°02' W., bet. secs. 3 and 4.
	Over nearly level land, through medium creosote brush.

CHAINS 0.80	Wash, 10 lks. wide, 6 ins. deep, drains S. 70° W.
	Wash, 5 lks. wide, 1 ft. deep, drains S. 80° W.
11.70	
40.00	Point for the ½ sec. cor. of secs. 3 and 4.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	s 4 s 3 1964
	Build a mound of stones W. of the iron post.
75.30	Wash, 7 lks. wide, with 3 ft. banks, drains irregularly W.; asc. gentle S. slope.
80.04	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
	Land, nearly level. Soil, fine, sandy clay.
	Timber, none. Undergrowth, medium creosote brush.
	ondergrowth, median creasure brasis.
	From the Std. cor. of secs. 32 and 33 on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., as described in the official record.
	N. 0°02' W., bet. secs. 32 and 33.
	Over gently rolling land, through medium creosote brush and scattered cacti.
1.50	Bladed road, bears S. 70° E. and NW.
4.70	Base of hills; asc. SW. slope.
23.90	Spur, slopes SW.; thence along W. slope.
28.60	Begin desc. over NW. slope.
33.70	Draw, drains W.; asc. SW. slope.
40.00	Point for the ½ sec. cor. of secs. 32 and 33.
	Set the iron post 8 ins. in the ground to bedrock, mound of stones to top, cap mkd.
	T1NR12W
	\$32 \$33 1964
	Build a mound of stones W. of the iron post.
61.10	Ridge, bears SE. and NW.; desc. NE. slope.
77.90	Base of hill, bears E. and W.; thence over rolling land.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.

28

BOOK 4748 Subdivision, T. 1 N., R. 12 W., Arizona

CHAINS	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
·	S29 S28 S32 S33
	1964
	Build a mound of stone W. of the iron post.
	Land, hilly. Soil, shallow and stony. Timber, scattered palo verde in wash areas. Undergrowth, medium creosote brush and scattered cacti.
	From the cor. of secs. 27, 28, 33 and 34.
	West, bet. secs. 28 and 33.
	Over rough, rolling land, through scattered undergrowth.
1.00	Draw, drains SE.; asc. broken NE. slope.
15.00	Ridge, bears SE. and NW.; desc. SW. slope.
23.10	Draw, drains SSE.; thence along S. slope.
27.10	Low ridge, bears N. and S.; desc. SW. slope.
28.90	Draw, drains S.; asc. SE. slope.
31.90	Spur, slopes N.; desc. W. slope.
33.90	Draw, drains N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set the iron post 18 ins. in the ground, cap mkd.
	T1NR12W
	S28 S33
	1964
	Build a mound of stones N. of the iron post.
41.10	Spur, slopes NW.; desc. broken SW. slope.
61.00	Wash, 35 lks. wide, 1 ft. deep, drains SSE.; desc. gentle W. slope.
63.20	Bladed road, bears SSE. and NNW.
67.00	Enter wash, 10 lks. wide, 1 ft. deep, drains irregularly W.
72.00	Leave same wash, drains S. 80° W. from irregularly E.
80.00	The cor. of secs. 28, 29, 32 and 33.
	Land, rough and rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.

CHAINS	N. 0°02' W., bet. secs. 28 and 29.
	Over rolling land, through medium undergrowth.
9.80	Wash, 290 lks. wide, 2 ft. deep, drains SW.
17.00	Draw, drains SE.; asc. S. slope.
24.80	Rocky ledge, bears S. 70° E. and N. 70° W.
32.70	Wash, 25 lks. wide, 1 ft. deep, drains S. 20° E.
40.00	Point for the ½ sec. cor. of secs. 28 and 29.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	\$\frac{7}{\$29\\$28}
	1964
	Build a mound of stones W. of the iron post.
43.60	Asc. S. slope.
45.20	Spur, slopes W.
46.80	Wash, 10 lks. wide, 1 ft. deep, drains SW.
60.60	Asc. SW. slope.
63.80	Spur, slopes W.; desc. NW. slope.
65.90	Draw, drains irregularly SW.; asc. S. slope of hill.
77.20	Top of hill bears E., 50 lks.; desc. NW. slope.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 18 ins. in the ground, cap mkd.
	T1NR12W S20 S21
	\$29 \$28 1964
,	Build a mound of stones W. of the iron post.
	Land, rough and hilly.
	Soil, shallow and stony. Timber, scattered palo verde.
	Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°59' W., bet. secs. 21 and 28.
	Over rolling land, through scattered undergrowth.
	Asc. SE. slope.
2,90	Low ridge, bears N. and S.; desc. SW. slope.

6.60	Begin desc. over gentle W. slope.	
15.40	Track road, bears S. 40° E. and N. 30° W.	
18.80	Wash, 60 1ks. wide, 3 ft. deep, drains S. 10° E.	
20.80	Bladed road, bears N. 15° E. and S. 20° W.	
22.40	Wash, 5 1ks. wide, 8 ins. deep, drains SSE.	
34.00	Draw, drains irregularly SE.	
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.	
	Set the iron post 18 ins. in the ground, cap mkd.	
	T1NR12W 1/4 S21 1964	
	Build a mound of stones N. of the iron post.	
44.80	Draw, drains ESE.	
54.10	Spur, slopes SE.	
57.80	Wash, 20 lks. wide, 1 ft. deep, drains irregularly NE.	
66.90	Same wash, 8 1ks. wide, 6 ins. deep, drains irregularly E. from S. 70° W.	
78.90	Ridge on hill, bears N. 30° E. and S. 30° W.; desc. steep W. slope.	
80.04	The cor. of secs. 20, 21, 28 and 29.	
	Land, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.	
	N. 0°02' W., bet. secs. 20 and 21.	
	Over rolling land, through scattered undergrowth.	
2.90	Spur, slopes N. 70° W.; desc. N. slope.	
11.30	Bottom of hill; thence over rolling land.	
30.80	Draw, drains W.; asc. gentle SW. slope.	
40.00	Point for the ½ sec. cor. of secs. 20 and 21.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T1NR12W	
	\$20 \$21 1964	
	Build a mound of stones W. of the iron post.	
45.10	Spur, slopes W.; desc. NW. slope.	

2	1	

CHAINS	The standard of small market 1411
67.50	West edge of small rocky hill.
76.60	Track road, bears NE. and SW.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	<u>S17 S16</u> S20 S21
	. 1964
	Build a mound of stones W. of the iron post.
	Land, rolling. Soil, shallow and stony.
	Timber, scattered palo verde.
	Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 15, 16, 21 and 22.
. !	West, bet. secs. 16 and 21.
	Over nearly level land, through scattered undergrowth.
23.70	Bladed road, bears S. 25° E. and N. 25° W.
40.00	Point for the ½ sec. cor. of secs. 16 and 21.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	½ <u>\$16</u> \$21
,	1964
٠	Build a mound of stones N. of the iron post.
75.50	Track road, bears NE. and SW.
80.00	The cor. of secs. 16, 17, 20 and 21.
	Land, nearly level. Soil, fine, sandy clay.
	Timber, scattered palo verde.
	Undergrowth, scattered creosote brush and cacti.
	N. 0°02' W., bet. secs. 16 and 17.
	Over nearly level land, through scattered creosote brush and patches of catclaw.
19.00	Enter dense catclaw and mesquite, bears E. and S. 70° W.
23.00	Leave dense catclaw; enter scattered creosote brush and catclaw.
40.00	Point for the 4 sec. cor. of secs. 16 and 17.
	Set the iron post 22 ins. in the ground, cap mkd.

-	
CHAINS	T1NR12W
	1/4
	S17 S16 1964
·	Build a mound of stones W. of the iron post.
49.20	Track road, bears irregularly E. and W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	S 8 S 9 S17 S16
	1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, fine, sandy clay.
	Timber, scattered clumps of mesquite. Undergrowth, scattered creosote brush and scattered
	to dense catclaw.
٥	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°59' W., bet. secs. 9 and 16.
	Over nearly level land, through medium to dense creosote brush and scattered catclaw.
22.80	Track road, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	$\frac{1}{4} \frac{S 9}{S16}$
	1964
	Build a mound of stones N. of the iron post.
50.00	Bladed road, bears SE. and NW.
80.00	The cor. of secs. 8, 9, 16 and 17.
	Land, nearly level. Soil, fine, sandy clay.
	Timber, scattered mesquite, medium to dense creosote brush and scattered catclaw.
	N 0°02 W bot good 8 and 0
	N. 0°02' W., bet. secs. 8 and 9.
21.90	Over nearly level land, through medium creosote brush. Wash, 7 lks. wide, 6 ins. deep, drains SW.
40.00	
-0.00	Point for the ½ sec. cor. of secs. 8 and 9.

CHAINS	
CHAINS	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	s 8 s 9 1964
	Build a mound of stones W. of the iron post.
45.40	Wash, 7 lks. wide, 8 ins. deep, drains irregularly W.
45.80	Wash, 7 lks. wide, 1 ft. deep, drains irregularly W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W S 5 S 4 S 8 S 9 1964
	Build a mound of stones W. of the iron post.
	Land, nearly level. Soil, fine, sandy clay. Timber, none. Undergrowth, medium creosote brush.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°56' W., bet. secs. 4 and 9.
	Over nearly level land, through medium creosote brush.
2.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.
40.00	Point for the ½ sec. cor. of secs. 4 and 9.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	1 S 4 S 9
	1964
	Build a mound of stones N. of the iron post.
48.80	Wash, 9 lks. wide, 8 ins. deep, drains irregularly NW.
51.50	Wash, 8 lks. wide, 8 ins. deep, drains NW.
74.90	Bladed road, bears S. 25° E. and N. 25° W.
80.00	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level. Soil, fine, sandy clay. Timber, none. Undergrowth, medium creosote brush and scattered catclaw.

<u> </u>		34
CHAINS	N. 0°02' W., bet. secs. 4 and 5.	
	Over nearly level land, through medium creosote brush.	
6.50	Wash, 8 lks. wide, 8 ins. deep, drains irregularly W.	
15.70	Wash, 10 1ks. wide, 1 ft. deep, drains irregularly W.	
16.20	Bladed road, bears S. 25° E. and N. 25° W.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.	
	Set the iron post 22 ins. in the ground, cap mkd.	
:	T1NR12W	
	s 5 s 4 1964	
	Build a mound of stones W. of the iron post.	
76.80	Wash, 7 lks. wide, 6 ins. deep, drains irregularly W.	
79.50	Wash, 8 lks. wide, 1 ft. deep, drains W.	
80.12	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.	
	Land, nearly level. Soil, fine, sandy clay. Timber, none. Undergrowth, medium creosote brush and scattered catclaw.	-
	From the Std. cor. of secs. 31 and 32 on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., as described in the official record.	
:	N. 0°03' W., bet. secs. 31 and 32.	
	Over rolling land, through scattered undergrowth.	
8.00	Asc. SE. slope.	
16.20	Low spur, slopes E.; desc. NE. slope.	
23.90	Base of slope; thence over rolling land.	
37.90	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T1NR12W	
	S31 S32 1964	
	Build a mound of stones W. of the iron post.	
46.40	Small draw, drains S. 80° E.	

		·	3	5.
	CHAINS			
	49.30	Wash, 10 lks. wide, 1 ft. deep, drains ESE.	,	
	59.40	Wash, 10 lks. wide, 1 ft. deep, drains SE.		
	66.80	Wash, 15 1ks. wide, 1 ft. deep, drains S. 30° E.		,
	68.20	Wash, 35 lks. wide, with 3 ft. banks, drains S. 40°	E.	
	72.50	Track road, bears SE. and NW.; asc. gentle S. slope	•	
	80.00	Point for the cor. of secs. 29, 30, 31 and 32.		
		Set the iron post 18 ins. in the ground, cap mkd.		
		T1NR12W <u>S30</u> <u>S29</u> <u>S31</u> <u>S32</u> 1964		
		Build a mound of stones W. of the iron post.		
		Land, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush, catclaw and cacti.	,	
		From the cor. of secs. 28, 29, 32 and 33.		
		S. 89°59' W., bet. secs. 29 and 32.		
	•	Over rolling land, through scattered undergrowth.		
	5.40	Wash, 50 lks. wide, with 4 ft. banks, drains S. 40° asc. SE. slope.	W.;	
	11.70	Wash, 35 lks. wide, 1 ft. deep, drains S. 30° W.		
	13.60	Draw, drains SSW.		
	15.30	Draw, drains SSE.		
	34.30	Small draw, drains S. 70° E.		
İ	38.20	Small draw, drains irregularly SE.	,	
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.		
		Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.	,	
		T1NR12W 2 S29 S32 1964		
	53.00	Low spur, slopes S.; thence over broken S. slope.	,	
	64.00	Wash, 8 1ks. wide, 1 ft. deep, drains S.		
	67.60	Low spur, slopes S.; desc. gentle SW. slope.		
	71.20	Draw, drains S. 50° W.		
			l	

· · · · · · · · · · · · · · · · · · ·	3
80.00	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	S. 89°58' W., bet. secs. 30 and 31.
	Over rolling land, through scattered undergrowth. Desc. gentle W. slope.
4.80	Small draw, drains SW.
9.00	Track road, bears NE. and SW.
9.80	Small draw, drains S. 20° W.
11.80	Wash, 40 1ks. wide, with 3 ft. banks, drains S. 30° E.
16.00	Asc. E. slope.
20.00	Begin asc. over broken E. slope.
23.00	Small draw, drains S. 20° E.
27.90	Rim, bears SE. and NW.
28.70	Ridge, bears S. 30° E. and N. 30° W.; desc. broken W. slope.
39.60	Wash, 25 1ks. wide, 2 ft. deep, drains N. 30° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
	Set the iron post 20 ins. in the ground, cap mkd.
	T1NR12W 530 331 1964
	Build a mound of stones N. of the iron post.
41.60	Wash, 15 1ks. wide, 2 ft. deep, drains irregularly N. 30° E.
47.80	Draw, drains irregularly NE.
52.40	Draw, drains irregularly NE.
70.60	Small draw, drains N.
78.70	Right bank of wash, bears S. 30° W. and N. 30° W.
79.70	Center of wash, drains N. 20° E. curving NE.
79.83	Point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., from which
	The witness cor. bears North 1.80 chs. dist., monumented by an iron post 2 ins. diam., as described in the official record.

3	7
٦,	,

_		3
	CHAIÑS	Land, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		From the cor. of secs. 29, 30, 31 and 32.
		N. 0°03' W., bet. secs. 29 and 30.
		Over rolling land, through scattered creosote brush and cacti.
	1.70	Wash, 7 lks. wide, 8 ins. deep, drains W.
	9.20	Wash, 7 lks. wide, 8 ins. deep, drains W.
	20.00	Small draw, drains S. 70° W.; asc. SW. slope.
	39.50	Wash, 8 lks. wide, 1 ft. deep, drains SW.
	40.00	Point for the ½ sec. cor. of secs. 29 and 30.
		Set the iron post over an "X" chiseled on bedrock, mound with stones to top, cap mkd.
		T1NR12W
		な S30 S29 1964
	54.40	Spur, slopes W.; desc. NW. slope.
	63.00	Spur, slopes W.
	67.50	Wash, 25 lks. wide, 2 ft. deep, drains irregularly W.; thence over broken W. slope.
	80.00	Point for the cor. of secs. 19, 20, 29 and 30.
		Set the iron post 4 ins. in the ground to bedrock, mound with stones to top, cap mkd.
		T1NR12W <u>S19</u> S20 S30 S29 1964
	,	Land, broken and rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		From the cor. of secs. 20, 21, 28 and 29.
		S. 89°54' W., bet. secs. 20 and 29.
		Over broken and mountainous land.
		Desc. SW. slope through scattered undergrowth.
	8.50	Draw, drains S. 20° E.; asc. NE. slope.

2	O	
.)	o	

 	30
CHAINS	
17.30	Small draw, drains NE.
22.30	Small draw, drains N. 70° E.
40.00	Point for the ½ sec. cor. of secs. 20 and 29.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T1NR12W
52.70	Spur, slopes N. 20° W.; desc. steep NW. slope.
74.50	Base of mountain, bears N. and S.; continue desc. over NW. slope.
80.00	The cor. of secs. 19, 20, 29 and 30.
	Land, mountainous. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	S. 89°58' W., bet. secs. 19 and 30.
	Over rolling land, through scattered undergrowth.
	Desc. broken W. slope.
37.50	Wash, 15 lks. wide, with 3 ft. banks, drains S. 20° W.
40.00	Point for the ½ sec. cor. of secs. 19 and 30.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W 2 S19 3 S30 1964
	Build a mound of stones N. of the iron post.
56.00	Begin over nearly level land.
79.66	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
	Land, gently rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over rolling land, through scattered undergrowth.
10.30	Small draw, drains NW.

	39.
CHAINS	
14.10	Small draw, drains N. 20° W.
27.80	Wash, 20 1ks. wide, with 3 ft. banks, drains S. 70° W.
32.70	Wash, 6 lks. wide, 6 ins. deep, drains SW.
40.00	Point for the ½ sec. cor. of secs. 19 and 20.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T1NR12W \$ S19 S20
	1964
58.70	Begin asc. over S. slope of a hill.
62.30	Spur, slopes E.; desc. N. slope.
63.30	Bottom of desc.; asc. gentle S. slope.
71.20	Draw, drains SW.; asc. along E. slope.
77.50	Top of asc.; thence over rolling E. slope.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 20 ins. in the ground, cap mkd.
•	T1NR12W S18 S17 S19 S20 1964
	Build a mound of stones W. of the iron post.
	Land, rolling. Soil, shallow and stony. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
·	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°52' W., bet. secs. 17 and 20.
	Over nearly level land, through scattered undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	1/4 S17 S20 1964
	Build a mound of stones N. of the iron post.
51.50	Begin asc. over gentle E. slope.
72.00	Spur, slopes N.; desc. gentle W. slope.
ļ	1

<u> </u>	/····	4
	CHAINS	
	74.00	Small draw, drains N. 30° W.; thence over gently rolling land.
	77.10	Small draw, drains NE.; asc. gentle E. slope.
	80.00	The cor. of secs. 17, 18, 19 and 20.
		Land, nearly level. Soil, fine, sandy clay. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		N. 89°58' W., bet. secs. 18 and 19.
		Asc. over E. slope, through scattered undergrowth.
	5.50	Ridge, bears S. 30° E. and N. 30° W.; desc. NW. slope.
	11.40	Base of desc., bears NE. and SW.
	13.70	Wash, 15 lks. wide, 1 ft. deep, drains SW.; thence over gently rolling land.
	20.50	Thence along small wash draining irregularly W.
	31.00	Leave same wash, drains S. 70° W. from irregularly E.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
	·	Set the iron post 18 ins. in the ground, cap mkd.
		T1NR12W 1 S18 3 S19 1964
		Build a mound of stones N. of the iron post.
	:	Thence over nearly level land.
	79.46	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
		Land, nearly level. Soil, fine, sandy clay. Timber, scattered palo verde. Undergrowth, scattered creosote brush and cacti.
		From the cor. of secs. 17, 18, 19 and 20.
		N. 0°03' W., bet. secs. 17 and 18.
		Over nearly level land, through scattered undergrowth.
	3.20	Small draw, drains S. 70° E.; asc. SW. slope.
	4.50	Low spur, slopes W.; desc. NW. slope.
	6.80	Small draw, drains irregularly NE.; desc. gentle N. slope.
	10.70	Wash, 12 1ks. wide, 1 ft. deep, drains NE.

1.	1
4	1

	CHAINS	T The second second second second second second second second second second second second second second second
	22.50	Wash, 5 1ks. wide, 8 ins. deep, drains NE.
	40.00	Point for the ½ sec. cor. of secs. 17 and 18.
		Set the iron post 22 ins. in the ground, cap mkd.
		T1NR12W
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
		\$18 \$17 1964
		Build a mound of stones W. of the iron post.
		Thence over nearly level land.
	61.70	Track road, bears E. and W.
	72.00	Enter scattered to dense catclaw and mesquite.
	80.00	Point for the cor. of secs. 7, 8, 17 and 18.
		Set the iron post 20 ins. in the ground, cap mkd.
		T1NR12W
		<u>S 7 S 8</u> S18 S17
		1964
		Build a mound of stones W. of the iron post.
	*	Land, gently rolling to nearly level. Soil, sandy and gravelly.
		Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote brush and cacti.
	-	
		From the cor. of secs. 8, 9, 16 and 17.
		S. 89°53' W., bet. secs. 8 and 17.
		Over nearly level land, through scattered undergrowth.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
		Set the iron post 22 ins. in the ground, cap mkd.
	·	T1NR12W 1/4 S 8 S17
		4 S17 1964
		Build a mound of stones N. of the iron post.
	80.00	The cor. of secs. 7, 8, 17 and 18.
		Land, nearly level.
	,	Soil, fine, sandy clay. Timber, none.
		Undergrowth, scattered creosote brush and catclaw.
		N. 89°55' W., bet. secs. 7 and 18.
		Over nearly level land, through scattered undergrowth.
1	1	1

r ==	
40.00	Point for the ½ sec. cor. of secs. 7 and 18.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	1 INKIZW 1/4 S 7 5 18
	⁴ S18 1964
	1904
	Build a mound of stones N. of the iron post.
	Continue over nearly level land, through medium creosote brush.
79.44	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post 2 ins. diam., as described in the official record.
	Land, nearly level.
	Soil, fine, sandy clay and gravel. Timber, scattered mesquite.
	Undergrowth, scattered creosote brush and catclaw.
1 1	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over nearly level land, through dense creosote brush
	and scattered catclaw.
16.00	Catclaw becomes widely scattered.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	s 7 s 8
:	1964
	Build a mound of stones W. of the iron post.
1	Continue over nearly level land, through dense creosote brush and scattered catclaw.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set the iron post 22 ins. in the ground, cap mkd.
	T1NR12W
	S 6 S 5
	1964
	Build a mound of stones W. of the iron post.
	Land, nearly level.
	Soil, fine, sandy clay and gravel.
	Timber, none. Undergrowth, dense creosote brush and scattered catclaw.

 		43.
CHAINS		
	From the cor. of secs. 4, 5, 8 and 9.	
	S. 89°52' W., bet. secs. 5 and 8.	
	Over nearly level land, through medium creosote brush.	
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.	
	Set the iron post 22 ins. in the ground, cap mkd.	
,	T1NR12W	
	¹ / ₄ S 5 S 8	
	1964	
	Build a mound of stones N. of the iron post.	
79.98	The cor. of secs. 5, 6, 7 and 8.	
	Land, nearly level.	
	Soil, fine, sandy clay and gravel. Timber, none.	
	Undergrowth, medium creosote brush and scattered	
	catclaw.	
	N. 89°53' W., bet. secs. 6 and 7.	-
	Over nearly level land, through medium creosote brush	
	and scattered catclaw.	
40.00	Point for the ½ sec. cor. of secs. 6 and 7.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T1NR12W	
	\frac{S 6}{S 7}	
	1964	
	Build a mound of stones N. of the iron post.	
56.00	Begin asc. over gentle E. slope.	
79.39	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of	
	the Tp., monumented by an iron post 2 ins. diam., as described in the official record.	
	Land, nearly level.	
	Soil, sandy clay and gravel. Timber, none.	
	Undergrowth, medium greasewood and scattered catclaw.	
	From the cor. of secs. 5, 6, 7 and 8.	
	N. 0°03' W., bet. secs. 5 and 6.	
	Over nearly level land, through medium to dense greosote brush and scattered catclaw.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.	
	Set the iron post 22 ins. in the ground, cap mkd.	
		1

Township 1 North, Range 12 West, G&SRM, Arizona

44. CHAINS T1NR12W s 6 s 5 1964 from which A water well bears N. 35° E., 2.46 chs. distant. Build a mound of stones W. of the iron post. 43.70 Fence, bears E. and W. The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., monumented by an iron post as described in 80.24 the official record. Land, nearly level. Soil, fine, sandy clay. Timber, none. Undergrowth, dense creosote brush and scattered catclaw. General Description

The elevation of Township 1 North, Range 12 West, ranges from a low of 1,400 feet to a high of 2,375 feet above sea level in the southwest portion. The northwest portion is nearly level at about 1,500 feet average elevation. The remainder of the township consists of rolling land and small hills. The soil is a fine, sandy clay in the flat areas and shallow, stony soil in the hilly areas. The general drainage is to the south. There is a scattered growth of palo verde and ironwood trees in the major wash areas, while creosote brush and

No mining activity was noted within the township during this survey. The land is primarily used for very limited grazing of livestock.

scattered catclaw, also saguaro and other cacti are

prominent in the more level areas.



BOOK 4748

Form 4-680 (June 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Louis D. Gilbert	Transit
Lyman W. Polacca	Notes
David Sakiestewa	Flagman
Robert F. Johnson	Crew Chief
Control of the second s	

	7

BOOK 4748

CERTIFICATE OF SURVEY

I, Boyd S. Owens	, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the	11thday of February , 1963 ,
I have surveyed the east boundary and the	subdivisional lines of Township
1 North, Range 12 West,	
•	
of the Gila & Salt River Meridian, in the	State of Arizona , which
are represented in the foregoing field notes as having be	een executed by me and under my direction;
and that said survey has been made in strict conformity	with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of	the United States, and in specific manner
described in the foregoing field notes.	
February 15, 1965 (Date)	Royd & Orvers (Gadastral Surveyor)
(Date)	((Gadastrai Surveyor)
(Date)	(Cadastral Surveyor)
CERTIFICATE OF A	PPROVAL
SUBMITTED FOR APPROVAL Date NOV 1 1965	BUREAU OF LAND MANAGEMENT, Washington, D. C.
The foregoing field notes of the survey of the e	ast boundary and the subdivisional
lines of Township 1 North, Range 12 Wes	t, of the Gila & Salt River Meridia
in the State of Arizona,	
executed by Boyd S. Owens, Cadastral Surve	yor,
having been critically examined and found correct, are	hereby approved.
JAN 3 1966	- 5/ -
(Date)	(Chief, Division of Engineering)
CERTIFICATE OF TR	ANISCRIPT
CERTIFICATE OF TR	ANSCRIPT
I CERTIFY That the foregoing transcript of the field no	otes of the above-described surveys in
	, is a true copy of the original field notes.
(Date)	(Chief, Division of Engineering)