BOOK4767 ORIGINAL

Form 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

METES AND BOUNDS	SURVEY
of	
. Congress Cemete	ery (Lot 20)
in	
Section 23	
Township 10 North, Ran	nge 6 West
	iver Meridian,
n the State of Arizona	
EXECUTED	
Boyd S. Owens, Cadast	ral Surveyor
Inder special instructions datedMarch 18	, 19 <u>65</u> , which provided for the surveys
ncluded under Group Number424, appro	ved <u>March</u> 19, 1965
nd assignment instructions datedDecember 20	, 19 65
Survey commencedJanuary 4	4 19.66
	,

Survey completed _____ January 6 _____, 19 66

BOOK 4767 INDEX DIAGRAM

Townsh	ip10 No	orth	, Range <u>6</u>	West	, , , , , , , , , , , , , , , , , , ,
6	8	4	8	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	28	24
30	29	28	27	26	25
31	32	33	84	85	36

CHAINS

Section 23, as shown on the plat approved May 5, 1905, was surveyed in 1904 by J. F. Hesse. The south boundary was dependently resurveyed in 1952 by Ty White as shown on the plat accepted January 23, 1953.

The following notes are those of a metes and bounds survey in the StSWt of Section 23.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, and the Special Instructions dated March 18, 1965.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Direction of all lines refer to the true meridian and were determined by angles from the line between Sections 23 and 26. Each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the corner of Sections 22, 23, 26 and 27 is: Latitude 34°11'25" North and Longitude 112°50'53" West, as determined by traverse from the corner of Sections 25, 26, 35 and 36 as shown on the plat approved January 23, 1953.

The mean magnetic declination was found to be $14\frac{1}{2}^{\circ}$ East.

Metes and Bounds Survey Sec. 23, T. 10 N., R. 6 W., Arizona

At point for Cor. No. 1 of Congress Cemetery

Set the iron post 24 ins. in the ground, cap mkd.

T10N R6W S23 COR 1 CONGRESS CEM 1966

from which

The cor. of secs. 22, 23, 26 and 27 bears S. 42°46' W., 25.35 chs. dist., monumented by an iron post, 2 ins. diam., set mkd. and witnessed as described in the official record of the 1952 survey.

The NW. fence cor. of existing cemetery bears S. 5°58' E., 67 1ks. dist.

A fence cor. at jog on the N. side of the existing cemetery bears S. 41°24' E., 1.28 chs. dist.

A fence cor. at jog on the N. side of the existing cemetery bears S. 58°33' E., 1.485 chs. dist.

Raise a mound of stone SE. of the cor.

S. 68°24' E., along the N. bdy. of the cemetery.

Over gentle rise bearing N. 20° E. and S. 20° W.

Metes and Bounds Survey Sec. 23, T. 10 N., R. 6 W., Arizona

- 		
CHAINS		
3.50	Bladed road on bend, bears S. 30° E. and irregularly N.	
4.20	Point for Cor. No. 2.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T10n R6W	
	<u>\$23</u>	
	COR 2 CONGRESS	
	CEM	
	1966	
	from which	
	The NE. fence cor. of existing cemetery bears S. 48°45' W., 67 lks. dist.	
	A fence cor. at jog on the N. bdy. of existing cemetery bears N. 83°14' W., 2.30 chs. dist.	
	A fence cor. at jog on the N. bdy. of existing cemetery bears N. 74°06' W., 2.23 chs. dist.	
	Raise a mound of stone SW. of the cor.	
	S. 21°36' W., along the E. bdy. of the cemetery.	
	Over nearly level land.	
.80	Bladed road, bears N. 10° E. and S. 10° W.	
4.20	Point for Cor. No. 3.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T10N R6W S23	
	CON 3/	
	CONGRESS CEM	
	1966	
	from which	
	The SE. fence cor. of existing cemetery bears N. 26°25' W., 36 lks. dist.	
	Raise a mound of stone NW. of the cor.	
	N. 68°24' W., along the S. bdy. of the cemetery.	
	Over gentle rise bearing N. 20° E. and S. 20° W.	
3.61	Point for Cor. No. 4.	
	Set the iron post 24 ins. in the ground, cap mkd.	
1		

BOOK 4767

Metes and Bounds Survey 23, T. 10 N., R. 6 W., An

	Sec. 23, T. 10 N., R. 6 W., Arizona 3.
CHAINS	
	T10N R6W S23 COR 4 CONGRESS CEM 1966
	from which
	The SW. fence cor. of existing cemetery bears N. 59°24' E., 31 lks. dist.
	Raise a mound of stone NE. of the cor.
	N. 13°35' E., along the W. bdy. of the cemetery.
	Along the E. side of wash, 10 lks. wide, 1 ft. deep, draining S. 13° W.
4.24	Cor. No. 1, the place of beginning.
	General Description
	This cemetery site is located in desert land about one-half mile southwest of the old Congress Mine, and about two miles north of the present city of Congress, Arizona. The existing cemetery, located on a low rise bearing

North 20° East and South 20° West, has been fenced and about 50% of the acreage utilized. The additional acreage included in the metes and bounds survey, Lot 20, was declared adequate by the parties concerned.

BOOK 4767

CHAINS		*
		•
		_
		-
		•
		•
		*6
	·	
		-
		·
		-
		-
		•
		Acc
	•	•
		•
		-

BOOK 4767

Form 4-680 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Wallace R. Ott	Transit
Gary T. Oviatt	Front Chainman
Loyal E. Steele	Flagman
James E. Muth	Cornerman
Victor E. Templeton	Axeman

(6)

BOOK 4767

CERTIFICATE OF SURVEY

I, Boyd S. Owens	, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing dat	e of the 18thday of March , 19 65,
I have made a metes and bounds surve	y of Congress Cemetery in Section 23,
Township 10 North, Range 6 West,	
of the Gila and Salt River Meridia	n, in the State of Arizona , which
are represented in the foregoing field notes as h	naving been executed by me and under my direction;
and that said survey has been made in strict co	onformity with said special instructions, the Manual
of Instructions for the Survey of the Public L	ands of the United States, and in specific manner
described in the foregoing field notes.	
	B. 1 10.0
January 19, 1966 (Date)	Boyd S Owens (Cadastral Surveyor)
	·
(Date)	(Cadastral Surveyor)
SUBMITTED FOR APPROVAL	
Date FEB 3 1966 CERTIFICAT	E OF APPROVAL
The foregoing field notes of the metes and	d bounds survey of Congress Cemetery
in Section 23 of Township 10 North	, Range 6 West, of the Gila and Salt
River Meridian in the State of Ari	zona,
executed by Boyd S. Owens, Cadastral	Surveyor,
having been critically examined and found corr	ect, are hereby approved.
APR 1 4 1966	
(Date)	(Chief, Division of Engineering)
CERTIFICATI	E OF TRANSCRIPT
I CERTIFY That the foregoing transcript of th	e field notes of the above-described surveys in
	, is a true copy of the original field notes.

(Chief, Division of Engineering)