

Form 4-679
(January 1963)

BOOK 4814
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 22 North, Range 8 East

[Lined area for field notes]

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys included under Group Number 446, approved March 29, 1966, and assignment instructions dated June 28, 19 66.

Survey commenced July 6, 19 66

Survey completed October 25, 19 66

BOOK 4814 INDEX DIAGRAM

Township 22 North, Range 8 East,
1 1

6	5	4	3	3 2	1
				3	
7	8	9	10	3 11	12
			4	2	
18	17	16	15	14	13
			4	2	
19	20	21	22	23	24
30	29	28	27	26	25
		5 5			
31	32	33	34	35	36

BOOK 4814

Township 22 North, Range 8 East
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The south boundary was surveyed in 1879 by J. L. Harris, retraced in 1883 by O. D. Wheeler and partially retraced in 1903 by J. A. Lamport. The east, north and west boundaries and subdivisional lines were surveyed in 1883 by O. D. Wheeler. The east boundary was resurveyed in 1902 by F. B. Jacobs. A portion of the west boundary and subdivisional lines were resurveyed by J. A. Lamport in 1903.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, T. 22 N., R. 8 E., Arizona

The cor. of secs. 2, 3, 34 and 35, Ts. 22 and 23 N., R. 8 E., monumented by a lava stone, 8 x 14 x 16 ins., firmly set, with a mound of stone to the W., mkd. with 4 notches on the W. and 2 notches on the E., from which the original bearing trees

A pine, 32 ins. diam., bears N. 13½° E., 318 lks. dist., mkd. with an overgrown blaze

A pine, 32 ins. diam., bears N. 80½° W., 238 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T23N R8E
S34|S35
S 3|S 2
T22N
1966

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on the NW. edge of Cinder Lake and about 5.00 chs. S. of a track road bearing E. and W.

The point for the cor. of secs. 3, 4, 33 and 34, Ts. 22 and 23 N., R. 8 E., is determined by using record course and dist. from the original bearing trees

A pine, 20 ins. diam., bears N. 81° E., 110 lks. dist., mkd. with an overgrown blaze

A pine, 30 ins. diam., bears S. 51° W., 80 lks. dist., mkd. T22N R8E S4 BT

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 30 ins. in the ground, brass cap mkd.

T23N R8E
 S33|S34
 S 4|S 3
 1966

Drive a steel fence post alongside the iron post.

Cor. is on the N. side of a junction of roads which bear NE., S. and W., and 50 lks. N. of a fence cor. from which fences bear S. and W.

The cor. of secs. 14, 15, 22 and 23, monumented by a malpais stone, 8 x 10 x 10 ins., firmly set in a mound of stones, mkd. with 3 notches on the S. and 2 notches on the E., from which the original bearing trees

A pine, 20 ins. diam., bears N. 74½° E., 30 lks. dist., mkd. with part of the scribe mks. visible.

A pine stump, bears S. 25° W., 105 lks. dist.

A pine, 18 ins. diam., bears N. 16° W., 46 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E
 S15|S14
 S22|S23
 1966

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on an E. slope about 5.00 chs. W. of a fence bearing N. and S.

The cor. of secs. 10, 11, 14 and 15, monumented by the remains of a charred post, from which the original bearing trees

A pine, 18 ins. diam., bears N. 44° E., 148 lks. dist., mkd. with part of the scribe mks. visible

A pine, 20 ins. diam., bears S 24½° E., 166 lks. dist., mkd. with an overgrown blaze

A pine, 34 ins. diam., bears N. 70° W., 14 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E
 S10|S11
 S15|S14
 1966

CHAINS

Raise a mound of stone W. of the iron post.

Cor. is in moderate timber, 50 lks. E. of paved road to Flagstaff garbage dump, bearing N. and S., and 20 lks. E. of a fence bearing N. and S.

The point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11 is determined by using record course and distance from the remains of the original bearing trees

A pine stump, bears N. 69° E., 33 lks. dist., mkd. $\frac{1}{2}$ S BT

A pine, 24 ins. diam., bears S. $63\frac{1}{2}^\circ$ W., 69 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E

$\frac{1}{4}$
S10|S11
1966

from which

A pine, 18 ins. diam., bears N. $77\frac{1}{2}^\circ$ E., 94 lks. dist., mkd. $\frac{1}{4}$ S11 BT

Cor. is on nearly level land in moderate timber.

The cor. of secs. 2, 3, 10 and 11, monumented by a post, $3\frac{1}{2}$ ft. long, set in a mound of stone, mkd. with part of the scribe mks. visible, from which the original bearing tree

A pine, 32 ins. diam., bears N. $36\frac{1}{2}^\circ$ E., 564 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E

S 3|S 2
S10|S11
1966

Raise a mound of stone W. of the iron post.

Bury the original corner post alongside the iron post.

Cor. is near the center of Cinder Lake.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented by a lava stone, 8 x 10 x 14 ins., set 10 ins. in the ground, mkd. with $\frac{1}{4}$ on W., from which the remains of the original bearing trees

A pine stump, bears S. 50° E., 12 lks. dist., mkd. $\frac{1}{2}$ S BT

A fallen pine, bears S. 30° W., 86 lks. dist.

4

CHAINS

A pine, 20 ins. diam., bears N. $55\frac{1}{2}^\circ$ W., 20 lks. dist., mkd. $\frac{1}{4}$ S3BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E

$\frac{1}{4}$
S3|S2
1966

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E slope and about 2.50 chs. W of the edge of Cinder Lake.

The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented by an old mound of stone, from which the remains of the original bearing trees

A juniper, 30 ins. diam., bears S. 71° W., 63 lks. dist., mkd. $\frac{1}{4}$ S BT

A pine stump, bears N. 68° W., 48 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E

$\frac{1}{4}$
S15
S22
1966

from which

A pine, 4 ins. diam., bears N. 67° E., 92 lks. dist., mkd. $\frac{1}{4}$ S15 BT

Raise a mound of stone N. of the iron post.

Cor. is on the SW. slope of a small knoll.

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented by an iron pin, 1 in. diam., from which the original bearing tree

A pine, 40 ins. diam., bears S. 36° W., 44 lks. dist., mkd. $\frac{1}{4}$ S BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E

$\frac{1}{4}$
S10
S15
1966

from which

A pine, 5 ins. diam., bears N. 72° E., 87 lks. dist., mkd. $\frac{1}{4}$ S BT

BOOK 4814

Remonumentation, T. 22 N., R. 8 E., Arizona

5.

CHAINS

Cor. is on a gentle N. slope in moderate timber.

The cor. of secs. 28, 29, 32 and 33, monumented by a granite stone, 6 x 6 x 16 ins., firmly set flush with the ground, mkd. with 4 notches on the E. and 1 notch on the S., from which the remains of the original bearing tree

A pine stump, bears S. $89\frac{1}{2}^{\circ}$ W., 268 lks. dist., mkd. with most of the scribe mks. visible

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E
 $\frac{S29}{S32}$ | $\frac{S28}{S33}$
 1966

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on cultivated land adjacent to cor. No. 1 of HES 373, and at a fence cor. from which fences bear E., S. and W.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented by a limestone, 10 x 10 x 18 ins., firmly set flush with the ground, plainly mkd. with $\frac{1}{4}$ on the N., from which the original bearing tree

A pine, 34 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E., 144 lks. dist., mkd. $\frac{1}{4}$ S28 BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T22N R8E
 $\frac{1}{4}$ $\frac{S28}{S33}$
 1966

Bury the original corner stone and glass alongside the iron post.

Cor. is on the N. edge of a bladed dirt road bearing E. and W.

7

BOOK 4814

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 28th day of March, 1966,
I have remonumented cadastral survey corners in Township 22 North,
Range 8 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)
(Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumentation of cadastral survey corners in
Township 22 North, Range 8 East, Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician,
having been critically examined and found correct, are hereby approved.

FEB 27 1968
(Date)

R. E. Braun
(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Engineering)~~