### **BOOK 4828**

Form 9180-6 (April 1965) (formerly 4-679)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

# FIELD NOTES

DEPENDENT RESURVEY
of the
NORTH, EAST and WEST BOUNDARIES
and
SUBDIVISIONAL LINES
of
Township 13 North, Range 30 East
Of the Gila and Salt RiverMeridian,
In the State of
EXECUTED BY
EXECUTED BY
Paul G. Bauer, Supervisory Cadastral Surveyor
Kenneth D. Herman, Cadastral Surveyor
Gary T. Oviatt, Surveying Technician
Under special instructions datedFebruary 16, 1966 _, which provided for the surveys
included under Group Number 444 , approved February 16, 1966 ,
and assignment instructions dated May 11, 19 _66
Survey commenced <u>June 16</u> , 19 <u>66</u>

Survey completed \_\_\_\_\_ August 8 \_\_\_\_, 19 \_\_66

## BOOK 4828

# INDEX DIAGRAM

	Townsh	ip 13 No	orth	Range	30 East	
	13	12	11	11	10	9
8	6	: 44 <b>5</b>	36 <b>4</b>	30 <b>8</b>	25 2	19 <b>1</b> 4
ļ	44	43	36	30	24	18
8	7	43 s	35 9	29 10	24 11	18 12 4
l	42	42	35	29	23	17
7	18	41 17	34 16	28 15	22 14	16 13 3
	41	40	33	28	22	16
6	19	40 20	33 <b>21</b>	27 22	21 28	15 24 2
	39	39	32	27	21	15
6	30	38 29	32 28	26 27	20 26	14 25 2
	37	37	31	26	20	14
5	31	36 32	31 88	25 84	19 85	13 36 1

Township 13 North, Range 30 East Gila and Salt River Meridian, Arizona

-		Gila and Salt River Meridian, Arizona
	CHAIŃS	The boundaries and subdivisional lines were surveyed in 1882 by M. Santee, who also resurveyed the south boundary, the Third Standard Parallel North, the same year. The Third Standard Parallel North was resurveyed by Bauer, Johnson and Oviatt in 1966 under Group 443.
		The following field notes are those of a dependent resurvey of the north, east and west boundaries, and the subdivisional lines of Township 13 North, Range 30 East, designed to restore the corners according to the best available evidence.
		Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base, and with a brass cap riveted to the top.
		The geographic position of the southeast corner of the township is: Latitude, 34°29'01.7" North, and Longitude, 109°06'11" West. This position was calculated from a tie to U.S.C.&G.S. triangulation station "St. Johns," located in sec. 8, Township 12 North, Range 30 East.
ľ		The mean magnetic declination was found to be 14° East.
		Dependent Resurvey, East Boundary Township 13 North, Range 30 East
		Reestablishment of the Survey Executed in 1882 by M. Santee
		Beginning at the standard cor. of T. 13 N., Rs. 30 and 31 E., monumented by an iron post, 2½ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.
İ		N. 0°11' E., bet. secs. 31 and 36.
	2.60	Over nearly level land.
	39.94	Track road, bears S. 75° E. and N. 75° W.
	39.94	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented by a sandstone, 26 x 15 x 5 ins., mkd. $\frac{1}{4}$ on W. face, loosely set.
		At the corner point,
		Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
		T13N R30E R31E
		s 36 s 31
		1966
	!	Bury the orig. cor. stone alongside the iron post.
		N. 0°13' E., beginning new measurement.
	35.10	Track road, bears E. and W.
	40.06	The cor. of secs. 25, 30, 31 and 36, monumented by a basalt stone, $9 \times 5 \times 4$ ins., firmly set, mkd. with 5 notches on the N. face and 1 notch on the S. face.
		At the corner point,
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T13N R30E R31E S 25   S 30 S 36   S 31 1966

		2. Dep. Resurvey, East Boundary, T. 13 N., R. 30 E., Arizona	
	CHAINS	from which	
		A fence, bearing N. and S., bears W., 25 1ks. dist.	
ł		Bury the orig. cor. stone alongside the iron post.	
		Raise a mound of stone W. of the corner.	
		Land, nearly level to gently rolling. Soil, shalow sandy loam.	
		Timber, none. Undergrowth, bunch grass and sagebrush.	
		N. 0°06' W., bet. secs. 25 and 30.	١
		Over gently rolling land, through scattered juniper timber.	
	30.90	Wash, 20 1ks. wide, 2 ft. deep, drains NE.	
	40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 24 ins. in the ground, brass cap mkd.	
		T13N R30E_R31E	
		s 25 s 30	
		1966	l
		The corner falls in a fence bearing N. and S.	
		Raise a mound of stone W. of the corner.	l
	59.60	Old fence line, bears E. and W.	
	79.70	Fence, bears E. and W.	ŀ
	80.09	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor	
		Set the iron post 24 ins. in the ground, brass cap mkd.	
	i	T13N	
		R30E R31E	
		S 24 S 19 S 25 S 30	
		1966	l
		from which	l
		A corner of fences bearing S. and W. bears S. 36°22' E., 48 1ks. dist.	
	i	Raise a mound of stone W. of the corner.	
		Land, gently rolling. Soil, shallow, sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.	
			-
		N. 0°06' W., bet. secs. 19 and 24.	
		Over gently rolling land, through moderate juniper timber.	
	27.20	Trail road, bears N. 75° E. and S. 75° W.	
	36.80	Draw, drains NE.	
	40.05	Point for the ½ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		1	- 1

	3.
	Dep. Resurvey, East Boundary, T. 13 N., R.30 E., Arizona
CHAINS	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
:	T13N R30E R31E
3	s 24 s 19
à	1966
	Raise a mound of stone W. of the corner.
73.00	Graded road, bears N. 80° E. and S. 80° W.
80.09	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13N R30E R31E S 13 S 18
	S 24 S 19 1966
	from which
	A fence, bearing E. and W., bears North, 10 1ks. dist.
	Raise a mound of stone W. of the corner.
	Land, gently rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
	N. 0°06' W., bet. secs. 13 and 18.
-	Over gently rolling land, through scattered juniper timber.
7.20	Fence, bears E. and W.
7.90	Fence, bears S. 30° E. and N. 30° W.
19.20	Fence, bears N. 60° E. and S. 60° W.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
·	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13N R30E R31E
	s 13 s 18
	1966
	Raise a mound of stone W. of the corner.
47.00	Left bank of Carrizo Wash, bears E. and N.
52.50	Right bank of Carrizo Wash, bears E. and N.
80.09	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T13N R30E R31E
	<u>S 12   S 7</u> S 13   S 18
	1966
	Raise a mound of stone W. of the corner.
1	

Dep.	Resurvey,	East	Boundary,	T.13 N.,	R.30	Ε.,	Arizona

<u>,</u>	Dep. Resurvey, East Boundary, T. 13 N., R. 30 E., Arizona
CHAII	Land, gently rolling to nearly level. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	N. 0°06' W., bet. secs. 7 and 12.
	Over nearly level land.
40.0	Point for the ½ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
42.0	O Enter heavy juniper timber, bears E. and W.
80.0	The cor. of secs. 1, 6, 7 and 12, monumented by a sandstone, 14 x 12 x 2 ins., set in old mound of stone, mkd. with 5 notches on the S. and 1 notch on the N. face.
Ì	At the corner point,
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13N R30E R31E S 1   S 6 S 12   S 7 1966
	from which
	A fence, bearing N. and S., bears E., 58 lks. dist.
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the corner.
	Land, nearly level to gently rolling. Soil, sandy loam.
	Timber, none, to heavy juniper. Undergrowth, bunch grass and sagebrush.
	N. 1°24' E., bet. secs. 1 and 6.
	Over gently rolling land, through moderate juniper timber.
37.9	Wash, 20 1ks. wide, 2 ft. deep, drains S. 70° W.
40.00	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13N R30E R31E
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	1966
	Raise a mound of stone W. of the corner.
80.00	The cor. of Tps. 13 and 14 N., Rs. 30 and 31 E., monumented by a lava stone, 18 x 12 x 12 ins., mkd. with 6 notches on the N., E., S. and W. faces, set in the corner of fences bearing N., E., S. and W.

	Dep.	Resurvey,	West	Boundary,	Т.	13	N .	, R	30	Ε.,	Arizona
CHAINS											

CHAINS		
	At the corner point,	
	Set the iron post 14 ins. in the ground, in a mound of stone, brass cap mkd.	
	T14N	
	R30E R31E	
1	<u>S 36 S 31</u> S 1 S 6	
	T13N	
	1966	
	Bury the orig. cor. stone alongside the iron post.	
	Land, gently rolling.	
	Soil, shallow sandy loam. Timber, thick to moderate juniper.	
	Undergrowth, bunch grass and sagebrush.	
į	· ·	
	Dependent Resurvey, West Boundary Township 13 North, Range 30 East	
	Reestablishment of the Survey Executed in 1882 by M. Santee	
	From the standard con 10 m 10 m 20 m	
	From the standard cor. of T. 13 N., Rs. 29 and 30 E., monumented by an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.	
	N. 0°05' W., bet. secs. 31 and 36.	
	Desc. over mountainous land, through moderate juniper timber.	
19.50	Bottom of descent, bears E. and W.; thence over gently rolling land.	
20.40	Fence, bears N. 10° E. and S. 10° W.	
37.90	Track road, bears S. 70°20' E. and N. 70°20' W.	
40.60	Point for the ½ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner was not monumented.	
80.60	Fence, bears N. 89°20' E. and S. 89°20' W.	
81.20	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	T13N	
	R29E R30E	
	<u>S 25 S 30</u> S 36 S 31	
	2 20 2 21	
	1966	
	from which	
	A corner of fences bearing N., S. and W., bears S 49°20' E., 90 lks. dist.	
	, l	

Dep.	Resurvey,	West	Boundary,	Т.	13 N.,	R.	30 E.,	Arizona

CHAINS	Raise a mound of stone W. of the corner.
	Land, mountainous to gently rolling. Soil, shallow sandy loam. Timber, moderate to scattered juniper. Undergrowth, bunch grass and sagebrush.
	N. 0°05' W., bet. secs. 25 and 30.
	Over rolling land, through scattered juniper timber.
15.60	Enter moderate juniper timber, bears NE. and SW.
24.20	Wash, 10 1ks. wide, 2 ft. deep, drains N. 55° W.
40.60	Point for the ½ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13N R29E R30E
	s 25 s 30
	1966
	Raise a mound of stone W. of the corner.
43.30	Right bank of wash, bears NE. and SW.
54.90	Right bank of wash, bears S. 30° E. and N. 30° W.
66.60	Right bank of wash, bears NE. and SW
81.00	Left bank of wash, bears N. 20° E. and S. 20° W.
81.20	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R29E R30E S 24 S 19 S 25 S 30
	1966
	Raise a mound of stone W. of the corner.
	Land, gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	N. 0°05' W., bet. secs. 19 and 24.  Over gently rolling land, through scattered juniper timber.
1	

•		7.
		Dep. Resurvey, West Boundary, T. 13 N., R. 30 E., Arizona
	CHAINS	
	8.60	Track road, bears E. and W.
	40.60	Point for the ½ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
•	81.20	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R29E R30E S 13 S 18 S 24 S 19
	,	1966
		from which
		A fence, bearing N. and S., bears West 17 lks. dist.
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		N. 0°05' W., bet. secs. 13 and 18.
		Over nearly level land.
	40.60	Point for the ½ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R29E R30E
		S 13 S 18
		1966
		from whi <b>ch</b>
		A fence, bearing N. and S., bears West, 40 lks. dist.
		Raise a mound of stone W. of the cor.
	81.20	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
• ·		T13N R29E R30E S 12 S 7 S 13 S 18
		1300

Den.	Resurvey.	West	Boundary,	Т.	13	N.,	R.	30	E.,	Arizona
Deb.	Mesurvey,	MESE	Doumary	т.		74.0 3	T	50		milla

	Dep. Resurvey, west boundary, 1. 13 N., R. 30 E., Allzona
CHAINS	from which
	A fence, bearing N. and S., bears West 40 1ks. dist.
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 0°05' W., bet. secs. 7 and 12.
	Over nearly level land.
7.40	Track road, bears E. and W.
40.60	Point for the ½ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
75.60	Fence, bears N. 87°40' E. and S. 87°40' W.
81.20	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R29E R30E S 1   S 6 S12   S 7
	1966
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 0°05' W., bet. secs. 1 and 6.
	Over nearly level land.
40.60	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R29E R30E 2 S 1   S 6
	1966
	Raise a mound of stone W. of the cor.
81.20	Point for the cor. of Tps. 13 and 14 N., Rs. 29 and 30 E., at proportionate dist.; there is no remaining
1	evidence of the orig. cor.

Dep. Resurvey, North Boundary, T. 13 N., R. 30 E., Arizona

#### CHAINS

Set the iron post 16 ins. in the ground, in a mound of stone, brass cap mkd.

T14N R29E R30E S 36 S 31 S 1 S 6 T13N

1966

from which

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, Tps. 13 and 14 N., R. 29 E., bears S. 89°48' W., 201.95 chs. dist., monumented by a basalt stone, 16 x 8 x 8 ins., mkd.  $\frac{1}{4}$  on the N. face, firmly set. This cor.was not remonumented.

The cor. of secs. 1, 6, 31 and 36, Tps. 14 and 15 N., Rs. 29 and 30 E., bears N. 0°30' E., 487.21 chs. dist., monumented by an old post 5 ins. sq., dimly mkd., in the cor. of fences bearing N., S. and W. (This cor. was shown to me by Mr. Hinkson of Holbrook, Arizona, who testified that the cor. of fences with the old 5 ins. cedar post alongside was the township cor.) This cor. was not remonumented.

These control lines were fully retraced, and careful search was made for evidence of intervening corners, none of which was recovered.

Land, nearly level to gently rolling. Soil, shallow sandy loam. Timber, none. Undergrowth, sagebrush and bunch grass.

Dependent Resurvey, North Boundary T. 13 N., R. 30 E., Arizona

Reestablishment of the Survey Executed in 1882 by M. Santee

From the cor. of Tps. 13 and 14 N., Rs. 30 and 31 E. N.  $89^{\circ}15^{\circ}$  W., bet. secs. 1 and 36.

Over gently rolling land, through moderate juniper timber.

40.26

Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 22 ins. in the ground, brass cap mkd.

T14N R30E

1/4 S 36
S 1
T13N
1966

Raise a mound of stone N. of the cor.

80.52

Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

10,

	10,
	Dep. Resurvey, North Boundary, T. 13 N., R. 30 E., Arizona
CHAINS	broom and mkd
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T14N R30E S 35 S 36
	$\frac{3}{8}$ $\frac{33}{2}$ $\frac{30}{8}$ $\frac{30}{1}$
	T13N
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling.
	Soil, shallow sandy loam.
	Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
	N. 89°15' W., bet. secs. 2 and 35.
	Over rolling land, through moderate juniper timber.
14.00	Leave timber, bears N. and S.
40.26	Point for the ½ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 14 ins. in the ground, brass cap mkd.
	T14N R30E
	$\frac{1}{4} \frac{\text{S} 35}{\text{S} 2}$
	S 2 T13N
	1966
	from which
	A fence, bearing E. and W., bears S. 1.22 chs. dist
	Raise a mound of stone N. of the cor.
80.52	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
ŕ	T14N_R30E
	<u>s 34 s 35</u>
	S 3   S 2 T13N
	1966
	from which
	A fence, bearing E. and W., bears South 39 1ks. dist.
	Raise a mound of stone W. of the cor.
	Land, gently rolling to nearly level. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.

		<del></del> -
		Dep. Resurvey, North Boundary, T. 13 N., R. 30 E., Arizona
	CHAINS	N. 89°15' W., bet. secs. 3 and 34.
		Over gently rolling land.
	3.20	Wash, 20 1ks. wide, 3 ft. deep, drains S. 10° W.
	8.10	Track road, bears N. 30° E. and S. 30° W.
•	23.00	Enter moderate juniper timber, bears N. and S.
	40.26	Point for the ½ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T14N R30E
		$\frac{1}{4} \frac{S}{S} \frac{34}{3}$
		T13N
		1966
		from which
		A fence, bearing E. and W., bears S. 5 lks. dist.
		Raise a mound of stone N. of the cor.
	80.52	The cor. of secs. 3, 4, 33 and 34, monumented by a volcanic stone, $8 \times 8 \times 6$ ins., mkd. with 3 notches on E. face and 3 notches on W. face, set in old mound of stone.
		At the cor. point
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T14N R30E
		S33 S34_
		S 4 S 3 T13N
		1966
		Bury the orig. cor. stone alongside the iron post.
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
		S. 89°34' W., bet. secs. 4 and 33.
		Over gently rolling land, through moderate to scattered juniper timber.
	27.00	Enter moderate juniper timber, bears NE. and SW.
	40.39	Point for the ½ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	40.80	Wash, 10 lks. wide, 1 ft. deep, drains S.
	80.78	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.

12.

Dep. Resurvey, North Boundary, T. 13 N., R. 30 E., Arizona

	Dep. Resulvey, North Boundary, 1. 13 1., 1. 31 2.,
CHAINS	Set the iron post 24 ins. in the ground, brass cap mkd.
	Set the fron post 24 fils. In the ground, brass cap mixe.
	T14N R30E
	S 32 S 33 S 5 S 4
	T13N
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling.
	Soil, shallow sandy loam. Timber, scattered to moderate juniper.
	Undergrowth, bunch grass and sagebrush.
	S. 89°34' W., bet. secs. 5 and 32.
	Over gently rolling land, through moderate juniper timber.
40.39	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T14N R30E
	$\frac{1}{4} \frac{S}{S} \frac{32}{5}$
	T13N
	1966
n .	Raise a mound of stone N. of the cor.
75.00	Fence, bears S. 20° E. and N. 20° W.
77.20	Right bank of Carrizo Wash, bears S. 10° E. and N. 10° W.
77.40	Fence, bears S. 20° E. and N. 20° W.
80.60	Left bank of Carrizo Wash, bears S. 10° E. and N. 10° W.
80.78	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T14N R30E
	S31 S32 S 6 S 5
	5 6   5 5 T13N
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling to nearly level.
	Soi <b>1</b> , shallow sandy loam.
	Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.

,		13.
.·		Dep. Resurvey, Subdivisional Lines, T. 13 N , R. 30 E., Arizona
	CHAINS	
•		S. 89°34' W., bet. secs. 6 and 31.
		Over nearly level land.
- -	40.39	Point for the ½ sec. cor. of secs 6 and 31, at proportionate dist; there is no remaining evidence of the orig. cor.
_		Set the iron post 24 ins. in the ground, brass cap mkd.
		T14N R30E
		$\begin{array}{c} \frac{1}{4} \frac{S}{S} \frac{31}{6} \\ \text{T13N} \end{array}$
		1966
		Raise a mound of stone N. of the corner.
	79.67	The cor. of Tps. 13 and 14 N., Rs. 29 and 30 E., monumented by an iron post, as described herein.
		Land, nearly level.
		Soil, shallow sandy loam. Timber, none.
		Undergrowth, bunch grass and sagebrush.
•		Dependent Resurvey, Subdivisional Lines Township 13 North, Range 30 East
•		Reestablishment of the Survey Executed in 1882 by M. Santee
		From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.
		N. 0°21' E., bet secs. 35 and 36.
		Over gently rolling land.
	39.66	Point for the ½ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 16 ins. in the ground, in a mound of stone, brass cap mkd.
		T13N R30E
		s 35 s 36
		1966
	58.10	Enter moderate juniper timber, bears E. and W.
	79.32	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
-		Set the iron post 20 ins. in the ground, brass cap mkd.
•		T13N R30E S 26 S 25 S 35 S 36
•		1966

Dep.	Resurvey,	Subdivisional	Lines,	Τ.	13	Ν.,	R.	30	E	,Arizona

	Dep. Resulvey, Subdivisional Lines, 1. 13 N., R. 30 E, Aliz
CHAINS	Raise a mound of stone W. of the corner.
	Land, gently rolling to rolling. Soil, shallow sandy loam.
	Timber, moderate juniper.
	Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp.
	N. 89°51' W., bet. secs. 25 and 36.
20.80	Track road, bears SE. and NW.
40.07	Point for the ½ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T13N R30E
	½ S 25 S 36
	1966
	from which
	A stock tank, bears S. 70°20' E., 8.33 chs. dist.
	A culvert in the center of a dike, bears S. 13°27' E., 22.24 chs. dist.
	Raise a mound of stone N. of the corner.
80.14	The cor. of secs. 25, 26, 35 and 36
	Land, rolling
	Soil, shallow sandy loam. Timber, moderate juniper.
	Undergrowth, bunch grass and sagebrush.
	N. 0°35' E., bet. secs. 25 and 26.
	Over gently rolling land, through moderate juniper timber.
39.66	Point for the ½ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T13N R30E
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	1966
	Set a cedar post, 4 ft. long, 4 ins. sq., alongside the corner.
79.32	The cor. of secs 23, 24, 25 and 26, monumented by a volcanic stone, 9 x 7 x 5 ins., with 2 notches on S. face and 1 notch on E. face, in the corner of fences bearing E. and N. 58°03' W.

Dε	p.	Resurvey,	Subdivisional	Lines,	Т	13	Ν.,	R	30	Ε.,	Arizona

-			
	CHAINS	At the corner point,	
		Set the iron post 24 ins. in the ground, brass cap mkd.	
		T13N R30E S 23 S 24 S 26 S 25	
		1966	
	!	Bury the orig. cor. stone alongside the iron post.	
		Raise a mound of stone W. of the corner.	
		Land, gently rolling. Soil, shallow sandy loam. Timber, moderate to scattered juniper. Undergrowth, bunch grass and sagebrush.	
		From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.	
		S. 89°37' W., bet. secs. 24 and 25.	
		Over rolling land, through moderate juniper timber.	
	39.61	Point for the ½ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 24 ins. in the ground, brass cap mkd.	
		T13N R30E  4 S 24 S 25	
		1966	
		from which	
		The center of a dike, bears S. 72°45' W., 8.47 chs. dist.	
		Raise a mound of stone N. of the cor.	
	42.00	Track road, bears N. and S. 10° E.	
	51.70	Wash, 1 ch. wide, 8 ft. deep, drains N. 10° W.	
	79.22	The cor. of secs. 23, 24, 25 and 26.	
		Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper: Undergrowth, bunch grass and sagebrush.	
		N. 1°02' W., bet. secs. 23 and 24.	
		Over rolling land, through scattered juniper timber.	
	40.21	Point for the ½ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented. from which	
		The SW cor. of an old rock house, bears N. 62°08' E., 4.81 chs. dist.	

Dep.	Resurvey,	Subdivisional	Lines,	T.13	Ν.,	R.30	Ε.,	Arizona

I	CHAINS	Track road, bears S. 70° E. and N. 70° W
ļ	56.00	
	73.80	Graded road, bears E. and W.
	79.90	Fence, bears N. 87° E. and S. 87° W.
	80.42	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T13N R30E S 14 S 13 S 23 S 24
		1966
		Raise a mound of stone W. of the corner.
		Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp.
		S. 89°49' W., bet. secs. 13 and 24.
		Over rolling land, through moderate juniper timber.
	40.26	Point for the ½ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E
		½ S 13 S 24
į		1966
		from which
		A pond, bears N 64°33' E , 24.33 chs. dist.
	46.00	Graded road, bears S. 30° E. and N. 30° W
	80.52	Point for the cor of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
		N. 0°04' W., bet. secs. 13 and 14.
		Over gently rolling land, through moderate to scattered juniper timber.
	1	

 · · · · · · · · · · · · · · · · · · ·	Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Ariz	ona
40.20	Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of	
	the orig. cor.  Set the iron post 16 ins. in the ground, in a mound	
	of stone, brass cap mkd.	İ
	T13N R30E	
	s 14 s 13	
	1966	
80.40	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist; there is no remaining evidence of the orig. cor.	
	Set the iron post 16 ins. in the ground, in a mound of stone, brass cap mkd.	
	T13N R30E	
	<u>S 11 S 12</u> S 14 S 13	
	1966	
	Land, rolling. Soil, shallow sandy loam.	
	Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.	
	ondergrowen, button grass and sagebrasin.	
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.	
	N. 89°57' W., bet. secs. 12 and 13.	
	Over nearly level land.	
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.	
	T13N R30E	
	$\frac{1}{4} \frac{S \cdot 12}{S \cdot 13}$	
	1966	
	Raise a mound of stone N. of the cor.	
64.20	Right bank of Carrizo Wash, bears S. 10° E. and N. 10° W.	
66.20	Left bank of Carrizo Wash, bears S. 10° E. and N. 10° W.	
80.46	The cor. of secs. 11, 12, 13 and 14.	
	Land, nearly level. Soil, shallow sandy loam. Timber, none.	
	Undergrowth, bunch grass.	1

	10.	
 ·	Dep. Resurvey, Subdivisional Lines, T. 13 N., R.30 E., Arizon	ıa
CHAINS	N. 0°07' E., bet. secs. 11 and 12.	
	Over gently rolling land.	•
14.50	Left bank of Carrizo Wash, bears E. and W.	
17.10	Right bank of Carrizo Wash, bears E. and W.	<b>L</b>
40.20	Point for the ½ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.	•
	Set the iron post 24 ins. in the ground, brass cap mkd.  T13N R30E  \$\frac{1}{4}\$\$ S 11   S 12  1966	
	Raise a mound of stone W. of the cor.	
61.70	Enter heavy juniper timber, bears E. and W.	
80.40	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T13N R30E S 2 S 1 S11 S12	
	1966	
	Raise a mound of stone W. of the cor.	
	Land, gently rolling. Soil, shallow sandy loam. Timber, heavy juniper. Undergrowth, bunch grass and sagebrush.	
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.	
	N. 89°42' W., bet. secs. 1 and 12.	
	Over rolling land, through moderate juniper timber.	
40.08	Point for the ½ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
,	T13N R30E  2 S 1 S 12	
	1966	
	Raise a mound of stone N. of the cor.	
76.50	Leave moderate juniper timber, bears N. 10° E. and SW.	
80.16	The cor. of secs. 1, 2, 11 and 12.	

19.

Dep. Resurvey, Subdivisional Lines, T.13 N., R. 30 E., Arizona

	bep. Resurvey, Bushir Lines, 1111 111, 1111
CHAINS	Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
	N. 1°06' E., bet. secs. 1 and 2.
	Over gently rolling land, through moderate juniper.
40.21	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R30E
	S 2   S 1
	1966
	Raise a mound of stone W. of the corner.
78 <b>.</b> 50	Fence, bears E. and W.
80.59	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp.
	Land, rolling to gently rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
	From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.
	N. 0°23' E., bet. secs. 34 and 35.
	Over gently rolling land, through scattered juniper timber.
13.20	Leave juniper timber, bears SE. and NW.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R30E
	s 34 s 35
	1966
	Raise a mound of stone W. of the corner.
58.20	Wash, 30 1ks. wide, 2 ft. deep, drains SW.
79.96	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Resurvey, Subdivisional Lines, T.13 N	., R.	30	E. Arizona
--	-------	----	------------

	<del></del>	
	CHAINS	Set the iron post 13 ins. in the ground, in a mound of stone, brass cap mkd.
		T13N R30E S 27 S 26
		S 34 S 35
		1966
	į	Land, gently rolling.
*		Soil, shallow sandy loam. Timber, scattered juniper.
		Undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 25, 26, 35 and 36.
		S. 89°06' W., bet. secs. 26 and 35.
		Over rolling land, through moderate juniper timber.
	40.22	Point for the ½ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
	•	T13N R30E
		1 S 26 S 35
		1966
		Raise a mound of stone N. of the corner.
	63.20	Leave moderate juniper timber, bears S. 20° E. and N. 20° W.
	80.44	The cor. of secs. 26, 27, 34 and 35.
		Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, sagebrush and bunch grass.
		N. 0°26' E., bet. secs. 26 and 27.
		Over rolling land.
	17.30	Enter moderate juniper timber.
	39.98	Point for the ½ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E
		s 27 s 26
		1966
		Raise a mound of stone W. of the corner.
- 1		

	]	Dep. Resurvey, Subdivisional Lines, T.13 N.,R.30 E., Arizona
	chains 79.96	The cor. of secs. 22, 23, 26 and 27, monumented by a basalt stone, 16 x 8 x 5 ins., mkd. with 2 notches on S. face and 2 notches on E. face, set in old mound of stone.
		At the corner point,
		Set the iron post 24 ins. in the ground, brass cap mkd.
•		T13N R30E S 22 S 23 S 27 S 26
		1966
		Bury the orig. cor. stone alongside the iron post.
		Raise a mound of stone W. of the corner.
		Land, rolling to gently rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 23, 24, 25 and 26.
	·	S. 89°33' W., bet. secs. 23 and 26.
		Over rolling land, through moderate juniper timber.
	40.33	Point for the ½ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 15 ins. in the ground, in a mound of stone, brass cap mkd.
		T13N R30E  2 S 23  3 S 26  1966
	80.66	The cor. of secs. 22, 23, 26 and 27.
		Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunchgrass and sagebrush.
		N. 1°04' W., bet. secs. 22 and 23.
		Over gently rolling land, through moderate juniper timber.
	12.30	Graded road, bears N. 70° E. and S. 70° W.
	40.38	Point for the ½ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep.	Resurvey,	Subdivisional	Lines,	T.13N.,R.	30 E.,	Arizona
------	-----------	---------------	--------	-----------	--------	---------

		Dep. Resurvey, Subdivisional Lines, T.13N., R. 30 E., Arizona
	CHAINS	Set the iron post 21 ins. in the ground, brass cap mkd.
		T13N R30E
		s 22 s 23
		1966
1		Raise a mound of stone W. of the corner.
?	80.40	Fence, bears E. and W.
	80.77	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E
		<u>S 15 S 14</u> S 22 S 23
		1966
		Raise a mound of stone W. of the corner.
		Land, rolling.
		Soil, shallow sandy loam.
		Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
		ondergrowen, bunen grass and sagebrush.
		From the cor. of secs. 13, 14, 23 and 24.
		S. 89°50' W., bet. secs. 14 and 23.
		Over rolling land, through moderate juniper timber.
	40.33	Point for the ½ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T13N R30E
		$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{14}{23}$
		1966
		Raise a mound of stone N. of the cor.
	45.70	Wash, 1 ch. wide, 8 ft. deep, drains N. 20° W.
	48.80	Fence, bears SE. and NW.
	80.66	The cor. of secs. 14, 15, 22 and 23.
		Land, rolling.
		Soil, shallow sandy loam. Timber, moderate to scattered juniper.
		Undergrowth, bunch grass and sagebrush.
		N 0°221 F bet sees 1/2 and 15
		N. 0°22' E., bet. secs. 14 and 15.  Over rolling land, through scattered juniper timber.
	35 00	
	35.00	Wash, 80 lks. wide, 8 ft. deep, drains NW.

23.

Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizona

		Dep. Resurvey, Subdivisional Lines, 1:15M., M.50 2., Millon
	CHAINS	
	40.38	Point for the ½ sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 12 ins. in the ground, in a mound of stone, brass cap mkd.
		T13N R30E
		S 15 S 14 `
		1966
	59.30	Graded road, bears E. and W.
	67.10	Track road, bears S. 70° E. and N. 70° W.
	73.30	Left bank of Carrizo Wash, bears S. 80° E. and N. 80° W.
	77.80	Right bank of Carrizo Wash, bears S. 80° E. and N. 80° W.
,	80.76	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E S10 S11
		S15 S14
		1966
		Raise a mound of stone W. of the cor.
		Land, rolling to gently rolling.
		Soil, shallow sandy loam. Timber, scattered juniper.
		Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 11, 12, 13 and 14.
		N. 89°56' W, bet. secs. 11 and 14.
		Over rolling land, through scattered juniper timber.
-	40.07	Point for the ½ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
		T13N R30E
		\$\frac{1}{4}\frac{S}{S}\frac{11}{14}
		1966
		Raise a mound of stone N. of the cor.
	55.80	Left bank of Carrizo Wash, bears N. 75° E. and S. 75° W., down Carrizo Wash.
	74.80	Right bank of Carrizo Wash, bears N. 75° E. and S. 75° W.
	1	l l

	24.
, I	Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizona
CHAINS	
80.14	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling. Soil, shallow sandy loam.
	Timber, scattered juniper.
,	Undergrowth, bunch grass and sagebrush.
	N. 0°06' W., bet. secs. 10 and 11.
	Over nearly level land.
40.38	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 21 ins. in the ground, brass cap mkd.
	T13N R30E
	\$10 S11
	·
	1966
	Raise a mound of stone W. of the cor.
80.76	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 21 ins. in the ground, brass cap mkd.
	T13N R30E <u>S 3 S 2</u> S10 S11
	1966
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, shallow sandy loam. Timber, none.
	Undergrowth, bunchgrass and sagebrush.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°42' W., bet. secs. 2 and 11.
	Over mountainous land, through scattered juniper timber.
20.80	Base of mountain, thence ascend NE. slope.
40.18	Point for the ½ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 14 ins. in the ground, in a mound of stone, brass cap mkd.
	T13N R30E
	$\frac{1}{4} \frac{S}{S} \frac{2}{11}$
	1966
46.00	Desc. over rolling SW. slope.
46.00	

		25.
		Dep. Resurvey, Subdivisional Lines, T.13 N , R. 30 E., Ariz
	CHAINS	
	56.70	Base of mountain, bears SE. and NW.
	80.36	The cor. of secs. 2, 3, 10 and 11.
-		Land, rolling to mountainous. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		N. 0°59' E., bet. secs. 2 and 3.
		Over rolling land, through scattered juniper timber.
	40.38	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E
		s 3 s 2
		1966
	<u>.</u> <u>.</u>	Raise a mound of stone W. of the corner.
	81.19	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
		Land, rolling to gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.
		N. 0°39' E., bet. secs. 33 and 34.
		Over rolling land, through scattered juniper timber.
	40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E
		s 33 s 34
		1966
		Raise a mound of stone W. of the corner.
	80.96	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res	ırvey, Su	bdivisional	Lines,	T.13	Ν.,	R.	30	Ε.,	Arizona
----------	-----------	-------------	--------	------	-----	----	----	-----	---------

<del></del>	
CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.
;	T13N R30E
	<u>s 28 s 27</u> s 33 s 34
	1966
	Raise a mound of stone W. of the corner.
	Land, rolling to nearly level. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°31' W., bet. secs. 27 and 34.
	Over gently rolling land.
35.30	Wash, 1 ch. wide, 4 ft. deep, drains NW.
40.08	Point for the ½ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 16 ins. in the ground, in a mound of stone, brass cap mkd.
	T13N_R30E
	½ S 27 S 34
	1966
80.15	The cor. of secs. 27, 28, 33 and 34.
	Land, gently rolling to nearly level. Soil, shallow sandy loam.
	Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 0°15' E., bet. secs. 27 and 28.
	Over nearly level land.
1.30	Fence, bears S. 89°42' E. and N. 89°42' W.
40.48	Point for the ½ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
77.40	Old post fence, bears E. and W.
80.96	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	from which
	A spring, heavy with mineral water, bears N. 88°06' W., 5.17 chs. dist.
	-

27,
Dep. Resurvey, Subdivisional Lines, T. 13 N., R. 30 E., Arizona

		Dep. Resurvey, Subdivisional Lines, 1.13 N., R.30 E., Arizon
	CHAINS	Land, rolling to nearly level. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 22, 23, 26 and 27.
•		N. 89°44' W., bet. secs. 22 and 27.
		Over gently rolling land, through scattered juniper timber.
	11.60	Graded road, bears N. 60° E. and S. 60° W.
,	40.18	Point for the ½ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
į		T13N R30E
		$\frac{1}{4} \frac{S}{S} \frac{22}{27}$
		1966
	43.30	Fence, bears N. 60° E. and S. 60° W.
,	57.60	Graded road, bears N. and S.
	71.40	Rock fence, bears N. and S.
	74.60	East edge of old post corral, bears N. and S.
	77.90	West edge of old post corral, bears N. and S.
	80.36	Proportionate point for the cor. of secs.21, 22, 27 and 28.
		Land, rolling to gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		N. 0°09' W., bet. secs. 21 and 22.
		Over rolling land.
	2.60	Fence, bears E. and W.
	13.40	Creek, heavy with mineral water, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains N. 20° E.
	20.20	Track road, bears N. 32° E. and S. 32° W.
	21.10	Fence, bears N. 33°30' E. and S. 30°10' W.
	21.60	Track road, bears N. 32° E. and S. 32° W.
	30.20	Fence, bears SE. and NW.
	33.10	Fence, bears SE. and NW.
	40.48	Point for the ½ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.

Dep.	Resurvey,	Subdivisional	Lines,	T.13 N.,	R.30	Ε.,	Arizona

	L	Dep. Resurvey, Subdivisional Lines, 1.13 N., R.30 E., Arizona
	CHAINS 80.96	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E S 16 S 15 S 21 S 22 1966
		Raise a mound of stone W. of the cor.  Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 14, 15, 22 and 23.
		N. 89°38' W., bet. secs. 15 and 22.
		Over rolling land, through scattered juniper timber.
	16.90	Fence, bears NE. and SW.
	36.50	Wash, 1.20 chs. wide, 10 ft. deep, drains N. 20° W.
	39 <b>.5</b> 3	Point for the ½ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	41.80	Track road, bears N. and S.
	78.10	Old fence, bears N. and S.
	79 <b>.0</b> 6	The cor. of secs. 15, 16, 21 and 22.
		Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		N. 0°29' W., bet. secs. 15 and 16.
	:	Over gently rolling land, through moderate juniper timber.
	40.48	Point for the ½ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T13N R30E
		\$16 <sup>†</sup> \$15 1966
		Set a 4 ins. squared cedar post, 4 ft. long, alongside the cor.
	80.96	Point for the cor. of secs. 9, 10, 15, and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
- 1		,

29.

Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizona

	CHAINS	
		Set the iron post 12 ins. in the ground, in a mound of stone, brass cap mkd.
		T13N R30E
•		<u>S 9 S 10</u> S16 S 15
		1966
4		Land, gently rolling to rolling.
		Soil, shallow sandy loam. Timber, moderate juniper.
·		Undergrowth, bunch grass and sagebrush.
		·
		From the cor. of secs. 10, 11, 14 and 15.
		N. 89°27' W., bet. secs. 10 and 15.
·		Over nearly level land.
	5.10	Track road, bears NE. and SW.
	40.08	Point for the ½ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E
		<sup>1</sup> / <sub>4</sub> S 10 S 15
		1966
		Raise a mound of stone N. of the cor.
	52.50	Right bank of Carrizo Wash, bears S. 55° E. and N. 55° W.
	57.30	Left bank of Carrizo Wash, bears S. 55° E. and N. 55° W.
	60.80	Dike, bears S. 5° E. and N. 5° W.
	80.16	The cor. of secs. 9, 10, 15 and 16.
* .		Land, nearly level.
!		Soil, shallow sandy loam.
		Timber, none. Undergrowth, bunch grass and sagebrush.
,		
		N. 0°03' E., bet. secs. 9 and 10.
		Over nearly level land.
	15.70	Left bank of Carrizo Wash, bears E. and W.
	18.70	Right bank of Carrizo Wash, bears E. and W.
	40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at pro-
		portionate dist.; there is no remaining evidence of the orig. cor.
-		Set the iron post 22 ins. in the ground, brass cap mkd.
	-	T13N R30E
		s 9 s 10
	_	1966

30,

Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizona  CHAINS  Raise a mound of stone W. of the cor.  Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post on an "X", on solid rock, in a mound of stone, brass cap mkd.  T13N R30E	•
Raise a mound of stone W. of the cor.  Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post on an "X", on solid rock, in a mound of stone, brass cap mkd.  T13N R30E	-
portionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post on an "X", on solid rock, in a mound of stone, brass cap mkd.  T13N R30E	•
of stone, brass cap mkd.  T13N R30E	•
i I	
<u>S 4   S 3</u> S 9   S10	
1966	
Land, nearly level. Soil, shallow sandy loam. Timber, none.	
Undergrowth, bunch grass and sagebrush.	
From the cor. of secs. 2, 3, 10 and 11.	
N. 89°19' W., bet. secs. 3 and 10.	,
Over mountainous land, through scattered juniper timber.	
Point for the ½ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.	
Set the iron post 20 ins. in the ground, brass cap mkd.	•
T13N R30E <sup>1</sup> / <sub>4</sub> S 3 <del>1</del> / <sub>5</sub> S 10	
1966	
Set a 4 ins. sq. cedar post, 4 ft. long, alongside the cor.	
47.50 Base of mountain, bears N. and S.	
75.00 Track road, bears N. and S.	
80.02 The cor. of secs. 3, 4, 9 and 10.	,
Land, mountainous. Soil, shallow sandy loam.	
Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.	
N. 0°34' E., bet. secs. 3 and 4.	
Over rolling land, through scattered juniper timber.	
9.80 Track road, bears SE. and NW.	
24.80 Track road, bears N. 60° E. and S. 60° W.	
26.30 Wash, 40 lks. wide, 4 ft. deep, drains N. 60° E.	
26.60 Track road, bears N. 70° E. and S. 70° W.	
26.80 Fence, bears N. 73°30' E. and S. 69°45' W.	

	<del></del> -
 CHAINS	Dep. Resurvey, Subdivisional Lines, T.13 N., R. 30 E., Ariz
40.48	Point for the ½ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
80.40	Fence, bears E. and W.
81.28	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
	Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	From the standard cor. of secs. 32 and 33 on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.
	N. 0°35' E., bet. secs. 32 and 33.
	Over rolling land, through scattered juniper timber.
40.49	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 14 ins. in the ground, in a mound of stone, brass cap mkd.
	T13N R30E
	s 32 s 33
	1966
51.50	Wash, 1.00 ch. wide, 12 ft. deep, drains N. 70° E.
80.98	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 19 ins. in the ground, in a collar of stone, brass cap mkd.
·	T13N R30E S 29 S 28 S 32 S 33
	1966
	from which
	A corner of fences bearing S. 87°50' E., S. and N. 87° W., bears N. 84°26' W., 2.10 chs. dist.
٠.	Raise a mound of stone W. of the corner.
	Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 27, 28, 33 and 34.
	S. 89°20' W., bet. secs. 28 and 33.
	Over nearly level land.

	D	ep. Resurvey, Subdivisional Lines, T.13N., R.30 E., Arizona
	CHAINS	
	40.02	Point for the ½ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	80.04	The cor. of secs. 28, 29, 32 and 33.
		Land, nearly level. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		N. 0°05' E., bet. secs. 28 and 29.
		Over rolling land, through scattered juniper timber.
	.20	Fence, bears S. 87°50' E. and N. 87°50' W.
	40.49	Point for the ½ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	68.50	Track road, bears S. 80° E. and N. 80° W.
	80.98	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
l		T13N R30E
		s 20 s 21
		S 29 S 28
		1966
		from which
		A corner of fences, bearing N., E. and W., bears N. 88°20' E., 3.08 chs. dist.
		Raise a mound of stone W. of the corner.
		Land, rolling to gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		From the point for the cor. of secs. 21, 22, 27 and 28.
		S. 89°19' W., bet. secs. 21 and 28.
		Over rolling land, through scattered juniper timber.
	4.90	Creek, 10 lks. wide, 1 ft. deep, drains N.
1	7.90	Fence, bears N. 30° E. and S. 30° W.
	12.50	Track road, bears N. 50° E. and S. 50° W.
	20.80	Fence, bears SE. and NW.
	20.90	Track road, bears SE. and NW.

		<b>33.</b>
		Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizo
	CHAINS	
	40.15	Point for the 4 sec. cor. of secs. 21 and 28, at proportionate d st.; there is no remaining evidence of the orig. cor. This cor. is not monumented.
•	80.30	The cor. of secs. 20, 21, 28 and 29.
	**	Land, rolling. Soil, shallow sandy loam. Timber, scattered to moderate juniper. Undergrowth, bunch grass and sagebrush.
•	•	N. 0°28' W., bet. secs. 20 and 21.
		Over gently rolling land, through scattered juniper timber.
	3.10	Fence, bears E. and W.
	40.49	Point for the ½ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E
		S20 S 21
		1966
		from which
		A corner of fences bearing E. and S., bears N. 77°07' W., 2.38 chs. dist.
		Raise a mound of stone W. of the cor.
	42.80	Fence, bears E. and W.
	42.90	Track road, bears E. and W.
	80.98	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 23 ins. in the ground, brass cap mkd.
		T13N R30E <u>S17 S16</u> S20 S21 1966
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	-	From the cor. of secs. 15, 16, 21 and 22.
		S. 89°21' W., bet. secs. 16 and 21.
		Over gently rolling land.
	1	

l Chr	rs	
40.	Point for the 4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.	
,	Set the iron post 14 ins. in the ground, in a mound of stone, brass cap mkd.	
	T13N R30E	
: ]	$\frac{1}{4} \frac{\text{S} \cdot 16}{\text{S} \cdot 21}$	
	1966	
57	Fence, bears S. 46°52' E. and N. 41°12' W.	
80	72 The cor. of secs. 16, 17, 20 and 21.	
	Land, gently rolling. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.	
:	N. 0°14' W., bet. secs. 16 and 17.	
	Over gently rolling land.	
22	Fence, bears S. 46°30' E. and N. 46°30' W.	
40	Point for the ½ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	T1 3N R30E	
	S17 S .16	
	1966	
	Raise a mound of stone W. of the cor.	
	Through moderate juniper timber.	
50	90 Fence, bears N. 50° E. and S. 50° W.	
59	70 Leave juniper timber, bears E. and W.	
80	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 16 ins. in the ground, in a mound of stone, brass cap mkd.	
	T13N R30E S 8 S 9 S17 S16	
	1966	
	Land, gently rolling to rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.	.•

	<b>55.</b>
<u> </u>	Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizo
СНА	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°22' W., bet. secs. 9 and 16.
	Over rolling land, through scattered juniper timber.
40.	Point for the ½ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R30E
	$\frac{1}{4} \frac{\text{S} 9}{\text{S} 16}$
. :	1966
79.	Fence, bears N. and S.
80.3	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass, and sagebrush.
	N. 0°04' W., bet. secs. 8 and 9.
	Over rolling land.
25.4	0 Left bank of Carrizo Wash, bears E. and W.
28.4	i
40.4	
	Set the iron post 21 ins. in the ground, brass cap mkd.
	T13N R30E
	s 8 s 9
	1966
	Raise a mound of stone W. of the corner.
77.8	1
80.9	
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13N R30E S 5 S 4 S 8 S 9
	1966
	Raise a mound of stone W. of the corner.

36.

Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizon	Dep.	Resurvey,	Subdivisional	Lines,	T.13 N., R.30	Ε.,	Arizon
--	------	-----------	---------------	--------	---------------	-----	--------

i	Dep. Resurvey, Subdivisional lines, 1:10 11, 110 12, 110
CHAINS	Land, rolling to nearly level. Soil, shallow sandy loam.
	Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°21' W., bet. secs. 4 and 9.
	Over rolling land.
40.24	Point for the 2 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
76.50	Fence, bears N. and S.
80.48	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling to nearly level.
	Soil, shallow sandy loam. Timber, none.
	Undergrowth, bunch grass and sagebrush.
	N. 0°18' E., bet. secs. 4 and 5.
	Over nearly level land.
5.10	Fence, bears S. 85° E. and N. 85° W.
7.20	Track road, bears S. 60° E. and N. 60° W.
23.10	South edge of pond, bears E. and W.
31.10	North edge of pond, bears SE. and NW.
40.49	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
81.53	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.
	Land, nearly level to gently rolling. Soil, shallow sandy loam. Timber, none.
:	Undergrowth, bunch grass and sagebrush.
	From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the 1966 resurvey of T. 12 N., R. 30 E.
	North, bet. secs. 31 and 32.
	Over rolling land.
40.58	Point for the ½ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 15 ins. in the ground, in a mound of stone, brass cap mkd.

	CHAINS	Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Ari
		T13N R30E
		S 31 S.32
		1966
	80.70	Track road, bears NE. and SW.
	81.16	The cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor
		Set the iron post 21 ins. in the ground, brass cap mkd
		T13N R30E S 30 \$ 29 S 31 S 32
		1966
ı		from which
		The corner of fences bearing N. and E. and the remains of old fences bearing S. and W., bears N. 76°14' E., 95 lks. dist.
		Raise a mound of stone W. of the cor.
		Land, rolling to gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
	;	From the cor. of secs. 28, 29, 32 and 33.
		S. 89°13' W., bet. secs. 29 and 32.
		Over rolling land, through scattered juniper timber.
	40.20	Point for the ½ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E  1/2 S 29 S 32
		1966
		Raise a mound of stone N. of the cor.
	58.10	Wash, 20 1ks. wide, 3 ft. deep, drains N.
	79.95	Track road, bears NE. and SW.
	80.40	Land, rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.
		S. 89°26' W., bet. secs. 30 and 31.

Dep.	Resurvey.	Subdivisional	Lines, T.13 N.,	R.30 E.,	Arizona
F •					

	CHAINS	
	40.13	Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 23 ins. in the ground, brass cap mkd.
		T13N R30E  1/4 S 30 S 31
		1966
-		Raise a mound of stone N. of the cor.
	79.60	Fence, bears N. and S.
	80.16	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp.
		Land, gently rolling. Soil, shallow sandy loam. Timber, none.
	·	Undergrowth, bunch grass and sagebrush,
		From the cor. of secs. 29, 30, 31 and 32.
		N. 0°11' E., bet. secs. 29 and 30.
		Over nearly level land.
	39.30	Fence, bears N. 89°34' E. and S. 89°34' W.
	40.58	Point for the ½ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E
		s 30 s 29
		1966
		from which
		A corner of fences bearing N., S. and W., bears S. 46°15' E., 1.82 chs. dist.
		Set a 3 ins. sq. cedar post, 3 ft. long, alongside the cor.
	80.35	Track road, bears E. and W.
	81.16	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 23 ins. in the ground, brass cap mkd.
		T13N R30E S 19 S 20 S 30 S 29
	·	1966
		Raise a mound of stone W. of the cor.
	1	

		39.	
	CHAINS	Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Arizo	na
	CHAINS	Land, nearly level. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.	
	,	From the cor. of secs. 20, 21, 28 and 29.	
		S. 89°21' W., bet. secs. 20 and 29.	,
		Over gently rolling land.	
	24.30	Track road, bears N. 10° E. and S. 10° W.	
	40.14	Point for the ½ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.	۸.
		Set the iron post 24 ins. in the ground, brass cap mkd.	
		T13N R30E  2 S 20 2 S 29	
		1966	
		Raise a mound of stone N. of the corner.	
ļ	75.60	Fence, bears N. and S.	
	80.28	The cor. of secs. 19, 20, 29 and 30.	
	·	Land, gently rolling. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.	
		S. 89°30' W., bet. secs. 19 and 30.	
		Over gently rolling land.	
	40.20	Point for the ½ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 19 ins. in the ground, brass cap mkd.	
		T13N R30E <sup>1</sup> / <sub>4</sub> S 19 S 30	
		1966	
		Raise a mound of stone N. of the corner.	
	75.10	Right bank of wash, 4 ft. deep, bears N. and S.	
	77.70	Fence, bears SE. and NW.	
	80.40	Left bank of wash, 4 ft. deep, bears N. and S.	
	80.51	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.	
		Land, gently rolling. Soil, shallow sandy loam. Timber, scattered juniper. Undergrowth, bunch grass and sagebrush.	
- 1			

		40.
		ep. Resurvey, Subdivisional Lines, T.13 N.,R.30 E., Arizona
	CHAINS	From the cor. of secs. 19, 20, 29 and 30.
		N. 0°18' W., bet. secs. 19 and 20.
		Over gently rolling land, through scattered juniper timber.
4	4.00	Track road, bears E. and W.
	30.30	Enter moderate juniper timber, bears NE. and SW.
•	40.58	Point for the 2 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E
<b>4</b>	,	s 19 s 20
		1966
		Raise a mound of stone W. of the corner.
	44.20	Wash, 20 1ks. wide, 6 ft. deep, drains NE.
	81.16	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	,	Set the iron post 20 ins. in the ground, brass cap mkd.
		T13N R30E S 18 S 17 S 19 S 20 1966
		Raise a mound of stone W. of the corner.
		Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 16, 17, 20 and 21.
		S. 89°29' W., bet. secs. 17 and 20.
		Over rolling land.
	35.90	Enter moderate juniper timber, bears N. and S.
	40.05	Point for the ½ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 23 ins. in the ground, brass cap mkd.
		T13N R30E
		$\frac{S}{S} \frac{17}{20}$
		1966
		Raise a mound of stone N. of the corner.

CHAINS	Dep. Resurvey, Subdivisional Lines, T.13 N., R.30 E., Ariz
80.10	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
	S. 89°31' W., bet. secs. 18 and 19.
	Over rolling land, through moderate juniper timber.
40.22	Point for the ½ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 21 ins. in the ground, brass cap mkd.
	T13N R30E $\frac{1}{4} \frac{S}{S} \frac{18}{19}$
	1966
	Raise a mound of stone N. of the cor.
46.80	Wash, 1.20 chs. wide, 4 ft. deep, drains N.
80.16	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.
	Land, rolling. Soil, shallow sandy loam. Timber, moderate juniper. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°22' W., bet. secs. 17 and 18.
	Over rolling land, through moderate juniper timber.
37.70	Wash, 1.00 ch. wide, 8 ft. deep, drains NE.
40.58	Point for the ½ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 21 ins. in the ground, brass cap mkd.
	T13N R30E
	S 18 S 17
	1966
	Raise a mound of stone W. of the cor.
67.50	Wash, 4.00 chs. wide, 6 ft. deep, drains NW.
81.16	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.

	. D	Dep. Resurvey, Subdivisional Lines, T.13N., R.30 E., Arizona
	CHAINS	Set the iron post 21 ins. in the ground, brass cap mkd.
-		T13N R30E
÷		<u>S 7 S 8</u> S18 S17
		1966
·		Raise a mound of stone W. of the cor.
		Land, rolling to nearly level.
		Soil, shallow sandy loam. Timber, moderate juniper.
		Undergrowth, bunch grass and juniper.
		From the cor. of secs. 8, 9, 16 and 17.
		S. 89°38' W., bet. secs. 8 and 17.
		Over nearly level to mountainous land.
	25.20	Base of mountain, bears N. 10° E. and S. 10° W.
	40.13	Point for the 4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 14 ins. in the ground, in a mound of stone, brass cap mkd.
		T13N R30E
		1/4 S 8 S17 1966
	50.50	Top of mountain, bears N. and S.
	52.50	Base of mountain, bears S. 10° E. and N. 10° W.
	80.26	The cor. of secs. 7, 8, 17 and 18.
	00.20	Land, nearly level to mountainous.
		Soil, shallow sandy loam. Timber, scattered juniper.
		Undergrowth, bunch grass and sagebrush.
		S. 89°35' W., bet. secs. 7 and 18.
		Over rolling land.
	6.30	Wash, 2.00 chs. wide, 6 ft. deep, drains N.
	28.60	Center of old Indian village.
	40.15	Point for the ½ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E  1/4 S 7/S 18
		<sup>4</sup> <del>S</del> 18 1966
		1

		43.
	CHAINS	Dep. Resurvey, Subdivisional Lines, T.13 N., R. 30 E., Aria
	CHAINS	Raise a mound of stone N. of the cor.
	79.72	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
•		Land, rolling. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 7, 8, 17 and 18.
		N. 0°11' W., bet. secs. 7 and 8.
		Over mountainous land.
	40.58	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
•		T13N R30E
		s 7   s 8
		1966
		Raise a mound of stone W. of the cor.
	67.10	Wash, 1.20 chs. wide, 10 ft. deep, drains NE.
	71.90	Track road, bears NE. and SW.
	79.50	Fence, bears N. 71°30' E. and S. 73°30' W.
	81.16	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T13N R30E
		<u>S 6 S 5</u> S 7 S 8
		1966
		from which
		The remains of an old Indian village, bears N. 15°27' E., 7.20 chs. dist.
		Raise a mound of stone W. of the cor.
		Land, mountainous to rolling. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 4, 5, 8 and 9.
		S. 89°40' W., bet. secs. 5 and 8.
		Over nearly level land, through numerous dry washes.

	44.
 I	Dep. Resurvey, Subdivisional Lines, T.13 N.,R. 30 E., Arizona
CHAINS 40.19	Point for the ½ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 19 ins. in the ground, in a collar of stone, brass cap mkd.
	T13N R30E
	$\frac{1}{4} \frac{S}{S} \frac{5}{8}$
	1966
55.90	Right bank of Carrizo Wash, bears S. 70° E. and N. 70° W.
63.70	Left bank of Carrizo Wash, bears S. 70° E. and N. 70° W.
70.50	Track road, bears NE. and SW.
80.38	The cor. of secs. 5, 6, 7 and 8.
	Land, nearly level. Soil, shallow sandy loam.
	Timber, none. Undergrowth, bunch grass and sagebrush.
	S. 89°38' W., bet. secs. 6 and 7.
	Over rolling land.
40.14	Point for the ½ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T13N R30E
	$\frac{1}{4} \frac{\text{S} 6}{\text{S} 7}$
	1966
	Raise a mound of stone N. of the cor.
79.56	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	Land, rolling. Soil, shallow sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	·
	Over rolling land.
40.58	Point for the ½ sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Resurvey,	Subdivisional Lines,	T.13 N.	, R.30 E.,	Arizona

		bep. Resulvey, Bubulvisional Lines, 1915-19, 1901-19,	
	CHAINS		
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T13N R30E	
•		s 6 s 5	
4		1966	
•		Raise a mound of stone W. of the cor.	
	48.10	Track road, bears SE. and NW.	
	60.10	Fence, bears N. 20° E. and S. 20° W.	
•	81.34	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township.	
		Land, rolling to nearly level. Soil, shallow sandy loam.	
· .		Timber, none. Undergrowth, bunch grass and sagebrush.	
		General Description	
		Township 13 North, Range 30 East is located in the southeastern portion of Apache County. The land is of a semi-arid nature, with the main portion being rolling to nearly level in certain areas. The soil is a shallow sandy loam interspersed with clay loam along Carrizo Wash.	
		Moderate juniper and pinon are found in the southern portion of the township, with bunch grass and sagebrush being the principal undergrowth.	
		The southwestern portion of the township drains in a northeasterly direction and the northeastern portion drains in a southwesterly direction, in which both drain into Carrizo Wash, which enters the township on the east boundary of sec. 13 and traverses in a west-northwest direction, leaving the township on the northern boundary of sec. 5.	
		The area is accessible from St. Johns, Arizona, by traveling on a dirt road in an easterly direction for approximately 6 miles, thence northeasterly for approximately 5 miles, entering the township on the	

approximately 5 miles, entering the township on the west boundary of  $\sec$  31.

Grazing of livestock in the greater portion of the township is the primary interest at present.

The township is uninhabited at the present time, with an abandoned cabin in sec. 3 and ruins of cabins in secs. 22 and 27.

A spring, located in the southeastern portion of sec. 21, flows in a northeasterly direction for approximately 6 chains, terminating by going underForm 4-680 (June 1963)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Ned E. Carnahan	Surveying Aid
John J. Griswold	Surveying Aid
Lyman W. Polacca	Surveying Aid
Ira M. Thiessen	Surveying Aid
Howard H. Thomas	Surveying Aid
Victor E. Templeton	Surveying Aid
Fred C. Struckmeyer	Surveying Aid
	· · · · · · ·

# X

#### CERTIFICATE OF SURVEY

We, Paul G. Bauer, Kenneth D. Herman and // HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16thday of February , 19 66, we // have made a dependent resurvey of the north, east, and west boundaries and subdivisional lines of Township 13 North, Range 30 East,

of the Gila and Salt River Meridian, in the State of Arizona , which us our are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 15, 1966

(Date)

November 15, 1966

(Date)

November 15, 1966

(Date)

(Cadastral Surveyor)

Kenneth D. Merran

(Cadastral Surveyor)

Sary J. Vital

(Carrier Market Market Market)

(Surveying Technician)

### CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date MAR 7 1968

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the dependent resurvey of the north, east, and west boundaries and subdivisional lines of Township 13 North, Range 30 East, of the Gila and Salt River Meridian,

executed by Paul G. Bauer, Kenneth D. Herman and Gary T. Oviatt, having been critically examined and found correct, are hereby approved.

SEP 2 7 1968	Kalshoun	
(Date)	(Chief, Division of Engineering)	

CERT	FICATE OF TRANSCRIPT
I CERTIFY That the foregoing transcri	ipt of the field notes of the above-described surveys in
(Data)	(Chief, Division of Engineering)