

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of the

BOUNDARIES

and

SURVEY

of the

SUBDIVISION

of

Sections 3, 10 and 11

Township 10 North, Range 10 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Kenneth D. Herman, Cadastral Surveyor

Jerrold E. Knight, Cadastral Surveyor

Under special instructions dated May 22, 19 67, which provided for the surveys  
included under Group Number 480, approved May 22, 1967,  
and assignment instructions dated May 22, 19 67.

Survey commenced May 31, 19 67

Survey completed July 20, 19 67

## CHAINS

The north, south and west boundaries were surveyed in 1904 by Campbell and Oakes. The east boundary and subdivisional lines were surveyed in 1904 by I. E. Oakes. The north boundary was concurrently resurveyed by Herman and Knight under Group No. 456. The north boundary of section 3 was retraced and corners reestablished under this group. The boundary was concurrently resurveyed under Group 456 and the field notes record is included in the notes of Township 11 North, Range 10 East.

The following notes are those of a dependent resurvey of the section boundaries of sections 3, 10 and 11, designed to restore the corners in their true original location according to the best available evidence, and survey of subdivision in sections 3, 10 and 11, Township 10 North, Range 10 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 22, 1967.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long,  $2\frac{1}{2}$  inches diameter, flanged at the base, and with a brass cap riveted to the top.

The geographic position of the southeast corner of section 11 as determined from a tie to triangulation station Huston in section 26, Township 11 North, Range 10 East, is: Latitude,  $34^{\circ}13'02.74''$  North, and Longitude,  $111^{\circ}17'24.46''$  West.

The magnetic declination was found to be  $13\frac{1}{2}^{\circ}$  East.

Dependent Resurvey of the Boundaries  
of Sections 3, 10 and 11  
Township 10 North, Range 10 East

Reestablishment of the Survey  
Executed by I. E. Oakes in 1904

Beginning at the cor. of secs. 11, 12, 13 and 14, monumented by a granite stone, 12 x 8 x 6 ins., firmly set in a mound of stone, plainly mkd. with 4 notches on S. and 1 notch on E. face, from which the original bearing trees

A yew tree, 14 ins. diam., bears N.  $8^{\circ}$  E.,  
64 lks. dist., mkd. T10N R10E S 12 B T.

A yew tree,  $12\frac{1}{2}$  ins. diam., bears S.  $6^{\circ}$  E.,  
53 lks. dist., mkd. T10N R10E S 13 B T.

A yew tree, 13 ins. diam., bears S.  $77\frac{1}{2}^{\circ}$  W.,  
 $44\frac{1}{2}$  lks. dist., mkd. T10N R10E S 14 B T.

A yew tree, 10 ins. diam., bears N.  $76\frac{1}{2}^{\circ}$  W.,  
46 lks. dist., mkd. T10N R10E S 11 B T.

At the corner point,

BOOK 4833

# INDEX DIAGRAM

Township 10 North, Range 10 East

6	5	4	14-20 14 8 12	8 2 7	1
7	8	9	20-24 11 10 10	24-27 5 11 3	2 12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4833

2.

Dep. Resurvey, Subdivisional Lines, T.10 N., R.10 E., Arizona

CHAINS	
	<p>Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T10N R10E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 80<math>\frac{3}{4}</math>° E., 35 lks. dist., mkd. T10N R10E S 13 BT.</p> <p style="padding-left: 40px;">A yew tree, 12 ins. diam., bears N. 64° W., 12 lks. dist., mkd. T10N R10E S 11 BT.</p> <p>Deposit the orig. corner stone in the mound of stone, alongside the iron post.</p> <p>N. 0°17' E., bet. secs. 11 and 12.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>
9.80	Top of rocky outcrop; desc. along E. edge of rocky outcrop.
11.30	Base of rock formation, approx. 75 ft. high.
17.60	Ravine, drains E.
25.20	Ravine, drains NW.
38.80	Dry creek bed, 30 lks. wide, 8 ft. deep, drains N. 50° E.
40.12	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, as determined from the remains of an original bearing tree</p> <p style="padding-left: 40px;">The stump hole of a fallen oak, 9 ins. diam., bears S. 45° W., 44 lks. dist. Tree is faintly scribed with a partially sealed blaze.</p> <p>At the corner point,</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R10E <math>\frac{1}{4}</math> S 11 S 12</p> <p style="text-align: center;">1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 70<math>\frac{1}{4}</math>° E., 41 lks. dist., mkd. <math>\frac{1}{4}</math> S 12 B T.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 81<math>\frac{1}{4}</math>° W., 13 lks. dist., mkd. <math>\frac{1}{4}</math> S 11 B T.</p>
	<p>N. 0°09' W., beginning new measurement.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>
1.10	Dim track road, bears E. and W.

Dep. Resurvey, Subdivisional Lines, T.10 N., R.10 E., Arizona

CHAINS

39.82

The cor. of secs. 1, 2, 11 and 12, monumented by a granite stone, 18 x 8 x 6 ins., firmly set, plainly mkd. with 5 notches on S. and 1 notch on E. face, from which the original bearing trees

A pine, 26 ins. diam., bears N. 57° E., 80 lks. dist., mkd. with a sealed blaze.

An oak, 10 ins. diam., bears S. 53° W., 140 lks. dist., mkd. with a sealed blaze

A juniper, 15 ins. diam., bears N. 29° W., 184 lks. dist., mkd. T10N R10E S2 BT.

At the corner point,

Set the iron post 20 ins. in the ground, brass cap mkd.

T10N R10E

S 2	S 1
S11	S12

1967

from which

A pine, 13 ins. diam., bears S. 29 3/4° E., 68 lks. dist., mkd. T10N R10E S12 BT.

An oak, 10 ins. diam., bears S. 78 1/2° W., 31 1/2 lks. dist., mkd. T10N R10E S11 BT.

Bury the orig. corner stone alongside the iron post.

Land, rolling.

Soil, rocky loam.

Timber, medium dense pine, cedar and juniper, with scattered oak.

Undergrowth, medium manzanita, oak brush and cacti.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°50' W., bet. secs. 11 and 14.

Over rolling land, through dense timber and undergrowth.

22.30

Main ridge, bears SE. and NW.

23.20

Fence, bears SE. and NW.

39.62

The 1/4 sec. cor. of secs. 11 and 14, monumented by a granite stone, 15 x 8 x 4 ins., firmly set, plainly mkd. with 1/4 on N. face, from which the original bearing trees

A pine, 11 ins. diam., bears S. 2 1/4° W., 98 lks. dist., mkd. 1/4 S 14 BT.

A cedar, 11 ins. diam., bears N. 4 1/2° W., 95 lks. dist., mkd. 1/4 S 11 BT.

At the corner point,

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

Dep. Resurvey, Subdivisional Lines, T.10 N., R. 10 E., Arizona

CHAINS	
	<p style="text-align: center;">T10N R10E  <math>\frac{1}{4}</math> <math>\frac{S 11}{S 14}</math>                      1967</p> <p>from which</p> <p>A cedar, 10 ins. diam., bears S. 13° W., 74½ lks. dist., mkd. T10N R10E ¼ S 14 BT.</p> <p>A cedar, 9 ins. diam., bears S. 89° W., 35½ lks. dist., mkd. T10N R10E ¼ S 14 BT.</p> <p>Bury the orig. corner stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°33' W., beginning new measurement.</p>
20.10	Ravine, drains N. 80° E.
36.30	Ravine, drains S. 20° W.
39.91	<p>The cor. of secs. 10, 11, 14 and 15, monumented by a granite stone, 16 x 8 x 8 ins., firmly set and plainly mkd. with 4 notches on S. and 2 notches on E. face, and a mound of stone to the W., from which the orig. bearing trees</p> <p>A cedar, 12 ins. diam., bears S. 72½° W., 153 lks. dist., illegibly scribed.</p> <p>A cedar, 12 ins. diam., bears N. 74½° W., 110 lks. dist., mkd. 10, and other faint scribe mks. visible.</p> <p>At the corner point,</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T10N R10E  <math>\frac{S 10}{S 15}   \frac{S 11}{S 14}</math>                      1967</p> <p>from which</p> <p>A cedar, 5 ins. diam., bears N. 53¾° E., 57 lks. dist., mkd. T10N R10E S11 BT.</p> <p>A pine, 7 ins. diam., bears S. 28½° E., 22 lks. dist., mkd. T10N R10E S14 BT.</p> <p>A pine, 7 ins. diam., bears S. 72½° W., 50 lks. dist., mkd. T10N R10E S15 BT.</p> <p>Bury the orig. corner stone alongside the iron post.</p> <p>Land, rolling.                      Soil, rocky with areas of rocky clay.                      Timber, dense pine, juniper and cedar, with scattered oak.                      Undergrowth, medium dense manzanita and oak brush with scattered cacti.</p>

## Dep. Resurvey, Subdivisional Lines, T.10 N., R.10 E., Arizona

## CHAINS

N. 0°10' E., bet. secs. 10 and 11.

Over rolling land, through dense timber and undergrowth.

2.50 Ridge, bears NE. and SW.

17.30 Ravine, drains S. 70° W.

32.50 Mainridge, bears E. and W.; desc. N. slope.

40.02 The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, monumented by a granite stone, 15 x 6 x 6 ins., firmly set and plainly mkd. with  $\frac{1}{4}$  on W. face, in a mound of stone, from which the original bearing trees

A dead juniper, 12 ins. diam., bears S. 70° E., 163 lks. dist., mkd.  $\frac{1}{4}$  S 11 BT.

A pine, 22 ins. diam., bears S. 47 $\frac{1}{2}$ ° E., 158 lks. dist., with a sealed blaze

At the corner point,

Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.

T10N R10E

$\frac{1}{4}$   
S 10 | S 11

1967

from which

A pine, 8 ins. diam., bears S. 81 $\frac{1}{4}$ ° E., 39 lks. dist., mkd.  $\frac{1}{4}$  S 11 BT.

A pine, 9 ins. diam., bears N. 78 $\frac{1}{4}$ ° W., 70 lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

Deposit the orig. corner stone in the mound of stone, alongside the iron post.

N. 0°04' W., beginning new measurement.

Over rolling land, through dense timber and undergrowth.

12.00 Enter nearly level land.

12.70 Wash, 10 lks. wide, 1 ft. deep, drains N. 70° E.

13.70 Fence, bears S. 50° W. and N. 50° E. for 60 lks. to cor. of fences bearing N. and N. 80° E.

14.94 Point for the N-S-N 1/256 sec. cor. of secs. 10 and 11, at proportionate dist.

Set the iron post 20 ins. in the ground, brass cap mkd.

T10N R10E  
N-S-N 1/256

S 10 | S 11

1967

BOOK 4833

6.

Dep. Resurvey, Subdivisional Lines, T.10 N., R. 10 E., Arizona

CHAINS	
19.92	<p>from which</p> <p>A cedar, 6 ins. diam., bears S. 23° E., 7 lks. dist., mkd. NSN 1/256 S11 BT.</p> <p>A cedar, 10 ins. diam., bears S. 47½° W., 53 lks. dist., mkd. NSN 1/256 S10 BT.</p> <p>Point for the N 1/16 sec. cor. of secs. 10 and 11, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R10E N 1/16 S 10 S 11 1967</p>
20.85	<p>from which</p> <p>An oak, 12½ ins. diam., bears N. 73° E., 63 lks. dist., mkd. N 1/16 S11 BT.</p> <p>An oak, 12½ ins. diam., bears S. 43¼° E., 66 lks. dist., mkd. N 1/16 S11 BT.</p> <p>A pine, 12½ ins. diam., bears N. 66¼° W., 22½ lks. dist., with a nail in it.</p> <p>Continue along W. edge of bladed road bearing N.</p> <p>Fall, 5 lks. E. of cor. of fences bearing N., S. and W.</p>
21.30	<p>Driveway, bears W.</p>
22.90	<p>Fall, 10 lks. E. of cor. of fences bearing S. and W.</p>
23.60	<p>Driveway, bears W.</p>
29.88	<p>Point for the N-N 1/64 sec. cor. of secs. 10 and 11, at proportionate dist.</p> <p>Set the iron post 4 ins. below the surface of the bladed road, brass cap mkd.</p> <p style="text-align: center;">T10N R10E N-N 1/64 S 10 S 11 1967</p>
32.20	<p>from which</p> <p>A cedar, 15 ins. diam., bears N. 60¾° E., 47 lks. dist., with a nail in it.</p> <p>A pine, 12½ ins. diam., bears S. 79½° E., 66 lks. dist., mkd. NN 1/64 S11 BT.</p> <p>A pine, 20 ins. diam., bears S. 20¾° W., 71 lks. dist., with a nail in it.</p> <p>Driveway, bears W.</p>



CHAINS								
39.84	<p>The cor. of secs. 2, 3, 10 and 11, as determined from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12½ ins. diam., bears S. 64° E., 121 lks. dist., faintly scribed T10N R10E S11 BT.</p> <p>At the corner point,</p> <p>Set the iron post 6 ins. below the surface of the road, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T10N</td><td>R10E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S10</td><td>S11</td></tr> </table> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 17 ins. diam., bears N. 5¼° E., 98 lks. dist., mkd. T10N R10E S 2 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N. 43° E., 60½ lks. dist., with a spike in it.</p> <p style="padding-left: 40px;">A re-bar on cor. of rock fence, bears S. 25¼° W., 11½ lks. dist.</p> <p style="padding-left: 40px;">A light pole, bears N. 3° W., 43 lks. dist., with a spike in it.</p> <p>Corner falls at intersection of Frontier Drive and Mud Springs Trail.</p> <p>Land, rolling. Soil, gravelly loam. Timber, medium dense pine, cedar and juniper, with scattered oak. Undergrowth, medium manzanita and oak brush with some cacti.</p>	T10N	R10E	S 3	S 2	S10	S11	
T10N	R10E							
S 3	S 2							
S10	S11							
12.10 28.80 28.90 32.20 39.80	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°40' W., bet. secs. 2 and 11.</p> <p>Over rolling land, through medium timber and undergrowth.</p> <p>Spur, slopes SE.</p> <p>Creek, 3 lks. wide, 1 ft. deep, course S. 30° E.</p> <p>Fence, bears NE. and SW.; enter meadow.</p> <p>Leave meadow; enter timber.</p> <p>The ¼ sec. cor. of secs. 2 and 11, monumented by a granite stone, 12x8x6 ins., firmly set and plainly mkd. with ¼ on N. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead juniper, 9 ins. diam., bears N. 29½° E., 115 lks. dist., mkd. ¼ S 2 BT. Sealed blaze has been chopped open.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 39¾° W., 74 lks. dist., mkd. ¼ S 11 BT.</p>							

BOOK 4833

8.

Dep. Resurvey, Subdivisional Lines, T.10 N., R.10 E., Arizona

CHAINS	
	<p>At the corner point, Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T10N R10E <math>\frac{1}{4} \frac{S 2}{S 11}</math> 1967</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. <math>52\frac{1}{2}^{\circ}</math> E., 49<math>\frac{1}{2}</math> lks. dist., mkd. <math>\frac{1}{4}</math> S 2 BT.</p> <p>A pine, 8 ins. diam., bears S. <math>60\frac{1}{2}^{\circ}</math> W., 36 lks. dist., mkd. <math>\frac{1}{4}</math> S 11 BT.</p> <p>A shed, bears N. <math>86^{\circ}11'</math> E., 7.58 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>89^{\circ}45'</math> W., beginning new measurement.</p> <p>Over rolling land, through medium timber and undergrowth.</p>
13.20	Spur, slopes N.
19.89	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R10E <math>W \frac{1}{16} \frac{S 2}{S 11}</math> 1967</p> <p>from which</p> <p>A pine, 6 ins. diam., bears S. <math>58\frac{3}{4}^{\circ}</math> E., 48 lks. dist., mkd. W 1/16 S 11 BT.</p> <p>A pine, <math>7\frac{1}{2}</math> ins. diam., bears N. <math>14^{\circ}</math> W., 42 lks. dist., mkd. W 1/16 S 2 BT.</p>
26.30	Wash, 10 lks. wide, 2 ft. deep, drains S.
29.80	Wash, 10 lks. wide, 1 ft. deep, drains S. $20^{\circ}$ E.
39.35	Fence, bears N. and S.
39.78	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, rocky loam. Timber, medium pine, cedar and juniper, with some oak. Undergrowth, medium manzanita and oak brush, with scattered cacti.</p>
	<p>N. <math>0^{\circ}03'</math> E., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through medium timber and undergrowth.</p>

## Dep. Resurvey, Subdivisional Lines, T. 10 N., R. 10 E., Arizona

CHAINS	
0.44	Jog in fence, bears irregularly N. and S.; enter timber, bears E. and W. By traverse, topography as calculated to true line.
19.53	A local corner bears East, 21½ lks. dist., monumented by a square iron peg set in the corner of fences bearing NE. and S.
19.90	Enter developed land with sheds, corrals, houses and other improvements.
25.60	Fence, bears East about 1.55 chs., thence irregularly South, and West about 15 lks., thence SW.; leave developed land, enter medium timber.
29.30	Power line, bears S. 89¼° E. and N. 89¼° W.; bladed road bearing West starts about 80 lks. W of this point.
35.50	Bladed road, bears N. and W.; thence along road bearing N.
39.33	The ¼ sec. cor. of secs. 2 and 3, determined from an original bearing tree
	<p style="padding-left: 40px;">A juniper, 24 ins. diam., bears S. 48° E., 120 lks. dist., mkd. ¼ S2 BT. (Record calls for an oak.)</p>
	At the corner point,
	Set an iron post 4 ins. below the surface of the road, brass cap mkd.
	<p>T10N R10E  ¼  S 3   S 2  1967</p>
	from which
	<p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 43¼° E., 102 lks. dist., mkd. T10N R10E ¼ S 2 BT.</p>
	<p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 76° W., 51½ lks. dist., mkd. T10N R10E ¼ S 3 BT.</p>
	<p style="padding-left: 40px;">A fence cor., bears East 51 lks. dist.; fences bear S. and E.</p>
	<p style="padding-left: 40px;">A pond, bears S. 58½° W., 3.60 chs. dist.</p>
	Corner falls in center of intersections of bladed roads bearing S., E. and W.
	<hr style="width: 10%; margin: 0 auto;"/>
	N. 0° 43' E., beginning new measurement.
	Over gently rolling land, through medium timber and undergrowth.
1.30	Fence, bears N. 60° W. and S. 60° E. 60 lks. to fences bearing N., SE. and NW.
9.95	Old hard surfaced road, abandoned, bears N. 65° E. and S. 65° W.
17.48	Center of State Highway No. 160, bears N. 73¾° E. and S. 76° W.

BOOK 4833

10.

Dep. Resurvey, Subdivisional Lines, T. 10 N., R. 10 E., Arizona

<p>CHAINS 20.34</p>	<p>Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R10E N 1/16 S 3   S 2 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 77° E., 41 lks. dist., mkd. N 1/16 S 2 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 31<math>\frac{3}{4}</math>° W., 18 lks. dist., mkd. N 1/16 S 3 BT.</p>
<p>23.30</p>	<p>Track road, bears irregularly NE. and SW.</p>
<p>32.90</p>	<p>Track road, bears W. and E. 50 lks., thence SE.</p>
<p>40.46</p>	<p>The cor. of secs. 2 and 3, on the N. bdy. of the Tp., monumented by an iron post, 2<math>\frac{1}{2}</math> ins. diam., described in the concurrent resurvey notes of T. 11 N., R. 10 E.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, medium pine, juniper, cedar and oak. Undergrowth, medium manzanita and oak brush, with some Spanish bayonet.</p>
<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89° 47' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>	
<p>4.20</p>	<p>Spur, slopes S.</p>
<p>35.90</p>	<p>Ravine, drains S. 70° E.</p>
<p>39.85</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 15, monumented by a granite stone, 12x10x3 ins., loosely set, plainly mkd. <math>\frac{1}{4}</math> on N. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N. 20° E., 132 lks. dist., mkd. S BT.</p> <p style="padding-left: 40px;">A cedar 18 ins. diam., bears S. 2° E., 132 lks. dist., illegibly scribed.</p> <p>At the corner point,</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R10E <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> 10 S 15 1967</p>

CHAINS	
	<p>from which</p> <p>A cedar, 8 ins. diam., bears S. 40° E., 19 lks. dist., mkd. <math>\frac{1}{4}</math> S 15 BT.</p> <p>A cedar, 8 ins. diam., bears N. 19° W., 51<math>\frac{1}{2}</math> lks. dist., mkd. <math>\frac{1}{4}</math> S 10 BT.</p> <p>Raise a mound of stone N. of the cor. Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>N. 89° 28' W., beginning new measurement.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>
15.00	Ravine, drains SW.
40.02	<p>The cor. of secs. 9, 10, 15 and 16, monumented by a granite stone, 12x8x5 ins., firmly set, plainly mkd. with 4 notches on S. and 3 notches on E. edge, with a penny cemented on top of cor. and mound of stone to W., from which the original bearing trees</p> <p>A cedar, 12 ins. diam., bears N. 36<math>\frac{1}{2}</math>° E., 102 lks. dist., illegibly scribed.</p> <p>A cedar, 9 ins. diam., bears S. 43<math>\frac{3}{4}</math>° E., 55 lks. dist., mkd. T10N R10E S15 BT.</p> <p>A cedar, 12<math>\frac{1}{2}</math> ins. diam., bears S. 52<math>\frac{1}{2}</math>° W., 72 lks. dist., illegibly scribed.</p> <p>A cedar, 9<math>\frac{1}{2}</math> ins. diam., bears N. 41° W., 36<math>\frac{1}{2}</math> lks. dist., mkd. B, with illegible scribe mks.</p> <p>Land, rolling. Soil, rocky. Timber, medium dense juniper and cedar, with scattered pine. Undergrowth, cat claw, oak brush, cacti and Spanish bayonet.</p>
	<p>N. 0° 03' W., bet. secs. 9 and 10.</p>
	<p>Asc. gentle S. slope through medium dense timber.</p>
21.30	Track road, bears irregularly E. and W.
28.10	Fence, bears N. 85° E. and S. 85° W.
31.10	Ridge, bears E. and W.
32.30	Fence, bears S. 85° E. and N. 85° W.
40.10	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, monumented by a granite stone, 9x9x6 ins., above ground, in a collar of cement, with a brass tablet, cemented in top of stone, mkd.</p>
	<p>ARIZONA HIGHWAY DEPT.</p> <p>T10N R10E</p> <p><math>\frac{1}{4}</math></p> <p>S 9   S 10</p> <p>1904</p> <p>1966</p>

Dep. Resurvey, Subdivisional Lines, T. 10 N., R. 10 E., Arizona

CHAINS		
	<p>from which the original bearing trees</p> <p>A cedar, 20 ins. diam., bears S. <math>14\frac{1}{2}^{\circ}</math> E., <math>82\frac{1}{2}</math> lks. dist., mkd. <math>\frac{1}{4}</math> S BT.</p> <p>A cedar, 16 ins. diam., bears S. <math>35\frac{1}{2}^{\circ}</math> W., <math>46\frac{1}{2}</math> lks. dist., illegibly scribed.</p> <hr/> <p>N. <math>0^{\circ} 01'</math> E., beginning new measurement.</p> <p>Through residential area of Payson, Arizona.</p>	
0.40	Bladed road, bears W. and E. 20 lks. to road bearing N. (Buena Vista St.); thence along W. edge of Buena Vista Street.	
2.60	Power line, bears W. and E., 30 lks., thence N.	
4.70	Bladed road, bears E. and W.; continue along W. edge of street.	
9.72	Phoenix Avenue, bears E. and W.	
9.97	The S-N $1/64$ sec. cor. of secs. 9 and 10, monumented by a $\frac{1}{2}$ inch re-bar flush with ground.	
	<hr/> <p>North, beginning new measurement.</p> <p>Through residential area of Payson.</p>	
2.40	Power line, bears E. and W.	
4.95	Bladed road, bears E. and W.	
9.85	Paved road, bears E. and W.	
9.96	Point for the N $1/16$ sec. cor. of secs. 9 and 10, at proportionate dist.	
	This corner was not monumented.	
19.20	State Highway No. 87, bears N. $30^{\circ}$ E. and S. $30^{\circ}$ W.	
29.88	<p>The cor. of secs. 3, 4, 9 and 10, monumented by an iron peg flush with the pavement at the center of the intersections of Concord Road and First Street. Local land owners and State Highway Department recognize this point as the sec. cor., and I accept this as the best remaining evidence of the orig. corner.</p> <p>from which</p> <p>A telephone pole #PS61799, bears N. <math>38^{\circ}</math> E., 27 lks. dist., with spike in it.</p> <p>A telephone pole, bears S. <math>21\frac{3}{4}^{\circ}</math> W., 87 lks. dist., with spike in it.</p> <p>The SE. cor. of Gallagher Plumbing shop, bears N. <math>50\frac{3}{4}^{\circ}</math> W., 69 lks. dist.</p>	
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. <math>89^{\circ} 46'</math> W., bet. secs. 3 and 10.</p>	

Dep. Resurvey, Subdivisional Lines, T. 10 N., R. 10 E., Arizona

CHAINS	
	Over nearly level land, along the S. edge of Frontier Drive.
19.80	Bladed road, bears N. and S., end of Frontier Drive.
19.97	Point for the E 1/16 sec. cor. of secs. 3 and 10, at proportionate dist.  Set the iron post 20 ins. in the ground, brass cap mkd.  <div style="text-align: center;">                     T10N R10E  <math display="block">E \frac{1}{16} \frac{S}{10}</math>                     1967                 </div> from which  A pine, 18 ins. diam., bears N. 27¼° E., 138 lks. dist., with nail in it.  A fence post, bears S. 6¼° W., 59 lks. dist., with nail in it.  A power pole, bears N. 72° W., 7 lks. dist., with nail in it.
20.00	Fence bears N. and S.
20.05	Power line, bears N. and S.; enter cleared pasture.
20.23	Fence cor., bears S. 2 lks. dist.; fence bears irreg. S. and W.
30.50	End of pasture; enter timber, bears N. and S.
39.94	The ¼ sec. cor. of secs. 3 and 10, monumented by a granite stone, 12x8x8 ins. above the ground, firmly set and plainly mkd. ¼ on N. face, with small nail cemented in the top. No evidence of the original bearing trees.  <hr style="width: 20%; margin: auto;"/> N. 89° 44' W., beginning new measurement.  Asc. rocky E. slope through medium timber and undergrowth.
8.00	Top of rocky spur, slopes N.
19.97	Point for the W 1/16 sec. cor. of secs. 3 and 10, at proportionate dist.  This corner was not monumented.  Corner point falls in center of bladed road bearing N. and S. 60 lks., to paved roads bearing S. and W.
33.00	State Highway No. 87, curves N. 25° E. and S. 30° W.
39.94	The cor. of secs. 3, 4, 9 and 10.  Land, nearly level. Soil, sandy loam. Timber, medium dense pine, oak and juniper East 60 chs.; then enter Payson. Undergrowth, medium manzanita and oak brush East 60 chs.

Dep. Resurvey, Subdivisional Lines, T. 10 N., R. 10 E., Arizona

CHAINS	
	N. 0° 07' E., bet. secs. 3 and 4. Over level land, along E. edge of Concord Road.
12.50	Concord Road curves NW.; continue along W. edge of bladed road.
25.10	Paved road, Bonita Drive, bears E. and W.
39.80	The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, determined from an original bearing tree  A juniper, 11 ins. diam., bears S. 24° W., 56 lks. dist., mkd. $\frac{1}{4}$ S4 BT.  This corner was not monumented.
	—————
	N. 0° 12' E., beginning new measurement. Over nearly level land, along E. edge of bladed road.
5.90	Bladed road, bears E. and W.
11.70	Enter State Highway maintenance yard.
14.00	Edge of gravel pit, bears E. and W.
27.00	Leave gravel pit; enter timber, bears E. and W.
40.04	The cor. of secs. 3 and 4, on the N. bdy. of the Tp., monumented by an iron post, 2 $\frac{1}{2}$ ins. diam., described in the concurrent resurvey notes of T. 11 N., R. 10 E.  Land, gently rolling. Soil, sandy loam. Timber, medium dense pine on N. 15 chs. Undergrowth, medium manzanita and oak brush on N. 15 chs.
	Subdivision of Section 3 Township 10 North, Range 10 East
	—————
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10. N. 0° 15' E., on the N-S center line of sec. 3. Over nearly level land, through medium timber.
2.20	Track road, bears irregularly SE. and NW.
6.50	Leave timber; enter cleared land, bears E. and W.
9.20	Bladed road, bears E. and W.; enter residential area of Payson, Arizona; thence along E. edge of bladed road.
13.50	Bladed road, bears E. and W.; continue along E. edge of road.
18.60	Bladed road, bears E. and W.; continue along E. edge of road.
24.80	Paved road, bears E. and W.; N. and S. bladed road ends; enter pasture.
39.71	The C $\frac{1}{4}$ sec. cor. of sec. 3, monumented by a $\frac{1}{2}$ in. iron pipe. This corner is locally accepted.
	—————



Subdivision, Section 3, T. 10 N., R. 10 E., Arizona

CHAINS	
	N. 0° 13' E., beginning new measurement.
0.03	Fence, bears irregularly E. and W.; enter timber.
7.15	Granite Dells Road, bears S. 80° E. and S. 80° W.
9.50	State Highway No. 160, bears N. 80° E. and S. 80° W.
10.06	Point for the C-S-N 1/64 sec. cor. of sec. 3. This corner was not monumented.
17.90	Track road, bears NE. and SW.
18.87	The 1/4096 sec. cor. of sec. 3, monumented by a 3/4 in. re-iron and a lath alongside, mkd. Northwest cor.- Bill Miller.  At the corner point  Set an iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.  1/4096  1967  from which  A pine, 16 ins. diam., bears S. 58° E., 50 1/2 lks. dist., mkd. 1/4096 BT.  A pine, 10 ins. diam., bears S. 57° W., 44 lks. dist., mkd. 1/4096 BT.  N. 0° 17' E., beginning new measurement.  Over nearly level land, through medium timber.
1.23	Point for the C-N 1/16 sec. cor. of sec. 3.  Set the iron post 18 ins. in the ground, brass cap mkd.  C N 1/16   S 3 C 1967  from which  A pine, 10 ins. diam., bears N. 72° E., 15 lks. dist., mkd. CN 1/16 S 3 BT.  A pine, 12 1/2 ins. diam., bears S. 74° W., 59 1/2 lks. dist., mkd. CN 1/16 S 3 BT.
21.23	The 1/4 sec. cor. of sec. 3, on the N. bdy of the Tp., monumented by an iron post, 2 1/2 ins. diam., described in the concurrent resurvey notes of T. 11 N., R. 10 E.  Land, nearly level. Soil, sandy loam. Timber, medium pine, scattered oak and cedar except in town.
	From the 1/4 sec. cor. of secs. 2 and 3.

Subdivision, Section 3, T. 10 N., R. 10 E., Arizona

CHAINS	
	N. 88° 57' W., on the E-W center line of sec. 3. Over level land, through residential area.
3.10	Road, bears NE. to Granite Dells Road and SW. to trailer court.
4.22	Shed, 21 ft. wide, bears S., connected to garage and cabin, and N. 8 lks. to N. end of shed.
4.55	Fence, bears N. 10° E. and S.
6.20	Fall, 20 lks. N. of pump on cement slab.
15.00	Bladed road, bears S. 15° E. and N. 15° W.
15.15	Fence, bears S. 15° E. and N. 15° W., 5 lks. thence W.
19.44	The C-E 1/16 sec. cor. of secs. 3, monumented by a ½ in. re-iron in cor. of fences bearing E. and S. This corner is locally accepted.  At the corner point  Set the iron post 18 ins. in the ground, brass cap mkd.  <div style="text-align: center;"> <math display="block">C \frac{E \ 1/16}{S \ 3} C</math> <p>1967</p> </div> from which  An oak, 10½ ins. diam., bears N. 41° E., 70 lks. dist., mkd. E 1/16 S 3 BT.  A pine, 7½ ins. diam., bears N. 79° E., 52 lks. dist., mkd. E 1/16 S 3 BT.  Reset re-iron alongside the iron post.  <hr style="width: 10%; margin: auto;"/> N. 89° 37' W., beginning new measurement.
0.15	Bladed road, bears N. 20° E. and S. 20° W. to house.
4.90	Corner of fences bearing E. and S.
5.275	The C-E-W-E 1/256 sec. cor. of sec. 3, monumented by a ¼ in. re-iron in a collar of stone, with a lath mkd. Bill Millers SE. cor.  At the corner point  Set the iron post 22 ins. in the ground, brass cap mkd.  <div style="text-align: center;"> <math display="block">C-E-W-E \ 1/256</math> <p>S 3 1967</p> </div> from which  A nail in fence cor., bears N. 88° E., 32 lks. dist.  A pine, 17 ins. diam., bears N. 85° W., 77½ lks. dist., mkd. with a nail in blaze.  Reset re-iron alongside the iron post.  <hr style="width: 10%; margin: auto;"/>

## Subdivision, Section 3, T. 10 N., R. 10 E., Arizona

CHAINS	
	N. 89° 06' W., beginning new measurement.
4.66	The C-W-E 1/64 sec. cor. of sec. 3, monumented by a square iron peg. This is the local accepted corner.
	A 3/4 in. re-iron is 2 1/2 lks. N. of this point.
	N. 89° 32' W., beginning new measurement.
0.30	Bladed road, bears N. and S.
1.65	Fence, bears N. 2 lks., thence W., and S. 4 lks. to house.
5.70	Cor. of fences bearing S., E. and W.
10.42	The C 1/4 sec. cor. of sec. 3.
	N. 89° 35' W., beginning new measurement.
	By traverse through residential area of Payson.
40.07	The 1/4 sec. cor. of secs. 3 and 4.
	Land, nearly level.
	Soil, sandy loam.
	Timber, scattered pine.
	Undergrowth, some manzanita and oak brush.
	From the C-E 1/16 sec. cor. of sec. 3.
	N. 0° 09' W., on the N-S center line of the NE 1/4 of sec. 3.
	Over nearly level land, through medium timber and undergrowth, along E. edge of bladed road.
4.60	Granite Dells Road, bears S. 85° E. and N. 85° W.
10.07	Point for the C-S-NE 1/64 sec. cor. of sec. 3.
	This corner was not monumented.
13.20	State Highway No. 160, bears N. 79 1/2° E. and S. 79 1/2° W.
15.105	Point for the C-N-S-NE 1/256 sec. cor. of sec. 3.
	This corner was not monumented.
20.14	Point for the NE 1/16 sec. cor. of sec. 3.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	NE 1/16
	S 3
	1967
	from which
	A juniper, 15 ins. diam., bears S. 70° E.,
	21 1/2 lks. dist., mkd. NE 1/16 S 3 BT.
	A pine, 10 ins. diam., bears N. 88° W.,
	27 lks. dist., mkd. NE 1/16 S 3 BT.

BOOK 4833

18.

Subdivision, Section 3, T. 10 N., R. 10 E., Arizona

<p>CHAINS 21.00</p>	<p>Track road, bears N. 45° E. and S. 45° W.</p>
<p>40.19</p>	<p>The E 1/16 sec. cor. of sec. 3, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., described in the concurrent resurvey notes of T. 11 N., R. 10 E.</p>
	<p>From the N 1/16 sec. cor. of secs. 2 and 3.</p> <p>N. 89° 31' W., on the E-W center line of the NE ¼ of sec. 3.</p> <p>Over rolling land, through medium dense timber and undergrowth.</p>
<p>4.70</p>	<p>Top of small knoll.</p>
<p>8.55</p>	<p>Fence, bears N. and S.</p>
<p>11.90</p>	<p>Track road, bears N. and S.</p>
<p>19.75</p>	<p>The NE 1/16 sec. cor. of sec. 3.</p>
<p>24.80</p>	<p>Point for the C-E-W-NE 1/256 sec. cor. of sec. 3.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 3. C-E-W-NE 1/256 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 89° W., 74½ lks. dist., mkd. C-E-W-NE 1/256 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 47° W., 52 lks. dist., mkd. C-E-W-NE 1/256 BT.</p>
<p>29.85</p>	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 3.</p> <p>This corner is not monumented.</p>
<p>32.50</p>	<p>Track road, bears N. 70° E. and S. 70° W.</p>
<p>38.90</p>	<p>Track road, bears N. 30° E. and S. 30° W.</p>
<p>39.95</p>	<p>The C-N 1/16 sec. cor. of sec. 3.</p>
	<p>From the C-W-E 1/64 sec. cor. of sec. 3.</p> <p>N. 0° 40' W., on the N-S center line of the SW¼ NE¼ of sec. 3.</p> <p>Over nearly level land, through medium timber and undergrowth.</p>
<p>5.80</p>	<p>Granite Dells Road, bears E. and W.</p>
<p>10.04</p>	<p>Point for the SW-NE 1/64 sec. cor. of sec. 3.</p> <p>This corner is not monumented.</p>
<p>11.40</p>	<p>State Highway No. 160, bears N. 79¼° E. and S. 79¼° W.</p>

Subdivision, Section 3, T. 10 N., R. 10 E., Arizona

<p>CHAINS 15.07</p>	<p>Point for the C-N-SW-NE 1/256 sec. cor. of sec. 3.</p> <p>This corner was not monumented.</p>
<p>20.10</p>	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 3.</p> <hr/> <p>From the point for the C-S-NE 1/64 sec. cor. of sec. 3.</p> <p>N. 89° 25' W., on the E-W center line of the SW<math>\frac{1}{4}</math> NE<math>\frac{1}{4}</math> of sec. 3.</p> <p>Over level land, through medium timber and undergrowth.</p>
<p>5.005</p>	<p>Point for the C-E-SW-NE 1/256 sec. cor. of sec. 3.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 3 C-E-SW-NE 1/256  1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears East, 8 lks. dist., mkd. CE SW NE 1/256 BT.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 56° W., 37 lks. dist., mkd. CE SW NE 1/256 BT.</p>
<p>10.01</p>	<p>Point for the SW-NE 1/64 sec. cor. of sec. 3.</p>
<p>20.27</p>	<p>Point for the C-S-N 1/64 sec. cor. of sec. 3.</p> <hr/> <p>From the C-E-SW-NE 1/256 sec. cor. of sec. 3.</p> <p>N. 1° 02' W., on the N-S center line of the NE<math>\frac{1}{4}</math> SW<math>\frac{1}{4}</math> NE<math>\frac{1}{4}</math> of sec. 3.</p> <p>Over nearly level land, through medium timber and undergrowth.</p>
<p>2.25</p>	<p>State Highway No. 160, bears N. 79° 11' E. and S. 79° 11' W.</p>
<p>5.035</p>	<p>Point for the NE-SW-NE 1/256 sec. cor. of sec. 3.</p> <p>This corner was not monumented.</p>
<p>8.845</p>	<p>The 1/4096 sec. cor. of sec. 3, monumented by a <math>\frac{3}{4}</math> in. re-iron with lath, mkd. NE. cor. Bill Miller.</p> <p>At the corner point,</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4096}</math>  1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 4<math>\frac{1}{2}</math>° W., 35 lks. dist., mkd. 1/4096 BT.</p>

Subdivision, Section 3, T. 10 N., R. 10 E., Arizona

<p>CHAINS</p> <p>1.225</p> <p>5.085</p> <p>10.055</p> <p>25.40</p> <p>37.70</p> <p>40.32</p> <p>49.30</p> <p>54.50</p> <p>55.26</p>	<p>N. 4° 23' E., beginning new measurement.</p> <p>The C-E-W-NE 1/256 sec. cor. of sec. 3.</p> <hr/> <p>From the point for the C-N-S-NE 1/256 sec. cor. of sec. 3.</p> <p>N. 89° 30' W., on the E-W center line of the NE¼ SW¼ NE¼ of sec. 3.</p> <p>Over level land, through medium timber and undergrowth.</p> <p>Point for the NE-SW-NE 1/256 sec. cor. of sec. 3.</p> <p>Point for the C-N-SW-NE 1/256 sec. cor. of sec. 3.</p> <hr/> <p style="text-align: center;">Subdivision of Section 10 Township 10 North, Range 10 East</p> <hr/> <p>From the ¼ sec. cor. of secs. 10 and 15.</p> <p>N. 0° 01' W., on the N-S center line of sec. 10.</p> <p>Over rolling land, through dense timber; asc. S. slope.</p> <p>Ridge, bears E. and W.</p> <p>Fence, bears N. 76¾° E. and S. 76¾° W.</p> <p>Point for the C ¼ sec. cor. of sec. 10.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>C ¼</p> <p>S 10</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 30° E., 11 lks. dist., mkd. C ¼ S10 BT.</p> <p style="padding-left: 40px;">A cedar, 22½ ins. diam., bears N. 63¾° W., 32½ lks. dist., mkd. C ¼ S10 BT.</p> <p>Desc. N. slope.</p> <p>Desc. sharply.</p> <p>Point for the C-N-S-N 1/256 sec. cor. of sec. 10.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>C-N-S-N 1/256</p> <p>C</p> <p>S   10</p> <p>C</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 87¾° E., 72 lks. dist., mkd. CNSN 1/256 BT.</p>
---	---

Subdivision, Section 10, T. 10 N., R. 10 E., Arizona

CHAINS	
	A pine, 17½ ins. diam., bears N. 74½° W., 31½ lks. dist., mkd. CNSN 1/256 BT.
60.24	Point for the C-N 1/16 sec. cor. of sec. 10.  This corner was not monumented.
72.00	Track road, bears N. 70° E. and S. 70° W.
75.30	Rocky spur, slopes E.
78.20	Fence, bears N. 80° E. and S. 80° W.
78.60	Track road, bears irregularly NE. and SW.
80.15	The ¼ sec. cor. of secs. 3 and 10.  Land, rolling. Soil, rocky loam. Timber, dense cedar and juniper with some pine. Undergrowth, scattered oak brush, manzanita, cacti and Spanish bayonet.
	From the ¼ sec. cor. of secs. 10 and 11.  N. 89° 47' W., on the E-W center line of sec. 10.  Over rolling land, through dense timber.
2.80	Top of spur, slopes N.
8.50	Wash, 10 lks. wide, 1 ft. deep, drains irreg. N.
28.18	Fence, bears N. 76¾° E. and S. 76¾° W.
39.99	The C ¼ sec. cor. of sec. 10.
56.60	Wash, 10 lks. wide, 1 ft. deep, drains NW.
59.98	Point for the C-W 1/16 sec. cor. of sec. 10.  Set the iron post 18 ins. in the ground, brass cap mkd.
	$\begin{array}{c} \text{C} \frac{\text{W } 1/16}{\text{S } 10} \text{C} \\ 1967 \end{array}$
	from which  A cedar, 7½ ins. diam., bears S. 30° E., 24 lks. dist., mkd. CW 1/16 S 10 BT.  A cedar, 7½ ins. diam., bears S. 60° W., 66½ lks. dist., mkd. CW 1/16 S 10 BT.
68.70	Fence, bears N. 30° E. and S. 30° W.
69.98	Point for the C-W-W 1/64 sec. cor. of sec. 10.  Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	$\begin{array}{c} \text{C} \frac{\text{W-W } 1/64}{\text{S } 10} \text{C} \\ 1967 \end{array}$

Subdivision, Section 10, T. 10 N., R. 10 E., Arizona

CHAINS	
	<p>from which</p> <p>A pine, 5 ins. diam., bears S. <math>7\frac{1}{4}^{\circ}</math> E., <math>78\frac{1}{2}</math> lks. dist., mkd. WW 1/64 S 10 BT.</p> <p>A cedar, 5 ins. diam., bears S. <math>53\frac{3}{4}^{\circ}</math> W., <math>23\frac{1}{2}</math> lks. dist., mkd. WW 1/64 S 10 BT.</p> <p>Cor. of fences bearing N. and W., bears N. <math>45^{\circ}</math> E., 4 lks. dist.</p>
73.40	Cor. of fences bearing N. and E., bears N. 6 lks. dist.
74.90	Along S. edge of old road bearing irreg. W.
79.40	Leave old road; along N. slope.
79.98	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	<p>Land, rolling. Soil, rocky loam. Timber, dense juniper and cedar with scattered pine. Undergrowth, oak brush, manzanita, cacti and Spanish bayonet.</p>
	<p>From the C-W 1/16 sec. cor. of sec. 10.</p> <p>N. <math>0^{\circ} 01'</math> W., on the N-S center line of the NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>Over rolling land, through dense timber and undergrowth; desc. N. slope.</p>
4.70	Wash, 10 lks. wide, 1 ft. deep, drains NW.; enter medium timber.
6.50	Old fence, bears N. $80^{\circ}$ E. and S. $80^{\circ}$ W.
9.96	Point for the C-S-NW 1/64 sec. cor. of sec. 10.
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S 10 C-S-NW 1/64 1967</p>
	<p>from which</p> <p>A cedar, 8 ins. diam., bears S. <math>88\frac{1}{2}^{\circ}</math> E., <math>28\frac{1}{2}</math> lks. dist., mkd. CS NW 1/64 BT.</p> <p>A cedar, 6 ins. diam., bears S. <math>7\frac{3}{4}^{\circ}</math> W., 65 lks. dist., mkd. CS NW 1/64 BT.</p>
14.60	Fence, bears E. and W. 20 lks., thence N.
14.90	S. end of wooden shed, 14 ft. wide.
14.94	Point for the C-N-S-NW 1/256 sec. cor. of sec. 10.



Subdivision, Section 10, T. 10 N., R. 10 E., Arizona

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 10 C-N-S-NW 1/256</p> <p style="text-align: center;">1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 82<math>\frac{3}{4}</math>° E., 113 lks. dist., mkd. CNS NW 1/256 BT, with nail in it.</p> <p style="padding-left: 40px;">A power pole, bears N. 3° W., 62<math>\frac{1}{2}</math> lks. dist., with nail in it.</p> <p>Corner is located in wooden shed.</p>
15.15	N. edge of shed.
15.60	Along E. edge of power line bearing N.
19.70	Fence, bears S. 73° E. and N. 73° W. 20 lks. to fences bearing N. and S.; enter pasture.
19.92	Point for the NW 1/16 sec. cor. of sec. 10.
	This corner was not monumented.
39.00	Fence, bears S. 70° E. and N. 70° W. 10 lks.; thence S.
39.86	Point for the W 1/16 sec. cor. of secs. 3 and 10.
	<hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 10.</p> <p>N. 89° 47' W., on the E-W center line of the NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>Over rolling land, through dense timber.</p>
14.90	Leave timber; enter pasture, bears N. and S.
19.985	The point for the NW 1/16 sec. cor. of sec. 10.
20.20	Fence, bears N. and S. 7 lks., thence S. 70° E.
20.45	Paved road, bears N. and W.; thence along N. edge of road.
29.97	Point for the C-W-NW 1/64 sec. cor. of sec. 10.
	This corner was not monumented.
39.955	Point for the N 1/16 sec. cor. of secs. 9 and 10.
	<hr/> <p>From the C-W-W 1/64 sec. cor. of sec. 10.</p> <p>N. 0° 01' E., on the N-S center line of the SW<math>\frac{1}{4}</math> NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>Over rolling land, through residential area.</p>
9.97	Point for the SW-NW 1/64 sec. cor. of sec. 10.
	Set the iron post 22 ins. in the ground, brass cap mkd.


Subdivision, Section 10, T. 10 N., R. 10 E., Arizona

CHAINS	
	<p style="text-align: center;">S 10 SW NW 1/64 1967</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 5 ins. diam., bears S. 21<math>\frac{3}{4}</math>° E., 65 lks. dist., mkd. SW NW 1/64 BT.</p> <p style="padding-left: 40px;">SE. cor. of house, bears N. 25° W., 85<math>\frac{1}{2}</math> lks. dist.</p>
19.85	Paved road, bears E. and W.
19.925	The point for the C-W-NW 1/64 sec. cor. of sec. 10.
<p style="text-align: center;">From the C-S-NW 1/64 sec. cor. of sec. 10.</p> <p style="padding-left: 40px;">N. 89° 45' W., on the E-W center line of the SW<math>\frac{1}{4}</math> NW<math>\frac{1}{4}</math> of sec. 10.</p> <p style="padding-left: 40px;">Over rolling land, through medium timber.</p>	
3.80	Wash, 15 lks. wide, 1 ft. deep, drains NW.; enter scattered timber.
6.70	Track road, bears NE. and SW.
9.99	The SW-NW 1/64 sec. cor. of sec. 10.
11.50	Intersection of streets bearing N. and W.; thence along N. edge of Phoenix Avenue.
19.975	The S-N 1/64 sec. cor. of secs. 9 and 10.
<p>Subdivision of Section 11 Township 10 North, Range 10 East</p>	
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14.</p> <p>N. 0° 03' W., on the N-S center line of sec. 11.</p> <p>Over rolling land, through dense timber and undergrowth.</p>
23.40	Fence, bears S. 35° E. and N. 35° W.
24.10	Ridge, bears E. and W.; desc. steep N. slope.
40.16	Point for the C $\frac{1}{4}$ sec. cor. of sec. 11.
	<p>Cement a standard brass tablet in solid rock, brass cap mkd.</p> <p style="text-align: center;">T10N R10E C <math>\frac{1}{4}</math> S 11 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 77<math>\frac{1}{2}</math>° E., 33 lks. dist., mkd. C <math>\frac{1}{4}</math> S 11 BT.</p> <p style="padding-left: 40px;">An oak, 7<math>\frac{1}{2}</math> ins. diam., bears N. 74<math>\frac{1}{4}</math>° W., 37<math>\frac{1}{2}</math> lks. dist., mkd. C <math>\frac{1}{4}</math> S 11 BT.</p>

Subdivision, Section 11, T. 10 N., R. 10 E., Arizona

CHAINS

- 40.50 Ravine, drains NE.
- 43.30 Ravine, drains NE.
- 45.30 Enter gently rolling land.
- 55.10 Creek, 10 lks. wide, 1 ft. deep, course S. 20° E.
- 56.00 Track road, bears SE. and NW.
- 60.085 Point for the C-N 1/16 sec. cor. of sec. 11.  
Set the iron post 18 ins. in the ground, brass cap mkd.



from which

A cedar, 10 ins. diam., bears N. 86° E., 49 lks. dist., mkd. CN 1/16 BT.


A pine, 10 ins. diam., bears S. 49½° W., 51 lks. dist., mkd. CN 1/16 BT.

- 64.70 Ravine, drains SE.
- 80.01 The ¼ sec. cor. of secs. 2 and 11.  
Land, rolling.  
Soil, rocky loam.  
Timber, dense pine, cedar and juniper, with oak.  
Undergrowth, manzanita, oak brush, cacti and Spanish bayonet.

---

From the ¼ sec. cor. of secs. 11 and 12.  
N. 89° 46' W., on the E-W center line of sec. 11.  
Through dense timber and undergrowth.

- 39.84 The C ¼ sec. cor. of sec. 11.
- 47.90 Fence, bears S. 25° E. and N. 25° W.
- 55.40 Ridge, bears S. 30° E. and N. 30° W.
- 57.90 Ravine, drains N. 30° E.
- 59.715 Point for the C-W 1/16 sec. cor. of sec. 11.  
Set the iron post 22 ins. in the ground, brass cap mkd.



Subdivision, Section 11, T. 10 N., R. 10 E., Arizona

CHAINS	
	<p>from which</p> <p>A pine, 16 ins. diam., bears N. 8½° E., 95 lks. dist., mkd. CW 1/16 BT.</p> <p>A pine, 12½ ins. diam., bears S. 24½° W., 53 lks. dist., mkd. CW 1/16 BT.</p>
79.59	<p>The ¼ sec. cor. of secs. 10 and 11.</p> <p>Land, rolling. Soil, rocky loam. Timber, dense pine, juniper and cedar, with some oak. Undergrowth, dense manzanita and oak brush with cacti and Spanish bayonet.</p>
7.50	<p>From the C-W 1/16 sec. cor. of sec. 11.</p> <p>N. 0° 03' W., on the N-S center line of the NW¼ of sec. 11.</p> <p>Over rolling land, through dense timber and undergrowth.</p>
14.40	<p>Ravine, drains NE.</p>
18.50	<p>Track road, bears N. 70° E. and S. 70° W.</p>
18.80	<p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p>
19.92	<p>Fence, bears N. 80° E. and S. 80° W.</p>
25.60	<p>Point for the NW 1/16 sec. cor. of sec. 11.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R10E NW 1/16 S 11</p> <p style="text-align: center;">1967</p>
29.865	<p>from which</p> <p>A cedar, 10 ins. diam., bears N. 37° E., 58 lks. dist., mkd. NW 1/16 S 11 BT.</p> <p>A pine, 14 ins. diam., bears S. 89° W., 44 lks. dist., mkd. NW 1/16 S 11 BT.</p> <p>A spring fed cement trough, bears S. 18½° E., 8.02 chs. dist.</p>
29.865	<p>Wash, 15 lks. wide, 3 ft. deep, drains S. 70° E.</p> <p>Point for the C-N-NW 1/64 sec. cor. of sec. 11.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">CN-NW 1/64</p> <p style="text-align: center;">1967</p> <p>from which</p> <p>An oak, 12 ins. diam., bears S. 6¾° E., 77 lks. dist., mkd. CN NW 1/64 S 11 BT.</p> <p>A pine, 17 ins. diam., bears S. 32½° W., 68 lks. dist., mkd. CN-NW 1/64 S 11 BT.</p>

## Subdivision, Section 11, T. 10 N., R. 10 E., Arizona

CHAINS 39.81	The W 1/16 sec. cor. of secs. 2 and 11.
	From the C-N 1/16 sec. cor. of sec. 11.
	N. 89° 46' W., on the E-W center line of the NW $\frac{1}{4}$ of sec. 11.
	Over rolling land, through dense timber and undergrowth.
13.70	Fence cor., bears South, 14 lks. dist.; fences bear S. 20° E. and S. 70° W.
19.88	The NW 1/16 sec. cor. of sec. 11.
39.60	Mud Springs Road, bears N. and S. for 30 lks.; thence E.
39.75	Fence, bears N. and S.
39.76	The N 1/16 sec. cor. of secs. 10 and 11.

## General Description

The elevation ranges from about 5450 feet above sea level in the center south portion of sec. 11 to about 5000 feet in the area of Payson, Arizona in sec. 3. The land is rolling and has a rocky to gravelly loam soil. Timber is dense to medium dense and consists of pine, cedar and juniper, with oak in the lower areas.

A small creek is in the NE. and a spring is in the center of the NW portion of sec. 11. The spring drains into water trough; no other water development was noticed other than in the town of Payson.

Part of the town of Payson is in the north half of sec. 3, and has a population of about 900.

State Highway Nos. 87 and 160 go to Payson.

The main use of the land is livestock grazing, with private land being subdivided and developed.

Form 4-680  
(June 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ira M. Thiessen	Surveying Aid
Ronald G. Williams	Surveying Aid
Martin W. Fuller	Surveying Aid
George P. Oviatt	Surveying Aid
Harry C. Shriver, Jr.	Surveying Aid

28

CERTIFICATE OF SURVEY

We  
A, Kenneth D. Herman and Jerrold E. Knight , HEREBY CERTIFY upon honor that,  
in pursuance of special instructions bearing date of the 22d day of May , 19 67 ,  
we  
A have made a dependent resurvey of the boundaries and a survey of the  
subdivision of sections 3, 10 and 11 of Township 10 North, Range 10 East,

of the Gila and Salt River Meridian, in the State of Arizona , which  
are represented in the foregoing field notes as having been executed by <sup>us</sup> ~~me~~ and under <sup>our</sup> ~~my~~ direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual  
of Instructions for the Survey of the Public Lands of the United States, and in specific manner  
described in the foregoing field notes.

March 28, 1968  
(Date)

Kenneth D. Herman  
(Cadastral Surveyor)

March 28, 1968  
(Date)

Jerrold E. Knight  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date OCT 3 1968

BUREAU OF LAND MANAGEMENT,  
Washington, D. C.

The foregoing field notes of the dependent resurvey of the boundaries and survey of  
the subdivision of sections 3, 10 and 11 of Township 10 North, Range 10 East,  
of the Gila and Salt River Meridian, Arizona,

executed by Kenneth D. Herman and Jerrold E. Knight,  
having been critically examined and found correct, are hereby approved.

FEB 13 1969  
(Date)

Clark J. Sumner  
Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
T. 10 N R 10 E., is a true copy of the original field notes.

(Date)

Clark J. Sumner  
Chief, Division of Cadastral Survey