Form 9180-6 (April 1965) (formerly 4-679)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FIELD NOTES

DEPENDENT RESURVEY
of the
NORTH, SOUTH, EAST and WEST BOUNDARIES
and the
SUBDIVISIONAL LINES
of
Township 15 North, Range 21 East
Of theGila and Salt RiverMeridian,
In the State of
EXECUTED BY
Boyd S. Owens, Cadastral Surveyor
Kenneth D. Herman, Cadastral Surveyor
Under special instructions dated August 1 , 19 66, which provided for the surveys
included under Group Number 447 approved August 1, 1966 ,
and assignment instructions dated September 27 , 19 66.
Survey commenced October 19 , 19 66

November 30

Survey completed _

_, 19 _66

INDEX DIAGRAM

	Т	ownsh	ip	15 N	orth		, Range		21 East			
	18		1	7	16		16		15		14	
13	6	52	5	43	4	37	8	29	2	23	1	9
	51		51		43		36		29		23	
13	7	50	8	42	9	35	10	28	11	22	12	9
	50		49		41		35		28		22	
12	18	48	17	41	16	34	15	27		21	13	8
	48		47		40		33		27		21	
11	19	47	20	40	21	32	22	26	23	21	24	8
	46		46		39		32		25		20	
10	30	45	29	38	28	31	27	25	26	20	25	7
	45		44		38		30		25		19	
9	31	43	32	37	38	30	84	24	35	19	36	7
	6		5		4		3		2		1	

(1B)

Township 15 North, Range 21 East Gila and Salt River Meridian, Arizona

CHAINS

The east boundary was surveyed by C. B. Foster in 1875. The west boundary was surveyed by M. N. Grant in 1883. The east boundary was retraced and the north and south boundaries and subdivisional lines were surveyed by H. Meyrick in 1883.

The following notes are those of a dependent resurvey of the boundaries and the subdivisional lines of Township 15 North, Range 21 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 1, 1966.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 ins. long, $2\frac{1}{2}$ ins. diameter, flanged at the base, and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude, 34°38'41" North, and Longitude, 110°03'46.2" West, as calculated from the Tp. cor. of Tps. 15 and 16 North, Rs. 21 and 22 East.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey of the South Boundary, Township 15 North, Range 21 East

Reestablishment of the Survey Executed by H. Meyrick in 1883

The cor. of Tps. 14 and 15 N., Rs. 21 and 22 E., monumented by a sandstone, 15 x 12 x 3 ins., plainly mkd. with 6 notches on each edge, loosely set with mound of stone W.

At the corner point

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

T15N R21E R22E S 36 S 31 S 1 S 6 T14N

1966

Deposit the orig. cor. stone alongside the iron post.

S. 89°26' W., bet. secs. 1 and 36.

Over rolling land, through railed area.

Leave railed area, bears N. and S.

	Ľ	Dep. Resurvey, South Boundary, T. 15 N., R. 21 E., Arizona
	CHAINS	
	5.50	East rim of Silver Creek Canyon, bears N. 15° E. and S. 25° W.; thence, by triangulation, topography as estimated; desc. about 200 ft. over vertical wall facing W.
	8.50	Center of Silver Creek Canyon, drains N. 15° E.
	11.00	Asc. about 200 ft. over vertical wall facing E.
	11.50	West rim of Silver Creek Canyon, bears N. 15° E. and S. 25° W.; asc. E. slope, through moderate cedar timber.
	26.70	End of triangulation on low ridge, bearing N. and S.; thence over rolling land.
	39.54	Point for the ½ sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T15N R21E
		$\frac{1}{4} \frac{S}{S} \frac{36}{1}$
		T14N
		1966
		Raise a mound of stone N. of the cor.
	78.40	Low sag, drains SW.
	79.08	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T15N R21E
		<u>s 35 s 36</u>
		S 2 S 1 T14N
		1966
		Raise a mound of stone W. of the cor.
		Land, broken on E. 12 chs.; rolling on remainder.
		Soil, sandy loam.
		Timber, scattered to moderate cedar. Undergrowth, sagebrush and bunch grass.
ļ		S. 89°26' W., bet. secs. 2 and 35.
		Over gently rolling land, through scattered cedar timber.
	12.50	Enter moderate cedar timber, bears N. and S.
	25.40	Wash, 40 lks. wide, 9 ft. deep, drains S. 15° E., curving to SE.
:	39.54	Point for the ½ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

	3.
CHAIN	Dep. Resurvey, South Boundary, T. 15 N., R. 21 E., Arizona
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{s}{s} \frac{35}{2}$
	T14N
	1966
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the cor.
68.90	Power line, bears S. 9°09' E. and N. 9°09' W.
70.40	Highway R-O-W fence, bears S. 9°09' E. and N. 9°09' W.
71.90	Arizona State Highway No. 77, bears S. 9°09' E. and N. 9°09' W.
73.50	Highway R-O-W fence, bears S. 9°09' E. and N. 9°09' W.
74.90	Telephone line, bears S. 9°09' E. and N. 9°09' W.
79.08	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T15N R21E S 34 S 35 S 3 S 2
	T14N
	1966
	from which
	A cedar, 10 ins. in diam., bears S. 70°45' E., 13 lks. dist., mkd. T14N R21E S 2 BT.
	A cedar, 10 ins. in diam., bears N. 67° W., 82 lks. dist., mkd. T15N R21E S 34 BT.
	Set a cedar post, 3 ins. diam., 5 ft. long, alongside the cor.
	Land, gently rolling. Soil, sandy loam. Timber, moderate to scattered cedar. Undergrowth, sagebrush and bunch grass.
	S. 89°26' W., bet. secs. 3 and 34.
	Over rolling land, through scattered cedar timber.
1.00	Wash, 25 1ks. wide, 3 ft. deep, drains N. 40° E.
7.30	Fence, barbed wire, bears N. 4°30' E. and S. 4°30' W.
39.54	Point for the ½ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.

	4.
I	Dep. Resurvey, South Boundary, T. 15 N., R. 21 E., Arizona
CHAINS	
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{8}{8} \frac{34}{3}$
	T14N
	1966
	1900
	from which
	The SE. cor. of materials site excavation, 4 ft. deep, 4 chs. long, and 50 lks. wide, bears N. 27° W., 14.40 chs. dist.
	Raise a mound of stone N. of the cor.
48.40	Low sag, drains NE.
79.08	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E
	<u>s 33 s 34</u>
	S 4 S 3 T14N
	1966
	1900
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the cor.
	Land, rolling.
	Soil, sandy loam. Timber, scattered cedar.
	Undergrowth, sagebrush and bunch grass.
	S. 89°26' W., bet. secs. 4 and 33.
	Over rolling land, through scattered timber.
6.40	Low sag, drains N.
11.70	Fence, barbed wire, bears S. 17°05' E. and N. 17°05' W.
34.10	Rocky wash, 80 lks. wide, 10 ft. deep, drains N. 15° E.; ascend E. slope over exposed sandstone.
39.54	Point for the ½ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post over an "X" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{S}{S} \frac{33}{4}$
	S 4 T14N
	1966
48.40	Leave exposed sandstone, enter widely scattered timber.

		5 .
	CHAINS	Dep. Resurvey, South Boundary, T. 15 N., R. 21 E., Arizona
	70.90	Low ridge, bears N. and S.
	79.08	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
•		Set the iron post 20 ins. in the ground, brass cap mkd.
		T15N R21E
•		S 32 S 33 S 5 S 4
		T14N
		1966
		Set a cedar post, 3 ins. diam., 4 ft. long, alongside the cor.
:		Land, rolling. Soil, sandy loam and exposed sandstone. Timber, scattered to widely scattered cedar. Undergrowth, sagebrush and bunch grass.
		S. 89°26' W., bet. secs. 5 and 32.
		Over rolling land, through widely scattered cedar timber.
	23.10	Fence, barbed wire, bears S. 9°03' E. and N. 9°03' W.
	24.40	Old bladed dirt road, bears S. 9° E. and N. 9° W.
	39.54	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T15N R21E
		$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{32}{5}$
		T14N
		1966
:		from which
:		A stock tank bears N. 35°32' W., 13.50 chs. dist.
		Raise a mound of stone N. of the cor.
	42.60	Wash, 5 1ks. wide, 3 ft. deep, drains S. 15° E.
	79.08	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E S 31 S 32 S 6 S 5 T14N
		1966

	Dep. Resurvey, South Boundary, T. 15 N., R. 21 E., Arizona
CHAINS	Land, rolling to gently rolling. Soil, sandy loam. Timber, widely scattered cedar.
	Undergrowth, sagebrush and bunch grass.
	S. 89°26' W., bet. secs. 6 and 31.
	Over gently rolling land, through widely scattered cedar timber.
.95	Apache Railroad on curve, bears N. 15°14' E. and South.
22.70	Fence, barbed wire, bears N. 18°50' W. and S. 18°15' E.
26.60	Track road, bears SE. and NW.
31.00	Low sag, drains S. 10° E.
39.54	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E 2 S 31 S 6 T14N
	1966
77.10	The cor. of Tps. 14 and 15 N., Rs. 20 and 21 E., monumented by a squared cedar post, 6 ins. diam., 4 ft. above ground, firmly set, mkd. with 6 notches on N., E., S. and W. edges, and faintly scribed marks on each face. Note: Old survey record called for a sandstone (no dimensions given) and bearing trees.
	At the corner point
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R20E R21E S 36 S 31 S 1 S 6 T14N
	1966
	Set the orig. cor. post alongside the iron post.
	Cor. is located in a fence line bearing E. and W.
	Land, gently rolling to level.
	Soil, sandy loam with severe erosion the last ½ mile. Timber, widely scattered cedar. Undergrowth, sagebrush, bunch grass and cacti.
1	

Den.	Resurvey,	East	Boundary,	т.	15 N.,	R.	21 E.,	Arizona
Den.	MCGGT ACA	циос	DOGILGGE / 9				,	

		Dep. Resulvey, East Boundary, 1. 15 N., R. 21 1., Illians
	CHAINS	Dependent Resurvey of the East Boundary Township 15 North, Range 21 East
	·	Reestablishment of the Survey Executed by H. Meyrick in 1883
		Cor. points along the E. bdy. were determined by the broken boundary method, based on the record of the 1883 retracement by H. Meyrick.
		From the cor. of Tps. 14 and 15 N., Rs. 21 and 22 E.
		N. 1°01' W., bet. secs. 31 and 36.
		Over rolling land, through scattered cedar timber.
	6.50	East rim of Silver Creek Canyon, bears S. 15° W. and irregularly N. 20° E.; by triangulation, topography as estimated; desc. over nearly vertical wall about 200 ft. high, facing NW.
2	0.00	Bottom of Silver Creek Canyon, drains N. 20° E.
3	35.00	Approximate west rim of Silver Creek Canyon, bears N. 20° E. and S. 20° W.
4	0.85	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post over an "X" chiseled on solid rock, mound with stone to top, brass cap mkd.
		T15N R21E R22E ♭
		s 36 s 31 1966
		End of triangulation.
		End of triangulation. N. 1°07' W., beginning new measurement.
		-
	.30	N. 1°07' W., beginning new measurement.
4	.30 +0.60	N. 1°07' W., beginning new measurement. Over rolling land, through scattered cedars.
4		N. 1°07' W., beginning new measurement. Over rolling land, through scattered cedars. Small draw, drains SE. Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the
4		N. 1°07' W., beginning new measurement. Over rolling land, through scattered cedars. Small draw, drains SE. Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
4		N. 1°07' W., beginning new measurement. Over rolling land, through scattered cedars. Small draw, drains SE. Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T15N R21E R22E S 25 S 30 S 36 S 31
4		N. 1°07' W., beginning new measurement. Over rolling land, through scattered cedars. Small draw, drains SE. Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T15N R21E R22E S 25 S 30 S 36 S 31 1966 Set a cedar post, 2 ins. diam., 3 ft. long, alongside

· r	Dep. Resurvey, East Boundary, T. 15 N., R. 21 E., Arizona
CHAINS	N. 1°04' W., bet. secs. 25 and 30.
	Over gently rolling land, through widely scattered cedar timber.
40.75	Point for the ½ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
81.50	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	Land, gently rolling. Soil, sandy loam with fine gravel. Timber, widely scattered cedar. Undergrowth, sagebrush and bunch grass.
	N. 1°04' W., bet. secs. 19 and 24.
	Over gently rolling land, through scattered cedar timber.
17.30	Wash, 1.00 ch. wide, 10 ft. deep, drains irreg. NE.
40.65	Point for the 4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
72.10	Fence, barbed wire, bears N. 88°30' E. and S. 88°30' W.
81.49	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, sagebrush and bunch grass.
	N. 1°04' W., bet. secs. 13 and 18.
	Over gently rolling land.
24.90	Wash, 15 1ks. wide, 5 ft. deep, drains NE.
30.40	Low ridge, bears E. and W.
40.71	Point for the ½ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
81.30	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, sagebrush and bunch grass, some small cacti.

	9.
	Dep. Resurvey, West Boundary, T. 15 N., R. 21 E., Arizona
CHAINS	N. 1°04' W., bet. secs. 7 and 12.
	Over gently rolling land.
34.30	Track road, bears S. 11° E. and N. 11° W.
40.65	Point for the ½ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
81.74	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	Land, gently rolling. Soil, sandy loam.
	No timber; undergrowth, sagebrush and bunch grass.
	N. 1°04' W., bet. secs. 1 and 6.
	Over gently rolling land.
40.83	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
81.81	The cor. of Tps. 15 and 16 N., Rs. 21 and 22 E., monumented by a mound of stone, 2 ft. diam., 1 ft. high. After considerable retracement, this is accepted as the best available evidence of the orig. cor.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T16N
	R21E R22E S 36 S 31
	S 1 S 6 T15N
	1966
	Raise a mound of stone S. of the cor.
	Land, gently rolling. Soil, sandy loam with small gravel.
	Timber, none. Undergrowth, sagebrush and bunch grass, scattered cacti.
	Dependent Resurvey of the West Boundary, Township 15 North, Range 21 East
	Reestablishment of the Survey Executed by M. N. Grant in 1883
	From the cor. of Tps. 14 and 15 N., Rs. 20 and 21 E.
	N. 0°06' E., bet. secs. 31 and 36.
	Over gently rolling land, through widely scattered cedar timber.

		10.	
<u>:</u>	CHAINS	Dep. Resurvey, West Boundary, T. 15 N., R. 21 E., Arizona	
	39.00	Dirt road, bears S. 35° E. and N. 35° W.; leave timber.	
÷	41.45	Point for the ½ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.	•
		T15N R20E R21E	.
		s 36 s 31	
		1966	
	80.00	Track road, bears NE. and SW.	
	82.91	Point for the cor. of secs. 25, 30, 31 and 36, at pro-	
		portionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 20 ins. in the ground, brass cap mkd.	
		T15N R20E R21E	
		S 25 S 30 S 36 S 31	•
		1966	
		Raise a mound of stone W. of the cor.	
		Land, gently rolling. Soil, silty clay loam. Timber, widely scattered cedars on S ½ mile. Undergrowth, sagebrush and bunch grass.	
	•	N. 0°06' E., bet. secs. 25 and 30.	
		Over gently rolling land.	
	13.90	Low sag, drains NW.	
	41.45	Point for the ½ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 20 ins. in the ground, brass cap mkd.	
		T15N	
		R20E R21E	,
		s 25[s 30	
		1966	
		Raise a mound of stone W. of the cor.	
	82.91	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.	

 	Dep. Resurvey, West Boundary, T. 15 N., R. 21 E., Arizona	_
CHAINS	Set the iron post 20 ins. in the ground, brass cap mkd.	
	T15N R20E R21E S 24 S 19 S 25 S 30 1966	
	Raise a mound of stone W. of the cor.	
	Land, gently rolling. Soil, silty sandy loam. No timber; undergrowth, sagebrush and bunch grass.	
	N. 0°06' E., bet. secs. 19 and 24.	
	Over gently rolling land.	
18.20	Fence, barbed wire, bears S. 85°40' E. and N. 85°40' W.	
21.10	Low sag, drains W.	
28.70	Fence, barbed wire, bears S. 10°10' E. and N. 10°10' W.	
41.45	Point for the ½ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 20 ins. in the ground, brass cap mkd.	
	T15N R20E R21E 宏	
	S 24 S 19 1966	
	from which	
	A NS. fence, bears West 18 1ks. dist.	
	Raise a mound of stone W. of the cor.	
82.91	The cor. of secs. 13, 18, 19 and 24, monumented by a sandstone, 24 x 6 x 4 ins., firmly set, mkd. with 3 notches on N. and S. faces.	
	At the corner point	
	Set the iron post 18 ins. in the ground, brass cap mkd.	
	T15N R20E R21E S 13 S 18 S 24 S 19 1966	
	from which	
	An old squared post, 4 ins. diam., 4 ft. long, bears N. 11°19' E., 25 lks. dist.; post is set in N-S. fence line.	
	Deposit the orig. cor. stone alongside the iron post.	
	Raise a mound of stone W. of the cor.	

Dep. Resurvey, West Boundary, T. 15 N., R. 21 E., Ariz	Dep.	Resurvey,	West	Boundary,	т.	15	Ν.,	R.	21	Ε.,	Arizon
--	------	-----------	------	-----------	----	----	-----	----	----	-----	--------

		Dep. Resurvey, west boundary, 1. 13 N., R. 21 E., Arizona
	CHAINS	Land, gently rolling. Soil, silty loam. No timber; undergrowth, sagebrush and bunch grass.
		N. 0°26' E., bet. secs. 13 and 18.
		Over nearly level land.
	38.80	Track road, bears W. and N. 75° E.
	40.82	Point for the ½ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T15N R20E R21E 点 S 13 S 18
		1966
		from which
		A N-S. fence line, bears East 6 lks. dist.
		Raise a mound of stone W. of the cor.
	61.20	Dyke, bears E. and W.
	66.60	Dyke, bears E. and W.
	78.60	Wash, 20 lks. wide, 2 ft. deep, drains N. 15° E.
	79.50	Wash, 60 lks. wide, 4 ft. deep, drains N. 30° E.
	81.64	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T15N R20E R21E S 12 S 7 S 13 S 18 1966
		from which
		A N-S. fence, bears East 7 lks. dist.
		Raise a mound of stone W. of the cor.
		Land, nearly level. Soil, clay loam. Timber, none.
		Undergrowth, sagebrush and bunch grass.
1		

	13.
	Dep. Resurvey, West Boundary, T. 15 N., R. 21 E., Arizo
CHAINS	N. 0°26' E., bet. secs. 7 and 12.
	Over nearly level land.
10.00	Leave low washed area, asc. S. slope.
13.00	Top of ascent, thence over nearly level land.
40.82	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R20E R21E
	s 12 s 7
	1966
	from which
	A N-S. fence, bears East, 9 lks. dist.
81.64	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R20E R21E S 1 S 6 S12 S 7
	1966
	from which
	A N-S. fence, bears East, 19 1ks. dist.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit bush.
-	N. 0°26' E., bet. secs. 1 and 6.
	Over nearly level land.
40.82	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented by a sandstone, 13 x 12 x 3 ins., firmly set, mkd. $\frac{1}{4}$ on W. face.
	At the corner point,
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R20E R21E
	s 1 s 6
	1966

Dep.	Resurvey,	North	Boundary,	Τ.	15 N.,	R.	21 E.,	Arizona
------	-----------	-------	-----------	----	--------	----	--------	---------

	7, 2, 2, 3, 11, 12, 11, 11, 11, 11, 11, 11, 11, 11
CHAINS	from which
	A N-S. fence, bears East, 26 lks. dist.
	Deposit the orig. cor. stone alongside the iron post.
	N. 0°46' E., beginning new measurement.
	Over nearly level land.
40.87	The cor. of Tps. 15 and 16 N., Rs. 20 and 21 E., monumented by a sandstone, $9 \times 6 \times 2$ ins., firmly set, mkd. with 6 notches on N., E., S. and W. faces.
	At the corner point,
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T16N R20E R21E S 36 S 31 S 1 S 6 T15N
	1966
	from which
	Cor. of fences bears East 05 1ks. dist.; fences bear N. 88°15' E., S. and S. 88°15' W.
	Deposit the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	Dependent Resurvey of the North Boundary, Township 15 North, Range 21 East
	Reestablishment of the Survey Executed by H. Meyrick in 1883
	From the cor. of Tps. 15 and 16 N., Rs. 21 and 22 E.
	S. 89°58' W., bet. secs. 1 and 36.
	Over gently rolling land.
2.50	Fence, barbed wire, bears N. and S.
29.00	Wash, 30 1ks. wide, 7 ft. deep, drains N. 60° E.
39 . 5 1	Point for the ½ sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
	` `

Den.	Resurvey,	North	Boundary,	т.	15 N.	, R.	21 E.,	Arizona
11(-1)	resurvey.	HOTCH	Dograda			,		

		Dep. Resurvey, North Boundary, 1. 12	
	CHAINS	Set the iron post 24 ins. in the ground, brass cap mkd.	
		T16N R21E 1/4 S 36 T15N	
•		1966	
-		The cor. is located 50 lks. North of a wash, 30 lks. wide, 7 ft. deep, draining East.	
		Raise a mound of stone N. of the cor.	
	60.10	Wash, 1.00 ch. wide, 5 ft. deep, drains S. 86° E.	
	68.20	Wash, 5 1ks. wide, 2 ft. deep, drains N. 80° E.	
	79.02	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.	
		T16N R21E S 35 S 36 S 2 S 1 T15N	
		1966	
		Land, gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.	
		S. 89°58' W., bet. secs. 2 and 35.	-
		Over gently rolling land.	
	9.80	Wash, 5 lks. wide, 2 ft. deep, drains N. 35° E.	
	39.51	Point for the ½ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T16N R21E	
		$\begin{array}{ccc} \frac{1}{4} & \frac{S}{S} & \frac{35}{5} \\ & \frac{1}{4} & \frac{1}$	
		1966	
		Raise a mound of stone N. of the cor.	
	79.02 -	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T16N R21E S 34 S 35 S 3 S 2 T15N	
		1966	
	7 (0-4-1	4) (formerly 4–673b) USDI—BLM FIELD	NOTE

		Dep. Resurvey, North Boundary, T. 15 N., R. 21 E., Arizona	
1	CHAINS	Raise a mound of stone W. of the cor.	
		Land, gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.	
	·	S. 89°58' W., bet. secs. 3 and 34.	-
;		Over gently rolling land.	
	12.90	Wash, 10 1ks. wide, 2 ft. deep, drains N. 65° E.	
	39.51	Point for the ½ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.	
į.		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T16N R21E 2 S 34 S 3 T15N	
		1966	
		Raise a mound of stone N. of the cor.	,
	74.80	Fence, barbed wire, bears S. 12°30' E. and N. 12°30' W.	
	74.85	Power line, bears S. 12°30' E. and N. 12°30' W.	
	77.90	Arizona State Highway No. 77, bears S. 12°30' E. and N. 12°30' W.	
	79.02	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 24 ins. in the ground, brass cap mkd.	
		T16N R21E S 33 S 34 S 4 S 3 T15N	
	-	1966	
		from which	
		A windmill, bears N. 79°18' W., 4.20 chs. dist. Raise a mound of stone W. of the cor.	
		Land, gently rolling.	
		Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.	
		S. 89°58' W., bet. secs. 4 and 33.	
	·	Over gently rolling land.	
	1.85	Telephone line, bears S. 12°30' E. and N. 12°30' W.	
	1.90	Fence, barbed wire, bears S. 12°30' E. and N. 12°30'W.	
	15.60	Old bladed road, bears NE. and SW.	

	Dep. Resurvey, North Boundary, T. 15 N., R. 21 E., Arizona
CHAINS 36.60	Track road, bears NE. and SW.
39.51	Point for the ½ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T16N R21E ½ S 33 S 4 T15N
	1966
	Raise a mound of stone N. of the cor.
79.02	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T16N R21E S 32 S 33 S 5 S 4 T15N
	1966
	Set a cedar post alongside and raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	S. 89°58' W., bet. secs. 5 and 32.
	Over gently rolling land.
22.80	Bladed road, bears S. 26°20' E. and N. 26°20' W.
23.30	Apache railroad, bears S. 26°20' E. and N. 26°20' W.
34.71	Low swale, drains N.
39.51	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T16N R21E 2 S 32 T15N
	1966
	from which
	A large rock pile with a post, 3 ins. diam., 3 ft. long in the center, bears N. 86°37' W., 5.16 chs. dist.

•		Dep. Resurvey, North Boundary, T. 15 N., R. 21 E., Arizona	
	CHAINS		
÷	43.30	Fence, barbed wire, bears N. and S.	
	43.90	Old bladed road, bears N. and S.	
:	79.02	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.	
1		Set the iron post 22 ins. in the ground, brass cap mkd.	
•		T16N R21E S 31 S 32	•
		S 6 S 5 T15N	
į		1966	
		Deposit glass in hole alongside the iron post.	
		Raise a mound of stone W. of the cor.	
		Land, gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.	
		S. 89°58' W., bet. secs. 6 and 31.	
		Over gently rolling land.	
	8.10	Enter small patch of scattered cedar timber.	
	19.80	Wash, 1.00 ch. wide, 10 ft. deep, drains NE.	
	21.10	Leave cedar timber.	
	39.51	Point for the ½ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.	
		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.	
		T16N R21E	
		1 S 31 S 6	
		S 6 T15N	
		1966	•
		from which	•
		A fence, bearing E. and W., bears North 80 lks. dist.	
		Set a cedar post alongside the cor.	
	48.10	Low sag, drains N.	
	65.10	The cor. of Tps. 15 and 16 N., Rs. 20 and 21 E.	
		Land, gently rolling. Soil, clay loam. Timber, small patch of cedar. Undergrowth, sagebrush and bunch grass.	
	,		

19.

Dep. Resur	vev, Subdi	visional	Lines,	Τ.	15	Ν.,	R.	21	Ε.,	Arizona
Deb. Resur	vey, bubui	VISIONAL	штись,	.		_,,,			_ ,	

		Dependent Resurvey of the Subdivisional Lines, Township 15 North, Range 21 East
		Reestablishment of the Survey Executed by H. Meyrick in 1883
-		From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
-		N. 1°13' W., bet. secs. 35 and 36.
		Over gently rolling land.
	40.83	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
		s 35 s 36
		1966
		from which
		A wind mill, bears N. $31^{\circ}51$ ' E., 16.97 chs. dist.
	48.70	Top of low ridge, bears E. and W.
•	60.30	Track road, bears S. 80° E. and N. 80° W.
	78.50	Low swale, drains E.
	81.66	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E S 26 S 25 S 35 S 36
		1966
		Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
		S. 89°36' W., bet. secs. 25 and 36.
		Over nearly level land.
	39.63	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

		20.	
		Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 21 E., Ariz	ona
	CHAINS	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.	
:		T15N R21E 2 S 25 2 S 36	
		1966	-
	63.50	Track road and old telegraph line, bears N. and S.	_
	79.26	The cor. of secs. 25, 26, 35 and 36.	
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.	
		N. 0°54' W., bet. secs. 25 and 2 6.	i.
		Over gently rolling land, through widely scattered cedar timber.	
	40.60	Leave cedar timber.	
	40.82	Point for the ½ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor. This cor. is not monumented.	·
		From the corner point	
		A stock reservoir, bears S. 69° E., 10.30 chs. dist.	
		A stock reservoir, bears N. 8° E., 27.83 chs. dist.	
	75.10	Track road, bears SE. and NW.	
	81.64	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.	
		Land, gently rolling. Soil, sandy loam with loose gravel on surface. Timber, widely scattered cedars on S. ½ mile. Undergrowth, sagebrush and bunch grass.	
		From the point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.	
		S. 89°42' W., bet. secs. 24 and 25.	
		Over gently rolling land.	
	15.40	Wash, 20 lks. wide, 3 ft. deep, drains irreg. N.	
	39.50	Point for the ½ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.	
	79.00	Point for the cor. of secs. 23, 24, 25 and 26.	
		Land, gently rolling. Soil, clay loam. Timber, none.	

Undergrowth, sagebrush, bunch grass and rabbit bush.

	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Ari
CHAINS	N. 1°17' W., bet. secs. 23 and 24.
	Over gently rolling land.
40.83	Point for the ½ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
60.30	Top of ridge, bears E. and W.; enter widely scattered cedar timber.
81.66	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
:	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E <u>S14 S13</u> S23 S24
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunch grass.
	From the point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	S. 89°49' W., bet. secs. 13 and 24.
	Over nearly level land.
6.50	Fence, barbed wire, bears S. 0°13' E. and N. 0°13' W.
39.65	Point for the ½ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	From the corner point
	A stock reservoir, bears N. 27°33' E., 4.64 chs. dist.
45.10	Wash, 30 1ks. wide, 6 ft. deep, drains NE.
48.90	Wash, 20 1ks. wide, 10 ft. deep, drains irreg. NE.
79.30	The cor. of secs. 13, 14, 23 and 24.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 1°18' W., bet. secs. 13 and 14.
	Over gently rolling land, through widely scattered cedar timber.
33.80	Base of vertical rock cliff, bears E. and W.
1 25 50	Rim of vertical cliff, bears E. and W.; descend
35.50	over N. slope.

Dep.	Resurvey,	Subdivisional	Lines,	T.15	N.,R.	21	Ε.,	Arizona

		bep. Resurvey, Subdivisional Lines, 1.15 N., R. 21 E., Alizona
	CHAINS	
	40.83	Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.
,		Set the iron post 18 ins. in the ground, brass cap mkd.
:		T15N R21E
		s 14 s 13
		1966
		Raise a mound of stone W. of the cor.
	56.30	Leave widely scattered cedar timber.
	63.60	Fence, barbed wire, bears S. 87°39' E. and N. 87°39' W.
	81.66	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T15N R21E S 11 S 12 S 14 S 13
		1966
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunch grass.
		
		From the point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
		N. 89°56' W., bet. secs. 12 and 13.
		Over nearly level land.
l	5.00	Fence, barbed wire, bears N. 0°9' E. and S. 0°9' W.
	39.80	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	79.60	The cor. of secs. 11, 12, 13 and 14.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and rabbit brush.
		N. 0°55' W., bet. secs. 11 and 12.
	į	Over gently rolling land.
	21.40	Ridge, bears E. and W.
	40.82	Point for the ½ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	81.64	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.
\perp		

Dep.	Resurvey.	Subdivisional	Lines,	T.15	N.,R.	21	Ε.,	Arizona
------	-----------	---------------	--------	------	-------	----	-----	---------

	Dep. Resulvey, Subdivisional Lines, 1:15 M., R. 21 L., M. 12000
CHAINS	Set the iron post 24 ins. in the ground, brass cap mkd.
	T15N R21E
	<u>S 2 S 1</u> S11 S12
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, sandy loam, gravel on the surface. No timber; undergrowth, sagebrush and bunch grass.
	From the point for the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
	West, bet. secs. 1 and 12.
	Over gently rolling land.
3.50	Track road, bears S. 0°14' E. and N. 0°14' W.
3.60	Fence, barbed wire, bears S. 0°14' E. and N. 0°14' W.
9.30	Track road, bears N. 5° E. and S. 5° W.
33.30	Rolling ridge, bears N. and SW. for 3 chs., thence SE.
39.69	Point for the ½ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
79.38	The cor. of secs. 1, 2, 11 and 12.
	Land, gently rolling to nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit bush.
	N. 0°50' W., bet. secs. 1 and 2.
	Over gently rolling land.
14.00	Wash, 20 1ks. wide, 4 ft. deep, drains NE.
40.83	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E
	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$
	1966
	from which
	A windmill, bears N. 30°11' W., 30.74 chs. dist.
60.10	Wash, 25 1ks. wide, 6 ft. deep, drains NE. for 1 ch., thence E.

Don	Dogumerore	Subdivisional	Times	Tr.	15	NΤ	D 21	다	Arizona
Dep.	Resurvey,	Dubutatstonar	TITHES,	_ +	LJ	TA .	, A - 4 I	ر • تا	ALIZUNA

81.78	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp.
	N. 1°28' W., bet. secs. 34 and 35.
	Over gently rolling land, through scattered cedar timber.
5.10	Fence, barbed wire, bears N. 86°36' E. and S. 86°36' W.; leave scattered cedar timber.
28.80	Telephone line, bears S. 9°11' E. and N. 9°11' W.
35.30	Wash, 100 1ks. wide, 5 ft. deep, drains irreg. E.
39.30	Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W.
40.86	Point for the ½ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	s 34 s 35
1	
	1966
	·
	1966
	1966 from which
51.50	1966 from which A N-S. fence, bears East, 11 lks. dist.
51.50 52.90	from which A N-S. fence, bears East, 11 lks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and
	from which A N-S. fence, bears East, 11 lks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W.
52.90	from which A N-S. fence, bears East, 11 lks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W. Wash, 100 lks. wide, 5 ft. deep, drains irreg. E.
52 . 90 63 . 70	from which A N-S. fence, bears East, 11 lks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W. Wash, 100 lks. wide, 5 ft. deep, drains irreg. E. Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W.
52.90 63.70 65.60	from which A N-S. fence, bears East, 11 lks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W. Wash, 100 lks. wide, 5 ft. deep, drains irreg. E. Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W. Track road, bears S. 60° E. and N. 60° W.
52.90 63.70 65.60 76.20	from which A N-S. fence, bears East, 11 1ks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W. Wash, 100 1ks. wide, 5 ft. deep, drains irreg. E. Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W. Track road, bears S. 60° E. and N. 60° W. Power line, bears S. 9°11' E. and N. 9°11' W. Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of
52.90 63.70 65.60 76.20	from which A N-S. fence, bears East, 11 1ks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W. Wash, 100 1ks. wide, 5 ft. deep, drains irreg. E. Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W. Track road, bears S. 60° E. and N. 60° W. Power line, bears S. 9°11' E. and N. 9°11' W. Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of orig. cor.
52.90 63.70 65.60 76.20	from which A N-S. fence, bears East, 11 lks. dist. Raise a mound of stone W. of the cor. Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W. Wash, 100 lks. wide, 5 ft. deep, drains irreg. E. Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W. Track road, bears S. 60° E. and N. 60° W. Power line, bears S. 9°11' E. and N. 9°11' W. Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd. T15N R21E S 27 S 26

25.

Dep. Resurvey, Sub	divisional Lines,	T. 15	N.,R.21	E.,Arizona
--------------------	-------------------	-------	---------	------------

1		bep. Resurvey, Subdivisional Lines, 1. 15 N., K.21 E., Alizo
	CHAINS	Land, gently rolling.
		Soil, clay loam. Timber, scattered cedar.
	·	Undergrowth, sagebrush, bunch grass and cacti.
		From the cor. of secs. 25, 26, 35 and 36.
		S. 89°29' W., bet. secs. 26 and 35.
•		Over nearly level land.
•	39.71	Point for the ½ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	79.42	The cor. of secs. 26, 27, 34 and 35.
		Land, nearly level.
		Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit bush.
		N. 0°50' W., bet. secs. 26 and 27.
		Over nearly level land.
	40.85	Point for the ½ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
	60.00	Desc. over N. slope.
	67.00	Bottom of desc., thence over nearly level land.
- 407	81.70	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T15N R21E S 22 S 23 S 27 S 26
		1966
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, clay loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunch grass.
		From the point for the cor. of secs. 23, 24, 25 and 26.
		S. 89°32' W., bet. secs. 23 and 26.
		Over gently rolling land.
	5.20	Track road, bears SE. and NW.
	39.66	Point for the ½ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor. This corner is not monumented.
- 1	;	

26.

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona

CHAINS 79.32	From the corner point A stock pond, bears N. 32°07' E., 25.37 chs. dist. The cor. of secs. 22 ,23, 26 and 27. Land, gently rolling.
79.32	A stock pond, bears N. 32°07' E., 25.37 chs. dist. The cor. of secs. 22 ,23, 26 and 27. Land, gently rolling.
79.32	The cor. of secs. 22,23, 26 and 27. Land, gently rolling.
,,,,,,	Land, gently rolling.
1	Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass, rabbit bush and cacti.
	N. 1°22' W., bet. secs. 22 and 23.
	Over nearly level land.
14.40	Track road, bears irregularly E. and W.
40.86	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate d ist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E
	s 22 s 23
	1966
	Raise a mound of stone W. of the corner.
72.00	Base of bluff, bears E. and W.
72.40	Top of bluff, bears E. and W.
76.50	Base of bluff, bears E. and W.
79.90	Top of bluff, bears E. and W.
81.72	Point for the sec. cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post over an "X" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T15N R21E S 15 S 14 S 22 S 23
	1966
	Cor. falls on top of spur, sloping N.
	Land, gently rolling. Soil, clay loam.
	Timber, widely scattered cedar. Undergrowth, sagebrush and bunch grass.

Dep.	Resurvey,	Subdivisional	Lines,	T.15	N.,R.	21	E.,Arizona
------	-----------	---------------	--------	------	-------	----	------------

	I	Dep. Resurvey, Subdivisional Lines, 1.15 N., K. 21 E., Alizona
	CHAINS	From the cor. of secs. 13, 14, 23 and 24.
		S. 89°33' W., bet. secs. 14 and 23.
		Over nearly level land, through widely scattered cedar timber.
	39.73	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
•		Set the iron post 24 ins. in the ground, brass cap mkd.
		T15N R21E \$\frac{S}{5} \frac{14}{S} \frac{23}{23}
-	-	1966
		Raise a mound of stone N. of the cor.
	74.30	Base of bluff, asc. over spur sloping from the W.
	79.46	The cor. of secs. 14, 15, 22 and 23.
		Land, nearly level to rolling. Soil, clay loam. Timber, widely scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
		N. 1°05' W., bet. secs. 14 and 15.
		Over rolling land.
	4.30	Desc. steep N. point of spur.
	8.90	Bottom of spur, thence over nearly level land.
	40.86	Point for the ½ sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
		s 15 [†] s 14
		1966
	43.20	Top of low bluff, bears irreg. E. and W., desc. N. slope.
	44.20	Base of bluff, bears irreg. E. and W., thence over nearly level land.
	67.10	Fence, barbed wire, bears S. 88°04' E. and N. 88°04' W.
	81.72	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.

· · · · · · · · · · · · · · · · · · ·	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
CHAINS	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	<u>s 10 s 11</u>
\$	S 15 S 14 1966
	Set a cedar post, 3 ins. diam., 5 ft. long, alongside the cor.
	Land, nearly level to rolling.
	Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°38' W., bet. secs. 11 and 14.
	Over nearly level land.
39.54	Point for the ½ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{S}{S} \frac{11}{14}$
	1966
	Raise a mound of stone N. of the cor.
79.08	The cor. of secs. 10, 11, 14 and 15.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and
	rabbit brush.
	N. 1°12' W., bet. secs. 10 and 11.
	Over nearly level land.
40.86	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E
	s 10 s 11
	1966
57.70	Wash, 30 1ks. wide, 5 ft. deep, drains irregularly NE.
64.70	Wash, 50 1ks. wide, 8 ft. deep, drains irregularly E.
75.00	Wash, 20 1ks. wide, 4 ft. deep, drains E.
81.72	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of

Dep.	Resurvey,	Subdivisional	Lines,	T.15	N.,R.	21	E.,Arizona
------	-----------	---------------	--------	------	-------	----	------------

		Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
	CHAINS	
		Set the iron post 12 ins. in the ground, in a mound of stone, brass cap mkd.
		T15N R21E
		<u>S 3 S 2</u>
		S 10 S 11
		1966
*		Land, nearly level.
		Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
•		No timber, didenglowen, sagebrash and banen grass.
		From the cor. of secs. 1, 2, 11 and 12.
		S. 89°42' W., bet. secs. 2 and 11.
		Over nearly level land.
	39.75	Point for the ½ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
	1	$\frac{1}{4} \frac{S}{S} \frac{2}{11}$
		1966
		from which
		A reservoir, bears N. 67°57' E., 19.73 chs. dist.
	51.70	Wash, 30 1ks. wide, 4 ft. deep, drains NE.
	79.50	The cor. of secs. 2, 3, 10 and 11.
		Land, nearly level.
		Soil, clay loam. Timber, none.
		Undergrowth, sagebrush and bunch grass.
		N. 0°32' W., bet. secs. 2 and 3.
		Over nearly level land.
	17.70	Track road, bears S. 85° E. and N. 85° W.
	40.85	Point for the ½ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
		s 3 s 2
		·
		1966
	82.15	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
		Land, nearly level.
		Soil, clay loam.
		No timber; undergrowth, sagebrush and bunch grass.
	1	[

	30.
 CHAINS	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.
	N. 1°34' W., bet. secs. 33 and 34.
	Over rolling land, through medium cedar timber.
17.60	Rocky wash, 150 lks. wide, 6 ft. deep, drains E.
22.00	Timber, becomes scattered.
40.96	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
:	T15N R21E
	s 33 s 34
	1966
	Raise a mound of stone W. of the cor.
46.80	Ridge, bears E. and W.
47.40	Track road, bears N. 89° E. and S. 89° W.
48.70	Fence, barbed wire, bears N. 89° E. and S. 89° W.
55.30	Top of spur, slopes E.; leave cedar timber, desc. over N. slope.
81.50	Track road, bears irregularly S. 24° E. and N. 24° W.
81.92	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E S 28 S 27 S 33 S 34
	1966
	Raise a mound of stone W. of the cor.
	Land, rolling to gently rolling. Soil, exposed sandstone on S. ½ mile; clay loam on N. ½ mile. Timber, medium to scattered cedar.
	Undergrowth, sagebrush, bunch grass and rabbit brush.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°34' W., bet. secs. 27 and 34.
	Over nearly level land.
1.00	Power line, bears S. 9°11' E. and N. 9°11' W.
2.40	Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W.
3.90	Arizona State Highway No. 77, bears S. 9°11' E. and N. 9°11' W.

	Dep. Resurvey, Subdivisional Lines, T.15 N.,R. 21 E., Arizona
CHAIÑS 5.50	Fence, barbed wire, bears S. 9°11' E. and N. 9°11' W.
7.00	Telephone line, bears S. 9°11' E. and N. 9°11' W.
22.10	Track road, bears N. 23° E. and S. 23° W.
39.60	Point for the ½ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E 1/4 S 27 S 34
	1966
	Raise a mound of stone N. of the cor.
55.70	Wash, 20 1ks. wide, 3 ft. deep, drains S. 75° E.
79.20	The cor. of secs. 27, 28, 33 and 34.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 0°46' W., bet. secs. 27 and 28.
	Desc. over gently rolling land.
8.10	Enter nearly level land.
40.95	Point for the ½ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	s 28 s 27
	1966
	from which
	A dyke, bearing N. and S., bears S. 7°09' E., 20.11 chs. dist.
	Raise a mound of stone W. of the cor.
65.10	Enter scattered cedar timber.
81.90	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence

	32. Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
CHAINS	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E S 21 S 22 S 28 S 27
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, sandy loam. Timber, none to scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°44' W., bet. secs. 22 and 27.
:	Over gently rolling land.
7.60	Enter scattered cedar timber.
13.00	Power line, bears S. 14°09' E. and N. 14°09' W.
14.50	Fence, barbed wire, bears S. 14°09' E. and N. 14°09' W.
16.00	Arizona State Highway No. 77, bears S. 14°09' E. and N. 14°09' W.
17.60	Fence, barbed wire, bears S. 14°09' E. and N. 14°09' W.
19.10	Telephone line, bears S. 14°09' E. and N. 14°09' W.
39.57	Point for the ½ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E 2 S 22 3 27
	1966
	Raise a mound of stone N. of the cor.
50.10	Bottom of spur, projecting from the N.
69.50	Top of oblong knoll, bears N. 30° E., 7.50 chs. dist., and S. 30° W., 3.50 chs. dist.
79.14	The cor. of secs. 21, 22, 27 and 28.
	Land, gently rolling. Soil, clay loam, first half, then sandy loam. Timber, none to scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 1°44' W., bet. secs. 21 and 22.
	Over gently rolling land, through scattered cedar timber.
7.80	Ridge, bears E. and W.

	Don Poguryov Cubdivisional Time m 15 v n 01 - · ·
CHAI	Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 21 E., Ari
13.10	Track road, bears SE. and NW.
40.97	Point for the ½ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	s 21 s 22
·	1966
	from which
	A windmill, bears S. 59°52' W., 17.93 chs. dist.
	Set a cedar post alongside and raise a mound of stone W. of the cor.
43.90	Draw, drains E.
81.94	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E S 16 S 15 S 21 S 22
	1966
	Set a squared cedar post, 3 ins. diam., 4 ft. long, alongside the cor.
	Land, gently rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89°51' W., bet. secs. 15 and 22.
	Over heavy rolling land, through widely scattered cedar timber; desc. over W. slope.
2.00	Base of bluff, bears N. and S.
24.80	Power line, bears S. 12°46' E. and N. 12°46' W.
26.20	Fence, barbed wire, bears S. 12°46' E. and N. 12°46' W.
27.90	Arizona State Highway No. 77, bears S. 12°46' E. and N. 12°46' W.
29.60	Fence, barbed wire, bears S. 12°46' E. and N. 12°46' W.
31.10	Telephone line, bears S. 12°46' E. and N. 12°46' W.
31.40	Base of bluff, bears E. and W.
32.80	Top of bluff, bears E. and W.

ת	·
	ep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizo
39.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post over an "X" chiseled on solid rock, mound with stone to top, brass cap mkd.
	T15N R21E
	$\frac{1}{4}$ $\frac{S}{S}$ $\frac{15}{22}$
	1966
43.90	Desc. W. slope.
49.70	Enter nearly level land.
79.56	The cor. of secs. 15, 16, 21 and 22.
	Land, broken with high bluffs E. ½ mile, gently rolling on remainder. Soil, clay loam. Timber, scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 1°01' W., bet. secs. 15 and 16.
	Over gently rolling land, through scattered cedar timber.
8.20	Ridge, bears E. and W.
11.30	Edge of bluff, bears irreg. E. and W., desc. N. slope.
15.40	Base of bluff, enter nearly level land; leave timber.
38.30	Track road, bears E. and W.
40.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	s 16 s 15
	1966
	Raise a mound of stone W. of the cor.
76.10	Fence, barbed wire, bears S. 81°45' E. and N. 81°45' W.
79.60	Dim track road, bears NE. and SW.
81.90	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
	portionate dist.; there is no remaining evidence of
	portionate dist.; there is no remaining evidence of the orig. cor.

35.

Dep.	Resurvey,	Subdivisional	Lines,	T.15	N.,R.	21	Ε.,	Arizona
------	-----------	---------------	--------	------	-------	----	-----	---------

_		bep. Resurvey, Subdivisional Lines, 1.15 N., R. 21 E., Ar
	CHAINS	Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, clay loam.
		Timber, scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
		From the cor. of secs. 10, 11, 14 and 15.
		West, bet. secs. 10 and 15.
		Over nearly level land.
	38.50	Wash, 20 1ks. wide, 5 ft. deep, drains irreg. N., for 20 chs., then W.
	39.73	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
		T15N R21E $\frac{1}{4} \frac{S}{S} \frac{10}{15}$
		1966
		from which
		A stock pond, bears N. 17°42' E., 38.70 chs. dist.
		Raise a mound of stone N. of the cor.
	41.40	Power line, bears S. 12°25' E. and N. 12°25' W.
	42.80	Fence, barbed wire, bears S. 12°25' E. and N. 12°25' W.
	44.30	Arizona State Highway No. 77, bears S. 12°25' E. and N. 12°25' W.
	45.90	Fence, barbed wire, bears S. 12°25' E. and N. 12°25' W.
	47.50	Telephone line, bears S. 12°25' E. and N. 12°25' W.
	48.70	Wash, 30 1ks. wide, 7 ft. deep, drains N., 2.80 chs., then N. 36° E.
	50.20	Fence, barbed wire, bears N. 36°08' E. and S. 36°08' W.
	76.00	Track road, bears N. 40° E. and S. 40° W.
	79.46	The cor. of secs. 9, 10, 15 and 16.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	-	
		N. 0°58' W., bet. secs. 9 and 10.
		Over nearly level land.
	28.00	Track road, bears N. 85° E. and S. 85° W.
	39.60	Fence, barbed wire, bears S. 88°17' E. and N. 88°17' W.
١	ı	

	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
chains 40.95	Point for the ½ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of
	the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	s 9 s 10
	1966
	Raise a mound of stone W. of the cor.
81.90	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E
	<u>S 4 S 3</u> S 9 S 10
	1966
	from which
	A pit, 18 x 12 x 3 ft., bears South, 61 lks. dist.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	From the cor. of secs. 2, 3, 10 and 11.
-	N. 89°51' W., bet. secs. 3 and 10.
	Over nearly level land.
39.55	Point for the ½ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E \$\frac{1}{4} \frac{S}{S} \frac{3}{10}
	1966
58.00	Fence, barbed wire, bears S. 12°27' E. and N. 12°27' W.
	Power line, parallels fence.
59.60	Fence, barbed wire, parallels power line.
60.80	Arizona State Highway No. 77, bears S. 12°27' E. and N. 12°27' W.
62.30	Fence, barbed wire, bears S. 12°27' E. and N. 12°27' W.
ŀ	

		37.
]	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
	CHAINS	Telephone line, bears S. 12°27' E. and N. 12°27' W.
	63.80	
1	79.10	The cor. of secs. 3, 4, 9 and 10.
		Land, nearly level. Soil, clay loam.
		Timber, none.
		Undergrowth, sagebrush, bunch grass and rabbit brush.
		N. 0°32' W., bet. secs. 3 and 4.
		Over nearly level land.
	40.95	Point for the ½ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T15N R21E
		s 4 s 3
		1966
		Set a post, 4 ins. diam., 5 ft. long, alongside the cor.
	72.70	Fence, barbed wire, bears S. 12°26' E. and N. 12°26' W.
	72.80	Telephone line, bears S. 12°26' E. and N. 12°26' W.
	81.97	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
		N. 1°35' W., bet. secs. 32 and 33.
		Over nearly level land.
	13.00	Ridge, bears irreg. E. and W.
	37.50	Track road, bears E. and W.
	41.06	Point for the ½ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T15N R21E
		s 32 s 33
		1966
		from which
		A windmill, bears N. 75°46' W., 55.36 chs. dist.
		1

Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Ari
--

	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Ari
CHAINS	Paigo a mound of atoms II as all
5 0 (0	Raise a mound of stone W. of the cor.
58.60	Track road, bears NE. and SW.
82.12	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E S 29 S 28 S 32 S 33
	1966
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 27, 28, 33 and 34.
	S. 89°33' W., bet. secs. 28 and 33.
	Over nearly level land.
.50	Track road, bears S. 40° E. and N. 40° W.
9.40	Draw, drains N. 30° E.
3.10	Fence, barbed wire, bears S. 18°02' E. and N. 18°02' W.
9.53	Point for the ½ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{28}{33}$
	1966
	Raise a mound of stone N. of the cor.
9.80	Track road, bears N. 25° E. and S. 25° W.
9.06	The cor. of secs. 28, 29, 32 and 33.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 0°47' W., bet. secs. 28 and 29.
	Over nearly level land.
5.00	Wash, 15 lks. wide, 4 ft. deep, drains irregularly E.
41.04	Point for the ½ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep.	Resurvey,	Subdivisional	Lines,	T.15	N.,R.	21	E.,Arizona

7	
CHAINS	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E
	S 29 S 28
	1966
	Raise a mound of stone W. of the cor.
82.09	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E S 20 S 21 S 29 S 28
	1966
	Raise a mound of stone W. of the cor.
	Land, nearly level to gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	, salar, sagestain and banen grass.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°41' W., bet. secs. 21 and 28.
	Over gently rolling land, through scattered cedar timber.
31.50	Leave scattered cedar timber.
39.52	Point for the ½ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E 2 S 21 3 S 28
,	1966
	Raise a mound of stone N. of the cor.
58.60	Fence, barbed wire, bears S. 18°38' E. and N. 18°38' W.
79.04	The cor. of secs. 20, 21, 28 and 29.
	Land, gently rolling.
	Soil, clay loam. Timber, scattered cedar on E. ½ mile. Undergrowth, sagebrush, bunch grass and rabbit brush.

D	ep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
CHAINS	
	N. 1°37' W., bet. secs. 20 and 21.
	Over gently rolling land.
39.10	Fence, barbed wire, bears S. 85°27' W. and N. 85°27' E. for 8.45 chs. dist. to cor. of fences bearing N., S. and S. 85°27' W.
41.06	Point for the 1/2 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	$\mathbf{s} \ 20 \mathbf{s} \ 21$
	1966
	Raise a mound of stone W. of the cor.
82.12	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E S 17 S 16 S 20 S 21
	1966
	Raise a mound of stone W. of the cor.
	Land, gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°48' W., bet. secs. 16 and 21.
	Over rolling land, through scattered cedar timber.
6.50	Edge of mesa, bears irreg. N. and S.; desc. W. slope.
10.50	Draw, drains N.; asc. E. slope.
16.20	Spur, projects NW.
34.70	Spur, projects N. 80 1ks. to end.
39.43	Point for the 4 sec. cor. of secs. 16 and 21, at pro-
39.43	portionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{16}{21}$
	1966
	Raise a mound of stone N. of the cor.
	· ·

· ·	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
CHAINS	
41.10	Fence, barbed wire, bears N. 54°20' E. and S. 54°20' W.
62.50	Leave cedar timber.
71.40	Fence, barbed wire, bears S. 2°20' E. and N. 2°20' W.
78.86	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling E. ½ mile, then gently rolling. Soil, clay loam. Timber, scattered cedar. Undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 1°02' W., bet. secs. 16 and 17.
	Over gently rolling land.
41.05	Point for the ½ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	S 17 S 16
	1966
	from which
	A reservoir, bears N. 2°13' W., 27.68 chs. dist.
	Raise a mound of stone W. of the cor.
82.10	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E <u>S 8 S 9</u> S 17 S 16
	1966
	from which
	A windmill, bears N. 63°25' W., 21.54 chs. dist.
	Raise a mound of stone W. of the cor.
	Land, gently rolling to nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°56' W., bet. secs. 9 and 16.
	Over nearly level land.
36.50	Fence, barbed wire, bears S. 81°48' E. and N. 81°48' W.
39.46	Point for the ½ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.

	42.
CHAINS	ep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
CHAINS	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E
	$\frac{1}{4} \frac{\text{S} 9}{\text{S} 16}$
	from which
	A fence, bearing E. and W., bears North, 13 1ks. dist.
	Raise a mound of stone N. of the cor.
74.10	Wash, 10 lks. wide, 3 ft. deep, drains irregularly N.
75.00	Fence, barbed wire, bears S. 4°02' E. and N. 4°02' W.
78.92	The cor. of secs. 8, 9, 16 and 17.
	Land, nearly level.
	Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 0°54' W., bet. secs. 8 and 9.
	Over nearly level land.
5.30	Fence, barbed wire, bears N. 81°43' W. and S. 81°43' E.
5.80	Fence, barbed wire, bears N. 81°43' W. and S. 81°43' E.
6.50	Fence, barbed wire, bears N. 81°43' W. and S. 81°43' E.
16.10	Wash, 30 1ks. wide, 5 ft. deep, drains N. 15° E.
41.04	Point for the ½ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T15N R21E
	s 8 s 9
	1966
41.20	Wash, 30 lks. wide, 5 ft. deep, drains E.
82.08	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	<u>s 5 s 4</u> s 8 s 9
	1966
	Raise a mound of stone W. of the cor.
	Land, nearly level.
ļ	Soil, clay loam.

Dep. Resurvey	Subdivisional	Lines, T.15	N.,R.	21 E.,	Arizona
---------------	---------------	-------------	-------	--------	---------

	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizon	a
CHAINS	From the cor. of secs. 3, 4, 9 and 10.	
	N. 89°58' W., bet. secs. 4 and 9.	
	Over nearly level land.	
39.43	Point for the ½ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.	
	T15N R21E	
	$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{4}{9}$	
	1966	
78.86	The cor. of secs. 4, 5, 8 and 9.	
	Land, nearly level. Soil, clay loam.	
	No timber; undergrowth, sagebrush, bunch grass and rabbit brush.	
	N. 0°39' W., bet. secs. 4 and 5.	
	Over nearly level land.	
26.60	Old bladed road, bears N. 49°26' E. and S. 49°26' W.	
41.04	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 20 ins. in the ground, brass cap mkd.	
	T15N R21E	
:	s 5 s 4	
	1966	
	Raise a mound of stone W. of the cor.	
81.88	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.	
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.	
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.	
	N. 1°29' W., bet. secs. 31 and 32.	
	Over nearly level land.	
4.40	Apache Railroad, on curve, bears N. 15°14' E. and S. 15°14' W.	
25.00	Fence, barbed wire, bears N. 70°12' W. and S. 70°12' E.	

Dep. Resu	irvey, Subdi	visional L	ines. T.	15 N.	.R. 2	.L E.,	Arizona
-----------	--------------	------------	----------	-------	-------	--------	---------

	Dep. Resurvey, Subdivisional Lines, 1.13 N., R. 21 E., Alizon					
41.13	Point for the ½ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of					
	the orig. cor.					
	Set the iron post 24 ins. in the ground, brass cap mkd.					
	T15N R21E					
	s 31 s 32					
	1966					
	Raise a mound of stone W. of the cor.					
82.26	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.					
	Set the iron post 24 ins. in the ground, brass cap mkd.					
	T15N R21E					
	<u>S 30 S 29</u> S 31 S 32					
	1966					
	Raise a mound of stone W. of the cor.					
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.					
,						
	From the cor. of secs. 28, 29, 32 and 33.					
	S. 89°33' W., bet. secs. 29 and 32.					
7.40	Over nearly level land.					
7.40	Wash, 10 1ks. wide, 1 ft. deep, drains N. 60° E.					
35.30	Fence, barbed wire, bears S. 10°18' E. and N. 10°18' W.					
39.30	Old bladed road, bears S. 10°19' E. and N. 10°19' W.					
39.46	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.					
	Set the iron post 24 ins. in the ground, brass cap mkd.					
	T15N R21E 1/4 S 29 1/4 S 32					
	1966					
	Raise a mound of stone N. of the cor.					
54.20	Apache Railroad, bears N. 4°25' E and S. 4°25' W.					
78.92	The cor. of secs. 29, 30, 31 and 32.					
	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush, bunch grass and rabbit brush.					

		45.
	CHAINS	Dep. Resurvey, Subdivisional Lines, T. 15 N., R. 21 E., Arizona
·	CHAINS	S. 89°55' W., bet. secs. 30 and 31.
		Over nearly level land.
	39.55	Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.
•		Set the iron post 20 ins. in the ground, brass cap mkd.
•		T15N R21E 1/4 S 30 S 31
		1966
		Raise a mound of stone N. of the cor.
	48.70	Fence, barbed wire, bears S. 18°52' E. and N. 18°52' W.
	74.88	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
		From the cor. of secs. 29, 30, 31 and 32.
		N. 1°16' W., bet. secs. 29 and 30.
		Over nearly level land.
	41.13	Point for the ½ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T15N R21E
		s 30 s 29
		1966
		Raise a mound of stone W. of the cor.
	82.26	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T15N R21E S 19 S 20 S 30 S 29
		1966
		Raise a mound of stone W. of the cor.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	i !	· · · · · · · · · · · · · · · · · · ·

	46.
 -	Dep. Resurvey, Subdivisional Lines, T.15 N.,R.21 E., Arizona
CHAINS	From the cor. of secs. 20, 21, 28 and 29.
	S. 89°42' W., bet. secs. 20 and 29.
	Over nearly level land.
39.80	Point for the ½ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T15N R21E
	½ <u>\$ 20</u> <u>\$ 29</u>
	1966
	Raise a mound of stone N. of the cor.
42.80	Fence, barbed wire, bears S. 1°12' E. and N. 1°12' W.
43.40	Old bladed road, bears S. 1°12' E. and N. 1°12' W.
56.40	Apache Railroad, bears S. 10°05' E. and N. 10°05' W.
79.60	The cor. of secs. 19, 20, 29 and 30.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 89°33' W., bet. secs. 19 and 30.
	Over nearly level land.
39.60	Point for the ½ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E 1/4 S 19 S 30
	1966
	Raise a mound of stone N. of the cor.
67.60	Fence, barbed wire, bears S. 9°53' E. and N. 9°53' W.
72.87	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	Land, nearly level to gently rolling. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	,

	47.
CHAINS	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
Circuit	From the cor. of secs. 19, 20, 29 and 30.
	N. 1°32' W., bet. secs. 19 and 20.
	Over nearly level land.
31.30	Fence, barbed wire, bears N. 80°45' E. and S. 80°45' W.
41.13	Point for the ½ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E
	S 19 S 20
	1966
	Raise a mound of stone W. of the cor.
65.40	Apache Railroad, bears N. 77°53' W. and S. 77°53' E. for approx. 3.60 chs., then curves S.
82.26	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E S 18 S 17 S 19 S 20
	1966
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°48' W., bet. secs. 17 and 20.
	Over nearly level land.
9.10	Fence, barbed wire, bears S. 2°40' E. and N. 2°40' W.
26.00	Fence, barbed wire, bears S. 2°16' E. and N. 2°16' W.
39.75	Point for the ½ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E 2 S 17 S 20
41.50	1966 Fence, barbed wire, bears S. 0°40' E. and N. 0°40' W.

CHAINS	Dep. Resurvey, Subdivisional Lines, T.15 N.,R.21 E., Arizon
43.60	Old bladed road, bears S. $0^{\circ}40'$ E. and N. $0^{\circ}40'$ W.
79.50	The cor. of secs. 17, 18, 19 and 20.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	N. 88°59' W., bet. secs. 18 and 19.
	Over nearly level land.
36.40	Track road, bears S. 28°30' E. and N. 18°30' W.
37.20	Apache Railroad, bears S. 28°30' E. and N. 18°30' W.
39.70	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T15N R21E 3 S 18 4 S 19
	1966
	Set a cedar post, 5 ins. diam., 4 ft. long, alongside and raise a mound of stone N. of the cor.
70.45	Fence, barbed wire, bears N. 0°25' E. and S. 0°25' W.
70.50	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°44' W., bet. secs. 17 and 18.
	Over nearly level land.
41.12	Point for the ½ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	T15N R21E
	s 18 s 17
	1966
82.24	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence

		49.
	T	Dep. Resurvey, Subdivisional Lines, T.15 N., R.21 E., Arizon
	CHAINS	Set the iron post 20 ins. in the ground, brass cap mkd.
		T15N R21E S 7 S 8
		S 18 S 17
		1966
	,	Raise a mound of stone W. of the cor.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 8, 9, 16 and 17.
		S. 89°56' W., bet. secs. 8 and 17.
		Over nearly level land.
	11.50	Fence, barbed wire, bears S. 2°43' E. and N. 2°43' W.
	12.60	Wash, 10 1ks. wide, 4 ft. deep, drains NE., heads approx. 3.30 chs. S.
	23.00	Enter scattered cedar timber.
	27.10	Fence, barbed wire, bears S. 1°42' E. and N. 1°42' W.
Ì	38.00	Leave cedar timber.
	39.54	Point for the ½ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
		½ <u>S</u> 8
		1966
		from which
		A windmill, bears N. 64°28' E., 22.47 chs. dist.
		An abandoned house, bears N. 69°57' E., 16.70 chs. dist.
		A stock pond, bears N. 35°18' E., 5.70 chs. dist.
	42.80	Fence, barbed wire, bears S. 0°42' E. and N. 0°42' W.
	44.40	Old bladed road, bears S. 1°20' E. and N. 1°20' W.
	77.10	Fence, barbed wire, bears S. 81°07' E. and N. 81°07' W.
	79.08	The cor. of secs. 7, 8, 17 and 18.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
ı	ł	

De	p. Resurvey, Subdivisional Lines, T.15 N.,R. 21 E., Arizona
CHAINS	v 00°251 II hat good 7 and 18
	N. 89°25' W., bet. secs. 7 and 18.
	Over nearly level land.
7.00	Apache Railroad, bears N. 24°27' E. and S. 24°27' W.
39.61	Point for the 1/2 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15N R21E 1/4 S 7 S 18
	1966
	from which
	A reservoir, bears N. 57°38' E., 16.08 chs. dist.
	Raise a mound of stone N. of the cor.
42.40	Track road, bears NE. and SW.
67.90	Wash, 30 1ks. wide, 4 ft. deep, drains irregularly N.
68.82	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp.
	Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°58' W., bet. secs. 7 and 8.
	Over nearly level land.
.30	Fence, barbed wire, bears S. 81°07' E. and N. 81°07' W.
11.70	Track road, bears irregularly E. and W.
14.80	Apache Railroad, bears N. 24°28' E. and S. 24°28' W.
41.12	Point for the ½ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T15 N R21E
	s 7 s 8
	1966
	Raise a mound of stone W. of the cor.
82.24	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.

D	ep. Resurvey,	Subdivisional	Lines,	T.15	N.,R.	21 E.,	Arizona

		Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizona
	CHAINS	Set the iron post 8 ins. in the ground, mound with
		stone to top, brass cap mkd. T15N R21E
		S 6 S 5 S 7 S 8
		1966
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 4, 5, 8 and 9.
		N. 89°57' W., bet. secs. 5 and 8.
		Over nearly level land.
	36.60	Old bladed road, bears N. 55° E. and S. 55° W.
	39.59	Point for the ½ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T15N R21E
		$\frac{1}{4} \frac{s}{s} \frac{5}{8}$
		1966
		Raise a mound of stone N. of the cor.
	42.50	Fence, barbed wire, bears S. 0°44' E. and N. 0°44' W.
	44.70	Track road, bears N. and S.
	46.30	Apache Railroad, bears N. 29°32' E. and S. 29°32' W.
	79.18	The cor. of secs. 5, 6, 7 and 8.
		Land, nearly level. Soil, clay loam.
		No timber; undergrowth, sagebrush and bunch grass.
		N. 89°56' W., bet. secs. 6 and 7.
		Over nearly level land.
	31.30	Wash, 30 1ks. wide, 4 ft. deep, drains N. from a dyke approx. 1.50 chs. S.
	39.62	Point for the ½ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post, 8 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
		$\frac{1}{4} \frac{S}{S} \frac{6}{7}$
		1966
1	i	i e

Den	Regurvey	Subdivisional	Lines.	T.15	N.,R.	21 E.,	Arizona
neu.	VEDUTACA.	Dabatatorona	,		,		

	I	Dep. Resurvey, Subdivisional Lines, T.15 N., R. 21 E., Arizon
T	CHAINS	
	66.78	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
		Land, nearly level. Soil, clay loam. No timber; undergrowth, sagebrush, bunch grass and rabbit brush.
		From the cor. of secs. 5, 6, 7 and 8.
	-	N. 0°33' W., bet. secs. 5 and 6.
		Over nearly level land.
	41.12	Point for the 4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
		T15N R21E
		s 6 s 5
		1966
		from which
		A stock pond, bears S. 67°37' E., 8.80 chs. dist.
	81.83	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
		Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		General Description
		The land in Township 15 North, Range 21 East, is nearly level except for a few bluffs and low rolling ridges. The soil is clay loam with areas of exposed sandstone. Drainage is to the east and north with Silver Creek Canyon cutting through the southeast corner of sec. 36.
		Moderate to scattered cedars are found in the south central and southeast portion of the township, with scattered patches of cedars in the central area.
		Grazing of livestock is the predominant interest, as there is a good growth of native grass over most of the township, with windmills and stock ponds affording a continual water supply.

Arizona State Highway No. 77 enters the township near the corners of secs. 3 and 4 on the north boundary, cuts southeasterly, leaving the township in the southwest quarter of sec. 35. The Apache Railroad enters the township on the north boundary of sec. 5, meandering south, leaving near the corner of secs. 31 and 32. Track roads, branching off from State Highway No. 77, give access to most of the township.

Form 4-680 (June 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John H. Witmer	Supervisory Surveying Technician
Arvel R. Jones	Surveying Aid
Jerrold E. Knight	Surveying Aid
Miguel Luna	Surveying Aid
Ronald G. Williams	Surveying Aid
	7,6 1114
	1 2 2 2 2 3

INTERIOR--PORTLAND, OREGON

CERTIFICATE OF SURVEY

A, We, Boyd S. Owens and Kenneth D. Herman , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of August , 1966, we have made a dependent resurvey of the boundaries and subdivisional lines of Township 15 North, Range 21 East,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by to and under to direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 18, 1968 (Date) Boyd & Owens
(Cadastral Surveyor)

March 18, 1968 (Date) Kenneth O Kerman (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 1 3 1968

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the dependent resurvey of the boundaries and subdivisional lines of Township 15 North, Range 21 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens and Kenneth D. Herman,

having been critically examined and found correct, are hereby approved.

APR 1 8 1969 (Date)

Chief, Division of Cadastral Survey

CERTIFICATE	OF TRANSCRIP	1
-------------	--------------	---

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

, is a true copy of the original field notes.

(Chief, Division of Engineering)