_, 19 ___67

January 25

Survey completed _

Form 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY
of the
EAST, WEST and NORTH BOUNDARIES
and a
Portion of the SOUTH BOUNDARY
and
SUBDIVISIONAL LINES
and
SURVEY
of the
SUBDIVISION
of
Sections 4, 12, 22, 26 and 34
TOWNSHIP 19 NORTH, RANGE 19 EAST
Of theMeridian,
In the State ofArizona
EXECUTED BY
Boyd S. Owens, Cadastral Surveyor
Gary T. Oviatt, Cadastral Surveyor
Under special instructions dated October 21 , 19 66 , which provided for the surveys
included under Group Number 449 , approved October 21, 1966
and assignment instructions dated, 19
Survey commenced November 22 19 66

9



	To	ownsh	ip		19	North	1		, Ra	ange	19	Eas	t		 ,	
	15			15			14			13			13		12	
10	6	50		5	41		4	34		8	27		2	21	1	4
	49			49		4	0			33			27		21	
9	7	48		8	39		9	33		10	26		11	20	19	3
	48			47			39			32			26	 -	 19	
8	18	47		17	38		16	32		15	25		14	19	13	3
ļ	46			46			38			31			25		 19	
8	19	45		20	37		21	30		99	24		28	18	24	2
	44			44			37			29	L -	··-	24		 18	
7	30	43		29	36		28	29		27	24	1	26	17	25	2
	43			42			35			2 8			23		 17	
6	31	41		32	35		33	28-		84 5	22		85	16	36	1

<u>Subdivision</u>:

Sec. 12 - page 51 Sec. 26 - page 53 Sec. 34 - page 54 Sec. 22 - page 57 Sec. 4 - page 59

Gen. Descrip.-page 61

Township 19 North, Range 19 East Gila and Salt River Meridian, Arizona

	Township 19 North, Range 19 East Gila and Salt River Meridian, Arizona
CHAINS	The south boundary was surveyed in 1879 by J. L. Harris, retraced in 1882 by H. Meyrick and resurveyed in 1920-1921 by S. E. Blout. The east, west and north boundaries and the subdivisional lines were surveyed in 1882 by H. Meyrick. The north one mile of the west boundary and the west one mile of the north boundary were retraced in 1944 by Forrest and Warner.
	The following notes are those of a dependent resurvey of the east, west and north boundaries, a portion of the south boundary and subdivisional lines designed to restore the corners in their true original location according to the best available evidence, and survey of subdivisions of sections 4, 12, 22, 26 and 34 of Township 19 North, Range 19 East, Gila and Salt River Meridian, Arizona.
	This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated October 21, 1966.
	Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base, and with a brass cap riveted to the top. Original corner monuments, unless described otherwise, were deposited alongside the new monuments.
-	The geographic position of the southeast corner of the township as determined by traverse to first order U.S.G.S. triangulation station "ASYLUM", located in Section 16, Township 20 North, Range 20 East, is: Latitude 34°59'46" North and Longitude 110°16'14" West.
	The mean magnetic declination was found to be 14° East.
	Dependent Resurvey of the East Boundary Township 19 North, Range 19 East
·	Reestablishment of the Survey Executed by H. Meyrick in 1882
	From the cor. of Tps. 18 and 19 N., Rs. 19 and 20 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1920-1921 resurvey by S. E. Blout, in T. 18 N., R. 19 E.
	Topography was adjusted from random lines.
	N. 0°14' W., bet. secs. 31 and 36.
	Over nearly level land.
4.40	Fence, barbed wire, bears E. and W.
 33.80	Fence, barbed wire, bears N. 0°36' E. and S. 0°36' W.
40.02	Point for the ½ sec. cor. of secs. 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
58.60	Wash, 260 lks. wide, 5 ft. deep, drains S. 60° W.

	Dep. Resurvey, East Boundary, T. 19 N., R. 19 E., Arizona
CHAINS	
79.80	Fence, barbed wire, bears N. 89° E. and S. 89° W.
80.05	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. This corner was not monumented.
	Land, nearly level. Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	N. 0°14' W., bet. secs. 25 and 30. Over nearly level land.
40.02	Point for the ½ sec. cor. of secs. 25 and 30, at pro-
	portionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
41.20	Wash, 10 1ks. wide, 1 ft. deep, drains S. 50° E.
60.00	Leave nearly level land; enter rolling land, through scattered timber.
80.05	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	Land, nearly level first ½ mile, rolling last ½. Soil, clay loam. Timber, scattered cedar last ½ mile.
	Undergrowth, sagebrush and bunch grass.
	N. 0°14' W., bet. secs. 19 and 24.
	Over rolling land, through scattered timber.
3.40	Fence, barbed wire, bears S. 69°03' E. and N. 69°03' W.; ridge, bears S. 70° E. and N. 70° W.
21.35	Fence, barbed wire, bears N. 15° E. and S. 15° W.
35.24	Fence, barbed wire, bears S. 25° E. and N. 25° W.
40.02	Point for the ½ sec. cor. of secs. 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
44.90	Fence, barbed wire, bears N. 13° E. and S. 13° W.
61.65	Fence, barbed wire, bears N. 44°30' E. and S. 44°30' W.; enter nearly level land; leave scattered timber.
80.05	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	Land, rolling first { mile, nearly level last { . Soil, clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunch grass.
ł	

-	1	Dep. Resurvey, East Boundary, T. 19 N., R. 19 E., Arizona
	CHAINS	Per meter toy, Zase Beandary, 1. 15 N., R. 15 H., All Zona
•		N. 0°14' W., bet. secs. 13 and 18.
		Asc. gentle N. slope.
	39.65	SW. rim of Marcon Mesa, bears E. and W.
-	40.02	Point for the ½ sec. cor. of secs. 13 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	78.30	Dyke, bears E. and W.; bladed road bears N. 60° E. and S. 60° W.
	80.05	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E R20E <u>S12 S 7</u> S13 S18
		1966
		Set a wooden post alongside the iron post.
		Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		N. 0°14' W., bet. secs. 7 and 12.
		Over nearly level land.
	20.01	Point for the S 1/16 sec. cor. of secs. 7 and 12, at proportionate dist.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E R20E S 1/16 S 12 S 7
		1966
	40.02	Point for the ½ sec. cor. of secs. 7 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E R20E
		S 12 S 7
		1966
:	47.80	North rim of Marcon Mesa, bears N. 60° E. and S. 60° W.; desc. broken and rolling land.
	70.90	Low ridge, bears E. and W.; desc. gentle N. slope.
	80.05	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; unable to find any remaining evidence of the original

of the orig. cor.

 CHAINS	Dep. Resurvey, East Boundary, T. 19 N., R. 19 E., Arizona	-
	Set the iron post, 24 ins. in the ground, brass cap mkd.	
	T19N	
	R19E R20E S 1 S 6	
	S 12 S 7	
	1966	
	Raise a mound of stone W. of the cor.	
	Set a wooden post alongside the iron post.	
	Land, nearly level first 2/3 mile, rolling last 1/3 mile. Soil, clay loam. Timber, none.	
	Undergrowth, sagebrush and bunch grass.	
	N. 0°14' W., bet. secs. 1 and 6.	
	Over broken and rolling badlands.	
18.50	Long camel-backed spur, slopes N. 50° W.	
31.65	Wash, 25 1ks. wide, 1 ft. deep, drains irreg. N. 30° W.	
34.75	Rocky spur, slopes W.	
39.60	Rocky spur, slopes NW.	
40.03	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	T19N R19E_R20E	
	s 1 s 6	
	1966	
	Raise a mound of stone W. of the cor.	
74.25	Fence, barbed wire, bears S. 89° E. and N. 89° W.	
80.05	Point for the cor. of Tps. 19 and 20 N., Rs. 19 and 20 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T2ON R19E R2OE S 36 S 31 S 1 S 6	
	T19N 1966	
	from which	
	The cor. of Tps. 19 and 20 N., Rs. 20 and 21 E., bears S. 89°39' E., 485.36 chs. dist., monumented by a sandstone, 24 x 12 x 8 ins., dimly mkd. and set in a small mound of stone.	,
	At the corner point	
I	1	

Dep. Resurvey, Portion, S. Bdy., T. 19 N., R. 19 E., Arizona

CHAINS

Set the iron post 20 ins. in the ground, brass cap mkd.

T20N R20E R21E S 36 S 31 S 1 S 6 T19N 1966

Bury the orig. stone alongside the iron post.

The proportionate point for the closing cor. of T. 20 N., Rs. 19 and 20 E., on the Fifth Standard Parallel North, bears N. $0^{\circ}52$ ' E., 480.36 chs. dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap $\ensuremath{\mathsf{mkd}}\xspace.$

T21N R19E
S 36
S 1 S 6
R19E R20E
T20N
CC
1966

Raise a mound of stone S. of the cor.

From this cor., The Standard Tp. Cor. of T. 21 N., Rs. 19 and 20 E., bears N. 89°37' E., 11.93 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1947 resurvey of the Fifth Standard Parallel North by Ty White.

These control lines were fully retraced and a careful search was made for evidence of intervening cors., none of which were found.

Land, rolling.
Soil, clay loam and rocky.
Timber, none.

Undergrowth, sagebrush and bunch grass, with scattered Brigham tea.

Dependent Resurvey of a Portion of the South Boundary Township 19 North, Range 19 East

Reestablishment of the Survey Executed by S. E. Blout in 1920-1921

From the cor. of secs. 34 and 35 only, monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official records of the 1920-1921 resurvey by S. E. Blout.

N. $89^{\circ}50'$ W., on the S. bdy. of sec. 34.

Over gently rolling land.

16.80

Track road, bears North and South.

	Dep. Resurvey, West Boundary, T. 19 N., R. 19 E., Arizona
CHAINS 20.09	Point for the E 1/16 sec. cor. of sec. 34, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E E 1 S 34 17 1967
,	Set a wooden post, 6 ins. diam., 5 ft. long, alongside the iron post.
34.51	Fence, barbed wire, bears N. and S.
35.40	Underground pipe line, bears S. 43° E. and N. 43° W.
37.56	The ½ sec. cor. of sec. 3 only, T. 18 N., R. 19 E., monumented by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1920-1921 resurvey by S. E. Blout.
40.18	The ½ sec. cor. of sec. 34 only, monumented by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record of the 1920-1921 resurvey by S. E. Blout.
	Land, gently rolling.
	Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	Dependent Resurvey of the West Boundary Township 19 North, Range 19 East
	Reestablishment of the Survey Executed by H. Meyrick in 1882
	From the cor. of Tps. 18 and 19 N., Rs. 18 and 19 E., monumented by an iron post, as described in the survey notes of the 1920-1921 resurvey by S. E. Blout in T. 18 N., R. 19 E., set in a cor. of fences bearing N., E. and S.
	N. 0°07' W., bet. secs. 31 and 36.
	Over nearly level land.
22.70	Small rise, bears S. 20° E. and N. 20° W.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T19N R18E R19E
	s 36 s 31
	1966
	from which
l	

A N-S fence bears West, 46 lks. dist.

Dep. Resurvey, West Boundary, T. 19 N., R. 19 E., Arizona

	Dep. Resurvey, West Boundary, T. 19 N., R. 19 E., Arizona
CHAINS	
	Set a post alongside the cor.
80.05	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R18E R19E S 25 S 30 S 36 S 31
	1966
	from which
	A N-S. fence bears West, 57 lks. dist.
	Raise a mound of stone W. of the cor.
	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°07' W., bet. secs. 25 and 30.
	Over nearly level land.
27.40	Leave nearly level land; enter rolling land.
39.80	Top of ridge, bears E. and W.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R18E R19E 大 S 25 S30
	1966
	from which
	A N-S. fence, bears West, 68 1ks. dist.
	Raise a mound of stone W. of the corner.
71.00	Wash, 30 1ks. wide, 1 ft. deep, drains SW.
80.05	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R18E R19E S 24 S 19
	\$\overline{\sigma} \overline{\sigma} \
	1300

.]	Dep. Resurvey, West Boundary, T. 19 N., R. 19 E., Arizona
CHAINS	from which
	A N-S. fence, bears West, 85 lks. dist.
	Land, nearly level first 1/3 mile, rolling last 2/3. Soil, clay loam. Timber, none. Undergrowth, scattered sage, rabbit brush and bunch grass.
	N. 0°07' W., bet. secs. 19 and 24.
	Over rolling land.
30.70	Spur, slopes S. 60° W.
38.90	Leave rolling land; enter nearly level land.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R18E R19E
	s 24 s 19
	1966
	from which
	A N-S. fence, bears West, 98 lks. dist.
80.05	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R18E R19E S 13 S 18 S 24 S 19
	from which
	A N-S. fence, bears West, 116 lks. dist.
	A stock pond, bears N. 64°11' E., 12.41 chs. dist.
	Set a wooden post alongside the iron post.
	Land, rolling first ½ mile, nearly level last half. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°07' W., bet. secs. 13 and 18.

Over nearly level land.

		Dep. Resurvey, West Boundary, T. 19 N., R. 19 E., Arizona
	CHAINS 40.02	Point for the ½ sec. cor. of secs. 13 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 24 ins. in the ground, brass cap mkd.
		T19N R18E R19E
		s 13 s 18
		1966
		from which
		A N-S. fence, bears West, 132 lks. dist.
		Set a wooden post alongside the iron post.
	78.90	Underground pipe line, bears S. 43° E. and N. 43° W.
	80.05	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T19N R18E R19E S 12 S 7 S 13 S 18
		1966
		from which
		A N-S fence, bears West, 152 lks. dist.
		Set a wooden post alongside the iron post.
		Land, nearly level.
		Soil, clay loam. Timber, none.
		Undergrowth, sagebrush and bunch grass.
		N. 0°07' W., bet. secs. 7 and 12.
		Over nearly level land.
	26.30	Wash, 370 lks. wide, 2 ft. deep, drains W. into Cottonwood Wash.
	40.02	Point for the ½ sec. cor. of secs. 7 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N
		R18E R19E
		S 12 S 7
		1966
- 1		ı l

CHAINS	Dep. Resurvey, West Boundary, T. 19 N., R. 19 E., Arizona
CHAINS	from which
	A N-S. fence, bears West, 96 lks. dist.
	Set a wooden post alongside the iron post.
42.10	Fence, barbed wire, bears NE. and SW.
46.20	Cottonwood Wash, 480 lks. wide, 1 ft. deep, drains SW.
50.20	Fence, barbed wire, bears E. and W.
80.05	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T19N R18E R19E S 1 S 6 S12 S 7
	1966
	from which
	A N-S. fence, bears West, 181 1ks. dist.
	Set a wooden post alongside the iron post.
	Land, nearly level. Soil, clay loam, sandy in wash area. Timber, none. Undergrowth, sage, rabbit brush, bunch grass and salt cedar along wash.
	N. 0°07' W., bet. secs. 1 and 6.
	Over nearly level land.
40 .0 3	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R18E R19E
	s 1 s 6
	1966
	Set a wooden post alongside the iron post.
	A N-S fence, bears West, 1.93 chs. dist.
80.05	Point for the cor. of Tps. 19 and 20 N., Rs. 18 and 19 E., at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Dep. Resurvey, West Boundary, T.19 N., R. 19 E., Arizona

CHAINS

Set the iron post 22 ins. in the ground, brass cap mkd.

T20N R18E R19E S 36 S 31 S 1 S 6 T19N

1966

Set a wooden post alongside and deposit a lava stone S. of the iron post.

from which

A N-S fence, bears West, 2.06 chs. dist.

The cor. of Tps. 19 and 20 N., Rs. 17 and 18 E., bears S. $89^{\circ}44^{\circ}$ W., 483.14 chs. dist., monumented by a sandstone, $14 \times 8 \times 6$ ins., mkd. with 6 notches on one face and 2 notches on each of two other faces. No other marks legible.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T20N R17E R18E S 36 S 31 S 1 S 6 T19N

1966

Bury the orig. cor. stone alongside the iron post. Raise a mound of stone S. of the cor.

The proportionate point for the closing cor. of T. 20 N., Rs. 18 and 19 E., on the Fifth Standard Parallel North, bears N. 1°07' E., 480.30 chs. dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 22 ins. in the ground, brass cap mkd.

T21N R18E
S 36
S 1 S 6
R18E R19E
T20N
C C

1966

Raise a mound of stone S. of the cor.

From this cor., the Standard Corner of T. 21 N., Rs. 18 and 19 E., bears S. 89°58' E., 15.83 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1947 resurvey of the Fifth Standard Parallel North by Ty White.

These control lines were fully retraced and a careful search was made for evidence of intervening corners, none of which were found.

CHAINS	Dep. Resurvey, North Boundary, T. 19 N., R. 19 E., Arizona
CHAINS	Land, level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	Dependent Resurvey of the North Boundary Township 19 North, Range 19 East
	Reestablishment of the Survey Executed by H. Meyrick in 1882
	From the cor. of Ts. 19 and 20 N., Rs. 19 and 20 E.
	S. 89°47' W., bet. secs. 1 and 36.
	Over rolling land.
4.70	Clay ridge, bears N. and S.
18.20	Wash, 50 lks. wide, 2 ft. deep, drains N. 20° W.
26.10	Clay spur, slopes irreg. N.
38.30	Small wash, drains irreg. N.
39.93	Point for the ½ sec. cor. of secs. 1 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R19E 2 S 36 S 1 T19N
	1966
	Raise a mound of stone N. of the cor.
44.50	Wash, 60 lks. wide, 2 ft. deep, drains N. 30° W.
59.70	Clay camel-backed ridge, bears irreg. N. and S.
63.00	Enter flat land.
73.00	Wash, 30 lks. wide, 1 ft. deep, drains N. 60° W.
79.86	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T20N R19E S 35 S 36 S 2 S 1 T19N
	1966
	Raise a mound of stone W. of the cor.

•		Dep. Resurvey, North Boundary, T. 19 N., R. 19 E., Arizona
	CHAINS	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, scattered sagebrush and bunch grass.
		S. 89°47' W., bet. secs. 2 and 35.
		Over gently rolling land.
	34.30	Wash, 50 1ks. wide, 1 ft. deep, drains N. 30° W.
	39.93	Point for the ½ sec. cor. of secs. 2 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 18 ins. in the ground, brass cap mkd.
		T20N R19E ¹ / ₄ S 35 S 2 T19N
		1966
		Raise a mound of stone N. of the cor.
	56.40	Wash, 40 lks. wide, $3\frac{1}{2}$ ft. deep, drains N. 40° W.
	64.40	Wash, 20 1ks. wide, 1 ft. deep, drains N. 10° W.
	67.30	Enter rough land.
	71.10	Clay knoll.
	73 .2 0	Small clay ridge, bears N. and S.
	75.60	Enter flat land.
	79.86	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 18 ins. in the ground, brass cap mkd.
		T20N R19E S 34 S 35 S 3 S 2 T19N 1966
		Raise a mound of stone W. of the cor.
		Land, gently rolling to rough to nearly level. Soil, clay loam. Timber, none. Undergrowth, bunch grass first ¾ mile, none last ¼.
		S. 89°47' W., bet. secs. 3 and 34. Over nearly level land.
	39.93	Point for the ½ sec. cor. of secs. 3 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Dep.	Resurvey,	North	Boundary,	т.	19	Ν.,	R.	19	Ε.,	Arizona
------	-----------	-------	-----------	----	----	-----	----	----	-----	---------

	Dep. Resurvey, North Boundary, T. 19 N., R. 19 E., Arizona
CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.
,	T20N R19E 2 S 34 S 3
	T19N
	1966
	Set a wooden post alongside the iron post.
75.10	Fence, barbed wire, bears N. 1° E. and S. 1° W.
79.86	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T20N R19E
	<u>s 33 s 34</u> s 4 s 3
	T19N
	1966
	Set a wooden post alongside the iron post.
	Land, nearly level.
	Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	S. 89°47' W., bet. secs. 4 and 33.
	Over nearly level land.
20.50	Wash, 70 1ks. wide, 2 ft. deep, drains N. 25° W.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T20N R19E
	$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{33}{4}$
	T19N
	1966
	Raise a mound of stone N. of the cor.
79.86	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T2ON R19E
	S 32 S 33
	S 5 S 4 T19N
	1966

	Dep. Resurvey, North Boundary, T. 19 N., R. 19 E., Arizona	
CHAINS	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.	
	S. 89°47' W., bet. secs. 5 and 32.	
	Over nearly level land.	
39.93	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T20N R19E 1/4 S 32 1/4 S 5 T19N 1966	
	Raise a mound of stone N. of the cor.	
42.30	Wash, 3.00 lks. wide, 1 ft. deep, drains SW.	
69.10	Bladed road, bears N. 43° E. and S. 43° W.	
71.90	Old fence line, no wire, bears N. 1° E. and S. 1° W.	
79.86	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T20N R19E S 31 S 32 S 6 S 5 T19N 1966	
	Deposit glass and set a wooden post alongside the iron post.	
	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.	
	S. 89°47' W., bet. secs. 6 and 31.	
	Over nearly level land.	
27.20	Dirt road and underground pipe line, bears S. 19° E. and N. 19° W.	
31.30	Dirt road, bears S. 19° E. and N. 19° W.	
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Ariz	oná ·_
CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T20N R19E 1/4 S 31 S 6 T19N 1966	
	Raise a mound of stone N. of the cor. and set a wooden post alongside the iron post.	-
40.05	Fence, barbed wire, bears N. 16° E. and S. 16° W.	
46.90	Left bank, Cottonwood Wash, bears S. 35° E. and N. 35° W.	
48.30	Right bank, Cottonwood Wash, bears S. 35° E. and N. 35° W.	
83.20	The cor. of Tps. 19 and 20 N., Rs. 18 and 19 E.	
	Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.	
•	Dependent Resurvey of the Subdivisional Lines Township 19 North, Range 19 East	
•	Reestablishment of the Survey Executed by H. Meyrick in 1882	
	From the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official records of the 1920-1921 resurvey by S. E. Blout.	
	N. 0°07' W., bet. secs. 35 and 36.	
	Over nearly level land.	
40.03	Point for the ½ sec. cor. of secs. 35 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T19N R19E	
	s 35 s 36	
	1966	
	Set a cedar post, 4 ins. diam., 4½ ft. long, alongside the iron post.	
67.80	Leave flat; enter gently rolling land.	
72.90	Track road, bears irreg. E. and W.	
80.07	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	

Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona

	L	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Ariz
	CHAINS	Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E S 26 S 25 S 35 S 36 1966
	·	Set a cedar post, 4 ins. diam., 4½ ft. long, alongside the iron post.
		Land, nearly level to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
		From the point for the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
		S. 89°51' W., bet. secs. 25 and 36.
		Over gently rolling land.
	29.30	Wash, 60 lks. wide, 1 ft. deep, drains S.
	34.50	Fence, barbed wire, bears S. 89°40' E. and N. 89°40' W.
	40.32	Point for the ½ sec. cor. of secs. 25 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	80.64	The cor. of secs. 25, 26, 35 and 36.
		Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		N. 0°09' W., bet. secs. 25 and 26.
		Over rolling land.
	1.40	Fence, barbed wire, bears N. 87°05' E. and S. 87°05' W., on a ridge bearing E. and W.
•	28.70	Wash, 40 1ks. wide, 3 ft. deep, drains irreg. SW.
:	40.03	Point for the ½ sec. cor. of secs. 25 and 26, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
	:	T19N R19E
		s 26 s 25 1966
		Set a cedar post, 3 ins. diam., 4 ft. long, alongside and raise a mound of stone W. of the iron post.
	67.40	Wash, 10 lks. wide, 3 ft. deep, drains irreg. SW.

Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizo
CHAINS 80.07	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
	From the point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
	S. 89°50' W., bet. secs. 24 and 25.
	Over rolling land.
16.80	Wash, 90 lks. wide, 4 ft. deep, drains S.
40.24	Point for the ½ sec. cor. of secs. 24 and 25, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
80.47	Point for the cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°11' W., bet. secs. 23 and 24.
	Over rolling land.
5.10	Gully, 10 lks. wide, with 8 ft. banks, drains irreg. S. 20° W.
18.80	Gully, 10 lks. wide, with 12 ft. banks, drains S. 20° W.
28.50	Leave rolling land; enter gently rolling land.
40.03	Point for the ½ sec. cor. of secs. 23 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
47.50	Wash, 80 lks. wide, 8 ft. deep, drains SW.
80.07	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was monumented.
	Land, rolling to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
i	1 ·

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
CHAINS	From the point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	S. 89°47' W., bet. secs. 13 and 24.
	Over gently rolling land.
23.9	Wash, 35 1ks. wide, 6 ft. deep, drains S.
40.2	Point for the ½ sec. cor. of secs. 13 and 24, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
80.4	The point for the cor. of secs. 13, 14, 23 and 24.
	Land, gently rolling to rolling. Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	N. 0°21' W., bet. secs. 13 and 14.
	Over gently rolling land.
40.03	Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
56.5	Track road, bears irreg. NE. and SW.
80.0	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E S 11 S 12
	S 14 S 13 1966
	Set a cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.
	Land, gently rolling. Soil, sandy loam.
	Timber, none. Undergrowth, bunch grass.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
	S. 89°45' W., bet. secs. 12 and 13.
	Over gently rolling land.
2.30	Center of stock pond.
20.15	Point for the E 1/16 sec. cor. of secs. 12 and 13, at proportionate dist.
	Set the iron post 20 ins. in the ground, brass cap mkd.

Dep.	Resurvey,	Subdivisional	Lines	т.	19	Ν.,	R.	19	Ε.,	Arizona
------	-----------	---------------	-------	----	----	-----	----	----	-----	---------

CHAINS	T19N R19E
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	1967
	Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.
38.80	Leave gently rolling land; enter badlands, bears NE. and SW.
40.30	Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E 1/4 S 12 S 13 1967
	Raise a mound of stone N. of the cor.
59.20	Leave badlands; enter gently rolling land; bears SE. and NW.
80.59	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling and rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°02' W., bet. secs. 11 and 12.
	Over nearly level land.
12.40	Leave nearly level land; enter badlands, bears SE. and NW.
40.03	Point for the 4 sec. cor. of secs. 11 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 12 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E
	S 11 S 12 1966
80.06	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 16 ins. in the ground to bedrock, brass cap mkd.
	T19N R19E <u>S 2 S 1</u> S11 S12
	1966

-	Dep	. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
-	CHAINS	Set a cedar post, 5 ins. diam., 3 ft. long, alongside the iron post.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
		S. 89°43' W., bet. secs. 1 and 12.
		Over rolling badland.
	33.90	Wash, 30 lks. wide, 5 ft. deep, drains NE. approx. 2.00 chs.; thence N.
	36.20	Wash, 25 lks. wide, 4 ft. deep, drains NE.
•	40.15	Point for the ½ sec. cor. of secs. 1 and 12, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T19N R19E 表 <u>S 1</u>
		S 12 1967
		Raise a mound of stone N. of the cor.
	80.29	The cor. of secs. 1, 2, 11 and 12.
		Land, rolling badlands. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass, approx. 95% bare ground.
		N. 0°01' E., bet. secs. 1 and 2.
		Over rolling badlands.
	40.03	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 16 ins. in the ground, brass cap mkd.
		T19N R19E
		s 2 s 1 1966
		Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.
	75.55	Fence, barbed wire, bears S. 89° E. and N. 89° W.
	80.24	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.

Dej	p. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizo
CHAINS	Land, rolling badlands. Soil, clay loam.
	Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official records of the 1920-1921 resurvey by S. E. Blout, found at cor. of fences bearing N., E. and W.
	N. 0°03' W., bet. secs. 34 and 35.
	Over gently rolling land.
20.01	Point for the S 1/16 sec. cor. of secs. 34 and 35, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T19N R19E S <u>1</u>
	16 \$34\\$35
	1967
	from which
	A N-S. fence bears West, 6 1ks. dist.
	Set a cedar post, 6 ins. diam., 5 ft. long, alongside and raise a mound of stone W. of the iron post.
24.00	Wash, 10 1ks. wide, 2 ft. deep, drains SW.
40.02	Point for the ½ sec. cor. of secs. 34 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
53.10	Fence, barbed wire, bears NE. for 100 lks., thence N.; SW. for 40 lks., thence S.
60.02	Point for the N 1/16 sec. cor. of secs. 34 and 35, at proportionate dist.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T19N R19E N <u>1</u> 16
	\$34\\$35 1967
	from which
	A N-S fence, bears East, 59 lks. dist.
	Set a cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.
64.40	Enter clay hills, bears East and West.
74.00	Leave clay hills; enter gently rolling land.

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
CHAINS 78.60	Fence, barbed wire, bears W. and E., 79 lks. dist., to a cor. of fences bearing E., S. and W.
80.03	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E S 27 S 26 S 34 S 35 1967
	Set a cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.
	Land, gently rolling and rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89°46' W., bet. secs. 26 and 35.
	Over rolling land.
9.60	Wash, 65 lks. wide, 6 ft. deep, drains South.
40.32	Point for the ½ sec. cor. of secs. 26 and 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E S 26 S 35 1967
	from which
	An East-West fence bears North, 33 1ks. dist.
	Set a cedar post, 3 ins. diam., 5 ft. long, alongside the iron post.
46.50	Fence barbed wire, bears N. 21°30' E. and S. 21°30' W.
47.50	Wash, 25 lks. wide, 5 ft. deep, drains S.
60.48	Point for the W 1/16 sec. cor. of secs. 26 and 35, at proportionate dist.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E W 1/6 S 26 S 35 1967
	from which
	An East-West fence, bears South, 32 lks. dist.

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizon
CHAINS	Set a cedar post, 4 ins. diam., 5 ft. long, alongside and raise a mound of stone N. of the iron post.
69.60	Wash, 30 1ks. wide, 3 ft. deep, drains S.
80.64	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°12' W., bet. secs. 26 and 27.
	Over gently rolling land.
20.01	Point for the S 1/16 sec. cor. of secs. 26 and 27, at proportionate dist. This corner was not monumented.
40.02	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
80.04	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the point for the cor. of secs. 23, 24, 25 and 26.
	S. 89°46' W., bet. secs. 23 and 26.
	Over rolling land.
40.34	Point for the 4 sec. cor. of secs. 23 and 26, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
41.10	Wash, 40 1ks. wide, 5 ft. deep, drains irreg. SW.
72.30	Wash, 60 lks. wide, 3 ft. deep, drains SE. for 6.00 chs., thence SW.
80.67	The point for the cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°08' W., bet. secs. 22 and 23.
	Over gently rolling land.
6.10	Wash, 25 1ks. wide, 4 ft. deep, drains E. 4.30 chs., thence irreg. SE.

^	D	ep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
•	CHAINS 18.60	Wash, 15 lks. wide, 5 ft. deep, drains S. 70° E.
	20.00	Point for the S 1/16 sec. cor. of secs. 22 and 23, at proportionate dist. This corner was not monumented.
-	40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	80.03	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
		Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		From the point for the cor. of secs. 13, 14, 23 and 24.
		S. 89°47' W., bet. secs. 14 and 23.
		Over rolling land.
	13.90	Track road, bears S. 34° E. and N. 34° W.
	40.33	Point for the ½ sec. cor. of secs. 14 and 23, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	60.00	Wash, 40 lks. wide, 4 ft. deep, drains S.
	80.66	The point for the cor. of secs. 14, 15, 22 and 23.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		N. 0°21' W., bet. secs. 14 and 15.
		Over gently rolling land.
	22.40	Track road, bears East and West.
	40.02	Point for the ½ sec. cor. of secs. 14 and 15, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	77.40	Fence, barbed wire, bears N. 17° E. and S. 17° W.
	80.04	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E S 10 S 11 S 15 S 14 1967
		Set a cedar post, 6 ins. diam., 5 ft. long, alongside the iron post.

Dep.	Resurvey,	Subdivisional	Lines,	Т.	19	Ν.,	R.	19	Ε.,	Arizona
------	-----------	---------------	--------	----	----	-----	----	----	-----	---------

		The state of the s
	CHAINS	Land, gently rolling. Soil, clay loam.
		Timber, none. Undergrowth, sagebrush and bunch grass.
		ondergrowen, sugestion and banen grass.
		From the cor. of secs. 11, 12, 13 and 14.
		S. 89°45' W., bet. secs. 11 and 14.
		Over rolling land.
	40.34	Point for the ½ sec. cor. of secs. 11 and 14, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	79.30	Fence, barbed wire, bears N. 19° E. and S. 19° W.
	80.67	The cor. of secs. 10, 11, 14 and 15.
		Land, rolling. Soil, clay loam.
		Timber, none. Undergrowth, sagebrush and bunch grass.
		N. 0°03' W., bet. secs. 10 and 11.
		Over gently rolling land.
	1.20	Leave gently rolling land; enter rolling badlands, bears irreg. NE. and SW.
	40.02	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate dist.; falls on a steep slope where a permanent monument cannot be established; unable to find any remaining evidence of the orig. cor.
		from which
		The point selected for the witness 1/4 sec. cor. of secs. 10 and 11, bears N. 21°46' E., 74 lks. dist.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		WC T19N R19E
		\$10\s11 1967
		Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.
	80.03	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E S3 S2
		\$\frac{\sisting \frac{\sisting \sizeta}{\sizeta}}{\sizeta \frac{\sizeta}{\sizeta}{\sizeta}} \tag{5.11}
1		

Dep. Resurvey, Subdivisional Lines, T.19 N., R. 19 E., Arizo	Dep.	Resurvey,	Subdivisional	Lines,	T.19	Ν.,	R.	19	Ε.,	Arizon
--	------	-----------	---------------	--------	------	-----	----	----	-----	--------

	bep. Resurvey, Subdivisional Lines, 1.19 N., R. 19 E., Allzo
CHAINS	Set an iron pipe, 4 ins. diam., 5 ft. long, alongside the cor.
	Land, gently rolling to steep badlands. Soil, clay loam. Timber, none. Undergrowth, some sagebrush and bunch grass.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89°45' W., bet. secs. 2 and 11.
	Over rolling badlands.
40.34	Point for the ½ sec. cor. of secs. 2 and 11, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
80.68	The cor. of secs. 2, 3, 10 and 11.
	Land, steep badlands. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°37' E., bet. secs. 2 and 3.
	Over steep badlands.
14.20	Leave badlands; enter rolling land.
32.00	Wash, 20 1ks. wide, 4 ft. deep, drains NW.
40.02	Point for the ½ sec. cor. of secs. 2 and 3, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	S 3 S 2
	1967
	Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.
46.90	Leave rolling land; enter steep clay hills, bears East and West.
75.10	Fence, barbed wire, bears East and West.
80.22	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
	Land, rolling and steep clay hills. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
i	1

 · D	ep. Resurvey, Subdivisional Lines, T.19 N.,R. 19'E., Arizon
CHAINS	From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official
	records of the 1920-1921 resurvey by S. E. Blout.
	N. 0°14' W., bet. secs. 33 and 34.
25.30	Over gently rolling land.
39.98	Wash, 2.00 lks. wide, 5 ft. deep, drains S. 30° W.
39.90	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
·	Set the iron post 20 ins. in the ground, collar of stone to the top, brass cap mkd.
	T19N R19E
	s 33 s 34 1967
57.40	Underground pipeline, bears S. 33°00' E. and N. 33°00' W.
79.78	Fence, barbed wire, bears East and West.
79.96	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 16 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E S 28 S 27 S 33 S 34
•	1967
	Land, gently rolling. Soil, fine clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°58' W., bet. secs. 27 and 34.
	Over rolling land.
3.50	Gully, 10 lks. wide, 5 ft. deep, drains S.
40.37	Point for the ½ sec. cor. of secs. 27 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E 1/4 S 27 S 34
	1967
	·

Dep	p.]	Resur	vey,	Subd	livis	ional	Lines,	T.19	Ν.	,R.	19	Ε.,	Arizona
-----	------	-------	------	------	-------	-------	--------	------	----	-----	----	-----	---------

		Dep. Resurvey, Subdivisional Lines, T.19 N., R.19 E., Arizon
	CHAINS	Set a cedar post, 4 ins. diam., 5 ft. long, alongside and raise a mound of stone N. of the iron post.
	52.90	Wash, 40 lks. wide, 5 ft. deep, drains South.
	80.74	The cor. of secs. 27, 28, 33 and 34.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		N. 0°06' W., bet. secs. 27 and 28.
		Over rolling badlands.
	38.70	Track road, bears E. and W.
	39.98	Point for the ½ sec. cor. of secs. 27 and 28, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 22 ins. in the ground, brass cap mkd.
		T19N R19E
		s 28 s 27
		1967
		Set a squared cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.
	50.90	Track road, bears SE. and NW.
	51.80	Wash, 10 1ks. wide, 2 ft. deep, drains West.
	58.60	Track road, bears NE. and SW.
	79.96	Point for the cor. of secs. 21, 22, 27 and 28,at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 22 ins. in the ground, brass cap mkd.
		T19N R19E S 21 S 22 S 28 S 27
		1967
		Raise a mound of stone W. of the cor.
		Land, rolling to gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		From the point for the cor. of secs. 22, 23, 26 and 27.
		S. 89°56' W., bet. secs. 22 and 27.
		Over rolling land.
-		

 D	ep. Resurvey, Subdivisional Lines, T.19 N.,R. 19 E., Arizon
CHAINS 20.15	Point for the E 1/16 sec. cor. of secs. 22 and 27, at proportionate dist.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E
	$E \frac{1}{16} \frac{S}{S} \frac{22}{27}$
	1967
	Set a cedar post, 4 ins. diam., 6 ft. long, alongside the iron post.
40.10	Track road, bears N. 30° E. and S. 30° W.
40.31	Point for the ½ sec. cor. of secs. 22 and 27, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E
	$\frac{1}{4} \frac{S}{S} \frac{22}{27}$
	1966
	from which
	A stock pond, bears N. 50° E., 6.00 chs. dist.
	Set a cedar post alongside the iron post.
41.15	Fence, barbed wire, bears N. 30° E. and S. 30° W.
56.80	Leave rolling land; enter gently rolling land, bears N. and S.
80.61	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling to gently rolling. Soil, clay loam.
	Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°13' W., bet. secs. 21 and 22.
	Over gently rolling land.
3.30	Small gulley, 5 lks. wide, 4 ft. deep, drains N. 40° W.
21.10	Spur, projects West for 1.00 ch.
39.98	Point for the ½ sec. cor. of secs. 21 and 22, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	S 21 S 22
	1967
	Raise a mound of stone W. of the cor.
1	1

CHAINS	
61.00	Wash, 50 1ks. wide, 2 ft. deep, drains SW.; leave rolling land; enter badlands.
79.96	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 16 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E S 16 S 15 S 21 S 22
	1967
	Land, gently rolling to steep badlands. Soil, clay loam.
	Timber, none. Undergrowth, sagebrush and bunch grass.
	From the point for the cor. of secs. 14, 15, 22 and 23.
	S. 89°52' W., bet. secs. 15 and 22.
	Over rolling land.
15.10	Track road, bears N. and S.
20.18	Point for the E $1/16$ sec. cor. of secs. 15 and 22, at proportionate dist.
	Set the iron post, 20 ins. in the ground, brass cap mkd.
	T19N R19E
	$\frac{\text{E} \frac{1}{16} \frac{\text{S} 15}{\text{S} 22}}{1}$
	1967
	Set a cedar post, 5 ins. diam., 4 ft. long, alongside the iron post.
22.18	Fence, barbed wire, bears S. 5° E. and N. 5° W.
40.36	Point for the 4 sec. cor. of secs. 15 and 22, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
	T19N R19E
	$\frac{1}{4} \frac{S}{S} \frac{15}{22}$
	1967
	Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
56.00	Wash, 25 1ks. wide, 4 ft. deep, drains SW.
71.60	Leave rolling land; enter badlands, bears NE. and S.

D	ep. Resurvey, Subdivisional Lines, T.19 N., R. 19 E., Ariza
CHAINS	Land, rolling to steep badlands. Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	N. 0°08' W., bet. secs. 15 and 16.
	Over steep badlands.
39.98	Point for the ½ sec. cor. of secs. 15 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T19N R19E
	s 16 s 15
	1967
	Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.
58.50	Wash, 20 1ks. wide, 3 ft. deep, drains NW.
79.96	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 16 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E S 9 S 10 S16 S 15
	1967
	Land, steep badlands. Soil, clay loam. Timber, none.
	Undergrowth, scattered sagebrush and bunch grass, approximately 95% bare ground.
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89°46' W., bet. secs. 10 and 15.
	Over rolling land.
4.40	Leave rolling land; enter broken badlands, bears irreg. N. and S.
40.25	Point for the ½ sec. cor. of secs. 10 and 15, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 16 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E 2 S 10 S 15
	1967

	Dep. Resurvey, Subdivisional Lines, T.19 N.,R.19 E.,Arizona
CHAINS	
80.49	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling to broken badlands. Soil, clay. Timber, none. Undergrowth, scattered sagebrush and bunch grass, approximately 95% bare ground.
	N. 0°14' W., bet. secs. 9 and 10.
	Over badlands.
22.80	Wash, 6 lks. wide, 4 ft. deep, drains W.
39.98	Leave badlands; enter rolling land, bears E. and W.
39.98	Point for the ½ sec. cor. of secs. 9 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
	T19N R19E
	s 9 s 10
	1967
	Set a cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.
54.60	Wash, 40 1ks. wide, 4 ft. deep, drains NW.
66.80	Wash, 30 1ks. wide, 5 ft. deep, drains West.
79.96	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T19N R19E
	<u>S 4 S 3</u> S 9 S 10
	1967
	Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
	Land, badlands to rolling land. Soil, clay loam.
	Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89°47' W., bet. secs. 3 and 10.
	Over steep badlands.
10.50	Wash, 25 1ks. wide, 3 ft. deep, drains NW.

	Dep. Resurvey, Subdivisional Lines, T.19 N., R.19 E., Arizona
CHAINS	
26.25	Fence, barbed wire, bears N. and S.
40.34	Point for the 4 sec. cor. of secs. 3 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T19N R19E
	1 S 3 S 10
	1967
	Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.
69.90	Leave badlands; enter rolling land, bears N. and S.
80.68	The cor. of secs. 3, 4, 9 and 10.
	Land, badlands to rolling.
	Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	N. 1°10' E., bet. secs. 3 and 4.
	Over rolling land.
19.995	Point for the S 1/16 sec. cor. of secs. 3 and 4, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	\$ 1/16 \$ 4 \$ 3
	1967
	Raise a mound of stone W. of the cor.
30.30	Track road, bears E. and W.
39.99	Point for the ½ sec. cor. of secs. 3 and 4, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	s 4 s 3
	1967
	Set a cedar post, 5 ins. diam., 4 ft. long, alongside the iron post.
65.90	Wash, 70 1ks. wide, 7 ft. deep, drains irreg. NW.
80.26	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.

	De	ep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
-	CHAINS	From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1920-1921 resurvey by S. E. Blout.
		N. 0°08' W., bet. secs. 32 and 33.
		Over nearly level land.
	30.10	Fence, barbed wire, bears S. 1°59' E. and N. 1°59' W.
	39.98	Point for the ½ sec. cor. of secs. 32 and 33, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	·	Set the iron post 24 ins. in the ground, brass cap mkd.
		T19N R19E
		s 32 s 33 1966
		Set a cedar post, 6 ins. diam., 5 ft. long, alongside and raise a mound of stone W. of the iron post.
	60.80	Low sandy ridge, bears East and West.
	66.90	Wash, 40 1ks. wide, 1 ft. deep, drains irreg. W.
	77.60	Bladed road, bears S. 10° E. and N. 10° W.
	79.96	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; falls on edge of bladed road where a monument cannot be perpetuated; unable to find any remaining evidence of the orig. cor.
		from which
		A post, 8 ins. diam., bears N. 81°03' W., 33 lks. dist., with a metal tag mkd. Sta. 50, T 19 N R 19 E.
		Point for the witness cor. of secs. 28, 29, 32 and 33, bears N. 89°47' E., 10 lks. dist.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E \$ 29 S 28 WC \$ 32 S 33 1966
		Set a squared cedar post, 4 ins. diam., 5 ft. long, alongside and raise a mound of stone W. of the iron post.
		Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, scattered sagebrush and bunch grass.
		From the cor. of secs. 27, 28, 33 and 34.
		S. 89°47' W., bet. secs. 28 and 33.
		Over rolling land.
	14.70	Underground pipe line, bears S. 33° E. and N. 33° W.
	33.80	Wash, 35 1ks. wide, 4 ft. deep, drains SW.
	1 i	

_	Dep	. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
	40.30	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E \$\frac{\s 28}{\s 33} 1967
		from which
		An East-West fence, bears South, 45 1ks. dist.
		Set a cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.
	42.10	Wash, 35 lks. wide, 4 ft. deep, drains SW.
	48.00	Underground pipe line, bears S. 19°04' W. and N. 19°04' E.
	78.55	Fence, barbed wire, bears S. 89°05' E. and N. 89°05' W.
	80.50	Witness cor. of secs. 28, 29, 32 and 33.
	80.60	The true point for the cor. of secs. 28, 29, 32 and 33.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		From the true point for the cor. of secs. 28, 29, 32 and 33.
		N. 0°12' W., bet. secs. 28 and 29.
		Over nearly level land.
	• 04	Fence, barbed wire, bears S. 89°05' E. and N. 89°05' W.
	39.98	Point for the 4 sec. cor. of secs. 28 and 29, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E
		s 29 s 28 1967
		Set a cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.
	47.60	Wash, 380 1ks. wide, 3 ft. deep, drains S. 40° W.
	79.96	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 20 ins. in the ground, brass cap mkd.
		T19N R19E S 20 S 21 S 29 S 28
		1967

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Ar
CHAINS	Raise a mound of stone W. of the cor.
	Land, nearly level.
	Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°51' W., bet. secs. 21 and 28.
	Over gently rolling land.
33.90	Wash, 30 1ks. wide, 4 ft. deep, drains SW.
40.37	Point for the 4 sec. cor. of secs. 21 and 28, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	$\frac{1}{4} \frac{S}{S} \frac{21}{28}$
	1967
	Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
40.80	Wash, 20 1ks. wide, 3 ft. deep, drains SW.
52.70	Wash, 15 1ks. wide, 4 ft. deep, drains irreg. SW.
75.50	Underground pipe line, bears S. 19° E. and N. 19° W.
79.00	Underground pipe line, bears S. 41°00' E. and N. 41°00' W.
80.75	The cor. of secs. 20, 21, 28 and 29.
	Land, gently rolling. Soil, clay loam.
	Timber, none. Undergrowth, sagebrush and bunch grass.
	N. 0°08' W., bet. secs. 20 and 21.
2.00	Underground pipe line, bears S. 41°00' E. and N. 41°00' W.
15.70	Underground pipe line, bears S. 19° E. and N. 19° W.
17.80	Wash, 20 1ks. wide, 2 ft. deep, drains S. 75° W.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	s 20 s 21 1967
	Raise a mound of stone W. of the cor.
	-

 I	pep. Resurvey, Subdivisional Lines T. 19 N., R. 19 E., Arizona
chains 74.90	Wash, 25 1ks. wide, 3 ft. deep, drains N. 60° W.
79.96	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 16 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E S 17 S 16 S 20 S 21 1967
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 89°54' W., bet. secs. 16 and 21.
	Over badlands.
40.33	Point for the ½ sec. cor. of secs. 16 and 21, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E. 2 S 16 S 21 1967
	Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.
80.66	The cor. of secs. 16, 17, 20 and 21.
	Land, badlands. Soil, clay loam. Timber, none. Undergrowth, scattered sagebrush and bunch grass, 98% bare ground.
	N. 0°07' W., bet. secs. 16 and 17.
	Over badlands.
31.40	Erosion dike, bears N. 40° E. and S. 40° W.
39.98	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
	T19N R19E
	s 17 s 16
	1967

,			

	Dep. Resurvey, Subdivisional Lines, T.19 N., R.19 E., Arizona
CHAINS	
	Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
42.20	Wash, 15 1ks. wide, 2 ft. deep, drains SE.
79.96	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E <u>S 8 S 9</u> S17 S16
	1967
·	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.
	Land, badlands.
	Soil, clay.
	Timber, none. Undergrowth, scattered sagebrush, 99% bare ground.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89°47' W., bet. secs. 9 and 16.
	Over steep badlands.
14.40	Wash, 30 1ks. wide, 4 ft. deep, drains N. 30° W.
40.33	Point for the 1/2 sec. cor. of secs. 9 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
	T19N R19E
	1 S 9 S 16
	1967
	Set a cedar post, 5 ins. diam., 4 ft. long, alongside the iron post.
40.80	Wash, 15 1ks. wide, 3 ft. deep, drains N. 20° W.
80.65	The cor. of secs. 8, 9, 16 and 17.
	Land, badlands.
	Soil, clay. Timber, none.
	Undergrowth, widely scattered sagebrush and bunch grass, 95% bare ground.
	N. 0°18' W., bet. secs. 8 and 9.
	Over steep badlands.
2.60	Leave badlands; enter gently rolling land, bears E. and W.

	Ďез	o. Resurvey, Subdivisional Lines, T.19N.,R.19 E., Arizona
\top	CHAINS	
	39.98	Point for the 2 sec. cor. of secs. 8 and 9, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 22 ins. in the ground, brass cap mkd.
		T19N R19E
		s 8 s 9
	of	1967
		Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.
	49.20	Wash, 60 lks. wide, 6 ft. deep, drains S. 70° W.
	79.96	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 22 ins. in the ground, brass cap mkd.
		T19N R19E S 5 S 4 S 8 S 9
		1967
		Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.
		Land, badlands to gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		From the cor. of secs. 3, 4, 9 and 10.
		S. 89°49' W., bet. secs. 4 and 9.
		Over rolling land.
	20.17	Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.
		Set the iron post, 22 ins. in the ground, brass cap mkd.
		T19N R19E
		$\frac{E_{16}}{16} \frac{S}{S} \frac{4}{9}$
		1967
		Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
	40.34	Point for the ½ sec. cor. of secs. 4 and 9, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This corner was not monumented.
	47.40	Wash, 35 lks. wide, 5 ft. deep, drains SW.
	80.68	The cor. of secs. 4, 5, 8 and 9.

Dep.	Resurvey,	Subdivisional	Lines,	T.19	9 N., R. 19	E.,Arizona
------	-----------	---------------	--------	------	-------------	------------

CHAINS	Land, rolling. Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	N. 1°47' E., bet. secs. 4 and 5.
	Over gently rolling land.
3.30	Wash, 30 1ks. wide, 3 ft. deep, drains West.
18.40	Old track road, bears NE. and SW.
40.00	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	1967
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.
80.20	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official records of the 1920-1921 resurvey by S. E. Blout, found at cor. of fences bearing irreg. N., S. and E.
t	N. 0°13' W., bet. secs. 31 and 32.
	Over gently rolling land.
39.30	Wash, 40 lks. wide, 3 ft. deep, drains SW.
40.00	Point for the $\frac{1}{6}$ sec. cor. of secs. 31 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	s 31 s 32
	1967
	from which
1	

Γ	ep. Resurvey, Subdivisional Lines, T.19 N.,R.19 E., Arizona
CHAINS	Set a cedar post, 5 ins. diam., 6 ft. long, alongside the iron post.
43.20	Wash, 80 1ks. wide, 2 ft. deep, drains West.
69.40	Wash, 150 1ks. wide, 3 ft. deep, drains S. 60° W.
80.00	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E S 30 S 29 S 31 S 32 1967
-	from which
	A cor. of fences bearing irreg. East and South, bears N. 41°17' W., 1.34 chs. dist.
	Set a cedar post, 4 ins. diam., 6 ft. long, alongside the iron post.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage and rabbit brush.
	From the true point for the cor. of secs. 28, 29, 32 and 33. S. 89°40' W., bet. secs. 29 and 32.
	Over gently rolling land.
.09	Bladed road, bears S. 10° E. and N. 10° W.
.68	NE. cor. of corral, bears North, 5 lks. dist.
1.58	NW. cor. of corral, bears North, 6 lks. dist.
40.37	Point for the ½ sec. cor. of secs. 29 and 32, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
·	T19N R19E 1/4 S 29 1/5 S 32
	1967
	Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
42.60	Wash, 80 1ks. wide, 5 ft. deep, drains South.
72.90	Wash, 70 1ks. wide, 6 ft. deep, drains SW.
80.74	The cor. of secs. 29, 30, 31 and 32.

	Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona	
CHAINS	Land, gently rolling. Soil, clay loam. Timber, none.	
	Undergrowth, sagebrush and bunch grass.	
	S. 89°34' W., bet. secs. 30 and 31. Over gently rolling land.	
.90	Fence, barbed wire, bears N. and S.	
39 . 98	Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	T19N R19E	
•	$\frac{1}{4} \frac{S}{S} \frac{30}{31}$	
	4 S 31 1967	
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.	
54.90	Wash, 30 lks. wide, 4 ft. deep, drains S.	
80.36	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.	
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.	
	From the cor. of secs. 29, 30, 31 and 32.	
	N. 0°09' W., bet. secs. 29 and 30.	
1 00	Over gently rolling land.	
1.00	Fence, barbed wire, bears E. and W.	
40.00	Point for the 4 sec. cor. of secs. 29 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T19N R19E	
	s 30 s 29 1967	
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.	
57 . 70	Spur, slopes East.	
80.00	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	Set the iron post 15 ins. in the ground, mound of stone to the top, brass cap mkd.	

CHAINS	T19N R19E S 19 S 20 S 30 S 29 1967
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush.
٠	From the cor. of secs. 20, 21, 28 and 29.
	S. 89°41' W., bet. secs. 20 and 29.
	Over gently rolling land.
20.80	Bladed road, bears S. 18° E. and N. 18° W.
36.20	Wash, 60 1ks. wide, 5 ft. deep, drains SW.
38.20	Wash, 100 1ks. wide, 4 ft. deep, drains SW.
40.34	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E ¹ / ₄ S 20 S 29 1967
	from which
	The remains of concrete pillar at old Beacon site, bears N. 82°10' E., 13.77 chs. dist.
	Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.
71.60	Leave gently rolling land; enter rolling land, bears NE. and SW.
80.67	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling to rolling. Soil, clay loam. Timber, none.
	Undergrowth, sagebrush and bunch grass.
	S. 89°38' W., bet. secs. 19 and 30.
	Over rolling land.
29.20	Leave rolling land; enter gently rolling land, bears N. and S.
39.99	Point for the ½ sec. cor. of secs. 19 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

		Dep. Resurvey, Subdivisional Lines, T.19 N.,R.19 E., Arizon	a .
	CHAINS		
		T19N R19E	
		$\frac{1}{4} \frac{s}{s} \frac{19}{30}$	
		1967	
,	İ	1707	
		Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.	
	70.00	Wash, 90 lks. wide, 6 ft. deep, drains N. 40° W.	
	80.30	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp.	
		Land, rolling to gently rolling.	
		Soil, clay loam. Timber, none.	
		Undergrowth, sagebrush and bunch grass.	
]		
		From the cor. of secs. 19, 20, 29 and 30.	·
		N. 0°09' W., bet. secs. 19 and 20.	
		Over rolling land.	
	16.50	Ridge, bears E. and W.	
	40.00	Point for the ½ sec. cor. of secs. 19 and 20, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
		Set the iron post, 24 ins. in the ground, brass cap mkd.	
		T19N R19E	
		s 19 s 20	
		1967	
		Set a cedar post, 6 ins. diam., 5 ft. long, alongside the iron post.	
	41.00	Wash, 20 lks. wide, 3 ft. deep, drains S. 80° W.	
	66.90	Ridge, bears NE. and SW.	
	80.00	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T19N R19E	
		<u>S 18 S 17</u> S 19 S 20	
		·	
		1967	
		Set a cedar post, 4 ins. diam., 4 ft. long, alongside and raise a mound of stone W. of the iron post.	
		Land, rolling.	
		Soil, clay loam.	
		Timber, none.	
		Undergrowth, sagebrush.	
	•		

	D	ep. Resurvey, Subdivisional Lines, T.19 N., R.19 E., Arizona
	CHAINS	From the cor. of secs. 16, 17, 20 and 21.
		S. 89°43' W., bet. secs. 17 and 20.
		Over badlands.
	16.70	Leave badlands; enter rolling land, bears N. and S.
	22.00	Underground pipe line, bears S. 19° E. and N. 19° W.
	30.70	Bladed road, bears N. 10° E. and S. 10° W.
	40.33	Point for the ½ sec. cor. of secs. 17 and 20, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 20 ins. in the ground, brass cap mkd.
		T19N R19E 2 S 17 S 20 1967
		Raise a mound of stone N. of the cor.
	67.30	Underground pipe line, bears S. 41° E. and N. 41° W.
	80.66	The cor. of secs. 17, 18, 19 and 20.
		Land, steep badlands to rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		S. 89°42' W., bet. secs. 18 and 19.
		Over rolling land.
	39.99	Point for the ½ sec. cor. of secs. 18 and 19, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
		Set the iron post, 18 ins. in the ground, mound of stone to the top, brass cap mkd.
		T19N R19E 1/4 S 18 S 19
•		1967
		Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
	80.21	The cor. of secs. 13, 18, 19 and 24, on the \mathbb{W} . bdy. of the \mathbb{T} p.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.

_		Dep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona	
	CHAINS	From the cor. of secs. 17, 18, 19 and 20.	
		N. 0°08' W., bet. secs. 17 and 18.	
		Over gently rolling land.	
	10.60	Underground pipe line, bears S. 52°45' E. and N. 52°45' W	
	40.00	Point for the ½ sec. cor. of secs. 17 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T19N_R19E	
		S 18 S 17 1967	
		Set a cedar post, 3 ins. diam., 3 ft. long, alongside the iron post.	
	79.20	Wash, 50 1ks. wide, 1 ft. deep, drains West.	
	80.00	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T19N R19E	
		S 7 S 8 S18 S17	
		1967	
		Set a cedar post, 4 ins. diam., 5 ft. long, alongside the iron post.	
		Land, gently rolling.	
		Soil, clay loam. Timber, none.	
		Undergrowth, sage and rabbit brush.	
		From the cor. of secs. 8, 9, 16 and 17.	
		S. 89°49' W., bet. secs. 8 and 17.	
		Over steep badlands.	
	7.00	Leave badlands; enter rolling land, bears N. and S.	
	40.35	Point for the ½ sec. cor. of secs. 8 and 17, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
		Set the iron post 22 ins. in the ground, brass cap mkd.	
		T19 N R19E	
		$\begin{smallmatrix} \frac{1}{4} & \frac{S}{S} & \frac{8}{17} \\ 1067 & \frac{1}{2} & \frac{1}$	
		1967	
		Set a cedar post, 3 ins. diam., 6 ft. long, alongside the iron post.	

De	ep. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizon
chains 44.00	Wash, 15 lks. wide, 2 ft. deep, drains N.
45.30	Bladed road, bears N. and S.
49.00	Underground pipe line, bears S. 19° E. and N. 19° W.
80.69	The cor. of secs. 7, 8, 17 and 18.
	Land, badlands to rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	S. 89°50' W., bet. secs. 7 and 18.
	Over rolling land.
2.50	Wash, 50 lks. wide, 1 ft. deep, drains N. 40° W.
39.97	Point for the ½ sec. cor. of secs. 7 and 18, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	S 7 S 18 1967
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.
80.12	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°11' W., bet. secs. 7 and 8.
	Over gently rolling land.
32.30	Wash, 150 lks. wide, 3 ft. deep, drains W.
40.00	Point for the 4 sec. cor. of secs. 7 and 8, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	s 7 s 8 1967
	Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.

 De	p. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizon
80.00	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T19N R19E S 6 S 5 S 7 S 8 1967
	Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sage and rabbit brush.
	From the cor. of secs. 4, 5, 8 and 9.
	S. 89°49' W., bet. secs. 5 and 8.
	Over rolling land.
12.00	Track road, bears N. 35° E. and S. 35° W.
40.27	Point for the ½ sec. cor. of secs. 5 and 8, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E 2 S 5 S 8 1967
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the iron post.
71.70	Bladed road, bears S. 18° E. and N. 18° W.
76.80	Underground pipe line, bears S. 19° E. and N. 19° W.
80.53	The cor. of secs. 5, 6, 7 and 8.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	S. 89°55' W., bet. secs. 6 and 7.
	Over rolling land.
39.95	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Dep. Re	survey.	Subdivisional	Lines,	Τ.	19	Ν.,	R.	19	Ε.,	Arizona
---------	---------	---------------	--------	----	----	-----	----	----	-----	---------

Dep	. Resurvey, Subdivisional Lines, T. 19 N., R. 19 E., Arizona
CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E \$\frac{S}{5} \frac{6}{5} \frac{7}{1967}
	Set a cedar post, 3 ins. diam., 4 ft. long, alongside the cor.
57.70	Wash, 120 1ks. wide, 8 ft. deep, drains S. 30° W.
66.80	Cottonwood Wash, 330 lks. wide, 5 ft. deep, drains S.
79.99	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 2°13' E., bet. secs. 5 and 6.
	Over gently rolling land.
12.03	Underground pipe line, bears S. 19°10' E. and N. 19°10' W.
19.10	Bladed road, bears S. 40° E. and N. 40° W.
40.03	Point for the ½ sec. cor. of secs. 5 and 6, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E
	S 6 S 5 1967
	Set a cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.
68.34	Wash, 140 lks. wide, 3 ft. deep, drains S. 70° W.
71.90	Bladed road, bears N. 80° E. and SW.
80.23	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.

Subdivision, Section 12, T. 19 N., R. 19 E., Arizona

		Subdivision, Section 12, T. 19 N., R. 19 E., Arizona	•
	CHAINS	Subdivision, Section 12, T. 19 N., R. 19 E.	
		From the ½ sec. cor. of secs. 12 and 13.	
•		N. 0°07' W., on the N. and S. center line of sec. 12.	
		Over steep badlands.	
•	20.05	Point for the CS 1/16 sec. cor. of sec. 12.	
		Set the iron post 24 ins. in the ground, brass cap mkd.	
		T19N R19E	
		$\operatorname{CS} \frac{1}{16}$	
		S 12 1967	
		Raise a mound of stone W. of the cor.	
	40.10	Point for the C ½ sec. cor. of sec. 12.	
		Set the iron post, 18 ins. in the ground, mound of stone to the top, brass cap mkd.	
		T19N R19E C	
		S 12	
		1967	
		Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.	
	.80.15	The ½ sec. cor. of secs. 1 and 12.	
		Land, steep badlands. Soil, clay loam.	
		Timber, none. Undergrowth, widely scattered sagebrush and bunch grass.	
		From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.	
		S. 89°44' W., on the E. and W. center line of sec. 12.	
	,	Over steep badlands.	
	20.12	Point for the CE 1/16 sec. cor. of sec. 12.	
	4	Set the iron post 22 ins. in the ground, brass cap mkd.	
		T19N R19E	,
	·	$CE \frac{1}{16}$	
		S 12	
	4	1967	
	40.04	Raise a mound of stone N. of the cor.	
	40.24	The C ½ sec. cor. of sec. 12.	
	80.50	The ½ sec. cor. of secs. 11 and 12.	

	Subdivision, Section 12, T. 19 N., R. 19 E., Arizona
CHAINS	Land, steep badlands. Soil, clay loam. Timber, none. Undergrowth, widely scattered sagebrush and bunch grass.
	Subdivision, SE ½ of Sec. 12, T. 19 N., R. 19 E.
	From the E 1/16 sec. cor. of secs. 12 and 13.
	N. 0°11' W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 12.
	Over nearly level land.
7.60	Leave nearly level land; enter badlands, bears NE.
20.04	Point for the SE 1/16 sec. cor. of sec. 12.
	Set the iron post 15 ins. in the ground, mound of stone to the top, brass cap mkd.
	T19N R19E
	SE $\frac{1}{16}$
	S 12
	1967
40.06	The CE 1/16 sec. cor. of sec. 12.
	Land, nearly level to badlands. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	From the S 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.
	S. 89°43' W., on the E. and W. center line of the SE ½ of sec. 12.
	Over nearly level land.
12.00	Leave nearly level land; enter badlands, bears NE. and SW.
20.14	The SE 1/16 sec. cor. of sec. 12.
40.28	The CS 1/16 sec. cor. of sec. 12.
	Land, nearly level to badlands. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.

		Subdivision, Section 26, T. 19 N., R. 19 E., Arizona
	CHAINS	
		Subdivision of Sec. 26, T. 19 N., R. 19 E.
		From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
•		N. 0°10' W., on the N. and S. center line of sec. 26.
•		Over rolling land.
	20.03	Point for the CS 1/16 sec. cor. of sec. 26.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E C S
		$\frac{1}{16}$
		S 26
		1967
		Set a cedar post, 4 ins. diam., 5 ft. long, alongside and raise a mound of stone W. of the cor.
	40.06	Point for the C 1/2 sec. cor. of sec. 26.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N_R19E
		C 1/4
		s 26
		1967
		Raise a mound of stone W. of the cor.
	80.06	The point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
		Land, rolling.
	`	Soil, clay loam. Timber, none.
		Undergrowth, sagebrush and bunch grass.
		From the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
		S. 89°46' W., on the E. and W. center line of sec. 26.
		Over rolling land.
	9.40	Wash, 40 lks. wide, 6 ft. deep, drains S.
	23.60	Wash, 25 lks. wide, 5 ft. deep, drains SE. for 2.00 chs., thence drains S.
	40.36	The C ½ sec. cor. of sec. 26.
	60.54	Point for the CW $1/16$ sec. cor. of sec. 26. This cor. was not monumented.
	80.72	The point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
		Land, rolling. Soil, clay loam.
		Timber, none.
1	Ī	Undergrowth, sagebrush and bunch grass.

	Subdivision, Section 34, T. 19 N., R. 19 E., Arizona
CHAINS	Subdivision, SW な, Sec. 26, T. 19 N., R. 19 E.
	From the W 1/16 sec. cor. of secs. 26 and 35.
°	N. 0°14' W., on the N. and S. center line of the SW ½ of sec. 26.
	Over rolling land.
20.01	Point for the SW 1/16 sec. cor. of sec. 26.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E S W
	$\frac{1}{16}$
	s 26
	1967
40.03	The point for the CW 1/16 sec. cor. of sec. 26.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	ondergrowth, sagebrush and bunch grass.
	From the CS 1/16 sec. cor. of sec. 26.
	S. 89°47' W., on the E. and W. center line of the SW な of sec. 26.
	Over rolling land.
20.17	The SW 1/16 sec. cor. of sec. 26.
40.35	The point for the S 1/16 sec. cor. of secs. 26 and 27.
	Land, rolling. Soil, clay loam.
	Timber, none. Undergrowth, sagebrush and bunch grass.
	ondergrowth, sagebrash and bunch grass.
	Subdivision of Section 34, T. 19 N., R. 19 E.
·	From the ½ sec. cor. of sec. 34 on the S. bdy. of the Tp., monumented by an iron post as described in the official records of the 1920-1921 resurvey by S. E. Blout.
	N. 0°13' W., on the N. and S. center line of sec. 34.
	Over gently rolling land.
5.10	Underground pipe line, bears S. 43° E. and N. 43° W.
19.95	Point for the CS 1/16 sec. cor. of sec. 34.
	,

Subdivision, Section 34, T. 19 N., R. 19 E., Arizona

		Subdivision, Section 34, T. 19 N., R. 19 E., Arizona
	CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E
		C
•		$S\frac{1}{16} S 34$
		1967
		Raise a mound of stone W. of the cor.
	26.90	Track road, bears E. and W.
	35.80	Leave gently rolling land; enter rolling land, bears E. and W.
	39.90	Point for the C ½ sec. cor. of sec. 34.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E
		C ½ S 34
		1967
		from which
		A flowing spring, bears N. 45°26' E., 1.02 chs. dist.
		A flowing spring, bears N. 48°03' E., 4.50 chs. dist.
		A stock pond, bears S. 67°08' E., 12.90 chs. dist.
		Raise a mound of stone W. of the cor.
	44.80	Wash, 10 lks. wide, 3 ft. deep, drains W.
	59.91	Point for the CN 1/16 sec. cor. of sec. 34.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E
		1 C N 16 S 34
		1967
		Set a cedar post, 5 ins. diam., 5 ft. long, alongside the iron post.
	78.86	Fence, barbed wire, bears E. and W.
	79.92	The $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
·		Land, gently rolling to rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		From the 4 sec. cor. of secs. 34 and 35.
		S. 89°57' W., on the E. and W. center line of sec. 34.
\		Over gently rolling land.

	S	ubdivision, Section 34, T. 19 N., R. 19 E., Arizona
СНА 18.	1	ack road, bears N. and S. 40° E.
19.		sh, 25 1ks. wide, 3 ft. deep, drains S. 15° W.
20.	l6 Po	pint for the CE 1/16 sec. cor. of sec. 34. This or. was not monumented.
22.		rack road, bears N. and S.
22.	I	ence, barbed wire, bears N. and S. for 2 chs., nence E. and W.
24.		eave gently rolling land; enter rolling land,
39.	40 Fe	ence, barbed wire, bears N. and S.
40.	32 T1	ne C ½ sec. cor. of sec. 34.
69.	35 Ur	nderground pipe line, bears S. 30° E. and N. 30° W.
73.	50 Wa	ash, 200 lks. wide, 5 ft. deep, drains S.
80.	70 T1	ne ½ sec. cor. of secs. 33 and 34.
	So	and, gently rolling to rolling. oil, clay loam. imber, none. ndergrowth, sagebrush and bunch grass.
		Subdivision, SE ½ of Sec. 34, T. 19 N., R. 19 E.
	1	rom the E 1/16 sec. cor. of sec. 34, on the S. bdy. f the Tp.
		. 0°08' W., on the N. and S. center line of the E $\frac{1}{4}$ of sec. 34.
,	0,	ver gently rolling land.
12.	75 Dy	yke, bears E. and W.
13.	75 W	est edge of stock tank.
19.	99 P	oint for the SE 1/16 sec. cor. of sec. 34.
	Se	et the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E SE $\frac{1}{16}$ S 34
		1 6 1967
		et a cedar post, 4 ins. diam., 4 ft. long, alongside ne iron post.
39.	96 T1	ne point for the CE 1/16 sec. cor. of sec. 34.
	S	and, gently rolling. oil, clay loam. imber, none.
	Uı	ndergrowth, sagebrush and bunch grass.

57.

	Subdivision,	Section	22,	т.	19 N.,	R.	19	Ε.,	Arizona
--	--------------	---------	-----	----	--------	----	----	-----	---------

CHAINS	From the S 1/16 sec. cor. of secs. 34 and 35.
	S. $89^{\circ}57'$ W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 34.
	Over gently rolling land.
20.13	The SE 1/16 sec. cor. of sec. 34.
39.17	Fence, barbed wire, bears N. and S.
40.26	The CS 1/16 sec. cor. of sec. 34.
	Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	Subdivision, Section 22, T. 19 N., R. 19 E.
	From the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	N. 0°10' W., on the N. and S. center line of sec. 22.
	Over rolling land.
2.05	Fence, barbed wire, bears N. 30° E. and S. 30° W.
20.01	Point for the CS 1/16 sec. cor. of sec. 22.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E C S $\frac{1}{16}$ S 22 16 1967
	from which
	A local 1 in. survey pipe, bears N. 21°17' W., .94 lks. dist.
40.03	Point for the C ½ sec. cor. of sec. 22.
	Set the iron post 20 ins. in the ground, collar of stone to the top, brass cap mkd.
	T19N R19E
	C な S 22 1967
63.40	Wash, 20 1ks. wide, 3 ft. deep, drains W.
80.05	The ½ sec. cor. of secs. 15 and 22.
	Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.

		Subdivision, Section 22, T. 19 N., R. 19 E., Arizona
	CHAINS	From the point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.
		S. 89°53' W., on the E. and W. center line of sec. 22.
		Over rolling land.
	20.17	Point for the CE 1/16 sec. cor. of sec. 22.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E C E
		$\frac{1}{16}$ S 22
		1967
		Set a cedar post, 6 ins. diam., $5\frac{1}{2}$ ft. long, alongside the iron post.
	32.90	Track road, bears N. 30° E. and S. 30° W.
	34.50	Fence, barbed wire, bears N. 20° E. and S. 20° W.
	40.34	The C な sec. cor. of sec. 22.
	77.30	Wash, 15 1ks. wide, 2 ft. deep, drains W.
	80.70	The ½ sec. cor. of secs. 21 and 22.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
		Subdivision, SE な of Sec. 22, T. 19 N., R. 19 E.
		From the E 1/16 sec. cor. of secs. 22 and 27.
·		N. 0°09' W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 22.
		Over rolling land.
	20.01	Point for the SE 1/16 sec. cor. of sec. 22.
		Set the iron post 16 ins. in the ground, mound of stone to the top, brass cap mkd.
		T19N R19E S E
		1 1 6 S 22 1967
	40.01	The CE 1/16 sec. cor. of sec. 22.

Land, rolling.
Soil, clay loam.
Timber, none.
Undergrowth, sagebrush and bunch grass.

Subdivision, Section 4, T. 19 N., R. 19 E., Arizona

		Subdivision, Section 4, T. 19 N.,R. 19 E., Arizona
	CHAINS	
		From the point for the S 1/16 sec. cor. of secs. 22 and 23.
		S. 89°54' W., on the E. and W. center line of the SE 表 of sec. 22.
~		Over rolling land.
•	20.17	The SE 1/16 sec. cor. of sec. 22.
	37.50	Track road, bears S. 10° E. and N. 10° W.
	38.00	Fence, barbed wire, bears S. 10° E. and N. 10° W.
	40.34	The CS 1/16 sec. cor. of sec. 22.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush and bunch grass.
	-	
		Subdivision, Section 4, T. 19 N., R. 19 E.
		From the point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
		N. 1°26' E., on the N. and S. center line of sec. 4.
		Over rolling land.
	20.02	Point for the CS 1/16 sec. cor. of sec. 4.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T19N R19E
·		CS $\frac{1}{16}$
		S 4
		1967
	·	Set a cedar post, 4 ins. diam., 3 ft. long, alongside the iron post.
	35.20	Track road, bears East and West.
	40.04	Point for the C ½ sec. cor. of sec. 4.
,		Set the iron post 20 ins. in the ground, brass cap mkd.
		T19N R19E
		C ½ S 4
		1967
		Set a cedar post, 4 ins. diam., 4 ft. long, alongside the iron post.
	80.29	The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
		Land, rolling.
		Soil, clay.
		Timber, none. Undergrowth, scattered sage and bunch grass.

	Subdivision, Section 4, T. 19 N., R. 19 E., Arizona
CHAINS	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	S. 89°52' W., on the E. and W. center line of sec. 4.
	Over rolling land.
20.075	Point for the CE 1/16 sec. cor. of sec. 4.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T19N R19E
	CE $\frac{1}{16}$
	S 4
	1967
	Set a cedar post, 6 ins. diam., 4 ft. long, alongside the iron post.
40.15	The C ½ sec. cor. of sec. 4.
80.31	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
-	Land, rolling. Soil, clay.
	Timber, none.
	Undergrowth, scattered sage and bunch grass.
	Subdivision, SE 4, Sec. 4, T. 19 N., R. 19 E.
	From the E 1/16 sec. cor. of secs. 4 and 9.
	N. 1°18' E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 4.
	Over rolling land.
20.01	Point for the SE 1/16 sec. cor. of sec. 4.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T19N R19E
	SE 1/16
	S 4
	1967
33.04	Track road, bears East and West.
40.02	The CE 1/16 sec. cor. of sec. 4.
	From the S 1/16 sec. cor. of secs. 3 and 4.
	S. 89°51' W., on the E. and W. center line of the SE ½ of sec. 4.
	Over rolling land.
20.12	The SE 1/16 sec. cor. of sec. 4.
40.24	The CS 1/16 sec. cor. of sec. 4.

T. 19 N., R. 19 E., G&SR M., Arizona

General Description

CHAINS T

The land in Township 19 North, Range 19 East, varies from gently rolling in the south and west portions to rolling hills and gently rolling mesa in the central and east portions. The north central and northeast portions are steep badlands. The soil is clay loam except the badlands, which is clay hardpan.

The township is cut by numerous washes, with Cottonwood Creek in the northwest corner. Some stock ponds throughout and flowing springs in the south central portion give a moderate water supply. The grazing of livestock is the primary interest as there is moderate grass throughout most of the township except the badlands.

A bladed road in the west portion and some track roads give access to most of the township. Two natural gas pipe lines cross the west half of the township. One enters in section 34 and exits in section 18. The other enters in section 33 and exits in section 6. Both pipe lines are underground; therefore, bearings and distances are approximate. No evidence of the original corners was found, due mostly to the time elapsed since the original survey.

	CHAINS	
,		
		•
	- ' '	
,		
	-	

BOOK 4843

Form 4-680 (June 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John H. Witmer	Supervisory Surveying Technician
Duane R. Erlandson	Surveying Aid
Martin W. Fuller	Surveying Aid
David G. Jaramillo	Surveying Aid
Willard R. Wilber	Surveying Aid
Ira M. Thiessen	Surveying Aid
	1.4
	•

INTERIOR--PORTLAND, OREGON

BOOK 4843

CERTIFICATE OF SURVEY

, HEREBY CERTIFY upon honor that, Wel, Boyd S. Owens and Gary T. Oviatt in pursuance of special instructions bearing date of the $21 \text{st}_{\text{day}}$ of , 19 66, October we Nave made a dependent resurvey of the east, west, and north boundaries, a portion of the south boundary and subdivisional lines, and a survey of subdivisions of sections 4, 12, 22, 26 and 34 of Township 19 North, Range 19 East,

Gila and Salt River Meridian, in the State of Arizona , which of the are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 4, 1968

December 4, 1968 (Date)

Say J. Avatt

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL JAN 2 9 1969 Date -

BUREAU OF LAND MANAGEMENT,

The foregoing field notes of the dependent resurvey of the east, west, and north boundaries, a portion of the south boundary and subdivisional lines, and survey of subdivisions of sections 4, 12, 22, 26 and 34 of Township 19 North, Range 19 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens and Gary T. Oviatt having been critically examined and found correct, are hereby approved.

> JUN 2 5 1969 (Date)

_	co	т.	1=1	CA	TE	ΩE.	TR/	244	CRI	D.	Ŧ
\Box		$\overline{}$	ш	\sim	CLÉ.	OI.	111/	1110	٠. ٠.	•	•

That the foregoing transcript	of the field notes of the above-described surveys in
I CERTIFI That the folegoing the	_

is a true copy of the original field notes.

(Chief, Division of Engineering) (Date)