BOOK 4845

Form 4-679 (January 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

	DEPENDENT RESURVEY
	of the
	SOUTH and EAST BOUNDARIES
	and
	SUBDIVISIONAL LINES
	and the
ESTABLISHME	ENT of the NORTH & SECTION COR. of SECTION 6
	and
	SURVEY of SUBDIVISIONS
in SECTI	IONS 6, 8, 10, 12, 14, 20, 28, 30 and 36,
	TOWNSHIP 20 NORTH, RANGE 20 EAST
Of the	Gila and Salt RiverMeridi
n the State of	Arizona
	EXECUTED BY
Louis D. Gilbert	Supervisory Cadastral Surveyor
.•	
<i>I</i>	ed <u>June 23</u> , 19 <u>67</u> , which provided for the surve
	459, approvedJune 26, 1967
nd assignment instructions date	ed, 19 <u>67</u> .
Survey c	commenced July 10 19 67

August 9

Survey completed _

_, 19 __67

INDEX DIAGRAM

Townsl	hip20 No	orth	, Range <u>2</u>	0 East	· · · · · · · · · · · · · · · · · · ·	
6 36	37 5 36	29 4 28	23 8	18 2	14 1 13	4
7	-35 8	28 9	22-10-	17 11	1212	4
35 18	34 17	27 27 16	21 15	17	1 ² 2	3
34 19	-33 20	26 25 21	20 22	16 15 28	11 10 24	2
32 	31 29	25	20 19 27	15 15 26	10 10 25	2
30 31	30	24	19 19 84	14 14 85	9 -8 -8	1
8	7	7	6	6	5	- :

Subdivision of section 6----Page 38 Subdivision of section 8----Page 39 Subdivision of section 10----Page 40 Subdivision of section 12----Page 42 Subdivision of section 14----Page 43 Subdivision of section 20----Page 44 Subdivision of section 28-----Page 46 Subdivision of section 30-----Page 47 Subdivision of section 36--------Page 50

1: /

Township 20 North, Range 20 East

	Township 20 North, Range 20 East Gila and Salt River Meridian, Arizona
CHAINS	The south boundary of Township 20 North, Range 20 East was surveyed in 1882 by H. Meyrick. The south boundary was retraced under Group 449 in 1966 by Owens and Oviatt who remonumented the corner of Townships 19 and 20 North, Ranges 20 and 21 East. The east boundary was surveyed in 1882 by F. Follman. The north boundary, the Fifth Standard Parallel North, was surveyed in 1882 by F. Follman and resurveyed in 1947 by Ty White. The west boundary was surveyed in 1882 by F. Follman, retraced in 1966 by Owens and Oviatt, and resurveyed concurrently under this same group. The field note record thereof is included under Township 20 North, Range 19 East. The subdivisional lines were surveyed in 1882 by F. Follman.
	The following field notes are those of a dependent resurvey of the east and south boundaries and subdivisional lines, designed to restore the corners to their true original location according to the best available evidence, together with the establishment of the north ½ section corner of section 6, and the survey of subdivisions in sections 6, 8, 10, 12, 14, 20, 28, 30 and 36, Township 20 North, Range 19 East, Gila and Salt River Meridian, Arizona.
	This resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated June 23, 1967
	Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, $2\frac{1}{2}$ inches in diameter, flanged at the base and with a brass cap riveted to the top.
	The geographic position of the southeast corner of the township as determined by traverse from U.S.C. & G.S. triangulation station "ASYLUM" is: Latitude 35°04'58" North, and Longitude 110°09'50" West.
	The mean magnetic declination was observed to be 14° E.
	Dependent Resurvey of the East Boundary, T. 20 N., R. 20 E., G&SRM, Arizona
	Reestablishment of the Survey Executed by F. Follman in 1882
	From the cor. of Tps. 19 and 20 N., Rs. 20 and 21 E., monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field note record of the retracement of the S. bdy., T. 20 N., R. 20 E., in 1966.
	N. 1°04' E., bet. secs. 31 and 36.
	Over rolling land, along fence line to the east.
10.50	Wash, 30 1ks. wide, 5 ft. deep, drains SE.
22.50	Power line, bears N. 42°21' E., and S. 42°21' W.
24.30	Track road, bears N. 60° E. and S. 60° W., curving S. 42°21' W.
25.40	Power line, bears N. 42°21' E. and S. 42°21' W.

		Dep. Res., E. Bdy., T. 20 N., R. 20 E.
	chains 40.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		from which
		A N-S fence line, bears East, 67 lks. dist.
	46.70	Wash, 10 1ks. wide, 2 ft. deep, drains E.
	68.10	Wash, 15 lks. wide, l ft. deep, drains SE.
	74.40	Fence, bears S. 0°50' E. and N. 0°50' W.
	80.56	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		from which
		A N-S fence line, bears West, 15 lks. dist.
		Land, rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		N. 1°04' E., bet. secs. 25 and 30.
		Over rolling land.
	3.50	Wash, 10 lks. wide, 1 ft. deep, drains E.
	10.40	· ·
		Wash, 10 lks. wide, 1 ft. deep, drains S. 80° E.
	15.60	Enter rolling badlands.
	40.28	Point for the ½ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
,	42.30	Wash, 5 lks. wide, 1 ft. deep, drains S. 70° E.
	52.10	Wash, 20 1ks. wide, 1 ft. deep, drains S. 80° E.
	65.80	Cor. of fences, bears West, 60 lks. dist.; fences bear S. 0°50' E., S. 45° W. and N. 0°50' W.
	70.90	Leave badlands; thence over gently rolling land.
	80.56	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		from which
		A fence line bears West, 1.78 chs. dist.; fence bears S. 0°50' E. and N. 0°50' W.
		Land, rolling to gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass and cacti.
		N. 1°04' E., bet. secs. 19 and 24.
		Over nearly level land.

Dep. Res., E. Bdy., T. 20 N., R. 20 E.

		
	CHAINS 40.28	Point for the ½ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
•		from which
		A fence bears West, 2.52 chs. dist.; fence bears S. 0°50' E. and N. 0°50' W.
	70.90	Enter rolling badlands.
	80.56	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		from which
		A fence line bears West, 3.37 chs. dist.; fence bears S. 0°50' E. and N. 0°50' W.
		Land, nearly level to rolling badlands. Soil, clay loam.
		Timber, none. Undergrowth, bunch grass and cacti.
		N. 1°04' E., bet. secs. 13 and 18.
		Over rolling badlands.
	40.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		from which
		A fence, bears West, 4.12 chs. dist.; fence bears S. 0°50' E. and N. 0°50' W.
	52.00	Leave badlands; thence over gently rolling land.
	68.40	Leave gently rolling land; enter rolling badlands.
	80.56	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T20N
		R20E R21E S 12 S 7 S 13 S 18 1967
		from which
		A fence bears West, 4.90 chs. dist.; fence bears S. 0°50' E. and N. 0°50' W.
		Raise a mound of stone W. of the cor.
	ì	Land, gently rolling and badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and cacti.
	_	ondergrowth, bullet grass and cacer.
		.

	Dep. Res., E. Bdy., T. 20 N., R. 20 E.
CHAINS	N. 1°04' E., bet. secs. 7 and 12.
	Over rolling badlands.
40.28	Point for the ½ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E R21E
,	s 12 s 7 1967
	from which
	A fence, bears West, 5.73 chs. dist.; fence bears S. 0°50' E. and N. 0°50' W.
	Deposit glass in hole.
80.56	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
·	T20N R20E R21E
	S 1 S 6 S 12 S 7 1967
	from which
	A fence bears West, 6.97 chs. dist.; fence bears irregularly N. and S.
,	Land, rolling badlands. Soil, clay loam.
	Timber, none. Undergrowth, bunch grass and sagebrush.
,	N. 1°04' E., bet. secs. 1 and 6.
	Over rolling badlands.
16.50	Wash, 20 lks. wide, 1 ft. deep, drains W.
35.20	Track road, bears E. and W.
40.28	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.58	Fence, barbed wire, bears E. and W.
81.04	Intersect the Fifth Standard Parallel North.
	Point for the closing cor. of Tps. 20 N., Rs. 20 and 21 E, at proportionate distance; there is no remaining evidence of the original cor.
1	

Dep. Res., S. Bdy., T. 20 N., R. 20 E.

	Dep. Res., D. Bay., 1. 20 R., R. 20 E.
CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.
	T21N R20E
	S 36 S 1 S 6
	C C T20N
	R20E R21E
	1967
	from which
	The Stan. cor. of Tps. 21 N., Rs. 20 and 21 E., bears S. 89°59' E., 4.83 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.
	Deposit glass in hole.
	Land, rolling badlands.
	Soil, clay loam. Timber, none.
	Undergrowth, bunch grass and cacti.
	Dependent Resurvey of the
	South Boundary, T. 20 N., R. 20 E., G&SRM, Arizona
	Reestablishment of the Survey Executed by H. Meyrick in 1882
	From the cor. of Tps. 19 and 20 N., Rs. 20 and 21 E.
	N. 89°39' W., bet. secs. 1 and 36.
	Over nearly level land.
10.00	Enter rolling badlands.
21.70	Power line, bears N. 42°21' E. and S. 42°21' W.
39.93	Point for the ½ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.86	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	T20N R20E
	<u>s 35 s 36</u> s 2 s 1
	T19N 1967
	Land, nearly level to rolling badlands. Soil, clay loam.
	Timber, none. Undergrowth, bunch grass and cacti.

Dep. Res., S. Bdy., T. 20 N., R.	≥p. Kes.,	S.	Bdy.,	т.	20	Ν.,	К.	20 E	
----------------------------------	-----------	----	-------	----	----	-----	----	------	--

CHAINS	N 89°39' W., bet. secs. 2 and 35.
	Over rolling badlands.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.
!	T20N R20E 2 S 35 T19N 1967
59.80	Leave rolling badlands.
73.40	Fence, barbed wire, bears N. and S.
79.86	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	from which
	An E-W fence line bears South 1.90 chs. dist.
	Land, rolling badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and cacti.
-	N. 89°39' W., bet. secs. 3 and 34.
	Over rolling land.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
79.86	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T20N R20E S 33 S 34 S 4 S 3 T19N 1967
	from which
	An E-W fence line bears South 1.74 chs. dist.
	Land, rolling. Soil, clay loam.

Dep. Res., S. Bdy., T. 20 N., R. 20 E.

	Dep. Res., S. Bdy., T. 20 N., R. 20 E.
CHAINS	N. 89°39' W., bet. secs. 4 and 33.
	Over gently rolling land.
6.20	Track road, bears N. and S.
19.50	Enter rolling badlands.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T20N R20E 2 S 33 S 4 T19N 1967
79.86	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	T20N R20E S 32 S 33 S 5 S 4 T19N 1967
	Land, gently rolling to rolling badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and cacti.
	N. 89°39' W., bet. secs. 5 and 32.
,	Over rolling badlands.
2.90	Top of spur, slopes N.
39.93	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
68.40	E. rim of mesa, bears N. and S., thence over top of mesa.
79.86	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E S 31 S 32 S 6 S 5
-	T19N 1967

|--|

	CHAINS	N. 89°39' W., bet. secs. 6 and 31.
		Over rolling badlands.
	10.30	W. rim of mesa, bears N. and S.
	19.10	Top of spur, slopes N.
	35.10	Top of spur, slopes N.
	39.93	Point for the ½ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
		Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
9		T20N R20E 1/4 S 31 S 6 T19N 1967
	58.40	Top of spur, slopes N.
	65.50	Fence, bears N. and S.
	86.06	The cor. of Tps. 19 and 20 N., Rs. 19 and 20 E., monumented by an iron post, set, mkd. and witnessed as described in the field note record of the dependent resurvey of the E. bdy., T. 19 N., R. 19 E., in 1966.
		Land, rolling badlands. Soil, clay loam. Timber, none. Undergrowth, bunch grass and cacti.
		Dependent Resurvey of the Subdivisional Lines, T. 20 N., R. 20 E., G&SRM, Arizona
		Reestablishment of the Survey Executed by F. Follman in 1882.
		From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
		N. 1°09' E., bet. secs. 35 and 36.
		Over rolling badlands.
	19.20	Wash, 30 1ks. wide, 4 ft. deep, drains S. 80° E.
	20.12	Point for the S 1/16 sec. cor. of secs. 35 and 36, at midpoint.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T20N R20 E S 1/16 S 35 S 36 1967
		Raise a mound of stone W. of the cor.

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.	
CHAINS 29.90	Wash, 30 1ks. wide, 3 ft. deep, drains S. 45° E.	
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.	
	Set the iron post 18 ins. in the ground, brass cap mkd.	
	T2ON R2OE	
	s 35 s 36 1967	
	Set a wooden post, 3 ins. in diam., 3 ft. long, alongside the cor.	
68.70	Wash, 10 1ks. wide, 2 ft. deep, drains. S. 45° W.	
75.90	Leave badlands; enter gently rolling land.	
80.48	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.	
	Set the iron post 20 ins. in the ground, brass cap mkd.	
	T20N R20E S 26 S 25 S 35 S 36 1967	
	Set a wooden post, 3 ins. in diam., 4 ft. long alongside the cor.	

From the point for the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

N. $89^{\circ}44'$ W., bet. secs. 25 and 36.

Land, rolling badlands and gently rolling.

Over rolling badlands.

Undergrowth, bunch grass.

Soil, clay loam. Timber, none.

- 0.15 Fence, bears S. 0°50' E. and N. 0°50' W.
- 39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set the iron post 18 ins. in the ground, brass cap mkd.

T20N R20E
$$\frac{1}{4}$$
 $\frac{S}{S}$ $\frac{25}{36}$ $\frac{36}{1967}$

Set a wooden post, 3 ins. in diam., 4 ft. long, alongside the $\operatorname{cor.}$

- 65.50 Leave badlands; thence over gently rolling land.
- 79.80 The cor. of secs. 25, 26, 35 and 36.

		Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.		
	CHAINS	Land, rolling badlands to gently rolling. Soil, clay loam.		
		Timber, none. Undergrowth, bunch grass.		
		N. 1°01' E., bet. secs. 25 and 26.		
		Over gently rolling land.		
	5.60	Fence, bears N. 63°10' E. and S. 63°10' W.		
	Point for the ½ sec. cor. of secs. 25 and 26, at propor tionate distance; there is no remaining evidence of the original corner. This corner is not monumented.			
		from which		
		A stock pond, bears N. 46°48' E., 13.40 chs. dist.		
	45.20	Track road, bears N. 45° E. and S. 45° W.		
	63.00	Track road, bears S. 25° E. and N. 25° W.		
	80.46 Point for the cor. of secs. 23, 24, 25 and 26, at propo tionate distance; there is no remaining evidence of the original corner. This corner is not monumented.			
		Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass.		
		From the point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.		
		N. 89°47' W., bet. secs. 24 and 25.		
		Over gently rolling land.		
	1.78	Fence, bears S. 0°50' E. and N. 0°50' W.		
	39.94	Point for the ½ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.		
	79.88	The point for the cor. of secs. 23, 24, 25 and 26.		
		Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.		
		N. 0°55' E., bet. secs. 23 and 24.		
		Over nearly level land.		
	40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.		
	50.90	Track road, bears N. 45° E. and S. 45° W.		
	55.60	Enter gently rolling land.		
- 1				

Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS 80.44	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T20N R20E S 14 S 13 S 23 S 24 1967
_	Land, nearly level to gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	From the point for the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	N. 89°51' W., bet. secs. 13 and 24.
	Over rolling land.
3.37	Fence, bears S. 0°50' E. and N. 0°50' W.
28.80	Enter rolling badlands.
40.05	Point for the ½ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
56.00	Leave badlands and enter gently rolling land.
59.50	Track road, bears N. and S.
80.10	The cor. of secs. 13, 14, 23 and 24.
	Land, gently rolling and badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	N. 0°55' E., bet. secs. 13 and 14.
	Over nearly level land.
20.11	Point for the S 1/16 sec. cor. of secs. 13 and 14.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T20N R20E S 1/16 S 14 S 13 1967
	Raise a mound of stone W. of the cor.
22.10	Wash, 5 lks. wide, 2 ft. deep, drains N. 45° W.
40.22	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
59.50	Wash, 50 lks. wide, 5 ft. deep, drains N. 45° W.

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.					
80.4	i l					
	Set the iron post 18 ins. in the ground, brass cap mkd.					
	T20N R20E S 11 S 12 S 14 S 13 1967					
	Raise a mound of stone W. of the cor.					
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.					
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.					
	N. 89°55' W., bet. secs. 12 and 13.					
	Over gently rolling land.					
4.9	Fence, bears S. 0°50' E. and N. 0°50' W.					
40.	Point for the ½ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.					
	Set the iron post 18 ins. in the ground, brass cap mkd.					
	T20N R20E S 12					
	$\frac{1}{4} \frac{\frac{S}{12}}{\frac{13}{1967}}$					
	from which					
	A stock pond, bears S. 3°40' W., 35.30 chs. dist.					
	Deposit glass in hole.					
52.	Wash, 10 1ks. wide, 2 ft. deep, drains S.					
59.	Track road, bears irregularly N. and S.					
80.	The cor. of secs. 11, 12, 13 and 14.					
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.					
	N. 1°01' E., bet. secs. 11 and 12.					
	Over nearly level land.					
40.	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.					
	Set the iron post 17 ins. in the ground, mound of stone to top, brass cap mkd.					

Dep.	Res.,	Subdivisional	Lines,	Τ.	20 N.,	R.	20	Ε	•

		Dep. Res., Subdivisional Lines, 1. 20 N., K. 20 E.
	CHAINS	T20N R20E
A-1		s 11 s 12 1967
		Thence over gently rolling land.
→	60.36	Point for the N $1/16$ sec. cor. of secs. 11 and 12.
~		Set the iron post 24 ins. in the ground, brass cap mkd.
		T20N R20E N 1/16 S 11 S 12 1967
		Raise a mound of stone W. of the cor.
	80.48	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		Land, nearly level to gently rolling. Soil, sandy loam.
		Timber, none. Undergrowth, bunch grass.
		From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
		N. 89°57' W., bet. secs. 1 and 12.
		Over rolling badlands.
	6.97	Fence, bears S. 0°50' E. and N. 0°50' W.
	11.00	Leave badlands and enter gently rolling land.
	30.50	Wash, 15 1ks. wide, 3 ft. deep, drains S. 75° W.
	40.14	Point for the ½ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T20N R20E
		$\frac{1}{4} \frac{S}{S} \frac{1}{12}$ 1967
		Set a wooden post, 3 ins. in diam., 4 ft. long, alongside the cor.
	50.60	Wash, 50 1ks. wide, 3 ft. deep, drains N. 45° W.
	72.30	Track road, bears N. and S.
	80.28	The point for the cor. of secs. 1, 2, 11 and 12.
		Land, gently rolling and badlands. Soil, sandy loam. Timber, none.
	00.20	Land, gently rolling and badlands. Soil, sandy loam.

Dep. Res., Subdivisional Lines, T. 20 N., R. 2				
CHAINS	N. 1°01' E., bet. secs. 1 and 2.			
	Over gently rolling land.			
1.90	Wash, 20 lks. wide, 3 ft. deep, drains W.			
16.50	Track road, bears S. 45° E. and N. 45° W.			
35.70	Track road, bears E. and W.			
40.23	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.			
57.60	Wash, 10 lks. wide, 2 ft. deep, drains W.			
79.40	Fence, bears E. and W.			
80.70	S. edge of wash, bears E. and W.			
80.86	Intersect the Fifth Standard Parallel North.			
	Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.			
	from which			
	The true point for the standard cor. of secs. 35 and 36, T. 21 N., R. 20 E., bears S. 89°59' E., 5.17 chs. dist. The standard cor. is witnessed S. 89°59' E., 1.50 chs. dist. from the true point, by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.			
	Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.			
	From the point for the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.			
	N. 1°19' E., bet. secs. 34 and 35.			
	Over gently rolling land.			
2.10	Wash, 5 lks. wide, 2 ft. deep, drains N. 45° W.			
40.21	Point for the ½ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.			
80.42	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner, This corner is not monumented.			
	Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.			
	From the cor. of secs. 25, 26, 35 and 36.			
	N. 89°43' W., bet. secs. 26 and 35.			

Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.

		Dep. Res., Subdivisional Lines, 1. 20 N., R. 20 E.
	CHAINS	Over gently rolling land.
	11.10	Fence, bears N. 70° E. and S. 70° W.
No.	39.89	Point for the ½ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	66.40	Fence, bears N. and S.
	79.78	The point for the cor. of secs. 26, 27, 34 and 35.
		Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		N. 0°50' E., bet. secs. 26 and 27.
		Over nearly level land.
	10.80	Track road, bears S. 35° E. and N. 35° W.
	40.21	Point for the ½ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	80.42	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		From the point for the cor. of secs. 23, 24, 25 and 26.
		N. 89°46' W., bet. secs. 23 and 26.
		Over nearly level land.
	8.10	Track road, bears S. 10° E. and N. 10° W.
	40.03	Point for the ½ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	75.80	Track road, bears S. 45° E. and N. 45° W.
	77.10	Fence, bears N. and S.
	80.06	The point for the cor. of secs. 22, 23, 26 and 27.
		Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		N. 0°54' E., bet. secs. 22 and 23.
		Over nearly level land.
	2.70	Track road, bears S. 65° E. and N. 65° W.
	1	1

Dep.	Res.,	Subdivisional	Lines, T	. •	20	Ν.,	к.	20	Ŀ.

ļ	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.				
CHAINS 31.20	Fence, bears S. 5° E. and N. 5° W.				
40.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
44.60	Descend N. slope of mesa.				
78.20	Wash, 5 1ks. wide, 2 ft. deep, drains E.				
80.42	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
	from which				
	A stock pond, bears S. 9°47' W., 15.54 chs. dist.				
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.				
	From the cor. of secs. 13, 14, 23 and 24.				
	N. 89°49' W., bet. secs. 14 and 23.				
	Over gently rolling land.				
20.02	Point for the E 1/16 sec. cor. of secs. 14 and 23.				
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.				
	T20N R20E				
	$E 1/16\frac{S}{S} \frac{14}{23}$				
	5 23 1967				
21.80	Wash, 10 lks. wide, 1 ft. deep, drains N. 45° W.				
37.80	Wash, 10 1ks. wide, 2 ft. deep, drains N. 45° W.				
40.04	Point for the ½ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
51.50	Wash, 15 1ks. wide, 2 ft. deep, drains N.				
59.50	Wash, 15 lks. wide, 4 ft. deep, drains N.				
68.40	Wash, 10 1ks. wide, 2 ft. deep, drains N.				
80.08	The point for the cor. of secs. 14, 15, 22 and 23.				
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.				
	N. 0°58' E., bet. secs. 14 and 15.				
	Over gently rolling land.				
4.70	Wash, 10 1ks. wide, 2 ft. deep, drains E.				
	- '				

		Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.	
	CHAINS 32.50	Wash, 10 1ks. wide, 2 ft. deep, drains E.	
ų.	40.21	Point for the 4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.	
~	40.80	Top of lava ridge, bears S. 45° E. and N. 45° W.	
	80.42	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.	
		Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.	
		T20N R20E S 10 S 11 S 15 S 14 1967	
		Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.	
		From the cor. of secs. 11, 12, 13 and 14.	
		N. 89°52' W., bet. secs. 11 and 14.	
		Over nearly level land.	
	31.20	Wash, 1.70 chs. wide, 4 ft. deep, drains N. 45° W.	
	33.20	Wash, 70 1ks. wide, 4 ft. deep, drains N. 45° E.	
	40.01	Point for the ½ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.	
	80.02	The cor. of secs. 10, 11, 14 and 15.	
		Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.	
	•	N. 0°58' E., bet. secs. 10 and 11.	
		Over gently rolling land.	
	13.10	Wash, 10 1ks. wide, 1 ft. deep, drains N. 45° E.	
	40.21	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.	
		Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.	
		T20N R20E	
		s 10 s 11 1967	
	l	1	

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.				
76.60	Wash, 2.00 chs. wide, 5 ft. deep, drains N. 45° W.				
80.42	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.				
	From the point for the cor. of secs. 1, 2, 11 and 12.				
	N. 89°52' W., bet. secs. 2 and 11.				
	Over nearly level land.				
3.50	Wash, 15 lks. wide, 1 ft. deep, drains S. 85° W.				
40.04	Point for the ½ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
80.08	The point for the cor. of secs. 2, 3, 10 and 11.				
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.				
	N. 0°51' E., bet. secs. 2 and 3.				
	Over nearly level land.				
3.50	Wash, 5 lks. wide, 3 ft. deep, drains W.				
18.70	Track road, bears N. 45° E. and S. 45° W.				
38.80	Wash, 1.20 chs. wide, 4 ft. deep, drains S. 45° W.				
40.21	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
	from which				
	A windmill, bears S. 85°48'30" E., 11.00 chs. dist.				
79.18	Fence, bears E. and W.				
80.78	Intersect the Fifth Standard Parallel North.				
	Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.				
	from which				
	The Stan. cor. of secs. 34 and 35, T. 21 N., R. 20 E., bears S. 89°59' E., 5.51 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.				

CHAINS	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS	Land, nearly level.
	Soil, sandy loam.
	Timber, none. Undergrowth, bunch grass.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.
	N. 1°05' E., bet. secs. 33 and 34.
	Over nearly level land.
24.30	Track road, bears N. 40° E. and S. 40° W.
40.18	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
58.00	Track road, bears S. 30° E. and N. 30° W.
80.36	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	from which
	A stock pond, bears S. 80°19' W., 14.30 chs. dist.
	Land, nearly level. Soil, sandy loam. Timber, none.
	Undergrowth, bunch grass.
	From the point for the cor. of secs. 26, 27, 34 and 35.
	N. 89°42' W., bet. secs. 27 and 34.
	Over nearly level land.
10.30	Track road, bears N. 45° E. and S. 45° W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
80.06	The point for the cor. of secs. 27, 28, 33 and 34.
	Land, nearly level.
	Soil, sandy loam.
	Timber, none. Undergrowth, bunch grass.
	N. 0°58' E., bet. secs. 27 and 28.
	Over gently rolling land.
40.18	Point for the ½ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
80.36	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.

Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.

		Dep. Res., Subdivisional Lines, 1. 20 N., R. 20 E.
	CHAINS	Land, gently rolling. Soil, sandy loam. Timber, none.
		Undergrowth, bunch grass.
		From the point for the cor. of secs. 22, 23, 26 and 27.
		N. 89°45' W., bet. secs. 22 and 27.
		Over nearly level land.
	7.20	Track road, bears N. 45° E. and S. 45° W.
	32.00	Track road, bears S. 15° E. and N. 15° W.
	39.94	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	79.88	The point for the cor. of secs. 21, 22, 27 and 28.
		Land, nearly level. Soil, sandy loam.
		Timber, none. Undergrowth, bunch grass.
		N. 0°53' E., bet. secs. 21 and 22.
		Over nearly level land.
	40.17	Point for the ½ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	79.60	Track road, bears N. 50° E. and S. 50° W., curving S. 80° W.
	80.34	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		Land, nearly level. Soil, sandy loam.
		Timber, none. Undergrowth, bunch grass.
		From the point for the cor. of secs. 14, 15, 22 and 23.
		N. 89°48' W., bet. secs. 15 and 22.
		Over nearly level land.
	4.60	Fence, bears N. and S.
	18.80	Along S. slope of lava ridge.
	38.00	Top of lava ridge, bears N. 45° E. and S. 45° W., thence over gently rolling land.
	39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	70.60	Track road, bears N. and S., curving S. 10° E.
-		1

Dep. Res., Subdivisional	Lines,	Τ.	20 N.	, R.	20	Ε.	•
--------------------------	--------	----	-------	------	----	----	---

		Dep. Res., Subdivisional Lines, 1. 20 N., R. 20 E.
	CHAINS 75.40	Track road, bears S. 45° E. and N. 45° W., curving W.
	77.70	Track road, bears N. 65° E. and S. 65° W.
•	79.92	The point for the cor. of secs. 15, 16, 21 and 22.
-	_	Land, nearly level to rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
		N. 0°52' E., bet. secs. 15 and 16.
		Over gently rolling land.
	37.40	Enter rolling badlands.
	40.17	Point for the 4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	80.34	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
		Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
		T20N R20E S 9 S 10 S 16 S 15 1967
		Raise a mound of stone W. of the cor.
		Land, gently rolling and badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	-	From the cor. of secs. 10, 11, 14 and 15.
		N. 89°53' W., bet. secs. 10 and 15.
		Over gently rolling land.
	2.40	Wash, 15 1ks. wide, 2 ft. deep, drains N. 75° E.
	12.20	Cor. of fences, bears South, 10 1ks. dist., fences bear S. and S. 70° W.
	39.10	Wash, 10 1ks. wide, 3 ft. deep, drains N. 45° E.
	40.00	Point for the ½ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
		Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
		T20N R20E
		S 10 S 15 1967
	İ	

)	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
	chains 51.80	Fence, bears S. 5° E. and N. 5° W.
,	60.00	Point for the W 1/16 sec. cor. of secs. 10 and 15. This corner is not monumented.
	62.10	Track road, bears N. and S.
	71.50	Wash, 30 1ks. wide, 3 ft. deep, drains N. 45° E.
	80.00	The cor. of secs. 9, 10, 15 and 16.
		Land, nearly level to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
	·	N. 0°50' E., bet. secs. 9 and 10.
		Over rolling badlands.
	18.80	Wash, 15 lks. wide, 3 ft. deep, drains N. 45° W.
	20.09	Point for the S 1/16 sec. cor. of secs. 9 and 10.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T20N R20E S 1/16 S 9 S 10 1967
		Raise a mound of stone W. of the cor.
	20.30	Leave badlands; thence over nearly level land.
	26.50	Wash, 10 1ks. wide, 3 ft. deep, drains W.
	36.40	Track road, bears S. 40° E. and N. 40° W.
	40.18	Point for the ½ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	43.90	Track road, bears E. and W.
	75.20	Fence, bears N. 80° E. and S. 80° W.
	76.60	Wash, 30 1ks. wide, 5 ft. deep, drains N. 45° W.
	80.36	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		Land, rolling badlands and nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		From the point for the cor. of secs. 2, 3, 10 and 11.
		N. 89°56' W., bet. secs. 3 and 10.
		Over nearly level land.
	2.50	Wash, 90 lks. wide, 5 ft. deep, drains N. 45° W.

Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.

	Dep. Res., Bubatvisional Bines, 1. 20 N., R. 20 L.
CHAINS 9.30	Track road, bears N. 45° E. and S. 45° W.
19.10	Wash, 5 1ks. wide, 4 ft. deep, drains N.
	Wash, 1.00 ch. wide, 6 ft. deep, drains N. 45° W.
27.00	
40.09	Point for the ½ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
62.40	Wash, 15 lks. wide, 6 ft. deep, drains N.
72.90	Fence, bears N. and S.; a cor. of fences bears South, 3.25 chs. dist.; fences bear N., S. and W.
77.50	Wash, 10 1ks. wide, 4 ft. deep, drains N. 30° W.
80.18	The point for the cor. of secs. 3, 4, 9 and 10.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
	N. 0°46' E., bet. secs. 3 and 4.
	Over nearly level land.
5.00	Wash, 2.00 chs. wide, 10 ft. deep, drains W.
40.17	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
49.80	Wash, 80 1ks. wide, 2 ft. deep, drains W., curving S. 45° W.
69.80	Wash, 50 lks. wide, 10 ft. deep, drains S. 45° W.
76.90	Wash, 30 1ks. wide, 7 ft. deep, drains S. 20° E.
78.84	Fence, bears E. and W.
80.62	Intersect the Fifth Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance. This corner point is monumented with a local $\frac{3}{4}$ in. iron pipe and is not remonumented.
	from which
	The Stan. cor. of secs. 33 and 34, T. 21 N., R. 20 E., bears S. 89°59' E., 5.85 chs. dist., monumented by an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.
	Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.

Dep. Res., Subdivisional Lines, T. 20 N., R. 20	Dep.	Res.,	Subdivisional	Lines.	Т.	20	Ν.,	R.	20	F
---	------	-------	---------------	--------	----	----	-----	----	----	---

		bep. Res., Subdivisional Lines, 1. 20 N., R. 20 E.
CI	HAINS	N. 0°54' E., bet. secs. 32 and 33.
		Over gently rolling land.
	2.30	Wash, 15 1ks. wide, 2 ft. deep, drains N. 45° W.
4	0.14	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
5	2.60	Wash, 10 1ks. wide, 2 ft. deep, drains W.
7	5.30	Wash, 30 1ks. wide, 6 ft. deep, drains W.
8	0.28	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		From the point for the cor. of secs. 27, 28, 33 and 34.
		N. 89°43' W., bet. secs. 28 and 33.
		Over gently rolling land.
41	0.01	Point for the ½ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
53	3.20	Enter gently rolling badlands.
69	9.50	Wash, 5 lks. wide, 5 ft. deep, drains SW.
80	0.02	The point for the cor. of secs. 28, 29, 32 and 33.
		Land, gently rolling to badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		N. 0°56' E., bet. secs. 28 and 29.
		Over gently rolling badlands.
20	0.00	Wash, 3 1ks. wide, 2 ft. deep, drains W.
24	4.30	Wash, 5 1ks. wide, 3 ft. deep, drains S. 45° W.
37	7.70	Leave gently rolling badlands; thence over gently rolling land.
4(0.14	Point for the ½ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
44	4.40	Enter gently rolling badlands.
60	0.21	Point for the N $1/16$ sec. cor. of secs. 28 and 29.

Dep. R	es., S	Subdivisional	Lines,	Τ.	20	Ν.,	R.	20	Ε.
--------	--------	---------------	--------	----	----	-----	----	----	----

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS	Set the iron post 18 ins. in the ground, brass cap mkd.
	T20N R20E N 1/16 S 29 S 28 1967
	Raise a mound of stone W. of the cor.
72.40	Wash, 10 1ks. wide, 2 ft. deep, drains N. 45° W.
80.28	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	T2 ON R2 OE S 20 S 21 S 29 S 28 1967
	Land, gently rolling badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	From the point for the cor. of sec. 21, 22, 27 and 28.
	N. 89°46' W., bet. secs. 21 and 28.
	Over gently rolling land.
27.80	Bottom of swale, drains N.
40.06	Point for the ½ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E 2 S 21 3 28 1967
	Deposit glass in hole.
68.70	Deposit glass in hole. Enter rolling badlands.
68.70 80.12	
	Enter rolling badlands.
	Enter rolling badlands. The cor. of secs. 20, 21, 28 and 29. Land, gently rolling to badlands. Soil, sandy, clay loam. Timber, none.
	Enter rolling badlands. The cor. of secs. 20, 21, 28 and 29. Land, gently rolling to badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	Enter rolling badlands. The cor. of secs. 20, 21, 28 and 29. Land, gently rolling to badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass. N. 0°54' E., bet. secs. 20 and 21.
80.12	Enter rolling badlands. The cor. of secs. 20, 21, 28 and 29. Land, gently rolling to badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass. N. 0°54' E., bet. secs. 20 and 21. Over rolling badlands.

 	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS	Set the iron post 18 ins. in the ground, brass cap mkd.
	T20N R20E S 1/16
	S 20 S 21 1967
	Deposit glass in hole.
35.20	Track road, bears N. 50° E. and S. 50° W.
38.30	Wash, 10 1ks. wide, 3 ft. deep, drains W.
40.14	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T2ON R2OE
	s 20 s 21 1967
	from which
	A stock pond bears N. 45°45' E., 12.90 chs. dist.
:	Deposit glass in hole.
46.90	Wash, 40 lks. wide, 4 ft. deep, drains W.
76.20	Enter rolling badlands.
80.28	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T2 ON R2 OE S 17 S 16 S 20 S 21 1967
	Raise a mound of stone W. of the cor.
	Land, gently rolling and badlands. Soil, sandy, clay loam. Timber, none.
i	Undergrowth, bunch grass.
	From the point for the cor. of secs. 15, 16, 21 and 22.
	N. 89°50' W., bet. secs. 16 and 21.
	Over gently rolling land.
40.06	Point for the ½ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
51.90	Wash, 30 1ks. wide, 3 ft. deep, drains S.
57.20	Enter rolling badlands.
80.12	The cor. of secs. 16, 17, 20 and 21.

Dep.	Res	Subdivisional	Lines,	Τ.	20 N.	, R.	20	Ε.

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS	Land, gently rolling and badlands. Soil, sandy, clay loam. Timber, none.
	Undergrowth, bunch grass.
	N. 0 ⁶ 49' E., bet. secs. 16 and 17.
	Over rough and rolling land.
27.70	Draw, drains S. 45° W.
33.60	Top of spur, slopes S. 45° W.
36.70	Draw, drains S. 45° W.
40.14	Point for the ½ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
42.90	Top of spur, slopes S. 45° W.
52.80	Draw, drains W.
80.28	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	T20N R20E S 8 S 9
	S 17 S 16 1967
	from which
	U.S.G.S Triangulation Station "Asylum", bears S. 21°04'40" E., 21.47 chs. dist.
	Land, rough and rolling.
	Soil, rocky, sandy loam. Timber, none.
	Undergrowth, bunch grass.
,	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°53' W., bet. secs. 9 and 16.
~	Over rough and rolling land.
12.10	Top of clay spur, slopes N.
17.60	Wash, 10 1ks. wide, 3 ft. deep, drains N. 20° E.
26.20	Top of clay spur, slopes N. 30° E.
34.40	Wash, 10 lks. wide, 3 ft. deep, drains N. 45° E.
40.13	Point for the 4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
69.60	Top of spur, slopes N.
	l l
78.70	Draw, drains N. 45° W.

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS 80.26	The cor. of secs. 8, 9, 16 and 17.
	Land, heavy rolling. Soil, rocky, clay loam.
	Timber, none. Undergrowth, bunch grass.
	N. 0°58' E., bet. secs. 8 and 9.
	Over heavy rolling land.
3.70	Draw, drains W.
6.80	Top of hill on ridge, bears E. and W.
16.20	Draw, drains N. 20° W.
32.20	Enter gently rolling land.
40.14	Point for the ½ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T20N R20E
	S 8 S 9 1967
	Raise a mound of stone W. of the cor.
51.20	Top of dike, bears S. 40° E. for 1.00 ch. to a small earthen dam.
53.50	Center of stock pond, 3.00 chs. in diam.
62.40	Track road, bears E. and W.
67.90	Fence, bears E. and W.
73.30	Left bank of Wash, 5 ft. high, bears E. and W.
80.28	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	from which
	A windmill, bears S. 64°19' E., 25.70 chs. dist.
	Land, heavy rolling to gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 3, 4, 9 and 10.
	N. 89°57' W., bet. secs. 4 and 9.
	Over nearly level land.
2.00	Enter wash area draining westerly.
12.00	Leave wash area draining northwesterly.
	1

Dep. Res	s., Subdivisional	Lines, T.	20 N.,	R. 2	20 E.

	chains 17.80	Wash, 60 1ks. wide, 3 ft. deep, drains S. 45° W.	
	23.60	Wash, 60 1ks. wide, 5 ft. deep, drains S.	
•	40.00	Point for the ½ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.	
	40.05	Right bank of wash, 5 ft. high, bears S. 30° E. and irregularly W., thence over wash area.	
	59.60	Right bank of wash, 5 ft. high, bears irregularly E. and S. 45° W.	
	76.40	Right bank of wash, 6 ft. high, bears S. 45° E. and irregularly N. 70° W., thence over wash area.	
	77.00	Wash, 1.20 chs. wide, 3 ft. deep, drains N. 80° W.	
	80.00	The point for the cor. of secs. 4, 5, 8 and 9.	
		Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and willows along wash area.	
		N. 0°31' E., bet. secs. 4 and 5.	
		Over gently rolling land.	
	1.10	Right bank of wash, 10 ft. high, bears S. 80° E. and N. 80° W., for 3.00 chs., thence curving S. 45° W.	
	11.10	Wash, 10 1ks. wide, 3 ft. deep, drains W.	
	12.40	Wash, 10 1ks. wide, 3 ft. deep, drains S. 45° W.	
	12.60	Fence, bears N. 80° E. and S. 80° W.	
	40.14	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.	
	45.00	Center of Indian open site occupation area, bears West, 1.50 chs. dist., contains "flint" flakes and chips, sherds and scattered stones, on top of mesa bearing N. 45° E. and S. 45° W.	
	78.60	Fence, bears E. and W.	
	80.54	Intersect the Fifth Standard Parallel North.	
		Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.	
		from which	
		The Stan. cor. of secs. 32 and 33, T. 21 N., R. 20 E., bears S. 89°59' E., 6.19 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.	

Dep. Res., Subdivisional Lines, T. 20 N , R. 20 E.

	bep. kes., Subdivisional Lines, 1. 20 N , K. 20 E.
CHAINS	Land, gently rolling. Soil, sandy loam.
	Timber, none Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy.
	of the Tp. N. 0°46' E , bet. secs. 31 and 32.
	Over gently rolling land.
11.00	Wash, 25 1ks. wide, 6 ft. deep, drains N. 45° W.
16.00	Enter rolling land.
40.09	Point for the ½ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
80.18	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Land, gently rolling to rolling Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 28, 29, 32 and 33.
	N. 89°44' W., bet. secs. 29 and 32.
	Over gently rolling badlands.
13.20	Wash, 10 1ks. wide, 2 ft. deep, drains S.
18.60	Wash, 40 1ks. wide, 5 ft. deep, drains N. 45° W., curving W.
25.00	Wash, 20 1ks. wide, 3 ft. deep, drains N.
31.30	Wash, 70 1ks. wide, 3 ft. deep, drains S. 80° W.
35.70	Wash, 50 1ks. wide, 5 ft. deep, drains N.
39.97	Point for the ½ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
67.20	Wash, 10 1ks. wide, 2 ft. deep, drains N. 45° E.
69.60	Wash, 30 1ks. wide, 2 ft. deep, drains N. 20° E.
79.94	The point for the cor. of secs. 29, 30, 31 and 32.
,	Land, gently rolling badlands Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 89°45' W., bet. secs. 30 and 31.
	Over gently rolling badlands.

Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.

		Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
	CHAINS	VI 1 00 11 1 1 0 C. I I I I I V
	13.70	Wash, 20 1ks. wide, 2 ft. deep, drains N.
•	15.30	Navaho Indian Hogan (circular and in fair shape), bears South, 2.50 chs. dist.
~	39.95	Point for the ½ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.
•		Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
^		T20N R20E
		½ S 30 S 31
		1967
	59.93	Point for the W 1/16 sec. cor. of secs. 30 and 31.
		Set the iron post 20 ins. in the ground, brass cap mkd.
-		T20N R20E
		$\begin{array}{c} W \ 1/16 \ \frac{S}{S} \frac{30}{967} \\ \end{array}$
		Deposit glass in hole.
	66.80	Fence, bears N. and S.
	86.02	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.
		Land, gently rolling badlands. Soil, sandy clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		From the point for the cor. of secs. 29, 30, 31 and 32.
		N. 0°52' E., bet. secs. 29 and 30.
		Over gently rolling land.
	19.90	Wash, 1.00 ch. wide, 4 ft. deep, drains S. 45° W.
	40.09	Point for the ½ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.
_		Set the iron post 22 ins. in the ground, brass cap mkd.
		T20N R20E
,		s 30 s 29 1967
		Deposit glass in hole.
	80.18	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T20N R20E S 19 S 20 S 30 S 29 1967

Dep.	Res.,	Subdivisional	Lines,	Τ.	20	Ν.,	R.	20	Ε.
------	-------	---------------	--------	----	----	-----	----	----	----

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS	Deposit glass in hole.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°48' W., bet. secs. 20 and 29.
	Over gently rolling badlands.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E 1 S 20 2 S 29 1967
	Deposit glass in hole.
80.04	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	N. 89°53' W., bet. secs. 19 and 30.
	Over gently rolling land.
35.50	Wash, 2.40 chs. wide, 3 ft. deep, drains N.
39.99	Point for the $\frac{1}{4}$ sec. cor. of sec. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T20N R20E 3 19
	Deposit glass in hole.
59.99	Point for the W 1/16 sec. cor. of secs. 19 and 30. This corner is not monumented.
68.25	Fence, bears N. and S.
85.98	The point for the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
CHAINS	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°46' E., bet. secs. 19 and 20.
	Over nearly level land.
20.04	Point for the S 1/16 sec. cor. of secs. 19 and 20.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E S 1/16 S 19 S 20 1967
	Deposit glass in hole.
40.08	Point for the ½ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
42.90	Track road, bears E. and W.
61.40	Wash, 10 1ks. wide, 2 ft. deep, drains N. 70° W.
72.60	Wash, 10 1ks. wide, 3 ft. deep, drains W.
77.30	Wash, 1.00 ch. wide, 3 ft. deep, drains N. 50° W.
80.16	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the cor. of sec. 16, 17, 20 and 21.
	N. 89°51' W., bet. secs. 17 and 20.
	Over rolling badlands.
7.40	Leave badlands; thence over nearly level land.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T20N R20E \$\frac{1}{4} \frac{\text{S} \frac{17}{\text{S} \frac{20}{1967}}}{1967}
60.12	Point for the W $1/16$ sec. cor. of secs. 17 and 20.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T20N R20E
	W 1/16 S 17 S 20 1967

Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.

		Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
	CHAINS 80.16	The point for the cor. of secs. 17, 18, 19 and 20.
		Land, rolling badlands and nearly level. Soil, sandy, clay loam. Timber, none.
		Undergrowth, bunch grass and sagebrush.
		N. 89°59' W., bet. secs. 18 and 19.
		Over nearly level land.
	13.30	Wash, 40 1ks. wide, 3 ft. deep, drains N. 45° W.
	40.01	Point for the ½ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	62.30	Wash, 2.60 chs. wide, 3 ft. deep, drains N.
	69.60	Fence, bears N. and S.
	85.90	The point for the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.
		Land, nearly level. Soil, sandy loam.
		Timber, none. Undergrowth, bunch grass.
		From the point for the cor. of secs. 17, 18, 19 and 20.
		N. 0°53' E., bet. secs. 17 and 18.
		Over nearly level land.
	40.09	Point for the ½ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	80.18	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		Land, nearly level.
		Soil, sandy loam. Timber, none
		Undergrowth, bunch grass and sagebrush.
		From the cor. of secs. 8, 9, 16 and 17.
		N. 89°53' W., bet. secs. 8 and 17.
		Over rough and rolling land.
	6.60	Draw, drains N. 45° W.
	9.60	Draw, drains N. 45° W.
	14.80	Top of spur, slopes N. 60° W.
	19.70	Draw, drains N.
	27.50	Top of spur, slopes N. 75° W.
t		ı l

Dep. Res	., Subdivisional	Lines, T.	20 N.,	R. 20) E.
----------	------------------	-----------	--------	-------	------

CHAINS 40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T20N R20E
	$\frac{1}{4} \frac{\text{S}}{\text{S}} \frac{8}{17}$
	1967
	Raise a mound of stone N. of the cor.
50.60	Leave rough and rolling land; thence over nearly level land.
60.00	Point for the W 1/16 sec. cor. of secs. 8 and 17.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E
	W 1/16 <u>S 8</u> 5 17
	1967
	Raise a mound of stone N. of the cor.
80.00	The point for the cor. of secs. 7, 8, 17 and 18.
	Land, rough and rolling to nearly level. Soil, rocky, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	S. 89°56' W., bet. secs. 7 and 18.
	Over nearly level land.
15.70	Wash, 20 1ks. wide, 3 ft. deep, drains N.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
55.40	Wash, 2.00 chs. wide, 7 ft. deep, drains N. 5° E.
71.10	Fence, bears N. and S.
84.90	Track road, bears N. and S.
85.93	The point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	Land, nearly level.
	Soil, sandy loam. Timber, none.
	Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 7, 8, 17 and 18.
	N. 0°51' E., bet. secs. 7 and 8.
	Over nearly level land.
5.80	Wash, 70 1ks. wide, 2 ft. deep, drains N. 75° W.
3,00	,

36

	Dep. Res., Subdivisional Lines, T. 20 N., R. 20 E.
20.04	Point for the S 1/16 sec. cor. of secs. 7 and 8. This corner is not monumented.
27.10	Wash, 5 1ks. wide, 2 ft. deep, drains W.
40.08	Point for the ½ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
59.20	Track road, bears E. and W., curving S. 15° W.
59.50	Fence, bears N. 15° E. and S. 15° W.
70.60	Wash, 70 lks. wide, 5 ft. deep, drains N. 45° W., curving S. 45° W.
77.00	Fence, bears E. and W.
80.16	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the cor. of secs. 4, 5, 8 and 9.
	N. 89°56' W., bet. secs. 5 and 8.
	Over gently rolling land.
4.90	Wash, 1.20 chs. wide, 3 ft. deep, drains S. 45° W.
16.10	Wash, 40 lks. wide, 9 ft. deep, drains S. 80° W.
20.20	Wash, 40 lks. wide, 9 ft. deep, drains N. 20° W.
26.00	Wash, 40 lks. wide, 9 ft. deep, drains S. 70° W.
37.90	Fence, bears N. 70° E. and S. 70° W.
39.00	Wash, 25 1ks. wide, 6 ft. deep, drains S. 40° E.
40.03	Point for the ½ sec. cor. of sec. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
73.70	Wash, 30 lks. wide, 8 ft. deep, drains S.
80.06	The point for the cor. of secs. 5, 6, 7 and 8.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	S. 89°52' W., bet. secs. 6 and 7.
	Over gently rolling land.
40.09	Point for the ½ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.

Dep.	Res.,	Subdivisional	Lines,	т.	20.,	R.	20	Ε.
DCP.	1100.,	0 0.2 0.2	•					

		- 1
сн. 44	.20	Track road, bears N. 80° E. and S. 80° W.
72	.64	Fence, bears N. and S., and cor. of fences bears South, 21 1ks. dist., fences bear N., S. 45° E. and W.
77	.70	Wash, 20 1ks. wide, 5 ft. deep, drains S.
85	.91	The point for the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
		Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		From the point for the cor. of secs. 5, 6, 7 and 8.
		N. 0°20' E., bet. sees. 5 and 6.
		Over gently rolling land.
16	.10	Dim track road, bears E. and W.
40	0.09	Point for the ½ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
54	.00	Top of mesa, bears N. 45° E. and S. 45° W.
78	8.85	Fence, bears E. and W.
80	.42	Intersect the Fifth Standard Parallel North.
		Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. This corner is not monumented.
		from which
		The standard cor. of secs. 31 and 32, T. 21 N., R. 20 E., bears N. 89°37' E., 6.52 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.
		Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
		Point for the $\frac{1}{4}$ sec. cor. of sec. 6 is at proportionate distance and on the N. bdy. of the Tp.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		表 6 T20N R20E 1967

from which

The true point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 21 N., R. 20 E., bears N. 89°37' E., 6.52 chs. dist. The standard $\frac{1}{4}$ sec. cor. is witnessed N. 89°37' E., 1.00 ch. dist. from the true point, by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1947.

Deposit glass in hole.

<u> </u>	Survey, Subdivision Section 6, T. 20 N., R. 20 E.
CHAINS	From the point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	N. $0^{\circ}28'$ E., on the N. and S. center line of sec. 6.
	Over gently rolling land.
10.00	Enter rolling land.
27.00	Top of mesa, bears N. 45° E. and S. 45° W.
30.70	Wash, 10 1ks. wide, 3 ft. deep, drains S. 70° W.
40.08	Point for the C ½ sec. cor. of sec. 6.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T20N R20E C社 S6 1967
46.00	Enter nearly level land.
78.49	Fence, bears E. and W.
80.31	The ½ sec. cor. of sec. 6 on the N. bdy. of the Tp.
	Land, gently rolling, rolling and nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	S. 89°50' W., on the E. and W. center line of sec. 6.
	Over nearly level land.
3.00	Enter rolling land.
15.20	Wash, 10 lks. wide, 2 ft. deep, drains S.
32.20	Top of mesa, bears N. 45° E. and S. 45° W.
39.99	The C ½ sec. cor. of sec. 6.
41.80	Enter nearly level land.
72.40	Wash, 10 1ks. wide, 3 ft. deep, drains S.
73.10	Fence, bears N. and S.
85.56	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6 on the W. bdy. of the Tp
	Land, nearly level to rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.

Survey, Subdivision Section 8, T. 20 N., R. CHAINS From the 4 sec. cor. of secs. 8 and 17. N. 0°55' E., on the N. and S. center line of second N. slope of mesa. 4.20 Bottom of descent; thence over nearly level large 20.06 Point for the C-S 1/16 sec. cor. of sec. 8. Set the iron post 20 ins. in the ground, brass T20N R20E C S 1/16 S 8 C 1967	
Descend N. slope of mesa. 4.20 Bottom of descent; thence over nearly level lar 20.06 Point for the C-S 1/16 sec. cor. of sec. 8. Set the iron post 20 ins. in the ground, brass T20N R20E S 1/16 S 8 C	ec. 8.
4.20 Bottom of descent; thence over nearly level lar 20.06 Point for the C-S 1/16 sec. cor. of sec. 8. Set the iron post 20 ins. in the ground, brass T20N R20E S 1/16 S 8 C	
Point for the C-S 1/16 sec. cor. of sec. 8. Set the iron post 20 ins. in the ground, brass	
Set the iron post 20 ins. in the ground, brass T20N R20E C S 1/16 S 8 C	nd.
Set the iron post 20 ins. in the ground, brass T20N R20E C S 1/16 S 8 C	
S 1/16 S 8 C	cap mkd.
Ċ	
1967	
Raise a mound of stone W. of the cor.	
37.80 Wash, 60 1ks. wide, 3 ft. deep, drains S. 80° V	٧.
40.12 Point for the C ½ sec. cor. of sec. 8.	
Set the iron post 16 ins. in the ground, mound to top, brass cap mkd.	of stone
T2ON R2OE	
C ¹ ₄ — S 8	
56.80 Track road, bears E. and W.	
63.77 Fence, bears E. and W.	
69.50 Wash, 1.00 ch. wide, 15 ft. deep, drains S. 80	°W.
73.30 Wash, 40 1ks. wide, 9 ft. deep, drains W.	
76.10 Wash, 40 1ks. wide, 7 ft. deep, drains W.	
79.50 Fence, bears E. and W.	
80.22 The point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8	
Land, nearly level.	
Soil, sandy loam. Timber, none.	
Undergrowth, bunch grass and sagebrush.	
From the ½ sec. cor. of secs. 8 and 9.	
N. 89°52' W., on the E. and W. center line of	sec. 8.
Over nearly level land.	
36.60 Wash, 30 lks. wide, 3 ft. deep, drains S. 80°	w -
39.96 The C ½ sec. cor. of sec. 8. 59.99 Point for the C-W 1/16 sec. cor. of sec. 8. T	his corner
is not monumented.	
80.02 The point for the ½ sec. cor. of secs. 7 and 8	
Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunch grass and sagebrush.	

 	Survey, Subdivision Section 10, T. 20 N., R. 20 E.
CHAINS	Subdivision, SW4, Sec. 8
	From the W 1/16 sec. cor. of secs. 8 and 17.
	N. 0°53' E., on the N. and S. center line of the SW_4^1 of sec. 8.
	Over nearly level land.
19.20	Wash, 5 1ks. wide, 3 ft. deep, drains N. 10° W.
20.05	Point for the SW 1/16 sec. cor. of sec. 8.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T2ON R2OE
	SW 1/16 — S 8 1967
	Set a wooden post 3 ins. diam., 3 ft. long, alongside the cor.
23.80	Wash, 5 1ks. wide, 2 ft. deep, drains N. 80° W.
26.50	Wash, 30 1ks. wide, 3 ft. deep, drains W.
32.00	Wash, 20 1ks. wide, 2 ft. deep, drains S. 80° W.
40.10	The point for the C-W 1/16 sec cor. of sec. 8.
	From the C-S 1/16 sec. cor. of sec. 8.
	N. 89°52' W., on the E. and W. center line of the SW4 of sec. 8.
	Over nearly level land.
20.04	The SW 1/16 sec. cor. of sec. 8.
22.00	Wash, 5 1ks. wide, 3 ft. deep, drains N.
40.08	The point for the S 1/16 secs cor. of secs. 7 and 8.
	Survey, Subdivision Section 10, T. 20 N., R. 20 E.
	From the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	N. 0°53' E., on the N. and S. center line of sec. 10.
	Over nearly level land.
20.10	Point for the C-S 1/16 sec. cor. of sec. 10. This corner is not monumented.
40.20	Point for the C ½ sec. cor. of sec. 10.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T20N R20E C坛+S10 1967
49.07	Track road, bears E. and W.
80.40	The point for the ½ sec. cor. of secs. 3 and 10.

Survey,	Subdivision	Section	10,	T.	20	Ν.,	<u>R.</u>	20	E.	_
										-

		Survey, Subdivision Section 10, T. 20 N., R. 20 E.
•	CHAINS	Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
• ~		From the ½ sec. cor. of secs. 10 and 11.
•		N. 89°54' W., on the E. and W. center line of sec. 10.
*		Over nearly level land.
	30.50	Diversion Dam, bears S. 45° E. and N. 45° W.
•	34.00	Wash, 10 1ks. wide, 2 ft. deep, drains N. 45° W.
	40.03	The C ½ sec. cor. of sec. 10.
	60.05	Point for the C-W 1/16 sec. cor. of sec. 10.
	00.03	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
		T20N R20E C W 1/16 S10 1967
	80.07	The point for the ½ sec. cor. of secs. 9 and 10.
		Land, nearly level. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		Subdivision, SW4, Sec. 10
		From the point for the W 1/16 sec. cor. of secs. 10 and 15.
		N. 0°53' E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 10.
		Over nearly level land.
•	20.07	Point for the SW 1/16 sec. cor. of sec. 10.
•		Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
		T20N R20E SW 1/16+S 10 1967
•	26.80	Fence, bears S. 5° E. and N. 5° W.
	40.17	The C-W 1/16 sec. cor. of sec. 10.
		From the point for the C-S 1/16 sec. cor. of sec. 10.
		N. 89°55' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 10.
		Over nearly level land.
	17.60	Fence, bears S. 5° E. and N. 5° W.

Survey, Subdivis	ston Section	14, 1	. 20	14.,	к.	2.0	Ŀ.

 	Burvey, Bubarvision Beetion 12, 1. 20 N., R. 20 H.
CHAINS	
20.03	The SW 1/16 sec. cor. of sec. 10.
30.40	Track road, bears N. 20° E. and S. 35° E.
40.07	The S 1/16 sec. cor. of secs. 9 and 10.
	Survey, Subdivision Section 12, T. 20 N., R. 20 E.
	From the ½ sec. cor. of secs. 12 and 13.
	N. 1°02' E., on the N. and S. center line of sec. 12.
	Over gently rolling land.
3.90	Wash, 25 1ks. wide, 2 ft. deep, drains W.
40.26	Point for the C ½ sec. cor. of sec. 12. This corner is not monumented.
42.40	Wash, 10 1ks. wide, 2 ft. deep, drains W.
60.40	Point for the C-N 1/16 sec. cor. of sec. 12.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T20N R20E
	C N 1/16 S 12
	C 1967
	Set a wooden post, 3 ins. in diam., 3 ft. long, alongside the cor.
76.90	Wash, 20 1ks. wide, 2 ft. deep, drains W.
80.54	The ½ sec. cor. of secs. 1 and 12.
,	Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	From the ½ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.
	N. 89°55' W., on the E. and W. center line of sec. 12.
	Over gently rolling land.
5.74	Fence, bears N. and S.
40.16	The point for the C $\frac{1}{4}$ sec. cor. of sec. 12.
46.30	Wash, 10 1ks. wide, 2 ft. deep, drains S. 45° W.
53.60	Wash, 10 1ks. wide, 2 ft. deep, drains N. 75° W.

CHAIN	
61.3	Track road, bears S. 10° E. and N. 10° W.
80.2	The ½ sec. cor. of secs. 11 and 12.
A.*	Land, gently rolling. Soil, sandy, clay loam.
•	Timber, none.
	Undergrowth, bunch grass and sagebrush.
	Subdivision, NW4, Sec. 12
	From the G-N 1/16 sec. cor. of sec. 12.
	N. $89^{\circ}55'$ W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 12.
	Over gently rolling land.
25.7	O Track road, bears N. and S.
40.1	6 The N 1/16 sec. cor. of secs. 11 and 12.
	Survey, Subdivision Section 14, T. 20 N., R. 20 E.
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	N. $0^{\circ}57$ E., on the N. and S. center line of sec. 14.
	Over gently rolling land.
4.3	Wash, 10 1ks. wide, 2 ft. deep, drains N. 45° W.
12.0	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.
20.1	Point for the C-S 1/16 sec. cor. of sec. 14. This corner is not monumented.
40.2	Point for the C ½ sec. cor. of sec. 14. This corner is not monumented.
68.2	Wash, 60 lks. wide, 3 ft. deep, drains N. 20° E.
. 80.4	The point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.
	Land, gently rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	N. 89°48' W., on the E. and W. center line of sec. 14.
	Over gently rolling land.
20.0	O Point for the C-E 1/16 sec. cor. of sec. 14. This corner is not monumented.
40.0	The point for the C な sec. cor. of sec. 14.
	1

Survey, Subdivision	Section	20,	Τ.	20	Ν.,	R.	20	Ε.
---------------------	---------	-----	----	----	-----	----	----	----

	Survey, Subdivision Section 20, T. 20 N., R. 20 E.
chains 80.06	The point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	Land, gently rolling.
	Soil, sandy, clay loam. Timber, none.
	Undergrowth, bunch grass.
	Subdivision, SE4, Sec. 14
	From the E 1/16 sec. cor. of secs. 14 and 23.
	N. 0°58' E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 14.
	Over gently rolling land.
20.11	Point for the SE 1/16 sec. cor. of sec. 14.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T2ON R2OE
	SE 1/16+S 14 1967
	Raise a mound of stone W. of the cor.
40.22	The point for the C-E 1/16 sec. cor. of sec. 14.
	From the S 1/16 sec. cor. of secs. 13 and 14.
	N. $89^{\circ}48'$ W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 14.
	Over gently rolling land.
19.99	The SE 1/16 sec. cor. of sec. 14.
39.99	The point for the C-S 1/16 sec. cor. of sec. 14.
	Survey, Subdivision Section 20, T. 20 N., R. 20 E.
	From the 4 sec. cor. of secs. 20 and 29.
	N. 0°51' E., on the N. and S. center line of sec. 20.
	Over gently rolling land through scattered badlands.
1.40	Wash, 15 1ks. wide, 3 ft. deep, drains N. 10° W.
20.05	Point for the C-S 1/16 sec. cor. of sec. 20.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E
	S 1/16 S 20
	1967
	Deposit glass in hole.
40.10	Point for the C ½ sec. cor. of sec. 20.

Survey,	Subdivision	Section	20,	Τ.	20 N	., R.	20	Ε.
---------	-------------	---------	-----	----	------	-------	----	----

	:	Survey, Subdivision Section 20, 1. 20 N., R. 20 E.
	CHAINS	Set the iron post 19 ins. in the ground, brass cap mkd.
		T2ON R2OE
,		C½+S20 1967
÷		Deposit glass in hole.
		Continue over gently rolling land, leaving badlands.
,	41.85	Track road, bears S. 70° E. and W.
_	51.00	Wash, 5 1ks. wide, 2 ft. deep, drains N. 30° W.
	55.50	Wash, 50 lks. wide, 5 ft. deep, drains N. 45° W.
	80.24	The ½ sec. cor. of secs. 17 and 20.
		Land, gently rolling and scattered badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		From the 4 sec. cor. of secs. 20 and 21.
•		N. 89°49' W., on the E. and W. center line of sec. 20.
		Over gently rolling land.
	4.30	Wash, 10 1ks. wide, 4 ft. deep, drains N. 80° W.
	6.20	Wash, 20 1ks. wide, 4 ft. deep, drains N.
•	35.30	Track road, bears S. 70° E. and N. 70° W.
	40.02	The C ½ sec. cor. of sec. 20.
	60.04	Point for the C-W 1/16 sec. cor. of sec. 20.
	00.04	Set the iron post 18 ins. in the ground, brass cap mkd.
		T20N R20E C W 1/16 S 20 1967
•		Deposit glass in hole.
٥		Thence over scattered badlands.
٧	80.06	The point for the ½ sec. cor. of secs. 19 and 20.
		Land, gently rolling and scattered badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass.
		Subdivision, SE ¹ ₄ , Sec. 20
		From the S 1/16 sec. cor. of secs. 20 and 21.
		N. 89°49' W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 20.
		Over gently rolling land.
	40.02	The C-S 1/16 sec. cor. of sec. 20

Survey, Subdivision Section 28, T. 20 N., R. 20 E.

	Survey, Subdivision Section 28, T. 20 N., R. 20 E.
CHAINS	Subdivision, SW4, Sec. 20
	From the C-S 1/16 sec. cor. of sec. 20.
	N. 89°50' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 20.
	Over gently rolling land.
8.00	Enter gently rolling badlands.
31.60	Leave gently rolling badlands; thence over gently rolling land.
40.02	The S 1/16 sec. cor. of secs. 19 and 20.
	Subdivision, NW女, Sec. 20
	From the C-W 1/16 sec. cor. of sec. 20.
	N. 0°48' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 20.
	Over gently rolling land.
3.20	Track road, bears E. and W.
24.00	Wash, 50 lks. wide, 4 ft. deep, drains N. 80° W.
40.11	The W 1/16 sec. cor. of secs. 17 and 20.
	Survey, Subdivision Section 28, T. 20 N., R. 20 E.
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.
	N. $0^{\circ}57$ E., on the N. and S. center line of sec. 28.
	Over gently rolling land.
40.15	Point for the C $\frac{1}{4}$ sec. cor. of sec. 20. This corner is not monumented.
60.24	Point for the C-N 1/16 sec. cor. of sec. 20.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T20N R20E
	C N 1/16 S 20 C 1967
	from which
	Indian open site, occupation area, bears West, 50 lks. dist., contains "flint" flakes and chips, sherds and scattered stones.
80.33	The $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
·	Land, gently rolling. Soil, sandy loam.
	Timber, none. Undergrowth, bunch grass.
}	

Survey,	Subdivision	Section	30,	Τ.	20	Ν.,	R.	20	Ε.
---------	-------------	---------	-----	----	----	-----	----	----	----

		Survey, Subdivision Section 30, T. 20 N., R. 20 E.
	CHAINS	From the point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
		N. 89°45' W., on the E. and W. center line of sec. 28.
•		Over gently rolling land.
•	40.06	The point for the C ½ sec. cor. of sec. 28.
	80.10	The point for the ½ sec. cor. of secs. 28 and 29.
-		Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass.
		Subdivision, NW4, Sec. 28
		From the C-N 1/16 sec. cor. of sec. 28.
		N. 89°46' W., on the E. and W. center line of the NW $\frac{1}{4}$ sec. 28.
		Over gently rolling land.
	0.50 24.00 36.00	Indian ruins, hereinbefore described. Wash, 50 lks. wide, 4 ft. deep, drains N. 80° W. Leave gently rolling land; thence over rolling badlands.
	40.04	The N 1/16 sec. cor. of secs. 28 and 29.
		Survey, Subdivision Section 30, T. 20 N., R. 20 E.
		From the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.
		N. 0°50' E., on the N. and S. center line of sec. 30.
		Over rolling badlands.
	14.00	Leave badlands; thence over gently rolling land.
	20.01	Point for the C-S 1/16 sec. cor. of sec. 30.
•		Set the iron post 22 ins. in the ground, brass cap mkd.
•		T2ON R2OE Ç
		S 1/16 S 30 C 1967
		Deposit glass in hole.
	40.02	Point for the C ½ sec. cor. of sec. 30.
		Set the iron post 22 ins. in the ground, brass cap mkd.
	·	T20N R20E C 4+S 30 1967
		Deposit glass in hole.
	60.04	Point for the C-N 1/16 sec. cor. of sec. 30.

48

r

- 	Survey, Subdivision Section 30, T. 20 N., R. 20 E.
CHAINS	Set the iron post 22 ins. in the ground, brass cap mkd.
	T20N R20E
	N 1/16 S 30
	1967
	Deposit glass in hole.
73.50	Wash, 5 1ks. wide, 3 ft. deep, drains N. 75° E.
80.06	The ½ sec. cor. of secs. 19 and 30.
	Land, gently rolling badlands. Soil, sandy, clay loam. Timber, none.
	Undergrowth, bunch grass.
	From the ½ sec. cor. of secs. 29 and 30.
	N. 89°50' W., on the E. and W. center line of sec. 30.
	Over gently rolling land.
33.50	Wash, 1.00 ch. wide, 6 ft. deep, drains N.
39.99	The C ½ sec. cor. of sec. 30.
59.97	Point for the C-W 1/16 sec. cor. of sec. 30.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T20N R20E W 1/16
	C W 1/16 S 30 C 1967
	Deposit glass in hole.
67.60	Fence, bears N. and S.
76.00	Enter rolling badlands.
86.00	The point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.
	Land, gently rolling and badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass and sagebrush.
	Subdivision, SW½, Sec. 30
	From the W 1/16 sec. cor. of secs. 30 and 31.
	N. 0°50' E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 30.
	Over rolling badlands.
20.03	Point for the SW 1/16 sec. cor. of sec. 30.

Survey, S	Subdivision	Section	30,	т.	20 N.	. R.	20	Ε.
-----------	-------------	---------	-----	----	-------	------	----	----

		Survey, Subdivision Section 30, 1. 20 N., R. 20 E.
	CHAINS	Set the iron post 20 ins. in the ground, brass cap mkd.
		T20N R20E
*•		SW 1/16+S 30 1967
•		Deposit glass in hole.
	24.00	Leave badlands; thence over gently rolling land.
	40.05	The C-W 1/16 sec. cor. of sec. 30.
u		From the C-S 1/16 sec. cor. of sec. 30.
		N. 89°45' W., on the E. and W. center line of the SW 坛 of sec. 30.
		Over gently rolling land.
	10.00	Enter rolling badlands.
	19.95	The SW 1/16 sec. cor. of sec. 30.
	27.24	Fence, bears N. and S.
	45.99	The point for the S 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.
		Subdivision, NW4, Sec. 30
		From the C-W 1/16 sec. cor. of secs. 30.
		N. 0°46' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 30.
		Over gently rolling land.
	20.01	Point for the NW 1/16 sec. cor. of sec. 30.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T20N R20E NW 1/16+S 30 1967
		Deposit glass in hole.
	40.02	The point for the W 1/16 sec. cor. of secs. 19 and 30.
		From the C-N 1/16 sec. cor. of sec. 30.
		N. $89^{\circ}55'$ W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 30.
	1.10	Wash, 5 1ks. wide, 3 ft. deep, drains N.
	19.98	The NW 1/16 sec. cor. of sec. 30.
	27.88	Fence, bears N. and S.
	45.98	The point for the N 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.

Survey,	Subdivision	Section	36,	Τ.	20	Ν.,	R.	20	Ε.

	Survey, Subdivision Section 36, T. 20 N., R. 20 E.		
СНАІ	Survey, Subdivision Section 36, T. 20 N., R. 20 E.		
	From the point for the ½ sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.		
	N. 1°09' E., on the N. and S. center line of sec. 36.		
	Over rolling badlands.		
7.1	0 Wash, 25 lks. wide, 4 ft. deep, drains E.		
20.13 Point for the C-S 1/16 sec. cor. of sec. 36.			
	Set the iron post 20 ins. in the ground, brass cap mkd.		
	T20N R20E		
	S 1/16 S 36		
	C 1967		
	Raise a mound of stone W. of the cor.		
	Thence over gently rolling land.		
40.2	Point for the C ½ sec. cor. of sec. 36.		
	Set the iron post 20 ins. in the ground, brass cap mkd.		
	T20N R20E C 4+S 36 1967		
	Set a wooden post 3 ins. in diam., 3 ft. long, alongside the cor.		
80.5	The ½ sec. cor. of secs. 25 and 36.		
	Land, badlands, and gently rolling. Soil, clay loam. Timber, none. Undergrowth, bunch grass.		
	From the point for the ½ sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.		
	N. 89°42' W., on the E. and W. center line of sec. 36.		
	Over gently rolling land.		
20.3	Wash, 10 lks. wide, 2 ft. deep, drains N. 45° E.		
39.9	The C ½ sec. cor. of sec. 36.		
54.0	0 Enter rolling badlands.		
79.9	The ½ sec. cor. of secs. 35 and 36.		

Survey, Subdivision Section 36, T. 20 N., R. 20 E. CHAINS Land, gently rolling and badlands. Soil, sandy, clay loam. Timber, none. Undergrowth, bunch grass. Subdivision, SW4, Sec. 36 From the C-S 1/16 sec. cor. of sec. 36. N. 89°41' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 36. Over rolling badlands. 39.94 The S 1/16 sec. cor. of secs. 35 and 36. General Description Township 20 North, Range 20 East, is located about 29 miles east-northeast of Winslow, Arizona. The drainage is mainly from east to west. The elevation ranges from 6,009 feet above sea level in section 16 to about 5,000 feet above sea level in the extreme northwest portion of the township. The land is nearly level to broken and rolling badlands. Two track roads traverse the township, mostly from east to west. The soil ranges from a sandy loam to a clay loam. The vegetation consists of a fair amount of bunch grass, scattered sagebrush and cacti. The area is primarily used for grazing. There are numerous catch ponds and several windmills in the township. There is no evidence of mining activity.

Form 9180-7 (October 1964) (formerly 4-673b) USDI--BLM

BOOK 4845

Form 4-680 (June 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY		
John H. Witmer	Supv. Cadastral Surveyor		
Howard H. Thomas	Supv. Surveying Technician		
Ray E. Thiessen	Supv. Surveying Technician (WAE)		
James H. Jolly	Surveying Aid		
Fred C. Struckmeyer	Surveying Aid		
	:		

INTERIOR -- PORTLAND, OREGON

BOOK 4845

CERTIFICATE OF SURVEY

, Louis D. Gilbert	D. Gilbert , HEREBY CERTIFY upon honor	
in pursuance of special instructions bearing date	e of the 23 day of June	, 1967 ,
I have dependently resurveyed the sou	ith and east boundaries an	d subdivisional
ines, established the north $lac{1}{4}$ secti		
livisions in sections 6, 8, 10, 12,		
Range 20 East,		
of the Gila and Salt River Meridia	n, in the State of Arizona	, which
are represented in the foregoing field notes as h	naving been executed by me and und	der my direction;
and that said survey has been made in strict co	onformity with said special instruct	ions, the Manual
of Instructions for the Survey of the Public L	Lands of the United States, and in	specific manner
described in the foregoing field notes.		
December 20, 1968	Janis W. S	lelbert
(Date)	(Cadastral Surveyor)
(Date)	(Cadastral Surveyor)
OF DITIFICATI	TE OF ADDDOVAL	
CERTIFICAT	TE OF APPROVAL	
SUBMITTED FOR APPROVAL	BUREAU OF LAND Washington, D. C.	MANAGEMENT,
Date		
The foregoing field notes of the dependent	resurvey of the south and	d east boundaries
and subdivisional lines, establish	ment of the north $rac{1}{4}$ section	on corner of sec-
tion 6, and survey of subdivisions	s in sections 6, 8, 10, 12	, 14, 20, 28, 30
and 36, Township 20 North, Range 2	20 East, Gila and Salt Riv	er Meridian,
Arizona,		
executed by Louis D. Gilbert		
having been critically examined and found cor	rect, are hereby approved.	
	M $I + L$	
JUN 2 5 1969	Clark + Sh	umm
(Date)	(Chief, Division of Eng.) Chief, Division of Can	incoring) dastral Survey
CERTIFICAT	FE OF TRANSCRIPT	
		. J
I CERTIFY That the foregoing transcript of the	_	
	is a true copy of the or	riginal field notes.
(Date)	(Chief, Division of Eng	(ineering)