

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT OF A PORTION OF THE BOUNDARIES

OF

SECTION 25

AND A

METES AND BOUNDS SURVEY

OF

LOT 17, SECTION 25

IN

TOWNSHIP 1 NORTH, RANGE 15 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Louis D. Gilbert

Supervisory Cadastral Surveyor

Under special instructions dated April 25, 19 69, which provided for the surveys
included under Group Number 466, approved April 28, 1969,
and assignment instructions dated April 29, 19 69.

Survey commenced May 8, 19 69

Survey completed May 8, 19 69

1A

BOOK 4869

INDEX DIAGRAM


Township 1 North, Range 15 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	(Lot 17) 25
31	32	33	34	35	36

Township 1 North, Range 15 East,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Globe townsite was surveyed in 1881 by C. H. Wallace. The boundaries of Section 25 were surveyed by A. T. Colton in 1899. The east boundary of Section 25 was retraced by R. C. Ham in 1910.</p> <p>The following field notes are those of a retracement of a portion of the boundaries of Section 25 and a metes and bounds survey of Lot 17 in the N$\frac{1}{2}$N$\frac{1}{2}$ of Section 25, Township 1 North, Range 15 East, Gila and Salt River Meridian, Arizona.</p> <p>This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 25, 1969.</p> <p>Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2$\frac{1}{2}$ inches in diameter, flanged at the base, with a brass cap riveted to the top.</p> <p>The geographic position of the NE. corner of Section 25, as scaled from USGS quadrangle "Globe, Arizona", edition of 1947, scale 1:24000, is: Latitude 33°24'27" N. and Longitude 110°46'23" W.</p> <p>The magnetic declination was found to be 14° East.</p>
	<p style="text-align: center;">Retracement of a Portion of the Boundaries of Section 25, T. 1 N., R. 15 E.</p>
<p>21.065</p> <p>39.93</p>	<p style="text-align: center;">Retracement of the Retracement Executed by R. C. Ham in 1910</p> <hr/> <p>Beginning at the $\frac{1}{4}$ sec. cor. of secs. 25 and 27, on the E. bdy. of the Tp.; monumented by $\frac{3}{4}$ in. iron pipe, projecting 4 ins. above ground. This corner is accepted locally and is accepted as the best available evidence of the orig. cor. position; not remonumented.</p> <p>Thence, N. 0°05' E. bet. secs. 25 and 27.</p> <p>Over rolling land.</p> <p>Intersect line 2-3, Ohio Boy No. 2 lode, M.S. 2317, at a point S. 69°02' W., 7.106 chs. dist. of Cor. No. 2, Ohio Boy No. 2 lode, M.S. 2317 and N. 69°02' E., 2.099 chs. dist. of Cor. No. 3, Ohio Boy No. 2 lode, M.S. 2317, identical with Cor. No. 2, Ohio Boy No. 3 lode, M.S. 2342.</p> <p>The cor. of secs. 22, 24, 25 and 27, monumented by a quartzite stone, 12x6x6 ins. above ground, firmly set, mkd. with 4 notches on N. and 2 notches on S. faces, with mound of stone N.; not remonumented.</p>

Retracement, Portion of Bdys., Sec. 25, T. 1 N., R. 15 E.

<p>CHAINS</p>	<p>Thence, S. 89°41' W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p> <p>6.086 Intersect line 3-4, Ohio Boy No. 2 lode, M.S. 2317, at a point S. 11°49' E., 2.719 chs. dist. of cor. No. 4, Ohio Boy No. 2 lode, M.S. 2317, identical with Cor. No. 1, Surplus lode, M.S. 2341 and N. 11°49' W., 20.008 chs. dist. of cor. No. 3, Ohio Boy No. 2 lode, M.S. 2317, identical with Cor. No. 2, Ohio Boy No. 3 lode, M. S. 2342.</p> <p>39.458 Intersect line 4-1, Clinton lode, M.S. 2320, at a point S. 0°01' E., 1.781 chs. dist. of Cor. No. 4, Clinton lode, M.S. 2320 and N. 0°01' W., 0.805 chs. dist. of Cor. No. 1, Clinton lode M.S. 2320, identical with Cor. No. 1, Pay Rock lode, M.S. 2333.</p> <p>40.54 The 1/4 sec. cor. of secs. 24 and 25, monumented by a granite stone, 8x8x6 ins. above ground, firmly set, mkd. 1/4 S 24 on N. and 25 on S. faces, with mound of stone W.; not remonumented.</p>
<p>Survey of Lot 17</p>	
<p>At Cor. No. 1, Lot 17, sec. 25; which is on line 6-1 of Ohio Boy No. 5 lode, M.S. 2387.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R15E S 25</p>  </div> <p>from which</p> <p>Cor. No. 2, Trail lode, M.S. 2387, bears N. 21°44' W., 3.069 chs. dist., monumented by the remains of a rotted post, in a mound of stone. This corner was recovered by scraping layers of soil away until the squared form of the post was uncovered. Only small splinters of the post lined the edges of the square hole.</p> <p>Cor. No. 1, Ohio Boy No. 5 lode, M.S. 2387, bears N. 21°44' W., 8.149 chs. dist., monumented by the remains of a rotted post, set in mound of stone. This corner was recovered by scraping layers of soil away until the squared form of the post was uncovered. Only small splinters of the post lined the edges of the square hole.</p> <p>Point for Cor. No. 6, Ohio Boy No. 5 lode, M.S. 2387, bears S. 21°44' E., 3.363 chs. dist. This corner point was reestablished at record bearing and dist. from Cors. 1 and 5, Ohio Boy No. 5 lode, M.S. 2387; not monumented.</p>	

Survey of Lot 17, Sec. 25, T. 1 N., R. 15 E.

CHAINS

The cor. of secs. 22, 24, 25 and 27, T. 1 North, Rs. 15 and 15½ E., bears N. 61°41' E., 35.86 chs. dist.; hereinbefore described.

The ¼ sec. cor. of secs. 24 and 25, T. 1 N., R. 15 E., bears N. 28°06' W., 19.04 chs. dist.; hereinbefore described.

Raise a mound of stone NE. of the iron post.

Thence S. 89°37' W., along the N. bdy. of Lot 17.

7.876

Point for Cor. No. 2, Lot 17, identical with Cor. No. 2, Lime Ledge, M.S. 2272, monumented by the remains of a rotted post, 6 ins. long, 5 ins. square. This corner was recovered from a tie given in the official record of the mineral survey to Cor. No. 4, Ohio Boy No. 4, M.S. 2318; then by scraping layers of soil away until the squared form of the post was uncovered.

Set the iron post 20 ins. in the ground, brass cap mkd.

	T1N R15E	
	S 25	
LIME LEDGE		
M S 2272		
COR 2		
		COR 2
		LOT 17
	1969	

from which

Cor. No. 4, Ohio Boy No. 4 lode, M.S. 2318, bears N. 0°01' W., 6.953 chs. dist., monumented by the remains of a rotted post, set in a mound of stone. This corner was recovered by scraping layers of soil away until the squared form of the post was uncovered. Only small splinters of the post lined the edges of the square hole.

from which

A bearing rock, bears N. 22°48' W., 0.568 chs. dist., monumented by a limestone, 16x10x10 ins. above ground, firmly set, mkd. X BR, no other markings legible.

Lines 1-2, 2-3 and 3-4 of Lime Ledge were retraced, but no evidence of Cors. 1, 3 and 4 were found.

Bury the remains of the wooden post alongside the iron post.

Raise a mound of stone NW. of the cor.

Thence S. 0°01' E., along the W. bdy. of Lot 17.

0.37

Fence, bears E. and W.

2.30

Bladed road, bears E. and W.

3.244

Intersect N. bdy. of East Globe Townsite.

Survey of Lot 17, Sec. 25, T. 1 N., R. 15 E.

CHAINS	
	<p>Point for Cor. No. 3, Lot 17.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R15E S 25 LOT 17 COR 3 ----- 1969</p> </div> <p>Raise a mound of stone NW. of the iron post.</p> <p>Thence, N. 89°21' E., along the S. bdy. of Lot 17, and N. bdy. of East Globe Townsite.</p>
6.47	West side of house, bears S. 55° E. and N. 55° W.
6.76	East side of same house.
7.10	Driveway area to reach house, bears N. and S.
9.149	<p>Point for Cor. No. 4, Lot 17, at the intersection of the N. bdy. of East Globe Townsite line with the S. 21°44' E., extension of line 6-1, Ohio Boy No. 5 lode, M. S. 2387.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R15E S 25 LOT 17 COR 4 ----- 1969</p> </div> <p>from which</p> <p>NE. cor. of carport on house measuring 31 ft. by 42 ft., bears N. 84°21' W., 2.23 chs. dist., with the long side of the house bearing N. 55° W.</p> <p>NE. cor. of shed, measuring 17 ft. by 16 ft., bears N. 82°51' W., 3.26 chs. dist., with the long side of the shed bearing N. 70° W.</p> <p>SE. cor. of shed, measuring 13 ft. by 10 ft., bears N. 69°59' W., 3.45 chs. dist., with the long side of the shed bearing N. 60° W.</p> <p>Cor. No. 5, Ohio Boy No. 5 lode, M.S. 2387, bears N. 89°00' E., 5.476 chs. dist., monumented by the remains of a rotted post, set in mound of stone. This corner was recovered by scraping layers of soil away until the squared form of the post was uncovered. Only small splinters of the post lined the edges of the square hole.</p> <p>Raise a mound of stone NE. of the iron post.</p> <p>Thence N. 21°44' W., along the E. bdy. of Lot 17.</p>
0.072	Cor. No. 6, Ohio Boy No. 5 lode, M.S. 2387, hereinbefore described.
1.25	Fence, bears S. 60° E. and N. 60° W.

Survey of Lot 17, Sec. 25, T. 1 N., R. 15 E.

CHAINS

3.435

Cor. No. 1, Lot 17, point of beginning.

GENERAL DESCRIPTION

The land in Section 25, Township 1 North, Range 15 East, is mostly heavy rolling land, with numerous canyons and draws.

Scattered mesquite, together with creosote cover the entire section. There has been considerable mineral activity in the past.

There are a few improvements which lie in Lot 17, all of which ties are given in these notes.

BOOK 4869

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of April, 1969, (I) ~~(We)~~ have made a retracement of a portion of the boundaries of Section 25 and a metes and bounds survey of a small tract (Lot 17) in the N $\frac{1}{2}$ N $\frac{1}{2}$ of Section 25, Township 1 North, Range 15 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 7, 1969

(Date)

Louis D. Gilbert

~~(Cadastral Surveyor)~~

Supervisory Cadastral Surveyor

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 12 1969

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the retracement of a portion of the boundaries of Section 25 and the metes and bounds survey of a small tract (Lot 17) in the N $\frac{1}{2}$ N $\frac{1}{2}$ of Section 25, Township 1 North, Range 15 East, Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert

having been critically examined and found correct, are hereby approved.

SEP 23 1970

(Date)

J. J. Jordan
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-628