

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 12 NORTH, RANGE 1 WEST

TOWNSHIP 15 NORTH, RANGE 3 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

John H. Witmer, Cadastral Surveyor

Under special instructions dated July 1, 19 69, which provided for the surveys
included under Group Number 514, approved July 2, 1969,
and assignment instructions dated July 2, 19 69.

Survey commenced July 8, 19 69

Survey completed September 11, 19 69

BOOK 4884

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 12 N. R. 1 W. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	● 21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 15 N. R. 3 W. Mer. G&SR

6	5	4	3	2 2	1
7	8	9	10	● 11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. _____ R. _____ Mer. _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 12 North, Range 1 West
 Township 15 North, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 2, 1969 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The magnetic declination used was 15° East.

Township 12 North, Range 1 West, G&SR M., Arizona

The subdivisional lines were surveyed in 1961-1963 by Virgil Spratt, Paul Bauer and Gary Rutledge.

Remonumentation, T. 12 N., R. 1 W., Arizona

The ¼ sec. cor. of secs. 20 and 21, monumented by an iron post, 2½ ins. in diam., set 18 ins. in the ground, with a brass cap mkd. T12N R1W ¼ S20 S21 1963 from which the orig. bearing trees

A cedar, 7 ins. diam., bears S. 31°10' E., 65 lks. dist., mkd. ¼ S21 BT.

A forked cedar, 12 ins. diam., bears S. 19° W., 45 lks. dist., mkd. ¼ S20 BT.

from which new accessories

An iron post, set 22 ins. in the ground, for a reference monument, with a steel post with attention sign, set alongside, bears N. 45° E., 45.6 lks. dist., with brass cap mkd. T12N R1W ¼ S21 RM 30 FT 1969 and an arrow pointing to the true cor.

An iron post, set 22 ins. in the ground, for a reference monument, with a steel post with attention sign, set alongside, bears S. 45° E., 60.6 lks. dist., with brass cap mkd. T12N R1W RM 40 FT ¼ S21 1969 and an arrow pointing to the true cor.

Reference monuments were set for this cor., as original iron post cor. and bearing trees will be disturbed by Forest Service road construction. Left original iron post cor. in place, as Forest Service stated road fill during construction will cover it, and if not, it will be buried under road surface during construction.

Remonumentation, T. 15 N., R. 3 W., Arizona

CHAINS

Township 15 North, Range 3 West, G&SR M., Arizona

The subdivisional lines were surveyed in 1871 by S. W. Foreman and retraced in 1927 by S. E. Blout and C. E. Hunter.

Remonumentation, T. 15 N., R. 3 W., Arizona

The cor. of secs. 2, 3, 10 and 11, monumented by a granite stone, 18 x 10 x 10 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on S. face and 2 notches on the E. face.

At the cor. point

Set the iron post, 20 ins. in the ground, with broken glass in hole, and a steel post set alongside, with brass cap mkd.

T15N R3W
 S 3 | S 2
 S10 | S11
 1969

from which

A fence cor., from which fences bear N. and W., bears N. 7° W., 66 lks. dist.

A cor. pole of a telephone line, bears N. 14° W., 75½ lks. dist.

Bury orig. cor. stone alongside the iron post.

This cor. was remonumented with the permission of all interested parties, and at the request of the Forest Service, in order to provide control for section subdivision in the future.

4

CERTIFICATE OF SURVEY

(I) ~~(We)~~ John H. Witmer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1969, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 12 North, Range 1 West, and Township 15 North, Range 3 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me) ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 1, 1969
(Date)

John H. Witmer
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 18 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 12 North, Range 1 West, and Township 15 North, Range 3 West, both of the Gila and Salt River Meridian, Arizona,

executed by John H. Witmer, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUN 2 1971
(Date)

Clark F. Lumm
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-828