Form 9180-6 (April 1965) (formerly 4-679)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
AND A
RETRACEMENT
OF A
PORTION OF THE
SUBDIVISIONAL LINES
TOWNSHIP 8 SOUTH, RANGE 27 EAST
Of theGila and Salt RiverMeridia
In the State ofArizona
EXECUTED BY
Louis D. Gilbert Cadastral Surveyor
Under special instructions dated December 24 , 19 68 , which provided for the survey
included under Group Number 470 , approved December 26, 1968
and assignment instructions dated <u>December 26</u> , 19 <u>68</u> .
Survey commenced February 17 19 69

March 4

Survey completed _

_____, 19 ____

BOOK 494

INDEX DIAGRAM

Towns	hip8 So	uth	, Range	27 East	······································
6	5	4	8	16 2	7 1
7	8	9	15	15 14 11	6 12
32	32		14	13	6
18	31 17	25 16	20 18	12 14	5 13
31	30	24	20	12	4
19	29 20	24 21	19 22	11 ²⁸	4 24
29	28	23	18	10	3
30	28 29	22 28	18 27	9 26	3 25
27	26	22	17	9	2
31	26 32	21 33	16 84	8 35	1 36

Township 8 South, Range 27 East Gila and Salt River Meridian, Arizona

CHAINS

The boundaries and subdivisional lines were surveyed by T. F. White in 1875. The east boundary was resurveyed by W. B. Kimmel in 1914. The south, west and north boundaries and a portion of the subdivisional lines were resurveyed by D. E. Harding in 1957. The east $\frac{1}{2}$ mile between sections 4 and 33 on the south boundary was retraced by Dell Cazier in 1961. The west boundary was retraced concurrently by Louis D. Gilbert under this same Group No. and the record is included in the field notes of T. 8 S., R. 26 E.

The following field notes are those of a dependent resurvey of a portion of the subdivisional lines, designed to restore the corners in their true original location according to the best available evidence, and a retracement of a portion of the subdivisional lines in Township 8 South, Range 27 East, Gila and Salt River Meridian,

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated December 24, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the SE. corner of the township, as determined by traverse to U.S.S.E.S. triangulation station "Eleven" located in sec. 23 is: Latitude 32°41'11.2" N. and Longitude 109°31'39.7" W.

The mean magnetic declination was found to be 13° East.

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

Reestablishment of the Survey Executed by T. F. White in 1875

Beginning at the true point for the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., in a wash, 2.00 chs. wide, with 10 ft. banks, drains N. 10° W. This cor. is witnessed N. 89°58' W., 35 lks. dist., and monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 4 ins. above ground, firmly set, brass cap mkd.

N. 0°05' W., bet. secs. 35 and 36.

Over nearly level land cut by numerous washes.

7.50 Wash, 70 1ks. wide, 2 ft. deep, drains irregularly W.

Wash, 80 lks. wide, 3 ft. deep, drains irregularly W.

Point for the ½ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.

28.30

39.81

Dep. Res.	, Portion	Subdivisional	Lines,	Τ.	8	S.,	R.	27	Ε.
-----------	-----------	---------------	--------	----	---	-----	----	----	----

	Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
CHAINS	
-	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	\$35 S36 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
56.60	Wash, 50 1ks. wide, 2 ft. deep, drains irregularly W.
68.20	Top of low knoll.
75.00	Fence, bears SE. and NW.
77.20	Fence, bears S. 88° E. and N. 88° W.
79.62	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E <u>S26 S25</u> S35 S36 1969
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
,	Land, nearly level and badly eroded. Soil, sandy loam. Timber, none. Undergrowth, scattered creosote bush, bunchgrass and cacti.
	From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 6 ins. above ground, firmly set, with mound of stone W., brass cap mkd.
	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
	S. 89°52' W., bet. secs. 25 and 36.
	Over level land.
39,99	Point for the ½ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.

	*	bep. Res., Forcion Bubulvisional Lines, 1. 0 5., R. 2/ E.
	CHAINS 79.98	The cor. of secs. 25, 26, 35 and 36.
		Land, level and gently rolling.
		Soil, sandy loam.
		Timber, none. Undergrowth, creosote bush, bunchgrass and cacti.
		N. 0°13' E., bet. secs. 25 and 26.
		Over level land.
	37.80	Track road, bears E. and W.
	39.81	Point for the ½ sec. cor. of secs. 25 and 26, at propor-
	37.01	tionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T8S R27E
	· '	S26 S25
	, а	1969
		Set a wooden post, 4 ft. long, 5 ins. diam., alongside the iron post.
Ì	45.80	Track road, bears NE. and SW.
	54.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 75° W.
	79.62	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
		Land, level. Soil, sandy loam. Timber, none. Undergrowth, creosote bush, bunchgrass and cacti.
		From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 6 ins. above ground, firmly set in a collar of stone, brass cap mkd.
		T8S
		$\begin{array}{c c} R27E & \frac{S24}{S25} \end{array}$
	a o	$\frac{\text{S19}}{\text{S30}}$ R28E
	,	1914
		S. 89°45' W., bet. secs. 24 and 25.
		Over level land.
	39.87	Point for the ½ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	79.74	The point for the cor. of secs. 23, 24, 25 and 26.
		Land, level. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.

ه و	Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
CHAINS	
	N. 0°05' W., bet. secs. 23 and 24.
	Over level land.
28.10	Track road, bears E. and W.
39.81	Point for the ½ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	S23 S24 1969
۰	from which .
	U.S. Soil Erosion Service Triangulation Station "Eleven", bears S. 64°22'45" W., 23.48 chs. dist., monumented by a standard disk, set in a rectangular concrete post projecting 3 ins. above ground. Disk is unstamped. Geographic position: Latitude, 32°43'14.033" N., longitude, 109°32'57.182" W.
	Raise a mound of stone W. of the iron post.
44.90	Fence, bears N. 60° E. and S. 60° W.
73.10	Wash, 20 1ks. wide, 2 ft. deep, drains N. 60° W.
79.62	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	<u>\$14 \\$13</u>
6	S23 S24 1969
	Land, level.
	Soil, sandy loam. No timber, undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 8 ins. above ground, firmly set, with mound of stone W., brass cap mkd.
	T8S R27E S13 S18 S18 R28E 1914
	S. 89°50' W., bet. secs. 13 and 24.
	Over level land.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.

Fence, bears S. 25° E. and N. 15° W. 3.10 Wash, 20 lks. wide, 6 ins. deep, drains S. 80° W. Point for the \$ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$ \$13/824 1969 Raise a mound of stone N, of the iron post. Over gently rolling land. 79.86 The cor. of secs. 13, 14, 23 and 24. Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. 28.90 Track road, bears irregularly E. and W. Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the \$ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 \$13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 \$12 \$11 \$12 \$14 \$13	. Lines, F. 6 b., R. 27 B.	Dep. Res., Tortion Bubury
3.10 Wash, 20 lks. wide, 6 ins. deep, drains S. 80° W. 39.93 Point for the k sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \[\frac{	4.60	
39.93 Point for the ½ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E ½ \$13/524 1969 Raise a mound of stone N, of the iron post. Over gently rolling land. 79.86 The cor. of secs. 13, 14, 23 and 24. Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. 28.90 Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 S13 \\ 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 S12	₹ •	
tionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \(\frac{1}{8} \frac{\text{S13}}{\text{S24}} \\	ep, drains S. 80° W.	
T8S R27E 1 S13 S24 1969 Raise a mound of stone N, of the iron post. Over gently rolling land. The cor. of secs. 13, 14, 23 and 24. Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. 28.90 Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. 39.81 Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E S14 S13 1969 Raise a mound of stone W. of the iron post. 79.62 Foint for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12		tionate dist.; there is n
Raise a mound of stone N, of the iron post. Over gently rolling land. 79.86 The cor. of secs. 13, 14, 23 and 24. Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. 28.90 Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. 39.81 Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 S13 1969 Raise a mound of stone W. of the iron post. 79.62 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 S12	the ground, brass cap mkd.	Set the iron post 20 ins.
Over gently rolling land. The cor. of secs. 13, 14, 23 and 24. Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. 28.90 Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. 39.81 Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 \$13\$ 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 \$12}		· ½ <u>\$13</u>
The cor. of secs. 13, 14, 23 and 24. Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 S13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 S12	the iron post.	Raise a mound of stone N,
Land, level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 S13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 S12		Over gently rolling land.
Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti. N. 0°13' E., bet. secs. 13 and 14. Over gently rolling land. Track road, bears irregularly E. and W. 31.90 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 S13 1969 Raise a mound of stone W. of the iron post. 79.62 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 S12	and 24.	79.86 The cor. of secs. 13, 14,
Over gently rolling land. Track road, bears irregularly E. and W. Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E ½ S14 S13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12		Soil, sandy loam. No timber; undergrowth, so
Over gently rolling land. Track road, bears irregularly E. and W. Wash, 10 lks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 S13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 S12	1 14.	N. 0°13' E., bet. secs. 1
Wash, 10 1ks. wide, 2 ft. deep, drains irregularly W. Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E S14 S13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12	,	Over gently rolling land.
Point for the ½ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$\frac{1}{2}\$ \$\frac{1}{2	E. and W.	28.90 Track road, bears irregula
tionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. T8S R27E \$14 \$13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E \$11 \$12	o, drains irregularly W.	31.90 Wash, 10 1ks. wide, 2 ft.
T8S R27E S14 S13 1969 Raise a mound of stone W. of the iron post. Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12	The state of the s	tionate dist.; there is no
S14 S13 1969 Raise a mound of stone W. of the iron post. 79.62 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12	the ground, brass cap mkd.	Set the iron post 20 ins.
Raise a mound of stone W. of the iron post. 79.62 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12		T8S R2
Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12		
tionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, brass cap mkd. T8S R27E S11 S12	he iron post.	Raise a mound of stone W.
T8S R27E S11 S12		tionate dist.; there is no
<u>S11 S12 </u>	he ground, brass cap mkd.	Set the iron post 18 ins.
1969		<u>S11 S12 S14 S13 S14 S13 S14 S13 S14 S13 S14 S15 S14 S15 S15 </u>
Deposit glass at the base of the iron post.	he iron post.	Deposit glass at the base
Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.	ete bush, bunchgrass and	Soil, sandy loam. No timber; undergrowth, co

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.

D	ep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
CHAINS	
	From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 6 ins. above the ground, firmly set, with mound of stone W., brass cap mkd.
	T8S R27E
	S. 89°52' W., bet. secs. 12 and 13.
	Over gently rolling land.
20.00	Fence, bears N. and S.
39.90	Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T8S R27E
	1 S12 S13 S13 S1969
	Deposit glass at the base of the iron post.
43.80	Wash, 30 1ks. wide, 1 ft. deep, drains irregularly NW.
59,00	Wash, 30 1ks. wide, 1 ft. deep, drains N. 30° W.
79.80	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
	N. 0°15' E., bet. secs. 11 and 12.
	Over gently rolling land.
2.40	Wash, 30 1ks. wide, 2 ft. deep, drains irregularly W.
12.00	Track road, bears N. 15° E. and S. 15° W.
14.40	Same track road, bears W. from S. 15° W.
39.81	Point for the ½ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T8S_R27E
	\$11 \$12 1969
	Deposit glass at the base of the iron post.
79.62	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.

CHAINS

Set the iron post 20 ins. in the ground, brass cap mkd.

T8S R27E <u>S 2 S 1</u> <u>S11 S12</u> 1969

Raise a mound of stone W. of the iron post.

Land, gently rolling.

Soil, sandy loam.

No timber; undergrowth, creosote bush, bunchgrass and cacti.

From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 6 ins. above ground, firmly set, with mound of stone E., brass cap mkd. \cdot

$$\begin{array}{c|c}
 & T8S \\
 & \underline{S} & 1 & R28E \\
 & \underline{S} & 6 & \underline{S} & 7 \\
 & \underline{S} & 1914
\end{array}$$

S. 89°47' W., bet. secs. 1 and 12.

Over gently rolling land.

19.90 Fence, bears S. and N., 60 lks. dist. to cor. of fences bearing N. 25° E. and S.

Point for the ½ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 18 ins. in the ground, brass cap mkd.

79.58 The cor. of secs. 1, 2, 11 and 12.

Land, gently rolling. Soil, sandy loam.

No timber; undergrowth, creosote bush, bunchgrass and

N. 0°03' W., bet. secs. 1 and 2.

Over gently rolling land.

15.60 Wash, 10 lks. wide, 6 ins. deep, drains W.

Point for the ½ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 20 ins. in the ground, brass cap mkd.

Dep. Res.,	Portion	of the	Subdivisional	Lines, T.	8 S.,	R. 2	7 E.
							

	. D	ep. Res., Portion of the Subdivisional Lines, T. 8 S., R. 2
	CHAINS	
	•	T8S R27E
		\$ 2 S 1 1969
		Deposit glass at the base of the iron post.
	79.69	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, with mound of stone W., brass cap mkd.
	•	T7S R27E S 35 S 36 S 2 S 1 T8S 1957 Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
		From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, brass cap mkd.
		T8S R27E S 34 S 35 S 3 S 2 T9S 1957
		N. 0°07' W., bet. secs. 34 and 35.
		Over gently rolling land.
	39.81	Point for the ½ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T8S R27E
	,	s 34 s 35 1969
		Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.
1	41.80	Wash, 20 1ks. wide, 1 ft. deep, drains N. 60° E.
	79.62	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
	ı	Set the iron post 22 ins. in the ground, brass cap mkd.
•		T8S R27E S 27 S 26 S 34 S 35 1969

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.

	CHAINS	
		Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.
		Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	•	From the cor. of secs. 25, 26, 35 and 36.
Ì		N. 89°52' W., bet. secs. 26 and 35.
	!	Over nearly level land.
	3.70	Fence, bears S. 30° E. and N. 30° W.
	4.50	Fence, bears S. and N., 82 lks. dist., to cor. of fences bearing S. 30° E., S., W. and N. 30° W.
	27.30	Fence, bears N. and S.
	34.00	Right bank of the San Simon River, 30 ft. high, bears irregularly N. and S.
	36.40	San Simon River (dry), drains irregularly N.
	39.97	Point for the ½ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T8S R27E
		S 26 S 35 1969
)	3	Set a wooden post, 4 ft. long, 3 ins. squared, along- side the iron post.
	< .	Although this cor. falls within the banks of the river, it is monumented on high, dry ground.
	44.90 .	Left bank of the San Simon River, 30 ft. high, bears irregularly N. and S.
	56.70	Railraoad R-O-W fence, bears S. 5° E. and N. 5° W.
	58.50	Southern Pacific Railroad tracks, bears S. 5° E. and N. 5° W.
	59.00	Telephone line, bears S. 5° E. and N. 5° W.
	62.70	Wash, 50 lks. wide, 2 ft. deep, drains irregularly NE.
	79.94	The cor. of secs. 26, 27, 34 and 35.
	-	Land, nearly level. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
		N. 0°08' E., bet. secs. 26 and 27.
		Over nearly level land.
١		

Dep. I	Res.,	Portion	Subdivisional	Lines,	T. 8	S., · I	R. 27	Ε.

. Dej	p. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
CHAINS	
0.43	Fence, bears E. and W
12.90	Wash, 300 lks. wide, with 8 ft. banks, drains E.
39.81	Point for the ½ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd. T8S R27E 1/2 S 27 S 26 1969
	Set a wooden post, 3 ft. long, 4 ins. squared, alongside the iron post.
66.00	Telephone line, bears S. 31°30' E. and N. 31°30' W.
67.00	Southern Pacific Railroad tracks, bear S. 31°30' E. and N. 31°30' W.
70.00	Railroad R-O-W fence, bears S. 31°30' E. and N. 31°30' W.
79.32	Point selected for the witness cor. of secs. 22, 23, 26 and 27.
	Set the iron post 22 ins. in the ground, brass cap mkd.
•	T8S R27E W C
	S 22 S 23 S 27 S 26 1969
:	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
79.62	True point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist., falls in a crevice, 2 lks. wide, 6 ft. deep, drains northerly, impractical to monument; there is no remaining evidence of the orig. cor.
	Land, nearly level.
	Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the point for the cor. of secs. 23, 24, 25 and 26.
•	N. 89°52' W., bet. secs. 23 and 26.
	Over nearly level land.
16.80	Fence, bears N. 24° E. and S. 24° W.
19.80	Track road on top of Goat Springs Detention Dam, bears N. 24° E. and S. 24° W.
34.80	Draw, drains irregularly NW.
	,

Dep.	Res.,	\cdot Portion	Subdivisional	Lines,	T. 8	S.,	·R.	27	Ε.
------	-------	-----------------	---------------	--------	------	-----	-----	----	----

· De	p. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
CHAINS	
40.01	Point for the ½ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
•	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	½ S 23 S 26
	1969
	Deposit glass at the base of the iron post.
42.10	Draw, drains irregularly NW.
75.10	Right bank of the San Simon River, 30 ft. high, bears irregularly S. 10° E. and N. 10° W.
77.00	San Simon River (dry), drains irregularly N. 10° W.
78.10	Left bank of the San Simon River, 30 ft. high, bears irregularly S. 10° E. and N. 10° W.
80.02	True point for the cor. of secs. 22, 23, 26 and 27.
	Land, nearly level.
	Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	N. 0°03' E., bet. secs. 22 and 23.
٠	Over nearly level land.
1.30	Left bank of the San Simon River, 30 ft. high, bears irregularly S. 25° E. and N. 25° W.
8.90	San Simon River (dry), drains irregularly N. 25° W.
12.30	Right bank of the San Simon River, 30 ft. high, bears irregularly S. 25° E. and N. 25° W.
17.40	Left bank of wash, bears irregularly SE. and NW.
18.30	Wash, drains irregularly NW.
23.80	Right bank of same wash, bears irregularly SE. and NW.
39.81	Point for the ½ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
•	T8S R27E
	s 22 s 23
	1969
	Set a wooden post, 4 ft. long, 4 ins. squared, alongside the iron post.
59.10	Wash, 20 1ks. wide, 2 ft. deep, drains W.
78.70	Wash, 10 lks. wide, 1 ft. deep, drains irregularly W.
	1

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.

CHAINS	ep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
79.62	Point for the cor. of secs. 14, 15, 22 and 23, at propor tionate dist.; there is no remaining evidence of the orig. cor.
•	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E S 15 S 14 S 22 S 23 1969
	Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
·	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°51' W., bet. secs. 14 and 23.
•	Over nearly level land.
23.50	Track road, bears N. and S.
28.90	Wash, 20 lks. wide, 2 ft. deep, drains irregularly NW.
39.89	Point for the ½ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
٠	$\frac{1}{4}$ $\frac{.S}{S}$ $\frac{14}{23}$. 1969
	Deposit glass at the base of the iron post.
69.60	Fence, bears S. 30° E. and N. 30° W.
79.78	The cor. of secs. 14, 15, 22 and 23.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and
	cacti.
	N. 0°05' E., bet. secs. 14 and 15.
	Over gently rolling land.
3.20	Wash, 20 1ks. wide, 2 ft. deep, drains irregularly W.
28.50	Wash, 30 1ks. wide, 1 ft. deep, drains W.
29.40	Fence, bears S. 35° E. and N. 35° W.
38.90	Small wash, drains W.
39.81	Point for the ½ sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
•	

Dep.	Res.,	Portion	Subdivisional	Lines,	Τ.	8	S.,	R.	27	Ε.
------	-------	---------	---------------	--------	----	---	-----	----	----	----

	Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 27 E.
CHAINS	
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	S 15 S 14 1969
	Raise a mound of stone W. of the iron post.
77.50	Old fence line, bears S. 75° E. and N. 75° W.
79.62	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T8S R27E S 10 S 11 S 15 S 14 1969
	Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
`	From the cor. of secs. 11, 12, 13 and 14.
	N. 89°51' W., bet. secs. 11 and 14.
	Over gently rolling land.
3.70	Track road on top of detention dam, bears N. 18° E. and S. 18° W.
24.70	Track road on top of detention dam, bears irregularly N. and S.
-39.98	Point for the ½ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
·	1 S 11 S 14 1969
	·
76.40	Deposit glass at the base of the iron post. Small wash, drains irregularly NW.
79.96	The cor. of secs. 10, 11, 14 and 15.
,,,,,,	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.

	T. 8 S., R. 27 E.
CHAINS	
	N. 89°47' W., bet. secs. 10 and 15.
	Over gently rolling land.
21.80	Wash, 10 lks. wide, 1 ft. deep, drains irregularly NW.
33.40	Fence, bears S. 35° E. and N. 35° W.
40.02	Point for the ½ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
۰	T8S R27E ½ S 10 S · 15 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
56.50	Right bank of the San Simon River, 20 ft. high, bears irregularly N. and S.
64.90	San Simon River (dry), drains irregularly N.
66.80	Left bank of the San Simon River, 20 ft. high, bears irregularly N. and S.
80.04	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post, 2½ ins. diam., projecting 4 ins. above ground, firmly set, brass cap mkd.
	T8S R27E S 9 S 10 S 16 S 15 1957
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 0°19' E., bet. secs. 10 and 11.
•	Over nearly level land.
2.90	Wash, 120 1ks. wide, with 10 ft. banks, drains W.
39.81	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E S10 S11 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.

CHAINS	
79.62	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
×	T8S R27E S 3 S 2 S10 S11 1969
	Deposit glass at the base of the iron post.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°48' W., bet. secs. 2 and 11.
	Over nearly level land.
39.90	Point for the ½ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
N X	T8S R27E 1
	Deposit glass at the base of the iron post.
43.40	Detention dam, bears N. and S.
45.00	Track road, bears irregularly N. and S.
57.40	Track road, bears N. 80° E. and S. 80° W.
78.00	Same track road, bears SE. and NW.
79.80	The cor. of secs. 2, 3, 10 and 11.
	Land, nearly level to gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
	N. 89°48' W., bet. secs. 3 and 10.
	Over gently rolling land.
34.80	Track road, bears N. 60° E. and S. 60° W.
39.91	Point for the ½ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E ½ S 3 S 10 1969

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

CHAINS	
(0.00	Raise a mound of stone N. of the iron post.
40.20	Same track road, bears S. 80° E. and N. 80° W.
48.20	Same track road, bears NE. and SW.
74.90	Same track road, bears SE. and NW.
79.82	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, with mound of stone W., brass cap mkd.
	T8S R27E S 4 S 3 S 9 S 10 1957
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 0°10' W., bet. secs. 2 and 3.
	Over gently rolling land.
.0.50	Track road, bears S. 75° E. and N. 75° W.
21.40	Wash, 40 lks. wide, 4 ft. deep, drains W.
39.81	Point for the ½ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E
	· · · · · · · · · · · · · · · · · · ·
	S 3 S 2 1969
	Deposit glass at the base of the iron post.
41.90	Track road, bears E. and W.
79.50	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, firmly set, with mound of stone W., brass cap mkd.
	T7S R27E S 34 S 35 S 3 S 2 T8S 1957
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, firmly set, with mound of stone W., brass cap mkd.

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

	1. 0 D., R. 27 E.
CHAINS	
	T8S R27E
	<u>s 33 s 34</u> .
	S 4 S 3 T9S
	1957
	N. 0°15' W., bet. secs. 33 and 34.
	Over gently rolling land.
15.20	Jeep trail, bears irregularly SE. and NW.
40.03	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
•	T8S R27E
a	支
	s 33 s 34
	1969
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
55.30	Small wash, drains irregularly NE.
80.06	The cor. of Secs. 27, 28, 33 and 34, monumented by a wood post, 4 ft. long, 4 ins. square, firmly set in an E-W fence line, scribe marks visible on two faces.
	At the cor. point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E S 28 S 27
	\$ 28 S 27 S 33 S 34
· ·	1969
	Reset the original cor. alongside the iron post.
	Raise a mound of stone W. of the cor.
в	·
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and
	cacti.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°34' W., bet. secs. 27 and 34.
	Over gently rolling land.
39.93	Point for the ½ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E
	$\frac{5}{4}$ $\frac{\text{S }27}{\text{S }34}$
ν .	. 1969
	from which
	A fence, bears N., 20 lks. dist., fence bears E.
	and W.
1	ı

18.

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

		T. 8 S., R. 27 E.
	CHAINS	
		Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
	43.80	Wash, 30 1ks. wide, 4 ft. deep, drains N.
	79.86	The cor. of secs. 27, 28, 33 and 34.
		Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
		N. 0°08' E., bet. secs. 27 and 28.
		Over gently rolling land.
	19 . 90	Wash, 30 1ks. wide, 2 ft. deep, drains irregularly NE.
	21.10	Wash, 60 lks. wide, 4 ft. deep, drains irregularly NE.
	39.49	Point for the ½ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
	2	T8S R27E
		Set a wooden post, 5 ft. long, 4 ins. squared, alongside the iron post.
	77.90	Track road, bears E. and W.
	78.98	The cor. of Secs. 21, 22, 27 and 28, monumented by a wood post, 5 ft. long, 4 ins. square, firmly set, marked NE S 28 on S. face.
	•	At the cor. point
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T8S R27E S 21 S 22 S 28 S 27 1969
-		Reset the orig. cor. alongside the iron post.
		Deposit glass at the base of the iron post.
		Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
		From the cor. of secs. 22, 23, 26 and 27.
	•	S. 89°57' W., bet. secs. 22 and 27.
		Over gently rolling land.
	5.90	Railroad R-O-W fence, bears S. 31°30' E. and N. 31°30' W.
	v	

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

	L. Q.S., K. 2/ L.
 CHAINS	
·7 . 80	Southern Pacific Railroad tracks, bears S. 31°30' E. and N. 31°30' W.
8.30	Telephone line, bears S. 31°30' E. and N. 31°30' W.
15.00	Wash, 200 lks. wide, with 50 ft. banks, drains N. 30° W.
21.10	Wash, 450 lks. wide, with 50 ft. banks, drains NE.
39.90	Point for the ½ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E S 22 S 27 1969
	from which
•	A wooden windmill, bears N. 83°11' W., 5.06 chs. dist.
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
46.40	Center of corral measuring 3.00 chs. by 2.00 chs., with the long side bearing N. 25° E. and S. 25° W.
69.70	Track road, bears N. 80° E. and S. 80° W.
79.80	The cor. of secs. 21, 22, 27 and 28.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	N. 0°02' W., bet. secs. 21 and 22.
	Over gently rolling land.
39.91	Point for the ½ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
•	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S_R27E
•	s 21 s 22 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
	Continue over nearly level land.
79.82	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	·
·	
:	
 1	: !

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8.S., R. 27 E.

		T. 8.S., R. 27 E.
	CHAINS	
		Set the iron post 20 ins. in the ground, brass cap mkd.
	s	T8S R27E S 16 S 15 S 21 S 22 1969
		Deposit glass at the base of the iron post.
	•	Land, gently rolling to nearly level. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
		From the cor. of secs. 14, 15, 22 and 23.
		N. 89°53' W., bet. secs. 15 and 22.
		Over nearly level land.
	22.90	Wash, 30 1ks. wide, 1 ft. deep, drains N. 10° W.
	39.95	Point for the ½ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	ي •	Set the iron post 20 ins. in the ground, brass cap mkd.
	!	T8S R27E 2 S 15 S 22 1969
		Deposit glass at the base of the iron post.
	42.70	Right bank of the San Simon River, 30 ft. high, bears irregularly N. and S.
	48.90	San Simon River (dry), drains irregularly N.
	49.10	Left bank of the San Simon River, 30 ft. high, bears irregularly N. and S.
	54.80	Railroad R-O-W fence, bears S. 31°30' E. and N. 31°30' W.
	5 6. 80	Southern Pacific railroad tracks, bear S. 31°30' E. and N. 31°30' W.
	57.40	Telephone line, bears S. 31°30' E. and N. 31°30' W.
	79.90	The cor. of secs. 15, 16, 21 and 22.
		Land, nearly level. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
	N V	N. 0°02' E., bet. secs. 15 and 16.
		Over nearly level land.

_		1. 0 S., R. 2/ E.
	CHAINS	
	5.90	Wash, 30 1ks. wide, 3 ft. deep, drains NE.
	37.10	Telephone line, bears S. 31°30' E. and N. 31°30' W.
	38.10	Southern Pacific Railroad tracks, bears S. 31°30' E. and N. 31°30' W.
	39.91	Point for the ½ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T8S_R27E
		s 16 s 15 1969
		Set a wooden post, 3 ft. long, 6 ins. squared, alongside the iron post.
	41.20	Railroad R-0-W fence, bears S. 31°30' E. and N. 31°30' W.
	51.60	Small wash, drains irregularly NE.
	56.80	Wash, 30 lks. wide, 1 ft. deep, drains irregularly NE.
	79 . 82	The cor. of secs. 9, 10, 15 and 16, hereinbefore described.
		Land, nearly level. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
		From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 10 ins. above ground, firmly set, brass cap mkd.
		T8S R27E S 32 S 33 S 5 S 4 T9S 1957
		N. 0°03' E., bet. secs. 32 and 33.
		Over gently rolling land.
	2.10	Wash, 10 1ks. wide, 2 ft. deep, drains NE.
	36.40	Jeep trail, bears NE. and SW.
	39.78	Point for the ½ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T8S R27E
		s 32 s 33 1969
	1	1

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

	T. 8 S., R. 2/ E.
CHAINS	
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
79 . 56	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E <u>S 29 S 28</u> S 32 S 33 1969
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 27, 28, 33 and 34.
	S. 89°46' W., bet. secs. 28 and 33.
·	Over gently rolling land.
35.00	Wash, 20 1ks. wide, 1 ft. deep, drains N. 15° E.
39.97	Point for the ½ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E 2 S 28 S 33 1969
	from which
	A fence, bears N., 24 lks. dist., fence, bears E. and W.
	Raise a mound of stone N. of the iron post.
44.40	Wash, 30 lks. wide, 1 ft. deep, drains irregularly NE.
79.94	The cor. of secs. 28, 29, 32 and 33.
,	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	N. 0°10' E., bet. secs. 28 and 29.
	Over gently rolling land.
0.47	Fence, bears E. and W.

23.

	T. 8 S., R. 2/ E.
CHAINS	
14.60	Track road, bears N. 75° E. and S. 75° W.
39.78	Point for the ½ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 23 ins. in the ground, brass cap mkd.
	T8S_R27E
	s 29 s 28 1969
	Set a wooden post, 5 ft. long, 4 ins. diam., alongside the iron post.
63.90	Wash, 30 lks. wide, 1 ft. deep, drains irregularly NE.
79.56 ₂	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E S 20 S 21 S 29 S 28 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
V V	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
•	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°48' W., bet. secs. 21 and 28.
	Over gently rolling land.
19.00	Small wash, drains irregularly N.
22.20	Track road, bears irregularly N. and S.
39.98	Point for the ½ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S.R27E . \$\frac{\sigma 21}{\sigma 28}\$ \$1969
٠	Set a wooden post, 3 ft. long, 4 ins. diam., alongside the iron post.
46.60	Wash, 20 1ks. wide, 1.ft. deep, drains N. 20° W.
	• , .

72.80 79.96	Wash, 50 1ks. wide, 2 ft. deep, drains irregularly N. The cor. of secs. 20, 21, 28 and 29.
79.96	The cor of secs 20 21 28 and 20
	The cor. or sees. 20, 21, 20 and 29.
	Land, gently rolling. Soil, sandy loam. No timber, undergrowth, creosote bush, bunchgrass and cacti.
	N. 0°03' W., bet. secs. 20 and 21.
	Over nearly level land.
20.00	Enter rolling land.
38.50	Enter nearly level land.
39.79	Point for the ½ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S_R27E
	S 20 S 21 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
79.58	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E S 17 S 16 S 20 S 21 1969
	Deposit glass at the base of the iron post.
× .	Land, gently rolling to nearly level. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and
	cacti.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°59' W., bet. secs. 16 and 21.
	Over gently rolling land.
3.10	Wash, 30 1ks. wide, 3 ft. deep, drains irregularly N.
37.80	Wash, 20 1ks. wide, 1 ft. deep, drains NE.
	Point for the 2 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the

	· 1. 0 5., K. 2/ E.
CHAINS	
• •	Set the iron post 20 ins. in the ground, brass cap mkd.
4	T8S R27E
	$\frac{1}{4}$ $\frac{\text{S } 16}{\text{S } 21}$
	1969
	from which
1	A windmill, bears S. 14°25' E., 12.19 chs. dist.
	Deposit glass at the base of the iron post.
46.40	Wash, 50 lks. wide, with 6 ft. banks, drains N. 30° E.
60.20	Wash, 110 1ks. wide, with 7 ft. banks, drains irregular- ly N.
79.92	The cor. of secs. 16, 17, 20 and 21.
	Land, gently rolling.
•	Soil, sandy loam. No timber; undergrowth; creosote bush, bunchgrass and cacti.
	N. 0°04' W., bet. secs. 16 and 17.
	Over nearly level land.
39.79	Point for the ½ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.
İ	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S. R27E
	\$ 17 S 16 1969
	Set a wooden post, 5 ft. long, 4 ins. diam., alongside the iron post.
43.60	Wash, 75 lks. wide, with 5 ft. banks, drains irregularly NE.
63.90	Wash, 90 lks. wide, with 6 ft. banks, drains irregularly NE.
79.58	The cor. of secs. 8, 9, 16 and 17, monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, with a wooden post, projecting 4 ft. above ground, 6 ins. squared, alongside, brass cap mkd.
	T8S R27E
	<u>S 8 S 9</u> S17 S16
	1957
	Land, nearly level and gently rolling.
3	Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and
	cacti.

Dependent Resurvey, Portion of the Subdivisional Lines, . T. 8 S., R. 27 E.

	. T. 8 S., R. 27 E.
CHAINS	
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, firmly set, brass cap mkd.
	T8S R27E
	S31 S32 S 6 S 5
	T9S
	1957
·	North, bet. secs. 31 and 32.
3	Over gently rolling land.
1.80	Fence, bears N. 30° E. and S. 30° W.
22.20	Wash, 10 1ks. wide, 6 ins. deep, drains N. 20° E.
39.73	Point for the ½ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 23 ins. in the ground, brass cap mkd.
	T8S R27E
	\$31 \$32 1969
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
79.46	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R27E
	<u>s 30 s 29 </u>
	S 31 S 32 1969
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
	Land, gently rolling.
	Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89°56' W., bet. secs. 29 and 32.
	Over gently rolling land.
9.00	Wash, 30 lks. wide, 1 ft. deep, drains N.
18.00	Wash, 30 lks. wide, 1 ft. deep, drains N.
37.60	Fence, bears N. 30° E. and S. 30° W.
39.94	Point for the ½ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 22 ins. in the ground, brass cap mkd. T8S R27E
T8S R27E
g 20
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
1969
from which
A fence, bears North, 52 lks. dist., fence bears E. and W.
Wash, 10 1ks. wide, 1 ft. deep, drains irregularly N.
79.88 The cor. of secs. 29, 30, 31 and 32.
Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
N. 89°49' W., bet. secs. 30 and 31.
Over gently rolling land.
11.50 Wash, 20 lks. wide, 1 ft. deep, drains N. curving NE.
Fence, bears N. 40° E., 50 lks. dist. to cor. of fences bearing E., S. 40° W. and W.; and bears S. 40° W., approximately 7.00 chs. dist. to cor. of fences bearing N. 40° E. and S. 5° E.
Point for the k sec. cor. of secs, 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.
Set the iron post 22 ins. in the ground, brass cap mkd.
. T8S R27E
$\frac{1}{4}$ $\frac{\text{S } 30}{\text{S } 31}$
1969
from which
A fence bears N., 50 lks. dist., fence bears E. and W.
Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
45.00 Wash, 10 1ks. wide, 1 ft. deep, drains N. 20° E.
56.00 Wash, 20 lks. wide, 1 ft. deep, drains NE.
78.60 Fence, bears S. and N., 45 lks. dist. to cor. of fences bearing E. and S.
78.78 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., pro-
jecting 8 ins. above ground, firmly set, brass cap mkd.
· moo:
T8S R26E R27E S 25 S 30 S 36 S 31 1957
R26E R27E <u>S 25 S 30</u> S 36 S 31

	. T. 8 S., R. 27 E.
CHAINS	
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 29, 30, 31 and 32.
2	N. 0°11' E., bet. secs. 29 and 30.
	Over gently rolling land.
0.57	Fence, bears E. and W.
9.00	Wash, 20 1ks. wide, 1 ft. deep, drains N. 70° E.
20.20	Track road, bears E. and W.
39.74	Point for the ½ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
* * * * * * * * * * * * * * * * * * *	T8S R27E
63.90	Wash, 10 1ks. wide, 1 ft. deep, drains N. 10° E.
79.48	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E S 19 S 20 S 30 S 29 1969
•	Set a wooden post, 3 ft. long, 4 ins. diam., alongside the iron post.
	Land, gently rolling. Soil, sandy loam. No timber, undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°59' W., bet. secs. 20 and 29.
	Over gently rolling land.
39.92	Point for the ½ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.

		1, 0 0., K, 27 H.
	CHAINS	
		Set the iron.post, 20.insin the ground, brass cap mkd.
		T8S R27E
		½ <u>S 20</u> S 29
		1969
		Set a wooden post, 6 ft. long, 4 ins. diam., alongside the iron post.
	58.60	Wash, 20 lks. wide, 2 ft. deep, drains irregularly NE.
	79.84	The cor. of secs. 19, 20, 29 and 30.
		Land, gently rolling.
		Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote
		bush, bunchgrass and cacti.
		N. 89°45' W., bet. secs. 19 and 30.
		Over gently rolling land.
	9.50	Wash, 30 1ks. wide, 1 ft. deep, drains N.
	39.96	Point for the ½ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T8S R27E
		½ S 19 S 30
		1969
		Deposit glass at the base of the iron post.
	41.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 15° E.
	69.90	Track road, bears irregularly N. and S.
	78 . 92	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 8 ins. above ground, firmly set, brass cap mkd.
		T8S
		R26E R27E S 24 S 19
		S 25 S 30
		1957
		Land, gently rolling. Soil, sandy loam.
		No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
		From the cor. of secs. 19, 20, 29 and 30.
		N. 0°02' E., bet. secs. 19 and 20.
		Over gently rolling land.
		·
- 1		l l

	T. 8 S., R. 27 E.
CHAINS	
.39.74	Point for the ½ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T8S R27E
	$\frac{1}{2}$ S 19 S 20
	1969
	Deposit glass at the base of the iron post.
79.48	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remæining evidence of the orig. cor.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	T8S R27E S 18 S 17 S 19 S 20 1969
	Deposit glass at the base of the iron post.
7 7	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
•	
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°57' W., bet. secs. 17 and 20.
	Over gently rolling land.
29.00	Small wash, drains N.
39.86	Point for the ½ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T8S R27E 2 S 17 S 20 1969
	Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.
50.70	Wash, 15 1ks. wide, 2 ft. deep, drains irregularly N.
64.00	Wash, 20 lks. wide, 1 ft. deep, drains NE.
79.72	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.

Dependent Resurvey, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

	T. 8 S., R. 27 E.
CHAINS	N. 89°39' W., bet. secs. 18 and 19.
5.00	Over gently rolling land.
	Small wash, drains N. 15° W.
31.50	Small wash, drains NE.
39.91	Point for the ½ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.
•	Set the iron post 18 ins. in the ground, brass cap mkd.
	T8S R27E \$\frac{\sigma}{\pi} \frac{\sigma 1969}{\sigma}\$
	Deposit glass at the base of the iron post.
67.70	Track road, bears S. 10° E. and N. 10° W.
78.87	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 10 ins. above ground, firmly set, brass cap mkd.
•	T8S R26E R27E S 13 S 18 S 24 S 19 1957
	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°40' E., bet. secs. 17 and 18.
	Over gently rolling land.
32.70	Wash, 20 lks. wide, 1 ft. deep, drains NE.
36.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.
39.74	The ½ sec. cor. of secs. 17 and 18, monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, brass cap mkd.
	T8S R27E
	s 18 s 17 1957
·	Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.

Retracement, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

	CHAINS	
		Retracement of the Resurvey executed by Donald E. Harding in 1957
		From the cor. of secs. 8, 9, 16 and 17, hereinbefore described.
		N. 89°43' W., bet. secs. 8 and 17.
		Over gently rolling land.
	39 . 97	The $\frac{1}{2}$ sec. cor. of secs. 8 and 17, monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above ground, firmly set, with mound of stone N., brass cap mkd.
		T8S R27E
		支 <u>S 8</u> S17
		1957
	:	S. 89°44' W., beginning new measurement.
	•	Over gently rolling land.
	· 39 . 71	The cor. of secs. 7, 8, 17 and 18, monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, brass cap mkd.
		T8S R27E S 7 S 8 S18 S17 1957
		Land, gently rolling. Soil, sandy loam. No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.
		N. 89°42' W., bet. secs. 7 and 18.
		Over gently rolling land.
	39.77	The ½ sec. cor. of secs. 7 and 18, monumented by an iron post, 2½ ins. diam., projecting 6 ins. above ground, firmly set, brass cap mkd.
		T8S R27E
3	ì	$\frac{1}{4} \frac{\$7}{\$18}$ $\cdot 1957$
		N. 89°44' W., beginning new measurement.
		Over gently rolling land.
	38.92	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 8 ins. above ground, firmly set, brass cap mkd.
		T8S R26E R27E S 12 S 7 S 13 S 18 1957

33.

Retracement, Portion of the Subdivisional Lines, T. 8 S., R. 27 E.

CHAINS

from which

U.S. Soil Erosion Service Triangulation Station "Jones" bears N. 52°18' E., 29.58 chs. dist., monumented by a bronze disk, set in a concrete Post projecting 2 ins. above ground, mkd. 19 Jones 35. Geographic position: Latitude 32°44'51.150" N. and longitude 109°37'30.477" W.

Land, gently rolling. Soil, sandy loam.

No timber; undergrowth, scattered mesquite, creosote bush, bunchgrass and cacti.

General Description

The area encompassed by this survey is nearly level to gently rolling land. Elevations range from about 3060 feet to 3320 feet above sea level. The soil is mostly sandy clay loam. Vegetation consists of creosote bush, bunchgrass, mesquite, cacti and sparse grass.

The San Simon River, which is ordinarily dry, enters the township on the south boundary of section 35, traverses in a north-northwesterly direction, leaving the surveyed area on the north boundary of section 15. The Southern Pacific Railroad enters the township on the south boundary of section 35, traverses in a north-northwesterly direction leaving the surveyed area on the west boundary of section 15.

There is no one living within the area surveyed. The primary use of this land is for grazing.

There is no evidence of mineral activity.

Form 9180-8 (March 1969)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

TILLE ADDITION			
NAMES	CAPACITY		
John H. Witmer	Cadastral Surveyor		
Ray E. Thiessen	Surveying Technician		
Steven J. Hall	Surveying Aid		
Michael L. Minear	Surveying Aid		
Jerrel L. Jones	Surveying Aid		
,			

CERTIFICATE OF SURVEY

, HEREBY (I)(₩g), Louis D. Gilbert CERTIFY upon honor that, in pursuance of special instructions bearing date of the 24th day , 1968 , (I) (We) have made a dependent resurvey and a reof December tracement of a portion of the subdivisional lines, Township 8 South, Range 27 East, Meridian, in the State of Arizona , which of the Gila and Salt are represented in the foregoing field notes as having been executed by (me), (me), and under (my) (886) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes. November 26, 1969 (Cadastral Surveyor) (Date) CERTIFICATE OF APPROVAL SUBMITTED FOR APPROVAL BUREAU OF LAND MANAGEMENT MAR 3 0 1972 Date Washington, D.C. The foregoing field notes of the dependent resurvey and retracement of a portion of the subdivisional lines, Township 8 South, Range 27 East, Gila and Salt River Meridian, Arizona, executed by Louis D. Gilbert having been critically examined and found correct, are hereby approved. SEP 1 1 1972 (Date) CERTIFICATE OF TRANSCRIPT I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)