Form 9180-6 (April 1965) (formerly 4-679)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE SUBDIVISIONAL LINES
SUBDIVISIONAL LINES
TOWNSHIP 34 NORTH, RANGE 11 WEST
Of theMeridian
In the State ofArizona
EXECUTED BY
Jerrold E. Knight Cadastral Surveyor
John H. Witmer Cadastral Surveyor
Under special instructions dated <u>July 24</u> , 19 <u>69</u> , which provided for the survey
included under Group Number 512 , approved July 25, 1969
and assignment instructions dated, approved, 19 69
and assignment instructions dated, 19, 19
Survey commenced September 10 , 1969

November 25

Survey completed _

__, 19 69

B O O K 4 9 4 8

INDEX DIAGRAM

Township 34 Nor			lorth	n 11 West, Range				,				
							_		_			
6	55	5	41	4		32	8	21	2	11	1	
53		53		40			31		21	 	10	
7	51	8	39	9		30	10	20	11	9	12	
50		50		38			29		19		8	
18	49	17	37	16		28	15	18	14	7	13	
48		47		37			28	 	17	 	6	
19	46	20	36	21		27	22	16	23	5	24	
45		44		35			26		16		4	
									-			
30	43	29	34	28		25	27	14	26	3	25	
42				33			24	 	14	 	3	
31		32		33		23	84	12	35	1	36	

Township 34 North, Range 11 West Gila and Salt River Meridian, Arizona

CHAINS

The east boundary was surveyed in 1917-21 by D. R. Averill. The south boundary was surveyed in 1917 by W. H. Thorn and L. E. Sechrist.

The north boundary was surveyed in 1924 by W. E. Hiester and $C.\ E.\ Hunter.$

The west boundary was surveyed in 1926 by B. J. Kinsey. Section 32 was surveyed in 1956 by P. K. Russell.

The following notes are those of the completion survey of the subdivisional lines of Township 34 North, Range 11 West, G&SRM, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 and the Special Instructions dated July 24, 1969.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner is monumented with a standard iron post, 30 ins. long, 2½ ins. in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township, as determined by traverse from USC&GS Triangulation Station "North", located in section 33, T. 34 N., R. 11 W. is: Latitude 36°17'45.0" North and Longitude 113°24'51.0" West.

The mean magnetic declination was found to be 15° East.

Subdivision, T. 34 N., R. 11 W., G&SRM, Arizona

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.

T34N R11W S35 S36 S 2 S 1 T33N 1917

from which the original bearing trees:

A cedar, 12 ins. diam., bears N. $76\frac{3}{4}$ ° E., 441 lks. dist., mkd. T34N R11W S36 BT.

A cedar, 12 ins. diam., bears S. 56% E., 191 1ks. dist., mkd. T33N R11W S1 BT. (Record S. 36% E.).

A dead cinchona, 4 ins. diam., bears S. 12¾° W., 360 lks. dist., mkd. T33N R11W S2 BT.

A cedar, 15 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 225 lks. dist., mkd. T34N R11W S35 BT.

N. $0^{\circ}01^{\circ}$ W., bet. secs. 35 and 36.

CHAINS	
	Over rolling land, through scattered timber and medium undergrowth.
6.80	Track road, bears S. 75° E. and N. 75° W.
40.00	Point for the 1/2 sec. cor. of secs. 35 and 36.
٠	Set the iron post 22 ins. in the ground, brass cap mkd.
	T34N R11W
	S35 S36 1969
	from which
	A pine, 12 ins. diam., bears S. 41° E., 60 lks. dist., mkd. $\frac{1}{2}$ S36 BT.
	A juniper, 12 ins. diam., bears S. 35° W., 53 lks. dist., mkd. ½ S35 BT.
	Raise a mound of stone W. of the cor.
69.50	Desc. over N. slope.
74.90	Small canyon, drains NE.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
•	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W <u>S26 S25</u> S35 S36 1969
	from which
	A juniper, 11 ins. diam., bears N. 35½° E., 17 1ks. dist., mkd. T34N R11W S25 BT.
	A juniper, 11 ins. diam., bears S. 42° E., 41 lks. dist., mkd. T34N R11W S36 BT.
	A pinon, 13 ins. diam., bears S. 32½° W., 90 lks. dist., mkd. T34N R11W S35 BT.
	A juniper, 8 ins. diam., bears N. 88° W., 66 lks. dist., mkd. T34N R11W S26 BT.
	Land, rolling. Soil, rocky sandy loam.
	Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	• • • • • • • • • • • • • • • • • • • •

CHAINS	T
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T34N R11W R10W S25 S30 S36 S31 1917
	from which the original bearing trees:
	A pinon, 19 ins. diam., bears S. 25% E., 99 lks. dist., mkd. T34N R10W S31 BT.
	A pinon, 20 ins. diam., bears S. 17° W., 113 lks. dist., mkd. T34N R11W BT. No other mks. legible.
	N. 89°46' W., bet. secs. 25 and 36.
	Over rolling land, through scattered timber and undergrowth.
8.30	Narrow rocky spur, slopes N.
36.40	Spur, slopes N.; descend steep W. slope.
40.02	Point for the ½ sec. cor. of secs. 25 and 36.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W ½ <u>S25</u> S36 1969
	No suitable bearing trees available.
43.00	Deep ravine, drains NE.; ascend steep E. slope.
54.80	Spur, slopes NE.
63.70	Ravine, drains N.
68,70	Spur, slopes N.
76.20	Small canyon, drains N.; ascend E. slope.
80.04	The cor. of secs. 25, 26, 35 and 36.
ς•	Land, rolling. Soil, rocky, sand and clay. Timber, scattered pinon and juniper. Undergrowth, sagebrush, cacti and grama grass.
	N. 0°01' W., bet. secs. 25 and 26.
	Over rolling land, through scattered timber and under- growth.

CHAINS	
15.80	Wash, 15 lks. wide, 2 ft. deep, drains E., 80 lks. dist., thence N. 30° E.
27.40	Wash, 30 1ks. wide, 4 ft. deep, drains E.
40.00	Point for the ½ sec. cor. of secs. 25 and 26.
	Set the iron post 8 ins. in the ground to solid rock, mound of stone to top, brass cap mkd.
	T34N R11W
	\$26 \$25 1969
•	No suitable bearing trees available.
54.80	Track road, bears E. and W.
68.60	Wash, 10 1kś. wide, 1 ft. deép, drains E.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 12 ins. in the ground to bed rock, mound of stone to top, brass cap mkd.
1	T34N R11W S23 S24 S26 S25 1969
	from which A juniper, 9 ins. diam., bears N. 2½° E., 44 lks. dist., mkd. T34N R11W S24 BT.
	A juniper, 3 ins. diam., bears S. 45%° E., 65 lks. dist., mkd. X BT.
	A juniper, 9 ins. diam., bears S. 17° W., 62 1ks. dist., mkd. T34N R11W S26 BT.
	Land, rolling. Soil, limestone, sand and clay. Timber, scattered juniper and pinon. Undergrowth, cacti, grama grass and sagebrush.
	From the true point for the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp. in Parashant Canyon.
	from which
	The Witness cor., bears South, 10.00 chs. dist., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	W C T 34 N R11 W R10 W S24 S19 S25 S30 1921

35.00 38.50 40.00	N. 89°54' W., bet. secs. 24 and 25. By triangulation, asc. over walls of Parashant Canyon, through widely scattered timber. Leave canyon, enter rolling land, bears SE. and NW.
38.50	By triangulation, asc. over walls of Parashant Canyon, through widely scattered timber.
38.50	through widely scattered timber.
38.50	Leave canyon, enter rolling land, bears SE. and NW.
40.00	End of triangulation.
	Point for the ½ sec. cor. of secs. 24 and 25.
	Set the iron post 9 ins. in the ground, mound of stone to top, brass cap mkd.
,	T34N R11W
	$\frac{1}{4} \frac{\frac{\text{S}24}{\text{S}25}}{}$
	1969
	from which
	A juniper, 14 ins. diam., bears S. 82칯° W., 93 lks. dist., mkd. 칯 S25 BT.
	No other suitable bearing trees available.
46.60	Wash, 40 lks. wide, with 8 ft. banks, drains N.
50.60	Top of steep ledge, bears SE. and NW.
57.20	Wash, 30 lks. wide, 2 ft. deep, drains N. for 40 lks. dist., thence NE.
65.30	Top of steep rocky ledge, bears SE. and NW.
80.00	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling in W. ½ and steep canyon in E. ½. Soil, rocky, sand and clay. Timber, scattered juniper.
	Undergrowth, sagebrush, grama grass and cacti.
	N. 0°01' W., bet. secs. 23 and 24.
	Over gently rolling land, through medium timber and undergrowth.
22.30	South rim of a canyon, bears E. and W.; continue measurement using geodimeter, topography estimated.
34.00	Bottom of a deep canyon, drains E.
40.00	True point for the ½ sec. cor. of secs. 23 and 24, falls on a vertical rock cliff where a cor. cannot be perpetuated.
46.00	Point selected for the Witness $\frac{1}{2}$ sec. cor. of secs. 23 and 24.

	Subdivision, T. 34 N., R. 11 W.
CHAINS	
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	W C
	s23 Js24
	1969
	Thence, by chaining.
47.00	Spur, slopes E., desc. steep N. slope.
58.00	Bottom of a canyon, drains E.; ascend steep S. slope.
74.00	Spur, slopes E., descend steep N. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W <u>S14 S13</u> S23 S24 1969
	Land, mountainous with deep canyons. Soil, rocky, sand and clay. Timber, scattered juniper and pinon.
	Undergrowth, sagebrush and grama grass.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	т34м
	R11W R10W S13 S18
	S24 S19 1917
	from which the original bearing trees:
	A juniper, 11 ins. diam., bears N. 38° E., 178 1ks. dist., mkd. T34N R10W S18 BT.
	A juniper, 14 ins. diam., bears S. $10\frac{1}{2}$ ° E., 236 lks. dist., mkd. T34N R10W S19 BT.
	A juniper, 11 ins. diam., bears N. 62¾° W., 248 lks. dist., mkd. T34N R11W S13 BT.
	N. 89°39' W., bet. secs. 13 and 24.
,	Over rolling land through scattered timber and undergrowth.

		Subdivision, T. 34 N., R. II W.
	CHAINS	
	13.60	Wash, 20 1ks. wide, 8 ft. banks, drains SW.
e e	37.38	East rim of Parashant Canyon, bears N. and SE.; thence by triangulation, descend over steep W. slope.
	39.49	Point selected for the Witness $\frac{1}{2}$ sec. cor. of secs. 13 and 24.
	,	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W
		$\frac{1}{4}$ $\stackrel{\text{S13}}{\stackrel{\text{W}}{\text{S24}}}$ $\stackrel{\text{C}}{\stackrel{\text{C}}{\text{C}}}$
١		\$ \$24 C 1969
		1909
	39.99	True point for the ½ sec. cor. of secs. 13 and 24, falls on a steep ledge facing W. where the monument cannot be perpetuated.
	•	Thence by triangulation.
	70.00	Estimated location of Parashant Wash, 50 ft. deep (box canyon), 200 lks. wide, drains irregularly SE.; ascend steep NE. slope.
	79:98	The cor. of secs. 13; 14, 23 and 24; end of triangulation.
		Land, mountainous with deep canyons.
	•	Soil, rocky loam.
		Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		N. 0°01' W., bet. secs. 13 and 14.
		Over steep broken S. slope of Parashant Canyon, measurements by geodimeter, topography estimated.
	7.00	Parashant Wash, 150 lks. wide, with vertical walls 50 ft. high; drains irregularly E.
	12.00	Spur, slopes W.
	22.00	Parashant Wash, 150 lks. wide, with vertical walls 50 ft. high, drains SW.; asc. steep S. slope.
	40.00	True point for the ½ sec. cor. of secs. 13 and 14 falls on the vertical face of a rock 10 ft. high, where the monument cannot be perpetuated.
	40.10	Point selected for the Witness & sec. cor. of secs. 13 and 14.
		Set the iron post over an "X" cut into solid rock, mound of stone to top, brass cap mkd.
		T34N R11W
		W C S14 S13 1969

_		Subdivision, T. 34 N., R. II W.
	CHAINS	
	43.86	End of measurement by Geodimeter, on the N. rim of Parashant Canyon, rim bears S. 70° E. and N. 70° W., thence over gently rolling land, through scattered timber
	46.50	Track road, bears irregularly SE. and NW.
	76 . 70	Same track road, bears irregularly NE. and SW.
	80,00	Point for the cor. of secs. 11, 12, 13 and 14.
		Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W <u>S11 S12</u> S14 S13 . 1969
	,	from which
		A pinon, 10 ins. diam., bears N. 8%° E., 137 lks. dist., mkd. T34N R11W S12 BT.
)	A juniper, 9 ins. diam., bears S. 45½° E., 107 lks. dist., mkd. T34N R11W S13 BT.
	,	A pinon, 6 ins. diam., bears S. 29% W., 39 lks. dist., mkd. T34N R11W S14 BT.
		A pinon, 8 ins. diam., bears N. $41\frac{1}{2}^{\circ}$ W., 40 lks. dist., mkd. T34N R11W S11 BT.
		Land, rolling with deep canyons. Soil, rocky, sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	-	T34N R11W R10W S12 S 7 S13 S18 1917
	* -	from which original bearing trees:
		A juniper, 12 ins. diam., bears N. 62° E., 58 lks. dist., mkd. T34N R10W S7 BT.
		A juniper, 9 ins. diam., bears S. 53° W., 59

A juniper, 9 ins. diam., bears S. 53° W., 59 lks. dist., mkd. T34N R11W S13 BT.

A juniper, 11 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ W., 36 lks. dist., mkd. T34N R11W S12 BT.

An earthen stock tank, bears N. $43^{\circ}22^{\circ}$ W., 24.76 chs. distance.

Subdivision, T. 34 N., R. 11 W.

8.10 15.40 26.60 36.90	N. 89°39' W., bet. secs. 12 and 13. Over rolling land, through scattered timber and undergrowth. Track road, bears irregularly SE. and NW. Ridge, bears N. and S. Rocky wash, 30 lks. wide, with 8 ft. banks, drains SW. Wash, 20 lks. wide, with 10 ft. banks, drains S., 50 lks. dist., then S. 60° W. Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
8.10 15.40 26.60 36.90	Over rolling land, through scattered timber and undergrowth. Track road, bears irregularly SE. and NW. Ridge, bears N. and S. Rocky wash, 30 lks. wide, with 8 ft. banks, drains SW. Wash, 20 lks. wide, with 10 ft. banks, drains S., 50 lks. dist., then S. 60° W. Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
8.10 15.40 26.60 36.90	growth. Track road, bears irregularly SE. and NW. Ridge, bears N. and S. Rocky wash, 30 lks. wide, with 8 ft. banks, drains SW. Wash, 20 lks. wide, with 10 ft. banks, drains S., 50 lks. dist., then S. 60° W. Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
15.40 26.60 36.90	Ridge, bears N. and S. Rocky wash, 30 lks. wide, with 8 ft. banks, drains SW. Wash, 20 lks. wide, with 10 ft. banks, drains S., 50 lks. dist., then S. 60° W. Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
26.60 36.90	Rocky wash, 30 lks. wide, with 8 ft. banks, drains SW. Wash, 20 lks. wide, with 10 ft. banks, drains S., 50 lks. dist., then S. 60° W. Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
36.90	Wash, 20 1ks. wide, with 10 ft. banks, drains S., 50 1ks. dist., then S. 60° W. Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
,	Point for the ½ sec. cor. of secs. 12 and 13. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
40.03	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	to top, brass cap mkd.
	T34N R11W
,	
	$\frac{1}{4} \frac{\text{S12}}{\text{S13}}$ 1969
	from which
	A juniper, 9 ins. diam., bears S. 45¾° E., 85 lks. dist., mkd. ½ S13 BT.
	A juniper, 4 ins. diam., bears N. 34½° W., 69 lks. dist., mkd. X BT.
47.40	Jeep trail, bears N. and S.
76.50	Track road, bears NE. and SW.
80.06	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Soil, rocky, sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	N. 0°01' W., bet. secs. 11 and 12.
•	Over rolling land, through scattered timber and under- growth.
4.08	By triangulation, desc. steep NW. slope.
į	Wash, in the bottom of a canyon, 50 lks. wide, 5 ft. deep, drains W., 3.00 chs. dist., thence S. 10° W.; ascend steep S. slope.
29.91	End of triangulation, on a low spur sloping E.
	Same wash, in the bottom of a canyon, 50 lks. wide, 3 ft. deep, drains E., 3.00 chs. dist. curving irregularly S.
37.20	Wash, 10 lks. wide, 3 ft. deep, drains SW.

\neg		
	CHAINS	
	40.00	Point for the ½ sec. cor. of secs. 11 and 12.
		Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W
		S11 S12 1969
		from which
	9	A pinon, 12 ins. diam., bears N. 55½° E., 77 lks. dist., mkd. ½ S12 BT.
		A pinon, 14 ins. diam., bears S. 37½° W., 87 lks. dist., mkd. 첫 Sll BT.
	40.70	Spur, slopes S. 50° W.; desc. steep NW. slope.
	47.10	Wash, in bottom of canyon, 50 lks. wide, with 5 ft. banks, drains S. 35° W., ascend steep SE. slope.
	58.70	Spur, slopes E., desc. steep N. slope.
	62.70	Wash, 30 lks. wide, 4 ft. deep, drains N. 70° E.; ascend steep S. slope.
	67.50	South rim of mesa, bears E. and W.
	80.00	Point for the cor. of secs. 1, 2, 11 and 12.
		Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W <u>S 2 S 1</u> S11 S12 1969
		from which
		A juniper, 8 ins. diam., bears N. 5° E., 99 1ks. dist., mkd. T34N R11W S1 BT.
		A juniper, 8 ins. diam., bears S. 67° W., 81 lks. dist., mkd. T34N R11W S11 BT.
		A juniper, 9 ins. diam., bears N. 81° W., 100 lks. dist., mkd. T34N R11W S2 BT.
		Land, rolling with deep canyons. Soil, rocky, sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	,	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, brass cap mkd.

11.

Subdivision, T. 34 N., R. 11 W.

CHAINS	T
	T34N R11W R10W S 1 S 6 S12 S 7
	1917
	from which the original bearing trees: A juniper, 8 ins. diam., bears N. 89° E., 142
	lks. dist., mkd. T34N R10W S6 BT.
	A juniper, 11 ins. diam., bears S. 32° E., 82 1ks. dist., mkd. T34N R10W S7 BT.
	A juniper, 18 ins. diam., bears N. 15° W., 190 lks. dist., mkd. T34N R11W S1 BT.
	N. 89°39' W., bet. secs. 1 and 12.
	Over gently rolling land through railed area.
3.00	Leave railed area, enter scattered timber, bears N. and S.
7.00	Track road, bears N. and S.
40.02	Point for the ½ sec. cor. of secs. 1 and 12.
	Set the iron post over an "X" cut into solid rock, mound of stone to top, brass cap mkd.
	T34N_R11W
	$\frac{1}{4} \frac{S}{S12}$ 1969
*	No suitable bearing trees available.
48.00	Wash, 20 1ks. wide, 2 ft. deep, drains W.
54.90	Same wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.
55.20	Fence, bears N. and S.
61.40	Wash, 50 lks. wide, 4 ft. deep, drains S.; ascend steep E. slope.
64.10	Spur, slopes S.
80.04	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, rocky, sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	North, bet. secs. 1 and 2.
	Over rolling land, through scattered timber and undergrowth.

CHAINS	
40.00	Point for the ½ sec. cor. of secs. 1 and 2.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	S 2 S 1 1969.
	from which
	A juniper, 6 ins. diam., bears S. 27° E., 68 lks. dist., mkd. ½ Sl BT.
	A juniper, 7 ins. diam., bears N. 31½° W., 61 lks. dist., mkd. ½ S2 BT.
40.80	Wash, 10 lks. wide, 1 ft. deep, drains E.
59.70	Wash, 10 1ks. wide, 2 ft. deep, drains N. 70° E.
79.49	Fence, bears E. and W.
79.50	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, brass cap mkd.
	T35N R11W <u>S35 S36</u> S 2 S 1 T34N 1924
<u>.</u>	from which the original bearing trees:
	A cedar, 16 ins. diam., bears N. 29° E., 124 1ks. dist., mkd. T35N R11W S36 BT.
,	A cedar, 15 ins. diam., bears S. 69° E., 60 lks. dist., mkd. T34N R11W S1 BT.
	A cedar, 8 ins. diam., bears S. $45\frac{1}{4}^{\circ}$ W., 93 lks. dist., mkd. with an overgrown blaze.
	A cedar, 13 ins. diam., bears N. 45° W., 164 lks. dist., mkd. with an overgrown blaze.
	Land, rolling. Soil, rocky, sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a collar of stone, brass cap mkd.
	T34N R11W S34 S35 S 3 S 2 T33N 1917
1	

Subdivision, T. 34 N., R. 11 W.

CHAINS	T
	from which the original bearing trees:
	A cedar, 12 ins. diam., bears N. 34° E., 182 1ks. dist., mkd. T34N R11W S35 BT.
	A cedar, 11 ins. diam., bears S. 19° E., 102 lks. dist., mkd. T S2 BT visible; blaze partially healed.
	A cedar, 13 ins. diam., bears S. 81½° W., 318 1ks. dist., mkd. T33N R11W S3 BT.
	A cedar, 14 ins. diam., bears N. 35% W., 442 1ks. dist., mkd. T34N R11W S34 BT.
	N. 0°01' W., bet. secs. 34 and 35.
	Over gently rolling land through dense timber.
2.30	Wash, 20 1ks. wide, 1 ft. deep, drains E.
22.70	Wash, 10 lks. wide, with 4 ft. banks, drains NE.
40.00	Point for the ½ sec. cor. of secs. 34 and 35.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	\$34 S35
	1969
<u> </u>	from which
	A juniper, 6 ins. diam., bears N. 76½° E., 46 lks. dist., mkd. ½ S35 BT.
u	A juniper, 10 ins. diam., bears S. 53½° W., 49 lks. dist., mkd. ½ S34 BT.
`	An earthen stock tank, bears S. 47°20' E., 53.40 chs. dist.
41.60	Track road, bears N. 80° E. and S. 80° W.
45.40	Track road, bears SE. and NW.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W S27 S26 S34 S35 1969
	from which
	A juniper, 4 ins. diam., bears N. 74½° E., 96 lks. dist., mkd. X BT.

	Subdivision, T. 34 N., R. II W.
CHAINS	
	A juniper, 4 ins. diam., bears S. $48\frac{1}{2}$ ° E., 99 lks. dist., mkd. X BT.
	A juniper, 6 ins. diam., bears S. 44% W., 55 lks. dist., mkd. T34N R11W S34 BT.
	A juniper, 15 ins. diam., bears N. 89½° W., 281 lks. dist., mkd. T34N R11W S27 BT.
٠	Land, gently rolling. Soil, sandy, clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°55' W., bet. secs. 26 and 35.
	Ascend over steep E. slope, through scattered timber.
3.50	Ridge, bears N. and S.
29.60	Ridge, bears N. and S.
40.01	Point for the ½ sec. cor. of secs. 26 and 35.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	<u> </u>
	³ S35 1969
	from which
	A pinon, 12 ins. diam., bears S. 13° E., 80 lks. dist., mkd. ½ S35 BT.
3	A juniper, 8 ins. diam., bears N. 38° W., 56 lks. dist., mkd. ½ S26 BT.
66.60	Wash, 20 lks. wide, 1 ft. deep, drains N., 130 lks. dist., thence easterly.
80.02	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, rocky clay loam. Timber, medium juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	N. 0°01' W., bet. secs. 26 and 27.
!	Over rolling land, through medium timber and undergrowth.
1.80	Wash, 10 lks. wide, 1 ft. deep, drains E.
,	

CHAINS	
9 00	Week 20 lkg gride 1 55 days during B
8.00	Wash, 20 lks. wide, 1 ft. deep, drains E.
27.40	Draw, drains S. 40° E.
29.10	Track road, bears NE. and SW.
40.00	Point for the ½ sec. cor. of secs. 26 and 27.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	\$27 \sqrt{\$26} 1969
	from which
	A juniper, 7 ins. diam., bears S. $52\frac{1}{2}^{\circ}$ E., 77 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	A juniper, 8 ins. diam., bears S. 52½° W., 87 lks. dist., mkd. ½ S27 BT.
43.60	Wash, 10 lks. wide, 2 ft. deep, drains E.
49.10	Ridge, bears E. and W., desc. N. slope.
65.50	Wash, 20 lks. wide, 2 ft. deep, drains S. 80° E., 3.00 chs. dist., thence NE.
79.20	Wash, 15 lks. wide, 4 ft. deep, drains N. 40° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T34N R11W <u>S22 S23</u> <u>S27 S26</u>
	1969
	from which
	A juniper, 6 ins. diam., bears S. 30% E., 85 lks. dist., mkd. T34N R11W S26 BT.
y	A juniper, 8 ins. diam., bears S. 22° W., 33 lks. dist., mkd. T34N R11W S27 BT.
	A juniper, 12 ins. diam., bears N. $58\frac{1}{2}^{\circ}$ W., 141 lks. dist., mkd. T34N R11W S22 BT.
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky clay loam. Timber, medium juniper and pinon.

	Subdivision, 1. 54 N., K. II W.
CHAIN	S
	From the cor. of secs. 23, 24, 25 and 26.
	N. 89°52' W., bet. secs. 23 and 26.
	Over rolling land through medium timber and undergrowth.
8.9	O Leave medium timber, enter scattered timber, bears N. and S.
40.0	Point for the ½ sec. cor. of secs. 23 and 26.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	$\frac{1}{4} \frac{S23}{S26}$
	1969
,	No suitable bearing trees available.
43.8	O Track road, bears N. and S.
50.8	0 Wash, 15 lks. wide, 1 ft. deep, drains S.
59.2	0 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
67.0	Wash, 10 lks. wide, 1 ft. deep, drains S.
72.0	Wash, 10 1ks. wide, 1 ft. deep, drains S. 20° W.
74.7	Base of a rock cliff 10 ft. high, on a spur sloping S., bears E. and W.; desc. steep SW. slope.
80.0	The cor. of secs. 22, 23, 26 and 27.
•	Land, rolling and broken. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	N. 0°01' W., bet. secs. 22 and 23.
0	Over rolling land through scattered timber, along a steep W. slope.
3.7.0	Point selected for the Witness ½ sec. cor. of secs. 22 and 23.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	T34N R11W
	s22 ↑ s23
	W C 1969
37.3	Thence by triangulation, desc. over broken land, draining NE. into a canyon; topography estimated.
1	

	Subdivision, T. 34 N., R. 11 W.
CHAINS	
40.00	True point for the ½ sec. cor. of secs. 22 and 23 falls on sheer cliff facing NW., where the monument cannot be perpetuated.
50.00	Wash, in bottom of canyon, 100 lks. wide, 1 ft. deep, drains NE.
64.00	Spur, slopes E.
71.80	Draw, drains E.
79.63	End of triangulation.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post over an "X" cut into solid rock, mound of stone to top, brass cap mkd.
	T34N R11W <u>S15 S14</u> S22 S23 1969
	No suitable bearing trees available.
·	Land, rolling and broken. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
•	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°54' W., bet. secs. 14 and 23.
	Over the broken S. side of Parashant Wash. Dist. by triangulation and Geodimeter. Topography estimated.
38.13	Point selected for the Witness ½ sec. cor. of secs. 14 and 23.
	Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W ½ S14 S23 1969
	The cor. is located on a spur sloping N.
	No suitable bearing trees available.
40.03	True point for the ½ sec. cor. of secs. 14 and 23 falls on a steep NW. slope where the monument cannot be perpetuated.
49.80	Wash, in bottom of canyon, 140 lks. wide, 10 ft. deep, drains NE.; ascend steep SE. slope.
69.80	Leave broken land, enter rolling land, bears N. 10° E. and S. 10° W.

٦	CHAINS	
	78.53	End of Geodimeter and triangulation.
	80.06	The cor. of secs. 14, 15, 22 and 23.
		Land, broken and rolling. Soil, rocky clay loam. Timber, widely scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		N. 0°01' W., bet. secs. 14 and 15.
		Over rolling land through scattered timber.
	25.90	South rim of Parashant Canyon, bears NW. and SE., desc. steep N. slope.
	40.00	Point for the ½ sec. cor. of secs. 14 and 15.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T34N R11W
		. S15 S14 1969
		from which
		A pinon, 12 ins. diam., bears N. 67° E., 12 1ks. dist., mkd. 支 S14 BT.
		A pinon, 10 ins. diam., bears N. 74° W., 57 lks. dist., mkd. ½ S15 BT.
		Raise a mound of stone W. of the cor.
	•	The cor. is located on a low spur sloping N.
	50.00	Parashant Wash, 150 lks. wide, 10 ft. deep, drains irregularly SE., ascend steep S. slope.
	65.90	North rim of Parashant Canyon, bears SE. and NW.; enter rolling land.
	80.00	Point for the cor. of secs. 10, 11, 14 and 15.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T34N R11W S10 S11 S15 S14 1969
		from which
		A juniper, 8 ins. diam., bears N. 81½° E., 135 1ks. dist., mkd. T34N R11W S11 BT.
	•	A juniper, 8 ins. diam., bears S. 60½° E., 57 lks. dist., mkd. T34N R11W S14 BT.
	a	

CHAINS	
	A juniper, 11 ins. diam., bears S. 73½° W., 119 lks. dist., mkd. T34N R11W S15 BT.
	Raise a mound of stone W. of the cor.
	Land, rolling and broken.
8	Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89°51' W., bet. secs. 11 and 14.
	Over broken land, through scattered timber.
	Dist. by Geodimeter, topography estimated.
3.00	East rim of canyon bears N. and S.; desc. about 300 ft. over steep W. slope.
10.00	Wash, in bottom of canyon, 100 lks. wide, with 10 ft. banks, drains S. 30° W.; ascend steep E. slope.
35.00	Spur, slopes SE.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.
•	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W 2 S11 S14 1969
	from which
	A pinon, 10 ins. diam., bears S. 82° W., 62 lks. dist., mkd. ½ S14 BT.
•	No other bearing trees available.
48.00	Wash, 50 lks. wide, with 10 ft. banks, drains SE.
57.61	End of Geodimeter measurement, thence over rolling land.
74.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.
79.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 25° E.
80.04	The cor. of secs. 10, 11, 14 and 15.
^	Land, broken and rolling. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.

	CHAINS	
		N. 0°01' W., bet. secs. 10 and 11.
		Over rolling land, through scattered timber and undergrowth.
	4.80	Spur, slopes SE.
	21.50	South rim of a canyon, bears E. and W.; desc. N. slope.
	25.60	Wash, 10 1ks. wide, 2 ft. deep, drains E.
	27.70	Wash, 30 lks. wide, 4 ft. deep, drains S. 60° E.; ascend S. slope.
	32.50	N. rim of canyon, bears E. and W.; enter gently rolling land.
	40.00	Point for the ½ sec. cor. of secs. 10 and 11.
	2	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	^	T34N R11W
		\$10 S11 1969
		from which
		A juniper, 9 ins. diam., bears N. 9½° E., 86 lks. dist., mkd. 첫 S11 BT.
		A juniper, 8 ins. diam., bears N. 44° W., 90 lks. dist., mkd. ½ S10 BT.
		Leave scattered timber, enter medium timber, bears E. and W.
	61.60	Wash, 20 1ks. wide, 2 ft. deep, drains S. 80° E.
	80.00	Point for the cor. of secs. 2, 3, 10 and 11.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T34N R11W S 3 S 2 S10 S11 1969
		from which
		A juniper, 7 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ E., 33 lks. dist., mkd. T34N R11W S2 BT.
		A juniper, 6 ins. diam., bears S. $52\frac{1}{2}^{\circ}$ E., 100 lks. dist., mkd. T34N R11W S11 BT.
		Raise a mound of stone W. of the cor.
1	i	

		. Subdivision, 1 34 N., K. II W.
	CHAINS	
	,	Land, gently rolling. Soil, sandy clay loam. Timber, scattered to moderate juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 1, 2, 11 and 12.
		N. 89°52' W., bet. secs. 2 and 11.
	!	Over rolling land, through medium timber and undergrowth.
	2.10	Enter scattered timber, bears N. and S.; descend steep SW. slope.
	7.20	Wash, 25 lks. wide, with 5 ft. banks, drains S. 30° E.; ascend steep NE. slope.
	14.20	Spur, slopes N.; enter gently rolling land.
	40.03	Point for the 1/2 sec. cor. of secs. 2 and 11.
		Set the iron post 24 ins. in the ground, brass cap mkd.
•	•	T34N R11W 大 S 2 S11 1969
	,	from which
		A pine, 14 ins. diam., bears S. 81° E., 150 lks. dist., mkd. ½ S11 BT.
		A pine, 8 ins. diam., bears S. 44½° W., 99 lks. dist., mkd. ½ Sll BT.
		No suitable bearing trees near in section 2.
١		Raise a mound of stone N. of the cor.
	51.40	Wash, 10 1ks. wide, 3 ft. deep, drains S. 25° W.
	54.90	Wash, 10 1ks. wide, 2 ft. deep, drains SE.
	80.06	The cor. of secs. 2, 3, 10 and 11.
		Land, rolling in E. ½, gently rolling in remainder. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		N. 0°01' E., bet. secs. 2 and 3.
	₹*	Over gently rolling land, through scattered timber.
	1.70	Track road, bears N. 20° E. and S. 20° W.
	10.70	Same track road, bears S. 20° E. and N. 20° W.

	CHAINS	
	25.70	Same track road, bears N. 70° E. and S. 70° W.
	40.00	Point for the ½ sec. cor: of secs. 2 and 3.
		Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W
,		s 3 s 2 1969
		from which
		A juniper, 10 ins. diam., bears N. 72½° E., 63 lks. dist., mkd. ½ S2 BT.
		A juniper, 8 ins. diam., bears S. 17½° W., 81 lks. dist., mkd. ½ S3 BT.
		Leave scattered timber, enter medium timber, bears E. and W.
	43.50	Draw, drains N. 80° E.
	69.00	Wash, 15 lks. wide, with 5 ft. banks, drains E.
	74.00	Graded road to Salt Springs, bears N. 70° E. and S. 70° W
	76.00	Old abandoned road, bears N. 65° E. and S. 65° W.
	78.20	Wash, 10 1ks. wide, with 4 ft. banks, drains N. 70° E.
	79.20	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., firmly set, projecting 14 ins. above ground, brass cap mkd.
		T35N R11W <u>S34 S35</u> S 3 S 2 T34N 1924
		from which the remains of the original bearing trees:
		A juniper, 12 ins. diam., bears N. 52½° E., 231 1ks. dist., mkd. T35N R11W S35 BT.
		A juniper, 12 ins. diam., bears S. 2½° E., 253 lks. dist., scribe mks. visible but illegible.
		A juniper, 8 ins. diam., bears S. $48\frac{1}{2}^{\circ}$ W., 70 lks. dist., mkd. with an overgrown blaze.
		A stump hole with a fallen tree, 12 ins. diam., lying alongside, bears N. 4° W., 204 lks. dist., tree mkd. with a rotted out blaze.
		• • • • • • • • • • • • • • • • • • • •

CHAINS	
	Land, gently rolling. Soil, rocky clay loam. Timber, medium juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
e	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
,	T34N R11W <u>\$33 \$34</u> \$ 4 \$ 3 T33N 1917
	from which the original bearing trees:
	A juniper, 20 ins. diam., bears N. 82° E., 106 lks. dist., mkd. T34N R11W S34 BT.
	A pinon, 12 ins. diam., bears S. 84° E., 31 1ks. dist., mkd. T33N R11W S3 BT.
	A pinon, 13 ins. diam., bears S. 3½° W., 30 1ks. dist., mkd. T33N R11W S4 BT.
	A juniper, 12 ins. diam., bears N. 60° W., 83 lks. dist., mkd. T34N R11W S33 BT.
	N. 0°02' W., bet. secs. 33 and 34.
	Over mountainous land, through dense timber.
3.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 15° E.
18.30	Rock ledge, bears E. and W.; descend steep N. slope.
26.90	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E., 50 lks. dist., thence irregularly N.
40.00	Point for the ½ sec. cor. of secs. 33 and 34.
	Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.
	T34N R11W
	s33 s34 · · · · · · · · · · · · · · · · · · ·
	from which
	A pinon, 6 ins. diam., bears S. 28° E., 56 lks. dist., mkd. 눛 S34 BT.
	A pinon, 10 ins. diam., bears S. 40° W., 73 1ks. dist., mkd. 눛 S33 BT.
	Raise a mound of stone W. of the cor.

CHAINS	
46.00	Leave mountainous land, enter Jagwey Valley, bears S. 40° E. and N. 70° W.
53.20	Wash, 20 1ks. wide, 2 ft. deep, drains N. 80° W.
78.70	Wash, 20 lks. wide, with 4 ft. banks, drains N. 40° E.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T34N R11W <u>\$28 \$27</u> \$33 \$34 1969
	from which
	A juniper, 6 ins. diam., bears S. 15% E., 74 1ks. dist., mkd. T34N R11W S34 BT.
•	A juniper, 12 ins. diam., bears S. 48° W., 56 1ks. dist., mkd. T34N R11W S33 BT.
•	A juniper, 7 ins. diam., bears N. 78%° W., 154 lks. dist., mkd. T34N R11W S28 BT.
	Raise a mound of stone W. of the cor.
	Land, mountainous to gently rolling. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
•	From the cor. of secs. 26, 27, 34 and 35.
• * * *	N. 89°58' W., bet. secs. 27 and 34.
	Over gently rolling land, through medium timber and undergrowth.
17.60	Track road, bears N. and S.
30.14	Enter rolling land, bears NE. and SW.
32.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
34.50	Wash, 30 1ks. wide, 2 ft. deep, drains NW.
39.87	Point for the ½ sec. cor. of secs. 27 and 34.
	Set the iron post over an "X" cut into solid rock, mound of stone to top, brass cap mkd.
	T34N R11W 2 S27 S34 1969

Subdivision, T. 34 N., R. 11 W.

		. , , , , , , , , , , , , , , , , , , ,
,	CHAINS	
		from which
		A juniper, 8 ins. diam., bears S. 15° E., 103 lks. dist., mkd. ½ S34 BT.
		A juniper, 8 ins. diam., bears N. 35½° W., 78 lks. dist., mkd. ½ S27 BT.
	41.70	Wash, 30 1ks. wide, 3 ft. deep, drains NW.
	53.90	Track road, bears SE, and NW.; desc. steep W. slope.
	59.80	Enter Jagwey Valley, bears N. and S.
	79.00	Wash, 15 1ks. wide, 3 ft. deep, drains N. 10° E.
	79.74	The cor. of secs. 27, 28, 33 and 34.
		Land, rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
:		N. 0°02' W., bet. secs. 27 and 28.
		Over nearly level land in Jagwey Valley, through scattered timber.
	16.50	Wash, 25 1ks. wide, 1 ft. deep, drains E.
	17.40	Track road, bears S. 80° E. and N. 80° W.
	18.00	West edge of a detention dike, bearing E. and W., enter rolling land, bears NE. and SW.
	40.00	Point for the ½ sec. cor. of secs. 27 and 28.
		Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W
	٠.	支 S28 S27 1969
		from which
		A juniper, 4 ins. diam., bears S. 12° E., 128 1ks. dist., mkd. ½ S27 BT.
		A juniper, 6 ins. diam., bears S. 73½° W., 65 lks. dist., mkd. ½ S28 BT.
	45.80	Wash, 15 1ks. wide, 3 ft. deep, drains S. 70° E.
	56.50	Wash, 10 1ks. wide, 1 ft. deep, drains E.
	67 . 30	Wash, 20 lks. wide, with 8 ft. banks, drains E.
	80.00	Point for the cor. of secs. 21, 22, 27 and 28.

Subdivision, T. 34 N., R. 11 W.

	Subdivision, T. 34 N., R. 11 W.
CHAINS	
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	T34N R11W <u>S21 S22</u> S28 S27 1969
	from which
	· A pinon, 7 ins. diam., bears N. 63½° E., 49 lks. dist., mkd. T34N R11W S22 BT.
	A juniper, 5 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ E., 66 lks. dist., mkd. T34N R11W S27 BT.
	A juniper, 6 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ W., 34 . lks. dist., mkd. T34N R11W S28 BT.
	Raise a mound of stone W. of the cor.
	Land, gently rolling and rolling. Soil, rocky and sandy clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°57' W., bet. secs. 22 and 27.
	Over rolling land, through scattered timber and undergrowth.
0.60	Wash, 25 1ks. wide, 3 ft. deep, drains N. 30° W.
6.90	Spur, slopes N.
9.90	Wash, 20 1ks. wide, 3 ft. deep, drains NE.
15.50	Ridge, bears N. and S., desc. W. slope.
38.60	East rim of a small canyon, bears N. and S.; desc. over steep rocky W. slope.
39.86	Point for the 1/2 sec. cor. of secs. 22 and 27.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W S22 S27 1969
	No suitable bearing trees available.
40.80	Wash, in bottom of canyon, 60 lks. wide, with 6 ft. banks, drains irregularly N. 30° W., ascend steep E. slope.

		Babatvision, 1. 54 n., K. 11 w.
	CHAINS	
	46.60	W. rim of canyon, bears N. and S.; enter gently rolling land.
	79.72	The cor. of secs. 21, 22; 27 and 28.
		Land, rolling and broken. Soil, rocky sandy clay loam.
		Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		N. 0°02' W., bet. secs. 21 and 22.
		Over gently rolling land, through scattered timber.
	1.10	Wash, 20 1ks. wide, with 5 ft. banks, drains S. 80° E.
	10.40	Wash, 40 lks. wide, with 4 ft. banks, drains E.
	40.00	Point for the ½ sec. cor. of secs. 21 and 22.
	: 7	Set the iron post 20 ins. in the ground, brass cap mkd.
		T34N R11W
		S21 S22 1969
		from which
		A juniper, 14 ins. diam., bears N. 89½° W., 38 lks. dist., mkd. ½ S21 BT.
		Raise a mound of stone W. of the cor.
	48.00	Leave scattered timber, enter medium timber, bears E. and W.
	53.80	Track road, bears E. and W.
	80.00	Point for the cor. of secs. 15, 16, 21 and 22.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T34N R11W <u>S16 S15</u>
		S21 S22 1969
		from which
		'A pinon, 13 ins. diam., bears N. 34%° E., 79 1ks. dist., mkd. T34N R11W S15 BT.
	¢	A juniper, 12 ins. diam., bears S. 14½° E., 92 1ks. dist., mkd. T34N R11W S22 BT.
	`	A juniper, 10 ins. diam., bears S. 72½° W., 42 1ks. dist., mkd. T34N R11W S21 BT.
- 1		1

Subdivision, T. 34 N., R. 11 W.

	bubally 10 of my in 12 m
CHAINS	
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°56' W., bet. secs. 15 and 22.
	Over rolling land, through scattered timber and undergrowth.
4.70	Wash, 10 lks. wide, 2 ft. deep, drains S.
28.40	Ridge, bears N. and S.
39.87	Point for the ½ sec. cor. of secs. 15 and 22.
•	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W 1/2 S15 S22 1969
	No suitable bearing trees available.
43.00	Wash, 10 1ks. wide, 2 ft. deep, drains NW.
47.70	Wash, 15 1ks. wide, 2 ft. deep, drains N.
64.40	Wash, 30 1ks. wide, with 4 ft. banks, drains N. 60° E.
67.00	Enter gently rolling land, bears W. and NW.
75.00	Enter medium timber, bears N. and S.
79.74	The cor. of secs. 15, 16, 21 and 22.
•	Land, rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	N. 0°02' W., bet. secs. 15 and 16.
	Over rolling land, through medium timber.
6.20	Leave medium timber, enter widely scattered timber, bear E. and W.
13.70	South rim of a small canyon, bears NE. and SW.
16.60	Wash, in bottom of canyon, 15 1ks. wide, 2 ft. deep, drains E. 100 1ks. dist., thence NE.
10.00	

		Subdivision, T. 34 N., R. 11 W.
	CHAINS	
	20.10	Spur, slopes E.
	22.40	Draw, drains S. 40° E.
	40.00	Point for the 表 sec. cor. of secs. 15 and 16.
		Set the iron post over an "X" cut into solid rock, mound of stone to top, brass cap mkd.
9		T34N R11W
		\$16 \$15 1969
	. 1	No bearing trees available.
	44.00	Desc. 200 ft. over steep N. slope.
	56.00	Wash, in bottom of canyon, 100 lks. wide, with 5 ft. banks, drains S. 80° E., ascend steep S. slope.
	72.00	Rocky ridge, 50 lks. wide, bears E. and W., desc. steep N. slope into Parashant Wash.
	77.00	Base of sheer cliffs, bears NE. and SW., thence along steep rocky W. slope of a spur projecting N.
	80.00	True point for the cor. of secs. 9, 10, 15 and 16 falls on a steep rocky W. slope where the monument cannot be perpetuated.
		Land, gently rolling on S ½ mile, broken canyon remainder Soil, rocky clay loam. Timber, scattered juniper. Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 10, 11, 14 and 15.
		N. 89°54' W., bet. secs. 10 and 15.
		Over rolling land, through scattered timber.
	11.80	Track road, bears N. and S.
	17.20	East rim of draw, bears N. and S., desc. steep W. slope.
	22.40	Wash, 10 lks. wide, 3 ft. deep, drains S. 15° W., asc. over E. slope.
	26.00	West rim of draw, bears N. and S.
	33.60	Rim of Parashant Canyon, bears NW. and SE., desc. steep W. slope.
	39.84	Point for the ½ sec. cor. of secs. 10 and 15.
		Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
		·

	CHAINS	
		T34N R11W 1/2 S10 S15
		. 1969 .
		No bearing trees available.
		Cor. is located 20 lks. W. of a rocky vertical cliff 6 ft. high.
		Continue desc. over steep W. slope.
	42.00	Wash, 40 1ks. wide, with 5 ft. banks, drains S. 80° E., 100 1ks. dist., thence S.; continue over broken land in Parashant Canyon.
	45.00	Rocky spur, 50 lks. wide, slopes S. 60° E., desc. abrupt-ly over steep SW. slope.
	60.00	Rocky spur, slopes S., desc. abruptly over steep SW. slope.
	70.00	Parashant Wash, 150 lks. wide, with 5 ft. banks, drains S.; asc. steep E. slope.
	76.00	Spur, slopes N., desc. steep W. slope.
	79.68	True point for the cor. of secs. 9, 10, 15 and 16.
٠		Land, rolling and mountainous. Soil, rocky clay loam. Timber, scattered juniper. Undergrowth, sagebrush, cacti and grama grass.
		N. 0°02' W., bet. secs. 9 and 10.
		Along a steep rocky W. slope.
	3.00	Point selected for the Witness cor. of secs. 9, 10,15 and 16.
		Set the iron post, 4 ins. in the ground, mound of stone to top, brass cap mkd.
	•	T34N R11W W C
	•	<u>s 9 s10</u> s16 s15
		1969
	۰	No suitable bearing trees available.
		Continue along W. slope by triangulation.
	13.00	Parashant Wash, 150 lks. wide, with 5 ft. banks, drains E. about 10.00 chs. dist., thence S., ascend over steep S. slope.
	21.40	North rim of Parashant Canyon, bears E. and N. 65° W.; thence over rolling land through medium timber.

		Subdivision, 1. 54 N., R. II W.
	CHAINS	
	40.00	Point for the ½ sec. cor. of secs. 9 and 10.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T34N R11W
		s 9 s10
		1969
		from which
	•	A juniper, 8 ins. diam., bears S. 82½° E., 52 lks. dist., mkd. 表 S10 BT.
	·	A pinon, 10 ins. diam., bears S. 87½° W., 64 lks. dist., mkd. ½ S9 BT.
		Raise a mound of stone W. of the cor.
	80.00	Point for the cor. of secs. 3, 4, 9 and 10.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T34N R11W
		<u>s 4 s 3</u> s 9 s10
		1969.
		from which
		A pinon, 9 ins. diam., bears N. 74½° E., 88 1ks. dist., mkd. T34N R11W S3 BT.
		A pinon, 6 ins. diam., bears S. 83%° E., 14 lks. dist., mkd. T34N R11W S10 BT.
	•	A juniper, 6 ins. diam., bears S. 10½° W., 34 1ks. dist., mkd. T34N R11W S9 BT.
		A juniper, 12 ins. diam., bears N. 60½° W., 47 lks. dist., mkd. T34N R11W S4 BT.
		Raise a mound of stone W. of the cor.
		Land, mountainous and rolling.
-		Soil, rocky clay loam. Timber, juniper and pinon.
		Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 2, 3, 10 and 11.
		N. 89°54' W., bet. secs. 3 and 10.
		Over rolling land, through scattered timber and under- growth.
	2,40	Track road, bears NE. and SW.
	39.85	Point for the ½ sec. cor. of secs. 3 and 10.
		Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	•	

	CHAINS	
	•	T34N R11W 2 6 3 5 10
		⁴ S10 1969
		from which
		A juniper, 6 ins. diam., bears N. 77½° W., 49 lks. dist., mkd. ½ S3 BT.
4	46.50	Wash, 15 lks. wide, with 4 ft. banks, drains S. 25° W.
!	50.00	Spur, slopes SE.
. :	54.10	Wash, 40 lks. wide, with 6 ft. banks, drains S.; enter medium timber.
	79.70	The cor. of secs. 3, 4, 9 and 10.
		Land, gently rolling and rolling.
•		Soil, rocky clay loam. Timber, juniper and pinon.
		Undergrowth, sagebrush, cacti and grama grass.
		N. 0°12' W., bet. secs. 3 and 4.
		Over rolling land, through medium timber and undergrowth.
	9.50	Top. of knoll.
1	30.80	Wash, 10 1ks. wide, 2 ft. deep, drains E.
3	36.80	Wash, 25 1ks. wide, with 5 ft. banks, drains S. 70° E.
3	39.90	Wash, 20 1ks. wide, with 5 ft. banks, drains S. 60° E.
4	40.00	Point for the ½ sec. cor. of secs. 3 and 4.
		Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W
-		s 4 s 3
		1969
	,	from which
		A pinon, 10 ins. diam., bears S. 85° E., 26 lks. dist., mkd. ½ S3 BT.
		A juniper, 7 ins. diam., bears S. 30° W., 39 lks. dist., mkd. ½ S4 BT.
		Raise a mound of stone W. of the cor.
) 3	•

_		
	CHAINS	
	56.00	Graded road to Salt Springs, bears N. 30° E. and S. 60° W.
	61.10	Leave rolling land, ascend S. slope of Poverty Mountain.
	79.03	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone to top, brass cap mkd.
		T35N R11W <u>S33 S34</u> S 4 S 3 T34N 1924
		from which the original bearing trees:
		A cedar, 5 ins. diam., bears N. 44° E., 37 1ks. dist., mkd. T35N R11W S34 BT.
		A cedar, 7 ins. diam., bears S. 48½° E., 154 lks. dist., mkd. T34N R11W S3 BT.
		A cedar, 10 ins. diam., bears S. 60¾° W., 168 1ks. dist., mkd. T34N R11W S4 BT.
		A cedar, 6 ins. diam., bears N. 16½° W., 132 1ks. dist., mkd. T35N R11W S33 BT.
	· .	Land, rolling on S. ½ mile, mountainous on remainder. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass.
	•	From the cor. of secs. 27, 28, 33 and 34.
		N. 89°58' W., bet. secs. 28 and 33.
		Over rolling land, through medium timber and undergrowth.
	4.90	Wash, 10 1ks. wide, with 4 ft. banks, drains N.
	11.60	Wash, 15 1ks. wide, with 6 ft. banks, drains NE.
	18.90	Wash, 20 1ks. wide, with 5 ft. banks, drains NE.
	39.94	Point for the ½ sec. cor. of secs. 28 and 33.
		Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
		T34N R11W 2 S28 S33 1969
		from which
		A juniper, 9 ins. diam., bears S. 55½° W., 92 1ks. dist., mkd. ½ S33 BT.
	1	ı

/	CHAINS	
•		A juniper, 6 ins. diam., bears N. 25½° W., 72 lks. dist., mkd. ½ S28 BT.
	50.00	Spur, slopes N., desc. NW. slope.
	66.00	Wash, in Jagwey Valley, 30 lks. wide, with 7 ft. banks, drains NE., 150 lks. dist., thence N.
	79.88	The cor. of secs. 28, 29, 32 and 33, monumented by an iron post, 2½ ins. diam., firmly set in a mound of stone to top, brass cap mkd.
-		T34N R11W S29 S28 S32 S33 1956 from which the original bearing trees:
		A juniper, 8 ins. diam., bears N. 59% E., 60 lks. dist., mkd. T34N R11W S28 BT.
		· A juniper, 13 ins. diam., bears S. 67½° E., 31 1ks. dist., mkd. T34N R11W S33 BT.
		A juniper, 8 ins. diam., bears S. 79° W., 57 lks. dist., mkd. T34N R11W S32 BT.
:		A juniper, 8 ins. diam., bears N. 23½° W., 47 lks. dist., mkd. T34N R11W S29 BT.
		USC&GS triangulation station NORTH, bears S. 38° 15' E., 67.00 chs. dist., monumented by a standard bronze tablet, set in a boulder mkd. NORTH, 1953. Latitude: 36°18'03.100" N., Longitude: 113°28' 35.434" W.
		Land, rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass.
	•	N. 0°03' W., bet. secs. 28 and 29.
		Over gently rolling land, through scattered timber and undergrowth.
	5.70	Wash, 15 lks. wide, 2 ft. deep, drains S. 40° E.
	34.50	Wash, 10 1ks. wide, 2 ft. deep, drains S. 80° E.
	35.30	Wash, 15 1ks. wide, 2 ft. deep, drains S. 15° E.
	40.00	Point for the ½ sec. cor. of secs. 28 and 29.
		Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
		. T34N R11W
		\$29 \$28 1969

CHAINS	T T
Ì	from which
	A juniper, 8 ins. diam., bears S. 49° E., 202 lks. dist., mkd. ½ S28 BT.
	A juniper, 7 ins. diam., bears S. 16¾° W., 98 lks. dist., mkd. ½ S29 BT.
	A round metal granary, 20 ft. diam., bears S. 87° 15' W., 23.85 chs. dist.
53.00	Track road, bears S. 70° E. and N. 70° W.
69.00	Wash, 150 lks. wide, 1 ft. deep, drains NE.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N, R11W
	<u>s20 s21 </u>
	S29 S28 1969
	No suitable bearing trees available.
	Land, gently rolling. Soil, rocky clay loam.
	Timber, scattered juniper and pinon.
	Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°59'. W., bet. secs. 21 and 28.
	Over gently rolling land, through scattered timber.
39.93	Point for the ½ sec. cor. of secs. 21 and 28.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	1 S21 S22
	4 S 28 1969
	from which
	A juniper, 6 ins. diam., bears N. 20° E., 129 1ks. dist., mkd. ½ S21 BT.
	A juniper, 6 ins. diam., bears S. 22° W., 96 lks. dist., mkd. ½ \$28 BT,
42.40	Track road, bears NE. and SW.
	• • • •

	CHAINS	After a second contract of the
	68.20	Wash, 20 lks. wide, with 5 ft. banks, drains N. 40° E.
	79.86	The cor. of secs. 20, 21, 28 and 29.
		Land, gently rolling. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	•	N. 0°03' W., bet. secs. 20 and 21.
		Over gently rolling land, through scattered timber and undergrowth.
	13.00	Wash, 10 1ks. wide, 2 ft. deep, drains N. 70° E.
	20.10	Wash, 10 1ks. wide, 2 ft. deep, drains E.
	40.00	Point for the ½ sec. cor. of secs. 20 and 21.
		Set the iron post 23 ins. in the ground, brass cap mkd.
		T34N R11W
-		\$20 \$21 · 1969
		from which
		A pinon, 5 ins. diam., bears N. 57칯° E., 155 lks. dist., mkd. 攴 S21 BT.
		A juniper, 6 ins. diam., bears S. 78% W., 167 lks. dist., mkd. 첫 S20 BT.
		Raise a mound of stone W. of the cor.
	50.40	Wash, 15 1ks. wide, 2 ft. deep, drains S. 70° E.
	57.70	Enter medium timber, bears E. and W.
	74.50	Track road, bears E. and W.
	80.00	Point for the cor. of secs. 16, 17, 20 and 21.
		Set the iron post 18 ins. in the ground, brass cap mkd.
		T34N R11W S17 S16 S20 S21 1969
		from which
		A juniper, 6 ins. diam., bears N. 24½° E., 78 1ks. dist., mkd. T34N R11W S16 BT.
		A pinon, 7 ins. diam., bears S. 46½° E., 174 . 1ks. dist., mkd. T34N R11W S21 BT.
		A juniper, 8 ins. diam., bears S. 44½° W., 18 lks. dist., mkd. T34N R11W S20 BT.

		Subdivision, 1. 54 N., K. II W.
	CHAINS	
		A juniper, 5 ins. diam., bears N. 30½° W., 52 1ks. dist., mkd. T34N R11W S17 BT.
		Raise a mound of stone W. of the cor.
		Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 15, 16, 21 and 22.
	; **	N. 89°59' W., bet. secs. 16 and 21.
		Over gently rolling land, through medium timber and undergrowth.
	25.80	Wash, 10 1ks. wide, 2 ft. deep, drains N.; enter scattered timber, bears N. and S.
	39.10	Wash, 10 1ks. wide, 3 ft. deep, drains N. 10° E.
	39.94	Point for the ½ sec. cor. of secs. 16 and 21.
		Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W 2 S16 S21 1969
		No suitable bearing trees available.
	59.10	Track road, bears N. and S.
	65.90	Track road, bears N. 40° E. and S. 40° W.; enter medium timber, bears N. and S.
	79.88	The cor. of secs. 16, 17, 20 and 21.
		Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	,	N. 0°03' W., bet. secs. 16 and 17.
		Over rolling land, through medium timber and undergrowth.
	12.00	Enter widely scattered timber, bears E. and W.
	18.10	Wash, 20 1ks. wide, 2 ft. deep, drains E.
	40.00	Point for the ½ sec. cor. of secs. 16 and 17.
		Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
۱		1

\neg		
	CHAINS	
		T34N R11W
		· · · · · · · · · · · · · · · · · · ·
		1969
		from which
		A juniper, 7 ins. diam., bears N. 84½° E., 95 lks. dist., mkd. ½ S16 BT.
		A juniper, 6 ins. diam., bears N. 52° W., 74 lks. dist., mkd. ½ S17 BT.
	64.60	Wash, 30 lks. wide, with 5 ft. banks, drains N. 80° E., 150 lks. dist., thence NE.
	80.00	Point for the cor. of secs. 8, 9, 16 and 17.
		Set the iron post over an "X" cut into solid rock, mound of stone to top, brass cap mkd.
		T34N R11W <u>S 8 S 9</u> S17 S16 1969
		No suitable bearing trees available.
		Land, rolling. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		From the true point for the cor. of secs. 9, 10, 15 and 16.
		S. 89°57' W., bet. secs. 9 and 16.
	٠	Over broken land in Parashant Canyon.
	3.90	Parashant Wash, 150 lks. wide, with 5 ft. banks, drains N. 30° W. from SW.
	6.80	Rocky spur, slopes S.
	9.80	Parashant Wash, 150 1ks. wide, with 5 ft. banks, drains S. 30° E., 150 1ks. dist., thence NE., ascend steep NE. slope.
	20.50	South rim of Parashant Canyon, bears S. 20° E. and N. 70° W., continue along S. rim of Parashant Canyon.
	39.92	Point for the ½ sec. cor. of secs. 9 and 16.
		Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	2 3 3	T34N R11W S 9 S16 1969

		,
	CHAINS	
	^	from which
		A pine, 10 ins. diam., bears S. 82½° E., 115 1ks. dist., mkd. ½ S16 BT.
	^	A juniper, 13 ins. diam., bears S. 70° W., 69 lks. dist., mkd. 表 S16 BT.
		No suitable bearing trees available near the cor. in Sec. 9.
	53.10	Wash, 10 1ks. wide, 4 ft. deep, drains N. 30° E.
	59.90	Ridge, bears N. 25° E. and S. 25° W.; desc. steep W. slope.
	69.30	Wash, 40 lks. wide, with 10 ft. banks, drains NE.; ascend steep SE. slope.
	76.60	Rim of wash, bears NE. and SW.
	79.84	The cor. of secs. 8, 9, 16 and 17.
		Land, mountainous E. 20.00 chs., rolling on remainder. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		N. 0°03' W., bet. secs. 8 and 9.
		Over rolling land, through scattered timber.
	8.30	South rim of Parashant Canyon, bears E. and W.; desc. about 400 ft. over steep N. slope.
	15.30	Parashant Wash, 150 lks. wide, with 6 ft. banks, drains irregularly S. 80° E.; ascend about 400 ft. over steep S. slope.
	26.50	Ridge, bears E. and W., desc. over steep N. slope.
	32.00	East edge of Parashant Wash, 150 lks. wide, 6 ft. deep, drains SW. from irregularly W.; ascend 300 ft. over steep S. slope.
	39.92	North rim of Parashant Canyon, bears E. and W.
	40.00	Point for the ½ sec. cor. of secs. 8 and 9.
	,	Set the iron post 22 ins. in the ground, brass cap mkd.
		T34N R11W
		s 8 s 9 1969
		from which
		A pinon, 4 ins. diam., bears S. 64° E., 96 lks. dist., mkd. X BT.
ı		i

CHAINS	
	A pinon, 8 ins. diam., bears N. 67° W., 86 lks. dist., mkd. ½ S8 BT.
•	Raise a mound of stone W. of the cor.
4,5.00	Enter medium timber, bears E. and W.
58.40	Wash, 30 1ks. wide, 2 ft. deep, drains S. 60° E., 70 1ks. dist., thence S. 20° E.
63.90	Graded road to Salt Springs, bears S. 60° E., 40 lks. dist., thence E. and N. 40° W., 60 lks. dist., thence SW.
77.20	Wash, 30 1ks. wide, with 8 ft. banks, drains from irregularly NW. to SW.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
,	T34N R11W S 5 S 4 S 8 S 9 1969
	from which
	A juniper, 9 ins. diam., bears N. 58½° E., 13 1ks. dist., mkd. T34N R11W S4 BT.
•	A juniper, 12 ins. diam., bears S. 57° E., 71 lks. dist., mkd. T34N R11W S9 BT.
	A pinon, 8 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ W., 31 lks. dist., mkd. T34N R11W S8 BT.
	No other suitable bearing trees available.
•	Land, broken and rolling. Soil, rocky clay loam.
	Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°58' W., bet. secs. 4 and 9.
9	Over rolling land, through medium timber and undergrowth.
39.95	Point for the ½ sec. cor. of secs. 4 and 9.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
,	T34N R11W 1/2

	Justin, 1. 54 H., R. II W.
CHAINS	
<u> </u>	from which
	USC&GS Triangulation Station SOFT bears S. 50° 56' W., 32.85 chs. dist., monumented by a standard bronze tablet set in a drill hole in a boulder, mkd. SOFT 1934. Latitude: 36°21'52.788" N., Longitude: 113°28'57.474" W.
	A metal stock trough 10 ft. by 4 ft., 3 ft. high, bears N. 75°26' E., 10.94 chs. dist.
	No suitable bearing trees available.
43.20	Graded road to Salt Springs, bears SW. and NE., curving Easterly.
51.00	Wash, 20 1ks. wide, 3 ft. deep, drains S. 50° W.; ascend over steep SE. slope of Poverty Mountain.
66.60	Ridge, bears N. 35° E. and S. 35° W., desc. steep NW. slope.
79.90	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling and mountainous. Soil, rocky clay loam.
	Timber, med. juniper and pinon. Undergrowth, sagebrush and grama grass.
	N. 0°18' W., bet. secs. 4 and 5.
	Over S. slope of Poverty Mountain, through medium timber.
1.80	Wash, 20 1ks. wide, with 5 ft. banks, drains SW. from NW.
29.30	Wash, 20 1ks. wide, 1 ft. deep, drains S. 75° W.
40.00	Point for the ½ sec. cor. of secs. 4 and 5.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T34N_R11W
	S 5 S 4 1969
	from which
•	A juniper, 8 ins. diam., bears N. 51½° E., 40 lks. dist., mkd. ½ S4 BT.
	A pinon, 7 ins. diam., bears S. 65½° W., 29 lks. dist., mkd. 支 S5 BT.
	Raise a mound of stone W. of the cor.
53.80	Wash, 15 1ks. wide, 2 ft. deep, drains SW.
64.70	Ascend over steep rocky S. slope of Poverty Mountain; enter scattered timber, bears E. and W.

	Subdivision, I. 34 N., R. II W.
CHAINS	
79.05	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., firmly set, with 8 ins. projecting above the ground, brass cap mkd.
	T35N R11W S32 S33 S 5 S 4 T34N 1924
ę	from which the original bearing trees:
	A cedar, 18 ins. diam., bears N. 19° E., 68 1ks. dist., mkd. T35N R11W S33 BT.
	A cedar, 12 ins. diam., bears S. 35½° E., 59 1ks. dist., mkd. T34N R11W S4 BT.
	A pinon, 12 ins. diam., bears S. 54% W., 156 1ks. dist., mkd. T34N R11W S5 BT.
•	A cedar, 12 ins. diam., bears N. 45° W., 110 1ks. dist., mkd. T35N R11W S32 BT.
	Land, mountainous. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass.
	From the cor. of secs. 29, 30, 31 and 32, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.
	T34N R11W S30 S29 S31 S32 1956
	from which the original bearing tree:
•	A juniper, 8 ins. diam., bears S. 15½° W., 63 1ks. dist., mkd. T34N R11W S31 BT.
	N. 89°53' W., bet. secs. 30 and 31.
	Over gently rolling land, through medium timber and undergrowth.
40.00	Point for the ½ sec. cor. of secs. 30 and 31.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T34N R11W 2 S30 S31 1969
	from which
	A juniper, 18 ins. diam., bears N. 33½° E., 22 . 1ks. dist., mkd. ½ S30 BT.
	A juniper, 5 ins. diam., bears S. 17° W., 65 lks. dist., mkd. 表 S31 BT.
1	

==		
	CHAINS	
		Set a juniper post, 4 ins. diam., 4 ft. long, alongside the iron post.
	47.40	Dim jeep trail, bears N. and S.
	79 . 34	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
		T34N
	•	R12W R11W <u>S25 S30</u> S36 S31 1926
		from which the original bearing trees:
		A cedar, 14 ins. diam., bears N. 59° E., 238 lks. dist., mkd. T34N R11W S30 visible.
		A pinon, 15 ins. diam., bears S. 7° E., 200 lks. dist., mkd. with an overgrown blaze. (Record, a cedar).
		A cedar, 12 ins. diam., bears S. 89° W., 88 lks. dist., mkd. T34N R12W S36 BT.
		A cedar, 16 ins. diam., bears N. 58° W., 42 lks. dist., mkd. with an overgrown blaze.
		Land, gently rolling. Soil, sandy clay loam. Timber, juniper and pinon.
		Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 29, 30, 31 and 32.
		N. 0°03' W., bet. secs. 29 and 30.
		Over gently rolling land, through medium timber and undergrowth.
	8.70	Wash, 10 1ks. wide, 1 ft. deep, drains E.
j	24.90	Track road, bears N. 80° E. and S. 80° W.
	38.80	Bladed road to Grassy Mountain, bears S. 50° E. and N. 50° W.
	40.00	Point for the ½ sec. cor. of secs. 29 and 30.
	•	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N_R11W
		支 S30 S29 1969
		from which
		A juniper, 6 ins. diam., bears N. 74° E., 69 lks. dist., mkd. 表 S29 BT.
Ì		

	CHAINS	
		A juniper, 7 ins. diam., bears N. $48\frac{1}{2}$ ° W., 101 lks. dist., mkd. $\frac{1}{4}$ S30 BT.
	49 . 20	Wash, 20 1ks. wide, 3 ft. deep, drains N. 50° E.; enter scattered timber, bears NE. and SW.
	60.80	Wash, 10 lks. wide, 2 ft. deep, drains S. 50° E.
	80.00	Point for the cor. of secs. 19, 20, 29 and 30.
		Set the iron post 20 ins. in the ground, brass cap mkd.
		T34N R11W <u>\$19</u> <u>\$20</u> \$30 \$29 1969
		from which
		A juṇiper, 6 iṇs. diạm., bears N. 36½° E., 57 1ks. dist., mkd. T34N R11W S20 BȚ.
		A juniper, 7 ins. diam., bears S. 47½° E., 30 lks. dist., mkd. T34Ņ R11W S29 BT.
-	•	A juniper, 9 ins. diam., bears S. 29½° W., 25 1ks. dist., mkd. T34N R11W S30 BT.
		A juniper, 7 ins. diam., bears N. 46½° W., 36 1ks. dist., mkd. T34N R11W S19 BT.
		Raise a mound of stone W. of the cor.
e e		Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
		From the cor. of secs. 20, 21, 28 and 29.
		N. 89°56' W., bet. secs. 20 and 29.
	:	Over gently rolling land, through scattered timber and undergrowth.
	39.80	Wash, 20 1ks. wide, with 4 ft. banks, drains S.
	40.01	Point for the 1/2 sec. cor. of secs. 20 and 29.
		Set the iron post 24 ins. in the ground, brass cap mkd.
		T34N R11W S20
,		· S20 S29 1969
		from which
		A juniper, ll ins. diam., bears N. 2½° E., 118 lks. dist., mkd. ½ S20 BT.

Subdivision, T. 34 N., R. 11 W.

	Subdivision, 1. 34 N., R. II W.
CHAINS	
	A juniper, 10 ins. diam., bears S. 12½° E., 88 lks. dist., mkd. 눛 S29 BT.
	Raise a mound of stone N. of the cor.
58.10	Wash, 15 1ks. wide, 3 ft. deep, drains S. 20° E.
80.02	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, cacti and grama grass.
	N. 89°55' W., bet. secs. 19 and 30.
	Over gently rolling land, through scattered timber and undergrowth.
22.00	Ridge, bears N. and S.
31.10	Track road, bears SE. and NW.
40.00	Point for the 2 sec. cor. of secs. 19 and 30.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	½ S19 S30
	1969
	from which
	A juniper, 7 ins. diam., bears S. 20½° W., 67 lks. dist., mkd. ½ S30 BT.
	A juniper, 7 ins. diam., bears N. 31° W., 56 lks. dist., mkd. 눟 S19 BT.
55.60	Bladed road to Grassy Mountain, bears irregularly SE. and NW.
79.32	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a collar of stone, brass cap mkd.
	T34N R12W S24 S19 S25 S30 R11W 1926
	I remarked the brass cap:
-	T34N R12W R11W S24 S19 S25 S30 1969 1926

CHAINS	
	from which the original bearing trees:
	A cedar, 10 ins. diam., bears N. 24° E., 136 lks. dist., mkd. T34N R11W S19 BT. (Record, 36 lks. dist.).
	A pinon, 15 ins. diam., bears S. 51° E., 70 lks. dist., mkd. T34N R11W S30 BT. (Record, 58 lks. dist.).
	A cedar, 12 ins. diam., bears S. 22° W., 187 1ks. dist., mkd. T34N R12W S25 BT.
	A cedar, 13 ins. diam., bears N. 70° W., 95 lks. dist., mkd. with faint scribe mks.
	Land, gently rolling. Soil, rocky clay loam.
	Timber, juniper and pinon. Undergrowth, sagebrush and grama grass.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over gently rolling land, through scattered timber and undergrowth.
17.50	Draw, drains NE.
40.00	Point for the ½ sec. cor. of secs. 19 and 20.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W
	S19 S20 1969
	from which
	A juniper, 8 ins. diam., bears S. 14½° E., 77 1ks. dist., mkd. 및 S20 BT.
	A juniper, 6 ins. diam., bears S. 47½° W., 66 lks. dist., mkd. ½ S19 BT.
58.0	Track road, bears N. 80° E. and S. 55° W.
68.0	Draw, drains NE.
80.0	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 18 ins. in the ground, brass cap mkd.
•	T34N R11W <u>\$18 \$17</u> <u>\$19 \$20</u> 1969

Wash, 10 lks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W.		Subdivision, T. 34 N., R. II W.
A juniper, 6 ins. diam., bears N. 26% E., 250 lks. dist., mkd. T34N R1IW S17 BT. A juniper, 5 ins. diam., bears S. 23% W., 55 lks. dist., mkd. T34N R1IW S19 BT. A juniper, 5 ins. diam., bears N. 46° W., 80 lks. dist., mkd. T34N R1IW S18 BT. No other suitable bearing trees available. Raise a mound of stone W. of the cor. Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1IW ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	CHAINS	
lks. dist., mkd. T34N R11W S17 BT. A juniper, 5 ins. diam., bears S. 23½° W., 55 lks. dist., mkd. T34N R11W S19 BT. A juniper, 5 ins. diam., bears N. 46° W., 80 lks. dist., mkd. T34N R11W S18 BT. No other suitable bearing trees available. Raise a mound of stone W. of the cor. Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17 ½ S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		from which
lks. dist., mkd. T34N R11W S19 BT. A juniper, 5 ins. diam., bears N. 46° W., 80 lks. dist., mkd. T34N R11W S18 BT. No other suitable bearing trees available. Raise a mound of stone W. of the cor. Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. Wash, 10.1ks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the & sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W \(\frac{\text{S17}{\text{S20}} \) 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. 49.80 Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		
No other suitable bearing trees available. Raise a mound of stone W. of the cor. Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1IW ½ S17 S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		· · · · · · · · · · · · · · · · · · ·
Raise a mound of stone W. of the cor. Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 24.10 Wash, 15 lks. wide, 2 ft. deep, drains NE. 40.01 Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1IW ½ S17 ½ S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. 49.80 Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		
Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 24.10 Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1IW ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		No other suitable bearing trees available.
Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass. From the cor. of secs. 16, 17, 20 and 21. N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 24.10 Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. 80.02 The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	•	Raise a mound of stone W. of the cor.
N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. Wash, 10.1ks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	·	Soil, rocky clay loam. Timber, juniper and pinon.
N. 89°56' W., bet. secs. 17 and 20. Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. Wash, 10.1ks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		
Over gently rolling land, through medium timber and undergrowth. Enter widely scattered timber, bears N. and S. Wash, 10.1ks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1IW ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		From the cor. of secs. 16, 17, 20 and 21.
undergrowth. Enter widely scattered timber, bears N. and S. 22.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 24.10 Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		N. 89°56' W., bet. secs. 17 and 20.
Wash, 10 lks. wide, 2 ft. deep, drains N. Wash, 15 lks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R1IW ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		1
Wash, 15 1ks. wide, 2 ft. deep, drains NE. Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	19.20	Enter widely scattered timber, bears N. and S.
Point for the ½ sec. cor. of secs. 17 and 20. Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W ½ S17/S20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	22.70	.Wash, 10 1ks. wide, 2 ft. deep, drains N.
Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. T34N R11W \[\frac{\text{S17}}{\text{S20}} \] 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. 49.80 Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	24.10	Wash, 15 1ks. wide, 2 ft. deep, drains NE.
T34N R11W 1 S17 20 1969 No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. 49.80 Draw, drains N. 15° W. 20.02 Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	40.01	Point for the ½ sec. cor. of secs. 17 and 20.
No suitable bearing trees available. The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	•	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. 49.80 Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	· ·	· <u>\$17</u> S20
The cor. is located on the E. edge of a track road, bearing S. 10° E. and N. 10° W. 49.80 Draw, drains N. 15° W. The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		No suitable bearing trees available.
The cor. of secs. 17, 18, 19 and 20. Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.		The cor. is located on the E. edge of a track road,
Land, gently rolling. Soil, sandy clay loam and limestone. Timber, juniper and pinon.	49.80	Draw, drains N. 15° W.
Soil, sandy clay loam and limestone. Timber, juniper and pinon.	80.02	The cor. of secs. 17, 18, 19 and 20.
		Soil, sandy clay loam and limestone. Timber, juniper and pinon.

	CHAINS	
		N. 89°56' W., bet. secs. 18 and 19.
		Over gently rolling land, through scattered timber and undergrowth.
	5.30	Track road, bears N. and S.
	26.50	Dim track road, bears S. 10° E. and N. 10° W. approximately 4.00 chs. dist. to end of road.
	27.67	Desc. over W. slope.
	39.00	Wash, 10 lks. wide, 2 ft. deep, drains NW., 2.00 chs. dist., then Westerly; asc. E. slope.
	40.00	Point for the ½ sec. cor. of secs. 18 and 19.
		Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
-		T34N R11W
		\$\frac{\sqrt{1}}{2} \frac{\sqrt{1}}{\sqrt{1}} \frac{\sqrt{1}}{\sqrt{1}
		. 1969
		from which
		from which
		A juniper, 7 ins. diam., bears S. 43¾° W., 31 lks. dist., mkd. ½ S19 BT.
		A juniper, 7 ins. diam., bears N. 0°45' W., 39 . lks. dist., mkd. 表 S18 BT.
	45.00	Spur, slopes N.; desc. W. slope.
	54.90	Wash, 40 lks. wide, with 4 ft. banks, drains N. 30° W., 3.00 chs. dist., then N.
	79.30	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
		T34N
		R12W_R11W
		. <u>\$13 \$18</u>
		S24 S19 . 1926 .
		from which the original bearing trees:
		A cedar, 20 ins. diam., bears N. 4½° E., 347 1ks. dist., mkd. T34N R11W S18 BT.
		A cedar, 15 ins. diam., bears S. 56½° E., 146 1ks. dist., mkd. T34N R11W S19 BT.
		Land, gently rolling.
		Soil, rocky clay loam. Timber, juniper and pinon.
- 1		Undergrowth, sagebrush and grama grass.

	CHAINS	
		From the cor. of secs. 17, 18, 19 and 20.
		N. 0°03' W., bet. secs. 17 and 18.
		Over gently rolling land, through scattered timber.
	5.90	Enter medium timber, bears N. 30° E. and S. 30° W.
	23.00	Ridge, bears E. and W.
	25.50	Track road, bears N. 25° E. and S. 25° W.
	34.40	Same track road, bears SE. and NW.
	40.00	Point for the ½ sec. cor. of secs. 17 and 18.
		Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W
		S18 S17 1969
		from which
		A juniper, 7 ins. diam., bears S. 29° E., 15 lks. dist., mkd. ½ S17 BT.
		A juniper, 8 ins. diam., bears N. 14° W., 56 lks. dist., mkd. ½ S18 BT.
	74.00	Enter scattered timber, bears E. and W.
	80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	v	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
		T34N R11W S 7 S 8 S18 S17 1969
Ì		from which
		A juniper, 7 ins. diam., bears N. 22%° E., 178 lks. dist., mkd. T34N R11W S8 BT.
		A juniper, 10 ins. diam., bears S. 68° E., 62 lks. dist., mkd. T34N R11W S17 BT.
		A pinon, 7 ins. diam., bears S. 6½° W., 197 1ks. dist., mkd. T34N R11W S18 BT.
		A pinon, 5 ins. diam., bears N. 58° W., 190 1ks. dist., mkd. T34N R11W S7 BT.
		Land, gently rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.

	Subdivision, 1. 54 N., R. 11 W.
CHAINS	
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89°57' W., bet. secs. 8 and 17.
•	Over rolling land, through scattered timber.
37.40	Wash; 10 1ks. wide; 2 ft. deep, drains N.
40.01	Point for the ½ sec. cor. of secs. 8 and 17.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W 1 S 8 2 S17 1969
	No suitable bearing trees available.
64.80	Wash, 20 1ks. wide, 1 ft. deep, drains N. 25° W., 25 1ks. dist., thence Northwesterly.
80.02	The cor. of secs. 7, 8, 17 and 18.
	Land, rolling. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass.
	N. 89°58' W., bet. secs. 7 and 18.
	Over rolling land, through scattered timber.
6.10	Desc. steep W. slope.
9.50	Wash, in bottom of a small canyon, 30 lks. wide, 5 ft. deep, drains N.; ascend steep E. slope.
14.10	Ridge, bears N. and S.
28.00	Rim of Parashant Canyon, bears N. and S., by triangulation, topography estimated, descend 200 ft. over steep W. slope.
34.00	Parashant Wash, 150 lks. wide, with 10 ft. banks, drains N. 20° E.; ascend steep E. slope.
39.00	Spur, slopes S.; end of triangulation.
40.00	Point for the ½ sec. cor. of secs. 7 and 18.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T34N R11W 1 S 7 2 S18 1969

Subdivision, T. 34 N., R. 11 W.

	20002720200, 2000, 200 22 00
 CHAINS	
	from which
	A pine, 17 ins. diam., bears S. 44° E., 34 lks. dist., mkd. ½ S18 BT.
·	A pine, 12 ins. diam., bears N. 78° W., 184 1ks. dist., mkd. ½ S7 BT.
45.00	Descend 200 ft. over steep W. slope.
49.00	Parashant Wash, 150 lks. wide, with 10 ft. banks, drains S. 20° E., approximately 4.00 chs. dist., thence E.; asc. steep SE. slope.
56.80	Ridge, bears N. 60° E. and S. 60° W.; thence over rolling land.
79.44	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T34N R12W R11W S12 S 7 S13 S18 1926
,	from which the original bearing trees:
	A cedar, 13 ins. diam., bears N. 47° E., 470 1ks. dist., mkd. with faint scribe mks. (Record, N. 45° E., 497 1ks. dist.).
	A cedar, 16 ins. diam., bears S. 20½° W., 106 lks. dist., mkd. T34N R12W S13 BT. (Record, S. 48° W., 70 lks. dist.).
	A cedar, 12 ins. diam., bears N. 58½° W., 57 1ks. dist., mkd. T34N R12W S12 BT. (Record, N. 37° W., 91 1ks. dist.).
-	Land, rolling with deep canyons. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and grama grass.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over gently rolling land, through medium timber.
2.60	South rim of Parashant Canyon, bears E. and W.; by triangulation, topography estimated, desc. about 300 ft. over steep N. slope.
12.00	Parashant Wash, 150 1ks. wide, with 8 ft. banks, drains irregularly E.; ascend 300 ft. over steep S. slope.

CHAINS	
20.90	North rim of Parashant Canyon, bears E. and W.; thence over gently rolling land.
30.20	End of triangulation.
40.00	Point for the ½ sec. cor. of secs. 7 and 8.
	Set the iron post 18 ins. in the ground, in a mound of stone to top, brass cap mkd.
	T34N R11W
	· ½ · S 7 S 8 1969
	from which
	A juniper, 8 ins. diam., bears S. 35½° E., 68 lks. dist., mkd. ½ S8 BT.
	A juniper, 12 ins. diam., bears N. 86½° W., 71 1ks. dist., mkd. ½ S7 BT.
44.00	Spur, slopes W.
68.60	Low ridge, bears E. and W.
76.60	Graded road to Salt Springs, bears S. 80° E. and N. 80° W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T34N R11W S 6 S 5 S 7 S 8 1969
7	from which
	A juniper, 8 ins. diam., bears N. 61° E., 52 1ks. dist., mkd. T34N R11W S5 BT.
	A juniper, 12 ins. diam., bears S. 30° E., 105 1ks. dist., mkd. T34N R11W S8 BT.
	A juniper, 8 ins. diam., bears S. 75½° W., 84 lks. dist., mkd. T34N R11W S7 BT.
	A juniper, 8 ins. diam., bears N. 31칯° W., 159 lks. dist., mkd. T34N R11W S6 BT.
	Raise a mound of stone W. of the cor.
	Land, gently rolling, with canyons in S. ½. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and scrub oak.
. `	

	Subdivision, T. 34 N., R. 11 W.			
-	CHAINS			
	*	From the cor. of secs. 4, 5, 8 and 9.		
		N. 89°55' W., bet. secs. 5 and 8.		
		Along the south slope of the foothills of Poverty Mountain, through scattered timber.		
	1.30	Wash, 25 lks. wide, with 4 ft. banks, drains irregularly S.		
	18.10	Spur, slopes S.		
	33.80	Graded road, to Salt Springs, bears S. 35° E. and N. 35° W.		
	37.30	Wash, 30 1ks. wide, 3 ft. deep, drains S.		
	40.01	Point for the 1/2 sec. cor. of secs. 5 and 8.		
		Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.		
		T34N R11W 2 S 5 2 S 8 1969		
		from which		
	7	A juniper, 10 ins. diam., bears S. 66½° E., 26 lks. dist., mkd. ½ S8 BT.		
	0	A pinon, 7 ins. diam., bears N. 70½° W., 46 lks. dist., mkd. ½ S5 BT.		
	43.20	Ridge, bears N. and S.		
	47.20	Wash, 30 lks. wide, with 4 ft. banks, drains S. 25° W.		
	50.60	Graded road to Salt Springs, bears N. 50° E., 30 lks. dist., then N. 20° E. and S. 50° W., 120 lks. dist., then Westerly.		
	54.60	Graded road to Salt Springs, bears S. 55° E. and N. 55° W:		
	60.20	Graded road to Salt Springs, bears E. curving NE. and S. 20° W.		
	69.30	Spur, slopes S.; desc. over SW. slope.		
	77.00	Wash, 20 1ks. wide, 2 ft. deep, drains S.		
	80.02	The cor. of secs. 5, 6, 7 and 8.		
		Land, rolling. Soil, rocky and sandy clay loam. Timber, juniper, pine and pinon: Undergrowth, sagebrush and scrub oak.		
		N. 89°55' W., bet. secs. 6 and 7.		
		Over rolling land, along the S. slope of Poverty Mountain, through medium timber.		

TO THE PERSON NAMED OF THE PER

,	CHAINS	
	25.10	Wash, 25 lks. wide, with 5 ft. banks, drains S. 25° W.
	30.20	Track road, bears SE. and NW.
	33.00	Track road, bears S. 10° E. and N. 10° W.
	37.30	Fence, bears N. and S., ascend over steep SE. slope.
	40.00	Point for the ½ sec. cor. of secs. 6 and 7.
		Set the iron post 22 ins. in the ground, brass cap mkd.
		T34N R11W 2 S 6 5 7 1969
		from which
		A juniper, 6 ins. diam., bears S. 38½° E., 81 lks. dist., mkd. ½ S7 BT.
		A pine, 18 ins. diam., bears N. $23\frac{1}{4}$ ° W., 82 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
		Raise a mound of stone N. of the cor.
	46.90	Narrow rocky ridge, bears N. and S.; desc. over steep .W. slope.
	59.70	Wash, 10 1ks. wide, with 4 ft. banks, drains S. 20° W., 80 1ks. dist., thence south.
	63.50	Underground water line to Salt Springs, bears NE. and S. 60° W.
	76.30	Wash, 10 1ks. wide, with 5 ft. banks, drains SE.
	77.10	Graded road to Salt Springs, bears S. 20° E. and N. 20° W., 150 lks. dist., then W.
	79.40	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	•	T34N R12W R11W S 1 S 6 S12 S 7 1926
		from which the original bearing trees:
		A cedar, 14 ins. diam., bears N. 5° E., 86 lks. dist., mkd. T34N R11W S6 BT. (Record, 75 lks. dist.).
		A cedar, 9 ins. diam., bears S. 14½° E., 116 lks. dist., mkd. T34N R11W S7 BT. (Record, S. 10° E., 75 lks. dist.).
ξ		

1		
CHAINS		
	A cedar, 20 ins. diam., bears S. 50° W., 99 1ks. dist., mkd. T34N R12W S12 BT. (Record, 80 1ks. dist.).	
	A cedar, 8 ins. diam., bears N. 66½° W., 61 lks. dist., mkd. BT in a partially overgrown blaze. (Record, 11 ins. diam. and 79 lks. dist.).	
	The N. edge of a steel storage tank, bears S. 85° 06' E., 13.95 chs. dist., tank is 6 ft. high and 35 ft. diam.	
	An E. and W. fence line, bears South 87 lks. dist.	
	Land, rolling. Soil, rocky clay loam. Timber, pine, juniper and pinon. Undergrowth, sagebrush and grama grass.	
	From the cor. of secs. 5, 6, 7 and 8.	
	N. 0°18' W., bet. secs. 5 and 6.	
	Ascend over S. slope of Poverty Mountain, through medium timber and undergrowth.	
21.80	Ridge, bears E. and W.	
40.00	Point for the ½ sec. cor. of secs. 5 and 6.	
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	T34N_R11W	
;	s 6 s 5 1969	
• •	from which	
	A juniper, 9 ins. diam., bears N. 19½° E., 16 lks. dist., mkd. ½ S5 BT.	
	A juniper, 8 ins. diam., bears S. 82%° W., 40 lks. dist., mkd. ½ S6 BT.	
45.90	Wash, 20 lks. wide, 4 ft. deep, drains S. 50° W.	
79.06	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.	
	T35N R11W S31 S32 S 6 S 5 T34N 1924	

Subdivision, T. 34 N., R. 11 W.

CHAINS

from which the original bearing trees:

A cedar, 13 ins. diam., bears N. 40° E., 23 lks. dist., mkd. T35N R11W S32 BT.

A cedar, 15 ins. diam., bears S. 84½° E., 63 lks. dist., mkd. T34N R11W S5 BT.

A cedar, 10 ins. diam., bears S. 77½° W., 74 1ks. dist., mkd. T34N R11W S6 BT.

A cedar, 10 ins. diam., bears N. 26° W., 52 lks. dist., mkd. T35N R11W S31 BT.

Land, rolling and mountainous.
Soil, rocky clay loam.
Timber, juniper, pinon and pine.
Undergrowth, sagebrush and oak brush.

General Description

The land in Township 34 North, Range 11 West, is gently rolling in the southern portion becoming progressively rougher and broken to the North. The elevation ranges from 5400 ft. to 6700 ft. above sea level. The soil varies from shallow clay loam to sandy clay loam and limestone cut by numerous gullies and draws. The general drainage is Northerly in the South portion to Southerly in the North portion emptying into Parashant Wash, which enters the Tp. in sec. 7 draining irregularly through the center of the Tp. exiting through section 24.

Scattered to dense cedar and pinon covers most of the Tp. Sagebrush, cacti and grama grass are the predominant undergrowth with oak brush along the S. slope of Poverty Mountain.

A bladed road enters the Tp. in sec. 19 on the W. bdy. running easterly through the southern part of the Tp. A graded road enters the Tp. in sec. 6, running along the foothills of Poverty Mountain providing access for the N. portion of the Tp. with track roads branching off these main roads to most of the remainder.

Allotment fences and several stock ponds have been built within the Tp. Salt Springs tank in sec. 7 and a stock trough in sec. 4 are supplied with water through underground water lines. No mineral activity was noted during the survey.

Form 9180-8 (March 1969)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

7.1227.00101A(1)		
NAMES	CAPACITY	
Ronald G. Williams	Cadastral Surveyor	
Harry K. Smith	Surveying Aide	
Victor E. Templeton	Surveying Aide.	
Manual M. Palma	Surveying Aide	
	•	
•		

CERTIFICATE OF SURVEY

(XK(We), Jerrold E. Knight and John H. Witmer , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 24th day

of July , 19 69 XX (We) have completed the survey of the subdivisional

lines in Township 34 North, Range 11 West,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by (MA), (us) and under (MA) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Sept. 2, 1970

(Date)

Sept. 2, 1970

(Cadastral Surveyor)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date APR 2 4 1972 BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the completion survey of the subdivisional lines in Township 34 North, Range 11 West, of the Gila and Salt River Meridian, Arizona,

executed by Jerrold E. Knight and John H. Witmer, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

OCT 1 2 1972

(Date)

(Chief, Division of Company)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.