

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 13 NORTH, RANGE 11 EAST

TOWNSHIP 14 NORTH, RANGES 10 and 11 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Louis D. Gilbert, Cadastral Surveyor

Under special instructions dated July 1, 19 70, which provided for the surveys  
included under Group Number 527, approved July 1, 1970,  
and assignment instructions dated July 20, 19 70.

Survey commenced July 21, 19 70

Survey completed September 23, 19 70

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION  
CORNER MONUMENTS

Tp. 13 N. R. 11 E. Mer. G&SR

6	5	4	3 2	2	1
7	8	9	10	11	12
18	17 5	16 2	15	14	13
19 5	20 4	21	22	23	24
30	29 4	28	27	26	25
31	32	33	34	35	36

Tp. 14 N. R. 10 E. Mer. G&SR

6	5	4	3	2	1 9
7	8	9	10	11	12 8
18	17	16	15	14	13
19	20	21	22	23 9	24 7
30	29	28	27	26	25 7
31	32	33	34	35	36

Tp. 14 N. R. 11 E. Mer. G&SR

11	6	5 17	4	3	2	1
11	7	8	9	10 13	11	12
10	18	17 14	16	15	14	13
10	19 16	20 15	21	22	23	24
	30	29 14	28 13	27	26	25
	31	32	33	34	35	36

Township 13 North, Range 11 East  
 Township 14 North, Range 10 East  
 Township 14 North, Range 11 East  
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 1, 1970 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination is 14° E.

Township 13 North, Range 11 East, G&SR M., Arizona

The subdivisional lines were surveyed in 1900 by P. Contzen.

Remonumentation, T. 13 N., R. 11 E., Arizona

The cor. of secs. 9, 10, 15 and 16, monumented by a sandstone, 16 x 12 x 4 ins., firmly set 10 ins. in the ground, mkd. 4 notches on E. face and 3 notches on S. face, from which the orig. bearing trees

A dead pine, 12 ins. diam., bears N. 64 3/4° E., 130 lks. dist., mkd. NR11ES10 BT.  
 (Note: record dist. 100 lks.).

A fallen pine, 36 ins. diam., bears S. 20° E., 64 lks. dist., mkd. T13NR11ES15 BT.

A pine, 32 ins. diam., bears S. 78½° W., 141 lks. dist., mkd. T13NR11ES16 BT.

A fallen and rotted pine, bears N. 82° W., 127 lks. dist., mkd. T13NR11ES9 BT.

At the cor. point

Set the iron post, 12 ins. in the ground, in a mound of stone, brass cap mkd.

T13N R11E  
 S 9 | S10  
 S16 | S15  
 1970

from which

A pine, 14 ins. diam., bears N. 22° E., 34 lks. dist., mkd. T13N R11E S10 BT.

A pine, 12 ins. diam., bears S. 4° E., 41½ lks. dist., mkd. T13N R11E S15 BT.

Remonumentation, T. 13 N., R. 11 E., Arizona

CHAINS

A pine, 10 ins. diam., bears N. 28° W., 16½ lks. dist., mkd. T13N R11E S9 BT.

Bury the orig. cor. stone in the mound of stone alongside the iron post.

The ¼ sec. cor. of secs. 3 and 10, monumented by a rock in place, no mks., verified by record course and dist. from the orig. bearing trees

A pine, 16 ins. diam., bears N. 34½° E., 55 lks. dist., mkd. with an overgrown blaze.

A pine, 14 ins. diam., bears S. 27 3/4° W., 11 lks. dist., mkd. ¼ S10 BT.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T13N R11E

¼  $\frac{S}{S10}$

1970

The ¼ sec. cor. of secs. 16 and 17, reestablished by record course and dist. from the orig. bearing trees

A pine stump, 14 ins. diam., bears S. 75½° E., 28 lks. dist., mkd. ¼ S16 BT.

A pine stump, 40 ins. diam., bears N. 41° W., 17 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T13N R11E

¼  $\frac{S17}{S16}$

1970

from which

A pine, 20 ins. diam., bears N. 26° E., 30 lks. dist., mkd. ¼ S16 BT.

A pine, 25 ins. diam., bears N. 17° W., 92 lks. dist., mkd. ¼ S17 BT.

The cor. of secs. 8, 9, 16 and 17, monumented by a sandstone, 18 x 12 x 3 ins., firmly set 10 ins. in the ground, mkd. 4 notches on E. face and 4 notches on S. face, from which the orig. bearing trees

A pine, 30 ins. diam., bears N. 85° E., 111 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears S. 66½° E., 102 lks. dist., mkd. with an overgrown blaze.

Remonumentation, T. 13 N., R. 11 E., Arizona

CHAINS

A pine stump, 36 ins. diam., bears S. 33½° W.,  
58 lks. dist., mkd. T13N R11E S17 BT.

A rotted pine stump, bears N. 55° W., 55 lks.  
dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T13N R11E

S 8 | S 9

S17 | S16

1970

from which

A pine, 14 ins. diam., bears S. 85° W., 21½ lks.  
dist., mkd. T13N R11E S17 BT.

A pine, 10 ins. diam., bears N. 15° W., 57 lks.  
dist., mkd. T13N R11E S8 BT.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 29, 30, 31 and 32, monumented by a  
sandstone, 18 x 10 x 8 ins., firmly set 10 ins. in the  
ground, mkd. 5 notches on E. face and 1 notch on S.  
face, from which the orig. bearing trees

A pine, 40 ins. diam., bears N. 7° E., 52½ lks.  
dist., mkd. T13N R11E S29 BT.

A dead pine, 12 ins. diam., bears S. 58½° E.,  
21 lks. dist., mkd. T13N R11E S32 BT.

Unable to find any evidence of the other orig.  
bearing tree.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T13N R11E

S30 | S29

S31 | S32

1970

from which

A Douglas fir, 6 ins. diam., bears S. 40° W.,  
2 lks. dist., mkd. T13N R11E S31 BT.

A pine, 12 ins. diam., bears N. 50° W.,  
51 lks. dist., mkd. T13N R11E S30 BT.

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 13 N., R. 11 E., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, reestablished by record course and dist. from an orig. bearing tree

A pine, 18 ins. diam., bears N.  $23\frac{1}{2}^{\circ}$  W., 61 lks. dist., mkd. 30 BT.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T13N R11E

$\frac{1}{4}$

S30 | S29

1970

from which

An oak, 12 ins. diam., bears N.  $3^{\circ}$  E., 41 lks. dist., mkd. T13N R11E  $\frac{1}{4}$  S29 BT.

The cor. of secs. 19, 20, 29 and 30, monumented by a sandstone, 16 x 6 x 6 ins., firmly set 8 ins. in the ground, mkd. 5 notches on E. face and 2 notches on S. face, from which the orig. bearing trees

A pine, 30 ins. diam., bears N.  $34\frac{1}{2}^{\circ}$  E., 50 lks. dist., mkd. T13N R11E S20 BT.

An oak, 8 ins. diam., bears S.  $56^{\circ}$  E., 41 lks. dist., mkd. T13N R11E S29 BT.

A pine, 26 ins. diam., bears S.  $51\frac{1}{2}^{\circ}$  W., 32 lks. dist., mkd. T13N R11E S30 BT.

A pine, 29 ins. diam., bears N.  $42\frac{1}{2}^{\circ}$  W., 41 lks. dist., mkd. T13N R11E S19 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T13N R11E

S19 | S20

S30 | S29

1970

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, reestablished by record course and dist. from the orig. bearing trees

A pine stump, 36 ins. diam., bears S.  $15^{\circ}$  W., 4 lks. dist., no mks.

The roothole of a fallen pine, 30 ins. diam., bears N.  $17^{\circ}$  W.,  $11\frac{1}{2}$  lks. dist., pine mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.

## Remonumentation, T. 13 N., R. 11 E., Arizona

## CHAINS

T13N R11E

 $\frac{1}{4}$  S20  
S29

1970

from which

A pine, 6 ins. diam., bears N. 35° E., 8 lks.  
dist., mkd.  $\frac{1}{4}$  S 20 BT.

A pine, 8 ins. diam., bears S. 12° E., 34 lks.  
dist., mkd.  $\frac{1}{4}$  S29 BT.

The orig. cor. stone, a sandstone, 16 x 10 x 8 ins.,  
mkd.  $\frac{1}{4}$  on one face, was found down the slope where it  
had slid.

Bury the orig. cor. stone in the mound of stone along-  
side the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, monumented by a  
sandstone, 14 x 12 x 5 ins., firmly set 8 ins. in the  
ground, mkd. 30 on S. face, from which the orig. bearing  
trees

A dead pine, 8 ins. diam., bears N. 44 $\frac{1}{2}$ ° W.,  
13 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

A pine stump, 22 ins. diam., bears S. 48° W.,  
56 lks. dist., no mks.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T13N R11E

 $\frac{1}{4}$  S19  
S30

1970

from which

A pine, 6 ins. diam., bears N. 5° E., 49 lks.  
dist., mkd.  $\frac{1}{4}$  S19 BT.

A pine, 9 ins. diam., bears S. 42° W., 24 lks.  
dist., mkd.  $\frac{1}{4}$  S30 BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, reestablished by  
record course and distance from the remains of the  
orig. bearing trees

A pine stump, 30 ins. diam., bears N. 31 $\frac{1}{4}$ ° E.,  
43 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

A pine stump, 36 ins. diam., bears S. 14° E.,  
39 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.



6.

## Remonumentation, T. 13 N., R. 11 E., Arizona

CHAINS

T13N R11E

 $\frac{1}{4}$   $\frac{S17}{S20}$ 

1970

from which

A pine, 25 ins. diam., bears N. 36° W., 70 lks.  
dist., mkd. T13N R11E  $\frac{1}{4}$  S17 BT.

## Remonumentation, T. 14 N., R. 10 E., Arizona

## CHAINS

Township 14 North, Range 10 East, G&SR M., Arizona

The subdivisional lines were surveyed in 1881 by T. F. White.

Remonumentation, T. 14 N., R. 10 E., Arizona

The cor. of secs. 23, 24, 25 and 26, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A fallen pine, 36 ins. diam., bears N. 33° E., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears S. 74° E., 67 lks. dist., mkd. with an overgrown blaze.

A rotted pine stump, bears S. 72° W., 61 lks. dist., no mks.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T14N R10E	
S23	S24
S26	S25
1970	

from which

A pine, 20 ins. diam., bears N. 70° E., 106 lks. dist., mkd. T14N R10E S24 BT.

A pine, 14 ins. diam., bears S. 7° W., 85 lks. dist., mkd. T14N R10E S26 BT.

An oak, 12 ins. diam., bears N. 70° W., 28 lks. dist., mkd. T14N R10E S23 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, monumented by a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 28 ins. diam., bears S. 55° W., 88 lks. dist., no mks.

Remonumentation, T. 14 N., R. 10 E., Arizona

CHAINS

A pine stump, 28 ins. diam., bears N. 45° W.,  
42 lks. dist., no mks.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound  
of stone, brass cap mkd.

T14N R10E

$\frac{1}{2}$  S24  
S25

1970

from which

An oak, 12 ins. diam., bears S. 65° E., 74 lks.  
dist., mkd.  $\frac{1}{2}$  S25 BT.

A pine, 20 ins. diam., bears N. 55° W., 81 lks.  
dist., mkd.  $\frac{1}{2}$  S24 BT.

The  $\frac{1}{2}$  sec. cor. of secs. 11 and 12, monumented by a  
rotted pine post, 4 ins. squared, 8 ins. long, buried  
under the surface of the ground, no mks., from which  
the orig. bearing trees

A pine, 20 ins. diam., bears S. 31° E., 6 lks.  
dist., dimly mkd.  $\frac{1}{2}$  S BT.

A pine, 17 ins. diam., bears S. 45° W., 10 lks.  
dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T14N R10E

$\frac{1}{2}$   
S11 | S12

1970

Bury the orig. cor. post alongside the iron post.

Remonumentation, T. 14 N., R. 10 E., Arizona

CHAINS

The cor. of secs. 1, 2, 11 and 12, reestablished by record course and dist. from the orig. bearing trees

A pine, 34 ins. diam., bears N. 66° E., 22 lks. dist., mkd. with an overgrown blaze.

A pine, 34 ins. diam., bears S. 24° E., 11 lks. dist., mkd. TXIVNRXEX11.

An alligator juniper, 8 ins. diam., bears S. 71° W., 13 lks. dist., mkd. TXIVNRXEXI.

A pine stump, 20 ins. diam., bears N. 44° W., 54 lks. dist., mkd. TXIVNRXEII.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T14N R10E  
 $\frac{S\ 2}{S11} | \frac{S\ 1}{S12}$   
 1970

The  $\frac{1}{4}$  sec. cor. of secs. 23 and 26, monumented by a pine post, 4 ins. squared, 4 ft. long, set in a mound of stone, no mks., from which the orig. bearing trees

A pine, 25 ins. diam., bears S. 58° W., 60 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears N. 60° W., 17 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 26 ins. in the ground, in a collar of stone, brass cap mkd.

T14N R10E  
 $\frac{1}{4} \frac{S23}{S26}$   
 1970

Reset the orig. cor. post alongside the iron post.

Remonumentation, T. 14 N., R. 11 E., Arizona

CHAINS

Township 14 North, Range 11 East, G&SR M., Arizona

The west and north boundaries and subdivisional lines were surveyed in 1881 by T. F. White.

Remonumentation, T. 14 N., R. 11 E., Arizona

The cor. of secs. 13, 18, 19 and 24, T. 14 N., Rs. 10 and 11 E., monumented by a pine post, 4 ins. squared, 4 ft. long, set in a mound of stone, mkd. TXIVNRXIE on one face, from which the orig. bearing trees

A fallen pine, 40 ins. diam., bears N. 32° E., 82 lks. dist., mkd. with an overgrown blaze.

A pine stump, 50 ins. diam., bears S. 52° E., 147 lks. dist., mkd. TXIVRXIEXIX.

An oak, 20 ins. diam., bears S. 32° W., 77 lks. dist., mkd. with an overgrown blaze.

An oak, 16 ins. diam., bears N. 63° W., 45 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 14 ins. in the ground, in a mound of stone, brass cap mkd.

T14N  
R10E R11E  
S13|S18  
S24|S19  
1970

from which

A pine, 8 ins. diam., bears N. 12° E., 30 lks. dist., mkd. T14N R11E S18 BT.

A pine, 6 ins. diam., bears S. 53° E., 54 lks. dist., mkd. T14N R11E S19 BT.

Reset the orig. cor. post alongside the iron post.

The ¼ sec. cor. of secs. 13 and 18, T. 14 N., Rs. 10 and 11 E., monumented by a mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A pine stump, 32 ins. diam., bears N. 18° E., 102 lks. dist., mkd. with an overgrown blaze.

A pine stump, 36 ins. diam., bears N. 36° W., 26 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 12 ins. in the ground, in a mound of stone, brass cap mkd.

## Remonumentation, T: 14 N., R. 11 E., Arizona

CHAINS

T14N  
R10E R11E  
 $\frac{1}{2}$   
S13|S18  
1970

from which

An oak, 5 ins. diam., bears N. 38° E., 51 lks.  
dist., mkd.  $\frac{1}{2}$  S18 BT.

A pine, 5 ins. diam., bears S. 37° W., 121 lks.  
dist., mkd.  $\frac{1}{2}$  S13 BT.

The cor. of secs. 1, 6, 7 and 12; reestablished by  
record course and dist. from the orig. bearing trees

A pine, 35 ins. diam., bears N. 46° E., 111 lks.  
dist., mkd. with an overgrown blaze.

The roothole of a fallen pine, bears S. 14° E.,  
25 lks. dist., pine mkd. TXIVNRXIEVII BT.

A pine, 32 ins. diam., bears S: 59° W., 61 lks.  
dist., mkd. XIVNRXE.

A pine, 40 ins. diam., bears N. 43° W., 84 lks.  
dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar  
of stone, brass cap mkd.

T14N  
R10E R11E  
S 1 | S 6  
S12 | S 7  
1970

from which

A pine, 18 ins. diam., bears S. 74° E., 96 lks.  
dist., mkd. T14N R11E S7 BT.

The Tp. cor. of Tps. 14 and 15 N., Rs. 10 and 11 E.,  
monumented by a mound of stone, verified by record  
course and dist. from the orig. bearing trees

A pine, 32 ins. diam., bears N. 19° E., 115 lks.  
dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S. 67° E., 6 lks.  
dist., mkd. with an overgrown blaze.

A pine, 32 ins. diam., bears N. 22° W., 55 lks.  
dist., mkd. with an overgrown blaze.

Unable to find any evidence of the other orig.  
bearing tree.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar  
of stone, brass cap mkd.

Remonumentation, T. 14 N., R. 11 E., Arizona

CHAINS

T15N  
R10E R11E  
S36 | S31  
S 1 | S 6  
T14N  
1970

from which

A pine, 6 ins. diam., bears S. 68° W., 39 lks. dist., mkd. T14N R10E S1 BT.

The ¼ sec. cor. of secs. 6 and 31, Tps. 14 and 15 N., R. 11 E., reestablished by record course and dist. from the orig. bearing trees

A pine stump, 20 ins. diam., 5 ft. high, bears S. 47° W., 39 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears N. 66° W., 23 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T15N R11E  
¼ S31  
S 6  
T14N  
1970

The cor. of secs. 9, 10, 15 and 16, reestablished by record course and dist. from the remains of the orig. bearing trees

A pine stump, badly rotted, bears S. 13° E., 94 lks. dist., no mks.

A pine stump, 40 ins. diam., 5 ft. high, bears N. 21° W., 52 lks. dist., mkd. TXIVNRXIE.

Unable to find any evidence of the other orig. bearing trees.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T14N R11E  
S 9 | S10  
S16 | S15  
1970

from which

The center of a steel water tank, 9 ft. diam., bears N. 36° E., 29 lks. dist.

A pine, 16 ins. diam., bears S. 36° E., 130 lks. dist., mkd. T14N R11E S15 BT.

Cor. is 11 lks. E. of a fence bearing N. and S.

Remonumentation, T. 14 N., R. 11 E., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, monumented by an iron rebar,  $\frac{1}{2}$  in. diam., 14 ins. long, set 12 ins. in the ground, verified by record course and dist. from the orig. bearing trees

A pine, 22 ins. diam., bears S.  $44^\circ$  E., 61 lks. dist., mkd.  $\frac{1}{4}$  S.

A pine, 25 ins. diam., bears N.  $28^\circ$  W., 39 lks. dist., mkd.  $\frac{1}{4}$  S.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T14N R11E  
 $\frac{1}{4}$   
 S 9 | S10  
 1970

Reset the iron bar alongside the iron post.

The cor. of secs. 28, 29, 32 and 33, monumented by a pine post, 4 ins. squared, 4 ft. long, set in a mound of stone, mkd. XXVIII on one face and XXXIII on another face, from which the orig. bearing trees

A pine stump, 35 ins. diam., bears N.  $26^\circ$  E., 82 lks. dist., no mks.

A pine, 22 ins. diam., bears S.  $52^\circ$  E., 62 lks. dist., mkd. with an overgrown blaze.

A pine, 25 ins. diam., bears S.  $68^\circ$  W., 59 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears N.  $66^\circ$  W., 51 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T14N R11E  
S29 | S28  
S32 | S33  
 1970

Reset the orig. cor. post alongside the iron post.

The cor. of secs. 20, 21, 28 and 29, monumented by a pine post, 4 ins. squared, 3 ft. long, set in a mound of stone, no mks., from which the orig. bearing trees

A pine, 20 ins. diam., bears S.  $48^\circ$  E., 82 lks. dist., mkd. with an overgrown blaze.

A pine, 22 ins. diam., bears S.  $34\frac{1}{2}^\circ$  W., 27 lks. dist., mkd. with an overgrown blaze.

A fallen pine, 32 ins. diam., bears N.  $11\frac{1}{2}^\circ$  W., 54 lks. dist., mkd. with an overgrown blaze.

Unable to find any evidence of the other orig. bearing tree.



Remonumentation, T, 14 N., R. 11 E.

CHAINS

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T14N R11E  
S20|S21  
S29|S28  
 1970

from which

An alligator juniper, 14 ins. diam., bears N. 58° E., 115 lks. dist., mkd. T14N R11E S21 BT.

An oak, 5 ins. diam., bears N. 9° W., 70 lks. dist., mkd. T14N R11E S20 BT.

Reset the orig. cor. post alongside the iron post.

The cor. of secs. 8, 9, 16 and 17, reestablished by record course and dist. from the orig. bearing trees

A pine, 25 ins. diam., bears S. 59° E., 61 lks. dist., mkd. with an overgrown blaze.

A dead pine, 27 ins. diam., bears S. 53° W., 66 lks. dist., mkd. TXIVNRXIE.

Unable to find any evidence of the other orig. bearing trees.

At the cor. point

Set the iron post over a chiseled + in sold rock, in a mound of stone, brass cap mkd.

T14N R11E  
S 8|S 9  
S17|S16  
 1970

from which

A pine, 10 ins. diam., bears N. 6° E., 87 lks. dist., mkd. T14N R11E S9 BT.

A pine, 6 ins. diam., bears N. 35° W., 67 lks. dist., mkd. T14N R11E S8 BT.

The cor. of secs. 19, 20, 29 and 30, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A dead pine, 32 ins. diam., bears N. 16° E., 96 lks. dist., mkd. TXIVNRXIEXX.

A rotted pine stump, bears S. 47° E., 74 lks. dist., no mks.

A dead pine, 42 ins. diam., bears N. 32° W., 133 lks. dist., mkd. TXIVNRXIEXIX.

Unable to find any evidence of the other orig. bearing tree.

## Remonumentation, T. 14 N., R. 11 E., Arizona

## CHAINS

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T14N R11E  
 S19|S20  
 S30|S29  
 1970

from which

A pine, 20 ins. diam., bears N. 68° E., 31 lks. dist., mkd. T14N R11E S20 BT.

A pine, 14 ins. diam., bears S. 80° E., 20 lks. dist., mkd. T14N R11E S29 BT.

An oak, 6 ins. diam., bears S. 42° W., 12 lks. dist., mkd. T14N R11E S30 BT.

A pine, 14 ins. diam., bears N. 47° W., 38 lks. dist., mkd. T14N R11E S19 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, monumented by a pine post, 4 ins. squared, 4 ft. long, set in a mound of stone, mkd.  $\frac{1}{4}$  S on one face, from which the orig. bearing trees

A pine stump, 26 ins. diam., bears S. 84° E., 57 lks. dist., no mks.

A fallen and rotted pine, bears S. 79° W., 57 lks. dist., no mks.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.

T14N R11E  
 $\frac{1}{4}$   
 S19|S20  
 1970

from which

A pine, 6 ins. diam., bears N. 52° W., 19 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

An oak, 12 ins. diam., bears N. 10° W., 57 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

Reset the orig. cor. post alongside the iron post.

The cor. of secs. 17, 18, 19 and 20, monumented by a pine post, badly rotted, 4 ins. squared, 3 ft. long, set in the ground, no mks., from which the orig. bearing trees

A fallen pine, 36 ins. diam., bears N. 82° E., 33 lks. dist., mkd. with an overgrown blaze.

A pine stump, 32 ins. diam., bears S. 43° E., 42 lks. dist., mkd. NRXIEXX.

Remonumentation, T. 14 N., R. 11 E., Arizona

CHAINS

A pine stump, 30 ins. diam., bears S. 31° W.,  
90 lks. dist., no mks.

A fallen and rotted pine, bears N. 70° W., 80 lks.  
dist., no mks.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of  
stone, brass cap mkd.

T14N R11E  
S18|S17  
S19|S20  
1970

from which

A pine, 6 ins. diam., bears N. 54° E., 50 lks.  
dist., mkd. T14N R11E S17 BT.

A pine, 8 ins. diam., bears S. 25° E., 67 lks.  
dist., mkd. T14N R11E S20 BT.

A pine, 6 ins. diam., bears S. 37° W., 69 lks.  
dist., mkd. T14N R11E S19 BT.

A pine, 18 ins. diam., bears N. 12° W., 28 lks.  
dist., mkd. T14N R11E S18 BT.

Reset the orig. cor. post alongside the iron post.

The ¼ sec. cor. of secs. 17 and 20, monumented by a  
mound of stone, verified by record course and dist.  
from the orig. bearing trees

An oak, 12 ins. diam., bears S. 58° E., 47 lks.  
dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears N. 74° W., 27 lks.  
dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar  
of stone, brass cap mkd.

T14N R11E  
¼ S17  
S20  
1970

The ¼ sec. cor. of secs. 18 and 19, monumented by a  
pine post, 4 ins. squared, 3 ft. long, set in a mound  
of stone, no mks., from which the orig. bearing trees

A pine, 36 ins. diam., bears South, 52 lks.  
dist., mkd. with an overgrown blaze.

A dead oak, 20 ins. diam., bears N. 32° W.,  
52 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Remonumentation, T. 14 N., R. 11 E., Arizona

CHAINS

Set the iron post, 4 ins. in the ground, in a mound of stone, brass cap mkd.

T14N R11E

$\frac{1}{4}$   $\frac{S18}{S19}$   
1970

from which

An oak, 5 ins. diam., bears N. 46° W., 10½ lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

Reset the orig. cor. post alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 8, monumented by a rotted post, set flush with ground, in a mound of stone, no mks., from which the orig. bearing trees

A rotted pine, bears S. 87° E., 21 lks. dist., no mks.

A pine stump, 38 ins. diam., bears N. 73° W., 61 lks. dist., no mks.

At the cor. point

Set the iron post, 12 ins. in the ground, in a mound of stone, brass cap mkd.

T14N R11E

$\frac{1}{4}$   $\frac{S5}{S8}$   
1970

from which

A pine, 7 ins. diam., bears S. 35° W., 29 lks. dist., mkd.  $\frac{1}{4}$  S8 BT.

A pine, 4 ins. diam., bears N. 10° W., 37 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

Bury the remains of the orig. cor. post alongside the iron post.

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
George S. Pickett	District Ranger
Elrod L. Buckner	Asst. District Ranger
Timothy Armi	Surveying Aid
Eric Eichenauer	Surveying Aid
(All U. S. Forest Service personnel)	

19

CERTIFICATE OF SURVEY

(I) ~~(WE)~~, Louis D. Gilbert, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1970, (I) ~~(WE)~~ have remonumented a portion of the cadastral survey corners in Township 13 North, Range 11 East, and Township 14 North, Ranges 10 and 11 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 2, 1970

(Date)

*Louis D. Gilbert*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date NOV 16 1970

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 13 North, Range 11 East, and Township 14 North, Ranges 10 and 11 East, all of the Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

MAY 21 1973

(Date)

*Clark L. Gamm*

(Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Cadastral Survey) GPO 849-626~~