

BOOK 5025

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 14 N. R. 15 E. Mer. G&SR

	3	3	2	2	1
6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 13 N. R. 12 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations: 4 (corner 24-25), 5 (corner 25-26), 6 (corner 23-24), 7 (corner 28-29), 7 (corner 27-28), 6 (corner 33-34)

Tp. 14 N. R. 13 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Monument locations: 8 (corner 31-32), 9 (corner 32-33), 9 (corner 33-34), 10 (corner 27-28), 10 (corner 26-27), 11 (corner 28-29), 11 (corner 27-28), 12 (corner 20-21), 13 (corner 30-31), 13 (corner 29-30), 14 (corner 30-31)

Township 14 North, Range 15 East
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners in Township 14 North, Range 15 East, Township 13 North, Range 12 East and Township 14 North, Range 13 East, G&SRM., Arizona. The remonumentation is by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The remonumentation was executed in accordance with the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 577, Arizona, dated July 29, 1975. The approval of the Special Instructions on July 31, 1975 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 14 North, Range 15 East, G&SRM., Arizona

The north boundary was surveyed in 1893 by Philip Contzen.

Re monumentation, N. Bdy., T. 14 N., R. 15 E.,
G&SRM., Arizona

The mean magnetic declination is $13\frac{3}{4}^{\circ}$ E.

The cor. of secs. 1, 2, 35 and 36, Tps. 14 and 15 N., Rs. 15 E., monumented by a limestone, 17x12x6 ins., firmly set, projecting 12 ins. above ground, mkd. with 5 grooves on W face and 1 groove on E face, from which the remains of the original bearing trees

A pine, 9 ins. diam., bears N. 70° E., 82 lks. dist., mkd. with a partially healed blaze - scribe marks illegible. (Record, N. 71° E., 86 lks.)

A cedar, 16 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ E., 54 lks. dist., mkd. T14N R15E S1 BT. (Record, S. 45° E., 58 lks.)

A cedar stump, 16 ins. diam., bears S. 42° W., 99 lks. dist., mkd. T14N R15E S2 BT. (Record, S. 40° W., 92 lks.)

A stump hole, bears N. 88° W., 95 lks. dist.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground; mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

Remonumentation, T. 14 N., R. 15 E., G&SRM., Arizona

CHAINS

T 15 N R 15 E
S 35 | S 36
S 2 | S 1
 T 14 N
 1975

Deposit the mkd. stone alongside the iron post.

The cor. of secs. 2, 3, 34 and 35, Tps. 14 and 15 N.,
 Rs. 15 E., monumented by a limestone in place, 3x1x $\frac{1}{2}$ ft.
 above ground, mkd. with a + at the cor. point, from which
 the remains of the original bearing trees

A cedar, 8 ins. diam., bears S. 27 $\frac{1}{2}$ ° E., 73 lks.
 dist., mkd. T14N R15E S2 BT. (Record, a pine,
 bears S. 25° E., 73 lks.)

A cedar, 10 ins. diam., bears S. 67 $\frac{3}{4}$ ° W., 80 lks.
 dist., mkd. T14N R15E S3 BT. (Record, S. 71° W.,
 79 lks.)

A cedar stump, 8 ins. diam., bears N. 32 $\frac{1}{2}$ ° W.,
 57 lks. dist., no marks. (Record, N. 30° W.,
 57 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., over the
 +, mound of stone, 4 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 15 N R 15 E
S34 | S35
S 3 | S 2
 T 14 N
 1975

The cor. is located in an E-W fence.

The cor. of secs. 3, 4, 33 and 34, Tps. 14 and 15 N.,
 Rs. 15 E., monumented by a limestone, 16x14x3 ins., firm-
 ly set, projecting 10 ins. above ground, mkd. with 3
 grooves on the E face and 3 grooves on the W face, set in
 a small mound of stone, from which the remains of the
 original bearing trees

A stump hole, bears S. 57 $\frac{1}{2}$ ° E., 46 lks. dist.,
 a down pine alongside, 8 ins. diam., mkd.
 T14N R15E S3 BT. (Record, S. 61° E., 44 lks.)

A stump hole, bears S. 18° W., 70 lks. dist.,
 a down pine alongside, 10 ins. diam., mkd.
 T14N R15E S4 BT. (Record, S. 20 $\frac{1}{2}$ ° W., 70 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins.
 in the ground, with brass cap mkd.

Remonumentation, T. 14 N., R. 15 E., G&SRM., Arizona

CHAINS

T 15 N R 15 E
 S 33 | S 34
 S 4 | S 3
 T 14 N
 1975

from which a new bearing tree

A cedar, 8 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., 145.5 lks. dist., mkd. T14N R15E S3 BT.

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of the cor.

The cor. is located 3 lks. S of an E-W fence.

The $\frac{1}{2}$ sec. cor. of secs. 5 and 32, Tps. 14 and 15 N., Rs. 15 E., monumented by a limestone 16x12x6 ins., firmly set, projecting 9 ins. above ground, mkd. $\frac{1}{2}$ on N face.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 15 N R 15 E
 $\frac{1}{2}$ S 32
 S 5
 T 14 N
 1975

from which a new bearing tree

A cedar, 4 ins. diam., bears South, 132 lks. dist., mkd. X BT at the base.

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 1 ft. high, N of the cor.

The cor. is located 5.5 lks. S of an E-W fence.

The cor. of secs. 5, 6, 31 and 32, Tps. 14 and 15 N., Rs. 15 E., monumented by a limestone, 20x16x4 ins., firmly set, projecting 14 ins. above ground, mkd. with 5 grooves on E face and 1 groove on the W face, from which the remains of the original bearing trees

A cedar stump, 16 ins. diam., bears N. 16° E., 36 lks. dist., no marks visible. (Record, N. 16° E., 38 lks.)

A stump hole, bears S. 65° E., 116 lks. dist., a down pinon alongside, 8 ins. diam., mkd. T14N R15E S5 BT.

Remonumentation, T. 14 N., R. 15 E., G&SRM., Arizona

CHAINS

A pinon, 9 ins. diam., bears S. 27° W., 43 lks. dist., mkd. with a healed blaze.

A pinon, 14 ins. diam., bears N. 7° W., 88 lks. dist., mkd. T15N R15E S31 BT. (Record, N. 70° W., 91 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 3½ ft. base to top, with brass cap mkd.

T 15 N R 15 E
 S 31 | S 32
 S 6 | S 5
 T 14 N
 1975

Deposit the mkd. stone alongside the iron post.

The cor. is located 39 lks. S of a fence cor. with fences extending N, E and W.

Township 13 North, Range 12 East, G&SRM., Arizona

The east boundary was resurveyed and the subdivisional lines were surveyed by Daniel Drummond in 1893.

Remonumentation, E. Bdy., T. 13 N., R. 12 E., G&SRM., Arizona

The mean magnetic declination is 13½° E.

The cor. of secs. 19, 24, 25 and 30, Tps. 13 N., Rs. 12 and 13 E., monumented by a sandstone, 15x10x6 ins., firmly set, projecting 6 ins. above ground, mkd. with 4 grooves on the N face and 2 grooves on the S face, from which the remains of the original bearing trees

A pine stump, 6 ft. high, 32 ins. diam., bears N. 57½° E., 51 lks. dist., mkd. T13N R13E S19 BT. (Record, N. 54° E., 50 lks.)

A pine, 24 ins. diam., bears S. 14° E., 12 lks. dist., mkd. T13N R13E S30 BT.

A pine, 24 ins. diam., bears S. 45° W., 113 lks. dist., mkd. T13N R12E S25 BT.

A pine snag, 10 ft. high, 12 ins. diam., bears N. 60° W., 87 lks. dist., mkd. T13N R12E S24 BT.

At the cor. point

Remonumentation, T. 13 N., R. 12 E., G&SRM., Arizona

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 13 N
R 12 E R 13 E
S 24 | S 19
S 25 | S 30
1975

Deposit the mkd. stone alongside the iron post.

Remonumentation, Subdivision, T. 13 N., R. 12 E.,
G&SRM., Arizona

The cor. of secs. 25, 26, 35 and 36, monumented by a sandstone, 22x14x8 ins., firmly set, projecting 14 ins. above ground, mkd. with 1 groove on the S face and 1 groove on the E face, from which the remains of the original bearing trees

A pine stump, 32 ins. diam., 6 ft. high, bears N. 75° E., 78 lks. dist., mkd. T13N R12E S25 BT. (Record, N. 75° E., 77 lks.)

A stump hole, bears S. 74° E., 152 lks. dist., a down pine alongside, 20 ins. diam., no marks visible.

A stump hole, bears S. 64° W., 65 lks. dist., a down oak alongside, 8 ins. diam., no marks visible.

A pine, 24 ins. diam., bears N. 43° W., 80 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 13 N R 12 E
S26 | S25
S35 | S36
1975

from which new bearing trees

A pine, 14 ins. diam., bears S. $32\frac{1}{2}^\circ$ E., 55 lks. dist., mkd. T13N R12E S36 BT.

A pine, 6 ins. diam., bears S. $73\frac{1}{2}^\circ$ W., 10 lks. dist., mkd. T13N R12E S35 BT.

Deposit the mkd. stone alongside the iron post.

Remonumentation, T. 13 N., R. 12 E., G&SRM., Arizona

CHAINS

The cor. of secs. 23, 24, 25 and 26, monumented by a sandstone, 16x10x6 ins., firmly set, projecting 6 ins. above ground, mkd. with 1 groove on the E face and 2 grooves on the S face, from which the remains of the original bearing trees

A pine stump, 26 ins. diam., 5 ft. high, bears N. 65° E., 63 lks. dist., no marks visible.

A pine, 34 ins. diam., bears S. 62° W., 121 lks. dist., mkd. T13N R12E S2 B, other marks illegible.

A dead oak, 9 ins. diam., bears N. 3½° W., 127 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 13 N R 12 E
 S 23 | S 24
 S 26 | S 25
 1975

from which a new bearing tree

A pine, 8 ins. diam., bears N. 41½° E., 24.5 lks. dist., mkd. T13N R12E S24 BT.

Deposit the mkd. stone alongside the iron post.

The ¼ sec. cor. of secs. 33 and 34, monumented by a sandstone, 26x14x8 ins., firmly set, projecting 14 ins. above ground, mkd. ¼ on W face, from which the remains of the original bearing trees

A sawed off pine stump, 26 ins. diam., bears N. 45° E., 10 lks. dist., mkd. with a healed blaze.

A pine, 30 ins. diam., bears S. 50° W., 88 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone, 2 ft. base to top, with brass cap mkd.

T 13 N R 12 E
 S 33 | S 34
 1975

from which a new bearing tree

Remonumentation; T. 13 N.; R. 12 E., G&SRM., Arizona

CHAINS

A ponderosa pine, 4 ins. diam., bears N. 67° E.,
10.5 lks. dist., mkd. X at breast height and
BT at the base.

Deposit the mkd. stone alongside the iron post.

The cor. of secs. 27, 28, 33 and 34, monumented by a
sandstone, 26x12x10 ins., firmly set, projecting 10 ins.
above ground, mkd. with 1 groove on the S face and 3
grooves on the E face, from which the remains of the
original bearing trees

A pine stump, 24 ins. diam., bears N. 30° E.,
3 lks. dist., mkd. with a healed blaze.

A pine, 32 ins. diam., bears S. 54° E., 126 lks.
dist., mkd. with a healed blaze. (Record,
S. 54° E., 124 lks.)

A pine, 30 ins. diam., bears S. 81½° W., 46 lks.
dist., mkd. with a healed blaze. (Record,
S. 80° W., 44 lks.)

A pine, 16 ins. diam., bears N. 30° W., 13 lks.
dist., mkd. with a healed blaze. (Record,
N. 30° W., 11 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, mound of stone, 2 ft. base to top, with
brass cap mkd.

T	13	N	R	12	E
	S	28		S	27
	S	33		S	34
	1975				

Deposit the mkd. stone alongside the iron post.

The ¼ sec. cor. of secs. 28 and 33, monumented by a sand-
stone, 16x12x4 ins., firmly set, projecting 6 ins. above
ground, mkd. ¼ on N face, from which the remains of the
original bearing trees.

A decayed pine stump, 9 ins. diam., bears
N. 9° W., 34 lks. dist., no marks visible.

A stump hole, bears S. 20° W., 20 lks. dist.,
a down pine alongside, 16 ins. diam., mkd.
¼ S BT.

A dead ponderosa pine, 32 ins. diam., bears
S. 45° W., 10 lks. dist., mkd. ¼ with a
partially healed blaze. (Note: There
is no record of this bearing tree)

At the cor. point

Remonumentation, T. 13 N., R. 12 E., G&SRM., Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 13 N R 12 E

¼ $\frac{S\ 28}{S\ 33}$

1975

from which a new bearing tree

A ponderosa pine, 10 ins. diam., bears N. 41½° E., 44 lks. dist., mkd. ¼ S28 BT.

Deposit the mkd. stone alongside the iron post.

Township 14 North, Range 13 East, G&SRM., Arizona

The south boundary and subdivisional lines were surveyed in 1893 by Daniel Drummond.

Remonumentation, S. Bdy., T. 14 N., R. 13 E., G&SRM., Arizona

The mean magnetic declination is 13¾° E.

The cor. of secs. 4, 5, 32 and 33, Tps. 13 and 14 N., Rs. 13 E., monumented by a sandstone, 20x14x4 ins., firmly set, projecting 10 ins. above ground, mkd. with 4 grooves on the E face and 2 grooves on the W face, with a ½ in. re-bar, 18 ins. long, alongside, from which the remains of the original bearing trees

A pine, 25 ins. diam., bears N. 66° E., 35 lks. dist., mkd. with a healed blaze.

A pine stump, 12 ins. diam., cut flush with the ground, bears S. 25° E., 63 lks. dist., no marks visible.

A pine, 16 ins. diam., bears S. 57° W., 6 lks. dist., mkd. with a healed blaze. (Record, S. 47° W., 6 lks.)

A pine stump, 26 ins. diam., 3 ft. high, bears N. 52° W., 93 lks. dist., mkd. T, no other marks visible. (Record, N. 52° W., 92 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

Remonumentation, T. 14 N., R. 13 E., G&SRM., Arizona

CHAINS

T 14 N R 13 E
 S 32 | S 33
 S 5 | S 4
 T 13 N
 1975

Deposit the mkd. stone and re-bar alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, Tps. 13 and 14 N.,
 Rs. 13 E., monumented by a sandstone, 20x9x7 ins., firmly
 set, projecting 14 ins. above ground, mkd. $\frac{1}{4}$ on N face,
 from which the remains of the original bearing trees

A pine snag, 18 ins. diam., bears N. 32° E.,
 39 lks. dist., mkd. with a partially healed
 blaze, $\frac{1}{4}$ visible.

A pine, 26 ins. diam., bears south, 15 lks. dist.,
 mkd. with a burned out blaze. (Record,
 South, 14 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins.
 in the ground, mound of stone, 2 $\frac{1}{2}$ ft. base to top, with
 brass cap mkd.

T 14 N R 13 E
 $\frac{1}{4}$ S 33
 S 4
 T 13 N
 1975

Deposit the mkd. stone alongside the iron post.

The cor. of secs. 3, 4, 33 and 34, Tps. 13 and 14 N.,
 Rs. 13 E., monumented by a sandstone, 14x8x6 ins., firm-
 ly set, projecting 4 ins. above ground, mkd. with 3
 grooves on the E face, from which the remains of the
 original bearing trees

A juniper, 20 ins. diam., bears N. 50° E.,
 36 lks. dist., mkd. with a healed blaze.

A pine, 18 ins. diam., bears S. 6 $\frac{1}{2}$ ° E., 43 lks.
 dist., mkd. with a healed blaze.

A pine, 12 ins. diam., bears S. 40° W., 3 lks.
 dist., mkd. with a healed blaze.

A pine stump, 12 ins. diam., bears N. 60° W.,
 69 lks. dist., no marks visible. (Record,
 N. 60° W., 68 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins.
 in the ground, mound of stone, 2 ft. base to top, with
 brass cap mkd.

Remonumentation, T. 14 N., R. 13 E., G&SRM., Arizona

CHAINS

T 14 N R 13 E

S 33	S 34
S 4	S 3

T 13 N

1975

Deposit the mkd. stone alongside the iron post.

The cor. is located 40 lks. E of a track road which bears S. 15° E. and N. 15° W.

Remonumentation, Subdivision, T. 14 N., R. 13 E.,
G&SRM., Arizona

The ¼ sec. cor. of secs. 33 and 34, determined by record dist., from the remains of the original bearing trees

A pine, 18 ins. diam., bears N. 67½° E., 38 lks. dist., mkd. with a healed blaze. (Record, N. 65° E., 38 lks.)

A stump hole, bears S. 84½° W., 50 lks. dist., a down pine, 16 ins. diam., mkd. with a healed blaze. I open the blaze to reveal the marks ¼ S BT. (Record, S. 87° W., 50 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone, 2 ft. base to top, with brass cap mkd.

T 14 N R 13 E

S 33	S 34
¼	

1975

from which a new bearing tree

A ponderosa pine, 16 ins. diam., bears S. 48½° W., 106 lks. dist., mkd. ¼ S33 BT.

The cor. of secs. 27, 28, 33 and 34, monumented by a sandstone, 22x10x5 ins., firmly set in a small mound of stone, mkd. with 3 grooves on the E face and 1 groove on the S face, from which the original bearing trees

A pine, 12 ins. diam., bears N. 69½° E., 53 lks. dist., mkd. with a healed blaze.

A pine, 16 ins. diam., bears S. 54¾° E., 75 lks. dist., mkd. T14N R13E S34 BT. (Record, S. 55½° E., 73 lks.)

A pine, 22 ins. diam., bears S. 55¼° W., 100 lks. dist., mkd. with illegible scribe marks. (Record, S. 54° W., 99 lks.)

Remonumentation, T. 14 N., R. 13 E., G&SRM., Arizona

CHAINS

A pine, 24 ins. diam., bears N. 57½° W., 12 lks. dist., mkd. with illegible scribe marks. (Record, N. 60° W., 11 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 14 N R 13 E
S 28 S 27
S 33 S 34

1975

Deposit the mkd. stone alongside the iron post.

The ¼ sec. cor. of secs. 32 and 33, reestablished by record dist. from the remains of the original bearing trees

A pine stump, 32 ins. diam., 5 ft. high, bears N. 81° E., 95 lks. dist., mkd. ¼ S BT. (Record, N. 79° E., 95 lks.)

A pine, 20 ins. diam., bears N. 51½° W., 86 lks. dist., mkd. with a healed blaze. (Record, S. 50° W., 86 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 14 N R 13 E
S 32 S 33

1975

from which a new bearing tree

A ponderosa pine, 16 ins. diam., bears S. 14° E., 187 lks. dist., mkd. ¼ S33 BT.

The cor. of secs. 28, 29, 32 and 33, monumented by a sandstone, 16x16x5 ins., firmly set, projecting 8 ins. above ground, mkd. with 4 grooves on the E face and 1 groove on the S face, from which the original bearing trees

An oak, 8 ins. diam., bears N. 10° E., 51 lks. dist., mkd. with a healed blaze.

A pine, 14 ins. diam., bears S. 45° E., 82 lks. dist., mkd. with a healed blaze.

An oak, 10 ins. diam., bears S. 79° W., 81 lks. dist., mkd. with a healed blaze.

Remonumentation, T. 14 N., R. 13 E., G&SRM., Arizona

CHAINS

An oak, 8 ins. diam., bears N. 34° W., 56 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 14 N R 13 E
 S 29 | S 28
 S 32 | S 33
 1975

Deposit the mkd. stone alongside the iron post.

The ¼ sec. cor. of secs. 28 and 29, monumented by a sandstone, 16x10x8 ins., loosely set, mkd. ¼ on W face, from which the remains of the original bearing trees

A dead oak, 9 ins. diam., bears S. 82° E., 12 lks. dist., mkd. with a healed blaze.

A stump hole, bears S. 18° W., 34 lks. dist., a down pine alongside, 12 ins. diam., mkd. ¼ S. BT.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 14 N R 13 E
 S 29 | S 28
 1975

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears S. 44½° E., 48 lks. dist., mkd. ¼ S28 BT.

A ponderosa pine, 6 ins. diam., bears N. 59° W., 131 lks. dist., mkd. ¼ S29 BT.

Deposit the mkd. stone alongside the iron post.

The cor. of secs. 20, 21, 28 and 29, monumented by a sandstone, 18x12x5 ins., firmly set, projecting 10 ins. above ground, mkd. with 2 grooves on the S face, no other marks, from which the original bearing trees

A pine, 20 ins. diam., bears N. 86° E., 78 lks. dist., mkd. T14N R13E S21 BT.

Remonumentation, T. 14 N., R. 13 E., G&SRM., Arizona

CHAINS

A pine, 15 ins. diam., bears S. 52° E., 74 lks. dist., mkd. T14N R13E S28 BT.

A pine, 21 ins. diam., bears S. 30° W., 56 lks. dist., mkd. with a healed blaze.

An oak, 10 ins. diam., bears N. 16° W., 26 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 14 N R 13 E
 S 20 | S 21
 S 29 | S 28
 1975

Deposit the mkd. stone alongside the iron post.

The cor. of secs. 29, 30, 31 and 32, monumented by a sandstone, 18x12x5 ins., firmly set, projecting 8 ins. above ground, mkd. with 5 grooves on the E face and 1 groove on the S face, from which the original bearing trees

A dead pine, 26 ins. diam., bears N. 41½° E., 72 lks. dist., mkd. with a partially healed blaze, marks visible but illegible. (Record, N. 34° E., 72 lks.)

A pine, 27 ins. diam., bears S. 12° E., 80 lks. dist., mkd. with a healed blaze.

A pine, 16 ins. diam., bears S. 66½° W., 125 lks. dist., mkd. T14N R13E S31 BT.

A pine, 30 ins. diam., bears N. 82° W., 98 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 14 N R 13 E
 S 30 | S 29
 S 31 | S 32
 1975

Deposit the mkd. stone alongside the iron post.

The cor. is located 6.5 lks. N of a fence which bears S. 50° E. and N. 50° W.

Remonumentation, T. 14 N., R. 13 E., G&SRM., Arizona

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by a sandstone, 18x15x6 ins., firmly set, projecting 12 ins. above ground, mkd. $\frac{1}{4}$ on N face with a + on top, from which the original bearing trees

A dead pine, 22 ins. diam., bears N. 18° W., 11 lks. dist., mkd. $\frac{1}{4}$ S BT.

An oak, 14 ins. diam., bears S. 70° W., 71 lks. dist., mkd. with a healed blaze. (Record, a pine, 6 ins. diam., bears S. 70° W., 71 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.

T 14 N R 13 E
 $\frac{1}{4}$ $\frac{S 29}{S 32}$
 1975

Deposit the mkd. stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented by a sandstone, 24x15x8 ins., firmly set, projecting 14 ins. above ground, mkd. $\frac{1}{4}$ on W face, from which the remains of the original bearing trees

A stump hole, bears S: 6° E., 25 lks. dist., a down pine alongside, 18 ins. diam., no marks visible. (Record, S. 15° E., 25 lks.)

A pine, 15 ins. diam., bears N. 74° W., 23 lks. dist., mkd. $\frac{1}{4}$ S BT. (Record, S. 80° W., 23 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, mound of stone, 2 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 14 N R 13 E
 $\frac{1}{4}$
 S 30 | S 29
 1975

from which a new bearing tree

A ponderosa pine, 5 ins. diam., bears N. 64 $\frac{1}{2}$ ° E., 74.5 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Deposit the mkd. stone alongside the iron post.

CERTIFICATE OF SURVEY

(I) ~~WE~~ Paul L. Reeves, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of July, 19 75, (I) ~~WE~~ have remonumented a portion of the cadastral survey corners in Township 14 North, Range 15 East, Township 13 North, Range 12 East and Township 14 North, Range 13 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 15, 1976 (Date) Paul L. Reeves (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 14 North, Range 15 East, Township 13 North, Range 12 East and Township 14 North, Range 13 East, all of the Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

APR 27 1977 (Date) Bernard W. Falgout (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626