1

Form 9600-9 (December 1979) (formerly 9180-6)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

ORIGINAL

#### FIELD NOTES

of the
Dependent Resurvey of Portions
of the South and West Boundaries
and a Portion of the Subdivisional Lines
and the Survey of Subdivisions in
Sections 7, 18 and 29
Township 23 North, Range 2 West
Of the Gila and Salt River Meridian,
In the State of Arizona
EXECUTED BY
EXECUTED BY
Harry K. Smith, Cadastral Surveyor
Under special instructions dated <u>May 20</u> , 19 <u>80</u> , approved <u>May 21, 1980</u> ,
, which provided for the surveys included under U.S. Survey/Group
Number 619 , and assignment instructions dated May 21 , 19 80
Survey commenced June 9 , 19 80
Survey completed October 8 , 19 80

#### INDEX DIAGRAM

Township 23 North, Range 2 West

<b>6</b> 45	46 5 45 45 44	35 34 34	27 8 26 26	19 2 18	1
11 7 10 43 42	44 8 43 42	33 9 32 32	25 10 24 24	18 11 17	12
10 18 9 41 40	42 17 41 40	32 16 31 31	24 15 23 23	16 14 15	13
19 39 38	40 20 39 38	31 21 30 29	23 22 22 21	15 28 14	24
30 37 36	38 29 37 36	29 28 28 28	21 20 20	14 26 13	25
<b>31</b>	35 s <sub>2</sub>	28 33 27 6 5	20 84 19 4 3	13 35 12	36

Subdivision of Sec. 7 .... pp 46-50
Subdivision of Sec. 18 .... pp 50
Subdivision of Sec. 29 .... pp 50-51
Description of the Atchison Topeka and Sante Fe Railway .... pp 51-52

T 23 N, R 2 W, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the dependent resurvey of portions of the south and west boundaries and a portion of the subdivisional lines and the survey of subdivisions in sections 7, 18 and 29, of Township 23 North, Range 2 West, Gila and Salt River Meridian, Arizona.

The boundaries and subdivisional lines were surveyed by J.T. Smith in 1883. The west boundary was resurveyed by Fred Mensch, U.S. Surveyor, in 1916. The north boundary was resurveyed by Edward N. Thompson, U.S. Transitman, in 1916.

This survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 619, Arizona, dated May 20, 1980.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The center line and right-of-way data of the Atchison Topeka and Santa Fe Railway in sections 7 and 9, is taken from Atchison Topeka and Santa Fe Railway Right-of-Way and Track Maps 220-11975-30-1 and 220-11975-30-2; and Bureau of Land Management Serial Register Page AR 033935, a copy of the center line description is incorporated into these field notes.

The direction of lines was determined from direct solar observations and refers to the true meridian. Distances were measured electronically with a Hewlett Packard 3820 and Zeiss SM 4 instruments.

The geographic position of the corner of sections 2, 3, 34 and 35, Tps. 22 and 23 N, Rs. 2 W, determined by a tie to the U.S.C.&G.S. triangulation station "SLAB", is as follows:

Latitude: 35°19'30.42" N Longitude: 112°28'37.64" W

The mean magnetic declination is 14°30' E.

Dependent Resurvey of a Portion of the S Bdy., T 23 N, R 2 W, Gila and Salt River Mer., Arizona

(Restoring the survey executed by J.T. Smith in 1883)

Beginning at the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the Tp., monumented with a sandstone,  $15 \times 12 \times 6$  ins., set 7 ins. in the ground, mkd. with 2 grooves on the E face and 4 grooves on the W face, from which bearing trees, not of record

#### CHAINS

- A juniper, 18 ins. diam., bears N 61° E, 99 lks. dist., mkd. with partially healed blaze and illegible scribe marks.
- A juniper, 20 ins. diam., bears S 72° E, 100 lks. dist., mkd. TXXIIN RIIW SII BT, on a partially healed blaze.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

T23N R2W S34 | S35 S 3 | S 2 T22N 1980

from which new bearing trees

- A juniper, 8 ins. diam., bears N 27° E, 126 lks. dist., mkd. T23N R2W S35 BT.
- A juniper, 5 ins. diam., bears S 10° W,  $89\frac{1}{2}$  lks. dist., mkd. T22N R2W S3 BT.
- A juniper, 5 ins. diam., bears N 81° W, 32 lks. dist., mkd. T23N R2W S34 BT.

Deposit the mkd. stone alongside the iron post.

U.S.C.&G.S. triangulation station "SLAB", bears S 37°11'24" E, 306.818 chs. dist., monumented with a standard brass tablet,  $3\frac{1}{2}$  ins. diam., firmly set in a concrete block, 11 ins. sq., projecting 2 ins. above ground, mkd. SLAB 1958.

N 89°39' W, bet. secs. 34 and 3.

Over rolling land, through dense juniper.

40.27

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, monumented with a malpais stone, 10 x 8 x 8 ins. loosely set, mkd.  $\frac{1}{4}$  on the N face, with a scattered mound of stone N of cor.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

from which

- A juniper, 6 ins. diam., bears N 46° E, 41 lks. dist., mkd. 4 S34 BT.
- A juniper, 9 ins. diam., bears S 42° E, 90 lks. dist., mkd. 4 S3 BT.

	CHAINS	
		Deposit the mkd. stone alongside the iron post.
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of
		cor.
		N 90° IIII W boringing now management
	ho 05	N 89°44' W, beginning new measurement.
	40.35	The cor. of secs. 3, 4, 33 and 34, monumented with a malpais stone, 16 x 12 x 7 ins., firmly set 6 ins. in the ground, mkd. with 3 notches on the E and W edges, with a mound of stone, 3 ft. base, 8 ins. high, N of cor., from which the original bearing trees
		A juniper, 16 ins. diam., bears S 8° E, 166 lks. dist., mkd. IIN RIIW SIV BT, on a partially healed blaze. (Record: N 48° E 98 lks. dist.)
		A dead juniper, 17 ins. diam., bears N 56° W, 194 lks. dist., mkd. TXXIIIN RIIW SXXXIII BT. (Record: S 75° E, 98 lks. dist.)
		At the cor. point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
		T23N R2W S33   S34 S 4   S 3 T22N 1980
		from which new bearing trees
		A juniper, 7 ins. diam., bears N 82½° E, 42½ lks. dist., mkd. T23N R2W S34 BT.
ı		A juniper, 6 ins. diam., bears S 72° W, 66 lks. dist., mkd. T22N R2W S4 BT.
		A juniper, 8 ins. diam., bears N 79° W, 38 lks. dist., mkd. T23N R2W S33 BT.
		Deposit the mkd. stone alongside the iron post.
		Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
		S 89°27' W, bet. secs. 33 and 4.
		Over rolling land, through scattering to dense juniper.
	40.13	The ¼ sec. cor. of secs. 4 and 33, monumented with a malpais stone, 20 x 11 x 10 ins., firmly set 10 ins. in the ground, mkd. ¼ on N face, with a mound of stone, 3 ft. base, 6 ins. high, N of cor.
		At the cor. point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

CHAINS	
	T23N R2W 1 S33 T22N 1980
	from which new bearing trees
	A juniper, 10 ins. diam., bears N 31½° E, 125 lks. dist., mkd. ¼ S33 BT.
	A juniper, 16 ins. diam., bears S 61° E, 184 lks. dist., mkd. ½ S4 BT.
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	N 89°18' W, beginning new measurement.
3.00	Center of graded road, Forest Service Road No. 142, bears S 35° E and N 35° W.
40.21	The cor. of secs. 4, 5, 32 and 33, monumented with a malpais stone, 18 x 14 x 12 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 4 grooves on the E face and 2 grooves on the W face, from which the original bearing trees
	A juniper, 20 ins. diam., bears N 20¾° E, 25 lks. dist., mkd. TXXIIIN RIIW SXXXIII BT. (Record: N 10° E, 22 lks. dist.)
	A juniper, 26 ins. diam., bears S 33% E, 97 lks. dist., mkd. N RIIW SIV BT on a partially healed blaze. (Record: S 36° E, 91 lks. dist.)
	At the cor. point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over an X chiseled in solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	T23N R2W S32   S33 S 5   S 4 T22N 1980
	from which new bearing trees
	A juniper, 8 ins. diam., bears S 481° W, 68 lks. dist., mkd. T22N R2W S5 BT.
	A juniper, 14 ins. diam., bears N 173° W, 62 lks. dist., mkd. T23N R2W S32 BT.
	Deposit the mkd. stone in the mound of stone.
	N 89°20' W, bet. secs. 32 and 5.

		5 -1, 11 - 11, dilla cala callo lilyci rici , Al izolia
	CHAINS	
		Over rolling land, through dense juniper.
ë.	40.18	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented with a malpais stone, $14 \times 14 \times 7$ ins., firmly set 4 ins. in the ground, mkd. with $\frac{1}{4}$ on the N face, with a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, N of cor., from which the original bearing trees
		A dead juniper, 27 ins. diam., bears N 47° E, 35 lks. dist., mkd. ½ S BT. (Record: N 50° E, 37 lks. dist.)
		A dead juniper, 15 ins. diam., bears S 27° W, 106 lks. dist., mkd. ‡ S BT. (Record: S 12° W, 105 lks. dist.)
		At the cor. point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 19 ins. in the ground, with brass cap mkd.
		T23N R2W
		from which new bearing trees
		A juniper, 11 ins. diam., bears S 48° E, 17½ lks. dist., mkd. ¼ S5 BT.
		A juniper, 9 ins. diam., bears N 73½ W, 20 lks. dist., mkd. ¼ S32 BT.
		Deposit the mkd. stone alongside the iron post.
		Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, N of cor.
		N 89°18' W, beginning new measurement.
	40.26	The cor. of secs. 5, 6, 31 and 32, monumented with a malpais stone, 13 x 13 x 13 ins., firmly set 8 ins. in the ground, mkd. with 5 grooves on E face and 1 groove on W face.
		At the cor. point
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
		T23N R2W S31   S32 S 6   S 5 T22N 1980
		from which new bearing trees
		A juniper, 12 ins. diam., bears N $43\frac{1}{2}$ ° E, $110\frac{1}{2}$
		lks. dist., mkd. X BT at the base.

CHAINS	A juniper, 19 ins. diam., bears S 55° E, 86 lks. dist., mkd. T22N R2W S5 BT.
	A juniper, 11 ins. diam., bears S 24½° W, 104 lks. dist., mkd. T22N R2W S6 BT.
	A juniper, 4 ins. diam., bears N 35% W, 131 lks. dist., mkd. X at breast height, BT at the base.
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 4 ft. base, 1½ ft. high, W of cor.
	Cor. is located 30 lks. E of a N and S track road, and 47 lks. E of a N and S fence.
	N 89°23' W, bet. secs. 31 and 6.
	Over gently rolling land, through dense juniper.
40.64	Point for the ½ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	T23N R2W
	from which
	A juniper, 19 ins. diam., bears N 61° E, 41½ lks. dist., mkd. ‡ S31 BT.
	A juniper, 12 ins. diam., bears S 61° W, 56 lks. dist., mkd. ‡ S6 BT.
80.37	The cor. of Tps. 22 and 23 N, Rs. 2 and 3 W, monumented with an iron post, 3 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which bearing trees as recorded in 1916
	A limb of a juniper, 7 ins. diam., bears N 55° E, 176 lks. dist., mkd. TXXIIN RIIW SXXXI BT.
	A juniper, 11 ins. diam., bears S 75° E, 8 lks. dist., with illegible scribe marks visible through a partially healed blaze.
	A juniper, 11 ins. diam., bears N 24° W, 109 lks. dist., with illegible scribe marks visible through a partially healed blaze.
	A fence cor., bears S 60° E, 2 lks. dist., fences extend S and W.

CHAINS	
	(Restoring the resurvey executed by Fred Mensch in 1916)
	From the cor. of secs. 18 and 19 only, on the W bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which bearing trees as recorded in 1916
	A juniper, 20 ins. diam., bears N 69° E, 30 lks. dist., mkd. T23N R2W S18 BT.
	A juniper, 14 ins. diam., bears S 68° E, 15 lks. dist., mkd. T23N R2W S19 BT.
	The cor. is 3 lks. W of fence line, bears N and S.
	N 0°33' E, on the W bdy. of sec. 18.
	Over rolling land, along fence line, with medium juniper to E, and railed juniper to W.
39•05	The ½ sec. cor. of sec. 13 only, T 23 N, R 3 W, monumented with an iron post, 1 in. diam., projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey. Both bearing trees have been railed out. The cor. is 9 lks. W of fence line, bears N and S.
40.24	The ½ sec. cor. of sec. 18 only, T 23 N, R 2 W, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which bearing trees as recorded in 1916
	A juniper, 12 ins. diam., bears N 83½° E, 67 lks. dist., mkd. S18 and other illegible scribe marks through a partially healed blaze.
	A badly deteriorated juniper, 8 ins. diam., bears S 37° E, 7 lks. dist., limb laying alongside is mkd. 4 S18 BT.
	Cor. is located 4 lks. W of fence line, bears N and S.
	N 0°53' E, beginning new measurement.
38.82	The cor. of secs. 12 and 13 only, T 23 N, R 3 W, monumented with an iron post, 3 ins. diam., projecting 1 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey. Both bearing trees have been railed out. The cor. is 2 lks. W of a fence line, bears N and S.
40.25	The cor. of secs. 7 and 18 only, T 23 N, R 2 W, monumented with an iron post, 3 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which bearing trees as recorded in 1916

CHAINS		
	A juniper, 24 ins. diam., bears N 38° E, 31½ lks. dist., mkd. S7 BT and other illegible scribe marks through a partially healed blaze. (Record: 30 lks. dist.)	
	A juniper, 12 ins. diam., bears S 82½° E, 102 lks. dist., mkd. T23N R2W S18 BT.	
	Cor. is located 1 lk. W of fence line, bears N and S.	
	N 1°33' E, on the W bdy. of sec. 7.	
	Over rolling land, along fence line, railed juniper to W and dense juniper to E.	
5.451	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway and fence, bears N 60°13' E and S 60°13' W.	
5.56	Telegraph line, bears N 60° E and S 60° W.	
5.84	Track road, bears N 60° E and S 60° W.	
7.225	Center line of the Atchison Topeka and Santa Fe Railway right-of-way and center of railroad tracks, bears N 60°13' E and S 60°13' W.	
7.48	Center of railroad tracks, bears N 60°13' E and S 60°13' W.	
8.999	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 60°13' E and S 60°13' W.	
9.02	Fence, bears N 60° E and S 60° W, enter medium to dense juniper.	
20.115	Point for the S 1/16 sec. cor. of sec. 7 only.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.	
	T23N R3W   R2W   S 1/16 S7 1980	
	from which	
	A juniper, 16 ins. diam., bears S 63° E, 70½ lks. dist., mkd. S 1/16 S7 BT.	
	Cor. is located 14 lks. E of fence, bears N and S.	
22.84	Track road, bears N 57° E and S 57° W.	
38.68	The ¼ sec. cor. of sec. 12 only, T 23 N, R 3 W, monumented with an iron post, 1 in. diam., projecting 14 ins. above a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1916 resurvey, from which the 1916 bearing trees	
	A juniper, 10 ins. diam., bears S 49° W, 58 lks. dist., mkd. ‡ S12 BT.	

CHAINS	A juniper, 8 ins. diam., bears N 70° W, 68 lks. dist., mkd. ½ S12 BT.
	Cor. is located 7 lks. E of fence, bears N and S.
40.23	The ¼ sec. cor. of sec. 7 only, T 23 N, R 2 W, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which the 1916 bearing trees
	A dead juniper, 12 ins. diam., bears N 47° E, 82 lks. dist., mkd. ‡ S7 BT.
	A dead juniper, 6 ins. diam., bears S 17° E, 43 lks. dist., mkd. ‡ S7 BT.
	Raise a mound of stone, 3 ft. base, 15 ins. high, around iron post.
	Add the marks 1980 to the brass cap.
	Cor. is located 7 lks. E of fence, bears N and S.
	N 1°42' E, beginning new measurement.
38.45	The cor. of secs. 1 and 12 only, T 23 N, R 3 W, monumented with an iron post, 3 ins. diam., projecting 30 ins. above ground, and in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1916 resurvey, from which the 1916 bearing trees
	A juniper, 12 ins. diam., bears S 35° W, 90 lks. dist., mkd. T23N R3W S12 BT.
	A dead juniper, 14 ins. diam., bears N 78½° W, 45 lks. dist., mkd. T23N R2W S1 BT.
	Cor. is located 6 lks. W of fence, bears N and S.
40.525	The cor. of secs. 6 and 7 only, T 23 N, R 2 W, monumented with an iron post, 3 ins. diam., projecting 24 ins. above ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 resurvey, from which the bearing trees recorded in 1916
	A juniper limb, 7 ins. diam., bears N 76½° E, 43 lks. dist., mkd. TXXIIIN SVI BT.
	A juniper, 30 ins. diam., bears S 12½° E, 116 lks. dist., mkd. TN RIIW BT and other illegible marks through a partially healed blaze. (Record: 117 lks.dist.)
	Cor. is located 6 lks. W of fence, bears N and S.
	Dependent Resurvey, a Portion of the Subdivisional Lines T 23 N, R 2 W, Gila and Salt River Mer., Arizona
	(Restoring the survey executed by J.T. Smith in 1883)

CHAINS	
	From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the Tp., heretofore described.
	N 0°10' E, bet. secs. 34 and 35.
	Over rolling land, through dense juniper.
42.43	Point for the 4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N_R2W
	S34   S35 1980
	from which
	A juniper, 7 ins. diam., bears N 46° E, 59 lks. dist., mkd. ‡ S35 BT.
	A juniper, 6 ins. diam., bears N 75° W, 8½ lks. dist., mkd. ¼ S34 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
84.86	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W S27   S26 S34   S35 1980
	from which
	A juniper, 6 ins. diam., bears N 53° E, 29½ lks. dist., mkd. T23N R2W S26 BT.
	A juniper, 4 ins. diam., bears S 51° E, 19 lks. dist., mkd. X BT at the base.
	A juniper, 12 ins. diam., bears S 71° W, 14 lks. dist., mkd. T23N R2W S34 BT.
-	A juniper, 7 ins. diam., bears N 32° W, 82 lks. dist., mkd. T23N R2W S27 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From this point the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., bears N 89°06' E, 162.64 chs. dist., monumented with a malpais stone, 18 x 12 x 8 ins., loosely set 4 ins. in the ground, mkd. with 4 grooves on the N face and 1 groove on the S face, with a mound of stone, 2½ ft. base, 1 ft. high, W of cor., from which the original bearing tree
	the N face and 1 groove on the S face, with a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor., from which the

CHAINS A juniper limb, 8 ins. diam., bears S 72° E, 28 lks. dist., mkd. TXXIIIN RIW SXXXI BT. (Record: 21 lks. dist.) At the cor. point Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd. T23N R2W R1W S31 from which new bearing trees A juniper, 8 ins. diam., bears N  $50\frac{1}{2}^{\circ}$  E,  $35\frac{1}{2}$  lks. dist., mkd. T23N R1W S30 BT. A juniper, 8 ins. diam., bears S 26° W, 56 lks. dist., mkd. T23N R2W S36 BT. A juniper, 6 ins. diam., bears N 69° W, 19 lks. dist., mkd. T23N R2W S25 BT. Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor. From the cor. of secs. 26, 27, 34 and 35, a monument for secs. 25, 26, 35 and 36, established in 1962, by the Atchison Topeka and Santa Fe Railway Company, bears N 87°34' E, 82.66 chs. dist., monumented with an open end pipe, 2 ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, from which bearing trees mkd. in 1961 A juniper, 13 ins. diam., bears S 22° W, 81 lks. dist., mkd. BT S35. A juniper, 12 ins. diam., bears N 79° W, 46 lks. dist., mkd. BT S26. This monument was established at record distances from the north and east and is therefore not accepted. The control line was fully retraced, and no evidence of the intervening cors. was found. N 0°12' E, bet. secs. 26 and 27. Over rolling land, through dense juniper. 42.43 Point for the 4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd. T23N R2W

CHAINS	
	from which
	A juniper, 8 ins. diam., bears S 62°E, 104 lks. dist., mkd. ½ S26 BT.
	A juniper, 9 ins. diam., bears N 88° W, 70 lks. dist., mkd. ½ S27 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
45.23	Fence, bears S 70° E and N 70° W.
84.86	The cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 32 x 32 x 20 ins., firmly set 6 ins. in the ground, mkd. X on top, 2 grooves on the E and S faces, and 4 grooves on the N and W faces. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record
	A juniper, 8 ins. diam., bears S 60° E, 25 lks. dist., mkd. SXXVI XXIII.
	A juniper, 12 ins. diam., bears N 86° W, 55 lks. dist., mkd. SXXVI XXIII.
:	At the cor. point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W S22   S23 S27   S26 1980
	from which
	A juniper, 9 ins. diam., bears N 55° E, 113 lks. dist., mkd. T23N R2W S23 BT.
	A sandstone boulder, 42 x 7 x 6 ins. above ground, bears S 26° W, 57½ lks. dist., mkd. X BO on N face.
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W of cor.
	Deposit the mkd. stone in the mound of stone.
	Set a steel fence post alongside the iron post.
	N 0°20' E, bet. secs. 22 and 23.
	Over rolling land, through dense juniper.
39•97	The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 20 x 12 x 4 ins., firmly set 10 ins. in the ground, mkd. X on the top and ¼ on S face. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record

CHAINS

A juniper, 14 ins. diam., bears S 53° E, 118½ lks. dist., mkd.  $\frac{1}{4}$  S BT XXIII.

A juniper, 16 ins. diam., bears S  $12\frac{1}{2}$ ° W, 158 lks. dist., mkd.  $\frac{1}{4}$  S BT XXII.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

T23N R2W
S22 | S23
1980

Deposit the mkd. stone alongside the iron post.

N 0°28' E, beginning new measurement.

39.96

The cor. of secs. 14, 15, 22 and 23, monumented with a sandstone,  $24 \times 14 \times 5$  ins., firmly set in a mound of stone,  $2\frac{1}{2}$  ft. base, 1 ft. high, mkd. X on the top, 3 grooves on the N face, 2 grooves on the E face, 3 grooves on the S face, and 4 grooves on the W face. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record

- A juniper, 12 ins. diam., bears N 56° E, 26 lks. dist., mkd. SXIV BT.
- A juniper, 16 ins. diam., bears S  $66\frac{1}{2}$ ° E, 125 lks. dist., mkd. SXXIII BT.
- A juniper, 12 ins. diam., bears S 84° W, 43 lks. dist., mkd. SXXII BT.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone,  $3\frac{1}{2}$  ft. base, to top, with brass cap mkd.

from which

A sandstone boulder,  $3\frac{1}{2} \times 1\frac{1}{2} \times 1\frac{1}{2}$  ft. above ground, bears N 22° E,  $84\frac{1}{2}$  lks. dist., mkd. X BO on S face.

Deposit the mkd. stone in the mound of stone.

Cor. is located in a dry wash, 50 lks. wide, 2 ft. deep, drains S  $70^{\circ}$  W.

N 0°26' E, bet. secs. 14 and 15.

Over rolling land, through medium to dense juniper.

CHAINS

40.03

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, monumented with a sandstone, 22 x 8 x 4 ins., firmly set 12 ins. in the ground, mkd. X on top and  $\frac{1}{4}$  on S face. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record

- A juniper, 16 ins. diam., bears North,  $37\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S BT SXV.
- A juniper, 16 ins. diam., bears S 70° E,  $15\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S BT SXIV.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

T23N R2W

1

S15 | S14

1980

Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

Deposit the mkd. stone alongside the iron post.

N 0°28' E, beginning new measurement.

40.02

The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 33 x 11 x 4 ins., firmly set 20 ins. in the ground, mkd. X on top, 2 grooves on the N and E faces, 4 grooves on the S and W faces, with a mound of stone, 3 ft. base, 2 ft. high, NW of cor. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record

- A juniper, 10 ins. diam., bears S 87° E, 15 lks. dist., mkd. SXI BT.
- A juniper, 8 ins. diam., bears S 27° E, 79 lks. dist., mkd. SXIV BT.
- A juniper, 12 ins. diam., bears S 34° W, 74 lks. dist., mkd. SXV S BT.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 23 ins. in the ground, with brass cap mkd.

T23N R2W S10 | S11 S15 | S14 1980

from which

A juniper, 8 ins. diam., bears N 46° W, 61½ lks. dist., mkd. T23N R2W S10 BT.

Rebuilt a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W of cor.

-	CHAINS	
		Deposit the mkd. stone alongside the iron post.
		N 0°28' E, bet. secs. 10 and 11.
		Over rolling land, through dense juniper.
	40.16	The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with a sandstone, 30 x 14 x 5 ins., firmly set 12 ins. in the ground, mkd. X on top and $\frac{1}{4}$ on S face, with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N of cor. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record
		A juniper, 16 ins. diam., bears S 18° E, 58½ lks. dist., mkd. ¼ S BT XI.
		A juniper, 7 ins. diam., bears S 24° W, 40 lks. dist., mkd. ¼ S BT X.
		A juniper limb, 8 ins. diam., bears N 78° W, 82½ lks. dist., mkd. ¼ S BT X.
		At the cor. point
		Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	**	T23N R2W
-		S10   S11 1980
		from which
		A juniper, 5 ins. diam., bears S 28° E, 35½ lks. dist., mkd. ¼ S11 BT.
		Rebuilt a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
		Deposit the mkd. stone in the mound of stone.
		N 0°26' E, beginning new measurement.
	24.26	Fence, bears E and W.
	25.751	Center line of the Atchison Topeka and Santa Fe Railway right-of-way, bears N 89°45' E and S 89°45' W.
	25.77	Center of Atchison Topeka and Santa Fe Railway tracks, bears N 89°45' E and S 89°45' W.
	25•99	Center of Atchison Topeka and Santa Fe Railway tracks, bears N 89°45' E and S 89°45' W.
	26.75	Track road, bears E and W.
	27.16	Telegraph line, bears E and W.
	27.30	Fence, bears E and W.
	4 V	

CHAINS

39.98

The cor. of secs. 2, 3, 10 and 11, monumented with a sandstone,  $18 \times 18 \times 5$  ins., firmly set 7 ins. in the ground, mkd. with 1 groove on N face, 2 grooves on E face, 5 grooves on S face, and 4 grooves on W face, with a mound of stone,  $3\frac{1}{2}$  ft. base, 6 ins. high, N of cor. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record

- A juniper, 6 ins. diam., bears S  $89\frac{1}{2}$ ° E,  $23\frac{1}{2}$  lks. dist., mkd. S2 BT.
- A juniper, 15 ins. diam., bears S 51° W, 52 lks. dist., mkd. SX BT.
- A juniper, 30 ins. diam., bears N 24° W, 58 lks. dist., mkd. SIII BT.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T23N R2W S 3 | S 2 S10 | S11 1980

from which

- A juniper, 6 ins. diam., bears N 48½° E, 23 lks. dist., mkd. T23N R2W S2 BT.
- A juniper, 7 ins. diam., bears S  $4\frac{1}{2}$ ° E,  $64\frac{1}{2}$  lks. dist., mkd. T23N R2W S11 BT.

Rebuilt a mound of stone, 2 ft. base, 1 ft. high, W of cor.

Deposit mkd. stone alongside the iron post.

N 0°28' E, bet. secs. 2 and 3.

Over rolling land, through medium to dense juniper.

40.02

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 3, monumented with a sand-stone,  $18 \times 12 \times 10$  ins., firmly set 6 ins. in the ground, mkd. X on top and  $\frac{1}{4}$  on S face, with a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N of cor. This monument, of unknown origin, is accepted as the best available evidence of the original cor., from which bearing trees, not of record

- A pinyon, 15 ins. diam., bears S 58° E, 50 lks. dist., mkd. ¼ S BT II.
- A juniper, 18 ins. diam., bears N 8° W, 50 lks. dist., mkd. ¼ S BT III.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

CHAINS		
	T23N R2W	
	S 3 T S 2 1980	
	from which	
	A juniper, 9 ins. diam., bears N 28½° E, 100 lks. dist., mkd. ¼ S2 BT.	
	Rebuilt a mound of stone, 2½ ft. base, 1 ft. high, W of cor.	
	Deposit the mkd. stone alongside the iron post.	
	N 0°32' E, beginning new measurement.	
2.40	Track road, bears irregularly E and W.	
40.06	Fence, bears E and W.	
40.08	The cor. of secs. 2 and 3 only, on the N bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which bearing trees mkd. in 1883	
	A juniper, 15 ins. diam., bears S 48° E, 36 lks. dist., mkd. TXXIIIN RIIW SII BT. (Record: S 45° E, 34 lks. dist.)	
	A juniper, 18 ins. diam., bears S 62° W, 17 lks. dist., mkd. TXXIIIN RIIW SIII BT. (Record: S 46° W, 9 lks. dist.)	
	From the cor. of secs. 3, 4, 33 and 34, on the S bdy. of the Tp., heretofore described.	
	N 0°19' W, bet. secs. 33 and 34.	
	Over rolling land, through dense juniper.	
40.71	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.	
	T23N R2W	
	S33 T S34 1980	
	from which	
	A juniper, 6 ins. diam., bears S 69° E, 81 lks. dist., mkd. ¼ S34 BT.	
	A juniper, 6 ins. diam., bears S 34° W, 9 lks. dist., mkd. ¼ S33 BT.	
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W of cor.	
	1	

CHAINS	
81.42	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W S28   S27 S33   S34 1980
	from which
	A juniper, 8 ins. diam., bears N 16° E, 72 lks. dist., mkd. T23N R2W S27 BT.
	A juniper, 6 ins. diam., bears S 5° E, 48 lks. dist., mkd. T23N R2W S34 BT.
	A juniper, 15 ins. diam., bears S 51° W, 4½ lks. dist., mkd. T23N R2W S33 BT.
;	A juniper, 7 ins. diam., bears N 50° W, 37 lks. dist., mkd. T23N R2W S28 BT.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 26, 27, 34 and 35.
	S 87°51' W, bet. secs. 27 and 34.
40.68	Point for the 4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W
	from which
	A juniper, 6 ins. diam., bears N 45° E, 56 lks. dist., mkd. ‡ S27 BT.
	A juniper, 9 ins. diam., bears S 23° E, 52½ lks. dist., mkd. ¼ S34 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
73.68	Track road, bears S 35° E and N 35° W.
81.36	The cor. of secs. 27, 28, 33 and 34.
	N 0°18' E, bet. secs. 27 and 28.
	Over rolling land, through dense juniper.

CHAINS	
40.71	Point for the 4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	S28 Î S27 1980
	from which
	A juniper, 12 ins. diam., bears S 57° E, 32½ lks. dist., mkd. ¼ S27 BT.
	A juniper, 8 ins. diam., bears S 39° W, 21½ lks. dist., mkd. ¼ S28 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
45.30	Fence, bears W and E for 40 lks., thence SE.
81.42	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W S21   S22 S28   S27 1980
	from which
	A juniper, 6 ins. diam., bears N 29° E, 38½ lks. dist., mkd. T23N R2W S22 BT.
	A juniper, 7 ins. diam., bears S 44° E, 5½ lks. dist., mkd. T23N R2W S27 BT.
	A juniper, 10 ins. diam., bears S 72° W, 56 lks. dist., mkd. T23N R2W S28 BT.
	A juniper, 6 ins. diam., bears N 54° W, 44½ lks. dist., mkd. T23N R2W S21 BT.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	n in de Gregoria de Agresia de Contratorian de Cambrer, de Cambrer, aparte do directoria de Santa do Cambrer,
	From the cor. of secs. 22, 23, 26 and 27.
	S 85°26' W, bet. secs. 22 and 27.
	Over rolling land, through dense timber.
40.68	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS	
	Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T23N R2W 1 S22 1 S27 1980
	from which
	A juniper, 6 ins. diam., bears N 44° E, 96½ lks. dist., mkd. ¼ S22 BT.
	A juniper, 9 ins. diam., bears S 54½° W, 4 lks. dist., mkd. ¼ S27 BT.
81.37	The cor. of secs. 21, 22, 27 and 28.
	N 0°35' E, bet. secs. 21 and 22.
	Over rolling land, through dense juniper.
40.71	Point for the 4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 17 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T23N R2W
	S21
	from which
	A juniper, 7 ins. diam., bears N 79° E, 31 lks. dist., mkd. ¼ S22 BT.
	A juniper, 6 ins. diam., bears S 80° W, 55½ lks. dist., mkd. ¼ S21 BT.
81.42	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W <u>\$16   \$15</u> <u>\$21   \$22</u> 1980
	from which
	A juniper, 7 ins. diam., bears N 52° E, 6 lks. dist., mkd. T23N R2W S15 BT.
	A juniper, 10 ins. diam., bears S 34° E, 89 lks. dist., mkd. T23N R2W S22 BT.

Dependent Resurvey	, a Portion of	the Subdivisional Lines,
T 23 N. R 2 W.	Gila and Salt	River Mer. Arizona

CHAINS	1 25 M; It 2 W; dila and barb hiver here; At 1201a
	A juniper, 9 ins. diam., bears S 42° W, 103½ lks. dist., mkd. T23N R2W S21 BT.
	A juniper, 12 ins. diam., bears N 53° W, 105 lks. dist., mkd. T23N R2W S16 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 14, 15, 22 and 23.
	S 86°26' W, bet. secs. 15 and 22.
	Over rolling land, through dense juniper.
40.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a fiberglass post, 30 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W 1 S15 S22 1980
	from which
	A juniper, 8 ins. diam., bears N 15° E, 53½ lks. dist., mkd. ½ S15 BT.
	A juniper, 6 ins. diam., bears S 43½° W, 83 lks. dist., mkd. ¼ S22 BT.
	Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.
81.00	The cor. of secs. 15, 16, 21 and 22.
	N 0°25' E, bet. secs. 15 and 16.
	Over rolling land, through dense juniper.
40.71	Point for the ‡ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W
	S16   S15 1980
	from which
	A juniper, 18 ins. diam., bears S 80° E, 92½ lks. dist., mkd. ¼ S15 BT.
	A juniper, 18 ins. diam., bears S 84° W, 62 lks. dist., mkd. ‡ S16 BT.

T	CHAINE	
	CHAINS	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	81.42	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist., there is no remaining evidence of the original cor.
		Set a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$ in. stem, in a concrete filled drill hole, on S face of rock outcropping, 8 ft. high, with top mkd.
		T23N R2W S 9   S10 S16   S15 1980
		from which
		A juniper, 12 ins. diam., bears S 49° E, 55½ lks. dist., mkd. T23N R2W S15 BT.
		A juniper, 7 ins. diam., bears S 45° W, 53½ lks. dist., mkd. T23N R2W S16 BT.
		A juniper, 7 ins. diam., bears N 69½° W, 37½ lks. dist., mkd. T23N R2W S9 BT.
		Cor. is located along S rim of a mesa, edge bears irregularly E and W.
		From the cor. of secs. 10, 11, 14 and 15.
		S 87°26' W, bet. secs. 10 and 15.
		Over rolling land, through medium to dense juniper.
	40.47	Point for the ‡ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with cap mkd.
		T23N R2W 1 S10 1980
		from which
		A juniper, 10 ins. diam., bears N 67½° W, 30½ lks. dist., mkd. ¼ S10 BT.
		A juniper, 8 ins. diam., bears S 23° W, 60 lks. dist., mkd. ‡ S15 BT.
		Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.
	80.94	The cor. of secs. 9, 10, 15 and 16.
		N 0°42' E, bet. secs. 9 and 10.
		Over rolling land, through dense juniper.

	1 25 11, 11 2 11, 4114 414 6415 12161 1161 1, 12 2514
CHAINS	
40.71	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T23N R2W
	S 9 T S10 1980
	from which
	A juniper, 6 ins. diam., bears S 32° E, 57½ lks. dist., mkd. ¼ S10 BT.
	A juniper, 10 ins. diam., bears S 89½° W, 73 lks. dist., mkd. ¼ S9 BT.
53•273	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway and fence, bears N 56°57' E and S 56°57' W. From this point, a point referred to as Point B in Bureau of Land Management Serial Register Page AR 033935, bears S 60°20' W, 25.66 chs. dist.
55.07	Center of railroad tracks, bears N 56°57' E and S 56°57' W.
55•33	Center of railroad tracks, bears N 56°57' E and S 56°57' W.
56.68	Track road, bears N 57° E and S 57° W.
56.90	Telegraph line, bears N 57° E and S 57° W.
57.07	Fence, bears N 57° E and S 57° W.
57•10	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 56°57' E and S 56°57' W.
81.42	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W <u>S 4 S 3</u> S 9 S10 1980
	from which
	A juniper, 5 ins. diam., bears N 72° E, 66 lks. dist., mkd. T23N R2W S3 BT.
	A juniper, 9 ins. diam., bears S 58° E, 33 lks. dist., mkd. T23N R2W S10 BT.

CHAINS	
	A juniper, 5 ins. diam., bears S 68° W, 69 lks. dist., mkd. T23N R2W S9 BT.
	A juniper, 10 ins. diam., bears N 70° W, 47½ lks. dist., mkd. T23N R2W S4 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of cor.
	From the cor. of secs. 2, 3, 10 and 11.
	S 88°17' W, bet. secs. 3 and 10.
	Over rolling land, through medium to dense juniper.
40.26	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	from which
	A juniper, 7 ins. diam., bears N 26½° E, 15 lks. dist., mkd. ¼ S3 BT.
	A juniper, 8 ins. diam., bears S 10° E, 52 lks. dist., mkd. ‡ S10 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.
80.52	The cor. of secs. 3, 4, 9 and 10.
	N 0°37' E, bet. secs. 3 and 4.
	Over rolling land, through scattering to dense juniper.
40.71	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
	T23N_R2W
	s 4   s 3 1980
	from which
	A juniper, 9 ins. diam., bears S 66° E, 58 lks. dist., mkd. ¼ S3 BT.
	A juniper, 8 ins. diam., bears N 80½° W, 31 lks. dist., mkd. ¼ S4 BT.
81.51	Fence, bears E and W.

 	1 2) N, N 2 W, GILA AND BAIL NIVER MER., APIZONA	
CHAINS		
81.52	The cor. of secs. 3 and 4 only, on the N bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey, from which the remaining bearing tree mkd. in 1916	
	A juniper, 18 ins. diam., bears S 60°10' W, 70 lks. dist., mkd. T23N R2W S4 BT. (Record: pinyon, 69 lks. dist.)	
	and a new bearing tree	
	A juniper, 14 ins. diam., bears S 14° E, 68 lks. dist., mkd. T23N R2W S3 BT.	
	Add the marks 1980 to the brass cap.	
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, S of	
	COP • The Proposition of the control	
	From the cor. of secs. 4, 5, 32 and 33, on the S bdy. of the Tp., heretofore described.	
	N 0°57' W, bet. secs. 32 and 33.	
	Over rolling land, through dense juniper.	
40.75	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.	
	T23N R2W	
	S32   S33 1980	
	from which	
	A juniper, 14 ins. diam., bears N 70½° E, 129½ lks. dist., mkd. ¼ S33 BT.	
	A juniper, 12 ins. diam., bears South, 42 lks. dist., mkd. ¼ S32 BT.	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.	
81.50	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.	
	T23N R2W <u>S29   S28</u> <u>S32   S33</u> 1980	
	from which	

CHAINS	A juniper, 4 ins. diam., bears N 66½° E,
	132 lks. dist., mkd. X BT at the base.
	A juniper, 16 ins. diam., bears S 34° E, 80 lks. dist., mkd. T23N R2W S33 BT.
	A juniper, 8 ins. diam., bears S 20° W, 48 lks. dist., mkd. T23N R2W S32 BT.
	A juniper, 6 ins. diam., bears N 1° W, 98 lks. dist., mkd. T23N R2W S29 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 27, 28, 33 and 34.
	N 89°52' W, bet. secs. 28 and 33.
,	Over rolling land, through medium juniper.
40.62	Point for the 4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
	T23N R2W
	$\frac{1}{4}$ $\frac{S28}{S33}$
	1980
	from which
	A juniper, 8 ins. diam., bears N 22° E, 34 lks. dist., mkd. ‡ S28 BT.
	A juniper, 6 ins. diam., bears S 3½° E, 13 lks. dist., mkd. ¼ S33 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
81.24	The cor. of secs. 28, 29, 32 and 33.
	N 0°23' E, bet. secs. 28 and 29.
	Over rolling land, through medium juniper.
40.75	Point for the ½ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	S29   S28 1980
	from which

	1 2) N, It 2 W, GIIA AIM BAID HIVEI PEI ., AI 12011A
CHAINS	A juniper, 11 ins. diam., bears N 16° E,
	83 lks. dist., mkd. 4 S28 BT.
	A juniper, 18 ins. diam., bears N 74½° W, 88 lks. dist., mkd. ½ S29 BT.
	Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.
	Cor. is located 84 lks. W of fence, bears N and S.
	from which stock tanks
	Costello Tank, 2 chs. diam., bears N 87° E, 42.80 chs. dist.
	Big ASO Tank, 5 chs. diam., bears S 43° W, 18.70 chs. dist.
e C	A stock tank, 3 chs. x 8 chs., bears S 60° W, 15.70 chs. dist., long side bears N and S.
	A stock tank, 4 chs. diam., bears N 89° W, 14.50 chs. dist.
	Through scattering juniper.
81.50	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
	T23N R2W S20   S21
	S29   S28   1980
	from which
	A juniper, 8 ins. diam., bears N 70½° E, 67 lks. dist., mkd. S21 BT.
	A juniper, 6 ins. diam., bears S 18½° W, 81 lks. dist., mkd. T23N R2W S29 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 21, 22, 27 and 28.
7	N 89°49' W, bet. secs. 21 and 28.
	Over rolling land, through scattering juniper.
40•535	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

CHAINS	T23N R2W
	12 31 112W 1 S21 4 G29
	<sup>‡</sup> <del>S28</del> 1980
	1900
	from which
	A juniper, 9 ins. diam., bears N 30° E, 63½ lks. dist., mkd. ¼ S21 BT.
	A juniper, 10 ins. diam., bears S 1° E, 71 lks. dist., mkd. ‡ S28 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
81.07	The cor. of secs. 20, 21, 28 and 29.
	N 0°44' E, bet. secs. 20 and 21.
	Over rolling land, through scattering to medium juniper.
40.75	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	S20   S21 1980
	from which
	A juniper, 4 ins. diam., bears N 76° E, 62½ lks. dist., mkd. X BT at the base.
	A juniper, 10 ins. diam., bears N 24° W, 249 lks. dist., mkd. ‡ S20 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of cor.
81.50	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W <u>S17   S16</u> <u>S20   S21</u> 1980
	from which
	A juniper, 7 ins. diam., bears N 65½° E, 136 lks. dist., mkd. T23N R2W S16 BT.
	A juniper, 7 ins. diam., bears S 73° E, 161 lks. dist., mkd. T23N R2W S21 BT.

	1 25 N, N 2 W, WIIA AIR SAIT NIVER MER., APIZONA
CHAINS	A juniper, 8 ins. diam., bears S 42° W, 117 lks. dist., mkd. T23N R2W S20 BT.
	A juniper, 4 ins. diam., bears N 15½° W, 145 lks. dist., mkd. X BT at the base.
	Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.
	From the cor. of secs. 15, 16, 21 and 22.
	N 89°46' W, bet. secs. 16 and 21.
	Over rolling land, through medium to dense juniper.
40.41	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a fiberglass post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T23N R2W
	1 S16 4 S21
	1980 from which
	A juniper, 8 ins. diam., bears S 32½° E, 34½ lks. dist., mkd. ¼ S21 BT.
	A juniper, 8 ins. diam., bears N 16° W, 94 lks. dist., mkd. ½ S16 BT.
80.83	The cor. of secs. 16, 17, 20 and 21.
	N 0°27' E, bet. secs. 16 and 17.
	Over rolling land, through dense juniper.
40.75	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
	T23N R2W
	S17 <sup>†</sup> S16 1980
	from which
	A juniper, 8 ins. diam., bears S 79½° E, 43 lks. dist., mkd. ¼ S16 BT.
	A juniper, 7 ins. diam., bears N 60° W, 51 lks. dist., mkd. ¼ S17 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
	1

CHAINS	
81.50	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W S 8   S 9 S17   S16 1980
	from which
	A juniper, 6 ins. diam., bears N 69¼° E, 82 lks. dist., mkd. T23N R2W S9 BT.
	A juniper, 9 ins. diam., bears S 694° E, 46 lks. dist., mkd. T23N R2W S16 BT.
	A juniper, 6 ins. diam., bears S 43½° W, 137 lks. dist., mkd. T23N R2W S17 BT.
	A juniper, 22 ins. diam., bears N 24½° W, 161 lks. dist., mkd. T23N R2W S8 BT.
	Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.
	Cor. is 53 lks. E of fence, bears N 37° E and S 37° W.
	From the cor. of secs. 9, 10, 15 and 16.
	N 89°41' W, bet. secs. 9 and 16.
	Over rolling land, through medium juniper.
40.38	Point for the 4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W
	1980
	from which
	A juniper, 8 ins. diam., bears N 34° E, 59
	lks. dist., mkd. ‡ S9 BT.
	A juniper, 6 ins. diam., bears S 10° E, 86½ lks. dist., mkd. ¼ S16 BT.
	Mike Stock Tank, 2 chs. diam., bears N 84° E, 8.40 chs. dist.
80.76	The cor. of secs. 8, 9, 16 and 17.
	N 0°57' E, bet. secs. 8 and 9.
	, ·

=		
	CHAINS	
		Over rolling land, through scattering to dense timber.
	21.87	Fence, bears S 80° E and N 80° W.
	25.280	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears S 80° E and N 80° W, along a circular curve.
	26.87	Center of railroad tracks, bears S 80° E and N 80° W.
	27.08	Center of railroad tracks, bears S 80° E and N 80° W.
	27•99	Track road, bears S 80° E and N 80° W.
	28.59	Telegraph line, bears S 80° E and N 80° W.
	28.634	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears S 80° E and N 80° W, along a circular curve.
	28.65	Fence, bears S 80° E and N 80° W.
	40.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
		T23N R2W
		S 8 T S 9 1980
		from which
		A juniper, 7 ins. diam., bears N 42° E, 73 lks. dist., mkd. ‡ S9 BT.
		A juniper, 6 ins. diam., bears N 56° W, 61 lks. dist., mkd. ¼ S8 BT.
	81.50	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
		T23N R2W S5   S4 S8   S9 1980
		from which
	14 (A)	A juniper, 14 ins. diam., bears N 42½° E, 36 lks. dist., mkd. T23N R2W S4 BT.
		A juniper, 7 ins. diam., bears S 42° W, 47 lks. dist., mkd. T23N R2W S8 BT.
		Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W of cor.

CHAI	INS	
		Cor. is located 20 lks. N of crest of a low ridge, bears N 70° E and S 70° W.
		From the cor. of secs. 3, 4, 9 and 10.
		N 89°38' W, bet. secs. 4 and 9.
		Over rolling land, through scattering to medium juniper.
40.	185	Point for the 4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
		T23N R2W 1 S 4 5 9
		1980
		from which
		A juniper, 6 ins. diam., bears N 33° E, $72\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S4 BT.
		A juniper, 8 ins. diam., bears S 8° W, 72 lks. dist., mkd. 4 S9 BT.
		Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.
80.	37	The cor. of secs. 4, 5, 8 and 9.
		N 0°33' E, bet. secs. 4 and 5.
		Over gently rolling land, through scattering timber.
40.	75	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
		T23N R2W
		S 5   S 4 1980
		from which
		A juniper, 5 ins. diam., bears S 36½° E, 98 lks. dist., mkd. ¼ S4 BT.
		A juniper, 5 ins. diam., bears N 41° W, 25 lks. dist., mkd. 4 S5 BT.
		Raise a mound of stone, 5 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
81.	58	Fence, bears E and W.

the Tp.,
ecting 12 . base, official
bdy. of
imber.
pro— of the
22 ins.
W of
t propor— the
2 ins. in to top,
7
11,23,64 (4) 3 3 4 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

	1 2) 11, 11 2 11, 4114 414 414 414 11411, 12 12 13
CHAINS	
	From the cor. of secs. 28, 29, 32 and 33.
	N 89°15' W, bet. secs. 29 and 32.
	Over rolling land, through dense juniper.
40.59	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23N R2W
	1 S29 4 933
	1980
	from which
	A juniper, 8 ins. diam., bears S 16° W, 102 lks. dist., mkd. ½ S32 BT.
	A juniper, 16 ins. diam., bears N 32½° W, 77 lks. dist., mkd. ¼ S29 BT.
	Raise a mound of stone, 4 ft. base, 3 ft. high, N of cor.
81.18	The cor. of secs. 29, 30, 31 and 32.
	N 84°02' W, bet. secs. 30 and 31.
	Over rolling land, through dense juniper.
40.85	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T23N R2W
	1 S30 S31
	1980
	from which
	A juniper, 7 ins. diam., bears N 29° E, 60 lks. dist., mkd. ¼ S30 BT.
	A juniper, 13 ins. diam., bears S 25½° W, 60 lks. dist., mkd. ¼ S31 BT.
77.70	Track road, bears S 20° E and N 20° W.
80.38	The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp., remonumented by the U.S. Forest Service, with an aluminum post, $2\frac{1}{2}$ ins. diam., projecting 2 ins. above ground, with cap mkd.

 	- 13 11, 11 2 W, GIIG GR. SCIP TEVEL IN THE SCIP TEVEL TEVEL IN THE SCIP TEVEL TEVEL IN THE SCIP TEVEL TEVEL IN THE SCIP TEVEL TEVEL IN THE SCIP TEVEL
CHAINS	·
	T23N R3W R2W S25 S30 S36 S31 1980
	from which the remaining 1916 bearing trees
	A juniper, 28 ins. diam., bears N 713° E, 343 lks. dist., mkd. R2W S30, through a partially healed blaze.
	A juniper stump, 24 ins. diam., bears S 89° E, 291 lks. dist., mkd. S31 BT.
	and new bearing trees
	A juniper, 8 ins. diam., bears N 19½° E, 73 lks. dist., mkd. T23N R2W S30 BT.
	A juniper, 9 ins. diam., bears S 83° E, 192 lks. dist., mkd. T23N R2W S31 BT.
	From the cor. of secs. 29, 30, 31 and 32.
	N 0°26' E, bet. secs. 29 and 30.
	Over gently rolling land, through dense juniper.
40.82	Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	S30 T S29 1980
	from which
	A juniper, 9 ins. diam., bears S 41° E, 33 lks. dist., mkd. ¼ S29 BT.
	A juniper, 7 ins. diam., bears S 78° W, 85 lks. dist., mkd. ¼ S30 BT.
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
81.64	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W S19   S20 S30   S29 1980

CHAINS	
	from which
	A juniper, 6 ins. diam., bears N 79° E, 31 lks. dist., mkd. T23N R2W S20 BT.
	A juniper, 5 ins. diam., bears S 33° E, 24 lks. dist., mkd. T23N R2W S29 BT.
	A juniper, 7 ins. diam., bears S 60° W, 51 lks. dist., mkd. T23N R2W S30 BT.
	A juniper, 8 ins. diam., bears N 64° W, 126 lks. dist., mkd. T23N R2W S19 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of cor.
	From the cor. of secs. 20, 21, 28 and 29.
	N 89°09' W, bet. secs. 20 and 29.
	Over rolling land, through scattering to dense juniper.
40.55	Point for the 4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	1 S20 S29
	1980
	from which
	A juniper, 6 ins. diam., bears S 83° E, 30 lks. dist., mkd. ¼ S29 BT.
	A juniper, 18 ins. diam., bears N 38½° W, 86 lks. dist., mkd. ¼ S20 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of cor.
	The cor. is located 150 lks. S of an abandoned cinder topped road, bears E and W.
81.10	The cor. of secs. 19, 20, 29 and 30.
	N 84°46' W, bet. secs. 19 and 30.
	Over rolling land, through dense juniper.
40.69	Point for the 4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	‡ <u>\$19</u> \$30
	1980

CHAINS	
	T23N R2W S18   S17 S19   S20 1980
	from which
	A juniper, 5 ins. diam., bears N 75° E, 72½ lks. dist., mkd. T23N R2W S17 BT.
	A juniper, 7 ins. diam., bears S 8° E, 66 lks. dist., mkd. T23N R2W S20 BT.
	A juniper, 4 ins. diam., bears S 41° W, 64½ lks. dist., mkd. X BT at the base.
	A juniper, 8 ins. diam., bears N 8° W, 88½ lks. dist., mkd. T23N R2W S18 BT.
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	From the cor. of secs. 16, 17, 20 and 21.
	N 89°03' W, bet. secs. 17 and 20.
	Over rolling land, through scattering juniper.
40.515	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W 1 S17 1 S20 1980
	from which
	A juniper, 5 ins. diam., bears N 41½° E, 53 lks. dist., mkd. ¼ S17 BT.
	A juniper, 6 ins. diam., bears S $41\frac{1}{2}$ ° E, $70\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
81.03	The cor. of secs. 17, 18, 19 and 20.
	N 85°40' W, bet. secs. 18 and 19.
	Over rolling land, through dense juniper.
40.56	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
ĺ	

=			
	CHAINS		
		T23N R2W	
		, \$18	
		# <u>\$19</u>	
		1980	
		from which	
		A juniper, 12 ins. diam., bears N 32° E, 50 lks. dist., mkd. ¼ S18 BT.	
		A juniper, 16 ins. diam., bears S 2½° E, 65 lks. dist., mkd. ¼ S19 BT.	
		Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.	
	79•74	The cor. of secs. 18 and 19 only, on the W bdy. of the Tp., heretofore described.	
		From the cor. of secs. 17, 18, 19 and 20.	
		N 0°31' E, bet. secs. 17 and 18.	
		Over rolling land, through medium juniper.	
	40.82	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.	
		Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.	
1		T23N R2W	
		S18   S17 1980	
		from which	
		A juniper, 12 ins. diam., bears N 49° E, 119 lks. dist., mkd. ¼ S17 BT.	
		A juniper, 9 ins. diam., bears S 60½° W, 50 lks. dist., mkd. ¼ S18 BT.	
		Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.	
		Cor. is located on a N slope.	
	81.64	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.	
		Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.	
		T23N R2W S 7   S 8 S18   S17 1980	
		from which	
		A juniper, 8 ins. diam., bears N 45° E, 68½ lks. dist., mkd. T23N R2W S8 BT.	
١	<b>I</b>		

CHAINS	
	A juniper, 8 ins. diam., bears S 66° W, 156 lks. dist., mkd. T23N R2W S18 BT.
	A juniper, 7 ins. diam., bears N 23° W, 71½ lks. dist., mkd. T23N R2W S7 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
	A stock tank, 4 chs. diam., bears N 60° E, 10 chs. dist.
	From the cor. of secs. 8, 9, 16 and 17.
	N 88°56' W, bet. secs. 8 and 17.
	Over rolling land, through scattering juniper.
40.465	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	$\frac{1}{4}$ $\frac{\overset{\circ}{\text{S}} \overset{\circ}{\text{S}}}{\text{S17}}$
	1980
	from which
	A juniper, 7 ins. diam., bears N 56° W, 34 lks. dist., mkd. 4 S8 BT.
	A juniper, 5 ins. diam., bears S 84° W, 42½ lks. dist., mkd. ¼ S17 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.
	Cor. is on a N slope.
80.94	The cor. of secs. 7, 8, 17 and 18.
	N 86°29' W, bet. secs. 7 and 18.
	Over rolling land, through scattering to medium juniper.
40.49	Point for the 1 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	T23N R2W
	$\frac{1}{4} = \frac{\frac{S}{518}}{1980}$
	from which
	A sandstone, $8 \times 1\frac{1}{2} \times 1$ ft., bears N 78° E, 120 lks. dist., mkd. X BO on top.

CHAINS	
	A sandstone, $4 \times 2 \times 1\frac{1}{2}$ ft., bears N 34° W, $88\frac{1}{2}$ lks. dist., mkd. X BO on S face.
45.551	Point for the E-E-W 1/256 sec. cor. of secs. 7 and 18.
	Set an aluminum post, 28 ins. long, 1 in. diam., 28 ins. in the ground, with cap mkd.
	S 7 E-E-W 1/256 S18 1980
	from which
	A juniper, 14 ins. diam., bears N 86° E, 109 lks. dist., mkd. E-E-W 1/256 S7 BT.
	Cor. is located in a corral, along S edge, bears N 55° E and S 55° W.
60.735	Point for the W 1/16 sec. cor. of secs. 7 and 18.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.
	T23N R2W W 1/16 <u>S 7</u> S18 1980
	The southeast cor. of a concrete block generator house, 12 x 14 ft., bears N 38°48' W, 3.08 chs. dist., the long side bears N 5° W.
79•36	The cor. of secs. 7 and 18 only, on the W bdy. of the Tp., heretofore described.
	From the cor. of secs. 7, 8, 17 and 18.
	N 1°20' E, bet. secs. 7 and 8.
36.73	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 78° E and S 78° W, along a circular curve.
36.81	Fence, bears N 78° E and S 78° W.
37.12	Track road, bears N 78° E and S 78° W.
38.27	Center of railroad tracks, bears N 78° E and S 78° W, along a circular curve.
38.49	Center of railroad tracks, bears N 78° E and S 78° W, along a circular curve.
39.822	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway and telegraph line, bears N 78° E and S 78° W, along a circular curve.
40.83	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the

CHAINS	

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T23N R2W S 7 | S 8 1980

from which

A sandstone boulder,  $2\frac{1}{2}$  x 2 x 3 ft., bears S  $9\frac{1}{2}$ ° W,  $71\frac{1}{2}$  lks. dist., mkd. X BO on N face.

A juniper, 6 ins. diam., bears S 60° W, 97 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

41.00 | Fence, bears E and W.

81.66 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T23N R2W S 6 | S 5 S 7 | S 8 1980

from which

A juniper, 10 ins. diam., bears N 76° E, 27 lks. dist., mkd. T23N R2W S5 BT.

A juniper, 8 ins. diam., bears S 51° E, 54 lks. dist., mkd. T23N R2W S8 BT.

A juniper, 12 ins. diam., bears S 54° W, 19 lks. dist., mkd. T23N R2W S7 BT.

A juniper, 4 ins. diam., bears N 34½° W, 90 lks. dist., mkd. X BT at the base.

Cor. is located 42 lks. E of a fence, bears N and S.

From the cor. of secs. 4, 5, 8 and 9.

N 88°49' W, bet. secs. 5 and 8.

Over rolling land, through scattering juniper.

34.80 | Fence, bears N 35° E and S 35° W.

Point for the 4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.

CHAINS	MOSM DOM
	T23N R2W 1 S 5 2 S 8
	<sup>4</sup>
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
41.89	Track road, bears N 20° E and S 20° W.
80.38	The cor. of secs. 5, 6, 7 and 8.
	N 87°08' W, bet. secs. 6 and 7.
	Over rolling land, through dense juniper.
40•26	Point for the 4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	½ <u>S 6</u> S 7
	1980
	from which
	A juniper, 10 ins. diam., bears S 70° E, 48 lks. dist., mkd. ‡ S7 BT.
	A juniper, 8 ins. diam., bears N 70° W, 34 lks. dist., mkd. 4 S6 BT.
78.83	Fence, bears N and S.
78.89	The cor. of secs. 6 and 7 only, on the W bdy. of the Tp., heretofore described.
	From the cor. of secs. 5, 6, 7 and 8.
	N 0°21' E, bet. secs. 5 and 6.
	Over rolling land, through dense juniper.
40.82	Point for the 4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	T23N R2W
	S 6   S 5 1980
	from which
	A juniper, 12 ins. diam., bears N 10° E,
	121 lks. dist., mkd. ½ S5 BT.

CHAINS	
	A juniper, 30 ins. diam., bears N 84° W, 51½ lks. dist., mkd. ¼ S6 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.
	Cor. is located 29 lks. E of fence, bears N and S.
81.24	Track road, bears E and W.
81.63	Fence cor., fences extend E, S and W.
81.67	The cor. of secs. 5 and 6 only, on the N bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 resurvey.
	Subdivision of Section 7 T 23 N, R 2 W, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 7 and 18.
	N 1°29' E, on the N and S center line of sec. 7.
	Over rolling land, through railed juniper.
13.61	Fence, bears N 65° E and S 65° W.
19.56	Fence, bears N 65° E and S 65° W, enter scattering to medium juniper.
20.265	Point for the center S 1/16 sec. cor. of sec. 7.
	Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.
	T23N R2W C
	s 1/16   s 7
	C 1980
	from which
	A juniper, 14 ins. diam., bears N 62° E, 67 lks. dist., mkd. C—S 1/16 S7 BT.
	A juniper, 12 ins. diam., bears S 75½° W, 28½ lks. dist., mkd. C-S 1/16 S7 BT.
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
23.03	Track road, bears N 74½° E and S 74½° W.
23•357	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 74°33' E and S 74°33' W.
23.40	Fence, bears N 74½° E and S 74½° W.

		T 23 N, R 2 W, Gila and Salt River Mer., Arizona
	CHAINS	
	23.56	Telegraph line, bears N 74½° E and S 74½° W.
	24.01	Track road, bears N 74½° E and S 74½° W.
	24.98	Center of railroad tracks, bears N 74½° E and S 74½° W.
	25.20	Center of railroad tracks, bears N 74½° E and S 74½° W.
	26.52	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 74°33' E and S 74°33' W.
	26.57	Fence, bears N 74½° E and S 74½° W.
	27.22	Track road, bears N 74½° E and S 74½° W.
	28.14	Fence, bears N 74½° E and S 74½° W.
	40.53	True point for the center 1/4 sec. cor. of sec. 7, at intersection with the E and W center line of sec. 7, falls in center of wash, 1 ch. wide, 6 ft. deep, drains S 40° W, where it is impracticable to set a permanent monument.
	41.53	Point selected for the witness center 4 sec. cor. of sec. 7.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
		W C T23N R2W C ¼ ∫ S 7
		1980
		from which
		A juniper, 5 ins. diam., bears N 27° E, 34 lks. dist., mkd. X BT at the base.
		A juniper, 7 ins. diam., bears N 53° W, 16 lks. dist., mkd. X BT at the base.
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W of cor.
	43.60	Track road, bears N 75° E and S 75° W.
	81.21	The 1 sec. cor. of secs. 6 and 7.
	• •	From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
		N 86°55' W, on the E and W center line of sec. 7.
		Over rolling land, through scattering to medium juniper.
	23.45	Track road, bears N 30° E and S 30° W.
÷	25.85	Fence, bears N 45° E and S 45° W.
	26.30	Track road, bears N 45° E and S 45° W.

		1 2) N, N 2 W, GILA and Salt River Mer., Arizona
T	CHAINS	
	40.37	True point for the center 4 sec. cor. of sec. 7.
	60.59	Point for the center W 1/16 sec. cor. of sec. 7.
		Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.
		T23N R2W W 1/16 C S 7 1980
		from which
		A juniper, 18 ins. diam., bears S 6° E, 104 lks. dist., mkd. C-W 1/16 S7 BT.
		A juniper, 12 ins. diam., bears N 28° W, 54 lks. dist., mkd. C-W 1/16 S7 BT.
		Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	79•18	The ¼ sec. cor. of sec. 7 only, on the W bdy. of the Tp., heretofore described.
		SW ¼, Section 7
		From the W 1/16 sec. cor. of secs. 7 and 18.
		N 1°31' E, on the N and S center line of the SW4 of sec. 7.
		Over rolling land, through scattering to medium juniper.
	16.11	Fence, bears N 70° E and S 70° W, along a circular curve.
	16.127	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 70° E and S 70° W, along a circular curve.
	16.33	Telegraph line, bears N 70° E and S 70° W.
	16.57	Track road, bears N 70° E and S 70° W.
	17.74	Center of railroad tracks, bears N 70° E and S 70° W.
	17.97	Center of railroad tracks, bears N 70° E and S 70° W.
	19.35	Fence, bears N 74½° E and S 74½° W.
	19.388	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 70° E and S 70° W, along a circular curve.
	20.185	Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E and W center line of the $SW_4^1$ of sec. 7.
		Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with cap mkd.

	T 23 N, K 2 W, Glia and Salt River Mer., Arizona
CHAINS	MOOKI DOM
	T23N R2W SW 1/16 S7 1980
	from which
	A juniper, 6 ins. diam., bears N 33° E, 27½ lks. dist., mkd. SW 1/16 S7 BT.
	A juniper, 8 ins. diam., bears S 9° W, 32½ lks. dist., mkd. SW 1/16 S7 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
35.08	Track road, bears N 60° E and S 60° W.
40.37	The center W 1/16 sec. cor. of sec. 7.
	From the center S 1/16 sec. cor. of sec. 7.
	N 86°42' W, on the E and W center line of the SW4 of sec.
	Over rolling land, through scattering juniper.
5.058	Point for the center E-E-SW 1/256 sec. cor. of sec. 7.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with cap mkd.
	S7 C-E-E-SW 1/256 1980
	from which
	A juniper, 6 ins. diam., bears S 56° E, 145 lks. dist., mkd. C-E-E-SW S7 1/256 BT.
	The S end of a concrete cattleguard, mkd. X BO on S face, bears N 5° W, 167½ lks. dist.
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
9•213	Intersect the southerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 74°33' E and and S 74°33' W.
9.30	Fence, bears N 74½° E and S 74½° W.
9•75	Telegraph line, bears N 74½° E and S 74½° W.
10.50	Track road, bears N 74½° E and S 74½° W.
13.97	Center of railroad tracks, bears N 74½° E and S 74½° W.
14.58	Center of railroad tracks, bears N 74½° E and S 74½° W.
18.13	Fence, bears N $74\frac{1}{2}$ ° E and S $74\frac{1}{2}$ ° W.
1	į

50

CHAINS	
18.272	Intersect the northerly right-of-way of the Atchison Topeka and Santa Fe Railway, bears N 74°33' E and S 74°33' W.
20.23	The SW 1/16 sec. cor. of sec. 7.
38.85	The S 1/16 sec. cor. of sec. 7 only, on the W bdy. of the Tp., heretofore described.
	Subdivision of Section 18 T 23 N, R 2 W, Gila and Salt River Mer., Arizona
	From the 4 sec. cor. of secs. 18 and 19.
	N 0°32' E, on the N and S center line of sec. 18.
	Over rolling land, through dense juniper.
40.53	Point for the center 1 sec. cor. of sec. 18, at intersection with the E and W center line of sec. 18.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T23N R2W C ‡ S18 1980
	from which
	A juniper, 9 ins. diam., bears S 67° E, 58 lks. dist., mkd. C ‡ S18 BT.
	A juniper, 5 ins. diam., bears S 61½° W, 14½ lks. dist., mkd. C ¼ S18 BT.
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
58.60	Track road, bears E curving S, and W curving S, enter railed juniper.
58.70	Fence, bears E and W.
81.06	The ½ sec. cor. of secs. 7 and 18.
	From the 4 sec. cor. of secs. 17 and 18.
	N 86°05' W, on the E and W center line of sec. 18.
	Over rolling land, through dense juniper.
40.53	The center 4 sec. cor. of sec. 18.
79•67	The ¼ sec. cor. of sec. 18 only, on the W bdy. of the Tp., heretofore described.
	Subdivision of Section 29 T 23 N, R 2 W, Gila and Salt River Mer., Arizona

### Subdivision of Section 29 T 23 N, R 2 W, Gila and Salt River Mer., Arizona

1 25 N, h 2 W, Gila and Salt River Mer., Arizona					
From the 4 sec. cor. of secs. 29 and 32.					
N 0°25' E, on the N and S center line of sec. 29.					
Over rolling land, through dense juniper.					
Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E and W center line of sec. 29.					
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.					
T23N R2W C ‡ S29 1980					
-					
from which					
A juniper, 8 ins. diam., bears S 15° E, 31 lks. dist., mkd. C ¼ S29 BT.					
A juniper, 7 ins. diam., bears S 67° W, 47 lks. dist., mkd. C ‡ S29 BT.					
Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.					
The ¼ sec. cor. of secs. 20 and 29.					
From the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.					
N 89°12' W, on the E and W center line of sec. 29.					
Over rolling land, through dense juniper.					
The center 1/4 sec. cor. of sec. 29.					
The ½ sec. cor. of secs. 29 and 30.					
MEMORANDUM					

The center line of the Atchison Topeka and Santa Fe Railway right-of-way through sections 7 and 9, as taken from Bureau of Land Management Serial Register Page AR 033935, is a follows:

A strip of land of varying width by approximately 5800 feet in average length being a portion of said section 9, the center-line of said strip being more particularly described as follows: Commencing at a point in the westerly line of said Section 11 distant southerly along said westerly line 939.10 feet from a stone monument marking the northwest corner of said Section 11; thence westerly along a line that makes a southwesterly angle of 89°17'45" with said westerly line a distance of 2196.91 feet; thence southwesterly along the arc of a curve tangent to the preceding course, concave southeasterly and having a radius of 5732.01 feet through a central angle of 32°47'08" a distance of 3279.95 feet; thence southwesterly tangent to the preceding curve 1792.78 feet to a point hereinafter referred to as "Point B", thence southwesterly along the arc of a curve tangent to the preceding course, concave northwesterly and having a

T 23 N, R 2 W, Gila and Salt River Mer., Arizona

#### CHAINS

radius of 5732.01 feet through a central angle of 26°45'00" a distance of 2676.14 feet to a point hereinafter referred to as "Point C"; thence westerly along the prolongation of the arc of last said curve a distance of 1350 feet, more or less, to point of ending in the westerly line of said Section 9.

A strip of land 200 feet in width by approximately 5650 feet in average length being all that portion of said Section 7 which lies between lines that are parallel and/or concentric with and distant 100 feet measured at right angles and/or radially from and on each side of the following described center-line:

Commencing at a point in the westerly line of said Section 11 distant southerly along said westerly line 939.10 feet from a stone monument marking the northwest corner of said Section 11; thence westerly along a line that makes a southwesterly angle of 89°17'45" with said westerly line a distance of 2196.91 feet; thence southwesterly along the arc of a curve tangent to the preceding course, concave southeasterly and having a radius of 5732.01 feet through a central angle of 32°47'08" a distance of 3279.95 feet; thence south westerly tangent to the preceding curve 1792.78 feet; thence southwesterly along the arc of a curve tangent to last said course concave northerly and having a radius of 5732.01 feet through a central angle of 49°26'00" a distance of 4945.43 feet; thence westerly tangent to the preceding curve 1883.01 feet; thence westerly along the arch (sic) of a curve tangent to last said course concave southerly and having a radius of 5732.01 feet through a central angle of 31°50'45" a distance of 3185.94 feet; thence southwesterly tangent to the preceding curve 3181.97 feet thence southwesterly along the arc of a curve tangent to the preceding course concave southeasterly and having a radius of 5732.01 feet through a central angle of 14°20'00" a distance of 1433.94 feet; thence southwesterly tangent to the preceding curve 440 feet, more or less, to a point in the westerly line of said section 7 distant northerly along said westerly line 476.85 feet from a stone monument marking the southwest corner of said section 7, last said course makes a south-easterly angle of 121°19'45" with last said westerly line.

The side lines of said strip to be lengthened or shortened to originate in the easterly line of said Section 7 and terminate in the westerly line of said Section 7.

#### GENERAL DESCRIPTION

The area encompassed in this survey is located about 7 miles north of Ash Fork, Arizona. Elevations range from 5,300 to 6,000 feet above sea level. The terrain varies from rolling to nearly level on some of the mesas. Vegetation consists primarily of juniper and native grasses with a few scattered pinyon.

, <del>100</del>		T 23 N, R 2 W, Gila and Salt River Mer., Arizona
	CHAINS	
•		Primary access into the area is by way of Forest Service Rd. 142, improved dirt, from Ash Fork. The Atchison Topeka and Santa Fe Railway traverses the township from sec. 36 northerly to sec. 12, thence westerly, exiting the township in sec. 7.
		Farthen stock tanks are located in secs. 8, 9, 28 and 29, and several intermittent springs located throughout the township.
		The only occupied buildings in the area are located on the Gold Trap Ranch in the SW4 of sec. 7.
		There is sporadic mining of flagstone scattered throughout the township and a cinder pit in sec. 8.
		An average number of readings throughout the area surveyed gives a mean magnetic declination of 14½° E, with a variation of 4° in local attraction.
	·	
·		
	**************************************	

Form 9600-11 (August 1979)

.′.

. .

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

### FIELD ASSISTANTS

TILLU ASSISTANTS						
NAMES	CAPACITY					
Paul L. Reeves	Cadastral Surveyor					
John P. Bennett III	Cadastral Surveyor					
Nina T. Clow	Cadastral Surveyor (student trainee)					
John J. Bulinski	Survey Technician					
Jack S. Harris	Survey Technician					

### B 0 0 K<sub>55</sub>5 1 8 9

### CERTIFICATE OF SURVEY

(I)(WAX), Harry K. Smith, Cadastra	l Surveyor	, HEREBY				
CERTIFY upon honor that, in pursuance of	special instructions bearing date of the	20th day				
of May , 1980 , (I) (NX)	have dependently resurveyed port	tions of				
the South and West boundaries ar	nd a portion of the subdivisional	l lines				
and surveyed subdivisions in sec	ctions 7, 18 and 29, Township 23	North,				
Range 2 West	•					
of the Gila and Salt River	Meridian, in the State of Arizona	<b>.</b>				
	Meridian, in the State of Arizona as having been executed by (me), (MK) and	, which				
	een made in strict conformity with said spec					
	urvey of the Public Lands of the United St					
specific manner described in the foregoing		ates, and in				
specific mainter described in the folegoing	neid notes.					
SEP 1 4 1983						
(Date)	Harry K. Smith					
(Butter)	(Cadastial Surveyor)					
(Date)	(Cadastral Surveyor)					
CERTIFIC	CATE OF APPROVAL					
	Arizona State Offi Bureau of Land Man					
m (	Phoenix, Arizona					
The foregoing field notes of the dependent resurvey of portions of the South and West boundaries and a portion of the subdivisional lines, and the survey of subdivisions in sections 7, 18 and 29, Township 23 North, Range 2 West, Gila and Salt River Meridian, Arizona						
executed by Harry K. Smith, Cada	stral Surveyor					
having been critically examined and found	2					
SEP 1 5 1983	James P. Le Cley					
(Date)	Chief Cadastral Surveyor of Ariz					
CERTIFIC	CATE OF TRANSCRIPT					
I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in						
T. 23 N., R. 2 W., G&SRM, Arizona , is a true copy of the original field notes.						

(Date)