# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

	OF THE	
	DEPENDENT RESURV	EY OF
	PORTIONS OF THE EAST AND NO	RTH BOUNDARIES,
	AND	
	A PORTION OF THE SUBDIVI	SIONAL LINES,
	AND	
	METES-AND-BOUNDS SURVEYS IN	CERTAIN SECTIONS,
	TOWNSHIP 2 NORTH, RANG	GE 8 WEST
Of the	Gila and Salt River	Meridian,
In the State of	Arizona	
	EXECUTED BY	
Darren R. B	reckenridge,	Cadastral Surveyor,
Under special in	tructions dated <u>March 9</u> , 19	88, approved <u>March 9, 1988</u>
ADA-14-MINING MANAGEMENT AND ADA-14-MINING MANAGEMENT AND ADA-14-MINING MANAGEMENT AND ADA-14-MINING MANAGEMENT	, which provided for the s	urveys included under Group Number
and a	ssignment instructions dated	March 9, 1988

Survey commenced <u>March 30</u>,

<u>April 25</u>,

Survey completed

1988

1988

### INDEX DIAGRAM

TOWNSHIP 2 NORTH , RANGE 8 WEST ,

	6	·	<b>-</b>		55
6	5 14	 	3		7 <u>1</u>
7	8	1210	10	99	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Metes-and-Bounds Survey in Section 2 pp. 14-15.

Metes-and-Bounds Survey in Section 4 pp. 15-16. Metes-and-Bounds Survey in Section 5 pp. 16-17.

Metes-and-Bounds Survey in Section 11 pp. 17.

### T 2 N, R 8 W, Gila and Salt River Mer., Arizona

#### CHAINS

The following field notes are those of the dependent resurvey of portions of the east and north boundaries, a portion of the subdivisional lines, and metes-and-bounds surveys in certain sections, Township 2 North, Range 8 West, Gila and Salt River Meridian, Arizona.

The east and north boundaries were surveyed by Jesse B. Wright in 1914, and the subdivisional lines were surveyed by John F. Hesse in 1914.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 9, 1988, for Group No. 705, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. All recovered monuments were in good condition; positions for lost corners were determined at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Positions for angle points on the south right-of-way line of the Central Arizona Project Canal when needed to establish intersections with section lines were determined from information shown on Bureau of Reclamation survey diagrams 344-330-1819, dated June 23, 1977, and 344-330-1240, dated November 2, 1978, revised July 13, 1979.

The directions of all lines were determined by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Geodimeter 140 total station.

The geographic position of the southeast corner of section 2, as determined from a tie made to U.S. Coast & Geodetic Survey triangulation station "BURNT WELL, 1947", located in the NE quarter of section 4, Township 2 North, Range 8 West, is as follows:

Latitude: 33°32'13.86" N Longitude: 113°02'24.13" W

The magnetic declination from U.S. Geological Survey quadrangle map "BIG HORN MTS., ARIZ.", published in 1961, is 14 1/2° E.

Dependent Resurvey of a Portion of the E Bdy., T 2 N, R 8 W, Gila and Salt River Mer., Arizona

### Dependent Resurvey of a Portion of the E Bdy., T 2 N. R 8 W. Gila and Salt River Mer., Arizona

#### **CHAINS**

## Reestablishment of the survey executed by Jesse B. Wright in 1914

Beginning at the 1/4 sec. cor. of secs. 1 and 6, on the E bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official notes of the 1914 survey of the W bdy. of T 2 N, R 7 W. Add marks to the brass cap to read,

T2N 1/4 R8W | R7W S1 | S6 1988 1914


A mound of stone, 3 ft. base, 1 ft. high, is W of cor.

North, bet. secs. 1 and 6.

Over nearly level land.

Point for a witness point on line bet. secs. 1 and 6 on the southerly right-of-way line of the Central Arizona Project Canal.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 349+07.49 R.O.W. 125.00 FT. RT., bears N 68°10.5' E, 6.120 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.

## Dependent Resurvey of a Portion of the E Bdy., T 2 N, R 8 W, Gila and Salt River Mer., Arizona

	T 2 N, R 8 W, Gila and Salt River Mer., Arizona
CHAINS	From this same point a robor 3/4 in diam with an unmarked
	From this same point a rebar, 3/4 in. diam., with an unmarked aluminum cap, 1 1/2 ins. diam., bent over but firmly set,
	projecting 6 ins. above ground, bears S 68°10.5' W, 2.852 chs.
	dist. This point was established by the Bureau of Reclamation on
	the S right-of-way line of the Central Arizona Project Canal.
40.00	The cor. of Tps. 2 and 3 N, Rs. 7 and 8 W, described in the field
	notes of the dependent resurvey of the S bdy. of T 3 N, R 7 W,
	surveyed concurrently under this same group.
	Dependent Resurvey of a Portion of the N Bdy.,
	T 2 N, R 8 W, Gila and Salt River Mer., Arizona
	Reestablishment of the survey executed by
	Jesse B. Wright in 1914
	From the cor. of Tps. 2 and 3 N, Rs. 7 and 8 W.
	S 89°59' W, bet. secs. 1 and 36.
}	Over rolling land.
40.07	The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron
Ì	post, 1 in. diam., firmly set, projecting 5 ins. above ground,
	with brass cap mkd. as described in the official notes of the
	1914 survey of the N bdy. of T 2 N, R 8 W. Add marks to the
	brass cap to read,
	T3N R8W
	1/4
	T2N
	1988
	1914
	A mound of stone, 1 1/2 ft. base, 1 1/2 ft. high, is N of cor.
Ì	A mound of scone, 1 1/2 ft. base, 1 1/2 ft. high, is wol col.
İ	5 000F01 W 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
	S 89°58' W, beginning new measurement.
	Over rolling land.
40.09	The cor. of secs. 1, 2, 35, and 36, monumented with an iron post,
40.05	3 ins. diam., firmly set, projecting 7 ins. above ground, with
	brass cap mkd.

Dependent Resurvey of a Portion of the N Bdy., T 2 N, R 8 W, Gila and Salt River Mer., Arizona

CHAINS	
	T3N S35 S36
	R8W
	S2   S1
	TŹN 1914
	There is no evidence of the original bearing tree.
	The E 1/2 mile bet. secs. 5 and 32 was resurveyed to verify the position of the Central Arizona Project Canal.
	From the cor. of sec. 4, 5, 32, and 33, monumented with an iron post, 3 ins. diam., in a mound of stone, 4 1/2 ft. base, 3 ft. high, to top, with brass cap mkd.
	T3N
	\$32   \$33 R8W
	S5   S4
	TŻN 1914
	S 89°58' W, bet. secs. 5 and 32.
	Over rolling land.
34.05	Intersect the southerly right-of-way line of the Central Arizona Project Canal, not monumented.
	From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 1034+99.97 R-58 R.O.W. 125.00 FT. RT., bears S 19°30.9' E, 4.214 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
	From this same point a brass disk, 3 3/4 ins. diam., seated in concrete, projecting 3 ins. above the ground, with top mkd. STA. 1029+04.89 R.O.W. 125.00 FT. RT., bears N 19°30.9' W, 4.800 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
40.18	The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official notes of the 1914 survey of the N bdy. of T 2 N, R 8 W. Add marks to the brass cap to read,

### Dependent Resurvey of a Portion of the N Bdy., T 2 N. R 8 W. Gila and Salt River Mer., Arizona

CHA	INS
-----	-----

T3N R8W

1/4 S32
S5
T2N
1988
1914

from which the original bearing trees

A dead ironwood, 12 ins. diam., bears S 82° W, 2.20 chs. dist., mkd. 4 BT on an open blaze.

An ironwood, 6 ins. diam., bears N 78 1/4° W, 1.75 chs. dist., with no visible marks.

Dependent Resurvey of a Portion of the Subdivisional Lines, T 2 N, R 8 W, Gila and Salt River Mer., Arizona

Reestablishment of the survey executed by John F. Hesse in 1914

From the cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

T2N R8W S2 S1 S11 S12 1914

from which the original bearing tree

An ironwood, 46 ins. diam., bears N 47 1/2° E, 2.26 chs.
dist., mkd. 1 BT on a weathered blaze. (Record:
N 49 1/2° E, 2.22 chs. dist.).

A mound of stone, 3 ft. base, 1/2 ft. high, is W of cor.

From this cor. a Bureau of Reclamation bench mark, bears N 66° E, 10 lks. dist., monumented with a brass disk, 3 3/4 ins. diam., firmly set in concrete, projecting 5 ins. above ground, mkd. TR-56 ELEV. FT. 1969.

N 0°00.5' E, bet. secs. 1 and 2.

Over rolling land.

38.51	Point for a witness point on line bet. secs. 1 and 2 on the southerly right-of-way line of the Central Arizona Project Canal.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with cap mkd.
	W P T2N R8W S2 S1 1988
	Set a steel fence post near the cor.
	From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 289+94.52 R.O.W. 125.00 FT. RT., bears N 68°09.5' E, 2.896 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
	From this same point the point for an angle point on the S right-of-way of the Central Arizona Project Canal, bears S 68°09.5' W, 8.990 chs. dist., hereinafter described.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original monument. The true point falls in the Central Arizona Project Canal where it is impracticable to establish a permanent monument.
79.88	The cor. of secs. 1, 2, 35, and 36, on the N bdy. of the Tp., hereinbefore described.
	From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	1/4 S10 S11 1914
	A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, is W of cor.
	N 0°00.5' E, bet. secs. 10 and 11.
	Over rolling land.
34.945	Point for a witness point on line bet. secs. 10 and 11 on the southerly right-of-way line of the Central Arizona Project Canal.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.

	1 2 My K O MY OTTA ANA DATE KIVET MELL, MITZONA	
CHAINS		
	W P	
	T2N R8W	
1		
	\$10   \$11	
	1988	
	Set a steel fence post near the cor.	
	From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal bears N 70°40.5' E, 7.732 chs. dist., hereinafter described.	
	From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., 2 ins. above the ground, with top mkd. 214+93.97 P.I. R.O.W. 125.00 FT. RT., bears S 70°40.5' W, 6.997 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.	
40.01	The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., projecting 13 ins. above ground, with brass cap mkd.	
	T2N R8W	
	\$3   \$2	
ĺ		
	\$10   \$11	
	1914	
	From the cor. of secs. 1, 2, 11, and 12,.	
	S 89°55.5' W, bet. secs. 2 and 11.	
	Over rolling land.	
40.03	The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.	
	\$2	
	$\frac{1/4}{\$11}$	
	1914	
	A mound of stone, 2 ft. base, 1 ft. high, is N of cor.	
	<del></del>	
	S 89°58' W, beginning new measurement.	
	,gg	

### CHAINS 32.395 Point for a witness point on line bet. secs. 2 and 11 on the southerly right-of-way line of the Central Arizona Project Canal. Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with cap mkd. WP T2N R8W S2 S11 1988 Set a steel fence post near the cor. From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 225+75.41 BK. 225+50.50 AHD. R.O.W. 125.00 FT. RT., bears N 6°56.8' E, 2.233 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal. From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 6°56.8' W, 2.527 chs. dist., hereinafter described. 39,995 The cor. of secs. 2, 3, 10, and 11. N 0°02' W, bet. secs. 2 and 3. Over rolling land. 40.05 The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. 1/4 S3 | S2 1914 A mound of stone, 2 ft. base, 2 ft. high, is W of cor. From the 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 \$9 | \$10 A mound of stone, 3 ft. base, 1 ft. high, is W of cor.

	T Z N, R 8 W, Gila and Salt River Mer., Arizona
CHAINS	N 0°02' W, bet. secs. 9 and 10.
	Over rolling land.
24.62	Point for a witness point on line bet. secs. 9 and 10 on the southerly right-of-way line of the Central Arizona Project Canal.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 36 ins. in the ground, with cap mkd.
	W P T2N R8W S9 S10 1988
	Set a steel fence post near the cor.
	From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., projecting 2 ins. above ground, with top mkd. STA. 166+52.33 R.O.W. 200.00 FT. RT., bears S 66°18.4' E, 8.699 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
	Two steel fence posts are set near the cor.
	From this same point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 160+68.41 R.O.W. 200.00 FT. RT., bears N 66°18.4' W, 0.151 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
1	Three steel fence posts are set near the cor.
40.01	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T2N R8W S4   S3
	S9 S10 1914
	A mound of stone, 3 ft. base, 2 1/2 ft. high, is W of cor.
	From the cor. of secs. 2, 3, 10, and 11.

	The state of the s
CHAINS	S 89°54.5' W, bet. secs. 3 and 10.
	Ascend along SE slope.
40.085	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., in a mound of stone, 3 1/2 ft. base, 18 ins. high, to top, with brass cap mkd.
	\$3 1/4 \$10 1914
:	A mound of stone, 2 ft. base, 2 ft. high, is N of cor.
	S 89°56' W, beginning new measurement.
40.025	The cor. of secs. 3, 4, 9, and 10.
	N 89°57.5' W, bet. secs. 4 and 9.
	Along rough S slope.
35.083	Point for a witness point on line bet. secs. 4 and 9 on the southerly right-of-way line of the Central Arizona Project Canal.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	W P T2N R8W S4
	S9 1988
	Set a steel fence post near the cor.
	Cor. is set in fill dirt for the Central Arizona Project Canal.
	From this point a brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 150+90.07 R.O.W. 200.00 FT. RT., bears S 66°16.6' E, 23.351 chs. dist. This point was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
	Continue measurement on the line bet. secs. 4 and 9 identical with the southerly right-of-way line of the Central Arizona Project Canal.

	The state of the s
CHAINS 39.897	The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., projecting 13 ins. above ground, with brass cap mkd.
	S4 1/4 S9 1914
	A mound of stone, 2 ft. base, 1 1/2 ft. high, is N of cor.
	N 89°56.5' W, beginning new measurement on the line bet. secs. 4 and 9, identical with the southerly right-of-way line of the Central Arizona Project Canal.
6.504	Point for a witness point on line bet. secs. 4 and 9 on the southerly right-of-way line of the Central Arizona Project Canal.
	Set an aluminum post, 36 ins. long, $3/4$ in. diam., 32 ins. in the ground, with cap mkd.
	W P T2N R8W S4
	S9 1988
	Set a steel fence post near the cor.
	From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 66°17.4' W, 16.135 chs. dist., hereinafter described.
40.13	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.
	T2N R8W S5 S4
	\$8 \$9 1914
	A mound of stone, 2 ft. base, 1 ft. high, is W of cor.
	From this cor. U.S.C.& G.S. triangulation station "BURNT WELL 1947," bears N 45°48.2' E, (forward bearing), 88.355 chs. dist., monumented with a brass disk, 3 1/2 ins. diam., projecting 3 ins. above ground, with disk mkd. BURNT WELL 1947.

<u></u>	T 2 N, K 8 W, Gila and Salt River Mer., Arizona
CHAINS	N 0°08' E, bet. secs. 4 and 5.
	Ascend steep rock S slope of Burnt Mountain.
31.033	Point for a witness point on line bet. secs. 4 and 5 on the southerly right-of-way line of the Central Arizona Project Canal.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	W P T2N R8W S5 S4 1988
	Set a steel fence post near the cor.
	From this point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears S 45°49.4' E, 14.720 chs. dist., hereinafter described.
	From this same point the point for an angle point on the S right-of-way line of the Central Arizona Project Canal, bears N 45°49.4' W, 35.218 chs. dist., hereinafter described.
39.89	The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., set in a mound of stone, 4 ft. base, 20 ins. high, to top, with brass cap mkd.
	1/4 S5 S4 1914
	A mound of stone, 3 ft. base, 1 ft. high, is W of cor.
	N 0°11' E, beginning new measurement.
	Descend down precipitous NE slope.
40.10	The cor. of secs. 4, 5, 32, and 33, on the N bdy. of the Tp., hereinbefore described.
	MEMORANDUM
	The following metes-and-bounds surveys are determined from Bureau of Reclamation survey diagrams 344-330-1819 dated June 23, 1977, and 344-330-1240 dated November 2, 1978, revised July 13, 1979.

Metes-and-Bounds Survey in Section 2, T 2 N, R 8 W, Gila and Salt River Mer., Arizon

	T 2 N, R 8 W, Gila and Salt River Mer., Arizona
CHAINS	From the witness point of secs. 1 and 2 on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 0°00.5' E, 38.510 chs. dist. from the cor. of secs. 1, 2, 11, and 12.
	S 68°09.5' W, on the southerly right-of-way line of the Central Arizona Project Canal.
8.990	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	S 21°50.5' E, on the southerly right-of-way line of the Central Arizona Project Canal.
1.515	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	S 68°09.5' W, on the southerly right-of-way line of the Central Arizona Project Canal, 225 ft. right of center line.
1.515	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	N 21°50.5' W, on the southerly right-of-way line of the Central Arizona Project Canal.
1.515	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	S 68°09.5' W, on the southerly right-of-way line of the Central Arizona Project Canal, 125 ft. right of center line.
1.735	A brass disk, 3 3/4 ins. diam., seated in a concrete post, 6 ins. diam., flush with the ground, with top mkd. STA. 279+95.75 R.O.W. 125.00 FT. RT. This monument was established by the Bureau of Reclamation on the S right-of-way line of the Central Arizona Project Canal.
	Metes-and-Bounds Survey in Section 4, T 2 N, R 8 W, Gila and Salt River Mer., Arizona
	From the witness point of secs. 4 and 9, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 89°56.5' W, 6.504 chs. dist., from the 1/4 sec. cor. of secs. 4 and 9.

## Metes-and-Bounds Survey in Section 4, T 2 N, R 8 W, Gila and Salt River Mer., Arizona

	T 2 N, R 8 W, Gila and Salt River Mer., Arizona
CHAINS	N 66°17.4' W, on the southerly right-of-way line of the Central Arizona Project Canal.
16.135	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	N 45°49.4' W, on the southerly right-of-way line of the Central Arizona Project Canal.
15.876	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	N 44°10.8' E, on the southerly right-of-way line of the Central Arizona Project Canal.
4.545	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	N 45°49.4' W, on the southerly right-of-way line of the Central Arizona Project Canal.
14.720	The witness point of secs. 4 and 5, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located S 0°08' W, 8.857 chs. dist., from the 1/4 sec. cor. of secs. 4 and 5.
	Metes-and-Bounds Survey in Section 5, T 2 N, R 8 W, Gila and Salt River Mer., Arizona
	From the witness point of secs. 4 and 5, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located S 0°08' W, 8.857 chs. dist., from the 1/4 sec. cor. of secs. 4 and 5.
4	N 45°49.4' W, on the southerly right-of-way line of the Central Arizona Project Canal.
35.218	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	N 19°30.9' W, on the southerly right-of-way line of the Central Arizona Project Canal.

17

## Metes-and-Bounds Survey in Section 5, T 2 N. R 8 W. Gila and Salt River Mer., Arizona

	T 2 N, R 8 W, Gila and Salt River Mer., Arizona
CHAINS	
21.663	Station 1034+99.97, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described.
	Metes-and-Bounds Survey in Section 11, T 2 N, R 8 W, Gila and Salt River Mer., Arizona
	From the witness point of secs. 2 and 11, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located N 89°58' E, 7.60 chs. dist. from the cor. of secs. 2, 3, 10, and 11.
	S 6°56.8' W, on the southerly right-of-way line of the Central Arizona Project Canal.
2.527	Point for an angle point on the S right-of-way line of the Central Arizona Project Canal, not monumented.
	S 70°40.5' W, on the southerly right-of-way line of the Central Arizona Project Canal.
7.732	The witness point of secs. 10 and 11, on the southerly right-of-way line of the Central Arizona Project Canal, hereinbefore described, located S 0°00.5' W, 5.065 chs. dist., from the cor. of secs. 2, 3, 10, and 11.
	GENERAL DESCRIPTION
	The land encompassed in this survey is about 7 miles northwest of Tonopah, Arizona. Elevations range from about 1,300 to 2,900 feet above sea level.
	The Central Arizona Project Canal enters the township on the north boundary of section 5 and traverses easterly. Access is provided by the road along the canal and other secondary roads.
	The terrain is gently rolling in the south. Burnt Mountain in sections 3 and 4 is a prominent landmark for miles around. Creosote, scattering paloverde, ironwood, and medium cacti are found over most of the area.

18

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

### FIELD ASSISTANTS

NAMES	CAPACITY
Luke B. Granger	Surveying Technician
Robert M. Charboneau	Surveying Technician

19

#### CERTIFICATE OF SURVEY

I, Darren R. Breckenridge, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of March, 1988, I have dependently resurveyed portions of the east and north boundaries and a portion of the subdivisional lines, and surveyed a metes-and-bounds survey in certain sections of Township 2 North, Range 8 West, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 0 2 1988	Varien R. Bruficks Q
(Date)	(Cadastral Surveyor)
(Date)	(Cadastral Surveyor)
	CERTIFICATE OF APPROVAL
	BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona
north boundaries and a porti survey in certain sections o Meridian, Arizona, executed	the dependent resurvey of portions of the east and on of the subdivisional lines, and a metes-and-bounds f Township 2 North, Range 8 West, Gila and Salt River by Darren R. Breckenridge, Cadastral Surveyor, having found correct, are hereby approved.
MAY 0 9 1988	James P. Kelley
(Date)	(Chief Cadastral Surveyor of Arizona)
	CERTIFICATE OF TRANSCRIPT
	transcript of the field notes of the above-described a and Salt River Meridian, Arizona is a true copy of the
(Date)	(Chief Cadastral Surveyor of Arizona)