UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE						
	DEPENDENT RESURVEY OF					
	THE SOUTH, EAST, WEST, AND NORTH BOUNDARIES					
	AND THE SUBDIVISIONAL LINES					
AND '	THE SURVEY OF THE SUBDIVISION OF CERTA	IN SECTIONS,				
	TOWNSHIP 26 NORTH, RANGE 29 EAS	[
Of the	Gila and Salt River	Meridian,				
In the State of	Arizona					
	EXECUTED BY					
JACK A. SAVLA	N, CADASTRAL SURVEYOR					
Under special in	structions dated April 18 , 198	4, approved April 18, 1984				
	or the surveys included under Group Nu					
	actions datedApril 18					
-		-				
	Survey commenced May 2	, 1984				
	Survey completed October 17	. 1984				

INDEX DIAGRAM

26 NORTH , RANGE 29 EAST

T	44	43	3		41		40	T	38			36	
34	6	 114 5 	 	98	4	 85 	3	 72 	2	 	59	1	25
<u> </u>	114	113	3		97		85		71			58	
33	7	 111 8	 	96	9	 83	10	 70	11		56	12	23
<u> </u>	111	110)		96		82	İ	69			55	
 32	18	108 17		94	16	 81 	15	 67 	14		53	13	21
	107	106			93		80	<u> </u>	66			52	
 30 	19 104	105 20 103	 - - -	92	21 91	 78 	22 77	 65 	23 64		51	24	19
 28 	30 102	102 29 101	1	89	28 88	 76 	27 75	 62 	26 61		48	25 47	18
 26 	31	99 32	 	87	33	 73 	34	 60 	35		4 5	36	16
<u></u>	14	12		115	11	 	9 on 29 gui	<u> </u>	6		110	4	l

Section 14 subdivision...pp. 115 Section 22 subdivision...pp. 117 Section 24 subdivision...pp. 118

Section 28 subdivision...pp. 119

Section 32 subdivision...pp. 120 Section 34 subdivision...pp. 121

T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of the south, east, west, and north boundaries, and the subdivisional lines and the survey of the subdivision of certain sections, of Township 26 North, Range 29 East, Gila and Salt River Meridian, Arizona.

Frank Follman surveyed the township in its entirety in 1883. John G. Evans surveyed the (abandoned) south boundary of the Navajo Indian Reservation in 1885. L. E. Sechrist and S. E. Blout remonumented the corner of Township 26 North, Ranges 28 and 29 East, during their resurvey of the south boundary of Township 26 North, Range 28 East, in 1920. S. E. Blout resurveyed the south boundary and established closing section and one-quarter section corners thereon during his survey of the subdivision of Township 25 North, Range 29 East, in 1927.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 655, Arizona, dated April 18, 1984.

Prior to the restoration of any corners, the lines of previous surveys were retraced and a diligent search made for any evidence of previously established corner monuments. Identified corners are remonumented, as required, in their original positions; and lost corners are reestablished by the rules of proportionate measurement, based on the 1883 record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines of this survey was determined by hour-angle observations on the sun, and refer to the true meridian. The lines were carried forward by sustained angulation, being supplemented by other hour-angle observations on the sun taken throughout the progress of the survey.

Instrument used in this survey: Zeiss SM-41 electronic instrument.

T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona

CHAINS

The geographic coordinates, listed below, of the southeast corner of section 36, were determined from a tie made to the southeast corner of section 36, T 26 N, R 30 E. The coordinates of that corner were determined by the technique of relative positioning using the Magnovax 1502 Satellite Surveyor.

Southeast corner of T 26 N, R 29 E, G&SRM

Latitude: 35°36'17.78 N Longitude: 109°11'15.40" W

The mean magnetic declination is 124° E.

Dependent Resurvey of the S. Bdy. of T 26 N, R 29 E Gila and Salt River Meridian, Arizona

Restoring the resurvey executed by Sechrist and S. E. Blout in 1920 and

the resurvey executed by S. E. Blout in 1927

Beginning at the cor. of Tps 26 N, Rs 29 and 30 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, 1.9 lks. W of which, a sandstone, not of record, 24 x 8 x 4 ins., loosely set 4 ins. in the ground, clearly mkd. with 6 grooves on the N, E, S and W faces, from which the remaining original bearing trees

An oak, 22 in. diam. bears N 75½° E., 59 lks. dist., with healed blaze. (Record: N 44½° E.)

A ponderosa pine, 22 ins. diam. bears N 27° W, 20 lks. dist., with well healed blaze. (Record: N 35° W.)

Deposit the mkd. stone alongside the iron post.

Add the marks 1984 to the brass cap.

CHAINS	
	The corner is located in a wooded area, on N edge of a pipeline right-of-way, bears E and W.
	S 89°55' W, bet. secs. 1 and 36.
	Along the N edge of a pipeline right-of-way.
37.88	The ½ sec. cor. of sec. 1 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which the original bearing trees
	A ponderosa pine, 18 ins. diam., bears S 38% E, 56 lks. dist., with healed blaze. (Record: S 39° E.)
	A ponderosa pine stump, 29 ins. diam., bears S 71¾° W, 1.16 chs. dist. mkd. BT. (Record: S 72° W.)
39.94	The ½ sec. cor. of sec. 36 only, monumented with a sandstone, 16 x 11 x 4 ins., mkd. ½ on N face, firmly set 8 ins. in the ground, alongside which an iron post, 1 in. diam., in decrepit condition, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which the remaining original bearing tree
	A ponderosa pine, 30 ins. diam., bears N 25¾° E 33 lks. dist., with healed blaze. (Record: N 26° E, 32 lks. dist.)
	and the 1927 bearing tree
	A ponderosa pine, 34 ins. diam., bears N 50° W, 1.53 chs. dist., with healed blaze.
	At the corner point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
·	

CHAINS	
	T26N R29E ½ S36 T25N R29E
	1984
	Deposit the mkd. stone and 1927 brass cap alongside the stainless steel post, and destroy the iron post.
	S 89°48' W, beginning new measurement.
	Over gently rolling land, through forest.
38.01	The closing cor. of secs. 1 and 2, T 25 N, R 29 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivision of T 25 N, R 29 E, thence, continue measurement, bet. secs. 2 and 36.
40.07	The cor. of sec. 35 and 36, monumented with an iron post 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which evidence of the remaining 1883 bearing tree
	A root hole, alongside which a portion of a fallen pinyon, 10 ins. diam., mkd. NR29ES2CCBT bears S 47° E, 63 lks. dist. (Record: S 54° E, 52 lks. dist.)
	and new bearing trees
	An oak, 12 ins. diam., bears N 24° E, 48 lks. dist., mkd. T26N R29E S36 BT
	A pinyon, 10 ins. diam., bears N 76½° W, 93 lks. dist., mkd. T26N R29E S36 BT
	Add the marks 1984 to the brass cap.
	Set a steel fence post near the cor.
•	S 89°50' W, bet. secs. 2 and 35.

B00K₇5269

CHAINS	Over wooded land, along N edge of a pipeline right-of-way.	
38.05	The ½ sec. cor. of sec. 2 only, monumented with an iron post 1 in. diam., projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which evidence of a bearing tree not of record	
	A ponderosa pine stump, 26 ins. diam., bears S 52° E, 70 lks. dist., mkd. BT	
39.96	The ½ sec. cor. of sec. 35 only, monumented with a sandstone, 14 x 11 x 4 ins., firmly set, with no visible mks., alongside which, an iron post, 1 in. diam., projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which the remaining original bearing tree	
	A ponderosa pine, 34 ins. diam., bears N 12½° W, 88 lks. dist., with open blaze, and illegible scribing. (Record: N 12½° W, 87 lks. dist.)	
	and the remains of the 1927 bearing tree	
	A ponderosa pine stump, 34 ins. diam., with scribe marks ½ S35 BT on open blaze, bears N 31¾° W, 96 lks. dist. (Record: N 32° W).	
	At the corner point	
	Reset the 1927 resurvey monument, 30 ins. in the ground, and add the marks T26N R29E on the N half, and T25N R29E 1984 on the S half, of the brass cap.	
	from which new bearing trees	
	An oak, 10 ins. diam., bears N 78½° E, 1.50 chs. dist., mkd. % S35 BT.	
	A ponderosa pine, 19 ins. diam., bears N 17° W, 2.08 chs. dist., mkd. 4 S35 BT.	
	Deposit the original cor. monument alongside the iron post.	
	Set a steel fence post near the cor.	
·		

CHAINS	
	S 89°48' W, beginning new measurement.
	Over gently rolling woodland.
38.17	The closing cor. of secs. 2 and 3, T 25 N, R 29 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivision of T 25 N, R 29 E, from which the remaining original bearing tree
	An oak, 17 ins. diam., with healed blaze, bears S 22° E, 2.88 chs. dist.
	Thence, continue measurement bet. secs. 3 and 35.
40.10	The cor. of secs. 34 and 35 only, monumented with a sandstone, 30 x 7 x 7 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, clearly mkd. with 2 grooves on the E face and 4 grooves on the W face alongside which an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which a remaining original bearing tree
	An oak, 12 ins. diam., bears N 72° W, 18 1ks. dist., with healed blaze. (Record: N 73½° W, 17 1ks. dist.)
	and a 1927 bearing tree
	A ponderosa pine, 30 ins. diam., bears N 65° E, 1.14 chs. dist. with scribe marks S35 BT, visible on partially healed blaze. (Record: N 65½° E).
	At the cor. point.
	Reset the 1927 resurvey monument, 26 ins. in the ground, and add the mks. 1984 to the brass cap.
	Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.
	Deposit the mkd. stone alongside the iron post.

CHAINS	
	Set a steel fence post near the cor.
	·
	S 89°47' W, bet. secs. 3 and 34.
	Over wooded land, along N edge of a pipeline right-of-way.
38.08	The ½ sec. cor. of sec. 3 only, T 25 N, R 29 E, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which the original bearing trees
	A ponderosa pine stump, 32 ins. diam., bears S 40½° E, 2.61 chs. dist., with no scribe marks visible. (Record: S 40½° E, 262 lks. dist.)
	A ponderosa pine, 13 ins. diam., bears S 16½° W, 2.02 chs. dist., with healed blaze. (Record: S 16½° W).
40.02	The ½ sec. cor. of sec. 34 only, determined at record dist. from the original bearing tree
	A ponderosa pine, 19 ins. diam., bears N ll½° W, 56 lks. dist., with scribing visible ½ S BT. (Record: N ll° W).
	and the 1927 bearing tree
	A ponderosa pine, 27 ins. diam., bears N 16° E, 90 lks. dist., with healed blaze. (Record: N 16½° E, 9 lks. dist.)
	Note: Field conditions reveal an error in the dist. returned in the official record of the 1927 resurvey. It was determined that the dist. should have been 90 lks. vice 9 lks.
	At the cor. point.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
·	

CHAINS	
	T26N R29E
	¹ / ₄ S34
	T25N R29E
	1984
	Set a steel fence post near the cor.
	N 89°53' W, beginning new measurement.
	Over gently rolling woodland.
2.00	Graded gravel road, 15 ft. wide, bears N 54° E and S 54° W.
38.06	The closing cor. of secs. 3 and 4, T 25 N, R 29 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey.
	Thence, continue measurement bet. secs. 4 and 34.
40.14	The cor. of secs. 33 and 34 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T26N R29E S33 S34 1927, from which the remaining original bearing tree
	A ponderosa pine, 31 ins. diam., bears N 75¾° E, 35 lks. dist., with healed blaze. (Record: N 76° E)
	and the 1927 bearing tree
	An oak stump, 11 ins. diam., bears N 49½° W, 104 lks. dist., with visible scribe marks 33 BT. (Record: N 49½° W)
	and new bearing trees
	A ponderosa pine, 21 ins. diam., bears N 10° E 1.10 chs. dist., mkd. T26N R29E S34 BT.
	An oak, 9 ins. diam., bears N 57° W, 72 lks. dist., mkd. T26N R29E S33 BT.

CHAINS	
	Add the marks T25N R29E S4 1984 on the S half of the brass cap.
	From this point United States Geological Survey triangulation station "Oak Ridge Lot", monumented with a 1 in. anchor bolt, on the SW leg of a steel lookout tower, projecting 19 ins. above ground, bears S 15°38.3' W, 18.831 chs. dist.
	N 89°42' W, bet. secs. 4 and 33.
	Over wooded land, along the N edge of a pipeline right-of-way.
37.86	The ½ sec. cor. of sec. 4 only, monumented with an iron post 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey.
40.22	The ½ sec. cor. of sec. 33 only, is determined at record distance from the 1927 bearing trees
	A ponderosa pine, 25 ins. diam., bears N 85¾° E, 2.76 chs. dist. with visible scribe marks S33 BT on open blaze. (Record: N 85½° E)
	A ponderosa pine, 32 ins. diam., bears N 82½° W, 4.85 chs. dist., with visible scribe marks BT on a partially healed blaze. (Record: N 82¾° W)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
·	1 ₄ S 33 T25N R29E
	1984
·	Set a steel fence post near the cor.
	N 89°44' W, beginning new measurement.

T	
CHAINS	
37.58	The closing cor. of secs. 4 and 5, T 25 N, R 29 E, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. as described in the official record of the 1927 survey of the subdivision of T 25 N, R 29 E, from which the remaining original bearing tree A ponderosa pine, 28 ins. diam., bears S 84½° W,
	1.63 chs. dist., with healed blaze. Thence, continue measurement bet. secs. 5 and 33.
	mence, continue measurement bet. secs. 5 and 55.
40.23	The cor. of secs. 32 and 33 only, monumented with a sandstone, 24 x 10 x 3 ins., firmly set, clearly mkd. with 4 grooves on E face, alongside which an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey, from which the remaining original bearing trees
	An oak, 27 ins. diam., bears N 80½° E, 1.43 chs. dist., with well healed blaze. (Record: Dead, N 81° E)
	An oak stump, 12 ins. diam., bears N 40½° W, 62 lks. dist., with a portion of a healed blaze. (Record: Dead, N 40° W, 61 lks. dist.)
	and the 1927 bearing tree
	A ponderosa pine, 26 ins. diam., bears N 68° E 40 lks. dist., with healed blaze. (Record: N 69° E)
	An oak, 14 ins. diam., bears N 40½° W, 69 lks. dist., with healed blaze. (Record: 68 lks.)
	At the cor. point
	Reset the 1927 resurvey monument, 23 ins. in the ground, and add the marks 1984 to the brass cap.
	Deposit the mkd. stone alongside the iron post.
	Set a steel fence post near the cor.
	N 89°46' W, bet. secs. 32 and 5.

	CHAINS	
		Over rolling woodlands along N edge of a pipeline right-of-way.
	37.40	The ½ sec. cor. of sec. 5 only, monumented with an iron post, 1 in. diam., projecting 7 ins. above ground, with brass cap mkd. as described in the official record of the 1927 resurvey.
	40.08	The ½ sec. cor. of sec. 32 only, monumented with a pinyon, 18 ins. diam., mkd. ½ S on N face, from which the 1927 bearing trees
,		A ponderosa pine, 20 ins. diam., bears N 14½° E, 49 lks. dist., with healed blaze. (Record: Norway Pine, N 15½° E)
·		A pinyon, 9 ins. diam., bears N 53° W, 92 lks. dist., mkd. X/S32BT. (Record: N 54¾° W, 93 lks.)
		and new reference monument
		A monument, 30 ins long, composed of a stainless steel post, 25 ins. long, 2¾ ins diam., bonded to a magnetic poly breakaway base 26 ins. in the ground, for a reference monument, bears N 45° E 16½ ft. dist., with brass cap mkd. RM T26N R29E ¼ S32 16.5 ft. 1984 and an arrow pointing to the cor.
		N89°49' W, beginning new measurement.
	37.30	The closing cor. of secs. 5 and 6, T 25 N, R 29 E, dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, the brass cap mkd. as described in the official record of the 1927 survey of the subdivision of T 25 N, R 29 E, from which the original bearing trees
		A ponderosa pine, 29 ins. diam., bears S 9° E, 4.40 chs. dist., with healed blaze.
		A pinyon, 13 ins. diam., bears S $14\frac{1}{2}^{\circ}$ W, 3.34 chs. dist., mkd. T25N R29E S6 CC BT.
		Thence, continue measurement bet. secs. 6 and 32.
		·

40.32

The cor. of secs. 31 and 32 only, is determined at record distance from the 1927 bearing trees

- A ponderosa pine, 31 ins. diam., bears N 81° E, 6.49 chs. dist., with healed blaze.
- A pinyon, 10 ins. diam., bears N 26¼° W, 4.45 chs. dist., mkd. T26 on partially healed blaze. (Record: N 26° W.)

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

T26N R29E | S31 | S32 T25N R29E S6 1984

Set a steel fence post near the cor.

N 89°49' W, bet., secs. 31 and 6.

Over gentle woodlands, along N edge of a pipeline right-of-way.

40.30

The $\frac{1}{4}$ sec. cor. of sec. 31 only, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1927 dependent resurvey, from which the 1927 bearing tree

A pinyon, 14 ins. diam., bears N 17½° W, 42 lks., dist., mkd. ¼ S on a partially healed blaze. (Record: N 17° W)

and a new bearing tree

A pinyon, 9 ins. diam., bears N 73° E, 59 lks., dist., mkd. ½ S31 BT.

Add the marks T26N R29E on the N half and T25N R29E 1984 on the S half of the brass cap.

	CHAINS	
		Set a steel fence post near the cor.
		NOTE: According to the official record of the 1927 dependent resurvey, the 1927 monument was set alongside the 1883 cor. tree and a 1927 bearing tree was supposedly established from the cor. tree. Field evidence indicates that the bearing tree was established from the iron post. No evidence of the cor. tree could be found, therefore, the 1927 monument is accepted as the best available evidence of the corner position.
		N 89°52' W, beginning new measurement.
·	35.89	The closing cor. of T 25 N, Rs. 28 and 29 E, monumented with an iron post, 3 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1920 survey of the E bdy. of T 25 N, R 28 E, from which the remaining original bearing tree
		A ponderosa pine stump, 18 ins. diam., bears S 45½° W, 2.89 chs. dist., mkd. S1CCBT.
		Thence, continue measurement bet. secs. 1 and 31.
	39.70	The cor. of Tps 26 N, Rs. 28 and 29 E, determined at record dist. from the remaining original bearing tree
		A pinyon, 19 ins. diam., bears N 18½° W, 2.16 chs., dist., with healed blaze.
		and the 1920 bearing trees
		A pinyon, 16 ins. diam., bears N $42\frac{1}{4}^{\circ}$ E, 1.37 chs., dist., mkd. T26N R29E S31 BT.
		A ponderosa pine, 20 ins. diam., bears N 40½° W, 3.35 chs. dist., mkd. T26N R28E S36 BT.
	·	At the cor. point
	·	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 15 ins. in the ground, with brass cap mkd.

CHAINS T26N	
R28E R29E S36 S31 	
from which a new bearing tree	
A pinyon, 9 ins. diam., bears N 55% E, 2.72 chs. dist., mkd. T26N R29E S31 BT	
and the remains of an original bearing tree	
A poorly defined root hole, bears N 57½° E, 1.97 chs. dist., alongside of which is lying a decayed pinyon, 16 ins. diam., with illegible scribing on open blaze. (Record: 199 lks.)	
Set a steel fence post near the cor.	
Dependent Resurvey of E. Bdy. of T 26 N, R 29 E Gila and Salt River Meridian, Arizona	
(Restoring the survey executed by Frank Follman in 1883.)	
From the cor. of Tps 26 N, Rs. 29 and 30 E.	
N 0°25' W, bet. secs. 31 and 36.	
Over rolling woodlands.	
The ½ sec. cor. of secs. 31 and 36, monumented with a sandstone, 16 x 10 x 2 ins., firmly set, 8 ins. in the ground, dimly mkd. 4 on W face.	
At the cor. point	
Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	3

		
CHAINS		
	T260	
	R29E R30E	
	S36 S31	
	1984	
	from which new bearing trees	
	A ponderosa pine, 11 ins. diam., bears S 37° E, 70 lks. dist., mkd. 4 S31 BT.	
	A pinyon, ll ins. diam., bears S 25¾° W, 100 lks., dist., mkd. ¼ S36 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	N 0°09' W, beginning new measurement.	
	Through gently rolling woodland.	
40.40	The cor. of secs. 25, 30, 31 and 36, monumented with a broken sandstone, 20 x 12 x 4 ins., firmly set 4 ins. in the ground, with no visible marks. This point is accepted as the best available evidence of the original cor. position.	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	
	T26N R29E R30E S25 S30 S 36 S 31 1984	
	from which new bearing trees	
	A ponderosa pine, 13 ins. diam., bears N 55½° E, 3.11 chs. dist., mkd. T26N R30E S30 BT.	
•		

CHAINS	
	A ponderosa pine, 19 ins. diam., bears S 59¼° E, 2.38 chs. dist., mkd. T26N R30E S31 BT.
	A ponderosa pine, 18 ins. diam., bears S 52½° W, 2.09 chs. dist., mkd. T26N R29E S36 BT.
	A ponderosa pine, 15 ins. diam., bears N 37½° W, 1.92 chs. dist., mkd. T26N R29E S25 BT.
	Deposit the stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	N 0°48' W, bet. secs. 25 and 30.
	Through gently rolling forests.
39.73	The ½ sec. cor. of secs. 25 and 30, monumented with a sandstone, 20 x 14 x 4 ins., loosely set 4 ins. in the ground, in a mound of stone, 4 ft. base, 1 ft. high, mkd. ½ on W face.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, encircled by an embedded collar of stone with brass cap mkd.
	T26N
	1/4 R29E R30E .
	S25 S30 1984
	from which a new bearing tree
	A ponderosa pine, 9 ins. diam., bears S 85° E, 57 lks. dist., mkd. ½ S30 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	N 0°09' W, beginning new measurement.

CHAINS	
	Through rolling forest.
40.24	The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 21 x 12 x 4 ins., firmly set 8 ins. in the ground, clearly mkd. with 4 grooves on the N face and 2 grooves on the S face from which the remaining original bearing trees
	A ponderosa pine, 36 ins. diam., bears S 3½° W, 65 lks. dist., with illegible scribings on nearly healed blaze. (Record: S 10° W.)
	A ponderosa pine, 12 ins. diam., bears N 42° W, 57 lks. dist., with illegible scribing on open blaze. (Record: N 40° W, 56 lks.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, encircled with an embedded collar of stone with brass cap mkd.
	T26N R29E R30E S24 S19 S25 S30 1984
	from which new bearing trees
	A ponderosa pine, 12 ins. diam., bears N 17° E, 80 lks. dist., mkd. T26N R30E S19 BT.
	A ponderosa pine, 17 ins. diam., bears S 47° W, 1.26 chs. dist., mkd. T26N R29E S25 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a steel fence post near the cor.
·	N 0°15' W, bet. secs. 19 and 24.
·	Through rolling forest.

CHAINS	
40.35	The ½ sec. cor. of secs. 19 and 24, monumented with a sandstone, 16 x 16 x 5 ins., loosely set 4 ins. in the ground, witnessed by a mound of stone, 3 ft. base, 2 ft. high, W of cor., mkd. ½ on W face, the original bearing trees
	An oak, 18 ins. diam., bears N 10½° E, 55 lks. dist., with well healed blaze. (Record: N 20° E, 57 lks. dist.)
	A ponderosa pine, 24 ins. diam., bears N 48½° W, 74 lks. dist., mkd. ¼ and other illegible marks. (Record: N 45¼° W, 75 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, encircled with an embedded collar of stone, with brass cap mkd.
	T26N
	120N
	R29E R30E
	S24 S19
	1984
	from which a new bearing tree
	A ponderosa pine, 8 ins. diam., bears N 47¾° E, 7 lks. dist., mkd. ¼ S19 BT.
	Deposit the original stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	N 0°08' W, beginning new measurement.
	Through rolling forest.
40.13	The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 16 x 12 x 4 ins., loosely set 6 ins. in the ground, clearly mkd. with 3 notches on N edge and 3 notches on S edge, from which the original bearing trees
•	

CHAINS	
	An oak, 6 ins. diam., bears N 83° E, 26 lks. dist., with no scribe marks visible on partially healed blaze. (Record: N 60° E, 27 lks. dist.)
	A ponderosa pine stump, 22 ins. diam., bears S 343,° W, 63 lks. dist., with no blaze visible. (Record: S 50° W.)
	A ponderosa pine, 26 ins. diam., bears N 39½° W, 75 lks. dist., with illegible scribing on nearly healed blaze. (Record: N 45° W, 74 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, encircled with an embedded collar of stone with brass cap mkd.
	T26N R29E R30E S13 S18 S24 S19 1984
	from which new bearing trees
	A ponderosa pine, 12 ins. diam., bears S 79° E, 72 lks. dist., mkd. T26N R30E S19 BT.
	A ponderosa pine, 12 ins. diam., bears S 69½° W, 1.19 chs. dist., mkd. T26N R29E S24 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	N 0°10' W, bet. secs. 13 and 18.
	Through rolling forests.
39.90	Point for the ½ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.

	
CHAINS	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N 1/4 R29E R30E S13 S18 1984
	from which
	A pinyon, 9 ins. diam., bears S 72½° E, 36 lks. dist., mkd. ½ S18 BT.
	A pinyon, 5 ins. diam., bears N 56½° W, 6 lks. dist., mkd. ½ S13 BT.
	Set a steel fence post near the cor.
75.88	The closing cor. of secs. 7 and 18, described in the official record of the dependent resurvey of a portion of the abandoned S bdy. of the Navajo Indian Reservation in T 26 N, through R 30 E, concurrently resurveyed under this same group.
	Thence, continue measurement bet. secs. 7 and 13.
79.80	The original cor. of secs. 7, 12, 13 and 18, this point now functions as the cor. of secs. 12 and 13 only, determined at record distance from the remaining original bearing trees
	A ponderosa pine, 18 ins. diam., bears S 57¾° W, 25 lks. dist., mkd. T26N R29E S13 on opened blaze. (Record: S 22° W.)
	A ponderosa pine stump, 23 ins. diam., bears N 75½° W, 28 lks. dist., with healed blaze. (Record: N 30° W.)
	At the cor. point

_			
	CHAINS		
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 10 ins. in the ground, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.	
		T26N T26N S12 S13 R30E R29E S7 1984	
		from which a new bearing tree	
		A pinyon, 7 ins. diam., bears N 54½° W, 55 lks. dist., mkd. T26N R29E S12 BT.	
		N 0°04' E, bet. secs. 7 and 12.	
		Through rolling forest.	
	36.08	The ½ sec. cor. of sec. 7 only, set described in the official record of the survey of a portion of the subdivisional lines, T 26 N, R 30 E, surveyed concurrently under this same group.	
	40.31	Point for the original ½ sec. cor. of secs. 7 and 12, this point now functions as the ½ sec. cor. of sec. 12 only, at proportionate dist; there is no remaining evidence of the original cor. position.	
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	
		T26N R29E R30E ¹ / ₄ S12 1984	
		from which	
		A ponderosa pine, 15 ins. diam., bears S 66° W, 1.46 chs. dist., mkd. ½ S12 BT.	
L			

CHAINS		
76.08	The closing cor. of secs. 6 and 7, set and witnessed as described in the official record of the survey of a portion of the subdivisional lines, T 26 N, R 30 E, surveyed concurrently under this same group.	
	Thence, continue measurement bet. sec. 6 and 12.	
80.62	The original cor. of secs. 1, 6, 7 and 12, this point now functions as the cor. of secs. 1 and 12 only, monumented with a sandstone, 16 x 9 x 4 ins., firmly set 4 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high, clearly mkd. with 1 groove on the N face and 5 grooves on the S face, from which the remains of the original bearing trees	
	A roothole, bears N 37¾° E, 60 lks. dist., alongside of which is lying a decayed ponderosa pine log, 24 ins. diam., with no visible scribing or blaze. (Record: N 45° E, 56 lks. dist.)	
	A ponderosa pine stump, 22 ins. diam., bears N½°W, 77 lks. dist., with scribe marks 3T on open blaze. (Record: N 15°W.)	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, encircled with an embedded collar of stone with brass cap mkd.	
	T 26 N T 26 N S 1 R 30 E S 12 R 29 E S 6 1984	
	from which a new bearing tree	
	A ponderosa pine, 16 ins. diam., bears S 71½° W, 52 lks. dist., mkd. T26N R29E S12 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a steel fence post near the cor.	

CHAINS	
	N 0°25' W, bet. secs. 1 and 6.
	Through rolling forest.
35.46	The ½ sec. cor. of sec. 6 only, set described in the official record of the survey of a portion of the subdivisional lines, T 26 N, R 30 E, surveyed concurrently under this same group.
40.29	Point for the original 4 sec. cor. of secs. 1 and 6, at proportionate dist; there is no remaining evidence of the original cor., this point now functions as the 4 sec. cor. of sec. 1 only.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 10 ins. in the ground, encircled in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T26N R29E R30E ½ S1 1984
	from which
	An oak, 8 ins. diam., bears N 73½° W, 1.42 chs. dist., mkd. ¼ S1 BT.
80.58	The cor. of Tps. 26 and 27 N, Rs. 29 and 30 E, monumented with a sandstone, 18 x 10 x 8 ins., loosely set 3 ins. in the ground, clearly mkd. with 6 grooves on the N and S faces, and dimly mkd. with 6 grooves on the E and W faces, from which the remaining original bearing trees
	A ponderosa pine, 32 ins. diam., bears N 49½° E, 1.43 chs. dist., with illegible scribing on a nearly healed blaze. (Record: N 50° E, 149 lks. dist.)

CHAINS

A root hole, bears S 79¾° W, 25 lks. dist., alongside of which is lying a decayed ponderosa pine log, 20 ins. diam., with illegible scribing on an open blaze. (Record: S 10° W, 18 lks. dist.)

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, encircled with an embedded collar of stone with brass cap mkd.

T27N
R29E | R30E
S36 | S31
S1 | S6
T26N
1984

from which new bearing trees

- A ponderosa pine, 20 ins. diam., bears S 25° E, 1.16 chs. dist., mkd. T26N R30E S6 BT.
- A ponderosa pine, 17 ins. diam., bears S 78½° W, 99 lks. dist., mkd. T26N R29E S1 BT.
- A ponderosa pine, 18 ins. diam., bears N 163° W, 1.21 chs. dist., mkd. T27N R29E S36 BT.

Deposit the mkd. stone alongside the stainless steel post.

Set a steel fence post near the cor.

Dependent Resurvey of W. Bdy. of T 26 N, R 29 E Gila and Salt River Meridian, Arizona

(Restoring the survey executed by Frank Follman in 1883)

From the cor. of Tps. 26 N, Rs. 28 and 29 E.

CHAINS	
	N 0°11' E, bet. secs. 31 and 36.
	Through rolling forest.
40.10	The ½ sec. cor. of secs. 31 and 36, monumented with a ponderosa pine, 33 ins. diam., with no visible scribe marks, from which the original bearing trees
	A ponderosa pine, 20 ins. diam., bears N 19½° E, 44 lks. dist., with scribe marks 4 visible on opened face. (Record: N 25° E, 41 lks. dist.)
	A ponderosa pine, 28 ins. diam., bears N 13½° W, 44 lks. dist., with scribe marks BT visible on opened face. (Record: N 20° W, 40 lks. dist.)
	At the cor. point
	Add the marks 1/4 S36 on the W face and S31 on the E face of the cor. tree.
	from which a new bearing tree and reference monument
	A pinyon, 10 ins. diam., bears N 85½° W, 91 lks. dist., mkd. ½ S36 BT.
	A stainless steel post, 10 ins. long, and in a mound of stone, 4 ft. base to top, for a reference monument, bears N 45° E, 16.5 ft. dist., with brass cap mkd. RM T26N R29E ½ S31 16.5 FT 1984 and an arrow pointing to the cor.
	Set a steel fence post near the cor.
	N 0°11' E, beginning new measurement.
40.00	Through rolling forest.
40.29	The cor. of secs. 25, 30, 31 and 36, determined at record dist. from the remaining original bearing trees
	A pinyon, 19 ins. diam., bears N 113 ° E, 1.53 chs. dist., with illegible scribing on opened face. (Record: N 10° E.)
	A pinyon, 16 ins. diam., bears N 73 ° W, 1.70 chs. dist., with scribe marks 6NR visible on opened face. (Record: N 74° W.)

CHAINS

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

T26N R30E | R29E S25 | S30 S36 | S31 1984

from which new bearing trees

A pinyon, 14 ins. diam., bears S $50\frac{3}{4}$ ° E, 1.64 chs. dist., mkd. T26N R29E S31 BT.

A pinyon, 17 ins. diam., bears S 66% W, 1.03 chs. dist., mkd. T26N R28E X S36 BT.

Set a steel fence post near the cor.

N 1°03' W, bet. secs. 25 and 30.

Through rolling forest.

39.83

The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a sandstone, 20 x 7 x 3 ins., firmly set 11 ins. in the ground, clearly mkd. $\frac{1}{4}$ on W face, from which the remains of an original bearing tree

A ponderosa pine stump, 23 ins. diam., bears S 17° W, 54 lks. dist., with scribe marks SBT visible on an open blaze. (Record: S 44° W, 137 lks. dist.)

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

CHAINS

from which new bearing trees

A ponderosa pine, 29 ins. diam., bears N 17½° E, 33 lks. dist., mkd. ¼ S30 BT.

A pinyon, 16 ins. diam., bears S 21½° W, 1.25 chs. dist., mkd. ¼ S25 BT.

Deposit the mkd. stone alongside the stainless steel post.

Set a steel fence post near the cor.

N 1°20' E, beginning new measurement.

Through rolling forest.

40.78

The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, $22 \times 10 \times 4$ ins., loosely set 3 ins. in the ground, encircled in a mound of stone 2 ft. base, 1 ft. high, clearly mkd. with 5 grooves on the N face, and 1 groove on the S face, from which the remaining original bearing trees

A pinyon, 12 ins. diam., bears N 84¾° E, 32 lks. dist., with illegible scribing on partially healed blaze. (Record: N 76° W, 30 lks. dist.)

A pinyon, 23 ins. diam., bears S 20° W, 50 lks. dist., with scribe marks T26N R28E S B visible on partially healed blaze. (Record: S 30° W, 84 lks. dist.)

CHAINS		
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	
	T26N	
	R28E R29E	
	1984	
	from which new bearing trees	
	A pinyon, 7 ins. diam., bears S 31¾° E,	
	32 lks. dist., mkd. T26N R29E S30 BT.	
	A pinyon, 7 ins. diam., bears N 823° W,	
	27 lks. dist., mkd. T26N R28E S24 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.	
	Set a steel fence post near the cor.	
	CHAINS	At the cor. point Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R28E R29E S24 S19 S25 S30 1984 from which new bearing trees A pinyon, 7 ins. diam., bears S 31¾° E, 32 lks. dist., mkd. T26N R29E S30 BT. A pinyon, 7 ins. diam., bears N 82¾° W, 27 lks. dist., mkd. T26N R28E S24 BT. Deposit the mkd. stone alongside the stainless steel post. Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

N 0°06' E, bet. secs. 19 and 24.

Through rolling forest.

40.30

The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented with a ponderosa pine stump, 40 ins. diam., with scribe marks 4S visible in open blaze on W face.

from which

A ponderosa pine, 18 ins. diam., bears S 67¾° E, 2.79 chs. dist., mkd. ¼ S19 BT.

A ponderosa pine, 20 ins. diam., bears S 36½° W, 1.74 chs. dist., mkd. ½ S24 BT.

CHAINS	
	Set a stainless steel post, 24 ins. in the ground, for a reference monument, bears S 45° E, 16.5 ft. dist., with brass cap mkd. RM T26N R29E 4 S19 16.5 FT. 1984 and an arrow pointing to the cor.
•	Set a steel fence post near the cor.
	N 0°03" W, beginning new measurement.
	Through rolling forest.
40.12	The cor. of secs. 13, 18, 19 and 24, determined at record dist. from the remaining original bearing trees
	A pinyon, 18 ins. diam., bears N 25½° E, 38 lks. dist., with scribe marks 26N R2 S1 visible on partially healed blaze. (Record: N 42° E).
	A pinyon, 11 ins. diam., bears N 64° W, 17 lks. dist., with scribe marks NR28S visible on partially healed blaze. (Record: N 45° W).
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N
	R28E R29E
	S13 S18 S24 S19 1984
	from which new bearing trees
	A pinyon, 8 ins. diam., bears S 66° E, 28 lks. dist., mkd. T26N R29E S19 BT.
	A pinyon, 9 ins. diam., bears S 384° W, 1.21 chs. dist., mkd. T26N R28E S24 BT.
	Set a steel fence post near the cor.

CHAINS	
	N 0°05' W, bet. secs. 13 and 18.
	Through rolling forest.
40.23	Point for the 1/2 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N
	R28E R29E
	S13 S18
	1984
	from which
	A ponderosa pine, 25 ins. diam., bears N 65½° E, 2.84 chs. dist., mkd. ¼ S18 BT.
	A pinyon, 7 ins. diam., bears N 70½° W, 1.36 chs. dist., mkd. ½ S13 BT.
	Set a steel fence post near the cor.
80.46	The cor. of secs. 7, 12, 13 and 18, determined at record dist. from the remaining bearing trees
	A ponderosa pine rotted stump, bears S 16° W, 45 lks. dist., with scribe marks 13 BT. (Record: S 17° W).
	A ponderosa pine, 28 ins. diam., bears N 33½° W, 40 lks. dist., with illegible scribing visible on opened blaze. (Record: N 36° W).
	At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.

T26N R28E | R29E S12 | S7 S13 | S18 1984

from which new bearing trees

A ponderosa pine, 20 ins. diam., bears N 213/4° E, 2.85 chs. dist., mkd. T26N R29E S7 BT.

A ponderosa pine, 17 ins. diam., bears S 40° E, 3.55 chs. dist., mkd. T26N R29E S18 BT.

A ponderosa pine, 18 ins. diam., bears S 51½°W, 89 lks. dist., mkd. T26N R28E S13 BT.

Set a stainless steel fence post near the cor.

N 0°20' W, bet. secs. 7 and 12.

Through rolling forest.

41.14

The ½ sec. cor. of secs. 7 and 12, determined at record bearing and dist. from the original bearing tree

A pinyon, 14 ins. diam., bears S 20° E, 1.20 chs. dist., mkd. 4 BT.

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

T26N

1/4

R28E | R29E

S12 | S7

1984

CHAINS	
	from which a new bearing tree
	A pinyon, 8 ins. diam., bears S 79° W, 47 lks. dist., mkd. ½ S12 BT.
•	Set a stainless steel fence post near the cor.
	N 1°55' W, beginning new measurement.
	Through rolling forest.
40.30	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R28E R29E S1 S6 S12 S7
	1984
	from which
	A pinyon, 12 ins. diam., bears N 42¾° E, 30 lks. dist., mkd. T26N R29E S6 BT.
	A pinyon, 9 ins. diam., bears S 70½°E, 20 lks. dist., mkd. T26N R29E S7 BT.
	A pinyon, 8 ins. diam., bears S 24° W, 15 lks. dist., mkd. T26N R28E S12 BT.
	A pinyon, 7 ins. diam., bears N 51¾° W, 58 lks. dist., mkd. T26N R28E S1 BT.
	Set a stainless steel fence post near the cor.
	N 1°55' W, bet. secs. 1 and 6.
	Through rolling forest.
•	

		office and bare Rever Meridian, Arizona
СН	IAINS	
40	0.30	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
		T26N
		R28E R29E S1 S6 1984
		from which
		A ponderosa pine, 11 ins. diam., bears S 37½° E, 1.37 chs. dist., mkd. ½ S6 BT.
		A ponderosa pine, 24 ins. diam., bears N 79½° W, 2.05 chs. dist., mkd. ¼ Sl BT.
		Dig pits on line N and S, 3 ft. dist.
		Set a stainless steel fence post near the cor.
80	.60	The cor. of Tps. 26 and 27 N, Rs. 28 and 29 E, determined at record dist. from the remaining original bearing trees
		A ponderosa pine sawed stump, 20 ins. diam., bears N 65° E, 97 lks. dist. with a healed and rotted blaze. (Record: N 52½° E)
		A ponderosa pine sawed stump, 36 ins. diam., bears S 1934° W, 1.99 chs. dist., with scribe marks BT visible on open blaze. (Record: S 25° W)
		At the cor. point
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T27N
	R28E R29E
	S36 S31
	S1 S6
	T26N
•	1984
	from which new bearing trees
	A pinyon, 10 ins. diam., bears N 42½° E, 14 lks. dist., mkd. T27N R29E S31 BT.
	A pinyon, 8 ins. diam., bears S $9\frac{1}{4}^{\circ}$ E, 44 lks. dist., mkd. T26N R29E S6 BT.
	A pinyon, 6 ins. diam., bears S 293° W,
	29 lks. dist., mkd. T26N R28E Sl BT.
	A ponderosa pine, 21 ins. diam., bears N 9½° W, 96 lks. dist., mkd. T27N R28E S36 BT.
	Set a stainless steel fence post near the cor.
	Dependent Resurvey of N Bdy. of T. 26 N., R. 29 E. Gila and Salt River Meridian, Arizona
	(Restoring the survey executed by Frank Follman in 1883)
	From the cor. of Tps. 26 and 27 N, Rs. 29 and 30 E.
	N 89°58' W, bet. secs. 1 and 36.
	Through rolling forest.
40.39	The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a sandstone, 8 x 6 x 3 ins., firmly set 4 ins. in the ground, clearly mkd. $\frac{1}{4}$ on the underside.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 5 ins. in the ground, encircled by a mound of stone, 4 ft. base to top with brass cap mkd.

 	
CHAINS	T27N R29E 1 ₄ S36 S1 T26N 1984
,	from which
	A ponderosa pine, 17 ins. diam., bears N 9½° E, 98 lks. dist., mkd ½ S36 BT.
	A ponderosa pine, 18 ins. diam., bears S 6½° E, 85 chs. dist., mkd ½ Sl BT.
	Deposit the mkd. stone alongside the stainless steel post.
	N 89 56'. W, beginning new measurement.
	Through rolling forest.
12.40	Graded road, 25 ft. wide, bears N 12° E and S 12° W.
13.43	Barbed wire fence, 5 strand, bears N 12° E and S 12° W.
40.33	The cor. of secs. 1, 2, 35, and 36, monumented with a sandstone, 7 x 7 x 3 ins., clearly mkd. with 5 grooves on the W face and 1 groove on the E face, firmly set 5 ins. below ground, from which the remaining original bearing trees
	A ponderosa pine, 32 ins. diam., bears N 36° E, 55 lks dist., with healed blaze. (Record: N 20° E, 54 lks dist.)
	A ponderosa pine, 28 ins. diam., bears S 71° W, 85 lks. dist., with scribe marks BT visible on an opened blaze. (Record: S 75° W., 73 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

CHAINS	T27N R29E S35 S36 S2 S1 T26N 1984
	from which new bearing trees
	A ponderosa pine, 17 ins. diam., bears S 75½° E, 2.14 chs. dist., mkd. T26N R29E S1 BT.
	A ponderosa pine, 22 ins. diam., bears N 22½° W, 1.33 chs. dist., mkd. T27N R29E S35 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 89°13' W, bet. secs. 2 and 35.
	Over rolling forest land.
40.18	The ½ sec. cor. of secs. 2 and 35, monumented with a sandstone, 18 x 9 x 6 ins. loosely set in a mound of stone, 3 ft. base, ½ ft high, clearly mkd. ¼ on the N face, from which the original bearing tree
	A ponderosa pine sawed stump, 12 ins. diam., bears N 4° W, 12 lks. dist., mkd. ½ S BT on open blaze. (Record: N 9½° E, 13 lks. dist.)
	At the cor. point
	Set an aluminum rod, l in. diam., l6 ins. long, ll ins. in a drill hole, with aluminum cap mkd.
	T27N R29E 1 ₄ S35 S2 T26N
	1984
	from which new bearing tree and bearing object

CHAINS	
	A ponderosa pine, 23 ins. diam., bears N 15½° W, 1.30 chs. dist., mkd. ½ S35 BT.
	A sandstone outcrop, 10 x 5 x 1 ft. above ground, even with the general surface, bears N 3½° W, 34 lks. dist., mkd. BXO
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Deposit the mkd. stone in the mound of stone.
	N 89°21' W, beginning new measurement.
	Through rolling forest.
39.71	The cor. of secs. 2, 3, 34 and 35, monumented with a sandstone, 16 x 9 x 6 ins. firmly set 11 ins. in the ground, clearly mkd. with 2 grooves on the E face and 4 grooves on the W face, from which the remaining original bearing tree
	A ponderosa pine sawed stump, 33 ins. diam., bears N 29½° W, 1.20 chs. dist., with illegible scribing visible on open blaze. (Record: N 40° E, 119 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T27N R29E
	S34 S35
	S3 S2 T26N
	1984
	from which new bearing trees
	A ponderosa pine, 26 ins. diam., bears N 1°E, 94 lks. dist., mkd. T27N R29E S35 BT.
·	A ponderosa pine, 25 ins. diam., bears S 54½° E, 2.95 chs. dist., mkd. T26N R29E S2 BT.
	i l

CHAINS	
	A pinyon, 6 ins. diam., bears S 82½° W, 1.14 chs. dist., mkd. T26N R29E S3 BT.
	Deposit the mkd. stone alongside the stainless steel post.
,	Set a stainless steel fence post near the cor.
	West, bet. secs. 3 and 34.
	Through rolling forest.
40.36	The ½ sec. cor. of secs. 3 and 34, monumented with a sandstone, 16 x 12 x 5 ins., firmly set 5 ins. in the ground, clearly mkd. ½ on top, from which the original bearing trees
	A ponderosa pine, 29 ins. diam., bears S 35¾° W, 36 lks. dist., with healed blaze. (Record: S 50° W, 38 lks. dist.)
	A ponderosa pine, 29 ins. diam., bears N 61½° W, 17 lks. dist., with healed blaze. (Record: N 9½° W, 19 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T27N R29E
	$\frac{1}{4} \frac{834}{33}$
	S3 T26N
	1984
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	S 89°58' W, beginning new measurement.

Through rolling forest.
Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
T27N R29E S33 S34 S4 S3 T26N 1984
from which
A ponderosa pine, 24 ins. diam., bears N 16½° E, 1.92 chs. dist., mkd. T27N R29E S34 BT.
A ponderosa pine, 22 ins. diam., bears S 18½° W, 1.68 chs. dist., mkd. T26N R29E S4 BT.
A ponderosa pine, 20 ins. diam., bears N 32½°W, 46 lks. dist., mkd. T27N R29E S33 BT.
Set a stainless steel fence post near the cor.
S 89°58' W, bet. secs. 4 and 33.
Through rolling forest.
The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with a sandstone, 10 x 5 x 5 ins., firmly set 2 ins. in the ground, clearly mkd. with $\frac{1}{4}$ on bottom.
At the cor. point
Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T27N R29E 1/4 S33 S4 T26N 1984
•	from which new bearing trees
	A ponderosa pine, 16 ins. diam., bears S 64½° E, 3.89 chs. dist., mkd. ½ S4 BT.
	A ponderosa pine, 24 ins. diam., bears N 37½° W, 2.66 chs. dist., mkd. ½ S33 BT.
	Dig pits on line E and W, 3 ft. dist.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	N 89°42' W, beginning new measurement.
40.28	The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 17 x 11 x 4 ins., loosely set on surface of ground, clearly mkd. with 2 grooves on the W face and 4 grooves on the E face, from which the remaining original bearing tree
	A ponderosa pine stump, 36 ins. diam., bears N 56° E, 53 lks. dist., with no scribing visible on an opened blaze. (Record: N 15½° E, 60 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T27N R29E S32 S33 S5 S4 T26N 1984

CHAINS	
	from which new bearing trees
	A ponderosa pine, 23 ins. diam., bears N 52° E, 2.26 chs. dist., mkd. T27N R29E S33 BT.
	A ponderosa pine, 19 ins. diam., bears S 85½° W, 1.50 chs. dist., mkd. T26N R29E S5 BT.
	A ponderosa pine, 21 ins. diam., bears N 27½° W, 1.33 chs. dist., mkd. T27N R29E S32 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 89°39' W, bet. secs. 5 and 32.
	Through rolling forest.
6.77	A barbed wire fence, 5 strand, bears S 73° E, and N 73° W.
11.33	Center line of Arizona State Highway No. 264, 30 ft. wide, asphalt surfaced, bears S 73° E and N 73° W.
12.93	Telephone line, bears S 66° E, and N 66° W.
14.98	Barbed wire fence, 5 strand, bears S 66° E and N 66° W.
40.33	Point for the ½ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T27N R29E 1/4 S32 S5
	T26N 1984
	from which

CHAINS	
	A ponderosa pine, 18 ins. diam., bears S 28½° W, 1.79 chs. dist., mkd. ½ S5 BT.
	A ponderosa pine, 18 ins. diam., bears N 17½° W, 2.19 chs. dist., mkd. ½ S32 BT.
,	Set a stainless steel fence post near the cor.
80.66	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T27N R29E S31 S32 S6 S5 T26N 1984
	from which
	A ponderosa pine, 21 ins. diam., bears N 21½° E, 1.61 chs. dist., mkd. T27N R29E S32 BT.
	A ponderosa pine, 25 ins. diam., bears S 77° E, 1.91 chs. dist., mkd. T26N R29E S5 BT.
	A ponderosa pine, 23 ins. diam., bears S 13½° W, 2.25 chs. dist., mkd. T26N R29E S6 BT.
	A pinyon, 16 ins. diam., bears N 48° W, 100 lks. dist., mkd. T27N R29E S31 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a stainless steel fence post near the cor.
	N 89°39' W, bet. secs. 6 and 31.
	Through rolling forest.

 Y	
CHAINS	
40.33	Point for the ½ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, encircled with a mound of stone, 3 ft. base to top with brass cap mkd.
·	T27N R29E ¹ / ₄ S31 S6 T26N 1984
	from which
	A ponderosa pine, 27 ins. diam., bears S 14½° E, 1.11 chs. dist., mkd. ½ S6 BT.
	A pinyon, 10 ins. diam., bears N 28° W, 1.62 chs. dist., mkd. ½ S31 BT.
	Set a stainless steel fence post near the cor.
79.91	The cor. of Tps. 26 and 27 N, Rs. 28 and 29 E.
	Dependent Resurvey, a Portion of the Subdivisional Lines T. 26 N., R. 29 E., Gila and Salt River Mer., Arizona
	(Restoring the survey executed by Frank Follman in 1883)
	From the cor. of secs. 35 and 36 only, on the S bdy. of the Tp.
	N 0°15' W, bet. secs. 35 and 36.
	Through rolling forest.
39.97	Point for the ½ sec. cor. of secs. 35, and 36 at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

T26N R29E

14
S35 | S36
1984

from which

A ponderosa pine, 16 ins. diam., bears N 24½° E, 2.08 chs. dist., mkd. ¼ S36 BT.

A ponderosa pine, 13 ins. diam., bears S 54½° W, 2.57 chs. dist., mkd. ½ S35 BT.

Set a stainless steel fence post near the cor.

79.94

The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, $18 \times 13 \times 6$ ins., firmly set 10 ins. in the ground, clearly mkd. with 1 groove on the E face and 1 groove on the S face.

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

T26N R29E S26 | S25 S35 | S36 1984

from which

A ponderosa pine, 20 ins. diam., bears N 38° E, 1.76 chs. dist., mkd. T26N R29E S25 BT.

A ponderosa pine, 19 ins. diam., bears S 51° E, 77 lks. dist., mkd. T26N R29E S36 BT.

An oak, 12 ins. diam., bears S 49½° W, 18 lks. dist., mkd. T26N R29E S35 BT.

CHAINS	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	•
	From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp.	
	S 88°59' W, bet. secs. 25 and 36.	
	Through rolling forest land.	
39.88	The ½ sec. cor. of secs. 25 and 36, monumented with a sandstone, 24 x 16 x 3 ins., firmly set 5 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, with no visible marks, from which the original bearing trees	
	A ponderosa pine stump, 29 ins. diam., bears S 45¾° W, 55 lks. dist., with no visible blaze or scribing. (Record: S 45° W, 53 lks. dist.)	
	A ponderosa pine stump, 27 ins. diam., bears N 52° W, 88 lks. dist., with scribe mark T visible. (Record: N 38° W, 87 lks. dist.)	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.	
	T26N R29E 1 ₄ S25 S36 1984	
	from which a new bearing tree and bearing object	
	A ponderosa pine, 24 ins. diam., bears N 26¼° E, 1.94 chs. dist., mkd. ¼ S25 BT.	
	A sandstone outcrop, 3 x 2 ft., even with the general surface, bears S 24½° W, 30 lks. dist., mkd. BXO	

48

CHAINS	Deposit the original stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	S 89°39' W, beginning new measurement.
	Through rolling forest.
40.12	The cor. of secs. 25, 26, 35 and 36.
	N 0°57' W, bet. secs. 25 and 25.
	Through rolling forest.
40.25	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a sandstone, 22 x 10 x 4 ins., firmly set 12 ins. in the ground, clearly mkd. $\frac{1}{4}$ on the W face, from which the original bearing tree
	A ponderosa pine stump, 20 ins. diam., bears S 76° W, 1.30 chs. dist., with illegible scribe marks on open blaze. (Record: S 65° W, 162 lks.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	S26 S25 1984
	from which new bearing trees
	A ponderosa pine, 20 ins. diam., bears S 49½° E, 77 lks. dist., mkd. ½ S25 BT.
	A ponderosa pine, 14 ins. diam., bears N 33½° W, 100 lks. dist., mkd. ½ S26 BT.
LL	

CHAINS	
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 0°10' E, beginning new measurement.
	Through rolling forest.
40.07	The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 18 x 12 x 4 ins. firmly set 3 ins. in the ground, clearly mkd. with 2 grooves on S face and 1 groove on E face, from which the original bearing trees
	A ponderosa pine, 27 ins. diam., bears N 28½° E, 20 lks. dist., with scribe marks visible R29E S24 BT on a partially healed blaze.
	A ponderosa pine, 29 ins. diam., bears N 77° W, 89 lks. dist., with a healed blaze.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E S23 S24 S26 S25 1984
	from which new bearing trees
	A ponderosa pine, 16 ins. diam., bears N 75° E, 1.31 chs. dist., mkd. T26N R29E S24 BT.
	A ponderosa pine, 9 ins. diam., bears S 55° E, 84 lks. dist., mkd. T26N R29E S25 BT.
	A ponderosa pine, 11 ins. diam., bears S 83¾° W, 95 lks. dist., mkd. T26N R29E S26 BT.

CHAINS	
	A ponderosa pine, 12 ins. diam., bears N 47¾° W, 95 lks. dist., mkd. T26N R29E S23 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of cor.
,	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 19, 24, 25 and 30 on the E bdy. of the Tp.
	S 89°07' W, bet. secs. 24 and 25.
	Through rolling forest.
39.05	The ½ sec. cor. of secs. 24 and 25, monumented with a sandstone, 18 x 12 x 6 ins., firmly set 5 ins. in the ground, clearly mkd. ½ on N face
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	½ S24
	S25 1984
	from which
	A ponderosa pine, 10 ins. diam., bears S 23¾° W, 62 lks. dist., mkd. ¼ S25 BT.
	A ponderosa pine, ll ins. diam., bears N 15° W, 60 lks. dist., mkd. ½ S24 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.

CHAINS	
CHAINS	S 89°57' W, beginning new measurement.
	Through rolling forest.
	intought totting totals.
11.50	Barbed wire fence, 2 strand, bears N 40° E, and S 40° W.
40.82	The cor. of secs. 23, 24, 25 and 26.
	N 0°17' W, bet. secs. 23 and 24.
	Through rolling forest.
40.07	The ½ sec. cor. of secs. 23 and 24, determined at record bearing and dist. from the remaining original bearing tree
	A root hole, bears S 26½° W, 40 lks. dist., alongside which a rotted ponderosa pine, 24 ins. diam., with scribe marks ½ SB visible on an open blaze.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 18 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.
	T26N R29E
	1/4 S23 S24 1984
	from which new bearing trees
	A ponderosa pine, 13 ins. diam., bears S 71° E, 1.06 chs. dist., mkd. ½ S24 BT.
	A ponderosa pine, 12 ins. diam., bears N 86¾° W, 92 lks. dist., mkd. ¼ S23 BT.
	Set a steel fence post near the cor.
	, · ·

Ι	
CHAINS	
	N 1°10' W, beginning new measurement.
	Through rolling forest.
40.43	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E S14 S13 S23 S24 1984
	from which
	A ponderosa pine, 13 ins. diam., bears N 82½° E, 74 lks. dist., mkd. T26N R29E S13 BT.
	A ponderosa pine, 14 ins. diam., bears S % E, 2.31 chs. dist., mkd. T26N R29E S24 BT.
	A ponderosa pine, 13 ins. diam., bears S 44° W, 64 lks. dist., mkd. T26N R29E S23 BT.
	A ponderosa pine, 10 ins. diam., bears N 71° W, 51 lks. dist., mkd. T26N R29E S14 BT.
	Set a steel fence post near the cor.
•	From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp.
	N 89°31' W, bet. secs. 13 and 24.
	Through rolling forest.
40.31	The 4 sec. cor. of secs. 13 and 24, determined at record bearing and dist. from the original bearing tree
	A pinyon, 15 ins. diam., bears S 10° E, 48 lks. dist., with scribe marks BT visible on partially open blaze.

CHAINS	
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	T26N R29E 1 ₄ S13 S24 1984
	from which new bearing trees
	An oak, 5 ins. diam., bears N 18½° E, 48 lks. dist., mkd. ½ S13 BT.
	A ponderosa pine, 14 ins. diam., bears S 26½° E, 92 lks. dist., mkd. ¼ S24 BT.
	Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.
	Set a steel fence post near the cor.
	S 88°42' W, beginning new measurement.
	Through rolling forest.
40.30	The cor. of secs. 13, 14, 23 and 24.
	N 0°31' W, bet. secs. 13 and 14.
	Through rolling forest.
40.42	The ½ sec. cor. of secs. 13 and 14, determined at record bearing and distance from the original bearing tree
	A ponderosa pine, 26 ins. diam., bears N 35° E, 22 lks. dist., mkd. 4 SBT on an open blaze.
	At the cor. point

Set a monument, 30 ins. long, composed of a stainless
steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a

magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.

ass cap mkd.

T26N R29E

14

S14 | S13

1984

from which new bearing trees

A ponderosa pine, 18 ins. diam., bears S 72° E, 1.26 chs. dist., mkd. ½ S13 BT.

A ponderosa pine, 10 ins. diam., bears N 54½° W, 61 lks. dist., mkd. ½ S14 BT.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

Set a steel fence post near the cor.

N 0°09' W, beginning new measurement.

Through rolling forest.

40.29

CHAINS

The cor. of secs. 11, 12, 13 and 14, monumented with a charred wooden post, $27 \times 3 \times 2$ ins. in the ground, with no visible marks alongside which a steel pipe, 2 ins. diam., 72 ins. long, 28 ins. in the ground, from which the remaining original bearing trees,

A ponderosa pine stump, 22 ins. diam., bears N 51¾° E, 37 lks. dist., with illegible scribing on an open blaze. (Record: N 30° E)

A ponderosa pine, 30 ins. diam., bears N 89¾° W, 75 lks. dist., with a healed blaze. (Record: N 22° W, 76 lks. dist.)

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

from which new bearing trees A ponderosa pine, 16 ins. diam., bears N 41½° E, 1.49 chs. dist., mkd. T20N R29E S12 ET. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 ET. A ponderosa pine, 10 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 ET. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 ET. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 ½ S13 1984			
from which new bearing trees A ponderosa pine, 16 ins. diam., bears N 41½° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53½° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13	CHAINS		
from which new bearing trees A ponderosa pine, 16 ins. diam., bears N 41½° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53½° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13		MOCN DOOR	
from which new bearing trees A ponderosa pine, 16 ins. diam., bears N 41½° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13			
from which new bearing trees A ponderosa pine, 16 ins. diam., bears N 41½° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13			
from which new bearing trees A ponderosa pine, 16 ins. diam., bears N 41½° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13			
A ponderosa pine, 16 ins. diam., bears N 41¼° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, ½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12/S13		1984	
A ponderosa pine, 16 ins. diam., bears N 41¼° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, ½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12/S13			
A ponderosa pine, 16 ins. diam., bears N 41¼° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, ½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12/S13			
A ponderosa pine, 16 ins. diam., bears N 41¼° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, ½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12/S13	•		
A ponderosa pine, 16 ins. diam., bears N 41¼° E, 1.49 chs. dist., mkd. T26N R29E S12 BT. A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, ½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12/S13		from which now hearing troop	
A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53½ W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13		Trong winds new bearing crees	
A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53½ W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13		3 1 1 1 1 1 1	
A ponderosa pine, 19 ins. diam., bears S 53½ E, 2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12 S13			
2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12 S13		1.49 chs. dist., mkd. T26N R29E S12 BT.	
2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12 S13			
2.51 chs. dist., mkd. T26N R29E S13 BT. A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ¼ S12 S13		A ponderosa pine, 19 ins. diam., bears S 53½ E,	
A ponderosa pine, 10 ins. diam., bears S 53% W, 1.18 chs. dist., mkd. T26N R29E S14 BT. Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13]		
Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13			
Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13		A nonderosa nine 10 ins diam hears S 53% W	
Deposit the wooden post and the steel pipe alongside the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13			
the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/4 S12 ½ S12/513		1.10 CIS. CISt., IIIKQ. 120N R29E 514 BT.	
the stainless steel post. Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/4 S12 ½ S12/513			
Set a stainless steel fence post near the cor. From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 ½ S12 ½ S13		Deposit the wooden post and the steel pipe alongside	
From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		the stainless steel post.	
From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		•	
From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		Set a stainless steel fence post near the cor.	
of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		The state of the s	
of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13			
of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13			
of the Tp. N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		From the cor of sees 12 and 12 only on the E bdy	
N 89°48' W, bet. secs. 12 and 13. Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12 S13			
Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		or the ip.	
Through rolling forest. 40.42 Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		37 00°401 77 1 1 1 30 3 10	
Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13		N 89 48° W, bet. secs. 12 and 13.	
Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E ½ S12/S13			
proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E 1/2 S13		Through rolling forest.	
proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E 1/2 S13			
proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E 1/2 S13	40.42	Point for the 4 sec. cor. of secs. 12 and 13, at	
of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E 1/4 S12/S13		· .	
Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E \[\frac{1}{2} \frac{\S12}{\S13} \]			
steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E \[\frac{1}{4} \frac{\text{S12}}{\text{S13}} \]		or o	
steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E \[\frac{1}{4} \frac{\text{S12}}{\text{S13}} \]		Set a moniment 30 inc long germand of a stairless	
magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd. T26N R29E 1/4 S12 S13			
with brass cap mkd. T26N R29E 1/4 S12 S13			
T26N R29E 1/4 S12 S13			
½ <u>S12</u> S13		with brass cap mkd.	
½ <u>S12</u> S13			
SI3		T26N R29E	
SI3		<u> 312</u>	
1984		⁴ S13	
1904		1994	
		1903	

	CHAINS	from which
		A ponderosa pine, 15 ins. diam., bears S 36° E, 2.10 chs. dist., mkd. 4 S13 BT.
		A ponderosa pine, 9 ins. diam., bears N 67° W, 1.05 chs. dist., mkd. ½ S12 BT.
		Set a stainless steel fence post near the cor.
	80.84	The cor. of secs. 11, 12, 13 and 14.
		N 0°43' W, bet. secs. 11 and 12.
		Through rolling forest.
	39.99	The ½ sec. cor. of secs. 11 and 12, determined at record bearing and dist. from the original bearing tree
		A rotted oak stump, 14 ins. diam., bears N 10° W, 27 lks. dist., mkd. ½ S BT on an opened blaze.
		At the cor. point
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 15 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.
		T26N R29E
		S11 S12 1984
	•	from which new bearing trees
		A ponderosa pine, 12 ins. diam., bears N 77¾° E, 38 lks. dist., mkd. ¼ S12 BT.
		A ponderosa pine, 12 ins. diam., bears S 89¾° W, 41 lks. dist., mkd. ¼ S11 BT.
		Set a stainless steel fence post near the cor.
ᆚ		

CHAINS	N 0°28' E, beginning new measurement.
	Through rolling forest.
16.60	A graded road, 25 ft. wide, bears N 25° E and S 25° W.
40.38	The sec. cor. of secs. 1, 2, 11 and 12, determined at record bearing and dist. from the remaining original bearing tree
	A rotten oak, 24 ins. diam., bears S 30° E, 23 lks. dist., with scribe marks visible T26N 11 S12 BT on an open blaze
	At the cor. point
·	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E S2 S1 S11 S12 1984
	from which new accessories
	An Arizona State Highway right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, an angle iron, projecting 26 ins. above ground, bears N 30°26' E, 9.63 chs. dist., mkd. P.T. 514+00.8 BK = 514+13.8 AHD.
	An Arizona State Highway right-of-way monument, marking the S right-of-way of Arizona Highway No. 264, an angle iron, projecting 26 ins. above ground, bears N 37°38' E, 5.20 chs. dist., mkd. P.T. 514+00.8 BK = 514+13.8 AHD.
	A ponderosa pine, 14 ins. diam., bears N 56¾° E, 82 lks. dist., mkd. T26N R29E S1 BT.
	A ponderosa pine, 17 ins. diam., bears S 70½° E, 69 lks. dist., mkd. T26N R29E S12 BT.
	A ponderosa pine, 16 ins. diam., bears S 30½° W, 1.25 chs. dist., mkd. T26N R29E S11 BT.
	a.

CHAINS	
	A ponderosa pine, 19 ins. diam., bears N 37½° W,
	2.02 chs. dist., mkd. T26N R29E S2 BT.

A steel tower with a parabolic antenna, bears S 13°35' W, 20.12 chs. dist.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

Set a stainless steel fence post near the cor.

From this point a rebar, 5/8 in. diam. flush with ground, bears S 37°04' W, 8.6 lks. dist., with metal tag mkd. N-W COR SEC 12 A.D.O.T 8-76. Remove this rebar at request of Arizona Division of Transportation.

From the cor. of secs. 1 and 12 only, on the E bdy. of the Tp.

N 89°58' W, bet. secs. 1 and 12.

Through rolling forest.

40.54

CHAINS

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12 at proportionate dist.; there is no evidence of the original cor.

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2^{\frac{1}{2}}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

T26N R29E 14 S1 S12 1984

from which

- A ponderosa pine, 13 ins. diam., bears S 8° W, 70 lks. dist., mkd. ½ S12 BT.
- A ponderosa pine, 11 ins. diam., bears N 13¾° W, 1.02 chs. dist., mkd. ¼ S1 BT.

CHAINS	An Arizona Highway right-of-way monument, marking the S right-of-way of Arizona Highway No. 264, an angle iron, projecting 28 ins. above ground, bears N 89°13' W, 15.61 chs. dist., mkd. P.O.T. 499+87.25.
	Set a stainless steel fence post near the cor.
49.40	Center line, Arizona State Highway No. 264, 30 ft. wide, asphalt surfaced, bears S 74° E and N 74° W.
55.00	Barbed wire fence, 4 strand, bears S 70° E and N 70° W.
73.30	Graded road, 25 ft. wide, bears N and S.
81.08	The cor. of secs. 1, 2, 11 and 12.
	N 0°09' W, bet. secs. 1 and 2.
	Through rolling forest.
6.37	Barbed wire fence, 5 strand, bears S 74° E and N 74° W.
7.90	Center line, Arizona State Highway No. 264, 30 ft. wide, asphalt surfaced, bears S 77° E and N 77° W.
9.48	Barbed wire fence, 5 strand, bears S 77° E and N 77° W.
40.22	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
•	T26N R29E
	S2 S1 1984
	from which
	A ponderosa pine, 20 ins. diam., bears N 55½° E, 1.75 chs. dist., mkd. ½ S1 BT.

CHAINS	
	A ponderosa pine, 13 ins. diam., bears S 55½° W, 69 lks. dist., mkd. ½ S2 BT.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.
	Dig pits, on line N and S, 3 ft. dist.
80.57	The cor. of secs. 1, 2, 35 and 36, on the N bdy. of the Tp.
	From the cor. of secs. 34 and 35, only, on the S bdy. of the Tp.
	N 0°42' W, bet. secs. 34 and 35.
	Through rolling forest.
40.30	Point for the ½ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	S34 S35 1984
	from which
	A pinyon, 10 ins. diam., bears N 84° E, 82 lks. dist., mkd. ½ S35 BT.
	An oak, 9 ins. diam., bears S $48\frac{1}{2}^{\circ}$ W, 41 lks. dist., mkd. $\frac{1}{4}$ S34 BT.
	The center shaft of a windmill, bears N 22°05' E, 3.63 chs. dist.
	Set a stainless steel fence post near the cor.
47.10	Graded road, 15 ft. wide, bears N 30° E and S 30° W.

80.60

The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, $24 \times 14 \times 3$ ins. firmly set 10 ins. in the ground, clearly mkd. with 2 grooves on the E face and 1 groove on the S face, from which the original bearing trees

- A ponderosa pine, 36 ins. diam., bears N 54½° E, 1.24 chs. dist., with a well healed blaze. (Record: N 54° E, 123 lks. dist.)
- A ponderosa pine stump, 16 ins. diam., bears S 17½° W, 1.54 chs. dist., flush with ground. (Record: S 17½° W, 139 lks. dist.)
- A ponderosa pine, 36 ins. diam., bears N 46¾° W, 29 lks. dist., with illegible scribe marks on a partially healed blaze. (Record: N 45¼ W, 25 lks. dist.)

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

T26N R29E S27 | S26 S34 | S35 1984

from which a new bearing tree

A ponderosa pine, 18 ins. diam., bears S 21½° W, 1.84 chs. dist., mkd. T26N R29E S34 BT.

Deposit the mkd. stone alongside the stainless steel post.

Set a stainless steel fence post near the cor.

From the cor. of secs. 25, 26, 35 and 36.

N 89°19' W, bet. secs. 26 and 35.

Through nearly level forest.

 · · · · · · · · · · · · · · · · · · ·	
CHAINS	
40.60	The ½ sec. cor. of secs. 26 and 35, determined at record bearing and dist. from the remaining original bearing tree
,	An oak, 18 ins. diam., bears S 5½° W, 98 lks. dist., clearly mkd. ½ BT on an opened blaze.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E 1 S26 335 1984
	from which new bearing trees
	A ponderosa pine, 14 ins. diam., bears N 63½° E, 40 lks. dist., mkd. ½ S26 BT.
	A ponderosa pine, 19 ins. diam., bears S 13° W, 1.28 chs. dist., mkd. ½ S35 BT.
	Set a stainless steel fence post near the cor.
	S 89°55' W, beginning new measurement.
	Through nearly level forest.
21.00	Graded road, 15 ft. wide, bears northeasterly and southwesterly. (Scaled)
40.08	The cor. of secs. 26, 27, 34 and 35.
	N 0°09' E, bet. secs. 26 and 27.
	Through rolling forest.
40.09	The ½ sec. cor. of secs. 26 and 27, monumented with an oak, 19 ins. diam, with an open blaze on the W face, from which the remaining original bearing tree

CHAINS

A ponderosa pine stump, 23 ins. diam., bears N 74° E, 1.22 chs. dist., with no scribing visible. (Record: N 75° E, 121 lks. dist.)

from which new bearing trees and a reference monument

An oak, 8 ins. diam., bears S $10\frac{1}{2}^{\circ}$ E, 1.01 chs. dist., mkd. $\frac{1}{4}$ S26 BT.

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, for a reference monument, bears N 45°09' W, 25 lks. dist., with brass cap mkd. RM T26N R29E $\frac{1}{4}$ S27 16.5 FT. 1984 and an arrow pointing to the cor.

A ponderosa pine, 7 ins. diam., bears N 13½° W, 2.53 chs. dist., mkd. ½ S27 BT.

N 0°09' E, beginning new measurement.

39.93

The cor. of secs. 22, 23, 26 and 27, determined at record bearing and dist. from the remaining original bearing tree

A ponderosa pine, 21 ins. diam., bears S 85½°E, 83 lks. dist., with scribe marks NRXXIXESXXVI visible on an opened blaze.

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.

T26N R29E S22 | S23 S27 | S26 1984

from which new bearing trees

A ponderosa pine, 20 ins. diam., bears N 27½° E, 2.89 chs. dist., mkd. T26N R29E S23 BT.

_			
	CHAINS		
		A ponderosa pine, 15 ins. diam., bears S 59½° W, 43 lks. dist., mkd. T26N R29E S27 BT.	
		An oak, 6 ins. diam., bears N 74½° W, 79 lks. dist., mkd. T26N R29E S22 BT.	•
	•	Set a stainless steel fence post near the cor.	
		From the cor. of secs. 23, 24, 25 and 26.	
		N 89°54' W, bet. secs. 23 and 26.	
		Through rolling forest.	l
	18.40	Graded road, 20 ft. wide, bears N 14° E and S 14° W.	1
	40.03	The ½ sec. cor. of secs. 23 and 26, monumented with a sandstone, 19 x 11 x 4 ins. firmly set 10 ins. in the ground, in a mound of stone 1 ft. base, 6 ins. high, clearly mkd. ½ on N face, from which the original bearing tree	
		A ponderosa pine, 36 ins. diam., bears S 27¾° E, 16 lks. dist., with a well healed blaze. (Record: S 20° E, 15 lks. dist.)	
		At the cor. point	
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 15 ins. in the ground, in a supporting mound of stone, 5 ft. base to top, with brass cap mkd.	
		T26N R29E ¹ / ₄ S23 S26 1984	
		from which a new bearing tree and bearing object	
		A sandstone boulder, 10 x 6 x 3 ft. above ground, bears S 68°51' W, 22.1 lks. dist., mkd. BXO.	
		A ponderosa pine, 16 ins. diam., bears N 26° W, 92 lks. dist., mkd. ½ S23 BT.	
1			

CHAINS	
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
,	N 89°52' W, beginning new measurement.
	Through rolling forest.
39.86	The cor. of secs. 22, 23, 26 and 27.
	N 1°06' W, bet. secs. 22 and 23.
	Through rolling forest.
40.91	Point for the ½ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	T26N R29E
	\$22 \$23 1984
	from which
	An oak, 7 ins. diam., bears N 4° E, 93 lks. dist., mkd. 4 S23 BT.
	Set a stainless steel fence post near the cor.
81.82	The cor. of secs. 14, 15, 22 and 23, monumented with a mound of stone, 4 ft. base, 1 ft. high, from which the remaining original bearing tree
	A root hole, bears S 15% E, 11 lks. dist., alongside of which is lying a decayed ponderosa pine, 36 ins. diam., with no visible scribe marks on an open blaze. (Record: S 16° E, 12 lks. dist.)

CHAINS	
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	T26N R29E S15 S14 S22 S23 1984
	from which new bearing trees
	A ponderosa pine, 16 ins. diam., bears S 38½° E, 2.98 chs. dist., mkd. T26N R29E S23 BT.
	A ponderosa pine, 13 ins. diam., bears S 46½° W, 1.71 chs. dist., mkd. T26N R29E S22 BT.
	A ponderosa pine, 11 ins. diam., bears N 40° W, 1.73 chs. dist., mkd. T26N R29E S15 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 13, 14, 23 and 24.
	N 88°01' W, bet. secs. 14 and 23.
	Through rolling forest.
17.10	Graded road, 20 ft. wide, bears N 10° W and S 10° E.
40.13	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a sandstone, 12 x 12 x 3 ins. firmly set 10 ins. in the ground, and in a mound of stone, 4 ft. base, 1 ft. high, clearly mkd. $\frac{1}{4}$ on N face,
	At the cor. point

CHAINS	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	T26N R29E ¹ / ₄ S14 S23 1984
	from which new bearing trees
	A ponderosa pine, 16 ins. diam., bears N 26½° E, 1.80 chs. dist., mkd. ¼ S14 BT.
	A ponderosa pine, 15 ins. diam., bears S 16° E, 2.25 chs. dist., mkd. ½ S23 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Set a stainless steel fence post near the cor.
	N 89°57' W, beginning new measurement.
	Through rolling forest.
40.36	The cor. of secs. 14, 15, 22 and 23.
	N 1°19' W, bet. secs. 14 and 15.
	Through rolling forest.
39.99	The ½ sec. cor. of secs. 14 and 15, monumented with a sandstone, 18 x 8 x 4 ins. covered with red and green paint, firmly set 11 ins. in ground, and in a mound of stone 3 ft. base, 1 ft. high, with no visible marks. This point is accepted as the best available evidence of the original cor. position.
	At the cor. point

CHAINS	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
,	T26N R29E
	1 ₄ S15 S14 1984
,	from which new bearing trees
	A ponderosa pine, 10 ins. diam., bears N 33¾° E, 1.03 chs. dist., mkd. ¼ S14 BT.
	A ponderosa pine, 12 ins. diam., bears N 53° W, 1.90 chs. dist., mkd. ½ S15 BT.
	Deposit the painted stone alongside the stainless steel post.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	Set a stainless steel fence post near the cor.
	N 0°07' E, beginning new measurement.
	Through rolling forest.
34.99	The original closing cor. of secs. 14 and 15, established by John G. Evans in 1885 at the intersection with the abandoned S bdy. of the Navajo Indian Reservation, monumented with a sandstone, 8 x 2½ ins., firmly set, projecting 8 ins. above ground, clearly mkd. with 2 grooves on the E face, 4 grooves and IACC on the S face.
40.06	The cor.of secs. 10, 11, 14 and 15, monumented with a sandstone, 20 x 13 x 3 ins., firmly set 12 ins. in the ground, clearly mkd. with 4 grooves on the S face and 2 grooves on the E face, from which the remaining original bearing tree
·	

CHAINS		
	A ponderosa pine, 26 ins. diam., bears N 63½° W, 1.35 chs. dist., with scribe marks NR29E 10 BT visible on a partially healed blaze. (Record: N 70° W, 52 lks. dist.)	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.	
	T26N R29E <u>S10 S11</u> <u>S15 S14</u> 1984	
	from which new bearing trees	
	A ponderosa pine, 17 ins. diam., bears N 70° E, 1.51 chs. dist., mkd. T26N R29E S11 BT.	
	A ponderosa pine, 17 ins. diam., bears S 50¾° E, 62 lks. dist., mkd. T26N R29E S14 BT.	
	A ponderosa pine, 13 ins. diam., bears S 34¾° W, 54 lks. dist., mkd. T26N R29E S15 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	From the cor. of secs. 11, 12, 13 and 14.	
	N 89°27' W, bet. secs. 11 and 14.	
	Through rolling forest.	
33.60	Graded road, 25 ft. wide, bears N and S.	
40.39	Point for the 4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.	

 	20 N., R. 27 E., GIIA and Bail River Mer., Arizona
CHAINS	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N T29E 1/4 S11 S14 1984
	from which
	A ponderosa pine, 17 ins. diam., bears S 64½° E, 1.61 chs. dist., mkd. ½ S14 BT.
	A ponderosa pine, 15 ins. diam., bears N 11¾° W, 95 lks. dist., mkd. ¼ S11 BT.
	Deposit the shattered glass of a 12 oz. beer bottle beneath the stainless steel post.
	Set a stainless steel fence post near the cor.
80.78	The cor. of secs. 10, 11, 14 and 15.
	N 0°40' E, bet. secs. 10 and 11.
	Through rolling forest.
40.24	Point for the ½ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	S10 S11 1984
	from which

Dependent	Resurvey,	a Portion of the Subdivisional Lines
T. 26 N.	, R. 29 E.	., Gila and Salt River Mer., Arizona

26 N., R. 29 E., Gila and Salt River Mer., Arizona
A ponderosa pine, 22 ins. diam., bears S 87° W, 2.72 chs. dist., mkd. ½ S10 BT.
Set a stainless steel fence post near the cor.
Point for the ½ sec. cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
T26N R29E S3 S2 S10 S11 1984
from which
A ponderosa pine, 19 ins. diam., bears N 16½°E, 1.67 chs. dist., mkd. T26N R29E S2 BT.
A ponderosa pine, 24 ins. diam., bears S 30° E, 94 lks. dist., mkd. T26N R29E S11 BT.
A ponderosa pine, 21 ins. diam., bears S 55° W, 64 lks. dist., mkd. T26N R29E S10 BT.
A ponderosa pine, 15 ins. diam., bears N 49° W, 1.35 chs. dist., mkd. T26N R29E S3 BT.
Set a stainless steel fence post near the cor.
From the cor. of secs. 1, 2, 11 and 12.
N 89°23' W, bet. secs. 2 and 11.
Through rolling forest.
Point for the \(\frac{1}{4} \) sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS	Set a standard brass tablet, 3 ins. stem, cemented in a drill hole in sandstone bedrock, 5 ins. below the surface with magnetized top mkd.	
	T26N R29E 1/4 S2 S11 1984	•
	from which	
	A ponderosa pine, 21 ins. diam., bears N 14° E, 72 lks. dist., mkd. ½ S2 BT.	
	A ponderosa pine, 14 ins. diam., bears S 11½° E, 1.84 chs. dist., mkd. ½ S11 BT.	
	Cor. falls in the N edge of a trail road, bears E and W.	
79.65	The cor. of secs. 2, 3, 11 and 12.	
•	N 0°21' W, bet. secs. 2 and 3. Through rolling forest.	
25.35	Barbed wire fence, 5 strand, bears S 76° E and N 76° W.	
26.90	Center line, Arizona State Highway No. 264, asphalt surfaced, 30 ft. wide, bears S 76° E and N 76° W.	
28.48	Barbed wire fence, 5 strand, bears S 76° E and N 76° W.	
39.13	Electric fence, 4 strand, bears S 80° E and N 80° W.	
40.24	Point for the ½ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	T26N R29E	
	s3 s2 1984	-

	CHAINS	from which
	•	A ponderosa pine, 21 ins. diam., bears N 29½° E, 73 lks. dist., mkd. ½ S2 BT.
		An Arizona State Highway right-of-way monument, marking the S right-of-way of Arizona Highway No. 264, monumented with an angle iron, firmly set, projecting 24 ins. above ground, alongside of which a concrete cylinder, 6 ins. diam., flush with the ground, bears S 27°47' W, 14.85 chs. dist., mkd. P.O.T. 576+00.
	·	An Arizona State Highway right-of-way monument, marking the N right-of-way of Arizona Highway No. 264, monumented with an angle iron, firmly set, projecting 24 ins. above ground, alongside of which a concrete cylinder, 6 ins. diam., flush with the ground, bears S 31°14′ W, 11.94 chs. dist., with illegible marks.
		A ponderosa pine, 22 ins. diam., bears S 43½° W, 1.98 chs. dist., mkd. ½ S3 BT.
		Set a stainless steel fence post near the cor.
	80.70	The cor. of secs. 2, 3, 34 and 35, on the N bdy. of the Tp.
		From the cor. of secs. 33 and 34 only, on the S bdy. of the Tp.
		N 0°09' W, bet. secs. 33 and 34.
		Through rolling forest.
	40.17	Point for the ½ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
		:
_		

CHAINS						
	T26N R29E					
,	s33 s34 1984					
	from which					
	A ponderosa pine, 13 ins. diam., bears N 69¾° E, 1.43 chs. dist., mkd. ¼ S34 BT.					
	A ponderosa pine, 10 ins. diam., bears S 53¾° W, 1.59 chs. dist., mkd. ¼ S33 BT.					
	Set a stainless steel fence post near the cor.					
80.34	The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 26 x 10 x 3 ins., firmly set 8 ins. in the ground, clearly mkd. with 3 grooves on the E face and 1 groove on the S face					
	At the cor. point					
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.					
	T26N R29E <u>S28 S27</u> <u>S33 S34</u> 1984					
	from which					
	An oak, 11 ins. diam., bears N 67° E, 1.68 chs. dist., mkd. T26N R29E S27 BT.					
	A ponderosa pine, 15 ins. diam., bears S 58° E, 3.09 chs. dist., mkd. T26N R29E S34 BT.					
	A ponderosa pine, 17 ins. diam., bears S $84\frac{1}{2}^{\circ}$ W, 3.10 chs. dist., mkd. T26N R29E S33 BT.					
	An oak, 10 ins. diam., bears N 45° W, 46 lks. dist., mkd. T26N R29E S28 BT.					
	Deposit the mkd. stone alongside the stainless steel post.					

	20 N., R. 29 E., Gila and Sait River Mer., Arizona
CHAINS	
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 26, 27, 34 and 35.
,	N 89°50' W, bet. secs. 27 and 34.
	Through rolling forest.
39.97	The ½ sec. cor. of secs. 27 and 34, monumented with a sandstone, 20 x 11 x 2 ins., firmly set in the ground, clearly mkd. ½ on W face, from which the original bearing tree
	A ponderosa pine, 30 ins. diam., bears N 51½° E, 1.38 chs. dist., with well healed blaze. (Record: N 30½° E, 137 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	1 S27 4 S24
	\$34 1984
	from which new bearing trees
	An oak, 6 ins. diam., bears N 3½° E, 1.17 chs. dist., mkd. ½ S27 BT.
	A ponderosa pine, 14 ins. diam., bears S 15½° E, 2.15 chs. dist., mkd. ½ S34 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	S 89°24' W, beginning new measurement.

	Through rolling forest.
39.40	The cor. of secs. 27, 28, 33 and 34.
	N 0°09' W, bet. secs. 27 and 28.
	Through rolling forest.
40.17	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a sandstone, 21 x 10 x 7 ins. firmly set 12 ins. in the ground, clearly mkd. $\frac{1}{4}$ on W face, from which the original bearing tree,
	A ponderosa pine, 24 ins. diam., bears S 13° W, 25 lks. dist., with healed blaze. (Record: S 20½° W.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	S28 S27 1984
	from which new bearing trees
	A ponderosa pine, 11 ins. diam., bears S 73° E, 3.23 chs. dist., mkd. ½ S27 BT.
	An oak, 6 ins. diam., bears N 86½° W, 1.31 chs. dist., mkd. ½ S28 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 0°33' W, beginning new measurement.

CHAINS	
	Through rolling forest.
40.52	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E S21 S22 S28 S27 1984
	from which
	A ponderosa pine, 27 ins. diam., bears N 53½° E, 1.20 chs. dist., mkd. T26N R29E S22 BT.
	A ponderosa pine, 7 ins. diam., bears S 53° W, 1.29 chs. dist., mkd. T26N R29E S28 BT.
	A ponderosa pine, 11 ins. diam., bears N 42¾° W, 78 lks. dist., mkd. T26N R29E S21 BT.
	Cor. falls on the N edge of a trail road, bears NW and SE.
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 22, 23, 26 and 27.
	West, bet. secs. 22 and 27.
	Through rolling forest.
40.00	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a sandstone, 17 x 12 x 6 ins., firmly set 12 ins. in the ground, clearly mkd. $\frac{1}{4}$ on N face,

CHAINS		
	At the cor. point	
·	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	T26N R29E 1 ₄ S22 S27 1984	
	from which	
	A ponderosa pine, 9 ins. diam., bears N 1½° W, 20 lks. dist., mkd. ½ S22 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	N 89°32' W, beginning new measurement.	
	Through rolling forest.	
40.07	The cor. of secs. 21, 22, 27 and 28.	
	N 2°26' W, bet. secs. 21 and 22.	
	Through rolling forest.	
40.56	The ½ sec. cor. of secs. 21 and 22, monumented with a sandstone, 22 x 9 x 3 ins., loose on ground, clearly mkd. ½ on one face. This point is accepted as the best available evidence of the original cor. position.	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 6 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.	

CHAINS	T26N R29E
	S21 S22 1984
	from which
	A ponderosa pine, 19 ins. diam., bears N 22½° E, 2.17 chs. dist., mkd. ½ S22 BT.
	A ponderosa pine, 12 ins. diam., bears S 70° W, 3.85 chs. dist., mkd. ½ S21 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 0°26' W, beginning new measurement.
	Through rolling forest.
41.22	The cor. of secs. 15, 16, 21 and 22, monumented with a sandstone, 21 x 8 x 2 ins., firmly set 9 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, clearly mkd. with 3 grooves on the S and E face, from which the remaining original bearing tree
	A ponderosa pine, 26 ins. diam., bears N 4° E, 64 lks. dist., mkd. T26N R29E S15 BT. on an open blaze. (Record: N 5½° E, 63 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 12 ins. in the ground, in a supporting mound of stone, 3 ft. base to top, with brass cap mkd.
	T26N R29E <u>S16 S15</u> <u>S21 S22</u> 1984

CHAINS	from which new bearing trees
	A ponderosa pine, 14 ins. diam., bears N 78° E, 1.73 chs. dist., mkd. T26N R29E S15 BT.
	A ponderosa pine, 12 ins. diam., bears S 42½° E, 1.66 chs. dist., mkd. T26N R29E S22 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 14, 15, 22 and 23.
	S 87°21' W, bet. secs. 15 and 22.
	Through rolling forest.
38.54	The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented with the remains of the original monument, a sandstone fragment, $6 \times 3 \times 1$ ins., loosely set in a mound of stone, 3 ft. base, 1 ft. high, clearly mkd. $\frac{1}{4}$ on N face, from which the remaining original bearing tree
	A ponderosa pine stump, 32 ins. diam., bears S 61½° W, 1.32 chs. dist., with no scribing visible. (Record: S 63° W, 122 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E 1/4 S15 S22 1984
	from which new bearing trees
	A ponderosa pine, 15 ins. diam., bears N 42½° E, 1.01 chs. dist., mkd. ½ S15 BT.
	A ponderosa pine, 17 ins. diam., bears S 6½° W, 1.18 chs. dist., mkd. ½ S22 BT.
	1

-	T	
	CHAINS	Deposit the mkd. stone alongside the stainless steel post.
		Set a stainless steel fence post near the cor.
	,	N 87°14' W, beginning new measurement.
		Through rolling forest.
	42.07	The cor. of secs. 15, 16, 21 and 22.
		N 0°12' E, bet. secs. 15 and 16.
		Through rolling forest.
	40.19	Point for the sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 5 ins. in the ground, and in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.
		T26N R29E
		S16 S15 1984
		from which
		A ponderosa pine, 17 ins. diam., bears N 464° E, 62 lks. dist., mkd. ½ S15 BT.
		An oak, 3 ins. diam., bears S 76° W, 1.19 chs. dist., mkd. ½ S16 BT.
	80.38	The cor. of secs. 9, 10, 15 and 16, in the general vicinity of which, a sandstone, 18 x 7 x 4 ins., laying loose on the ground, mkd. with 4 grooves on one face and 3 grooves on an adjacent face, determined at record bearing and distance from the remaining original bearing tree
	·	

CHAINS				
CHAINS	i			

visible on open blaze.

A ponderosa pine, dead, 25 ins. diam., broken off 3 ft. above ground, bears N 44½° E, 65 lks. dist., with scribe marks T26N R2 S10 BT

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 21 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.

T26N R29E <u>\$9 | \$10</u> <u>\$16 | \$15</u> 1984

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears S 42¾° E, 79 lks. dist., mkd. T26N R29E S15 BT.

A ponderosa pine, 22 ins. diam., bears S 8½° W, 1.34 chs. dist., mkd. T26N R29E S16 BT.

A ponderosa pine, 22 ins. diam., bears N 49¾° W, 1.22 chs. dist., mkd. T26N R29E S9 BT.

Cor. falls in a wash, 4 ft. deep, 5 lks. wide, drains northwesterly.

Deposit the remains of the mkd. stone alongside the stainless steel post.

Set a stainless steel fence post near the cor.

From the cor. of secs. 10, 11, 14 and 15.

N 89°34' W, bet. secs. 10 and 15.

Through rolling forest.

39.68 Point for

Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 18 ins. in the ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.
	T26N R29E 1/4 S10 S15 1984
	from which
	A ponderosa pine, 23 ins. diam., bears S 40° E, 98 lks. dist., mkd. 4 S15 BT.
	A ponderosa pine, 22 ins. diam., bears N 58¾° W, 70 lks. dist., mkd. ¼ S10 BT.
	Set a stainless steel fence post near the cor.
79.36	The cor. of secs. 9, 10, 15 and 16.
	N 0°12' E, bet. secs. 9 and 10.
	Through rolling forest.
40.12	Point for the ½ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	S9 S10 1984
	from which
İ	A ponderosa pine, 13 ins. diam., bears N 48½° E, 2.71 chs. dist., mkd. ½ S10 BT.

CHAINS	A ponderosa pine, 23 ins. diam., bears S 21° W, 1.26 chs. dist., mkd. ½ S9 BT.
	Set a stainless steel fence post near the cor.
80.24	The cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 24 x 8 x 6 ins. loosely set 3 ins. in the ground, in a mound of stone, 3 ft. base, 6 ins. high, clearly mkd. with 5 grooves on the S face and 3 grooves on the E face, from which the original bearing trees
	A ponderosa pine, dead, 20 ins. diam., bears N 70%° E, 67 lks. dist., with an open, rotted, blaze. (Record: N 50° E.)
	A root hole, bears N 41½° W, 65 lks. dist., alongside of which is lying a decayed ponderosa pine, 28 ins. diam., mkd. T26N R29E S4 BT on an open blaze. (Record: N 25° W, 66 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E <u>S4 S3</u> <u>S9 S1</u> 0 1984
	from which new bearing trees
	A ponderosa pine, 15 ins. diam., bears N 68½° E, 55 lks. dist., mkd. T26N R29E S3 BT.
	A ponderosa pine, 14 ins. diam., bears S 14½° E, 2.08 chs. dist., mkd. T26N R29E S10 BT.
	A ponderosa pine, 18 ins. diam., bears S 58½° W, 2.29 chs. dist., mkd. T26N R29E S9 Bt.
	A ponderosa pine, 19 ins. diam., bears N 56½° W, 2.05 chs. dist., mkd. T26N R29E S4 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

	20 N., R. 29 E., Gila and Salt River Mer., Arizona	
CHAINS		
	Deposit the mkd. stone alongside the stainless steel post.	
,	Set a stainless steel fence post near the cor.	,
	From the cor. of secs. 2, 3, 10 and 11.	
	N 89°11' W, bet. secs. 3 and 10.	
	Through rolling forest.	
39.90	The ½ sec. cor. of secs. 3 and 10, monumented with a sandstone, 29 x 18 x 3 ins., firmly set 16 ins. in the ground, clearly mkd. ½ on S face.	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	T26N R29E	
	$\frac{1}{4} \frac{\text{S3}}{\text{S10}}$	
	1984	
	from which	
	A ponderosa pine, 16 ins. diam., bears N 65¼° E, 57 lks. dist., mkd. ¼ S3 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	S 89°43' W, beginning new measurement.	
	Through rolling forest.	
40.14	The cor. of secs. 3, 4, 9 and 10.	
	N 0°49' W, bet. secs. 3 and 4.	

CHAINS	Through rolling forest.	
40.23	Point for the 1/4 sec. cor. of secs. 3 and 4, falls in a pond, 3 chs. long, 1 ch. wide where it is impossible to establish a permanent monument.	
	From this point, the point selected for the witness cor. to the ½ sec. cor. of secs. 3 and 4, bears S 70°05' E, 73.1 lks. dist.	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2^{\frac{1}{2}}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	wc	
•	T26N R29E	
	S4 S3	
	1984	
	From this same point a highway right-of-way monument, marking the N right-of-way of Arizona State Highway No. 264, an angle iron, firmly set, projecting 24 ins. above ground, alongside of which, a concrete cylinder, 6 ins. diam., flush with the ground, bears N 22°49' E, 8.18 chs. dist., mkd. P.T. 624+42.41.	
	From this same point a highway right-of-way monument, marking the S right-of-way of Arizona State Highway No. 264, an angle iron, firmly set, projecting 24 ins. above ground, alongside of which, a concrete cylinder, 6 ins. diam., flush with the ground, bears N 24°51' E, 5.17 chs. dist., mkd. P.T. 624+42.41.	
	Set a stainless steel fence post near the cor.	
46.11	Barbed wire fence, 5 strand, bears S 60° E and N 60° W.	
46.66	Telephone line, single wooden poles, bears S 66° E and N 66° W.	
47.40	Center line, Arizona State Highway No. 264, asphalt surfaced, 30 ft. wide, bears S 68° E and N 68° W.	

CHAINS 49.03	Barbed wire fence, 5 strand, bears S 68° E and N 68° W.
80.34	The cor. of secs. 3, 4, 33 and 34, on the N bdy. of the Tp.
,	From the cor. of secs. 32 and 33 only, on the S bdy. of the Tp.
	N 7°00' W, bet. secs. 32 and 33.
	Through rolling forest.
40.42	The ½ sec. cor. of secs. 32 and 33, monumented with a sandstone, 24 x 8 x 5 ins., firmly set 4 ins. in ground, in a mound of stone 3 ft. base, 6 ins. high, dimly mkd. ½ on W face, from which the original bearing trees
	A ponderosa pine, 23 ins. diam., bears N 29½° E, 27 lks. dist., with well healed blaze. (Record: N 25½° E.)
	A ponderosa pine sawed stump, 24 ins. diam., bears S 73½° W, 1.12 chs. dist., mkd. ½ S BT on an open blaze. (Record: S 75° E, 113 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 22 ins. in the ground, encircled with a mound of stone, 3 ft. base to top, with brass cap mkd.
	T26N R29E
	S32 S33 1984
	from which new bearing trees
İ	A ponderosa pine, ll ins. diam., bears S 70¾° E, 1.06 chs. dist., mkd. ¼ S33 BT.
	A ponderosa pine, 14 ins. diam., bears N 15° W, 1.43 chs. dist., mkd. 4 S32 BT.

CHAINS	
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 0°01' W, beginning new measurement.
	Through rolling forest.
40.35	The cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 21 x 12 x 5 ins., firmly set 12 ins. in the ground, clearly mkd. with 1 groove on the S face and 4 grooves on the E face.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	S29 S28 S32 S33
	1984
	Deposit the mkd. stone alongside the stainless steel post.
	Cor. falls in an open meadow.
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 27, 28, 33 and 34.
	N 89°20' W, bet. secs. 28 and 33.
	Through rolling forest.
40.34	The ½ sec. cor. of secs. 28 and 33, monumented with a sandstone, 23 x 11 x 3 ins., firmly set 7 ins. in the ground, dimly mkd. ½ on S face.
	At the cor. point

	·		
	CHAINS		
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	
		T26N R29E 1 ₄ S28 533 1984	
		from which	
		A ponderosa pine, 20 ins. diam., bears S 50½° W, 1.33 chs. dist., mkd. ¼ S33 BT.	
		A ponderosa pine, 18 ins. diam., bears N 15¾° W, 2.07 chs. dist., mkd. ¼ S28 BT.	
		Deposit the mkd. stone alongside the stainless steel post.	
		Set a stainless steel fence post near the cor.	
		N 89°56' W, beginning new measurement.	
		Through rolling forest.	
	44.81	The cor. of secs. 28, 29, 32 and 33.	
		N 6°28' E, bet. secs. 28 and 29.	
		Through an open meadow.	
	41.04	The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with a sandstone, 20 x 14 x 3 ins., firmly set 9 ins. in the ground, mkd. $\frac{1}{4}$ on W face.	
		At the cor. point	
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	
_			

CHAINS	
	T26N R29E
	S29 S28
	1984
•	from which
	A pinyon, 15 ins. diam., bears N 80° E, 2.57 chs. dist., mkd. 4 S28 BT.
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	N 0°05' W, beginning new measurement.
	Through rolling forest.
40.98	The cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 21 x 12 x 4 ins., firmly set 11 ins. in the ground, clearly mkd. with 2 grooves on the S face and 4 grooves on the E face.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	S20 S21
	S29 S28 1984
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	Deposit the mkd. stone alongside the stainless steel post.

91

_			
	CHAINS		
		Set a stainless steel fence post near the cor.	
		Cor. falls in an open meadow.	,
	•	From the cor. of secs. 21, 22, 27 and 28.	
		S 89°33' W, bet. secs. 21 and 28.	
		Through rolling forest.	
	39.97	The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with a sandstone, 18 x 12 x 3 ins., firmly set 8 ins. in the ground, clearly mkd. $\frac{1}{4}$ on S face,	
		At the cor. point	
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.	
		T26N R29E 1/4 S21 S28 1984	
		from which	
		A ponderosa pine, 10 ins. diam., bears S 2½° E, 7 lks. dist., mkd. ½ S28 BT.	
		A ponderosa pine, 9 ins. diam., bears N 31° W, 50 lks. dist., mkd. ½ S21 BT.	
		Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.	
		Deposit the mkd. stone alongside the stainless steel post.	
		Set a stainless steel fence post near the cor.	
		N 87°16' W, beginning new measurement.	
		Through rolling forest.	
_			

CHAINS	
40.12	The cor. of secs. 20, 21, 28 and 29.
	N 1°28' W, bet. secs. 20 and 21.
•	Through rolling forest.
40.01	Point for the 4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E
	14 GDO 1 GD3
	S20 S21 1984
	from which
	A ponderosa pine, 19 ins. diam., bears S 68¼° W, 1.70 chs. dist., mkd. ½ S20 BT.
	Set a stainless steel fence post near the cor.
80.02	The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 21 x 9 x 4 ins., firmly set 5 ins. in the ground, clearly mkd. with 3 grooves on the S face, from which the original bearing trees
	A ponderosa pine, 28 ins. diam., bears N 21½° E, 41 lks. dist., with scribe marks T25N R29E BT. visible on an open blaze. (Record: N 17½° E, 40 lks. dist.)
	A ponderosa pine sawed stump, 30 ins. diam., bears S 45° E, 94 lks. dist., with no scribe marks visible. (Record: S 45½° E, 87 lks. dist.)
	A ponderosa pine sawed stump, 32 ins. diam., bears S 33° W, 30 lks. dist., with scribe marks BT visible on an open blaze. (Record: S 35° W, 27 lks. dist.)

_					_
-c	ப	Α	11	N١	S
٠.	п	\boldsymbol{H}		N	٠,

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

T26N R29E S17 | S16 S20 | S21 1984

from which new bearing trees

A ponderosa pine, 26 ins. diam., bears S 67¾° E, 2.42 chs. dist., mkd. T26N R29E S21 BT.

A ponderosa pine, 25 ins. diam., bears S 58° W, 1.20 chs. dist., mkd. T26N R29E S20 BT.

A ponderosa pine, 22 ins. diam., bears N 30½° W, 1.87 chs. dist., mkd. T26N R29E S17 BT.

Deposit the mkd. stone alongside the stainless steel post.

Set a stainless steel fence post near the cor.

From the cor. of secs. 15, 16, 21 and 22.

S 89°55' W, bet. secs. 16 and 21.

Through rolling forest.

40.02

Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.

CHAINS	
	T26N R29E
	$\frac{1}{4} \frac{\text{S16}}{\text{S21}}$
	1984
,	from which
	A ponderosa pine, 18 ins. diam., bears N 5¾° E, 1.42 chs. dist., mkd. ¼ S16 BT.
	A ponderosa pine, 22 ins. diam., bears S 6° W, 1.31 chs. dist., mkd. ½ S21 BT.
	Set a stainless steel fence post near the cor.
80.05	The cor. of secs. 16, 17, 20 and 21.
	N 0°07' W, bet. secs. 16 and 17.
	Through rolling forest.
40.17	The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with a sandstone, 22 x 15 x 4 ins., firmly set 5 ins. in ground, clearly mkd. $\frac{1}{4}$ on N face, from which the original bearing tree
	A burnt ponderosa pine stump, 25 ins. diam., bears N 10¾° W, 50 lks. dist., with no scribing visible. (Record: N 15° W, 47 lks. dist.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	24
	S17 S16 1984
	from which new bearing trees

CHAINS		
	A pinyon, 10 ins. diam., bears N 60¾° E, 1.12 chs. dist., mkd. ¼ S16 BT.	
	A ponderosa pine, 25 ins. diam., bears N 33½° W, 85 lks. dist., mkd. ¼ S17 BT.	•
•	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	N 0°34' W, beginning new measurement.	
	Through rolling forest.	
40.16	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	T26N R29E	
	<u>S8 S9</u> S17 S16	
	1984	
	from which	
	A ponderosa pine, 10 ins. diam., bears N 7½° E, 2.26 chs. dist., mkd. T26N R29E S9 BT.	
	A ponderosa pine, 13 ins. diam., bears S 39¾° E, 3.26 chs. dist., mkd. T26N R29E S16 BT.	
	A ponderosa pine, 8 ins. diam., bears S 36° W,	

1.63 chs. dist., mkd. T26N R29E S17 BT.

Set a stainless steel fence post near the cor.

СНА	From the cor. of secs. 9, 10, 15 and 16.
	S 89°53' W, bet. secs. 9 and 16.
	Through rolling forest.
40.	Point for the ½ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	from which
	A ponderosa pine, 10 ins. diam., bears N 41° E, 92 lks. dist., mkd. 4 S9 BT.
	A ponderosa pine, 25 ins. diam., bears S 24° E, 1.32 chs. dist., mkd. 4 S16 BT.
	Set a stainless steel fence post near the cor.
80.	82 The cor. of secs. 8, 9, 16 and 17.
	N 0°03' E, bet. secs. 8 and 9.
	Through rolling forest.
40.	Point for the ½ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.

CHAINS	
	T26N R29E
	\frac{1}{2} S8 S9
	1984
,	from which
	A ponderosa pine, 23 ins. diam., bears N 12½° E, 1.30 chs. dist., mkd. ½ S9 BT.
	A ponderosa pine, 18 ins. diam., bears N 29½° W, 1.80 chs. dist., mkd. ½ S8 BT.
	Set a stainless steel fence post near the cor.
80.32	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E S5 S4 S8 S9
	1984
	from which
	A ponderosa pine, 10 ins. diam., bears N $16\frac{3}{4}^{\circ}$ E, 1.32 chs. dist., mkd. T26N R29E S4 BT.
	A ponderosa pine, 22 ins. diam., bears S 19¾° E, 2.63 chs. dist., mkd. T26N R29E S9 BT.
	A pinyon, 15 ins. diam., bears S 534° W, 96 lks. dist., mkd. T26N R29E S8 BT.
	Set a stainless steel fence post near the cor.
	From the cor. of secs. 3, 4, 9 and 10.
	S 89°56' W, bet. secs. 4 and 9.

CHAINS	
	Through rolling forest.
40.51	Point for the 4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	12 S4 S4 S4 S4 S4 S4 S4 S4 S4 S4 S4 S4 S4
	S9
	1984
	from which
	A ponderosa pine, 26 ins. diam., bears N 61½° E, 2.78 chs. dist., mkd. ½ S4 BT.
	Dig pits in line E and W, 3 ft. dist.
	Set a stainless steel fence post near the cor.
81.03	The cor. of secs. 4, 5, 8 and 9.
	N 0°31' W, bet. secs. 4 and 5.
	Through rolling forest.
40.16	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd.
	T26N R29E
	S5 S4 1984
	$oxed{I}$

CHAINS	from which
	A ponderosa pine, 17 ins. diam., bears N 38½° E, 2.66 chs. dist., mkd. ¼ S4 BT.
	A ponderosa pine, 17 ins. diam., bears S 21% W, 1.72 chs. dist., mkd. 4 S5 BT.
	Set a stainless steel fence post near the cor.
75.08	Barbed wire fence, 5 strand, bears N 70° W and S 70° E.
75.85	Telephone line, wooden poles, bears N 70° W and S 70° E.
76.67	Center line, Arizona State Highway No. 264, bears N 70° W and S 70° E.
78.30	Barbed wire fence, 5 strand, bears N 70° W and S 70° E.
80.62	The cor. of secs. 4, 5, 32 and 33, on the N bdy. of the Tp.
	From the cor. of secs. 31 and 32 only, on the S bdy. of the Tp.
	N 4°09' W, bet. secs. 31 and 32.
	Through rolling forest.
40.44	The ½ sec. cor. of secs. 31 and 32, monumented with a sandstone, 24 x 8 x 11 ins., firmly set 10 ins. in the ground, encircled with a mound of stone, 4 ft. base, 1 ft. high, clearly mkd. ½ on the W face.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 15 ins. in the ground, supported by a mound of stone, 3 ft. base to top, with brass cap mkd.

CHAING		
CHAINS	T26N R29E	
	S31 S32 1984	
	from which	•
·	A pinyon, 11 ins. diam., bears S 86½° E, 88 lks. dist., mkd. ½ S32 BT.	
	A ponderosa pine, 14 ins. diam., bears N 42¾° W, 1.08 chs. dist., mkd. ¼ S31 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	N 0°05'.E, beginning new measurement.	
	Through rolling forest.	
37.60	Dry wash, 23 lks. wide, 7 ft. deep, drains N 60° W.	
40.22	The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 24 x 13 x 5 ins., firmly set 9 ins. in the ground, clearly mkd. with 1 groove on the S face and 5 grooves on the E face, from which the original bearing trees	
	A ponderosa pine, 33 ins. diam., bears N 13° E, 55 lks. dist., with healed blaze. (Record: N 21½° E.)	
	A ponderosa pine, 21 ins. diam., bears S 19¾° W, 1.50 chs. dist., with well healed blaze. (Record: S 20¼° W, 147 lks. dist.)	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.	
	T26N R29E S30 S29 S31 S32 1984	

CHAINS		
	from which new bearing trees	
	A ponderosa pine, 20 ins. diam., bears S 35½° E, 3.29 chs. dist., mkd. T26N R29E S32 BT.	•
,	A ponderosa pine, 23 ins. diam., bears N 52¾° W, 4.08 chs. dist., mkd. T26N R29E S30 Bt.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	From the cor. of secs. 28, 29, 32 and 33.	
	N 89°35' W, bet. secs. 29 and 32.	
	Through rolling forest.	
38.08	The ½ sec. cor. of secs. 29 and 32, monumented with a sandstone, 30 x 9 x 6 ins. firmly set 8 ins. in the ground, encircled with a mound of stone, 1 ft. base, 2 ft high, clearly mkd. ½ on the N face, from which the original bearing tree	
	A ponderosa pine, 22 ins. diam., bears S 48½° E, 70 lks. dist., mkd. ½ BT on an open blaze. (Record: S 45½° E, 68 lks. dist.)	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 15 ins. in the ground, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.	
	T26N R29E 14 S29 532	
	1984	
	from which new bearing trees	
	A ponderosa pine, 18 ins. diam., bears N ½° E, 1.64 chs. dist., mkd. ½ S29 BT.	

A ponderosa pine, 18 ins. diam., bears S 8° W, 62 lks. dist., mkd. ½ S32 BT. Deposit the mkd. stone alongside the stainless steel post. Set a stainless steel fence post near the cor. N 89°50' W, beginning new measurement. Through rolling forest. 40.24 The cor. of secs. 29, 30, 31 and 32. N 89°56' W, bet. secs. 30 and 31. Through rolling forest. 38.62 Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$30 × \$31 1984 from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ \$31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32. N 0°12' E, bet. secs. 29 and 30.	 	20 M. 7 M. 25 2.7 CHA GIR BUIL REVEL RELL, ALIZON
Deposit the mkd. stone alongside the stainless steel post. Set a stainless steel fence post near the cor. N 89°50' W, beginning new measurement. Through rolling forest. 40.24 The cor. of secs. 29, 30, 31 and 32. N 89°56' W, bet. secs. 30 and 31. Through rolling forest. 38.62 Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$30 ½ \$31 1984 from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 ET. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp.	CHAINS	
Set a stainless steel fence post near the cor. N 89°50' W, beginning new measurement. Through rolling forest. 40.24 The cor. of secs. 29, 30, 31 and 32. N 89°56' W, bet. secs. 30 and 31. Through rolling forest. Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T2GN R29E ½ \$30/831 1984 from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		
N 89°50' W, beginning new measurement. Through rolling forest. 40.24 The cor. of secs. 29, 30, 31 and 32. N 89°56' W, bet. secs. 30 and 31. Through rolling forest. 38.62 Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ 530 531 1984 from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 ET. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.	,	
Through rolling forest. 40.24 The cor. of secs. 29, 30, 31 and 32. N 89°56' W, bet. secs. 30 and 31. Through rolling forest. 38.62 Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$30 4 \$31 1984 from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ \$31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		Set a stainless steel fence post near the cor.
The cor. of secs. 29, 30, 31 and 32. N 89°56' W, bet. secs. 30 and 31. Through rolling forest. 38.62 Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$30 531 1984 from which A ponderosa pine, 21 ins. diam., bears \$ 7½° W, 1.10 chs. dist., mkd. ½ \$31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		N 89°50' W, beginning new measurement.
N 89°56' W, bet. secs. 30 and 31. Through rolling forest. Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$30 S31 1984 from which A ponderosa pine, 21 ins. diam., bears \$ 7½° W, 1.10 chs. dist., mkd. ½ \$31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		Through rolling forest.
Through rolling forest. Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$30 531 1984 from which A ponderosa pine, 21 ins. diam., bears \$ 7½ W, 1.10 chs. dist., mkd. ½ \$31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.	40.24	The cor. of secs. 29, 30, 31 and 32.
Point for the ½ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ S30 S31 1984 from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		N 89°56' W, bet. secs. 30 and 31.
proportionate dist.; there is no remaining evidence of the original cor. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E		Through rolling forest.
steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd. T26N R29E ½ \$\frac{530}{831}\$ 1984 from which A ponderosa pine, 21 ins. diam., bears \$ 7½ w, 1.10 chs. dist., mkd. ½ \$31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.	38.62	proportionate dist.; there is no remaining evidence
from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 BT. The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 5 ft. base to top,
from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 BT. The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		T26N R29E , S30
from which A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 BT. The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		S31
A ponderosa pine, 21 ins. diam., bears S 7½° W, 1.10 chs. dist., mkd. ½ S31 BT. The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		
1.10 chs. dist., mkd. 1/4 S31 BT. 76.89 The cor. of secs. 25, 30, 31 and 36, on the W bdy. of the Tp. From the cor. of secs. 29, 30, 31 and 32.		
From the cor. of secs. 29, 30, 31 and 32.		
	76.89	
N 0°12' E, bet. secs. 29 and 30.		From the cor. of secs. 29, 30, 31 and 32.
		N 0°12' E, bet. secs. 29 and 30.

	CHAINS		
		Through rolling forest.	
	40.46	The ½ sec. cor. of secs. 29 and 30, monumented with a pinyon, 12 ins. diam., with dim scribe marks ½ S on W face visible on open blaze.	
	•	from which	
		A pinyon, 8 ins. diam., bears S 73½° E, 28 lks. dist., mkd. ½ S29 BT.	
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, for a reference monument, bears S 44°56' W, 16.5 ft. dist., with brass cap mkd. RM T26N R29E $\frac{1}{4}$ S30 16.5 FT. 1984 and an arrow pointing to the cor.	
		N 1°21' E, beginning new measurement.	
		Through rolling forest.	
	40.30	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.	
		Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
		T26N_R29E	
		S19 S20 S30 S29 1984	
		Set a stainless steel fence post near the cor.	
		From the cor. of secs. 20, 21, 28 and 29.	
		S 88°43' W, bet. secs. 20 and 29.	
		Through rolling forest.	
- ·	ruary 1097) IICDI	DIAG	

CHAINS	
42.40	The ½ sec. cor. of secs. 20 and 29, determined at record bearing and dist. from the remaining original bearing tree
	A root hole, bears S 60° W, 72 lks. dist., alongside of which is lying a ponderosa pine, 22 ins. diam., with scribing marks 4 SBT, on an open blaze.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E 1 S20 3 S29 1984
	from which a new bearing tree
	A ponderosa pine, 19 ins. diam., bears N 58° E, 1.98 chs. dist., mkd. 4 S20 BT.
	Set a stainless steel fence post near the cor.
	N 89°28' W, beginning new measurement.
	Through rolling forest.
39.39	The cor. of secs. 19, 20, 29 and 30.
	S 89°57' W, bet. secs. 19 and 30.
	Through rolling forest.
39.17	Point for the ½ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

T	
CHAINS	
	T26N R29E
	1 S19 S30
	1984
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor.
	Dig pits, on line E and W, 3 ft. dist.
	Set a stainless steel fence post near the cor.
	Cor. falls in a large sagebrush flat.
77.76	The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp.
	From the cor. of secs. 19, 20, 29 and 30.
	N 0°23' W, bet. secs. 19 and 20.
	Through rolling forest.
40.29	Point for the ½ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 5 ins. in the ground, encircled in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T26N R29E
	S19 S20
	1984
	Set a stainless steel fence post near the cor.
	Cor. falls in a meadow.
·	

CHAINS

80.58

The cor. of secs. 17, 18, 19 and 20, in the general vicinity of which, the original cor. monument, a sandstone, $20 \times 8 \times 4$ ins., laying loose on the ground, clearly mkd. with 3 grooves on one face and 5 grooves on an adjacent face, determined at record dist. from the original bearing trees

- A pinyon, 16 ins. diam., bears N 64½° E, 81 lks. dist., with scribing marks S17 BT, on a partially healed blaze. (Record: N 62° E.)
- A pinyon, 18 ins. diam., bears N 1½° W, 27 lks. dist., with a healed blaze.

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

T26N R29E S18 | S17 S19 | S20 1984

from which new bearing trees

- A pinyon, 6 ins. diam., bears S 20° E, 83 lks. dist., mkd. T26N R29E S20 Bt.
- A pinyon, 6 ins. diam., bears S 76½° W, 94 lks. dist., mkd. T26N R29E S19 BT.

Deposit the mkd. stone alongside the stainless steel post.

Dig pits, NE, SE, SW and NW, of cor., 3 ft. dist.

Set a stainless steel fence post near the cor.

From the cor. of secs. 16, 17, 20 and 21.

N 89°42' W, bet. secs. 17 and 20.

Through rolling forest.

CHAINS	
40.08	The ½ sec. cor. of secs. 17 and 20, determined at record bearing and dist. from the original bearing tree,
	A pinyon, 17 ins. diam., bears N 10¾° E, 90 lks. dist., with scribe marks BT, on a partially healed blaze.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 8 ins. in the ground, encircled with a mound of stone, 4 ft. diam., to top, with brass cap mkd.
	T26N R29E
	14 S17
•	. S20 1984
	1704
	from which a new bearing tree
	A pinyon, 9 ins. diam., bears S 73½° E, 82 lks. dist., mkd. ½ S20 BT.
	Cor. falls in a dense stand of pinyon.
	Set a stainless steel fence post near the cor.
	S 89°41' W, beginning new measurement.
	Through dense pinyon.
40.16	The cor. of secs. 17, 18 19 and 20.
	S 89°35' W, bet. secs. 18 and 19.
	Through dense pinyon.
40.24	The ½ sec. cor. of secs. 18 and 19, determined at record bearing and dist. from the original bearing tree

CHAINS	
	A pinyon, 15 ins. diam., bears N 30½° W, 24 lks. dist., with illegible scribing on a partially healed blaze.
	At the cor. point
·	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E 1 S18 519
	1984
	from which a new bearing tree
	A pinyon, 7 ins. diam., bears S 34° W, 81 lks. dist., mkd. ½ S19 BT.
	Set a stainless steel fence post near the cor.
	N 89°54' W, beginning new measurement.
	Through rolling forest.
36.91	The cor. of secs. 13, 18, 19 and 24, on the W bdy. of the Tp.
-	From the cor. of secs. 17, 18, 19 and 20.
	N 1°02' W, bet. secs. 17 and 18.
	Through rolling forest.
39.80	Point for the ½ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 18 ins. in the ground, encircled with a mound of stone, 3 ft. base to top, with brass cap mkd.

T26N R29E

s18 | s1 1984

from which

A ponderosa pine, 18 ins. diam., bears S 55¾° E, 87 lks. dist., mkd. ¼ S17 BT.

A ponderosa pine, 25 ins. diam., bears N 34¾° W, 2.09 chs. dist., mkd. ¼ SI8 BT.

Set a stainless steel fence post near the cor.

79.60

The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, $21 \times 6 \times 5$ ins., firmly set 4 ins. in the ground, in a mound of stone, 3 ft. base, 6 ins. high, clearly mkd. with 5 grooves on the E face, and 4 grooves on the S face, from which the remaining original bearing trees

- A ponderosa pine, 24 ins. diam., bears N 64° E, 54 lks. dist., with a healed blaze. (Record: N 25° E, 50 lks. dist.)
- A ponderosa pine, 23 ins. diam., bears S 39½° W, 84 lks. dist., with a healed blaze. (Record: S 25° W, 83 lks. dist.)

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

T26N R29E 57 | S8 S18 | S17 1984

from which new bearing trees

CHAINS	
	A ponderosa pine, 14 ins. diam., bears S 9½° E, 1.52 chs. dist., mkd. T26N R29E S17 BT.
	A pinyon, 9 ins. diam., bears N 1½° W, 88 lks. dist., mkd. T26N R29E S7 BT.
•	Dig pits, NE, SE, SW and NW, 3 ft. dist.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of cor.
	Set a stainless steel fence post near the cor.
	Deposit the mkd. stone alongside the stainless steel post.
	From the cor. of secs. 8, 9, 16 and 17.
	S 89°27' W, bet. secs. 8 and 17.
	Across nearly level ground, through forest.
40.58	Point for the ½ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	$\frac{1}{4} \frac{58}{517}$
	1984
	from which
	A ponderosa pine, 8 ins. diam., bears N ½° W, 1.98 chs. dist., mkd. ¼ S8 BT.
	Set a stainless steel fence post near the cor.
81.17	The cor. of secs. 7, 8, 17 and 18.

CHAINS	
	N 89°30' W, bet. secs. 7 and 18.
	Through rolling forest.
37.10	Wide Ruin Wash, 6 ft. deep, 70 lks. wide, drains southwesterly.
38.22	Point for the ½ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 1 in. diam., 13 ins. long, 8 ins. in drill hole, with magnetized aluminum cap mkd.
	T26N R29E 1 ₄ S7/S18 1984
	from which
	A ponderosa pine, 9 ins. diam., bears S $48\frac{1}{2}^{\circ}$ W, 56 lks. dist., mkd. $\frac{1}{4}$ S18 BT.
	A ponderosa pine, 16 ins. diam., bears N 38° W, 1.82 chs. dist., mkd. ½ S7 BT.
75.84	The cor. of secs. 7, 12, 13 and 18, previously described, on the W bdy. of the Tp.
	From the cor. of secs. 7, 8, 17 and 18.
	N 0°11' W, bet. secs. 7 and 8.
	Through rolling forest.
40.39	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a sandstone, 16 x 9 x 4 ins., firmly set 4 ins. in the ground, clearly mkd. $\frac{1}{4}$ on bottom
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T26N R29E ¹ 2 S7 S8 1984
	Deposit the mkd. stone alongside the stainless steel post.
	Set a stainless steel fence post near the cor.
	Cor. falls in a large meadow.
	N 0°09' E, beginning new measurement.
•	Across a rolling meadow.
40.43	The cor. of secs. 5, 6, 7 and 8, determined at record dist. from the original bearing trees
	A ponderosa pine sawed stump, 32 ins. diam., bears S 75½° W, 72 lks. dist., with scribe mark T visible on an open blaze. (Record: S 15° W.)
	A ponderosa pine, 34 ins. diam., bears N 74° W, 1.49 chs. dist., with illegible scribe marks visible on an opened blaze. (Record: N 22½° W.)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E <u>S6 S5</u> S7 S8 1984
	from which new bearing trees
	A ponderosa pine, 10 ins. diam., bears S 78¾° E, 60 lks. dist., mkd. T26N R29E S8 BT.
	.a.

CHAINS	A ponderosa pine, 17 ins. diam., bears S $8\frac{1}{2}^{\circ}$ W, 2.56 chs. dist., mkd. T26N R29E S7 BT.
	Set a stainless steel fence post near the cor.
,	From the cor. of secs. 4, 5, 8 and 9.
	N 89°27' W, bet. secs. 5 and 8.
	Through rolling forest.
40.64	The ½ sec. cor. of secs. 5 and 8, determined at record bearing and dist. from the original bearing tree
	A ponderosa pine sawed stump, bears S 20° W, 52 lks. dist., alongside of which is lying a section of the felled tree, 20 ins. diam., with scribing marks 1/2 on an open blaze.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, encircled with a mound of stone, 4 ft. to top, with brass cap mkd.
	T26N <u>R</u> 29E
	½ <u>S5</u> S8
	1984
	from which new bearing trees
	A ponderosa pine, 22 ins. diam., bears N 71¾° E, 1.26 chs. dist., mkd. ¼ S5 BT.
	A ponderosa pine, 18 ins. diam., bears S 18° W, 1.54 chs. dist., mkd. 4 S8 BT.
	Set a stainless steel fence post near the cor.
	Through rolling forest.
40.58	The cor. of secs. 5, 6, 7 and 8.

CHAINS	S 89°30' W, bet. secs. 6 and 7.	
	Through rolling forest.	
40.11	The ½ sec. cor. of secs. 6 and 7, determined at record bearing and dist. from the original bearing tree	•
	A ponderosa pine sawed stump, 36 ins. diam., `bears N 35° E, 73 lks. dist., with illegible scribe marks on an opened blaze.	
	At the cor. point	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	. T26N R29E	
	¹ / ₄ S6/S7	
	1984	
	from which new bearing trees	
	A ponderosa pine, 27 ins. diam., bears N 28½° E, 1.77 chs. dist., mkd. ½ S6 BT.	
	A ponderosa pine, ll ins. diam., bears S 32° E, 1.81 chs. dist., mkd. ½ S7 BT.	
	Set a stainless steel fence post near the cor.	
	N 87°30' W, beginning new measurement.	
	Through rolling forest.	
37.31	The cor. of secs. 1, 6, 7 and 12, on the W bdy. of the Tp.	
	From the cor. of secs. 5, 6, 7 and 8.	
	N 0°07' E, bet. secs. 5 and 6.	
	Through rolling forest.	

CHAINS		
40.39	The ½ sec. cor. of secs. 5 and 6, monumented with a sandstone, 22 x 19 x 3 ins., firmly set 10 ins. in the ground, clearly mkd. ½ on W face.	
	At the cor. point	•
,	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	T26N R29E	
	56 S5	
	1984	
	from which new bearing trees	
	A ponderosa pine, 35 ins. diam., bears S 49½° E, 2.58 chs. dist., mkd. ¼ S5 BT.	
	A pinyon, 12 ins. diam., bears S 61° W, 1.77 chs. dist., mkd. 4 S6 BT.	
	Deposit the mkd. stone alongside the stainless steel post.	
	Set a stainless steel fence post near the cor.	
	N 0°23' W, beginning new measurement.	
	Through rolling forest.	
40.98	The cor. of secs. 5, 6, 31 and 32, on the N bdy. of the Tp.	
	Survey of the Subdivision of Certain Sections T. 26 N., R. 29 E., Gila and Salt River Meridian, Arizona	
	Section 14	
	From the 4 sec. cor. of secs. 14 and 23.	
	N 0°33' W, on the N and S center line of sec. 14.	

CHAINS	
	Through rolling forest.
39.53	Point for the center 1/4 sec. cor. of sec. 14, at the intersection with the E and W center line.
,	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T26N R29E C ½ S14 1984
	from which
	A sandstone, of unknown origin, 9 x 3 ins., bears N 36% E, 69 lks. dist.firmly set, projecting 7 ins. above ground, mkd. C% on the W face. Deposit the mkd. stone in place.
	A ponderosa pine, 15 ins. diam., bears S 83¾° E, 1.53 chs. dist., mkd. C4 S14 BT.
	An oak, 8 ins. diam., bears S 79½°W, 71 lks. dist., mkd. C½ S14 BT.
	Set a stainless steel fence post near the cor.
79.71	The ½ sec. cor. of secs. 11 and 14.
	From the 4 sec. cor. of secs. 13 and 14.
	N 89°18' W, on the E and W center line of sec. 14.
	Through rolling forest.
21.30	Graded road, 25 ft. wide, bears N and S.
40.12	The center 4 sec. cor. of sec. 14.
80.99	The 1/4 sec. cor. of secs. 14 and 15.

	Section 22
	From the 4 sec. cor. of secs. 22 and 27.
	N 0°03' W, on the N and S center line of sec. 22.
	Through rolling forest.
40.88	Point for the center $\frac{1}{4}$ sec. cor. of sec. 22, at the intersection with the E and W center line.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 6 ins. in the ground, encircled with a mound of stone, 5 ft. base to top, with brass cap mkd.
	T26N R29E
	C ½ S22
	1984
	from which
	An oak, 9 ins. diam., bears N 26¾° E, 28 lks. dist., mkd. C¼ S22 BT.
	The NE cor. of a wood house, 12 x 14 ft., bears S 5° E, 14.49 chs. dist.
	A sandstone, of unknown origin, 20 x 4 ins., firmly set in a mound of stone, 2 ft. base, 6 ins., high, projecting 7 ins. above ground, mkd. CS 22 on the E face, bears S 23/4 W, 86 lks. dist. Deposit the mkd. stone in place.
	The center of a hogan, bears S 11½° W, 12.74 chs. dist.
	A ponderosa pine, 15 ins. diam., bears N 28¾° W, 2.84 chs. dist., mkd. C¼ S22 BT.
	Set a stainless steel fence post near the cor.
80.03	The $\frac{1}{4}$ sec. cor. of secs. 15 and 22.

CHAINS	From the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.	
	S 89°58' W, on the E and W center line of sec. 22.	
	Through rolling forest.	
39,24	The center 4 sec. cor. of sec. 22.	
80.97	The 1/4 sec. cor. of secs. 21 and 22.	
	Section 24	
	From the 1/4 sec. cor. of secs. 24 and 25.	
	N 1°05' W, on the N and S center line of sec. 24.	
	Through rolling forest.	
40.50	Point for the center \(\frac{1}{4} \) sec. cor. of sec. 24, at the intersection with the E and W center line.	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.	
	T26N R29E C ½ S24 1984	
	from which	
	A pinyon, 5 ins. diam., bears S 33° E, 28 lks. dist., mkd. C ½ S24 BT.	
	A sandstone, of unknown origin, 17 x 5 ins., firmly set, projecting 13 ins. above ground, mkd. CS24 on E face, bears S 86¾° W, 33 lks. dist. Deposit the mkd. stone in place.	
	A ponderosa pine, ll ins. diam., bears N 50½° W, 54 lks. dist., mkd. C½ S24 BT.	
	Set a stainless steel fence post near the cor.	

CHAINS	
81.39	The 4 sec. cor. of secs. 13 and 24.
	From the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E bdy. of the Tp.
,	S 89°21' W, on the E and W center line of sec. 24.
	Through rolling forest.
39.63	The center 1/4 sec. cor. of sec. 24.
79.87	The ½ sec. cor. of secs. 23 and 24.
	Section 28
	From the 1/4 sec. cor. of secs. 28 and 33.
	N 0°07' W, on the N and S center line of sec. 28.
	Through rolling forest.
40.26	Point for the center 4 sec. cor. of sec. 28, at the intersection with the E and W center line.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T26N R29E
	C ½ S28 1984
	from which
	A ponderosa pine, 8 ins. diam., bears N 71½° E, 78 lks. dist., mkd. C½ S28 BT.
	Set a stainless steel fence post near the cor.
79.89	The 1/4 sec. cor. of secs. 21 and 28.
	From the \(\frac{1}{4} \) sec. cor. of secs. 27 and 28.
	N 89°11' W, on the E and W center line of sec. 28.

1. 20	N., R. 29 E., Gila and Salt River Meridian, Arizona	
CHAINS		
	Through rolling forest.	
40.30	The center \(\frac{1}{4} \) sec. cor. of sec. 28.	•
80.40	The ½ sec. cor. of secs. 28 and 29.	
	Section 32	
	From the 1/4 sec. cor. of sec. 32 only, on the S bdy. of the Tp.	
	N 2°05' W, on the N and S center line of sec. 32.	
	Through rolling forest.	
40.23	Point for the center \(\frac{1}{4} \) sec. cor. of sec. 32, at the intersection with the E and W center line.	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 18 ins. in the ground, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.	
	T26N R29E C ½ S32 1984	
	from which	
	A pinyon, 14 ins. diam., bears S 74° E, 16 lks. dist., mkd. C ¼ S32 BT.	
	A ponderosa pine, 26 ins. diam., bears S 864° W, 2.30 chs. dist., mkd. C 4 S32 BT.	
	A sandstone, of unknown origin, 18 x 4 ins., firmly set in a mound of stone, 3 ft. base, 6 ins. high, projecting 10 ins. above ground, clearly mkd. CS32 on W face, bears N 8½° W, 15 lks. dist. Deposit the mkd. stone in place.	*
80.63	The ½ sec. cor. of secs. 29 and 32.	
 ·		

CHAINS	From the 1/4 sec. cor. of secs. 32 and 33.
	N 89°37' W, on the E and W center line of sec. 32.
	Through rolling forest.
36.61	The center \(\frac{1}{4} \) sec. cor. of sec. 32.
78.40	The ½ sec. cor. of secs. 31 and 32.
	Section 34
	From the ½ sec. cor. of secs. 34 only, on the S bdy. of the Tp.
	N 0°39' W, on the N and S center line of sec. 34.
	Through rolling forest.
1.50	Graded road, 25 ft. wide, bears N 50° E, and S 50° W.
40.35	Point for the center 4 sec. cor. of sec. 34, at the intersection with the E and W center line.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 18 ins. in the ground, encircled with a mound of stone, 4 ft. base to top, with brass cap mkd.
÷	T26N R29E C ½ S34 1984
	from which
	A sandstone, of unknown origin, 24 x 22 ins., firmly set, projecting 6 ins. above ground, mkd. CS34 on W face, bears N 12½° E, 40 lks. dist. Deposit the mkd. stone in place.
	An oak, 8 ins. diam., bears N 36½° E, 1.36 chs. dist., mkd. C½ S34 BT.
	A ponderosa pine, 15 ins. diam., bears S 34¾° W, 24 lks. dist., mkd. C ¼ S34 BT.

CHAINS	Set a stainless steel fence post near the cor.	
80.84	The ½ sec. cor. of secs. 27 and 34.	
	From the 4 sec. cor. of secs. 34 and 35.	
	S 89°52' W, on the E and W center line of sec. 34.	
	Over nearly level ground, through forest.	
5.10	Graded road, 25 ft. wide, bears N 34° E and S 34° W.	
39.99	The center \(\frac{1}{4} \) sec. cor. of sec. 34.	
79.76	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34.	
	GENERAL DESCRIPTION	
	Township 26 North, Range 29 East, is situated within the Navajo Indian Reservation, about 8 miles west of Window Rock, Arizona. The elevation varies from 7300 ft. to 7750 ft. above sea level. Straddling the summit of the Defiance Plateau, the township has no specific drainage pattern. Most of the land is gently rolling or flat. The soil varies from clay loam in the lower areas to sandstone along the ridges.	
	The principal use of the township is forestry, with ponderosa pine as the crop tree. Cattle grazing in the summer months is a secondary usage. No active mining was noted.	
	Arizona State Highway No. 264 crosses the northeast portion of the township in a northwesterly direction. Further access to the township is provided by numerous secondary logging roads.	
	A microwave radio facility is located within section ll, and an improved picnic area lies within section l. A windmill is located in section 35. Indian allotments are situated within the subdivided sections.	
	An average number of readings throughout the township gives a mean magnetic declination of 12½° E, with no noticeable differences due to local attraction.	

123 RUUK 2 2 0 7

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

CAPACITY
Engineering Technician II
Engineering Technician II
Engineering Technician II
Engineering Technician II
Engineering Technician II
Engineering Technician II
Engineering Technician II

CERTIFICATE OF SURVEY

I, Jack A. Savlan, Cadastral Land Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of April, 1984, I have dependently resurveyed the south, east, west, and north boundaries, and the subdivisional lines and the survey of the subdivision of certain sections, of Township 26 North, Range 29 East of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jack A. Savlan is no longer signature.	assigned to this office and not available for
(Date) (198)	8 (Cadastral Surveyor)
JUN 1 7 1988	
(Date)	(Cadastral Surveyor)
	CERTIFICATE OF APPROVAL
	BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona
and north boundaries, and th subdivision of certain secti River Meridian, Arizona exec	the dependent resurvey of the south, east, west, se subdivisional lines and the survey of the ons of T. 26 N., R. 29 E., of the Gila and Salt suted by Jack A. Savlan, Cadastral Surveyor, having found correct, are hereby approved.
JUN 17 1988	James P. Kelley
(Date)	(Chief Cadastral Surveyor of Arizona)
	ERTIFICATE OF TRANSCRIPT
I Certify That the foregoing described surveys in T 26 N, true copy of the original fi	transcript of the field notes of the above- R 29 E, Gila and Salt River Mer., Arizona, is a eld notes.
(Date)	(Chief Cadastral Surveyor of Arizona)