# BOOK, 5304 ORIGINAL

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD NOTES

OF THE

	DEPEND!	ENT RESURVEY OF PORTIONS OF
	THE SOUT	H, EAST, AND WEST BOUNDARIES,
	THE SUBDIVIS	SIONAL LINES, AND THE SURVEY OF,
	THE SUBI	DIVISION OF CERTAIN SECTIONS
	AND '	THE DEPENDENT RESURVEY OF
	CI	ERTAIN MINING CLAIMS,
	AND MINE	RAL SEGREGATION IN SECTION 25
	TOWNSI	HIP 10 NORTH, RANGE 5 WEST
Of the _	Gila and Salt	River Meridian,
In the State of _	Arizona	
		EXECUTED BY
Will C. Gabo	onay,	Cadastral Surveyor,
Duane R. Gar	routte,	Cadastral Surveyor,
and second supple	emental instructi	<u>January 3</u> , 1979, approved <u>January 4, 1979,</u> ions dated December 10, 1979, approved
		ovided for the surveys included under Group Number
	issignment instri	actions dated <u>January 21</u> , 1983, and
January 17, 1986		
	Supran comm	enced January 26 , 1983
	_	leted March 3 , 1986
	DULVEY COMP.	LUCIA IRLUIT / LUC

2

#### INDEX DIAGRAM

TOWNSHIP	10 NORTH	_, ]	RANGE	5	WEST	
----------	----------	------	-------	---	------	--

		<del></del>				·					
	6	5		4		3		2		1	
										21	
	7	8		9		10		11	20	12	11
		1						26		19	
	18	17		16		15	25	14		13	
	10	17		10		13	25	14		13	
15 ├──				36				24			
14	19	20	35	21	29	22		23		24	9
	<del>4</del> 1	40		34						18	
	20 2	20		20		27		26		25	
13 	30 3	37 29 	3 <b>4</b>	28	29 	27	23	26		25	
	~	36—		32		28		22		17	
12	31	32	31	33	27	34	22 	35	16	36	8
		Sec. 12 /		6		5				4	

Subdivision Sec.12 42 - 44
Subdivision Sec.14 44 - 47
Subdivision Sec.19 47 - 49
Subdivision Sec.20 50 - 51
Subdivision Sec.21 52 - 55
Subdivision Sec.24 55 - 59

Subdivision Sec.28 59 - 61
Subdivision Sec.29 61 - 67
Subdivision Sec.30 68 - 70
Subdivision Sec.33 70 - 74
Subdivision Sec.34 74 - 77

#### B00K 5304

2-A

#### INDEX DIAGRAM

		TOWNSHIP 10 No	ORTH, RANG	E	5 WEST,
		Mine	ral Surveys		
MS	1201	Mother	77-78		
			78-79, 88-89		
		Juniper	•	)7	
		Triangle			
MS	1114	Edmond	84-89		
MS	1704A	Side Issue	89-91, 107-10	8	
MS	1704A	Side Issue Comet	91-92		
MS	1184	Planet	92-93		
MS	1184	Saturn	93-95		
	1185		95-96, 98-99		
MS	1185	Cottonwood	96-98		
MS	1185	Oroville Placer	99-100		
MS	1185	Golden Bowl Place	100-101		
		Diamond Placer			
MS	1704A	Evening Placer	103-104		
MS	1277	Lucky Johnnie	108-109, 112-	·113	
MS	1277	Katie Hunter	110-111		
		Welcome Nol West		120,	126-126
MS	1971	Dixie No 3	115-115		
MS	1971	Dixie No 2 Dixie	115-116, 122-	·123	
MS	1971	Dixie	116-117, 123-	-123	
		New York No 2			
		New York No 1			
		Welcome No1 East			
			119-120, 125-	126	
		Suney Side			
		Katherine			
MS	2888	Margaret	127-128		
MS	2888	Grantley Denver	128-129		
		Denver	129-130		
	2888				
		Chester	131-132	1.40	
	2888		132-133, 140-	140	
	1744		133-135		
	4301	Upton	135 <b>-</b> 138 138 <b>-</b> 139		
	4301 2201	Upton Placer Midnight	139-140		
	2198	Mamic	140-141		
	2200		141-143		
	2200	Helen Morris			
	2199	Mountaineer	144-145		
	4398	Jerome Extension			
	4398	Jerome No 3	147-149		
	4398	Jerome	149-150		
	1070				

#### T 10 N, R 5 W, Gila and Salt River Mer., Arizona

#### CHAINS

The following field notes are those of the dependent resurvey of portions of the south, east, and west boundaries, the subdivisional lines, and the survey of the subdivision of certain sections, and the dependent resurvey of certain mining claims, and mineral segregation in section 25, in Township 10 North, Range 5 West, Gila and Salt River Meridian, Arizona.

Solomon W. Foreman surveyed a portion of the west boundary in 1871. Omar H. Case surveyed a portion of the north boundary in 1871. John F. Hesse resurveyed a portion of the west boundary in 1904. Chas. M. Pidgeon surveyed the south boundary, and portions of the west and north boundaries and a portion of the subdivisional lines, and resurveyed and retraced portions of the west boundary in 1916. Theodore O. Johnston surveyed portions of the west and north boundaries and a portion of the subdivisional lines in 1916. Benjamin J. Kinsey resurveyed a portion of the east boundary in 1936. Historys of the mineral surveys are contain in the official record.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions and Second Supplemental Special Instructions for Group 611, Arizona, dated January 3, 1979, and December 10, 1979, respectively.

The directions of all lines were determined by altitude observations on the sun and refer to the true meridian. Angles and distances were measured electronically using a Zeiss Elta 4S Total Station instrument.

Preliminary to the resurvey, the lines of orginal surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the SE corner of section 36, as determined from a tie made to U.S.G.S. triangulation station "LADY 1969", located in section 30, is as follows:

NAD 27: Latitude: 34°09'29.40" N. Longitude: 112°43'06.46" N.

The magnetic declination as taken from 7.5 series quadrangle map CONGRESS, ARIZ., published in 1969 by U.S. Geological Survey is 14 1/2° E.

CHAINS

Reestablishment of the survey executed by Chas. M. Pidgeon in 1916

Beginning at the cor. of Tps. 9 and 10 N, Rs. 4 and 5 W, monumented with an iron post, 3 ins. diam., projecting 18 ins. above ground, with brass cap mkd.

Remark the brass cap to read

Cor. is located 2 lks. N of a fence, extends E and W.

S 89°53' W, bet. secs. 1 and 36, on the S. Bdy. of the Tp.

Desc. over open, mountainous and rugged terrain, across patented mineral claims.

3.38 Intersect line 4-1, M.S. 2198 Mamie lode, at a point from which cor. 1, bears N 30°23' W, 5.02 chs. dist., hereinafter described.

Thence leave patented mineral claims.

- 35.00 Graded road, 30 lks. wide, bears N and S.
- 39.98 The 1/4 sec. cor. of secs. 1 and 36, identical with cor. 1 M.S. 4301 Upton Placer Claim Number #1, monumented with an iron post, 1 in. diam., projecting 4 ins. above ground, with brass cap mkd.

	1 10 N, R 5 W, G11a and Salt River Mer., Arizona
CHAINS	
	with mkds. 1 UP1 4301 on the side of the cap.
	from which a bearing object established in 1946
	A rock in place, 3 x 3 x 2 ft. high above ground, bears S 61°15' W, 13 lks. dist., mkd. X BR 1 UP1 4301.
	S 89°57' W, beginning new measurement, on the line bet. secs. 1 and 36, on the S. Bdy. of the Tp., identical with line 1-2, M.S. 4301 Upton Placer Claim Number #1.
23.90	Antelope Creek, 100 lks. wide, drains S 20° E.
30.00	Cor. 2, M.S. 4301 Upton Placer Claim Number #1, monumented with a malpais stone, 8 x 8 x 10 ins. above ground, firmly set, mkd. UP 1 2 4301 on N face, with a mound of stone, 3 ft. base, 2 1/2 ft. high, W.
	Not remonumented
32.20	Graded road, 30 lks. wide, bears N 15° E and S 15° W.
40.01	The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., projecting 4 ins. above a mound of stone, 3 1/2 ft. base, 1 ft. high, with brass cap mkd.
	T10N R5W S35   S36
	S 2 S 1
	T9N 1916
	From the 1/4 sec. cor. of secs. 3 and 34, on the S bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 4 ins. above ground, with brass cap mkd.
	1/4 S34
	S 3 1916
	S 89°57' W, bet. secs. 3 and 34.
	Over rolling terrain, through scattering undergrowth.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
20.01	Point for the W 1/16 sec. cor. of secs. 3 and 34.
	Set an aluminum post, 72 ins. long, 3/4 in. diam., 64 ins. in the ground, with cap mkd.
	T10N R5W
	W 1/16 ———
	s 3
	T9N 1983
	Set a steel fence post alongside the cor.
20.30	Wash, 45 lks. wide, drains S.
40.02	The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 3 ins. diam., projecting 7 ins. above ground, with brass cap erroneously mkd.
	T10N R5W
	<u>S 4   S 3</u>
	S33   S34 T9N
	1916
	Remark the brass cap to read
	T10N R5W S33   S34
	S 4   S 3 T9N
	1983
	1916
	S 89°57' W, bet. secs. 4 and 33.
	Over rolling terrain, through scattering undergrowth.
19.40	Wash, 15 lks. wide, drains S 20° E.
20.02	Point for the E 1/16 sec. cor. of secs. 4 and 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	T10N R5W S33 E 1/16 —— S 4 T9N 1983
	Set a steel fence post alongside the cor.
40.04	The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd.
	1/4 S33
	s 4 1916
	S 89°56' W, beginning new measurement.
20.00	Point for the W 1/16 sec. cor. of secs. 4 and 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, with cap mkd.
	T10N R5W S33 W 1/16 ——————————————————————————————————
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N of cor.
	Set a steel fence post alongside the cor.
	Cor. is located 2.00 chs. N of a road, 15 lks. wide, bears E and W.
40.00	The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., projecting 5 ins. above ground, with brass cap mkd.
	T10N R5W S32   S33
	S 5 S 4 T9N 1916
	L

	T 10 N, R 5 W, Gila and Sait River Mer., Arizona
CHAINS	
	Reestablishment of the survey executed by Chas. M. Pidgeon in 1916
	From the cor. of Tps. 9 and 10 N, Rs 4 and 5 W., hereinbefore described.
	N 0°04' W, on the E bdy. of sec. 36.
	Over rugged, mountainous terrain, across patented mineral claims.
40.02	True point for the 1/4 sec. cor. of sec. 36 only, at proportionate dist., falls on a granite boulder where it is impractical to set a permanent monument.
40.42	The witness 1/4 sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with a mound of stone, 3 ft. base, 3 ft. high, W, with brass cap mkd.
	1/4 S36 S31 W C
	1916–36
	Remark the brass cap to read
	1./4
	1/4 s36 ↓
	w <sup>*</sup> C
	1986 36
	1916
	Reestablishment of the survey executed by Benjamin J. Kinsey in 1936-37
	N 0°02' W, beginning new measurement.
1.78	Intersect line 2-3, M.S. 2199 Mountaineer lode, at a point from which cor. 3, identical with cor. 2 M.S. 2199 Golden Mountain Side lode, bears S 16°31' E, 36 lks. dist., hereinafter described.
	Thence leave patented mineral claim.
3.45	Intersect line 1-2, M.S. 4398 Jerome Extension lode, at a point from which cor. 1, bears S 17°44' E, 7.30 chs. dist., hereinafter described.
	Thence across patented mineral claims.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
32.28	Intersect line 1-2, M.S. 4398 Jerome lode, at a point from which cor. 1, bears N 34°17' W, 1.36 chs. dist., hereinafter described.
	Thence leave patented mineral claims.
36.86	The closing cor. of secs. 30 and 31, T 10 N, R 4 W, bears East, 3.5 lks. dist., monumented with an iron post, 2 ins. diam., projecting 12 ins. above a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1936-37 survey of the subdivision of T 10 N, R 4 W.
39.345	The cor. of secs. 25 and 36 only, monumented with a boulder in place, 6 x 3 x 4 ft. above ground, mkd. with a large + chiseled on top.
	From this cor., the witness cor. for the cor. of secs. 25 and 36 only, bears North, 0.295 chs. dist., monumented with an iron post, 3 ins. diam., set in a mound of stone, 4 ft. base, 2 ft. high, to top, with brass cap mkd.
	T10N R5W   R4W S25
	S36 v
ĺ	W'C
	1936
	1916
	Reestablishment of the survey executed by Chas. M. Pidgeon in 1916 ———————————————————————————————————
	From the cor. of secs. 24 and 25 only, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W, with brass cap mkd.
	T10N T10N R5W   R4W S24   S10
	S19 S25 1916-36
	N 0°03' W, on the E bdy. of sec. 24.
	Over open, mountainous terrain.

	1 10 N, K 5 W, GIIA AND SAIC RIVEL PRELL, ALIZONA
CHAINS	
20.00	The S 1/16 sec. cor. of sec. 24 only, monumented with a rebar of unknown origin, 3/4 in. diam., projecting 6 ins. above ground. This is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum post, 3/4 in. diam., 36 ins. long, 28 ins. in the ground, with cap mkd.
	T10N R5W   S 1/16 S24   1983
	Deposit the rebar alongside the aluminum post.
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W.
	Cor. is located 55 lks. W of a track road, 20 lks. wide, bears irregularly N and S.
40.00	The 1/4 sec. cor. of sec. 24 only, monumented with a rebar of unknown origin, 3/4 in. diam., projecting 2 ins. above a creek bed. This is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	T10N R5W   1/4 S24   1983
	from which
	An aluminum post, 36 ins. long, 3/4 in. diam., set 30 ins. in the ground and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N 10° W, 32.0 ft. dist., with cap mkd. 1/4 S24 32.0 FT RM 1983 and an arrow pointing to the cor.
	An aluminum post, 36 ins. long, 3/4 in. diam., set 28 ins. in the ground and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N 67° W, 34.8 ft. dist., with cap mkd. 1/4 S24 34.8 FT RM 1983 and an arrow pointing to the cor.

# Dependent Resurvey of a Portion of the East Bdy., T $10~\mathrm{N}$ , R $5~\mathrm{W}$ , Gila and Salt River Mer., Arizona

CHAINS	1 10 N, R 5 W, GIIa and Salt River Mer., Arizona
CHAINS	
	Deposit the rebar alongside the cor.
	Cor. is located in the center of Antelope Creek, 50 lks. wide, drains S 40° W.
	N 0°03' W, beginning new measurement.
0.60	Point for the witness 1/4 sec. cor. of sec. 24 only, at proportionate dist.; there is no remaining evidence of the original cor., not remonumented.
37.38	The closing cor. of secs.18 and 19, T 10 N, R 4 W, monumented with an iron post, 2 ins. diam., set in a mound of stone, 2 1/2 ft. base, 18 ins. high, to top, with brass cap mkd. as described in the official record of the 1936-37 survey of the subdivision of T 10 N, R 4 W.
40.00	The cor. of secs. 13 and 24 only, monumented with an iron post, 3 ins. diam., projecting 6 ins. above ground, with a scattered mound of stone, S, with brass cap mkd.
	TION
	R5W R4W S13
	S18
	S24   1916
	From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 6 ins. above ground, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W, with brass cap mkd.
	T10N
	R5W R4W S12
	S13 S 7
	Cor. is located in a fence, extends N and S.
	N 0°23' E, on the E bdy. of sec. 12, along a fence.
	Over open, mountainous land.
20.03	Point for the S 1/16 sec. cor. of sec. 12 only.

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over an X chiseled on bedrock and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T10N R5W | S 1/16 | S12 | 1986

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 lks. E of a fence, extends N and S.

40.06

The 1/4 sec. cor. of sec. 12 only, monumented with an iron post, 1 in. diam., projecting 14 ins. above ground, with a mound of stone, 2 1/2 ft. base, 6 ins. high, W, with brass cap mkd.



Cor. is located in a fence, extends N and S.

Dependent Resurvey of a Portion of the West Bdy., T 10 N, R 5 W, Gila and Salt River Mer., Arizona

Reestablishment of the resurvey executed by John F. Hesse, in 1904

From the cor. of secs. 25, 30, 31 and 36, Tps. 10 N, Rs. 5 and 6 W, monumented with a granite stone, 24 x 12 x 4 ins., firmly set, 16 ins. in the ground, mkd. with 5 grooves on the N face and 1 groove on the S face.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.

CHAINS	
	mlov.
	TION R6W   R5W
	S25 S30
	525 550
	S36 S31
	1983
	Deposit the mkd. stone alongside the aluminum post.
	Cor. is located S 45° W, 3 lks. dist., from cor. of fences and S 45° W, 9 lks. dist., from a wood post, 4 ins. square, projecting 3 1/2 ft. above a mound of stone, 3 ft. base, 1 ft. high.
	N 0°04' E, bet. secs. 25 and 30.
	Over open, rolling terrain.
40.04	The 1/4 sec. cor. of secs. 25 and 30, monumented with a granite stone, 18 x 10 x 6 ins., firmly set, 12 ins. in the ground, mkd. 1/4 on W face.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	TION
	1/4
	R6W R5W
	S25 S30
	1983
	Bury the stone alongside the aluminum post.
	Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W.
	Cor. is located 71 lks. W of a N-S fence, and 24 lks. E of a mine shaft, 24 lks. wide.
	N 0°03' E, beginning new measurement.
40.17	The cor. of secs. 19, 24, 25 and 30, monumented with a granite stone, 13 x 12 x 6 ins., firmly set, 8 ins. in the ground, mkd. with 4 grooves on the N and 2 grooves on the S faces.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground and in a mound of stone, 1 ft. base, to top, with cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	TION R6W   R5W
	S24 S19
	S25 S30
	1983
	Deposit the mkd. stone alongside the aluminum post.
	Set a steel fence post alongside the cor.
	Cor. is located on W edge of a pit, 26 lks. diam., 5 ft. deep.
	Reestablishment of the resurvey executed by Chas. M. Pidgeon in 1916
	North, between secs. 19 and 24, on the W. bdy. of the Tp.
	Over hilly terrain, through scattering undergrowth.
18.00	Wash, 50 lks. wide, drains S.
19.917	Point for the S 1/16 sec. cor. of sec. 19 only, T 10 N, R 5 W.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T10N
	R6W   R5W   S 1/16
	S19 1986
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E of cor.
20.045	Point for the S 1/16 sec. cor. of sec. 24, T 10 N, R 6 W.
	Set an aluminum post, 3/4 in. diam., 36 ins. long, 30 ins. in the ground, with cap mkd.
	T10N R6W   R5W S24   S 1/16   1983

T 10 N, R 5 W, Gila and Salt River Mer., Arizona
Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of cor.
Point for the 1/4 sec. cor. of sec. 19 only.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
T10N R6W R5W   1/4 S19 1986
Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor.
Set a steel fence post alongside the cor.
The 1/4 sec. cor. of sec. 24,T 10 N, R 6 W, monumented with a granite stone, 16 x 8 x 6 ins., firmly set, mkd. 1/4 on W face.
At the cor. point
Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
TION R6W   R5W 1/4 S24   1983
Deposit the mkd. stone alongside the aluminum post.
Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
N 0°01' W, beginning new measurement.
The closing cor. of secs. 18 and 19 only, monumented with an iron post, 2 ins. diam., projecting 8 ins. above a mound of stone, 2 ft. base, 6 ins. high, with a mound of stone, 3 ft. base, 1 ft. high, E, with brass cap mkd.
T10N R6W   R5W   S18 C   C   S19 1916

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
40.11	The cor. of secs. 13 and 24, T 10 N, R 6 W, monumented with a granite stone, 24 x 6 x 6 ins., firmly set, 10 ins in the ground, mkd. with 3 grooves on the N and on S faces, with a mound of stone, 3 ft. base, 2 ft. high, W.
	At the cor. point
	Set a stainless steel post 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	T10N R6W   R5W S13 S24 1986
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Deposit the mkd. stone alongside the stainless steel post.
	Rebuilt the mound of stone, 3 ft. base, 2 1/2 ft. high, W.
	Set a steel fence post alongside the cor.
	Dependent Resurvey, a Portion of the Subdivisional Lines, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	Reestablishment of the survey executed by Chas. M. Pidgeon in 1916
	From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the Tp.
	N 0°03' W, bet. secs. 35 and 36.
	Over rolling land, through scattering undergrowth.
39.90	The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W, with brass cap mkd.
	1/4 S35   S36 1916
	L

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 0°03' W, beginning new measurement.
2.86	Intersect line 2-3, M.S. 1736 Stanton lode, at a point from which cor. 2, bears N 81°44' E, 5.30 chs. dist., hereinafter described.
	Thence across patented mineral claims.
11.48	Intersect line 4-5, M.S. 1736 Stanton lode, at a point from which cor. 5, bears N 81°21' E, 33 lks. dist., hereinafter described.
	Thence leave patented mineral claims.
39.95	The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N, with brass cap mkd.
	T1ON R5W S26   S25
	S35 S36 1916
	From the cor. of secs. 25 and 36 only, on the E bdy. of the Tp, hereinbefore described.
	S 89°59' W, bet. secs. 25 and 36.
	Over rugged terrain.
9.79	Intersect line 1-2, M.S. 4398 Jerome No. 3 lode, at a point from which cor. 1, bears N 30°07' W, 1.56 chs. dist., hereinafter described.
	Thence across patented mineral claim.
13.56	Intersect line 4-1, M.S. 4398 Jerome lode, at a point from which cor. 4, bears S 65°44' W, 4.44 chs. dist., hereinafter described.
	Thence leave patented mineral claim.
40.00	The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., set in a mound of stone, 2 1/2 ft. base, 1 ft. high, to top, with brass cap mkd.

r	T 10 N, R 5 W, Glia and Sait River Mer., Arizona
CHAINS	
}	1/4 S25
	S36 1916
	From this point, a wood post, 4 x 4 ins. square, projecting 4 ft. above ground, mkd. USIM 1277 on S side, with a granite rock alongside, 3 x 3 ft., projecting 1 ft. above ground, mkd. USIM 1277, and an arrow pointing to the post, bears S 85°53' E, 7.49 chs. dist.
	From this same point, cor. No. 1, MS 4822 Red Twister No. 1, bears N 87°43'W, 9.72 chs. dist., described as mkd and set in the field note record of MS 4789 Red Twister No. 1.
	From this same point, cor. No. 2, MS 4822 Box Sliver, bears N 21°03'E, 22.73 chs. dist, described as set, mkd in the field note record of MS 4822 Box Sliver.
	S 89°58' W, beginning new measurement.
39.99	The cor. of secs. 25, 26, 35 and 36.
	From the cor. of secs. 24 and 25 only, on the E bdy. of the Tp., hereinbefore described.
	S 89°56' W, bet. secs. 24 and 25.
	Over rugged terrain.
19.99	Point for the E 1/16 sec. cor. of secs. 24 and 25.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, with cap mkd.
	T10N R5W
	E 1/16 ——
	S25 1983

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Cor. is located 182 lks. S of a track road, 15 lks. wide, bears SE and NW.
39.98	The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., projecting 5 ins. above ground, with a mound of stone, 2 ft. base, 1 1/2 ft. high, N, with brass cap mkd.
	1/4 S24
	1916
	From the cor. of secs. 13 and 24 only, on the E bdy. of the Tp., hereinbefore described.
	S 89°57' W, bet. secs. 13 and 24.
	Over rugged terrain.
39.89	The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., set in a mound of stone, 2 ft. base, 12 ins. high, to top, with brass cap mkd.
	1/4
	<u>\$13</u>
	S24 1916
	1910
	From the cor. of secs. 12 and 13 only, on the E bdy. of the Tp., hereinbefore described.
	N 89°59' W, bet. secs. 12 and 13.
	Over open, rugged, mountainous terrain.
17.00	Spur, slopes S 10° E.
19.92	Point for the E 1/16 sec. cor. of secs. 12 and 13.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.

	T 10 N, R 5 W, G11a and Salt River Mer., Arizona
CHAINS	
	T10N R5W S12 E 1/16 ——————————————————————————————————
	from which
	A pine, 5 ins. diam., bears S 3 1/2° E, 34 lks. dist., mkd. X BT.
	Cor. is located on a spur, slopes South, and 4.50 chs. N of a ravine, 30 lks. wide, drains S 50° E.
39.84	True point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., falls on steep cliffs, where it is impractical to set a monument.
45.88	The witness 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., set in a mound of stone, 4 ft. base, 1 ft. high, to top, with brass cap mkd.
	1/4
	S12
	${\text{S13}}$ WC
	1916
	From the cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap mkd.
	T10N R5W
	S11   S12
	S14 S13 1916
	Cor. is located in a fence, extends N and SE.
	N 0°03' E, bet. secs. 11 and 12.
	Over open, rugged, mountainous terrain, along a fence.
40.04	The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W, with brass cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	1/4 S11   S12 1916
	Cor. is located in a fence, extends N and S.
	N 0°04' E, beginning new measurement.
	Along a fence.
39.94	The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., projecting 7 ins. above ground, with a mound of stone, 2 ft. base, 1 ft. high, W, with brass cap mkd.
	TION R5W S 2   S 1
	S11 S12 1916
	Cor. is located alongside a fence cor.; fences extend N, E, S and W.
	From the cor. of secs. 1 and 12 only, on the E bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 8 ins. above ground, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E, with brass cap mkd.
	T10N
	R5W   R4W S 1
	S 6
	1937 1916
	Cor. is located alongside a fence cor.; fences extend N, E, and W.
	N 89°58' W, bet. secs. 1 and 12.
	Along fence.
1	True point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., falls on shelving rock where it is impractical to set a monument.

	T 10 N, R 5 W, Glia and Salt River Mer., Arizona
CHAINS	
40.30	The witness 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., set in a mound of stone, 5 ft. base, 30 ins. high, to top, with brass cap mkd.
	1/4
	S 1
	S12 WC
	1916
	Cor. is located in a fence, extends E and W.
	S 89°53' W, beginning new measurement.
	Along a fence.
39.71	The cor. of secs. 1, 2, 11 and 12.
	From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.
	1/4
	S34   S35 1916
	N 0°01' E, bet. secs. 34 and 35.
	Over open and nearly level terrain.
38.19	Intersect line 3-4, M.S. 1971 Welcome No. 1 West lode, at a point from which cor. 3, identical with cor. 4, M.S. 1971 Welcome lode, bears S 77°20' E, 9.40 chs. dist., hereinafter described.
I	Thence across patented mineral claim.
39.97	The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., projecting 6 ins. above ground, with brass cap mkd.
	TION R5W
	S27   S26
	S34 S35
	1916

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the cor. of secs. 25, 26, 35 and 36.
	N 89°55' W, bet. secs. 26 and 35.
	Over rugged, mountainous terrain.
37.82	Intersect line 3-4, M.S. 1971 New York No. 1 lode, at a point from which cor. 3, identical with cor. 2, M.S. 1971 Welcome No. 1 lode, bears S 9°11' E, 1.91 chs. dist., hereinafter described
	Thence across patented mineral claims.
40.00	The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W, with brass cap mkd.
	1/4
	S26
	s35
	1916
	N 89°56' W, beginning new measurement.
	Over open, rugged, mountainous terrain.
6.73	Intersect line 1-2, M.S. 1971 New York No. 1 lode, at a point from which cor. 2, bears S 9°08' E, 1.30 chs. dist., hereinafter described.
	Thence leave patented mineral claims.
14.07	Intersect line 1-2, M.S. 1971 Welcome lode, at a point from which cor. 2, identical with cor. 1, M.S. 1971 Welcome No. 1 East lode, bears S 70°47' E, 2.88 chs. dist., hereinafter described.
	Thence a cross patented mineral claim.
39.96	The cor. of secs. 26, 27, 34 and 35.
	N 0°03' E, bet. secs. 26 and 27.
	Over open, rugged, mountainous terrain.
	Across patented mineral claims.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
21.85	Intersect line 1-2, M.S. 1971 Dixie No. 3 lode, at a point from which cor. 2, identical with cor. 1, M.S. 1971 Dixie No. 2 lode, bears N 44°54' E, 1.86 chs. dist., hereinafter described.
	Thence leave patented mineral claims.
39.99	The witness 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., projecting 4 ins. above ground, with a mound of stone, 3 ft. base, 3 ft. high, W, with brass cap mkd.
	1/4 W C S27 A S26 1916
40.045	The 1/4 sec. cor. of secs. 26 and 27, monumented with a boulder in place 4 x 3 x 3 ft. above ground, mkd. with a + chiseled on top.
	From the 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., projecting 6 ins. above a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.
	1/4 S14 S23
	1916
	N 89°53' W, bet. secs. 14 and 23.
	Over mountainous terrain.
15.26	Intersect line 4-1, M.S. 1201 Mother lode, at a point from which cor. 1, bears N 2°27' E, 5.02 chs. dist., hereinafter described.
	Thence across a patented mineral claim.
37.55	Intersect line 2-3, M.S. 1201 Mother lode, at a point from which cor. 2, bears N 2°45' E, 5.96 chs. dist., hereinafter described.
	Thence leave patented mineral claim.
·	

	1 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
40.01	The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W, with brass cap mkd.
	TION R5W S15   S14
	S22 S23 1916
	North, bet. secs. 14 and 15.
	Over rugged, mountainous terrain.
6.39	Intersect line 1-2, M.S. 1113 Edgar lode, at a point from which cor. 1, bears S 65°58' W, 46 lks. dist., hereinafter described.
	Thence across patented mineral claim.
15.60	Intersect line 3-4, M.S. 1113 Edgar lode, at a point from which cor. 4, bears S 65°50' W, 7.41 chs. dist., hereinafter described.
	Thence leave patented claim.
40.03	The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., set in a mound of stone, 3 1/2 ft. base, 10 ins. high, to top, with brass cap mkd.
	1/4 S15   S14 1916
	N 0°02' E, beginning new measurement.
20.01	Point for the N 1/16 sec. cor. of secs. 14 and 15.
- - -	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
	TION R5W N 1/16 S15   S14 1983

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	from which
	A utility pole, bears S 24° W, 22 lks. dist.
	Cor. is located inside a corral, 6 lks. E of a fence, extends N and S.
39.70	Dirt road, projects W.
40.02	The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., buried 6 ins. below the surface of a road, with brass cap mkd.
)	TION R5W S10   S11
	S15 S14 1916
	from which new bearing objects.
	A power pole, bears N 85°34' W, 12 lks. dist.
	A boulder, 16 x 9 x 3 ft. high, mkd. with an X on top, bears N 3°47' W, 58.5 lks. dist.
	From the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., set in a mound of stone, 5 ft. base, 1 ft. high, to top, with brass cap mkd.
	1/4 S11
	S14 1916
	N 89°54' W, bet. secs. 11 and 14.
i	Over mountainous terrain.
19.99	Point for the W 1/16 sec. cor. of secs. 11 and 14.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.

·	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	TION R5W S11 W 1/16 ——————————————————————————————————
	from which
	A granite boulder, 4 x 3 x 2 ft. high, bears S 55° W, 71 lks. dist., mkd. X BO.
	A granite boulder, 5 x 4 x 3 ft. high, bears N 74° W, 91 lks. dist., mkd. X BO.
	Set a steel fence post alongside the cor.
	Cor. is located 12 lks. N of a fence, extends E and W.
39.98	The cor. of secs. 10, 11, 14 and 15.
	From the cor. of secs. 3, 4, 33 and 34, on the S bdy. of the Tp., hereinbefore described.
	N 0°01' W, bet. secs. 33 and 34.
20.01	Point for the S 1/16 sec. cor. of secs. 33 and 34.
	Set an aluminum post, 72 ins. long, 3/4 in. diam., 67 ins. in the ground, with cap mkd.
	TION R5W S 1/16 S33   S34 1983
	Set a steel fence post alongside the cor.
40.02	The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd.
	1/4
	S33   S34
	1916
<u></u>	

	T 10 N, R 5 W, Gila and Sait River Mer., Arizona
CHAINS	
	N 0°01' W, beginning new measurement.
20.00	Point for the N 1/16 sec. cor. of secs. 33 and 34.
	Set an aluminum post, 72 ins. long, 3/4 in. diam., 68 ins. in the ground, with cap mkd.
	TION R5W N 1/16 S33   S34 1983
	Set a steel fence post alongside the cor.
40.00	The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 in. diam., set in a mound of stone, 3 ft. base, 1 ft. high, to top, with brass cap mkd.
	T1ON R5W S28   S27
	S33 S34 1916
	From the cor. of secs. 26, 27, 34 and 35.
	S 89°58' W, bet. secs. 27 and 34.
	Over mountainous terrain.
	Across a patented mineral claim.
7.88	Intersect line 3-4, M.S. 1971 Welcome No. 1 West lode, at a point from which cor. 4, identical with cor. 3, M.S. 1971 Hunter lode, bears N 77°20' W, 4.99 chs. dist., hereinafter described.
1	Thence leave patented mineral claim.
40.03	The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., projecting 4 ins. above a mound of stone, 1 1/2 ft. base, 6 ins. high, with brass cap mkd.
	1/4 S27
	S34 1916

S 89*58' W, beginning new measurement.  20.02 Point for the W 1/16 sec. cor. of secs. 27 and 34.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.  TION R5W  S27  W 1/16  S34  1983  Set a steel fence post alongside the cor.  The cor. of secs. 27, 28, 33 and 34.  N 0*03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  19.05  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00  Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  TION R5W  S 1/16  S28   S27  1983  40.00  The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4  S28   S27  1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound of stone, 4 ft. base, 2 ft. high, W, with brass cap mkd.		T 10 N, R 5 W, Gila and Salt River Mer., Arizona
Point for the W 1/16 sec. cor. of secs. 27 and 34.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.  TION R5W S27 W 1/16 S34 1983  Set a steel fence post alongside the cor.  The cor. of secs. 27, 28, 33 and 34.  N 0°03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00  Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  TION R5W S 1/16 S28   S27 1983  40.00  The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound	CHAINS	
Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.  TION R5W  S27  W 1/16  S34  1983  Set a steel fence post alongside the cor.  40.04  The cor. of secs. 27, 28, 33 and 34.  N 0°03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00  Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  TION R5W  S 1/16  S28   S27  1983  40.00  The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4  S28   S27  1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound post, 2 ins. diam., projecting 16 ins. above ground, with a mound		S 89°58' W, beginning new measurement.
ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.  TION R5W S27 W 1/16	20.02	Point for the W 1/16 sec. cor. of secs. 27 and 34.
W 1/16  W 1/16  S34  1983  Set a steel fence post alongside the cor.  The cor. of secs. 27, 28, 33 and 34.  N 0°03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00  Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W  S 1/16  S28   S27  1983  40.00  The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4  S28   S27  1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		ground, and in a mound of stone, 2 ft. base, to top, with cap
W 1/16		
Set a steel fence post alongside the cor.  40.04 The cor. of secs. 27, 28, 33 and 34.  N 0°03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00 Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  TION R5W S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		
The cor. of secs. 27, 28, 33 and 34.  N 0°03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00 Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		
N 0°03' W, bet. secs. 27 and 28.  Over relatively level terrain, through sagebrush.  19.05 Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00 Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		Set a steel fence post alongside the cor.
Over relatively level terrain, through sagebrush.  19.05  Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00  Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W S 1/16 S28   S27 1983  40.00  The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound	40.04	The cor. of secs. 27, 28, 33 and 34.
19.05 Track road, 25 lks. wide, bears N 65° E and S 65° W.  20.00 Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		N 0°03' W, bet. secs. 27 and 28.
20.00 Point for the S 1/16 sec. cor. of secs. 27 and 28.  Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		Over relatively level terrain, through sagebrush.
Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  Tlon R5W S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound	19.05	Track road, 25 lks. wide, bears N 65° E and S 65° W.
ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap mkd.  TION R5W S 1/16 S28   S27 1983  The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound	20.00	Point for the S 1/16 sec. cor. of secs. 27 and 28.
S 1/16 S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		ground, in a collar of stone, 3 ft. base, 1/2 ft. high, with cap
S28   S27 1983  40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4 S28   S27 1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound	3	TION R5W
40.00 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4  S28   S27  1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		· ·
post, 1 in. diam., projecting 1 in. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.  1/4  S28   S27  1916  From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound		
From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., projecting 16 ins. above ground, with a mound	40.00	post, 1 in. diam., projecting 1 in. above ground, with a mound of
post, 2 ins. diam., projecting 16 ins. above ground, with a mound		S28   S27
		post, 2 ins. diam., projecting 16 ins. above ground, with a mound

30

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	TION R5W S21   S22 S28   S27 1916
	N 0°01' E, bet. secs. 21 and 22.
	Over rugged, mountainous terrain.
20.045	Point for the S 1/16 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., wedged between boulders, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T10N R5W S 1/16 S21   S22 1986
	from which
	A granite boulder, 6 x 4 x 5 ft. high, bears N 45° E, 4 lks. dist., mkd. X BO.
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd.
	1/4 S21   S22 1916
	From this point, U.S.L.M. 1184, bears N 78°00' W, 28.17 chs. dist., hereinafter described.
	N 0°02' W, beginning new measurement.
	Intersect line 15-16, M.S. 1185 Cottonwood Placer, at a point from which cor. 16, bears N 83°02' E, 6.54 chs. dist., hereinafter described.

CHAINC	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Thence across a patented mineral claim.
10.88	Intersect line 17-18, M.S. 1185 Cottonwood Placer, at a point from which cor. 17, bears N 83°39' E, 6.31 chs. dist., hereinafter described.
	Thence leave patented mineral claim.
25.79	Intersect line 5-6, M.S. 1184 Saturn lode, at a point from which cor. 6, bears N 57°40' E, 60 lks. dist., hereinafter described.
	Thence across a patented mineral claim.
26.69	Intersect line 6-7, M.S. 1184 Saturn lode, at a point from which cor. 6, bears S 41°26' E, 77 lks. dist., hereinafter described.
	Thence leave patented mineral claim.
39.99	The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., set in a mound of stone, 2 ft. base, 1 ft. high, to top, with brass cap mkd.
	TION R5W S16   S15
	S21 S22 1916
	From the cor. of secs. 4, 5, 32 and 33, on the S bdy. of the Tp., hereinbefore described.
	N 0°02' W, bet. secs. 32 and 33.
	Over level terrain, through paloverde and creosote.
20.01	Point for the S 1/16 sec. cor. of secs. 32 and 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	TION R5W S 1/16 S32   S33 1983
,	Set a steel fence post alongside the cor.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Cor. is located 35 lks. E of a wash, 10 lks. wide, drains S 10° E.
40.02	The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd.
1	1/4
	S32   S33
	1916
	N 0°01' W, beginning new measurement.
20.00	Point for the N 1/16 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T10N R5W
	N 1/16
	S32   S33 1986
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.
	Set a steel fence post alongside the cor.
40.00	The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground, with a wood post, 4 x 4 ins. squared, projecting 4 ft. above ground, in a collar of stone, E, with brass cap mkd.
	T10N R5W
	S29   S28
	S32 S33
	1916
	From the cor. of secs. 27, 28, 33 and 34.
	S 89°59' W, bet. secs. 28 and 33.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Over level terrain.
20.015	Point for the E 1/16 sec. cor. of secs. 28 and 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	TION R5W
	E 1/16 ——
	s33 1983
40.03	True point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance, falls on the edge of a wash, where it is impractical to set a monument.
40.435	The witness 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., projecting 4 ins. above ground, with a wood post, 4 x 4 ins. square, projecting 3 1/2 ft. above a mound of stone, 2 ft. base, 6 ins. high, N, with brass cap mkd.
	1/4 S28
	——————————————————————————————————————
	S33 1916
	S 89°58' W, beginning new measurement.
19.61	Point for the W 1/16 sec. cor. of secs. 28 and 33.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10n R5w
	S28 W 1/16
	S33
	1983
39.625	The cor. of secs. 28, 29, 32 and 33.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 0°02' W, bet. secs. 28 and 29.
	Over level terrain, through relatively open area with sagebrush, catclaw and cacti.
20.00	Point for the S 1/16 sec. cor. of secs. 28 and 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R5W S 1/16 S29   S28 1983
40.00	The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with a wood post, 4 x 4 ins. square, projecting 4 ft. above ground, in a mound of stone, 2 ft. base, 6 ins. high, W, with brass cap mkd.
	1/4 S29   S28 1916
	From the cor. of secs. 21, 22, 27 and 28.
	S 89°59' W, bet. secs. 21 and 28.
	Over rolling terrain, through creosote.
20.005	Point for the E 1/16 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R5W S21 E 1/16 ——— S28 1986
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.

OTT A TOTO	T 10 N, R 5 W, Gila and Sait River Mer., Arizona
CHAINS	
	Thence over nearly level terrain.
40.01	The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd.
	1/4 S21
	S28 1916
	S 89°59' W, beginning new measurement.
40.06	The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., projecting 4 ins. above ground, with brass cap mkd.
	T10N R5W S20   S21
	S29 S28 1916
	N 0°02' W, bet. secs. 20 and 21.
	Over level terrain, through creosote.
19.995	Point for the S 1/16 sec. cor. of secs. 20 and 21.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	T10N R5W
	S 1/16 S20   S21 1983
28.707	Intersect line 2-3, M.S. 1704 A Jupiter lode, at a point from which cor. 2 of said lode, bears N 29°12' W, 1.522 chs. dist., hereinafter described.
	Thence across a patented mineral claim.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
30.260	Intersect line 1-2, M.S. 1704 A Jupiter lode, at a point from which cor. 2, bears S 73°09' W, 0.775 chs. dist., hereinafter described.
	Thence leave patented mineral claim.
39.99	The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W, with brass cap mkd.
	1/4 S20   S21 1916
	N 0°02' W, beginning new measurement.
40.00	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., set in a mound of stone, 2 1/2 ft. base, 2 ft. high, to top, with brass cap mkd.
	T10N   R5W S17   S16
	S20 S21 1916
	From the cor. of secs. 15, 16, 21 and 22.
	S 89°58' W, bet. secs. 16 and 21.
	Desc. over rugged, mountainous terrain.
40.06	The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.
	1/4 S16
	S21
	1916
	S 89°55' W, beginning new measurement.
40.06	The cor. of secs. 16, 17, 20 and 21.

	T 10 N, R 5 W, Glia and Salt River Mer., Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with a wood post, 4 x 4 ins. square, projecting 4 ft. above ground, in a small mound of stone, N, with brass cap mkd.
	1/4 S29
	S32 1916
	S 89°59' W, bet. secs. 29 and 32.
	Over rolling terrain, through scattering undergrowth.
20.00	Point for the W 1/16 sec. cor. of secs. 29 and 32.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, and in a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, to top, with cap mkd.
	T10N R5W S29
	W 1/16 ———
	S32 1983
40.00	The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., projecting 6 ins. above ground, with a wood post, 4 x 4 ins. square, projecting 3 ft. above a mound of stone, 2 1/2 ft. base, 1 ft. high, N, with brass cap mkd.
	T10N R5W S30   S29
	S31   S32 1916
	N 0°01' W, bet. secs. 29 and 30.
	Over nearly level terrain.
20.01	Point for the S 1/16 sec. cor. of secs. 29 and 30.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
:	T10N R5W S 1/16 S30   S29 1983
	from which
	A mesquite, 9 ins. diam., bears S 85° W, 92 lks. dist., mkd. S 1/16 S30 BT.
30.015	Point for the N-S 1/64 sec. cor. of secs. 29 and 30.
	Set an aluminum post, 72 ins. long, 3/4 in. diam., 68 ins. in the ground, with cap mkd.
	N-S 1/64 S30   S29 1983
35.017	Point for the N-N-S 1/256 sec. cor. of secs. 29 and 30.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	N-N-S 1/256 S30   S29 1983
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	From this point a local cor., bears East, 16 lks. dist., a rebar, 1/2 in. diam., projecting 1 in. above ground.
40.02	The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., projecting 4 ins. above ground, with brass cap mkd.
	1/4 s30   s29 1916
	N 0°01' W, beginning new measurement.
5.002	Point for the S-S-N 1/256 sec. cor. of secs. 29 and 30.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

	T 10 N, R 5 W, Glia and Sait River Mer., Arizona
CHAINS	
	S-S-N 1/256 S30   S29 1983
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
	From this point a steel pipe, 1 in. diam., projecting 3 ins. above ground, bears N 77° W, 15 lks. dist.,
10.005	Point for the S-N 1/64 sec. cor. of secs. 29 and 30.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	S-N 1/64 S30   S29 1983
	from which
	A power pole, bears N 66°17' E, 2.63 chs. dist.
	A power pole, bears N 78°49' W, 3.73 chs. dist.
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.
20.01	Point for the N 1/16 sec. cor. of secs. 29 and 30.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R5W N 1/16 S30   S29 1983
	from which
	A mesquite, 8 ins. diam., bears N 35° E, 41 lks. dist., mkd. N 1/16 S29 BT.
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.
40.02	The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., projecting 3 ins. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, S, with brass cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	T10N R5W S19   S20 ————————————————————————————————————
	From the cor. of secs. 20, 21, 28 and 29. West, bet. secs. 20 and 29.
	Over nearly level terrain, through creosote.
20.00	Point for the E 1/16 sec. cor. of secs. 20 and 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R5W S20 E 1/16 ——————————————————————————————————
40.00	The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., projecting 1 in. above ground, with a wood post, 4 x 4 ins. square, projecting 4 ft. above ground, S, with brass cap mkd.
	1/4 S20
	S29 1916
	S 89°57' W, beginning new measurement.
19.99	Point for the W 1/16 sec. cor. of secs. 20 and 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R5W
	W 1/16 ———
	\$29 1983

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.
39.98	The cor. of secs. 19, 20, 29 and 30.
	N 89°44' W, bet. secs. 19 and 30.
	Over nearly level terrain.
20.015	Point for the E 1/16 sec. cor. of secs. 19 and 30.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, to top, with cap mkd.
	T10N R5W S19 E 1/16 ——————————————————————————————————
40.03	The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with a wood post, 4 x 4 ins. square, projecting 3 ft. above a mound of stone, 1 1/2 ft. base, 1 ft. high, W, with brass cap mkd.
	1/4 S19
	S30 1916
	N 89°44' W, beginning new measurement
20.005	Point for the W 1/16 sec. cor. of secs. 19 and 30.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	T10N R5W
	S19 W 1/16 ———
	\$30 1983
	Set a steel fence post alongside the cor.
39.84	The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp., hereinbefore described.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.
	1/4 S18
	S19 1916
	N 89°58' W, bet. secs. 18 and 19.
	Over rolling land, through scattering undergrowth.
39.84	The closing cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., hereinbefore described.
	Subdivision of Section 12, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the true point for the 1/4 sec. cor. of secs. 12 and 13.
	N 0°06' E, on the N and S center line of sec. 12.
20.015	Point for the center S 1/16 sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over X chiseled in bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	C S 1/16   S12 C
	1986
	from which
	A juniper, 7 ins. diam., bears N 65° E, 12.5 lks. dist., mkd. CS 1/16 S12 BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
40.03	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 12.

#### Subdivision of Section 12, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
	T10N R5W C 1/4 S12 1983
	from which
	A granite boulder, 7 x 5 x 4 ft. above ground, bears N 42° E, 32 lks. dist., mkd. X BO.
	A forked alligator juniper, 6 ins. diam., bears S 70° E, 63 lks. dist., mkd. C 1/4 S12 BT.
	Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.
	Cor. is located on a spur, slopes W.
80.03	The true point for the 1/4 sec. cor. of secs. 1 and 12, hereinbefore described
	From the 1/4 sec. cor. of sec. 12 only, on the E bdy. of the Tp.
	S 89°59' W, on the E and W center line of sec. 12.
20.02	Point for the center E 1/16 sec. cor. of sec. 12.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	$   \begin{array}{c}                                     $
	from which
	A forked alligator juniper, 12 ins. diam., bears S 45° E, 6.5 lks. dist., mkd. X BT.
	A forked alligator juniper, 12 ins. diam., bears S 79° W, 76.5 lks. dist., mkd. C E 1/16 S12 BT.
	Cor. is located on a spur, slopes NE.
40.04	The center 1/4 sec. cor. of sec. 12, hereinbefore described.
L	

#### Subdivision of Section 12, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
80.04	The 1/4 sec. cor. of secs. 11 and 12, hereinbefore described.
	SE 1/4 Section 12
	From the E 1/16 sec. cor. of secs. 12 and 13, hereinbefore described.
	N 0°15' E, on the N and S center line of the SE 1/4 of sec. 12.
20.03	Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE 1/4 of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	SE 1/16 S12 1986
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of cor.
40.05	The center E 1/16 sec. cor. of sec. 12.
	From the S 1/16 sec. cor. of sec. 12 only, on the E bdy. of the Tp., hereinbefore described.
	West, on the E and W center line of the SE 1/4 of sec. 12.
19.97	The SE 1/16 sec. cor. of sec. 12.
39.94	The center S 1/16 sec. cor. of sec. 12.
	Subdivision of Section 14, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 14 and 23.
	N 0°01' W, on the N and S center line of sec. 14.
39.98	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 14.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.

### Subdivision of Section 14, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	1 10 N, N 5 W, GITA AND BATE RIVEL PEL ., ALIZONA
CHAINS	
	T10N R5W
	C 1/4 S14 1983
	from which
	A rock outcropping, 12 x 10 x 8 ins. above ground, bears S 10 1/2° E, 6.5 lks. dist., mkd. X BO.
	A granite boulder, 24 x 12 x 10 ins. above ground, bears N 36° W, 21.5 lks. dist., mkd. X BO.
	From this cor., U.S. Geological Survey triangulation station "DISH 1969", bears S 39°57' W, forward bearing, 25.01 chs. dist., monumented with a brass tablet, 2 ins. diam., set in a granite boulder, 4 x 2 x 1 1/2 ft. above ground, mkd. ARIZONA HIGHWAY DEPT P&M DISH 1964, and a triangle in the middle.
59.99	Point for the center N 1/16 sec. cor. of sec. 14.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole on a rock shelf, 4 ft. long, 2 ft. wide, 6 ins. high, mkd.
	C N 1/16   S14
	1983
	from which
	A granite boulder, 5 x 4 x 3 ft. above ground, bears N 9° E, 24 lks. dist., mkd. X BO.
	A granite boulder, 4 x 3 x 2 ft. above ground, bears S 66° E, 25.5 lks. dist., mkd. X BO.
	Cor. is located 10 lks. E of a fence, extends N and S.
80.00	The 1/4 sec. cor. of secs. 11 and 14, hereinbefore described.
	From the 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., projecting 4 ins. above ground, with a mound of stone, 6 ft. base, 2 ft. high, W, with brass cap mkd.
	1/4 S14   S13 1916
	N 89°53' W, on the E and W center line of sec. 14.

#### Subdivision of Section 14, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arızona
CHAINS	
39.98	The center 1/4 sec. cor. of sec. 14.
53.52	Intersect line 3-4, M.S. 1115 Triangle lode, at a point from which cor. 3, bears S 44°58' E, 4.10 chs. dist., hereinafter described,
	Thence across patented mineral claims.
60.00	Point for the center W 1/16 sec. cor. of sec. 14.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	C W 1/16 S14 1983
	Set a steel fence post alongside the cor.
68.23	Intersect line 3-4, M.S. 1114 Edmond lode, at a point from which cor. 4, bears S 38°02' W, 11.18 chs. dist., hereinafter described.
	Thence leave patented mineral claims.
80.02	The 1/4 sec. cor. of secs. 14 and 15.
	NW1/4 Section 14
	From the center W 1/16 sec. cor. of sec. 14.
	N 0°01' E, on the N and S center line of the NW 1/4 of sec. 14.
	Across a patented mineral claim.
7.23	Intersect line 2-3, M.S. 1114 Edmond lode, at a point from which cor. 3, bears N 37°03' W, 2.11 chs. dist., hereinafter described.
	Thence leave patented mineral claim.
20.01	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 14.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.

#### Subdivision of Section 14, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	NW 1/16 S14 1983
	from which
	A granite boulder, 8 x 7 x 6 ft. above ground, bears N 50 1/2° E, 66 lks. dist., mkd. X BO.
	A granite boulder, 2 x 2 x 2 ft. above ground, bears N 32° W, 15.5 lks. dist., mkd. X BO.
	Set a steel fence post alongside the cor.
40.02	The W 1/16 sec. cor. of secs. 11 and 14.
-	From the center N 1/16 sec. cor. of sec. 14.
	N 89°54' W, on the E and W center line of the NW 1/4 of sec. 14.
20.01	The NW 1/16 sec. cor. of sec. 14.
40.02	The N 1/16 sec. cor. of secs. 14 and 15.
	Subdivision of Section 19, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 19 and 30.
	North, on the N and S center line of sec. 19.
19.96	Point for the center S 1/16 sec. cor. of sec. 19.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	S 1/16   S19
	_
	1986 1983
	Set a steel fence post alongside the cor.

Subdivision of Section 19, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
20.025	A rebar, 3/4 in. diam., projecting 4 ins. above ground, with plastic cap mkd. YAVAPAI COUNTY.
32.13	U.S. Highway 89, 28 ft. wide, bears N 39 3/4° E and S 39 3/4° W.
39.92	Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E and W center line of sec. 19.
	Set an aluminum post, 36 ins. long, 3/4 ins. diam., 26 ins. in the ground, with cap mkd.
	T10N R5W
	C 1/4 S19
	1986
	1983
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of cor.
	Set a steel fence post alongside the cor.
40.05	A rebar, 3/4 in. diam., projecting 2 ins. above ground.
79.83	The 1/4 sec. cor. of secs. 18 and 19.
•	
	From the 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd.
j	1/4
	S19   S20
	1916
	N 89°52' W, on the E and W center line of sec. 19.
33.55	U.S. Highway 89, 28 ft. wide, bears N 39 3/4° E and S 39 3/4° W.
40.02	The center 1/4 sec. cor. of sec. 19.
60.02	Point for the center W 1/16 sec. cor. of sec. 19.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.

## Subdivision of Section 19, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	C W 1/16 C S19 1986 1983
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of cor.
	Set a steel fence post alongside the cor.
79.86	The 1/4 sec. cor. of sec. 19 only, on the W bdy. of the Tp., hereinbefore described.
	SW 1/4 Section 19
	From the W 1/16 sec. cor. of secs. 19 and 30.
	North, on the N and S center line of the SW 1/4 of sec. 19.
8.00	U.S. Highway No. 89, 28 ft. wide, bears N 39° E and S 39° W.
19.94	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 19.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.  SW 1/16 S19  1986  1983
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
39.88	The center W 1/16 sec. cor. of sec. 19.
	From the center S 1/16 sec. cor. of sec. 19.
	N 89°48' W, on the E and W center line of the SW 1/4 of sec. 19.
10.10	U.S. Highway 89, 28 ft. wide, bears N 39 3/4° E and S 39 3/4° W.
20.005	The SW 1/16 sec. cor. of sec. 19.
39.84	The S 1/16 sec. cor. of sec. 19 only, on the W bdy. of the Tp., hereinbefore described.

### Subdivision of Section 20, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 20 and 29.
	N 0°02' W, on the N and S center line of sec. 20.
19.99	Point for the center S 1/16 sec. cor. of sec. 20.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	s 1/16 C S20
	1983
39.98	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 20.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
į	T10N R5W
	C 1/4 S20 1983
	1963
79.97	The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., set in a mound of stone, 2 ft. base, 6 ins. high, to top, with brass cap mkd.
	1/4   S17
	S22 S20 1916
	Remark the brass cap to read
	T10N R5W
	1/4 ———
	S20
	1983 1916
	1910

### Subdivision of Section 20, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 20 and 21.
	S 89°59' W, on the E and W center line of sec. 20.
20.00	Point for the center E 1/16 sec. cor. of sec. 20.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	E 1/16
	c — c
	S20 1983
40.00	The center 1/4 sec. cor. of sec. 20.
79.97	The 1/4 sec. cor. of secs. 19 and 20.
	SE1/4 Section 20
	From the E 1/16 sec. cor. of secs. 20 and 29.
	N 0°02' W, on the N and S center line of the SE 1/4 of sec. 20.
19.99	Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE 1/4 of sec. 20.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	SE 1/16 S20 1983
39.99	The center E 1/16 sec. cor. of sec. 20.
39.99	
	From the S 1/16 sec. cor. of secs. 20 and 21.
	S 89°59' W, on the E and W center line of the SE 1/4 of sec. 20.
19.99	The SE 1/16 sec. cor. of sec. 20.
39.99	The center S 1/16 sec. cor. of sec. 20.

#### Subdivision of Section 21, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	1 10 N, K J W, GIIA AND SAIL RIVER MEI., ALIZONA
CHAINS	
	From the 1/4 sec. cor. of secs. 21 and 28.
	N 0°03' W, on the N and S center line of sec. 21.
8.135	Intersect line 2-3, M.S. 2139 Diamond placer, at a point from which cor. no. 2, hereinafter described, bears N 61°04' E, 3.325 chs. dist.
	Thence across patented mineral claims.
12.70	Dirt road, 25 lks. wide, bears N 35° E and S 35° W.
20.025	Point for the center S 1/16 sec. cor. of sec. 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	C S 1/16   S21 C 1986
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of cor.
	Set a steel fence post alongside the cor.
40.05	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T10N R5W C 1/4 S21 1986
	from which
	A granite boulder, 6 x 5 x 5 ft. above ground, bears N 25°30' W, 35.5 lks. dist., mkd. XBO.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
47.11	Intersect line 3-4, M.S. 1184 Planet lode, at a point from which cor. 4, hereinafter described, bears S 48°34' W, 0.41 chs. dist.

### Subdivision of Section 21, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Thence leave patented mineral claims.
80.06	The 1/4 sec. cor. of secs. 16 and 21.
	From the 1/4 sec. cor. of secs. 21 and 22.
	S 89°55' W, on the E and W center line of sec. 21.
15.57	Intersect line 24-25, M.S. 1185 Mesa placer, at a point from which cor. 25, on line 18-15, M.S. 1185 Cottonwood Placer, bears N 61°18' E, 4.16 chs. dist. hereinafter described.
	Thence across patented mineral claims.
20.025	True point for the center E 1/16 sec. cor. of sec. 21, falls on the E face of a large boulder where it is impractical to set a monument.
	From this point, the point selected for the witness center E 1/16 sec. cor. of sec. 21, bears S 45°00' E, 0.93 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	C — C S21 1986
	from which
	A granite boulder, 12 x 10 x 8 ft. above ground, bears S 52° E, 11 lks. dist., mkd. + BR WC.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
I	

### Subdivision of Section 21, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
34.895	Intersect line 9-10, M.S. 1185 Oro Fino placer, at a point from which cor. 1, M.S. 1184 Planet lode on line 9-10, M.S. 1185 Oro Fino placer, bears N 60°36' E, 0.345 chs. dist., and from which cor. 9, identical with cor. 1, Scott placer and cor. 4 Comet lode, both of M. S. 1704A, bears S 60°36' W, 0.610 chs. dist., hereinafter described.
	Thence leave patented mineral claims.
35.59	Intersect line 4-1 E, M.S. 1704A Comet lode, at a point from which cor. 4, identical with cor. 9, M.S. 1185 Oro Fino placer, and cor. 1, M.S. 1704A Scott placer, bears S 28°37' E, 0.34 chs. dist. and from which cor. 1, bears N 28°37' W, 3.995 chs. dist., hereinafter described.
	Thence across patented mineral claim.
40.05	The center 1/4 sec. cor. of sec. 21.
52.80	Intersect line 1-2, M.S. 1704A Comet lode, at a point from which cor. 2, identical with cor. 1, M.S. 1704A Jupiter lode, on line 3-4, M.S. 1704A Side Issue lode, bears S 61°54' W, 7.36 chs. dist. hereinafter described.
	Thence leave patented mineral claim.
55.945	Intersect line 1-4, M.S. 1704A Side Issue lode, at a point from which cor. 4, bears S 24°29' E, 2.35 chs. dist. hereinafter described.
	Thence across a patented mineral claim.
71.35	Wash, 100 lks. wide, drains S 10° W.
77.635	Intersect line 1-2, M.S. 1704A Side Issue lode, at a point from which cor. 2, bears S 72°10' W, 2.54 chs. dist. hereinafter described.
	Thence leave patented mineral claim.
80.10	The 1/4 sec. cor. of secs. 20 and 21.
	SE 1/4 Section 21
	From the E 1/16 sec. cor. of secs. 21 and 28, hereinbefore described.

#### Subdivision of Section 21, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 0°01' W, on the N and S center line of the SE 1/4 of sec. 21.
20.035	Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE 1/4 of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	SE 1/16 S21 1986
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
37.64	Intersect line 24-25, M.S. 1185 Mesa placer, at a point from which cor. 24, bears S 61°18' W, 0.615 chs. dist. hereinafter described.
	Thence across a patented mineral claim.
40.07	True point for the center E 1/16 sec. cor. of sec. 21.
	From the S 1/16 sec. cor. of secs. 21 and 22.
	S 89°57' W, on the E and W center line of the SE 1/4 of sec. 21.
20.015	The SE 1/16 sec. cor. of sec. 21.
22.335	Intersect line 1-2, M.S. 1185 Golden Bowl placer, at a point from which cor. 1, bears S 12°52' W, 6.87 chs. dist. hereinafter described.
	Thence across patented mineral claims.
34.60	Dirt road, 25 lks. wide, bears N 25° E and S 25° W.
40.03	The center S 1/16 sec. cor. of sec. 21.

# Subdivision of Section 24, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 24 and 25.
	N 0°01' E, on the N and S center line of sec. 24.
20.02	The center S 1/16 sec. cor. of sec. 24, monumented with a rebar, 3/4 in. diam., projecting 3 ins. above ground, established by persons unknown. This is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top with cap mkd.
	C S 1/16   S24 C 1983
	Deposit the rebar alongside the aluminum post.
	N.0°01' E., beginning new measurement
20.02	The center 1/4 sec. cor., established by persons unkown, monumented with a rebar, 3/4 in. diam. set 3 ins. below the surface of a road, at intersection with the E and W center line of sec. 24. This is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum cap, 3 ins. diam., on top of same rebar, 3 ins. below the surface of a road, with cap mkd.
	T10N R5W C 1/4 S24 1983
	from which
	A power pole with a spike, 2 ft. above base, bears S 39 1/4° E, 198 lks. dist.
	An aluminum post, 36 ins. long, 3/4 in. diam., set 34 ins. in the ground, and in a mound of stone, 2 ft. base, to top, for a reference monument, bears N 43° W, 29.7 ft. dist., with cap mkd. C 1/4 S24 29.7 FT RM 1983, and an arrow pointing to the cor.
1	1

# Subdivision of Section 24, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	A power pole with a spike, 5 ft. above base, bears N 27 1/2° W, 126 lks. dist.
	Cor. is located 14 lks. N of center of road, bears S 50° E and N 65° W.
	N 0° 01'E, beginning new measurement
39.99	The 1/4 sec. cor. of secs. 13 and 24.
	From the 1/4 sec. cor. of sec. 24 only, on the E bdy. of the Tp., hereinbefore described.
	S 89°59' W, on the E and W center line of sec. 24.
19.98	Point for the center E 1/16 sec. cor. of sec. 24.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	E 1/16
	C ———— C S24
	1983
	from which
	A boulder, 3 x 3 x 2 ft. above ground, bears S 6° E, 11.5 lks. dist., mkd. with an X on top.
·	A steel pipe, 8 1/2 ins. diam., 1/4 in. thick, projecting 16 ins. above ground, encasing a turn valve, bears N 16° W, 23 lks. dist.
	Cor. is located at the base of an earth dam.
20.15	A pipe, 5 ins. diam.
20.25	A fence, extends N and S.
22.10	Track road, 20 lks. wide, bears N and S.
39.96	The center 1/4 sec. cor. of sec. 24.

### Subdivision of Section 24, T 10 N. R 5 W. Gila and Salt River Mer. Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 89°59'W, beginning new measurement
39.96	The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., projecting 3 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N, with brass cap mkd.
	1/4 23   24 1916
	Rebuilt the mound of stone, 3 ft. base, 2 ft. high, W of cor.
	SE 1/4 Section 24
	From the E 1/16 sec. cor. of secs. 24 and 25.
	N 0°01' W, on the N and S center line of the SE 1/4 of sec. 24.
20. 01	The SE 1/16 sec. cor. of sec. 24, established by persons unknown, monumented with a rebar, 1/2 in. diam., projecting 5 ins. above ground. This is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, 1/2 ft. high, with cap mkd.
	SE 1/16 S24 1983
	Cor. is located S 5°42' W, 124 lks. dist. from a fence cor. post, extends North and N 85°58' E, 196 lks. dist. from the SE cor. of a barn foundation.
	Deposit the rebar alongside the aluminum post.
	N 0° 01 W, beginning new measurement
20.01	The center E 1/16 sec. cor. of sec. 24.
	From the S 1/16 sec. cor. of sec. 24 only, on the E bdy. of the Tp., hereinbefore described.

### Subdivision of Section 24, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
]	S 89°57' W, on the E and W center line of the SE 1/4 of sec. 24.
19.98	The SE 1/16 sec. cor. of sec. 24.
	S 89° 57'W, beginning new measurement
19.98	The center S 1/16 sec. cor. of sec. 24.
	Subdivision of Section 28, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the true point for the 1/4 sec. cor. of secs. 28 and 33.
	N 0°01' W, on the N and S center line of sec. 28.
20.00	Point for the center S 1/16 sec. cor. of sec. 28.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.
	C S 1/16   S28 C 1983
	1983
40.00	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 28.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	T10N R5W
	C 1/4 S28 1983
80.00	The 1/4 sec. cor. of secs. 21 and 28.
	From the 1/4 sec. cor. of secs. 27 and 28.
	West, on the E and W center line of sec. 28.
20.01	Point for the center E 1/16 sec. cor. of sec. 28.
L	

#### Subdivision of Section 28, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	E 1/16
	c — c
	S28 1983
40.02	The center 1/4 sec. cor. of sec. 28.
60.04	Point for the center W 1/16 sec. cor. of sec. 28.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top with cap mkd.
	W 1/16
	c ——— c
	S28 1983
	1903
	from which
	A power pole, bears N 54°40' W, 1.47 chs. dist.
61.70	A power line road, 14 lks. wide, bears N 25° E and S 25° W.
80.06	The 1/4 sec. cor. of secs. 28 and 29.
	SE 1/4 Section 28
	From the E 1/16 sec. cor. of secs. 28 and 33.
	N 0°01' W, on the N and S center line of the SE 1/4 of sec. 28.
20.00	Point for the SE 1/16 sec. cor., at intersection with the E and W center line of the SE 1/4 of sec. 28.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	SE 1/16 S28 1983
40.00	The center E 1/16 sec. cor. of sec. 28.

### Subdivision of Section 28, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the S 1/16 sec. cor. of secs. 27 and 28.
	S 89°58' W, on the E and W center line of the SE 1/4 of sec. 28.
20.01	The SE 1/16 sec. cor. of sec. 28.
40.02	The center S 1/16 sec. cor. of sec. 28.
	SW 1/4 Section 28
	From the W 1/16 sec. cor. of secs. 28 and 33.
	N 0°02' W, on the N and S center line of the SW 1/4 of sec. 28.
20.00	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 28.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	SW 1/16 S28 1983
40.00	The center W 1/16 sec. cor. of sec. 28.
	From the center S 1/16 sec. cor. of sec. 28.
	S 89°58' W, on the E and W center line of the SW 1/4 of sec. 28.
20.02	The SW 1/16 sec. cor. of sec. 28.
40.04	The S 1/16 sec. cor. of secs. 28 and 29.
	Subdivision of Section 29, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 29 and 32.
	N 0°02' W, on the N and S center line of sec. 29.

#### Subdivision of Section 29, T 10 N, R 5 W, Gila and Salt River Mer. Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
20.01	Point for the center S 1/16 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	S 1/16   S29
	1983
40.02	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	T10N R5W C 1/4 S29
	1983
60.03	Point for the center N 1/16 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	C 220
	N 1/16 C S29
	1983
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.
80.04	The 1/4 sec. cor. of secs. 20 and 29.
	From the 1/4 sec. cor. of secs. 28 and 29.
	S 89°58' W, on the E and W center line of sec. 29.
40.00	The center 1/4 sec. cor. of sec. 29.

#### Subdivision of Section 29, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
60.00	Point for the center W 1/16 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	C W 1/16 S29 1983
	Raise a mound of stone, 2 1/2 ft. base, 16 ins. high, W of cor.
70.00	Point for the center W-W 1/64 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	S29 C W W 1/64 1983
80.00	The 1/4 sec. cor. of secs. 29 and 30.
	SW 1/4 Section 29
	From the W 1/16 sec. cor. of secs. 29 and 32.
	N 0°01' W, on the N and S center line of the SW 1/4 of sec. 29.
20.01	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	SW 1/16 S29 1983
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.

#### Subdivision of Section 29, T 10 N. R 5 W. Gila and Salt River Mer., Arizon

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
30.01	Point for the center N-SW 1/64 sec. cor. of sec. 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	S29
İ	C-N-SW
	1/64
1	1983
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.
40.01	The center W 1/16 sec. cor. of sec. 29.
	From the center S 1/16 sec. cor. of sec. 29.
	S 89°59'W, on the E and W center line of the SW 1/4 of sec. 29.
20.00	The SW 1/16 sec. cor. of sec. 29.
30.00	Point for the center W-SW 1/64 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 1 1/2 ft. base, to top with cap mkd.
	S29
	C-W-SW
	1/64
1	1983
	from which
	A paloverde, 6 ins. diam., bears S 4° W, 83 lks. dist., mkd. X BT.
40.00	The S 1/16 sec. cor. of secs. 29 and 30.
	From the center W-SW 1/64 sec. cor. of sec. 29.
	N 0°01' W, on the N and S center line of the NW 1/4 of the SW 1/4 of sec. 29.
	<u> </u>

# Subdivision of Section 29, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
10.00	Point for the NW-SW 1/64 sec. cor., at intersection with the E and W center line of the NW 1/4 of the SW 1/4 of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	S29
	NW-SW 1/64
	1983
14.40	Dirt road, 32 lks. wide, bears S 65° E and N 65° W.
15.00	Point for the center N-NW-SW 1/256 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top with cap mkd.
	S29
	C-N-NW-SW
	1/256
	1983
20.00	The center W-W 1/64 sec. cor. of sec. 29.
	From the center N-SW 1/64 sec. cor. of sec. 29.
	S 89°58' W, on the E and W center line of the NW 1/4 of the SW 1/4 of sec. 29.
10.00	The NW-SW 1/64 sec. cor. of sec. 29.
20.00	The N-S 1/64 sec. cor. of secs. 29 and 30.
	NW 1/4 Section 29
	From the center W 1/16 sec. cor. of sec. 29.
	N 0°01' W, on the N and S center line of the NW 1/4 of sec. 29.
10.01	Point for the center S-NW 1/64 sec. cor. of sec. 29.
10.01	TOTAL TOT CHE CENTET B INV 1/04 Sec. COI. OI Sec. 25.

#### Subdivision of Section 29, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
	S29 C-S-NW 1/64 1983
20.02	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	NW 1/16 S29 1983
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.
40.03	The W 1/16 sec. cor. of secs. 20 and 29.
	From the center N 1/16 sec. cor. of sec. 29.
	S 89°58' W, on the E and W center line of the NW 1/4 of sec. 29.
19.99	The NW 1/16 sec. cor. of sec. 29.
29.99	Point for the center W-NW 1/64 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	S29
	C-W-NW
	1/64
	1983
39.99	The N 1/16 sec. cor. of secs. 29 and 30.
	From the center W-W 1/64 sec. cor. of sec. 29.
	N0°01' W, on the N and S center line of the SW 1/4 of the NW 1/4 of sec. 29.

#### Subdivision of Section 29, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
5.005	Point for the center S-SW-NW 1/256 sec. cor. of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
	S29 C-S-SW-NW 1/256 1983
10.01	Point for the SW-NW 1/64 sec. cor., at intersection with the E and W center line of the SW 1/4 of the NW 1/4 of sec. 29.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, and in a mound of stone, 2 ft. base, to top high, with cap mkd.
	S29
	SW NW
	1/64 1983
20.02	The center W-NW 1/64 sec. cor. of sec. 29.
	From the center S-NW 1/64 sec. cor. of sec. 29.
	S 89°59' W, on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 29.
10.00	The SW-NW 1/64 sec. cor. of sec. 29.
20.00	The S-N 1/64 sec. cor. of secs. 29 and 30.

#### Subdivision of Section 30, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

		T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	CHAINS	
		From the 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., projecting 2 ins. above a mound of stone, 1 1/2 ft. base, 6 ins. high, with a 4 x 4 in. square wood post, projecting 3 ft. above a mound of stone, 2 1/2 ft. base, 2 ft. high, N, with brass cap mkd.
		1/4 S30 S31 1916
		N 0°01' W, on the N and S center line of sec. 30.
	39.45	A track road, 14 lks. wide, bears E and W.
	39.93	Fence, extends E and W.
	40.04	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 30.
		Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
		T10N R5W C 1/4 S30 1983
		Set a steel fence post near the cor.
		From this cor., U.S. Geological Survey triangulation station "LADY 1969", bears N 69°51' W, (forward bearing) 7.04 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., set in a concrete base, 4 x 4 x 2 ins. above ground, mkd. ARIZONA HIGHWAY DEPT P&M LADY 1964 and a triangle in the center.
	60.08	Point for the center N 1/16 sec. cor. of sec. 30.
		Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top with cap mkd.
		N 1/16   S30 C
		1983
١		

### Subdivision of Section 30, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set a steel fence post alongside the cor.
80.12	The 1/4 sec. cor. of secs. 19 and 30.
	From the 1/4 sec. cor. of secs. 29 and 30, hereinbefore described.
	N 89°50' W, on the E and W center line of sec. 30.
20.01	Point for the center E 1/16 sec. cor. of sec. 30.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	C — E 1/16 S30 1983
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of cor.
38.70	Track road, bears N and S.
40.02	The center 1/4 sec. cor. of sec. 30.
79.91	The 1/4 sec. cor. of secs. 25 and 30, on the W bdy. of the Tp.
	NE 1/4 Section 30
	From the center E 1/16 sec. cor. of sec. 30.
	North, on the N and S center line of the NE 1/4 of sec. 30.
20.025	Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE 1/4 of sec. 30.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	NE 1/16 S30 1983
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of cor.
40.05	The E 1/16 sec. cor. of secs. 19 and 30.

# Subdivision of Section 30, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the N 1/16 sec. cor. of secs. 29 and 30.
	N 89°47' W, on the E and W center line of the NE 1/4 of sec. 30.
20.01	The NE 1/16 sec. cor. of sec. 30.
40.02	The center N 1/16 sec. cor. of sec. 30.
	Subdivision of Section 33, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 4 and 33, on the S bdy. of the Tp.
	N 0°01' W, on the N and S center line of sec. 33.
20.005	Point for the center S 1/16 sec. cor. of sec. 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.
	S 1/16   S33 C 1983
	Set a steel fence post alongside the cor.
40.01	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	T10N R5W C 1/4 S33 1983
	Set a steel fence post alongside the cor.
42.20	Road, 64 lks. wide, bears SE and NW.

### Subdivision of Section 33, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
60.02	Point for the center N 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, ft. base, to top, with brass cap mkd.
	C N 1/16   S33 C 1986
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
80.03	True point for the 1/4 sec. cor. of secs. 28 and 33.
	From the 1/4 sec. cor. of secs. 33 and 34.
	S 89°58' W, on the E and W center line of sec. 33.
19.40	Wash, 50 lks. wide, drains S 40° E.
20.02	Point for the center E 1/16 sec. cor. of sec. 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	E 1/16
	C ——— C
	1983
	Set a steel fence post alongside the cor.
40.04	The center 1/4 sec. cor. of sec. 33.
60.05	Point for the center W 1/16 sec. cor. of sec. 33.

# Subdivision of Section 33, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 ft. base, to top with cap mkd.
;	c W 1/16 S33 1983
	Set a steel fence post alongside the cor.
80.06	The 1/4 sec. cor. of secs. 32 and 33.
	SE 1/4 Section 33
	From the E 1/16 sec. cor. of secs. 4 and 33, on the S bdy. of the Tp.
	N 0°01' W, on the N and S center line of the SE 1/4 of sec. 33.
20.00	Point for the SE $1/16$ sec. cor., at intersection with the E and W center line of the SE $1/4$ of sec. 33.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	SE 1/16 S33 1983
40.01	The center E 1/16 sec. cor. of sec. 33.
	From the S 1/16 sec. cor. of secs. 33 and 34.
	S 89°57' W, on the E and W center line of the SE 1/4 of sec. 33.
20.02	The SE 1/16 sec. cor. of sec. 33.
40.04	The center S 1/16 sec. cor. of sec. 33.
	SW 1/4 Section 33
	From the W 1/16 sec. cor. of secs. 4 and 33, on the S bdy. of the Tp., hereinbefore described.
	N 0°02' W, on the N and S center line of the SW 1/4 of sec. 33.

# Subdivision of Section 33, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona	
CHAINS		
20.01	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 33.	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with cap mkd.	
	SW 1/16 S33 1983	
	Set a steel fence post alongside the cor.	
40.02	The center W 1/16 sec. cor. of sec. 33.	
	NW 1/4 Section 33	
	From the center S 1/16 sec. cor. of sec. 33.	
	S 89°58' W, on the E and W center line of the SW 1/4 of sec. 33.	
20.01	The SW 1/16 sec. cor. of sec. 33.	
40.02	The S 1/16 sec. cor. of secs. 32 and 33.	
	From the center W 1 1/16 sec. cor. of sec. 33.	
	N 0°01' W, on the N and S center line of the NW 1/4 of sec. 33.	
20.005	Point for the NW /16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 33.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	NW 1/16 S33 1986	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.	
	Set a steel fence post alongside the cor.	
40.01	The W 1/16 sec. cor. of secs. 28 and 33.	

# Subdivision of Section 33, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From the center N 1/16 sec. cor. of sec. 33.
	S 89°58' W, on the E and W center line of the NW 1/4 of sec. 33.
4.90	Graded road, 40 lks. wide, bears S 10° E and N 10° W.
20.01	The NW 1/16 sec. cor. of sec. 33.
40.02	The N 1/16 sec. cor. of secs. 32 and 33.
	Subdivision of Section 34, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of secs. 3 and 34, on the S bdy. of the Tp.
	North, on the N and S center line of sec. 34.
20.02	Point for the center S 1/16 sec. cor. of sec. 34.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	C S 1/16   S34 C 1983
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.
	Set a steel fence post alongside the cor.
	Cor. is located 1.50 chs. W of a wash, 60 lks. wide, drains SW.
40.04	Point for the center 1/4 sec. cor., at intersection with the E and W center line of sec. 34.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top with cap mkd.
	T10N R5W C 1/4 S34 1983
	Set a steel fence post alongside the cor.

# Subdivision of Section 34, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona	
CHAINS		
40.70	Wash, 50 lks. wide, drains W.	
60.03	Point for the center N 1/16 sec. cor. of sec. 34.	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top with cap mkd.	
	N 1/16 C S34	
	1983	
	Set a steel fence post alongside the cor.	
80.02	The 1/4 sec. cor. of secs. 27 and 34.	
	From the 1/4 sec. cor. of secs. 34 and 35.	
	S 89°56' W, on the E and W center line of sec. 34.	
40.02	The center 1/4 sec. cor. of sec. 34.	
60.03	Point for the center W 1/16 sec. cor. of sec. 34.	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 1 1/2 ft. base, to top with cap mkd.	
	W 1/16	
	C ————— C	
	1983	
	Set a steel fence post alongside the cor.	
80.04	The 1/4 sec. cor. of secs. 33 and 34.	
	SW1/4 Section 34	
	From the W 1/16 sec. cor. of secs. 3 and 34, on the S bdy. of the Tp.	
	North, on the N and S center line of the SW 1/4 of sec. 34.	
20.01	Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW 1/4 of sec. 34.	

# Subdivision of Section 34, T 10 N, R 5 W, Gila and Salt River Mer., Arizona

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 72 ins. long, 3/4 in. diam., 68 ins. in the ground, with cap mkd.
	SW 1/16 S34 1983
	Set a steel fence post alongside the cor.
	Cor. is located 60 lks. W of a wash, 9 lks. wide, drains S 20° W.
40.02	The center W 1/16 sec. cor. of sec. 34.
	From the center S 1/16 sec. cor. of sec. 34.
	S 89°57' W, on the E and W center line of the SW 1/4 of sec. 34.
20.01	The SW 1/16 sec. cor. of sec. 34.
40.02	The S 1/16 sec. cor. of secs. 33 and 34.
	NTU 1/4 Continu 24
	NW 1/4 Section 34
	From the center W 1/16 sec. cor. of sec. 34.
	North, on the N and S center line of the NW 1/4 of sec. 34.
19.99	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW 1/4 of sec. 34.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	NW 1/16 S34 1983
	Set a steel fence alongside the cor.
39.99	The W 1/16 sec. cor. of secs. 27 and 34.
	From the center N 1/16 sec. cor. of sec. 34.
	S 89°57' W, on the E and W center line of the NW 1/4 of sec. 34.
20.02	The NW 1/16 sec. cor. of sec. 34.

# Subdivision of Section 34 T 10 N, R 5 W, Gila and Salt River Mer., Arizona


	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
40.04	The N 1/16 sec. cor. of secs. 33 and 34.
	Dependent Resurvey of Portions of Certain Mineral Surveys, T 10 N, R 5 W, Gila and Salt River Mer., Arizona
	Mineral Survey No. 1201 Mother Lode
	From Cor. 1, M.S. 1201 Mother lode, monumented with a granite stone, 6 x 12 x 30 ins. above ground, mkd. ML NO 1 1201 on W face, from which an original bearing object
	A granite boulder, 3 1/2 x 3 x 3 ft. above ground, bears S 38°22' W, 95.8 lks. dist., mkd. B + R ML NO 1 1201. (Record dist. 96.2 lks.)
	Not remonumented
	N 87°29' W, on line 1-2, M.S. 1201 Mother lode.
22.24	Cor. 2, M.S. 1201 Mother lode, monumented with a granite stone, 12 x 12 x 6 ins. above ground, in a mound of stone, 3 1/2 ft. base, 3 ft. high, mkd. ML NO 2 1201, from which an original bearing object
	A rock outcrop, bears S 54°15' E, 37 lks. dist., mkd. BR + 1201. (Record: S 56°25' E, 39.4 lks. dist.)
	and a local bearing object
	An open end pipe, 3/4 in. diam., projecting 14 ins. above ground, bears N 67°00' E, 16 lks. dist., not mkd.
	Not remonumented
	S 2°45' W, on line 2-3, M.S. 1201 Mother lode.
5.96	Intersect the line bet. secs. 14 and 23, at a point from which the cor. of secs. 14, 15, 22 and 23, bears N 89°53' W, 2.46 chs. dist., hereinbefore described.
h	

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
9.11	Cor. No. 3, M.S. 1201 Mother lode, monumented with a granite stone, 30 x 8 x 6 ins. above ground, in a mound of stone, 4 ft. base, 2 ft. high, mkd. ML 3 1201 on N face, from which a local bearing object
	An open end pipe, 3/4 in. diam., projecting 21 ins. above ground, bears S 45° E, 4 lks. dist., not mkd.
	Not remonumented
	S 87°22' E, on line 3-4, M.S. 1201 Mother lode.
22.29	Cor. 4, M.S. 1201 Mother lode, monumented with a granite stone, 36 x 15 x 6 ins. above ground, firmly set, marks legible are 1201, from which an original bearing object
	A granite stone, 8 x 3 x 2 ft. above ground, bears N 61° W, 23 lks. dist., mkd. BR + ML NO 4 1201.
	Not remonumented
	N 2°27' E, on line 4-1, M.S. 1201 Mother lode.
4.13	Intersect the line bet. secs. 14 and 23, at a point from which the 1/4 sec. cor. of secs. 14 and 23, bears S 89°53' E, 15.26 chs. dist., hereinbefore described.
9.15	Cor. 1, M.S. 1201 Mother lode, point of beginning.
	Mineral Survey No. 1113 Edgar Lode
	From Cor. 1, M.S. 1113 Edgar lode, monumented with a wood post, 4 x 4 ins. square, 3 ft. long, set in a mound of stone, 3 ft. base, 1 1/2 ft. high, no marks visible, from which an original bearing object
	A granite boulder, 8 x 5 x 3 ft. above ground, bears N 47°40' E, 1.56 chs. dist., mkd. + BRE 1 1113. (Record: N 48°20' E, 1.598 chs. dist.)

CH.	ΑI	N	S

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.



From this point an open end pipe, 3/4 in. diam., projecting 21 ins. above ground, bears N 55° W, 3 lks. dist., not mkd.

Deposit wood post alongside the aluminum post.

Cor. is located 1.00 ch. S of a creek, 16 lks. wide, drains W.

N 65°58' E, on line 1-2, M.S. 1113 Edgar lode.

1.46 Intersect the line bet. secs. 14 and 15, at a point from which the cor. of secs. 14, 15, 22 and 23, bears South, 6.39 chs. dist., hereinbefore described.


22.13 Cor. No. 2, M.S. 1113 Edgar lode, monumented with a wood post, 2 x 4 ins. x 3 ft. long, loosely set in a mound of stone, 4 1/2 ft. base, 1 1/2 ft. high, mkd. E 2 1113, from which original bearing objects

A granite boulder, 4 x 3 1/2 x 2 ft. above ground, bears S 81°51' E, 42.1 lks. dist., mkd. + BRE 2 1113.

A rock outcropping, 5 x 3 x 2 1/2 ft. above ground, bears N 78°03' W, 34.8 lks. dist., mkd. + BRE 2 1113.

At the cor. point

Set an aluminum post, 34 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 4 1/2 ft. base, to top, with cap mkd.



Deposit wood post alongside the aluminum post.

80

CHAINS	
Chang	Mineral Survey No. 1112  Juniper Lode
	From Cor. 2, M.S. 1113 Edgar lode, hereinbefore described.
	S 44°40' E, on a line between cor 2 M.S. 113 Edgar lode and cor 1 M.S. 1112 Juniper lode.
2.40	Cor. 1, M.S. 1112 Juniper lode, monumented with a wood post, 2 x 4 ins. x 3 ft. long, loosely set in a mound of stone, 3 ft. base, 1 1/2 ft. high, no visible marks, from which original bearing objects
	A rock outcrop, bears N 42°32' E, 2.905 chs. dist., mkd. + BRJ 1 1112. (Record: N 42°01' E, 3.008 chs.)
	A rock outcrop bears N 54°22' E, 61 5 lks. dist., mkd. + BRJ 1 1112. (Record: N 52°55' E, 63.6 lks. dist.)
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	MS 1112 JUNIPER  1
	1983
	Deposit the wood post alongside the aluminum post.
	N 44°08' E, on line 1-2, M.S. 1112 Juniper lode.
22.46	Cor. 2, M.S. 1112 Juniper lode, monumented with a wood post, 2 x 4 ins. x 2 1/2 ft. long, set in a mound of stone, 3 ft. base, 4 ft. high, mkd. J 2 1112, from which an original bearing object
	A porphyry stone, 4 ft. square above ground, bears S 85°06 W, 26 lks. dist., mkd. + BRJ 2 1112. (Record: 22.9 lks.)

Dependent Resurvey of Portions of Certain Mineral Surveys,

# T 10 N, R 5 W, Gila and Salt River Mer., Arizona **CHAINS** At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base, to top, with cap mkd. Deposit the wood post alongside the aluminum post. N 45°28' W, on line 2-3, M.S. 1112 Juniper lode. 4.46 Cor. 3, M.S. 1112 Juniper lode, monumented with a wood post, 4 x 4 ins. x 2 1/2 ft. above ground, firmly set, mkd. J 3 111 on a weathered face, from which the original bearing object A granite rock outcropping, 3 x 2 x 1 ft. above ground, bears S 7°20' W, 24 lks. dist., mkd. + BR 1112. (Record: 25.5 lks.) At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 4 1/2 ft. base, to top, with cap mkd. S14 3 JUNIPER MS 1112 1983 from which A granite rock, 2 x 2 x 2 ft. above ground, bears N 34° E, 8 lks. dist., mkd. X BO. From this point an open end iron pipe, 1 ins. diam., projecting 24 ins. above ground, bears N 18° W, 3 lks. dist. Deposit the wood post alongside the aluminum post.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 62°10' W, on line 3-4, M.S. 1112 Juniper lode.
4.65	Cor. 4, M.S. 1112 Juniper lode, identical with Cor. 2, M.S. 1115 Triangle lode, monumented with a wood post, 2 x 4 ins. by 3 1/2 ft. long, lying alongside a mound of stone, 4 ft. base, 2 ft. high, with no visible marks.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	TRIANGLE $2 \downarrow \frac{\text{S14}}{4}$
	MS 1115 JUNIPER MS 1112 1983
	from which
	A rock outcropping, 1 x 1 ft. x 6 ins. above ground, bears S 29° W, 36 lks. dist., mkd. X BO.
	A rock outcropping, bears S 75° W, 19 lks. dist., mkd. X BO.
	From this point an open end iron pipe, 1 in. diam., projecting 18 ins. above ground, bears S 71° E, 2.5 lks. dist., not mkd.
	Deposit the wood post alongside the aluminum post.
	Mineral Survey No. 1115 Triangle Lode
	From Cor. 2, M.S. 1115 Triangle lode, identical with Cor. 4, M.S. 1112 Juniper lode, hereinbefore described.
	N 11°36' W, on line 2-3, M.S. 1115 Triangle lode.
2.20	Cor. 3, M.S. 1115 Triangle lode, monumented with a wood post, 2 x 4 ins. x 3 ft. long, loosely set in a mound of stone, 3 ft. base, 1 ft. high, mkd. T 3 1115, from which the remaining original bearing object

#### CHAINS

A rock outcropping, 4 x 4 x 3 ft. above ground, bears N 48°30' E, 29.5 lks. dist., mkd. + BRT 3 1115. (Record: N 37° E 30.3 lks.)

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

MS 1115 S14
TRIANGLE 3 1983

from which a new bearing object

A rock outcropping, 3 x 2 x 2 ft. above ground, bears S 48 1/2° W, 41 lks. dist., mkd. X BO.


Deposit the wood post alongside the aluminum post.

N 44°58' W, on line 3-4, M.S. 1115 Triangle lode.

- 4.10 Intersect the E and W center line of sec. 14, at a point from which the center W 1/16 sec. cor. of sec. 14, bears N 89°53' W, 6.48 chs. dist., hereinbefore described.
- 7.01 Point for Cor. 4, M.S. 1115 Triangle lode, determined on the projection of line 1-2 and at record dist. from Cor. 2, M.S. 1114 Edmond lode, hereinafter described. There is no evidence of the original cor..

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.



	T 10 N, R 5 W, Gila and Salt River Mer., Arizona	
CHAINS	Cor. is located 18 lks. N of a fence, extends N 60° E and	
	S 60° W.	
	S 38°03' W, on line 4-5, M.S. 1115 Triangle lode.	
0.424	Cor. 2, M.S. 1115 Edmond lode, is determined at record bearing and dist. from an original bearing object	
	A porphyry rock outcropping, 3 1/2 x 3 x 3 ft. above ground, bears S 69°13' W, 32.4 lks. dist., mkd. + BRE 2 1114.	
	At the cor. point	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.	
	MS 1114 MS 1115 TRIANGLE	
	1983	
	Cor. is located in a fence, extends N 60° E and S 60° W.	
	From this point Cor. 1, M.S. 1114 Edmond lode, bears S 38°03' W, 22.36 chs. dist., hereinafter described.	
	Mineral Survey No. 1114 Edmond Lode	
	From Cor. 2, M.S. 1114 Edmond lode, on line 4-5, M.S. 1115 Triangle lode.	
	N 37°03' W, on line 2-3, M.S. 1114 Edmond lode.	
6.91	Intersect the N and S center line of the NW 1/4 of sec. 14, at a point from which the center W 1/16 sec. cor. of sec. 14, bears S 0°01' W, 7.23 chs. dist., hereinbefore described.	
1		

		T 10 N, R 5 W, Gila and Salt River Mer., Arizona		
CF	HAINS	_		
9.	.02	Cor. 3, M.S. 1114 Edmond lode, monumented with a mound of stone, 3 ft. base, 3 ft. high, from which original bearing objects		
		A granite boulder, 10 x 8 x 6 ft. above ground, bears N 42°30' E, 1.01 chs. dist., mkd. + BRE 3 1114. (Record: N 34°12' E, 1.015 chs.)		
		A granite boulder, 5 x 5 x 3 ft. above ground, bears N 40°00 'W, 46.6 lks. dist., mkd. + BRE3 1114. (Record: N 43°39' W, 50.8 lks.)		
		At the cor. point		
		Set an aluminum post, 36 ins. long, 3/4 in. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with cap mkd.		
		S14		
		3		
į		EDMOND		
		MS 1114		
		1983		
		From this point an open end iron pipe, 1 in. diam., projecting 15 ins. above ground, bears S 42° W, 4 lks. dist., not mkd.		
		S 38°02' W, on line 3-4, M.S. 1114 Edmond lode.		
11.	.29	Intersect the E and W center line of sec. 14, at a point from which the center W 1/16 sec. cor. of sec. 14, bears S 89°53' E, 8.23 chs. dist., hereinbefore described.		
22.	.47	Point for Cor. 4, M.S. 1114 Edmond lode, determined at proportionate distance; there is no remaining evidence of the original cor.		
		Set an aluminum post, 36 ins. long, 3/4 in. diam., 34 ins. in the ground, with cap mkd.		
		S14 4 EDMOND		
		1983 MS 1114		
		1703		

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	from which new bearing objects
	A power pole with spike, 2 ft. above base, bears N 51° E, 1.72 chs. dist.
	A power pole with spike, 1 ft. above base, bears S 63° E, 18 lks. dist.
	Raise a mound of stone, 2 ft. base, 1 ft. high, E of cor.
	Cor. is located 1.70 chs. S of Old Highway 89, bears N 60° E and S 60° W.
	From this point, a granite boulder, 10 x 9 x 5 ft. above ground, bears N 5°37' E, 11.27 chs. dist., mkd. X BR USLM 1112.
	S 37°42' E, on line 4-1, M.S. 1114 Edmond lode.
8.99	Cor. 1, M.S. 1114 Edmond lode, monumented with the remains of a wood post and a mound of stone, 4 ft. base, 2 1/2 ft. high.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	MS 1114 EDMOND
	S14 1983
	from which new bearing objects
	A granite boulder, 4 x 4 x 4 ft. above ground, bears S 19 1/2° W, 2.79 chs. dist., mkd. X BO.
	A granite boulder, 4 x 3 x 3 ft. above ground, bears S 31 1/2° W, 2.78 chs. dist., mkd. X BO.
	From this point an open end iron pipe, 1 in. diam., bears S 87° E, 2 lks. dist., not mkd.

	1 10 N, K 5 W, Gila and Salt River Her., Arizona
CHAINS	
	N 38°03' E, on line 1-2, M.S. 1114 Edmond lode.
0.42	Point for Cor. 5, M.S. 1115 Triangle lode, determined at record dist. from Cor. 1, M.S. 1114 Edmond lode, and on line 1-2, M.S. 1114 Edmond lode; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, in a mound of stone, 1 ft. base, to top, with cap mkd.
	MS 1114 EDMOND 5 MS 1115 TRIANGLE 1983
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, SE of cor.
	Cor. is located 27 lks. S of a track road, 15 lks. wide, bears E, W and N to a dead end.
	Mineral Survey No. 1115 Triangle Lode
	From Cor. 5, M.S. 1115 Triangle lode, hereinbefore described.
	S 45°32' E, on line 5-1 M.S. 1115 Triangle lode.
3.96	Cor. 3, M.S. 1113 Edgar lode, monumented with a wood post, 2 x 4 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 1 1/2 ft. high, mkd. E 3 1113, from which original bearing objects
	A granite rock outcropping, 11 x 4 1/2 ft. above ground, bears N 89° E, 2.66 chs. dist., mkd. + BRE 3 1113. (Record: N 89°35' E, 2.74 chs. dist.)
3	A granite rock, 24 x 18 x 8 ins. above ground, bears N 70° W, 85 lks. dist., mkd. E 3 1113. (Record: N 69°07' W)
	At the cor. point

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.
	S14 TRIANGLE  MS 1115  EDGAR  MS 1113  1983
	From this point an iron pipe, 1 in. diam., projecting 10 ins. above ground, bears N 85° E, 2 lks. dist.
	Deposit the wood post alongside the aluminum post.
	Cor. is located 35 lks. S of a track road, 15 lks. wide, bears S 55° E and N 55° W.
	Mineral Survey No. 1113 Edgar Lode
	From Cor. 3, M.S. 1113 Edgar lode, hereinbefore described.
	S 65°50' W, on line 3-4, M.S. 1113 Edgar lode.
14.78	Intersect the line bet. secs. 14 and 15, at a point from which the cor. of secs. 14, 15, 22, and 23 bears South, 15.60 chs. dist., hereinbefore described.
22.19	Cor. 4, M.S. 1113 Edgar lode, monumented with the remains of a wood post, 2 x 4 ins. x 3 ft. long, set in a mound of stone, 3 ft. base, 1 ft. high, mkd. E 4 1113.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	EDGAR S15 4 MS 1113
	1983

# **CHAINS** from which a new bearing object A granite rock, 18 x 12 x 10 ins. above ground, bears S 84 1/2° E, 1.24 chs. dist., mkd. X BO. Deposit wood post alongside the aluminum post. Cor. is located 64 lks. W of a creek, 18 lks. wide, course S, and 33 lks. E of a power line, bears N and S. S 44°54' E, on line 4-1, M.S. 1113 Edgar lode. 8.98 Cor. 1, M.S. 1113 Edgar lode, hereinbefore described. Mineral Survey No. 1704 A Side Issue Lode From Cor. 2, M.S. 1704 A Side Issue lode, monumented with a wood post, 4 ins. square, 2 1/2 ft. long, set in a mound of stone, 3 ft. base, 1 ft. high, mkd. S NO 10 2 on S side and 1704 A on E side, from which an original bearing object A granite rock, 12 x 5 x 4 ft. above ground, bears N 11°13' E, 2.99 chs. dist., mkd. B + R C NO 2 1704 A on SW face. (Record: 3.00 chs.) At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap

Deposit the wood post alongside the aluminum post.

From this point, the 1/4 sec. cor. of secs. 20 and 21, bears N 3°31' W, 78 lks. dist., hereinbefore described,

2 SIDE ISSUE MS 1704A

N 72°10' E, on line 2-1, M.S. 1704 A Side Issue lode.

mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
2.54	Intersect the E and W center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 20 and 21 bears S 89°55' W, 2.465 chs. dist., hereinbefore described.
22.43	Cor. 1, M.S. 1704 A Side Issue lode, monumented with a mound of stone, 2 ft. base, 1 ft. high, from which an original bearing object
	A granite rock, 5 x 5 x 3 ft. above ground, bears N 87°45' W, 15 lks. dist., mkd. B + R S 1 1704 A.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	S21
	SIDE ISSUE MS 1704A
	1983
	S 24°29' E, on line 1-4, M.S. 1704 A Side Issue lode.
6.65	Intersect the E and W center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 20 and 21 bears S 89°55' W, 24.155 chs. dist., hereinbefore described.
8.13	Intersect line 1-2, M.S. 1704 A Comet lode, at a point from which Cor. 2, M.S. 1704 A Comet lode, identical with Cor. 1, M.S. 1704 A Jupiter lode, bears S 61°54' W, 4.49 chs. dist., hereinafter described.
9.00	Cor. 4, M.S. 1704 A Side Issue lode, monumented with a wood post, 4 ins. square, 2 ft. long, set in a mound of stone, 2 ft. base, 1 ft. high, mkd. S NO 4, from which an original bearing object
	A granite rock, 9 x 7 x 6 ft. above ground, bears N 37° E, 34 lks. dist., mkd. B + R S 4 1704. (Record: N 34°35' E,)
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	MS 1704A SIDE ISSUE 4 COMET MS 1704A 1983
	Deposit the wood post alongside the aluminum post.
	Mineral Survey No. 1704 A Comet Lode
	From Cor. 2, M.S. 1704 A Comet lode, identical with Cor. 1, M.S. 1704 A Jupiter lode, and on line 4-1 M.S. 1704 A Side Issue lode, monumented with a wood post, 4 ins. square, 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd. C NO 2 1704 A.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	SIDE ISSUE MS 1704A 1 2 COMET
	JUPITER MS 1704A MS 1704A 1983
	Deposit the wood post alongside the aluminum post.
	N 61°54' E, on line 2-1, M.S. 1704 A Comet lode.
4.49	Intersect line 4-1, M.S. 1704 A Side Issue lode at a point from which cor. 4, M.S. 1704 A Side Issue lode, bears S 24°29' E, 87 lks. dist., hereinbefore described.
7.36	Intersect the E and W center line of sec. 21, at a point from which the center 1/4 sec. cor. of sec. 21, bears N 89°55' E, 12.75 chs. dist.
21.57	Intersect line 4-1, M.S. 1184 Planet lode at a point from which cor. 4, M.S. 1184 Planet lode, bears N 41°05' W, 15 lks. dist., hereinafter described.

#### CHAINS


#### 22.45

Cor. 1, M.S. 1704A Comet lode, monumented with a wood post, 4 ins. square, 18 ins. long, in a mound of stone, 3 ft. base, 1 1/2 ft. high, mkd. NO 1, from which an original bearing object

A granite rock, 15 x 10 x 10 ft. above ground, bears N 70°15' E, 47 lks. dist., mkd. B + R C NO 1 1704.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.



Deposit the wood post alongside the aluminum post.


#### Mineral Survey No. 1184 Planet Lode

From cor. 4, M.S. 1184 Planet lode, monumented with a mound of stone, 2 1/2 ft. base, 2 ft. high, from which an original bearing object

A granite rock, 15 x 10 x 8 ft. above ground, bears S 66°48' E, 84 lks. dist., mkd. + P NO 4 1184. (Record: 91 lks. dist.)

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.



From this point, a boulder, 11 x 6 x 3 ft. above ground, mkd. U.S.L.M. 1184, bears S 86*02' E, 12.84 chs. dist.  N 48*34' E, on line 4-3, M.S. 1184 Planet lode.  O.41 Intersect the N and S center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 16 and 21 bears N 0*03' W, 32.95 chs. dist., hereinbefore described.  Cor. 3, M.S. 1184 Planet lode, identical with cor. 8, M.S. 1184 Saturn lode, monumented with a wood post, 2 x 8 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd. S NO 8 1184 A, from which original bearing objects  A granite rock, 20 x 10 x 8 ft. above ground bears N 78 1/2' W, 59 lks. dist., mkd. + P NO 3 1184 A. (Record: N 82*40' W)  A granite rock, 10 x 8 x 4 ft. above ground, bears N 17 1/2' W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19*40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  S21  S21  Wineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57*31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, from which an original bearing object		T 10 N, R 5 W, Gila and Salt River Mer., Arizona
U.S.L.M. 1184, bears S 86°02' E, 12.84 chs. dist.  N 48°34' E, on line 4-3, M.S. 1184 Planet lode.  O.41 Intersect the N and S center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 16 and 21 bears N 0°03' W, 32.95 chs. dist., hereinbefore described.  Cor. 3, M.S. 1184 Planet lode, identical with cor. 8, M.S. 1184 Saturn lode, monumented with a wood post, 2 x 8 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd. S NO 8 1184 A, from which original bearing objects  A granite rock, 20 x 10 x 8 ft. above ground bears N 78 1/2° W, 59 lks. dist., mkd. + P NO 3 1184 A. (Record: N 82°40' W)  A granite rock, 10 x 8 x 4 ft. above ground, bears N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19°40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  Beposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,	CHAINS	
Intersect the N and S center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 16 and 21 bears N 0*03' W, 32.95 chs. dist., hereinbefore described.  21.37  Cor. 3, M.S. 1184 Planet lode, identical with cor. 8, M.S. 1184 Saturn lode, monumented with a wood post, 2 x 8 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd. S NO 8 1184 A, from which original bearing objects  A granite rock, 20 x 10 x 8 ft. above ground bears N 78 1/2° W, 59 lks. dist., mkd. + P NO 3 1184 A. (Record: N 82°40' W)  A granite rock, 10 x 8 x 4 ft. above ground, bears N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19°40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  PLANET MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		
which the 1/4 sec. cor. of secs. 16 and 21 bears N 0°03' W, 32.95 chs. dist., hereinbefore described.  21.37 Cor. 3, M.S. 1184 Planet lode, identical with cor. 8, M.S. 1184 Saturn lode, monumented with a wood post, 2 x 8 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd. S NO 8 1184 A, from which original bearing objects  A granite rock, 20 x 10 x 8 ft. above ground bears N 78 1/2° W, 59 lks. dist., mkd. + P NO 3 1184 A. (Record: N 82°40' W)  A granite rock, 10 x 8 x 4 ft. above ground, bears N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19°40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  B SATURN PLANET MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		N 48°34' E, on line 4-3, M.S. 1184 Planet lode.
Saturn lode, monumented with a wood post, 2 x 8 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd.  S NO 8 1184 A, from which original bearing objects  A granite rock, 20 x 10 x 8 ft. above ground bears N 78 1/2° W, 59 lks. dist., mkd. + P NO 3 1184 A. (Record: N 82°40' W)  A granite rock, 10 x 8 x 4 ft. above ground, bears N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19°40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  B SATURN PLANET MS 1184 1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode. N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,	0.41	which the 1/4 sec. cor. of secs. 16 and 21 bears N 0°03' W,
N 78 1/2° W, 59 lks. dist., mkd. + P NO 3 1184 A.  (Record: N 82°40' W)  A granite rock, 10 x 8 x 4 ft. above ground, bears N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19°40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  3 8 SATURN MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,	21.37	Saturn lode, monumented with a wood post, 2 x 8 ins. x 2 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd.
N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record: N 19°40' W)  At the cor. point  Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  3 8 SATURN PLANET MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		N 78 1/2° W, 59 lks. dist., mkd. + P NO 3 1184 A.
Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, with cap mkd.  S21  BEAUTIN MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		N 17 1/2° W, 83 lks. dist., mkd. S NO 8 1184 A. (Record:
ground, with cap mkd.  S21  3 8 SATURN PLANET MS 1184 1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  22.36  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		At the cor. point
Beposit the wood post alongside the aluminum post.  Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		
Beposit the wood post alongside the aluminum post.  Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		S21
PLANET \ MS 1184  MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  22.36  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		
MS 1184  1983  Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184  Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  22.36 Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		<b>\</b>
Deposit the wood post alongside the aluminum post.  Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  22.36 Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		· · · · · · · · · · · · · · · · · · ·
Mineral Survey No. 1184 Saturn Lode  From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		
From Cor. 8, M.S. 1184 Saturn lode, identical with cor. 3, M.S. 1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		Deposit the wood post alongside the aluminum post.
1184 Planet lode.  N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.  Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		· · · · · · · · · · · · · · · · · · ·
22.36 Cor. 7, M.S. 1184 Saturn lode, monumented with the remains of a wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		
wood post, 8 ins. square, 2 ft. long, set in a mound of stone,		N 57°31' E, on line 8-7, M.S. 1184 Saturn lode.
	22.36	wood post, 8 ins. square, 2 ft. long, set in a mound of stone,

# **CHAINS** A granite rock, 11 x 9 x 6 ft. above ground, bears N 28 1/2° E, 54 lks. dist., mkd. + NO 7 1184 A. (Record: N 28°42' E, 55 lks.) At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd. S21 SATURN MS 1184 1983 Deposit remains of wood post alongside the aluminum post. S 41°26' E, on line 7-6, M.S. 1184 Saturn lode. 8.26 Intersect the line bet. secs. 21 and 22, at a point from which the cor. of secs. 15, 16, 21 and 22 bears N 0°02' W, 13.30 chs. dist., hereinbefore described. 9.03 Cor. 6, M.S. 1184 Saturn lode, monumented with a wood post, 2 x 10 ins., set in a mound of stone, 4 ft. base, 2 ft. high, mkd. S 6 1184, from which an original bearing object A granite rock, 8 x 5 x 4 ft. above ground, bears S 69 1/2° W, 19 lks. dist., mkd. + NO 6 1184. (Record: S 54°30' W, 15 lks. dist.) At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, and in a mound of stone, 6 ft. base, to top, with cap mkd. SATURN MS 1184 1983 Deposit the wood post alongside the aluminum post.

95

CHADIC	T 10 N, R 5 W, Glia and Sait River Mer., Arizona
CHAINS	
	S 57°40' W, on a line between Cor.6, M.S. 1184 Saturn lode and Cor. 21, M.S. 1185 Mesa Placer.
0.60	Intersect the line bet. secs. 21 and 22, at a point from which the cor. of secs. 15, 16, 21 and 22 bears N 0°01' W, 14.20 chs. dist., hereinbefore described.
11.38	Cor. 21 , M.S. 1185 Mesa Placer, monumented with the remains of a wood post, 4 ins. square, 2 ft. long, lying loose alongside a mound of stone, 3 ft. base, 2 ft. high, mkd. M N 21 1185, from which an original bearing object
	A granite rock, 10 x 10 x 5 ft. above ground, bears N 63° W, 47 lks. dist., mkd. + M NO 21 1185. (Record: N 65°48' W)
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	MS 1184 SATURN
	21 S21
	MESA \ MS 1185
	1983
	Deposit the wood post alongside the aluminum post.
	Mineral Survey No. 1185  Mesa Placer
	From Cor. 21, M.S. 1185 Mesa Placer.
i.	S 19°25' E, on line 21-20, M.S. 1185 Mesa Placer.
10.36	Cor. 20, M.S. 1185 Mesa Placer, on line 17-18 M.S. 1185 Cottonwood Placer, monumented with a wood post, 2 x 8 ins. x 3 ft. long, lying loose on top of a mound of stone, 4 ft. base, 2 ft. high, mkd. M NO 20 1185, from which an original bearing object
	A granite rock, 5 x 4 x 4 ft. above ground, bears N 35°45' E, 77 lks. dist., mkd. with an X.
	Not remonumented


	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 9 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with cap mkd.
	MS 1185 S21 MESA 20
	COTTONWOOD  MS 1185  1983
	Deposit the wood post alongside the aluminum post.
	Mineral Survey No. 1185 Cottonwood Placer
	From Cor. 20, M.S. 1185 Mesa Placer, hereinbefore described.
	N 83°39' E, on line 18-17 M.S. 1185 Cottonwood Placer.
5.71	Intersect the line bet. secs. 21 and 22, at a point from which the 1/4 sec. cor. of secs. 21 and 22 bears S 0°02' E, 10.88 chs. dist., hereinbefore described.
12.02	Cor. 17, M.S. 1185 Cottonwood Placer, monumented with a wood post, 2 x 8 ins. x 1 ft. long, in a mound of stone, 4 ft. base, 18 ins. high, mkd. C NO 11, from which an original bearing object
	A granite rock, 9 x 3 x 2 1/2 ft. above ground, bears N 88° E, 54.8 lks. dist., mkd. + C NO 17 1185. (Record: N 87°47' E, 54 lks.)
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.

	T TO N, N 5 W, GITA AND BATE KIVEL TRITY THE ZONA
CHAINS	
j	S22
Ì	
	17 COTTONWOOD
	MS 1185
	1983
	Descrit the conduct along with the along ward
	Deposit the wood post alongside the aluminum post.
Į.	
	S 1°28' E, on line 17-16, M.S. 1185 Cottonwood Placer.
8.44	Cor. 16, M.S. 1185 Cottonwood Placer, monumented with a wood post, 2 x 8 x 18 ins. long, set in a mound of stone, 4 ft. base, 2 ft. high, mkd. C NO 16 1185, from which an original bearing object
	A granite rock, 4 x 2 x 1 ft. above ground, bears S 9° W, 1.737 chs. dist., mkd. + C NO 16 1185. (Record: S 9°12' W)
-	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.
	MS 1185 COTTONWOOD
	16 S22
	1983
	Deposit the wood post alongside the aluminum post.
	S 83°02' W, on line 16-15, M.S. 1185 Cottonwood Placer.
6.54	Intersect the line bet. secs. 21 and 22, at a point from which the 1/4 sec. cor. of secs. 21 and 22 bears S 0°02' E, 2.35 chs. dist., hereinbefore described.
18.34	Cor. 15, M.S. 1185 Cottonwood Placer, monumented with a wood post, 2 x 6 ins., set in a mound of stone, 6 ft. base, 3 ft. high, mkd. C NO 15 1185, from which an original bearing object
	A granite rock, 12 x 6 x 5 ft. above ground, bears S 3°58' W, 49 lks. dist., mkd. C NO 15 1185.

CHAINS

At the cor. point

Set a brass tablet, in a slab of granite, 7 x 3 x 2 ft. above ground, mkd.




N 11° 10' W, on line 15-18 M.S. 1185 Cottonwood Placer.

1.07 Cor. 25, M.S. 1185 Mesa Placer, monumented with a wood post, 2 x 8 ins., projecting 12 ins. above and wedged among boulders with supporting stone, mkd. M NO 25 1185.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., projecting 2 ins. above and wedged among boulders, with cap mkd.



from which

A power pole, bears S 62° W, 1.29 chs. dist.

Deposit wood post alongside the aluminum post.

Mineral Survey No. 1185 Mesa Placer

From Cor. 25, M.S. 1185 Mesa Placer, hereinbefore described.

S 61°18' W, on line 25-24, M.S. 1185 Mesa Placer.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
4.16	Intersect the E and W center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 21 and 22 bears N 89°55' E, 15.57 chs. dist., hereinbefore described.
9.235	Intersect the N and S center line of the SE 1/4 of sec. 21, at a point from which the true point for the center E 1/16 sec. cor. of sec. 21 bears N 0°01' W, 2.43 chs. dist., hereinbefore described.
9.85	Cor. 24, M.S. 1185 Mesa Placer, on line 11-12, M.S. 1185 Oroville Placer, monumented with a wood post, 2 x 8 ins. x 2 1/2 ft. long, set in a mound of stone, 5 ft. base, 2 1/2 ft. high, mkd. M NO 24 1185, from which an original bearing object
	A granite rock, 13 x 13 x 9 ft. above ground, bears S 40°11' W, 16 lks. dist., mkd. + M NO 24 1185.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 2 ins. in the ground, and in a supporting mound of stone, 5 ft. base, to top, with cap mkd.
	E L 5 L 8 MS 1185 I 1 MESA V 1 24 O S21 R S O M
	Deposit the wood post alongside the aluminum post.
	Mineral Survey No. 1185 Oroville Placer
	From Cor. 24, M.S. 1185 Mesa Placer, hereinbefore described.
	S 0°28' E, on line 12-11 M.S. 1185 Oroville Placer.
9.20	Cor. 11, M.S. 1185 Oroville Placer, identical with Cor. 2, M.S. 1185 Golden Bowl Placer, monumented with a wood post, 2 x 6 ins. x 3 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, from which an original bearing object
	A granite rock outcropping, 11 x 7 x 7 ft. above ground, bears S 37°47' E, 20.5 lks. dist., mkd. + GB NO 2 1185 on the W face.

# **CHAINS** At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with cap mkd. MS 1185 OROVILLE S21 **GOLDEN** BOWL MS 1185 1983 Deposit the wood post alongside the aluminum post. Mineral Survey No. 1185 Golden Bowl Placer From Cor. 2, M.S. 1185 Golden Bowl Placer, identical with Cor. 11, M.S. 1185 Oroville Placer, hereinbefore described. S 12°52' W, on line 2-1, M.S. 1185 Golden Bowl Placer. 8.33 Intersect the E and W center line of the SE 1/4 of sec. 21, at a point from which the SE 1/16 sec. cor. of sec. 21 bears N 89°57' E, 2.32 chs. dist., hereinbefore described. 15.20 Cor. 1, M.S. 1185 Golden Bowl Placer, monumented with a wood post, 2 x 6 ins. x 4 ft. long, set in a mound of stone, 4 ft. base, 2 ft. high, mkd. NO 1 1185, from which an original bearing object A granite rock, 12 x 8 x 5 ft. above ground, bears S 82°26' E, 42 lks. dist., mkd. BR + GB NO 1 1185 on W face. (Record: 41 lks. dist.) At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with cap mkd.

CHAINS MS 1185 **GOLDEN** BOWL S21 1983 Deposit the wood post alongside the aluminum post. N 77°08' W, on line 1-4, M.S. 1185 Golden Bowl Placer. 12.10 Cor. 4, M.S. 1185 Golden Bowl Placer, monumented with a wood post, 2 x 8 x 40 ins. long, set in a mound of stone, 3 1/2 ft. base, 1/2 ft. high, mkd. GB NO 4 1185, from which an original bearing object A granite rock, 14 x 9 x 8 ft. above ground, bears S 78°43' E, 1.85 chs. dist., mkd. + GB NO 4 1185 on W face. A steel fence post is set alongside the wood post. At the cor. point Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd. DIAMOND MS 2139 MS 1185 **GOLDEN** BOWL 1983 Deposit the wood post alongside the aluminum post. Cor. is located 1.60 chs. S of a road, 20 lks. wide, road bears N 40° E and S 40° W. Mineral Survey No. 2139 Diamond Placer

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From Cor. 4, M.S. 1185 Golden Bowl Placer.
	S 13°06' W, on a line between Cor.4, M.S. 1185, Golden Bowl Placer and Cor. 2, M.S. 2139 Diamond Placer.
6.45	Point for Cor. 2, M.S. 2139 Diamond Placer, determined using the grant bdy. proportion method; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	MS 2139
	DIAMOND 2 S21
	1983
<b>.</b>	from which
	A power pole, bears N 31° W, 1.13 chs. dist.
	Cor. is located 85 lks. E of a track road, 15 lks. wide, road bears S 25° E and N 70° W.
	S 61°04' W, on line 2-3, M.S. 2139 Diamond Placer.
3.325	Intersect the N and S center line of sec. 21, at a point from which the 1/4 sec. cor. of secs. 21 and 28 bears S 0°03' E, 8.135 chs. dist., hereinbefore described.
16.39	Cor. 3, M.S. 2139 Diamond Placer, monumented with a mound of stone, 2 1/2 ft. base, 6 ins. high.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
	MS 2139 DIAMOND 3 1983

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 13°01' E, on line 3-4, M.S. 2139 Diamond Placer.
16.40	Cor. 4, M.S. 2139 Diamond Placer, monumented with a mound of stone, 3 ft. base, 6 ins. high, from which a local bearing object, of unknown origin.
	A granite stone, 6 x 5 x 5 ins., above ground, bears North, 4 lks. dist., mkd. C on S face.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	EVENING MS 1704A  4 DIAMOND MS 2139  1983
	Cor. is located 25 lks. W of a wash, 5 lks. wide, course S 50° W.
	Mineral Survey No. 1704 A Evening Placer
	From Cor. 4, M.S. 2139 Diamond Placer.
	S 60°43' W, on a line between Cor.4 M.S. 2139, Diamond Placer and Cor. 4, M.S. 1704 A Evening Placer.
10.46	Cor. 4, M.S. 1704 A Evening Placer, monumented with a wood post, 4 x 4 ins. x 2 1/2 ft. long, set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with illegible scribe marks.
	At the cor. point

CHAINS

Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with cap mkd.



Deposit the wood post alongside the aluminum post.

N 4°51' W, on line 4-3, M.S. 1704 A Evening Placer.


15.09

Cor. 3, M.S. 1704 A Evening Placer, on line 4-3 M.S. 1704 A Jupiter lode, monumented with a wood post, 4 ins. square, 3 ft. long, set in a mound of stone, 6 ft. base, 2 ft. high, mkd. C NO 3 1704 A, from which an original bearing object

A granite rock, 7 x 4 x 3 ft. above ground, bears S 37°20' E, 14 lks. dist., mkd. B + R C NO 3 1704.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 2 ins. in the ground, supported by a mound of stone, 6 ft. base, to top, with cap mkd.



Deposit the wood post alongside the aluminum post.

Mineral Survey No. 1704 A Jupiter Lode

From Cor. 3, M.S. 1704 A Evening Placer.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 72°52' W, on line 4-3 M.S. 1704 A Jupiter lode.
19.08	Cor. 3, M.S. 1704 A Jupiter lode, monumented with the remains of a wood post, 2 1/2 ft. below the surface of a sandy wash, set in a mound of stone, 2 ft. base, 12 ins. high, from which an original bearing object
	A granite rock, 12 x 8 x 4 ft. above ground, bears S 67°35' E, 5.20 chs. dist., mkd. J NO 3 B + R 1704 A on W face.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
	MS 1704A
	JUPITER
	3
	S21 V
	1983
	N 29°12' W, on line 3-2, M.S. 1704 A Jupiter lode.
4.53	The W End Center Cor., M.S. 1704 A Jupiter lode, monumented with a wood post, 4 ins. square, 40 ins. long, set in a mound of stone, 2 1/2 ft. base, 6 ins. high, mkd. J N.
	At the cor. point
;	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.
	S21 W C END
	JUPITER
	MS 1704A
	1983
	Deposit the wood post alongside the aluminum post.

	T 10 N, R 5 W, G11a and Salt River Mer., Arizona
CHAINS	
	N 29°12' W, beginning new measurement.
3.04	Intersect the line bet. secs. 20 and 21, at a point from which the S 1/16 sec. cor. of secs. 20 and 21, bears S 0°02' E, 8.712 chs. dist., hereinbefore described.
4.562	Point for Cor. 2, M.S. 1704 A Jupiter lode, determined at record dist. from the original witness cor. for Cor. 2, on a projection of line 1-2 of said lode, hereinafter described.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with cap mkd.
	S20 2 JUPITER MS 1704A
	1983
	Raise a mound of stone, 3 ft. base, 18 ins. high, SE of the cor.
į	Cor. is located 20 lks. S of a wash, 10 lks. wide, course S 45° W.
,	N 73°09' E, on line 2-1 M.S. 1704 A Jupiter lode.
0.455	The witness cor. to Cor. 2, M.S. 1704 A Jupiter lode, monumented with the remains of a wood post, set in a mound of stone, 3 ft. base, 6 ins. high, from which an original bearing object
	A granite rock, 3 x 3 x 2 ft. above ground, bears N 12°59' E, 3.12 chs. dist., mkd. B + R J N 2 1704 A on W face. (Record: N 12°54' E)
	At the witness cor. point, now designated Angle Point No. 1.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	AP
	S20
	JUPITER MS 1704A
	1983

	T 10 N, R 5 W, G11a and Salt River Mer., Arizona
CHAINS	
	Deposit the remains of the wood post alongside the aluminum post.
	Thence, continue measurement on line 2-1 M.S. 1704A Jupiter lode.
0.775	Intersect the line bet. secs. 20 and 21, at a point from which the S 1/16 sec. cor. of secs. 20 and 21 bears S 0°02' E, 10.265 chs. dist., hereinbefore described.
4.505	Point for Cor. 3, M.S. 1704 A Side Issue lode, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.
	MS 1704A
	SIDE
	S21 \ ISSUE 3
	JUPITER
	MS 1704A
	1983
	Mineral Survey No. 1704 A Side Issue Lode
	Side issue lode
	From Cor. 3, M.S. 1704 A Side Issue lode.
	N 23°40' W, on a line between Cor. 3, M.S. 1704 A Side Issue lode and the W Center End Cor
4.09	The W Center End Cor., M.S. 1704 A Side Issue lode, monumented with a wood post, 4 ins. square, 48 ins. long, in a mound of stone, 3 ft. base, 1 1/2 ft. high, mkd. S NO 1704.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	S21 W C END SIDE ISSUE
	MS 1704A 1983

_				
- C	Н	Δ	ľ	v

Deposit the wood post alongside the aluminum post.

----

N 24°27' W, on a line between the W Center End Cor. and Cor. 2, M.S. 1704 A Side Issue lode.

4.54

Cor. 2, M.S. 1704 A Side Issue lode, hereinbefore described.

#### Mineral Survey No. 1277 Lucky Johnnie Lode

From Cor. 1, M.S. 1277 Lucky Johnnie lode, monumented with a mound of stone, 4 ft. base, 2 1/2 ft. high, from which original bearing objects

A granite rock, 8 x 4 x 1 1/2 ft. above ground, bears S 42°37' E, 36 lks. dist., mkd. B + R L J NO 1 1277.

A granite rock, 5 x 6 x 3 ft. above ground, bears S 44°36' W, 47 lks. dist., mkd. B + R L J NO 1 1277.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.



Set a steel fence post alongside the cor.

From this point, the 1/4 sec. cor. of secs. 25 and 36, bears S 77°01' W, 10.84 chs. dist., hereinbefore described.

From this same point, a wood post, 4 ins. square, 4 ft. above ground, mkd. USLM 1277 on S face, bears S 46°08' W, 4.29 chs. dist.


	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 20°54' E, on a line between Cor. 1, M.S. 1277 Lucky Johnnie lode and the E Side Center Cor.
11.41	E Side Center Cor., M.S. 1277 Lucky Johnnie lode, monumented with the remains of a wood post lying alongside a mound of stone, 3 ft. base, 1 ft. high.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	EAST SIDE CTR LUCKY JOHNNIE S25 MS 1277
	1983
	Deposit remains of the wood post alongside the aluminum post.
}	N 21°07' E, on a line between the E Side Center Cor. and Cor. 2, M.S. 1277 Lucky Johnnie lode.
11.36	Cor. 2, M.S. 1277 Lucky Johnnie lode, identical with Cor. 1, M.S. 1277 Katie lode, monumented with a mound of stone, 3 ft. base, 2 ft. high, from which an original bearing object
	A granite rock, 3 x 2 x 1 1/2 ft. above ground, bears N 43°25' W, 27 lks. dist., mkd. B + R K NO 1 1277.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	MS 1277
	KATIE,
	LUCKY 1
	JOHNNIE 2 S25
	MS 1277 / 1983
	1703

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Mineral Survey No. 1277  Katie Lode
	From Cor. 1, M.S. 1277 Katie lode, identical with Cor. 2, M.S. 1277 Lucky Johnnie lode, hereinbefore described.
	N 20°32' E, on line 1-2, M.S. 1277 Katie lode.
22.62	Cor. 2, M.S. 1277 Katie lode, monumented with a wood post, 4 ins. square, 3 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd. K NO 2 1277, from which original bearing objects
	A granite rock, 2 x 2 x 2 ft. above ground, bears S 51°15' E, 39 lks. dist., mkd. B + R K NO 2 1277.
	A granite rock, 3 x 6 x 4 ft. above ground, bears N 17°22' W, 41 lks. dist., mkd. B + R K NO 2 1277.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	KATIE 2 MS 1277 S25
	1983
	Deposit the wood post alongside the aluminum post.
	N 69°40' W, on line 2-3, M.S. 1277 Katie lode.
8.79	Cor. 3, M.S. 1277 Katie lode, monumented with a wood post, 4 ins. square, 4 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, mkd., but not legible, from which original bearing objects
	A granite rock, 2 x 3 ft. x 4 ins. above ground, bears N 84°55' E, 32 lks. dist., mkd. B + R K NO 3 1277.
	A granite rock, 3 x 3 x 3 ft. above ground, bears S 20°39' W, 27 lks. dist., mkd. B + R K NO 3 1277.

CHAINS

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with cap mkd.



Deposit the wood post alongside the aluminum post.

S 21°10' W, on line 3-4, M.S. 1277 Katie lode.


22.53 Cor. 4, M.S. 1277 Katie lode, identical with Cor. 3, M.S. 1277 Lucky Johnnie lode, monumented with a rebar of unknown origin, 1/2 in. diam., set in a mound of stone, 3 ft. base, 18 ins. high, from which original bearing objects

A granite rock, 4 x 8 x 2 ft. above ground, bears N 15°52' E, 38 lks. dist., mkd. B + R K NO 4 1277.

A granite rock, 4 x 4 x 4 ft. above ground, bears S 23°48' E, 58 lks. dist., mkd. B + R L J NO 3 1277.

At the cor. point

Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.



Deposit rebar alongside the aluminum post.

	1 10 N, R J W, Gila and Sait River Mer., Arizona
CHAINS	
	Mineral Survey No. 1277 Lucky Johnnie Lode
	From Cor. 3, M.S. 1277 Lucky Johnnie lode, identical with Cor. 4, M.S. 1277 Katie lode.
	S 21°03' W, on line 3-4, M.S. 1277 Lucky Johnnie lode.
22.73	Cor. 4, M.S. No. 1277 Lucky Johnnie lode, monumented with a rebar of unknown origin, 1/2 in. diam., projecting 2 ins. above ground, from which original bearing objects
	A granite rock, 2 x 2 ft. x 2 ins. above ground, bears S 18°22' E, 1.015 chs. dist., mkd. B + R LJ NO 4 1277.
	A granite rock, 2 1/2 x 1 x 1 1/2 ft. above ground, bears N 20°55' W, 50 lks. dist., mkd. B + R LJ NO 4 1277.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, with cap mkd.
	LUCKY
}	LUCKY 4 JOHNNIE S25 MS 1277
	S25 MS 1277 1983
	Raise a mound of stone, 3 ft. base, 2 ft. high, E of the cor.
	Set a steel fence post alongside the cor.
	Bury rebar alongside the aluminum post.
	S 69°04' E, on a line between Cor. 4, M.S. 1277 Lucky Johnnie lode and the S Center End Cor
4.55	South Center End Cor., M.S. 1277 Lucky Johnnie lode, monumented with the remains of a wood post, 2 x 4 ins. x 2 ft. long, in a mound of stone, 3 ft. base, 2 ft. high, with no visible marks.

CHAINS	
	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	SOUTH END CTR LUCKY JOHNNIE MS 1277 S25
	Deposit remains of wood post alongside the aluminum post.
	S 68°32' E, on a line between the S End Center Cor. and 1, M.S. 1277 Lucky Johnnie lode.
4.50	Cor. 1, M.S. 1277 Lucky Johnnie lode, hereinbefore described.
	Mineral Survey No. 1971 Hunter Lode
	From Cor. 4, M.S. 1971 Hunter lode, monumented with a granite rock, 6 x 15 x 15 ins. above ground, firmly set, mkd. H 4 1971 on W face, from which an original bearing object
	A granite rock, 10 x 7 x 3 ft. above ground, bears S 41°15' E, 40 lks. dist., mkd. B + R H 4 1971.
	Not remonumented
	From this point the 1/4 sec. cor. of secs. 27 and 34, bears S 43°54' W, 7.67 chs. dist., hereinbefore described.
	N 12°43' E, on line 4-1, M.S. 1971 Hunter lode.
	Cor. 1, M.S. 1971 Hunter lode, monumented with a granite rock, $4 \times 3 \times 2$ ft. above ground, firmly set, mkd. H 1 + 1971 on W face, with a post, 4 ins. square, 3 ft. high, set in a mound of stone, 3 ft. base, 2 ft. high, W of the cor.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 78°38' E, on line 1-2, M.S. 1971 Hunter lode.
22.43	Cor. 2, M.S. 1971 Hunter lode, identical with Cor. 1, M.S. 1971 Welcome No. 1 West lode, monumented with a granite stone, 10 x 8 x 6 ins. above ground, firmly set, mkd. W 1 W 1 1971 on N face and H 2 1971 on S face, with a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor., from which original bearing objects
	A granite rock, 7 x 6 x 5 ft. above ground, bears North, 13 lks. dist., mkd. B + R H 2 1971. (Record: N 20° E)
	A granite rock, 8 x 8 x 6 ft. above ground, bears N 85° W, 29 lks. dist., mkd. B + R W 1 W 1 1971.
	Not remonumented
	Mineral Survey No. 1971 Welcome No. 1 West Lode
	From Cor. 1, M.S. 1971 Welcome No. 1 West lode, identical with Cor. 2, M.S. 1971 Hunter lode.
	S 77°20' E, on line 1-2 M.S. 1971 Welcome No.1 West lode.
4.26	Cor. 5, M.S. 1971 Dixie No. 3 lode, on line 1-2 M.S. 1971 Welcome No.1 West lode, monumented with a wood post, 2 x 4 ins. x 4 ft. long, set in a mound of stone, 3 ft. base, 2 ft. high, marks are not visible.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	DIXIE NO 3 1971 5
	WELCOME NO 1 WEST 1971
	1983
	from which a new bearing object
	A granite rock, 3 x 3 ft. x 18 ins. above ground, bears N 65° W, 15 lks. dist., mkd. X BO.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Mineral Survey No. 1971 Dixie No. 3 Lode
	From Cor. 5, M.S. 1971 Dixie No. 3 lode, hereinbefore described.
	N 33°46' W, on line 5-1, M.S. 1971 Dixie No. 3 lode.
4.47	Cor. 1, M.S. 1971 Dixie No. 3 lode, monumented with a granite stone, 24 x 9 x 6 ins. above ground, firmly set, mkd. D 3 1 1971 on S face, with a mound of stone, 3 ft. base, 2 ft. high, W of the cor., from which an original bearing object
	A granite rock, 4 x 4 x 1 ft. above ground, bears N 74°45' E, 24.5 lks. dist., mkd. B + R D 3 1 1971.
	Not remonumented
	N 44°54' E, on line 1-2, M.S. 1971 Dixie No. 3 lode.
12.83	Intersect the line bet. secs. 26 and 27, at a point from which the cor. of secs. 26, 27, 34 and 35 bears S 0°03' W, 21.85 chs. dist., hereinbefore described.
14.69	Cor. 2, M.S. 1971 Dixie No. 3 lode, identical with Cor. 1, M.S. 1971 Dixie No. 2 lode, monumented with a granite rock, 4 x 3 x 3 ft. above ground, firmly set, mkd. D 2 1 1971 on S face and D 3 2 1971 on E face, with a wood post, 2 x 4 ins. above ground, set in a mound of stone, 3 ft. base, 3 ft. high, is N of the cor.
	from which a new bearing object
	A granite rock, 5 x 3 x 3 ft. above ground, bears N 66 1/2° E, 25.5 lks. dist., mkd. X BO.
	Not remonumented
	Mineral Survey No. 1971 Dixie No. 2 Lode
,	From Cor. 1, M.S. 1971 Dixie No. 2 lode, identical with Cor. 2, M.S. 1971 Dixie No. 3 lode, hereinbefore described.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 45°05' E, on line 1-2, M.S. 1971 Dixie No. 2 lode.
17.42	Cor. 2, M.S. 1971 Dixie No. 2 lode, identical with Cor. 1, M.S. 1971 Dixie lode, monumented with a granite rock, 2 1/2 x 2 1/2 x 1 ft. above ground, mkd. D 2 2 1971 X and D 1 1971.
	from which a new bearing object
	A stone, 5 x 5 x 4 ft., bears S 24° W, 21 lks. dist., mkd. X BO.
	Not remonumented
	Cor. is located on a hillside.
	Mineral Survey No. 1971 Dixie Lode
	From Cor. 1, M.S. 1971 Dixie lode, identical with Cor. 2, M.S. 1971 Dixie No. 2 lode.
	N 58°08' E, on line 1-2, M.S. 1971 Dixie lode.
22.99	Cor. 2, M.S. 1971 Dixie lode, monumented with a granite rock, 12 x 6 x 4 ins. above ground, marks are not legible, with a wood post, 2 x 4 ins. x 4 ft. above ground, set in a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.
	Not remonumented
	from which a new bearing object
	A granite stone, 3 x 2 x 1 ft. high, bears S 54° E, 14 lks. dist., mkd. X BO.
	S 33°25' E, on a line between Cor. 2, M.S. 1971 Dixie lode and the N End Center Cor.
4.61	North End Center Cor. M.S. 1971 Dixie lode, monumented with a granite stone, 12 x 10 x 6 ins. above ground, mkd. NCE D 1971.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 33°36' E, on a line between the N End Center Cor. and Cor. 3, M.S. 1971 Dixie lode.
4.45	Cor. 3, M.S. 1971 Dixie lode, identical with Cor. 5, M.S. 1971  New York No. 2 lode, monumented with a granite rock, 2 1/2 x  2 1/2 x 1 ft. above ground, mkd. NY 2 5 1971 and D 3 1971.
	Not remonumented
	from which a new bearing object
	A granite rock, 10 x 6 x 5 ft. above ground, bears N 16 1/2° W, 19.5 lks. dist., mkd. X BO.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.
	Mineral Survey No. 1971 New York No. 2 Lode
ž.	From Cor. 5, M.S. 1971 New York No. 2 lode, identical with Cor. 3, M.S. 1971 Dixie lode, hereinbefore described.
	S 85°56' E, on line 5-4, M.S. 1971 New York No. 2 lode.
4.58	Cor. 4, M.S. 1971 New York No. 2 lode, monumented with a granite stone, 14 x 10 x 4 ins. above ground, firmly set, mkd. NY 2 4 1971 on S face.
	Not remonumented
	from which a new bearing object
	A granite rock 15 x 8 x 5 ft. above ground, bears S 81 1/2° E, 7 lks. dist., mkd. X BO.
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S of the cor.
	S 8°56' W, on line 4-3, M.S. 1971 New York No. 2 lode.
22.40	Cor. 3, M.S. 1971 New York No. 2 lode, identical with Cor. 4, M.S. 1971 New York No. 1 lode, monumented with a porphyry stone, 12 x 8 x 6 ins. above ground, firmly set, mkd. NY 2 3 1971 on N face, NY 4 1971 on S face, and a + on top.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Not remonumented
	from which a new bearing object
	A rock outcropping, 20 x 10 x 6 ft. above ground, bears S 40° E, 7 lks. dist., mkd. X BO.
	Mineral Survey No. 1971 New York No. 1 Lode
	From Cor. 4, M.S. 1971 New York No. 1 lode, identical with Cor. 3, M.S. 1971 New York No. 2 lode, hereinbefore described.
	S 9°11' E, on line 4-3, M.S. 1971 New York No. 1 lode.
17.88	Intersect the line bet. secs. 26 and 35, at a point from which the 1/4 sec. cor. of secs. 26 and 35 bears N 89°55' W, 2.18 chs. dist., hereinbefore described.
19.79	Cor. 3, M.S. 1971 New York No. 1 lode, identical with Cor. 2, M.S. 1971 Welcome No. 1 East lode, monumented with a granite stone, 12 x 10 x 6 ins. above ground, firmly set, mkd. W 1 E 2 1971 on S face, and NY 3 1971 on N face, with a mound of stone, 3 ft. base, 2 ft. high, S of the cor.
	Not remonumented
	Mineral Survey No. 1971 Welcome No. 1 East Lode
	From Cor. 2, M.S. 1971 Welcome No. 1 East lode, identical with Cor. 3, M.S. 1971 New York No. 1 lode, hereinbefore described.
	S 12°48' W, on a line between Cor. 2, M.S. 1971 Welcome No. 1 East lode and the E Center End Cor
4.49	East Center End Cor., M.S. 1971 Welcome No. 1 East lode, monumented with the remains of a wood post, 4 ins. square, set in a mound of stone, 3 ft. base, 2 ft. high.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 12°52' W, on a line between the E Center End Cor. and Cor.3, M.S. 1971 Welcome No. 1 East lode.
4.50	Cor. 3, M.S. 1971 Welcome No. 1 East lode, monumented with a stone, 20 x 12 x 6 ins. above ground, loosely set, mkd. W 1 E 3 1971 on top.
	Not remonumented
	N 85°43' W, on line 3-4, M.S. 1971 Welcome No. 1 East lode.
13.83	Cor. 4, M.S. 1971 Welcome No. 1 East lode, identical with Cor. 3, M.S. 1971 Welcome lode, monumented with a granite stone, 8 x 8 x 8 ins. above ground, firmly set, mkd. W 1 E 4 1971, with a mound of stone, 2 1/2 ft. base, 2 ft. high, S of the cor.
	Not remonumented
	Mineral Survey No. 1971 Welcome Lode
	From Cor. 3, M.S. 1971 Welcome lode, identical with Cor. 4, M.S. 1971 Welcome No. 1 East lode, hereinbefore described.
	N 71°31' W, on line 3-4, M.S. 1971 Welcome lode.
18.44	Cor. 4, M.S. 1971 Welcome lode, identical with Cor. 3, M.S. 1971 Welcome No. 1 West lode, monumented with a granite stone, 12 x 8 x 6 ins. above ground, firmly set, mkd. W 1 W 3 1971 on W face, with a mound of stone, 4 ft. base, 2 1/2 ft. high, to the S, from which an original bearing object
	A granite rock, 2 x 2 1/2 x 1 ft. above ground, bears S 71°15' W, 49.7 lks. dist., mkd. B + R W 1 W 3 1971.
:	Not remonumented
	From this point, a rock outcropping, 30 x 10 x 8 ft., mkd. + USLM 1971 WD on top East side, bears S 78°13' E, 2.69 chs. dist., from which original bearing objects

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	A granite rock, 4 x 3 x 3 ft. above ground, bears N 41°30' E, 71 lks. dist., mkd. B + R USLM 1971 on S side.
	A granite rock, 5 1/2 x 5 1/2 x 3 ft. above ground bears S 50°45' E, 73 lks. dist., mkd. B + R USLM 1971 on top.
	Mineral Survey No. 1971 Welcome No. 1 West Lode
	From Cor. 3, M.S. 1971 Welcome No. 1 West lode, identical with Cor. 4, M.S. 1971 Welcome lode, hereinbefore described.
	N 77°20' W, on line 3-4, M.S. 1971 Welcome No. 1 West lode.
9.40	Intersect the line bet. secs. 34 and 35, at a point from which the cor. of secs. 26, 27, 34 and 35 bears N 0°01' E, 1.78 chs. dist., hereinbefore described.
17.45	Intersect the line bet. secs. 27 and 34, at a point from which the cor. of secs. 26, 27, 34 and 35 bears N 89°58' E, 7.88 chs. dist., hereinbefore described.
22.44	Cor. 4, M.S. 1971 Welcome No. 1 West lode, identical with Cor. 3, M.S. 1971 Hunter lode, monumented with a granite stone, 1 1/2 x 1 1/2 x 1 ft. above ground, mkd. H 3 1971 and W 1 W 4 1971 on S face.
	Not remonumented.
	from which a new bearing object
	A stone, 2 x 2 x 2 ft. above ground, bears S 18° W, 24 lks. dist., mkd. X BO.
	From this point the point of intersection of the N line of the unsurveyed Bull Hill lode, with line 4-1, identical with line 2-3, M.S. 1971 Hunter lode bears N 12°45' E, 3.33 chs. dist.
	Mineral Survey No. 1971 Hunter Lode
·	

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	From Cor. 3, M.S. 1971 Hunter lode, identical with Cor. 4, M.S. 1971 Welcome No. 1 West lode, hereinbefore described.
	N 78°39' W, on line 3-4, M.S. 1971 Hunter lode.
16.67	From this point the NW cor. of the unsurveyed Bull Hill lode, bears N 27°45' E, 3.33 chs. dist.
22.43	Cor. 4, M.S. 1971 Hunter lode, hereinbefore described.
,	Mineral Survey No. 1971 Suney Side Lode
	From Cor. 4, M.S. 1971 Suney Side lode, monumented with an iron post, 3/4 in. diam. x 12 ins. above ground, set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.
	US MINERAL SURVEY NO. 1971 S4
	\\ 3676 DMS 1
	This cor. was remonumented in 1920 by Harry E. Jones U.S. Mineral Surveyor, during the survey of M.S. No. 3676 Dixie Millsite, which was cancelled on May 6, 1983.
	From this point, the cor. of secs. 26, 27, 34 and 35, bears S 51°03' W, 9.46 chs. dist., hereinbefore described.
	N 45°10' E, on line 4-3, M.S. 1971 Suney Side lode.
18.99	Cor. 3, M.S. 1971 Suney Side lode, monumented with a boulder, 7 x 3 x 2 ft. above ground, in a wash, mkd. + SS 3 1971.
	Not remonumented
	from which new bearing objects
	A boulder in same wash, 8 x 7 1/2 x 7 ft. above ground, bears S 22° W, 21 lks. dist., mkd. X BO.
	A granite rock, 5 x 3 x 1 ft. above ground, bears N 71° W, 68 lks. dist., mkd. X BO SS 3.
	Cor. is located in a wash, 1.00 ch. wide, course S 30° W.
1	

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 77°11' W, on a line between Cor. 3, M.S. No. 1971 Suney Side lode, and the N Center End Cor.
4.69	North Center End Cor., M.S. 1971 Suney Side lode, monumented with a granite stone, 6 x 12 x 24 ins. above ground, firmly set, mkd. N C E SS 1971, with a mound of stone, 3 ft. base, 3 ft. high, W of the cor.
	N 77°21' W, on a line between the N Center End Cor and Cor 2, M.S. 1971 Suney Side lode.
4.67	Cor. 2, M.S. 1971 Suney Side lode, monumented with a granite stone, 8 x 8 x 8 ins. above ground, firmly set, mkd. SS 2 1971 on E face, with a mound of stone, 3 ft. base, 2 ft. high, W of the cor., from which an original bearing object
	A granite rock, 3 x 3 x 2 ft. above ground, bears N 34°55' E, 41 lks. dist., mkd. B + R SS 2 1971.
	Not remonumented
	from which a new bearing object
	A rock, 5 x 4 x 2 ft. above ground, bears S 2° W, 8 lks. dist., mkd. X BO.
	Mineral Survey No. 1971 Dixie No. 2 Lode
	From Cor. 2, M.S. 1971 Suney Side lode, hereinbefore described.
	N 45°34' E, on line 4-3 M.S. 1971 Dixie No. 2 lode.
9.59	Cor. 3, M.S. 1971 Dixie No. 2 lode, identical with Cor. 4, M.S. 1971 Dixie lode, monumented with a granite stone, 12 x 8 x 8 ins. above ground, firmly set, mkd. D 4 1971 on E face, and D 2 3 1971 on W face, and an X on top, with a mound of stone, 3 ft. base, 2 1/2 ft. high, S of the cor.
·	Not remonumented

CHAING	1 10 N, R 5 W, GIIA AND SAIL RIVER MET., AFIZONA
CHAINS	
	from which a new bearing object
	A stone, 5 x 4 x 4 ft. above ground, bears S 22° W, 28 lks. dist., mkd. X BO.
	Mineral Survey No. 1971 Dixie Lode
	From Cor. 3, M.S. 1971 Dixie No. 2 lode, identical with Cor. 4, M.S. 1971 Dixie lode, hereinbefore described.
	N 58°43' E, on line 4-3 M.S. 1971 Dixie lode.
17.23	Cor. 1, M.S. 1971 New York No. 2 lode, monumented with a porphyry stone, 10 x 10 x 8 ins. above ground, firmly set, mkd. NY 2 1 1971 on N face, with a mound of stone, 3 ft. base, 2 ft. high, W of the cor., from which original bearing objects
	Not remonumented
	A granite rock, 2 x 2 x 1 ft. above ground, bears S 75°20' E, 25 lks. dist., mkd. B + R NY 2 1 1971.
	A granite rock, 2 1/2 x 2 1/2 x 2 1/2 ft. above ground, bears N 19°53' W, 38 lks. dist., mkd. B + R NY 2 1 1971.
	Mineral Survey No. 1971 New York No. 2 Lode
	From Cor. 1, M.S. 1971 New York No. 2 lode, hereinbefore described.
	S 9°00' W, on line 1-2, M.S. 1971 New York No. 2 lode.
19.06	Cor. 2, M.S. 1971 New York No. 2 lode, identical with Cor. 1, M.S. 1971 New York No. 1 lode, monumented with a granite stone, 18 x 12 x 6 ins. above ground, firmly set, mkd. NY 2 2 1971 on N face, and NY NO 1 1 1971 on S face, from which original bearing objects

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	A granite rock, 4 x 4 x 3 ft. above ground, bears N 37°15' E, 19 lks. dist., mkd. B + R NY 2 2 1971.  A granite rock, 5 x 3 x 3 ft. above ground, bears S 49°50' W, 32 lks. dist., mkd. B + R NY 1 1 1971. (Record: 48 lks. dist.)
	Not remonumented
	Mineral Survey No. 1971 New York No. 1 Lode
	From Cor. 1, M.S. 1971 New York No. 1 lode, identical with Cor. 2, M.S. 1971 New York No. 2 lode, hereinbefore described.
	S 9°08' E, on line 1-2, M.S. 1971 New York No. 1 lode.
18.52	Intersect the line bet. secs. 26 and 35, at a point from which the 1/4 sec. cor. of secs. 26 and 35, bears S 89°56' E, 6.73 chs. dist., hereinbefore described.
19.82	Cor. 2, M.S. 1971 New York No. 1 lode, monumented with a granite stone, 10 x 10 x 6 ins. above ground, mkd. NY 2 1971, with a mound of stone, 3 ft. base, 3 ft. high, alongside the cor.
	Not remonumented
	Mineral Survey No. 1971 Welcome No. 1 East Lode
	From Cor. 2, M.S. 1971 New York No. 1 lode, hereinbefore described.
	N 85°56' W, on line 2-1 M.S. 1971 Welcome No.1 East lode.
4.83	Cor. 1, M.S. 1971 Welcome No. 1 East lode, identical with Cor. 2, M.S. 1971 Welcome lode, monumented with a porphyry stone, 10 x 10 x 8 ins. above ground, firmly set, mkd. W 2 1971 on W face, and W 1 E 1 1971 on E face, with a mound of stone, 3 ft. base, 3 ft. high, N of the cor., from which original bearing objects

### CHAINS A granite rock, 3 x 2 1/2 x 2 ft. above ground, bears N 51°15' E, 60 lks. dist., mkd. + BR W 2 1971. A granite rock, 4 x 3 x 2 ft. above ground, bears N 65°15' W, 79 lks. dist., mkd. B + R W 2 1971. (Record: S 65°15' W) Not remonumented Mineral Survey No. 1971 Welcome Lode From Cor. 2, M.S. 1971 Welcome lode, identical with Cor. 1, M.S. 1971 Welcome No. 1 East lode, hereinbefore described. N 70°47' W, on line 2-1, M.S. 1971 Welcome lode. 2.88 Intersect the line bet. secs. 26 and 35, at a point from which the 1/4 sec. cor. of secs. 26 and 35, bears S 89°56' E, 14.07 chs. dist., hereinbefore described. 18.48 Cor. 1, M.S. 1971 Welcome lode, identical with Cor. 2, M.S. 1971 Welcome No. 1 West lode, monumented with an iron post, 1 in. diam., 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. DMS 5 3676 1971 1777 W NO 1 2 W 1 from which original bearing objects A granite rock, 5 x 4 x 4 ft. above ground, bears N 18°05' E, 93 lks. dist., mkd. + BR W 1 W 2 1971. A granite rock, 4 x 4 x 3 ft. above ground, bears S 6°35' W, 11.5 lks. dist., mkd. + BR W 1 1971. The cor. was remonumented in 1920 by Harry E. Jones, U.S. Mineral Surveyor, during the survey of M.S. No. 3676 Dixie Millsite, which was cancelled on May 6, 1983.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Mineral Survey No. 1971 Welcome No. 1 West Lode
	From Cor. 2, M.S. 1971 Welcome No. 1 West lode, identical with Cor. 1, M.S. 1971 Welcome lode, hereinbefore described.
	N 77°25' W, on line 2-1, M.S. 1971 Welcome No. 1 West lode.
3.90	Cor. 4, M.S. 1971 Suney Side lode, on line 2-1, M.S. 1971 Welcome No. 1 West lode, hereinbefore described.
	Mineral Survey No. 2888 Katherine Lode
	From Cor. 4, M.S. 2888 Katherine lode, monumented with a stone 8 x 7 x 6 ins. above ground, firmly set, mkd. K 4 2888 on W face, with a mound of stone, 2 1/2 ft. base, 1 ft. high, S of the cor.
	Not remonumented
	N 30°03' W, on line 4-5, M.S. 2888 Katherine lode.
9.07	Cor. 5, M.S. 2888 Katherine lode, monumented with a stone, 14 x 14 x 8 ins. above ground, firmly set, and mkd. K 5 2888 on S face, with a + on top, with a mound of stone, 3 ft. base, 6 ins. high, N of the cor.
	Not remonumented
į	From this cor., the 1/4 sec. cor. of secs. 34 and 35, bears N 86°47' W, 12.46 chs. dist., hereinbefore described.
	N 59°58' E, on line 5-1, M.S. 2888 Katherine lode.
22.78	Cor. 1, M.S. 2888 Katherine lode, monumented with a stone, 10 x 10 x 8 ins. above ground, firmly set, mkd. K 1 2888 on S face, with a mound of stone, 3 ft. base, 2 ft. high, N of the cor., from which original bearing objects

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	A rock, 4 x 4 x 4 ft. above ground, bears N 76° E, 95 lks. dist., mkd. B + R M-1-2888 K-1-2888. (Record: S 72°56' E)
	A rock, 5 x 4 x 4 ft. above ground, bears S 57°44' W, 38.2 lks. dist., mkd. B + R K-1-2888 M-1-2888. (Record: 36.7 lks. dist.)
	Not remonumented
	S 29°53' E, on line 1-2 M.S. 2888 Katherine lode.
0.445	Cor. 1, M.S. 2888 Katherine lode, monumented with a stone, 12 x 12 x 8 ins. above ground, firmly set, mkd. M 1 2888, with a mound of stone, 2 1/2 ft. base, 18 ins. high, alongside the cor., from which original bearing objects
	A rock, 4 x 4 x 4 ft. above ground, bears N 46°11' E, 94.5 lks. dist., mkd. B + R M-1-2888 K-1-2888. (Record: 95.5 lks. dist.)
	A rock, 5 x 4 x 4 ft. above ground, bears N 70°39' W, 59 lks. dist., mkd. B + R K-1-2888 M-1-2888. (Record: 56 lks. dist.)
	Not remonumented
	Mineral Survey No. 2888 Margaret Lode
	From Cor. 1, M.S. 2888 Margaret lode, hereinbefore described.
	N 77°47' E, on line 1-4, M.S. 2888 Margaret lode.
22.69	Cor. 4, M.S. 2888 Margaret lode, monumented with a stone, 14 x 14 x 8 ins. above ground, firmly set, mkd. M 4 2888 on S face, with a mound of stone, 3 ft. base, 18 ins. high, S of the cor.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 30°01' E, on line 4-3, M.S. 2888 Margaret lode.
9.06	Cor. 3, M.S. 2888 Margaret lode, monumented with a stone, 7 x 7 x 7 ins. above ground, firmly set, mkd. M 3 2888 on N face, with + on top, with a mound of stone, 3 ft. base, 2 ft. high, S of the cor., from which original bearing objects
	A rock, 24 x 24 x 18 ins. above ground, bears N 71°30° E, 39.3 lks. dist., mkd. B + R M 3 2888. (Record: 40 lks.)
	A rock, 5 x 4 x 4 ft. above ground, bears S 63°15' E, 62 lks. dist., mkd. B + R M 3 2888.
	Not remonumented
	Mineral Survey No. 2888 Grantley Lode
	From Cor. 3, M.S. 2888 Margaret lode, hereinbefore described.
	N 77°35' E, on a line between Cor. 3, M.S. 2888 Margaret lode and Cor. 4, M.S. 2888 Grantley lode.
11.13	Cor. 4, M.S. 2888 Grantley lode, monumented with a stone, 12 x 9 x 5 ins. above ground, firmly set, mkd. G 4 2888 on S face, and a + on top, from which original bearing objects
	A rock, 3 x 2 x 2 ft. above ground, bears N 69°15' E, 33.3 lks. dist., mkd. B + R G 4 2888.
	A rock, 2 x 2 x 1 ft. above ground, bears N 89° E, 13.6 lks. dist., mkd. B + R G 4 2888.
	Not remonumented
	S 24°57' E, on line 4-3, M.S. 2888 Grantley lode.
9.09	Cor. 3, M.S. 2888 Grantley lode, monumented with a stone, 15 x 10 x 8 ins. above ground, firmly set, mkd. G 3 2888 on N face, and a + on top, from which original bearing objects

	1 10 N, R 5 W, GITA and Salt River Mer., Arizona
CHAINS	
	A rock, 6 x 6 x 6 ft. above ground, bears N 49°30' E, 37 lks. dist., mkd. B + R G 3 2888.
	A rock, 5 x 5 x 4 ft. above ground, bears N 28°15' W, 34 lks. dist., mkd. B + R G 3 2888.
	Not remonumented
	From this cor., the 1/4 sec. cor. of secs. 35 and 36, bears S 76°14' E, 6.36 chs. dist., hereinbefore described.
	S 78°06' W, on line 3-2, M.S. 2888 Grantley lode.
20.12	Intersect line 3-4, M.S. 2888 Denver lode, at a point from which Cor. 4, M.S. 2888 Denver lode, bears N 7°17' E, 3.94 chs. dist., hereinafter described.
22.61	Cor. 2, M.S. 2888 Grantley lode, monumented with a stone, 12 x 7 x 7 ins. above ground, mkd. W C G 2 2888 on W face, and + on top, with a mound of stone, 3 ft. base, 1 ft. high, S of the cor.
	Not remonumented
	Mineral Survey No. 2888 Denver Lode
	From Cor. 4, M.S. 2888 Denver lode, monumented with a stone, 12 x 12 x 6 ins. above ground, mkd. D 4 2888 on SW face, from which original bearing objects
	A rock, 3 x 3 x 2 ft. above ground, bears S 68°01' E, 69 lks. dist., mkd. B + R D 4 2888.
	A rock, 4 x 4 x 4 ft. above ground, bears S 59°10' E, 1.00 ch. dist., mkd. B + R D 4 2888.
	Not remonumented
	S 7°17' W, on line 4-3, M.S. 2888 Denver lode.
3.94	Intersect line 2-3, M.S. 2888 Grantley lode, at a point from which Cor. 2, M.S. 2888 Grantley lode bears S 78°06' W, 2.49 chs. dist., hereinbefore described.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
22.72	Cor. 3, M.S. 2888 Denver lode, monumented with a stone, 12 x 12 x 5 ins. above ground, firmly set, mkd. D 3 2888 on SW face, and a + on top, set in a mound of stone, 3 ft. base, 1 ft. high.
	Not remonumented
	S 64°47' W, on line 3-2, M.S. 2888 Denver lode.
9.08	Cor. 2, M.S. 2888 Denver lode, monumented with a stone, 12 x 10 x 8 ins. above ground, mkd. D 2 2888 on NE face, from which an original bearing object
	A rock, 3 x 4 x 1 ft. above ground, bears N 49°50' W, 94 lks. dist., mkd. B + R D 2 2888.
	Not remonumented
	N 7°19' E, on line 2-1 M.S. 2888 Denver lode.
13.65	Cor. 4, M.S. 2888 Germanic lode, monumented with a stone, 15 x 12 x 6 ins. above ground, mkd. G 4 2888 on N face, and a + on top, with a mound of stone, 3 ft. base, 3 ft. high, W of the cor.
	Mineral Survey No. 2888 Germanic Lode
	From Cor. 4, M.S. 2888 Germanic lode, hereinbefore described.
	S 64°54' W, on line 4-3, M.S. 2888 Germanic lode.
22.78	Cor. 3, M.S. 2888 Germanic lode, monumented with a stone, 12 x 10 x 10 ins. above ground, firmly set, mkd. G 3 2888 on N face, and a + on top, with a mound of stone, 2 1/2 ft. base, 18 ins. high, alongside.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 7°20' E, on line 3-2, M.S. 2888 Germanic lode.
8.01	Cor. 2, M.S. 2888 Germanic lode, monumented with a stone, 8 x 8 x 6 ins. above ground, firmly set, mkd. G 2 2888 on S face, and a + on top.
	Not remonumented
	Mineral Survey No. 2888  Chester Lode
	From Cor. 2, M.S. 2888 Germanic lode, hereinbefore described.
	S 54°54' W, on line 4-3 M.S. 2888 Chester lode.
17.53	Cor. 3, M.S. 2888 Chester lode, monumented with a stone, 12 x 12 x 10 ins. above ground, mkd. C 3 2888 on N face, and a + on top, from which an original bearing object
	A rock, 24 x 6 x 6 ins. above ground, bears S 31°26' W, 38 lks. dist., mkd. C 3 2888.
	Not remonumented
	N 24°17' W, on line 3-2, M.S. 2888 Chester lode and the W Center End Cor.
4.55	West Center End Cor., M.S. 2888 Chester lode, monumented with a mound of stone, 3 ft. base, 2 ft. high.
	At the cor. point
	Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, 2 1/2 ins. diam., bonded to a magnetic poly break-away base, 8 ins. in the ground, and in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	WEST END CTR
	S35 CHESTER  MS 2288  1983

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 25°53' W, on a line between the W Center End Cor. and Cor.2, M.S. 2888 Chester lode.
4.52	Cor. 2, M.S. 2888 Chester lode, monumented with a stone, 8 x 6 x 5 ins. above ground, firmly set, mkd. C 2 2888 on S face, and a + on top, with a mound of stone, 3 1/2 ft. base, 18 ins. high, N of the cor., from which a local bearing object
	A stone, 14 x 18 x 2 ins. above ground, bears N 20° E, 106 lks. dist., mkd. B M.
	Not remonumented
	N 54°52' E, on line 2-1 M.S. 2888 Chester lode.
11.64	Cor. 4, M.S. 2888 Katherine lode, hereinbefore described.
	Mineral Survey No. 1736 Stanton Lode
	From Cor. 3, M.S. 1736 Stanton lode, monumented with a stone, 12 x 10 x 7 ins. above ground, firmly set, mkd. S 3 1736 on N face, and a + on top, with a mound of stone, 3 ft. base, 3 ft. high, N of the cor., from which an original bearing object
	A rock, 10 x 8 x 4 ft. above ground, bears N 58° E, 25 lks. dist., mkd. + BR 1736 3.
	Not remonumented
	From this cor., the 1/4 sec. cor. of secs. 35 and 36 bears S 64°04' E, 5.04 chs. dist., hereinbefore described.
	N 31°49' W, on line 3-4, M.S. 1736 Stanton lode.
4.94	Intersect the line between E Center End point and the NE cor. of the unsurveyed Trinadad lode.
9.24	Cor. 4, M.S. 1736 Stanton lode, monumented with a stone, 24 x 14 x 10 ins. above ground, mkd. + 4 S 1736.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 81°21' E, on line 4-5, M.S. 1736 Stanton lode.
2.74	Intersect the line between the E Center End point and the NE Cor. of the unsurveyed Trinadad lode.
9.51	Intersect the line bet. secs. 35 and 36, at a point from which the 1/4 sec. cor. of secs. 35 and 36 bears S 0°03' E, 11.48 chs. dist., hereinbefore described.
9.84	Cor. 5, M.S. 1736 Stanton lode, monumented with a stone, 18 x 8 x 6 ins. above ground, mkd. 5 S 1736 on S face, with a mound of stone, 3 ft. base, 3 ft. high, W of the cor.
	Not remonumented
	from which a new bearing object
	A rock, 13 x 6 x 3 ft., bears S 10° E, 29 lks. dist., mkd. X BO.
	N 58°49' E, on line 5-6, M.S. 1736 Stanton lode.
13.01	Cor. 6, M.S. 1736 Stanton lode, identical with Cor. 3, M.S. 1744 Blue G lode, monumented with a stone, 16 x 6 x 4 ins. above ground, firmly set, mkd. 6 S 1736 on W face, and 3 GB 1744 on E face, with a mound of stone, 3 ft. base, 3 ft. high, W of the cor.
	Not remonumented
	Mineral Survey No. 1744 Blue G Lode
	From Cor. 3, M.S. 1744 Blue G lode, identical with Cor. 6, M.S. 1736 Stanton lode, hereinbefore described.
<del></del>	L

CHAINS N 52°39' E, on line 3-4, M.S. 1744 Blue G lode. 22.74 Point for Cor. 4, M.S. 1744 Blue G lode, determined using the grant bdy. proportion method; there is no evidence of the original cor. Set an aluminum post, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd. **S36** BLUE G MS 1744 1983 from which a new bearing object A power pole with a spike at base, bears S 32° W, 52.5 lks. dist. Set a steel fence post near the cor. Cor. is located 20 lks. S of a track road, 15 lks. wide, bears S 55° E and N 70° W. S 31°57' E, on a line between Cor. 4, M.S. 1744 Blue G lode and the E Center End Cor. 4.54 East Center End Cor., M.S. 1744 Blue G lode, monumented with a granite stone, 12 x 6 x 8 ins. above ground, mkd. ECEBG on S face, and a + on top, with a mound of stone, 3 ft. base, 1 ft. high, S of the cor. S 31°54' E, on a line between the E Center End Cor. and Cor. 1, M.S. 1744 Blue G lode.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
4.55	Cor. 1, M.S. 1744 Blue G lode, identical with Cor. 11, M.S. 4301 Upton Placer Claim # 2, monumented with a malpais stone, 6 x 8 ins. above ground, mkd. B G 1 + on N face and 11 UP 2 4301 on E face, set in a mound of stone, 3 ft. base, 1 ft. high, with a wood post, 4 x 4 ins., 4 ft. long, alongside.
	Not remonumented
	Mineral Survey No. 4301 Upton Placer Claim # 2
	From Cor. 11, M.S. 4301 Upton Placer Claim # 2, identical with Cor. 1, M.S. 1744 Blue G lode, hereinbefore described.
	S 89°01' E, on line 11-12, M.S. 4301 Upton Placer Claim # 2.
11.82	Cor. 12, M.S. 4301 Upton Placer Claim # 2, monumented with a malpais stone, 2 1/2 x 1 1/2 x 1 ft. above ground, mkd. + 12 UP 2 4301 on N face, with a mound of stone, 3 ft. base, 3 ft. high, N of the cor., from which original bearing objects
	A malpais ledge, 20 x 10 x 10 ft. above ground, bears N 70° E, 88 lks. dist., mkd. X B + R 12 UP 2 4301.
	A malpais rock, 4 x 3 x 3 ft. above ground, bears S 12°32' W, 43 lks. dist., mkd. B + R 12 UP2 4301.
	Not remonumented
	S 84°56' E, on line 12-13, M.S. 4301 Upton Placer Claim # 2.
7.04	Cor. 13, M.S. 4301 Upton Placer Claim # 2, monumented with a granite stone, 10 x 8 x 4 ins. above ground, firmly set, mkd. 13 UP2 4301 on S face, with a mound of stone, 3 ft. base, 2 ft. high, N of the cor.
	from which an original bearing object
	A granite rock, 6 x 3 x 3 ft. above ground, bears S 87°08' E, 18 lks. dist., mkd. B + R 13 UP2 4301.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	S 9°18' E, on line 13-14, M.S. 4301 Upton Placer Claim # 2.
14.33	Cor. 14, M.S. 4301 Upton Placer Claim # 2, monumented with a granite stone, 8 x 8 x 4 ins. above ground, mkd. X 14 UP2 4301, with a mound of stone, 3 ft. base, 3 ft. high, N of the cor., from which original bearing objects
	A granite rock, 5 x 3 x 3 ft. above ground, bears N 18°55' E, 6 lks. dist., mkd. B + R 14 UP2 4301.
	A bedrock cropping even with the general surface, bears S 19°02' E, 37 lks. dist., mkd. B + R 14 UP 4301.
	Not remonumented
	S 84°54' E, on line 14-15, M.S. 4301 Upton Placer Claim # 2.
4.54	Cor. 15, M.S. 4301 Upton Placer Claim # 2, monumented with a granite stone, 8 x 8 x 4 ins. above ground, mkd. 15 UP2 4301 on W face, with a mound of stone, 3 ft. base, 2 ft. high, E of the cor., from which an original bearing object
	A rock ledge, 18 x 6 x 4 ft. above ground, bears N 87°45' E, 32 lks. dist., mkd. X BR 15 UP2 4301.
į	Not remonumented
	S 0°58' W, on line 15-16, M.S. 4301 Upton Placer Claim # 2.
9.08	Cor. 16, M.S. 4301 Upton Placer Claim # 2, monumented with a granite stone, 14 x 14 x 12 ins. above ground, mkd. X 16 UP2 4301, from which an original bearing object
	A rock ledge, 15 x 4 x 3 ft. above ground, bears N 55°55' E, 6 lks. dist., mkd. B + R 16 UP2 4301.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 89°00' W, on line 16-17, M.S. 4301 Upton Placer Claim # 2.
10.24	Cor. 17, M.S. 4301 Upton Placer Claim # 2, monumented with a granite rock in place, 10 x 10 x 3 ft. above ground, mkd. + 17 UP2 4301, with a mound of stone, 3 ft. base, 2 ft. high, E of the cor., from which an original bearing object
	A rock outcropping, 10 x 4 x 4 ft. above ground, bears N 29°48' E, 11 lks. dist., mkd. B + R 17 UP2 4301.
	Not remonumented
	S 0°44' E, on line 17-18, M.S. 4301 Upton Placer Claim # 2.
33.10	Cor. 18, M.S. 4301 Upton Placer Claim # 2, monumented with a malpais stone, 26 x 14 x 6 ins. above ground, mkd. UP2 4301, from which an original bearing object
	A granite rock, 10 x 5 ft., level with surface of ground, bears N 85°33' W, 65 lks. dist., mkd. X BR 18 UP2 4301.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	UPTON PLACER 2 MS 4301 18 S36
	Deposit stone alongside the cor.
	Set a steel fence post alongside the cor.
	S 89°59' W, on line 18-1, M.S. 4301 Upton Placer Claim # 2.
1	

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
10.00	Cor. 1, M.S. 4301 Upton Placer Claim # 2, identical with Cor. 10, M.S. 4301 Upton Placer Claim Number # 1, monumented with a granite stone, 9 x 9 x 7 ins. above ground, firmly set, mkd. X 10 UP1 and 1 UP2 4301 with a mound of stone, 3 ft. base, 2 ft. high, alongside, from which an original bearing object
	A malpais rock, 3 x 2 x 1 ft. above ground, bears S 56°17' W, 42 lks. dist., mkd. X BR 10 UP1 and 1 UP2 4301.
	Not remonumented
	Mineral Survey No. 4301 Upton Placer Claim # 1
	From Cor. 10, M.S. 4301 Upton Placer Claim Number # 1, identical with Cor. 1, M.S. 4301 Upton Placer Claim # 2, hereinbefore described.
	S 0°01' E, on line 10-1, M.S. 4301 Upton Placer Claim # 1.
6.82	Cor. 1, M.S. 4301 Upton Placer Claim Number # 1, identical with the 1/4 sec. cor. of secs. 1 and 36, Tps. 9 and 10 N, R 5 W, hereinbefore described.
	S 89°57' W, on line 1-2, M.S. 4301 Upton Placer Claim Number # 1, identical with a portion of the line bet. secs. 1 and 36, on the S bdy. of the Tp.
30.00	Cor. 2, M.S. 4301 Upton Placer Claim Number # 1, hereinbefore described.
	From this cor., the cor. of secs. 1, 2, 35 and 36, Tps. 9 and 10 N, R 5 W, bears S 89°57' W, 10.01 chs. dist., hereinbefore described.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	N 0°03' W, on line 2-3, M.S. 4301 Upton Placer Claim # 1.
30.01	Cor. 3, M.S. 4301 Upton Placer Claim Number # 1, monumented with a schist stone, 4 x 8 x 4 ins. above ground, mkd. 3 UP1 4301, with a mound of stone, 3 ft. base, 3 ft. high, N of the cor., from which an original bearing object
	A rock outcropping, 20 x 6 x 2 ft. above ground, bears S 56°09' W, 41 lks. dist., mkd. X B + R 3 UP1 4301.
	Not remonumented
	N 56°50' E, on line 3-4, M.S. 4301 Upton Placer Claim # 1.
2.41	Cor. 4, M.S. 4301 Upton Placer Claim Number # 1, identical with Cor. 6, M.S. 2201 Midnight lode, monumented with a schist stone, 20 x 14 x 2 ins. above ground, firmly set, mkd. 4 UP1 4301 on W face, and M 6 2201 on E face, from which an original bearing object
	A rock, 4 x 2 x 2 ft. above ground, bears S 85°26' E, 10 lks. dist., mkd. + 4301 BR 6 2201.
	Not remonumented
	Mineral Survey No. 2201  Midnight Lode
	From Cor. 6, M.S. 2201 Midnight lode, identical with Cor. 4, M.S. 4301 Upton Placer Claim Number # 1, hereinbefore described.
	N 4°30' E, on line 6-7, M.S. 2201 Midnight lode.
17.22	Cor. 7, M.S. 2201 Midnight lode, monumented with a stone, 18 x 18 x 10 ins. above ground, mkd. M NO 7 2201, with a mound of stone, 3 ft. base, 3 ft. high, alongside.
	Not remonumented

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	from which a new bearing object
	A rock, 35 x 10 x 4 ft. above ground, bears N 87° W, 34 lks. dist., mkd. X BO.
	Mineral Survey No. 1736 Stanton Lode
	From Cor. 7, M.S. 2201 Midnight lode, hereinbefore described.
	S 58°33' W, on a line between Cor. 7, M.S. 2201 Midnight lode and Cor. 2, M.S. 1736 Stanton lode.
9.54	Cor. 2, M.S. 1736 Stanton lode, monumented with a schist stone, 12 x 12 x 2 ins. above ground, firmly set, mkd. 2 S 1736 on N face, with a mound of stone, E of the cor., from which an original bearing object
	A rock, 6 x 4 x 3 ft. above ground, bears S 66° W, 46.7 lks. dist., mkd. B + R 1736. (Record: S 48° W, 43.5 lks. dist.)
	Not remonumented
	S 81°44' W, on line 2-3, M.S. 1736 Stanton lode.
5.30	Intersect the line bet. secs. 35 and 36, at a point from which the 1/4 sec. cor. of secs. 35 and 36 bears S 0°03' E, 2.86 chs. dist., hereinbefore described.
9.88	Cor. 3, M.S. 1736 Stanton lode, hereinbefore described.
	Mineral Survey No. 2198  Mamie Lode
	From Cor. 4, M.S. 2198 Mamie lode, monumented as described in the official record of the 1979-84 resurvey of T 9 N, R 4 W, by Harry K. Smith and John P. Bennett, under this same group.
	At the cor. point
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with cap mkd.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	MS 2198 MAMIE  4 S6 1983
	N 30°23' W, on line 4-1, M.S. 2198 Mamie Lode.
17.93	Intersect the line bet. secs. 1 and 36, on the S bdy. of T 10 N, R 5 W, at a point from which the cor. of secs. 1 and 36 only, Tps. 9 and 10 N, R 5 W, bears N 89°53' E, 3.38 chs. dist., hereinbefore described.
22.95	Cor. 1, M.S. 2198 Mamie lode, monumented with a granite rock, 30 x 24 x 6 ins. above ground, mkd. + CN 1 M 2198 on W face, with a mound of stone, 3 ft. base, 3 ft. high, W of the cor., from which an original bearing object
	A rock, 5 x 4 x 3 ft. above ground, bears N 59°10' E, 17.0 lks. dist., mkd. B + R 2198. (Record: 18.2 lks.)
	Not remonumented
	N 60°28' E, on line 1-2, M.S. 2198 Mamie lode.
4.42	Intersect line 7-8, M.S. 2200 Gold King lode, at a point from which Cor. 7, M.S. 2200 Gold King lode bears S 5°29' E, 59 lks. dist., hereinafter described.
8.83	Cor. 2, M.S. 2198 Mamie lode, monumented with a granite rock outcropping, 15 x 10 x 3 ft. above ground, mkd. + M NO 2 2198 on top of rock, with a mound of stone, 3 ft. base, 4 ft. high, N of the cor., from which an original bearing object
	A rock, 10 x 10 x 4 ft. above ground, bears N 34° W, 10 lks. dist., mkd. B + R 2198. (Record: N 30°50' W)
	Not remonumented
	Mineral Survey No. 2200 Gold King Lode

CHAINS
--------

From Cor. 7, M.S. 2200 Gold King lode, monumented with a granite rock outcropping, 8 x 3 ft. above ground, mkd. G K NO 7 2200 +, with a mound of stone, 4 ft. base, 4 ft. high, E of the cor., from which an original bearing object


A rock outcropping, bears N 72° E, 18 lks. dist., mkd. B + R.

Not remonumented

N 5°29' W, on line 7-8, M.S. 2200 Gold King lode.

- O.59 Intersect line 1-2, M.S. 2198 Mamie lode, at a point from which Cor. 1, M.S. 2198 Mamie lode bears S 60°28' W, 4.42 chs. dist., hereinbefore described.
- 6.93 Cor. 8, M.S. 2200 Gold King lode, determined using the grant bdy. proportion method; there is no evidence of the original cor.

Set an aluminum post, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, wedged among boulders, with cap mkd.



from which a new bearing object

A rock, 3 x 2 1/2 x 2 ft. above ground, bears N 46° W, 18 lks. dist., mkd. X BO.

Cor. is located on the N side of a draw.

N 59°13' W, on line 8-9, M.S. 2200 Gold King lode.

8.94 Cor. 9, M.S. 2200 Gold King lode, monumented with a granite stone, 12 x 10 x 3 ins. above ground, firmly set, mkd. G K C N 9 2200 on W face, with + on top, with a mound of stone, 3 ft. base,

2 ft. high, N of the cor., from which an original bearing object

A rock, 6 x 3 x 2 ft. above ground, bears N 27° E, 16.9 lks. dist., mkd. B + R. (Record: 18.2 lks.)

CHAINS	1 10 N, N 5 W, GITA ANA BATE NIVEL INT. / INTEGRA
	Not remonumented
	from which a new bearing object
	A granite rock, 3 x 3 x 2 ft. above ground, bears N 65° W, 7.5 lks. dist., mkd. X BO.
	N 18°29' W, on line 9-1, M.S. 2200 Gold King lode.
1.52	Cor. 1, M.S. 2200 Gold King lode, identical with Cor. 4, M.S. 2200 Helen Morris lode, monumented with a granite stone, 20 x 8 x 8 ins. above ground, firmly set, mkd. H M C N 4 2200 on N face and G K C N 1 2200 on S face, with a mound of stone, 3 ft. base, 3 ft. high, S of the cor., from which an original bearing object
	A rock, 4 x 4 x 3 ft. above ground, bears N 6°43' E, 24.6 lks. dist., mkd. B + R. (Record: 26.2 lks.)
	Not remonumented
	Mineral Survey No. 2200 Helen Morris Lode
	From Cor. 4, M.S. 2200 Helen Morris lode, identical with Cor. 1, M.S. 2200 Gold King lode, hereinbefore described.
	N 10°59' W, on line 4-1, M.S. 2200 Helen Morris lode.
22.41	Cor. 1, M.S. 2200 Helen Morris lode, monumented with a granite stone, 18 x 12 x 4 ins. above ground, firmly set, mkd. H M NO 1 2200, with a mound of stone, 4 ft. base, 4 ft. high, E of the cor., from which an original bearing object
	A rock, 6 x 2 1/2 x 2 ft. above ground, bears N 18°10' E, 31 lks. dist., mkd. B + R.
	Not remonumented
	from which a new bearing object
	A rock ledge, 5 x 4 x 4 ft. above ground, bears S 20° W, 42 lks. dist., mkd. X BO.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	Cor. is located 1.20 chs. E of a track road, 20 lks. wide, road bears North and S 10° E.
	N 58°41' E, on a line between Cor. 1, M.S. 2200 Helen Morris lode and Cor. 6, M.S. 2199 Mountaineer lode.
4.88	Cor. 6, M.S. 2199 Mountaineer lode, monumented with a granite stone, 18 x 12 x 8 ins. above ground, firmly set, mkd. M NO 6 2199 on the E face, with a mound of stone, 4 ft. base, 4 ft. high, E of the cor.; there is no evidence of the original bearing object.
	Not remonumented
	Mineral Survey No. 2199 Mountaineer Lode
	From Cor. 6, M.S. 2199 Mountaineer lode.
	N 13°05' W, on line 6-1, M.S. 2199 Mountaineer lode.
18.16	Cor. 1, M.S. 2199 Mountaineer lode, monumented with a granite rock, 6 x 3 x 2 ft. above ground, mkd. M C NO 1 2199 on top, with a mound of stone, 4 ft. base, 4 ft. high, E of the cor.; there is
	no evidence of the original bearing object.
	Not remonumented
	***************************************
	N 73°47' E, on line 1-2, M.S. 2199 Mountaineer lode.
5.36	Intersect line 3-4, M.S. 4398 Jerome No. 3 lode, at a point from which Cor. 3, M.S. 4398 Jerome No. 3 lode, bears S 26°48' E, 5.73 chs. dist., hereinafter described.
9.03	Cor. 2, M.S. 2199 Mountaineer lode, monumented with a stone, 14 x 14 x 8 ins. above ground, firmly set, mkd. with a + on top, and M NO 2 2199 on the W face, from which an original bearing object

	1 10 N, R 3 W, GIIa and Salt River Mer., Arizona
CHAINS	
	A granite rock, 3 x 3 x 2 ft. above ground, bears S 82 1/2° E, 22 lks. dist., mkd. B + R. (Record: S 71°30' E, 20.5 lks. dist.)
	Not remonumented
	S 16°31' E, on line 2-3, M.S. 2199 Mountaineer lode.
5.36	Intersect line 2-3, M.S. 4398 Jerome No. 3 lode, at a point from which Cor. 2, M.S. 4398 Jerome Extension lode, on line 2-3, M.S. 4398 Jerome No. 3 lode, bears N 67°56' E, 14.8 lks. dist., hereinafter described.
22.30	Intersect the line bet. secs. 31 and 36, on the E bdy. of T 10 N, R 5 W, at a point from which the witness 1/4 sec. cor. of sec. 36 only, bears S 0°02' E, 1.78 chs. dist., hereinbefore described.
22.66	Cor. 3, M.S. 2199 Mountaineer lode, identical with Cor. 2, M.S. 2199 Golden Mountain Side lode, monumented with a rock outcropping, 20 x 20 ft. above ground, mkd. X on top and M C NO 3 on N face, and C NO 2 GM S 2199 on S face, with a mound of stone, 3 ft. base, 3 ft. high, E of the cor., from which an original bearing object  The face of a rock cliff, bears N 73°43' E, 5.2 lks. dist., mkd. B + R.
	Not remonumented
	Mineral Survey No. 4398  Jerome Extension Lode
	From Cor. 4, M.S. 4398 Jerome Extension lode, monumented with a granite rock in place, 4 x 3 x 2 ft. above ground, mkd. X on top, from which the original bearing objects
	An iron pipe, 1/2 in. diam., projecting 12 ins. above ground, set in a mound of stone, 3 ft. base, 2 ft. high, with a copper plate attached to the pipe, mkd. 4398 JE-4, bears N 8° E, 3 lks. dist.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona
CHAINS	
	A granite rock outcropping, 10 x 2 x 5 ft. above ground, bears S 67°54' W, 1.84 chs. dist., mkd. X on the top.
	Not remonumented
5	S 68°06' W, on line 4-1, M.S. 4398 Jerome Extension lode.
6.16	Witness cor. to Cor. 1, M.S. 4398 Jerome Extension lode, monumented with an iron pipe, 36 ins. long, 1/2 in. diam., set upright over X WC mkd. in bedrock of cliff top edge, and in a mound of stone, 4 ft. base, to top, with bolted copper plate attached to the pipe, mkd.
	4398
	WC -
	JE 1
9.08	True point for Cor. 1, M.S. 4398 Jerome Extension lode, determined at record dist. and on an extension of the end line from the witness cor.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with cap mkd.
	MS 4398  JEROME  EXTENSION  1
	S31
	1983
	from which new bearing objects
	A granite rock outcropping, bears N 58° E, 9 lks. dist., mkd. X BO.
	A granite rock outcropping, bears N 51 1/2° W, 34 lks. dist., mkd. X BO.
	N 17°44' W, on line 1-2, M.S. 4398 Jerome Extension lode.

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona			
CHAINS				
7.29	Intersect the line bet. secs. 31 and 36, at a point from which the witness 1/4 sec. cor. of sec. 36 only, bears S 0°02' E, 3.45 chs. dist.			
22.64	Cor. 2, M.S. 4398 Jerome Extension lode, monumented with an iron pipe, 36 ins. long, 1/2 in. diam., supported in a mound of stone, 3 ft. base, 3 ft. high, with copper plate attached to the pipe, mkd. 4398 JE 2.			
	Not remonumented			
	from which a new bearing object			
	A rock, 12 x 5 x 4 ft. above ground, bears N 78° E, 15 lks. dist., mkd. X BO.			
	Cor. is located 80 lks. N of a track road, 15 lks. wide, bears N 60° E and S 60° W.			
	Mineral Survey No. 4398 Jerome No. 3 Lode			
	From Cor. 3, M.S. 4398 Jerome No. 3 lode, monumented with an iron pipe, 36 ins. long, 1/2 in. diam., projecting 12 ins. above ground, set in a mound of stone, 3 ft. base, 2 1/2 ft. high, with copper plate attached to the pipe mkd. 4398 J3 3, from which an original bearing object			
	A granite rock, 4 x 4 x 2 ft. above ground, bears N 67°54' E, 3 lks. dist., mkd. B + R.			
	Not remonumented			
	N 26°48' W, on line 3-4, M.S. 4398 Jerome No. 3 lode.			
5.73	Intersect line 1-2, M.S. 2199 Mountaineer lode, at a point from which Cor. 2, M.S. 2199 Mountaineer lode bears N 73°47' E, 3.67 chs. dist., hereinbefore described.			
22.96	Cor. 4, M.S. 4398 Jerome No. 3 lode, monumented with an iron pipe, 36 ins. long, 1/2 in. diam., supported in a mound of stone, 3 ft. base, 3 ft. high, with copper plate attached to the pipe mkd. 4398 J3 4, from which an original bearing object			

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona		
CHAINS			
	A rock, 4 x 2 x 2 ft. above ground, bears S 44°23' W, 3 lks. dist., mkd. with an X.		
	Not remonumented		
<u> </u>	from which a new bearing object		
	A rock, 3 x 2 x 2 ft. above ground, bears S 43° E, 9.5 lks. dist., mkd. X BO.		
	N 65°44' E, on line 4-1, M.S. 4398 Jerome No. 3 lode.		
4.44	Intersect the line bet. secs. 25 and 36, at a point from which the 1/4 sec. cor. of secs. 25 and 36, bears S 89°59' W, 26.44 chs. dist., hereinbefore described.		
7.72 Cor. 1, M.S. 4398 Jerome No. 3 lode, monumented with an in pipe, 36 ins. long, 1/2 in. diam., supported in a mound of 3 ft. base, 3 1/2 ft. high, with copper plate attached to pipe mkd. 4398 J3 1,			
	from which new bearing objects		
	A rock, 2 1/2 x 2 1/2 x 2 1/2 ft. above ground, bears N 17 1/2° E, 13 lks. dist., mkd. X BO.		
	A rock, 2 x 2 x 2 ft. above ground, bears S 32° E, 20 lks. dist., mkd. X BO.		
	S 30°07' E, on line 1-2, M.S. 4398 Jerome No. 3 lode.		
1.56	Intersect the line bet. secs. 25 and 36, at a point from which the 1/4 sec. cor. of secs. 25 and 36 bears S 89°59' W, 30.21 chs. dist., hereinbefore described.		
11.72	Intersect line 4-1, M.S. 4398 Jerome lode, at a point from which Cor. 4, M.S. 4398 Jerome lode, bears S 54°01' W, 4.18 chs. dist., hereinafter described.		
23.41	True point for Cor. 2, M.S. 4398 Jerome No. 3 lode. This cor. point falls on a steep slope of bedrock where it is impractical to establish a permanent monument.		

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona				
CHAINS					
	S 67°56' W, on a line between Cor. 2, M.S. 4398 Jerome No. 3 lode and Cor. 3 M.S. 1398 Jerome lode				
0.28	Witness cor. for Cor. 2, M.S. 4398 Jerome No. 3 lode, on line 2-3, M.S. 4398 Jerome Extension lode, monumented with an iron pipe, 36 ins. long, 1/2 in. diam., supported in a mound of stone, 4 ft. base, 3 ft. high, with copper plate attached to the pipe mkd. 4398 WC J3 2.				
	Not remonumented				
	from which a new bearing object				
	A rock, 3 x 3 x 1 ft. above ground, bears S 6° E, 17 lks. dist., mkd. X BO.				
	Mineral Survey No. 4398  Jerome Lode				
	From Cor. 4, M.S. 4398 Jerome lode, determined at record bearing and dist. from the original bearing object				
	A granite rock, 6 x 3 x 3 ft. above ground, bears N 42°35' E, 0.8 lk. dist., mkd. X on top.				
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with cap mkd.				
	JEROME 4 JEROME NO 3 MS 4398				
	1983				
	from which a new bearing object				
	A granite rock, 4 x 4 x 3 ft. above ground, bears S 72° W, 9 lks. dist., mkd. X BO.				
	N 54°01' E, on line 4-1, M.S. 4398 Jerome lode.				
4.18	Intersect line 1-2, M.S. 4398 Jerome No. 3 lode, at a point from which Cor. 1, M.S. 4398 Jerome No. 3 lode, bears N 30°07' W, 11.72 chs. dist., hereinbefore described.				

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona			
CHAINS				
9.04	Cor. 1, M.S. 4398 Jerome lode, determined using the grant bdy. proportion method; there is no evidence of the original cor.			
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 2 ins. in the ground, supported and in a mound of stone, 4 ft. base, to top, with cap mkd.			
	S36			
	JEROME \			
	MS 4398 1983			
	from which a new bearing object			
	A granite rock, bears N 10° E, 6 lks. dist., mkd. X BO.			
	Cor. is located in a wash, 1.00 ch. wide, course S 50° W.			
	S 34°17' E, on line 1-2, M.S. 4398 Jerome lode.			
1.36	Intersect the line bet. secs. 31 and 36, on the E bdy. of the Tp., at a point from which the cor. of secs. 25 and 36 only, T 10 N, R 5 W, bears N 0°02' W, 7.065 chs. dist., hereinbefore described.			
22.59	Cor. 2, M.S. 4398 Jerome lode, monumented with an iron pipe, 1/2 in. diam., projecting 8 ins. above a mound of stone, 3 ft. base, 3 ft. high, with copper plate attached to the pipe mkd. 4398 J2; there is no evidence of the original bearing object.			
	Not remonumented			
	from which a new bearing object			
	A rock 3 1/2 x 2 1/2 x 2 1/2 ft. above ground, bears S 34° E, 12 lks. dist., mkd. X BO.			

	T 10 N, R 5 W, Gila and Salt River Mer., Arizona			
CHAINS				
	GENERAL DESCRIPTION			
The area encompassed in this survey is located approximatel mile south of Yarnell and 2 miles NE of Congress, Arizona. elevation ranges from 3,100 to 4,800 feet above sea level.				
	Yarnell creek and Antelope creek flow through the SW portion of the township in a southerly direction.  Access is by way of the Stanton-Octave Road, with a graded surface, which enters the township from the west and from the north off Highway 89 near Yarnell. There are several unimproved roads and jeep trails traversing the township.  The vegetation throughout the township consists primarily of mesquite, paloverde, creosote and cacti.  Mining activity was noticed primarily in section 35.  The mean magnetic declination is 14 1/2° E.			

BOOK 5304

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD ASSISTANTS

NAMES	CAPACITY
Paul L. Reeves	Land Surveyor
Kevin L. Miller	Surveying Technician
Donald L. Brewer	Surveying Technician
Delbert L. Bybee	Surveying Technician
Daniel C. Finkle	Surveying Technician
Neil A. Hemminger	Surveying Technician
Luke B. Granger	Surveying Technician
Rebecca N. Ramirez	Surveying Technician
Robert J. Lyle	Surveying Technician
Delbert L. Bybee  Daniel C. Finkle  Neil A. Hemminger  Luke B. Granger  Rebecca N. Ramirez	Surveying Technician Surveying Technician Surveying Technician Surveying Technician Surveying Technician

153

#### CERTIFICATE OF SURVEY

We, Will C. Gabonay and Duane R. Garoutte, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of January, 1979, and second supplemental instructions dated December 10, 1979. We have perform the dependent resurvey of portions of the south, east, and west boundaries and subdivisional lines, and the survey of the subdivision of certain sections and the dependent resurvey of certain mining claims, and mineral segregation in section 25, of Township 10 North, Range 5 west, of the Gila and Salt River Meridian, in the state of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Will C. Gabonary and Duane R. Garoutte are no longer assigned to this office and are not available for signatures.

2/1/91 fames R. Well (Supervisior, Field Section)

#### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT

The foregoing field notes of the dependent resurvey of portions of the south, east, and west boundaries and subdivisional lines, and the survey of the subdivision of certain sections and the dependent resurvey of certain mining claims, and mineral segregation in section 25, of Township 10 North, Range 5 west, Gila and Salt River Meridian, Arizona, executed by Will C. Gabonary and Duane R. Garoutte, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

(Date)

| CERTIFICATE OF TRANSCRIPT

I Certify that the foregoing transcript of the field notes of the above-described surveys in T 10 N, R 5 W, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.

(Chief Cadastral Surveyor of Arizona)