
ORIGINAL BOOK 5314

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FIELD NOTES OF THE

	DEPENDENT RESURVEY	
	OF PORTIONS	
OF ?	THE CAMP GOODWIN MILITARY RESERVATION (abandoned)	
	OF THE NORTH BOUNDARY	
	OF THE SUBDIVISIONAL LINES	****
THE I	EAST BOUNDARY OF THE SAN CARLOS INDIAN RESERVATION	parameter 18-18
	AND	
	THE SUBDIVISION OF SELECTED SECTIONS	
	IN	
	TOWNSHIP 5 SOUTH, RANGE 22 EAST	
Of the	Gila and Salt River Mer	<u>idian</u> ,
In the State of	Arizona	
	EXECUTED BY	
Paul L. Reeves	, Cadastral Surveyor	
Will C. Gabonay	y , Cadastral Surveyor	
	octions dated <u>April 8</u> , 1982, approved <u>April 8,</u> Decial instructions dated and approved January 11, 1985	1982
	, which provided for the surveys included under Group Nu	mber
	ignment instructions dated April 8 , 1982.	
and January 7, 19		
	Survey commenced April 12 , 1982	
	Survey completed February 23 , 1985	

INDEX DIAGRAM

TOWNSHIP	5 SOUTH ,	RANGE	22 EAST ,

	_	_		12	11
6	5	4	3	2 35	1
7	8	9	10	37—34 11 32 36—31——3	12
18	17	16	15	29 14 26	13
19	20	21	22	23 22	24 20
30	29	28	27	26 18	25 16
31	32	33	34	35 14	36

Bdy. Camp Goodwin pp 4-5
East bdy. San Carlos Indian Resv.pp 6-11
Subdivision Sec. 24 pp 38-41

Subdivision Sec. 25

pp 41-46

BOOK 5314

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of the SE boundary of the Camp Goodwin Military Reservation, (abandoned), the north boundary, the subdivisional lines, the east boundary of the San Carlos Indian Reservation and the subdivision of selected sections in Township 5 South, Range 22 East, Gila and Salt River Meridian, Arizona.

The Camp Goodwin Military Reservation, (abandoned), was surveyed by Clarence H. Wallace, in 1888. The north boundary and subdivisional lines within the Camp Goodwin Military Reservation were surveyed by Clarence H. Wallace, in 1888. The east boundary inside and outside of Camp Goodwin Military Reservation was surveyed by Theodore F. White, in 1875. The San Carlos Indian Reservation was surveyed by P. Riecker, in 1883, resurveyed by C.E. Walker, in 1887 and resurveyed again by Ray Harpin and Douglas A. Cody, in 1973-74. The east boundary was resurveyed by Philip Contzen, in 1900 outside of the Camp Goodwin Military Reservation. The north boundary and subdivisional lines outside the Camp Goodwin Military Reservation were surveyed by Philip Contzen, in 1900. A portion of the subdivisional lines were resurveyed by Will C. Gabonay in 1983.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 8, 1982, and the Supplemental Instructions dated January 11, 1985, for Group No. 634, Arizona.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian. Distances were measured with a Zeiss Elta 46 Total Station instrument.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 25, as determined from a tie to the U.S. Coast and Geodetic Survey triangulation station "STEER", located in section 11, T. 6 S., R. 22 E., is as follows:

NAD 27 Latitude: 32°57'43.10" N Longitude: 110°02'02.83" W

The mean magnetic declination is 13 1/2° E


Dependent Resurvey, of a Portion, Camp Goodwin Military Reservation (abandoned), T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by Clarence H. Wallace, in 1888

Beginning at the point of intersection of the SE boundary of the Camp Goodwin Military Reservation (abandoned) and the line between secs. 7 and 12, on the E. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

From this cor. point, the new cor. no. 2 of the Camp Goodwin Military Reservation, (abandoned), bears N. 44° 57' E., 161.215 chs. dist., monumented with an aluminum post, 1 ins. diam., projecting 14 ins. from the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd. and described in the field note record of the dependent resurvey of the SE bdy. of the Camp Goodwin Military Reservation, T. 5 S., R. 23 E., executed concurrently under this same group.

From this cor. point, the cor. of secs. 1, 6, 7 and 12, bears N. 0°13' W., 25.21 chs. dist., hereinafter described.

From this same cor. point, the 1/4 sec. cor. of sec. 12 only, T. 5 S., R. 22 E., bears S. 0°13' E., 11.41 chs. dist., hereinafter described.

S. 44°57.0' E., on the SE bdy. of the Camp Goodwin Military Reservation, (abandoned).

Point for the closing cor., with the line between secs. 12 and 13, outside Camp Goodwim Military Reservation, hereinafter described.

From this cor. point, the 1/4 sec. cor. of secs. 12 and 13, bears N. 89°53' E., 13.42 chs. dist., hereinafter described.

5

Dependent Resurvey, of a Portion, Camp Goodwin Military Reservation (abandoned), T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
76.995	Point for the closing cor., with the line between secs. 12 and 13, inside Camp Goodwin Military Reservation, hereinafter described.
	From this cor. point, the cor. of secs. 11, 12, 13 and 14, bears S. 87°43' W., 26.25 chs. dist., hereinafter described.
111.145	Point for the closing cor., with the line between secs. 13 and 14, outside Camp Goodwin Military Reservation, hereinafter described.
	From this cor. point, the 1/4 sec. cor. of secs. 13 and 14, bears S. 0°10' E., 13.08 chs. dist., hereinafter described.
114.630	Point for the closing cor., with the line between secs. 13 and 14, inside Camp Goodwin Military Reservation, hereinafter described.
	From this cor. point, the cor. of secs. 11, 12, 13 and 14 bears N. 0°49' E., 25.59 chs. dist., hereinafter described.
138.775	Point for Cor. No. 3 of the Camp Goodwin Military Reservation, on the E. bdy. of the San Carlos Indian Reservation.
	Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.
	T5S R23E
	S14
	CGMR SCIR COR.3
	SCIR COR.3
	1982
	Cor. is located in a N. and S. fence.
	From this cor. point, the original Cor. No. 3 of the Camp Goodwin Military Reservation, bears S. 44°57' W., 46.7 lks. dist., monumented with a granite stone, 11 x 9 x 4 ins., loosely set and mkd. CGMR 3.
	AM the cor., and bury in place.
	From this same cor. point, the 6 1/2 mile post of the San Carlos Indian Reservation, bears N. 0°15' W., 9.87 chs. dist., hereinafter described.

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

From this same cor. point, the 7 mile post of the San Carlos Indian Reservation, bears S. 0°15' E., 30.17 chs. dist., hereinafter described.

Restoring the resurvey by Ray Harpin and Douglas A. Cody, in 1973-74

From the 4 Mile Cor. of the San Carlos Indian Reservation, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from the ground, with brass cap mkd.

SCIR | T4S 4 M | R22E 1974

Not remonumented

A mound of stone, 2 1/2 x 1 ft. is set W. of cor.

Cor. is located in a N. and S. fence.

S. 0°13' E., on Mile 5

3.20 Point for the closing cor. of secs. 2 and 35, on the N. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the of the original cor. position.

A quartz stone, $14 \times 10 \times 6$ ins., mkd. CGMR CC, was found lying loose on the ground, in Reservation fence line, no evidence of original position.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Bury original stone alongside the cor.

From this cor. point, the 1/4 sec. cor. of sec. 2 only, bears S. 89°52' W., 19.94 chs. dist., hereinafter described.

Cor. is located in a N. and S. fence.

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

7.20 Point for the closing cor. of secs. 2 and 35, on the N. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the original cor. position.

A quartz stone, $16 \times 12 \times 6$ ins., mkd. CGMR CC, was found lying loose on the ground, in the Reservation fence line, no evidence of original position.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Bury original stone alongside the cor.

From this cor. point, the cor. of secs. 1 and 2, on the N. bdy. of Tp., bears S. 89°56' E., 17.745 chs. dist., hereinafter described.

Cor. is located in a N. and S. fence.

39.98 The 4 1/2 Mile Cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd.

Not remonumented

A mound of stone, 3 x 1 1/2 ft., is set W. of cor.

Cor. is located in a N. and S. fence.

S. 0°19' E., beginning new measurement

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

40.29 The 5 Mile Cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap

Not remonumented

A mound of stone, 3 x 1 1/2 ft., is set W. of cor.

Cor. is located in a N. and S. fence.

S. 0°15' E., on Mile 6

3.315 Point for a closing cor. with secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor. position.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

From this cor. point the 1/4 sec. cor. of secs. 2 and 11, bears N. 89°50' E., 20.25 chs. dist., hereinafter described.

Cor. is located in a N. and S. fence.

7.135 The closing cor. with the line between secs. 2 and 11, hereinafter described.

From this cor. point, the cor. of secs. 1, 2, 11 and 12, bears N. 89°46' E., 17.61 chs. dist., hereinafter described.

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS **40.11**

The 6 1/2 Mile Cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. from ground, with brass cap mkd.

Not remonumented

Cor. is located in a N. and S. fence.

S. 0°15' E., beginning new measurement

9.87 Cor. No. 3 of Camp Goodwin Military Reservation (abandoned), hereinbefore described.

From this cor. point, original cor. No. 3, of the Camp Goodwin Military Reservation, (abandoned), bears S. 44°57' W., 46.7 lks. dist., hereinbefore described.

40.04 The 7 Mile Cor., monumented with an iron post, 2 1/2 ins. diam., set flush with ground, with brass cap mkd.

Not remonumented

A mound of stone, 2 x 1 ft. is set W. of cor.

Cor. is located in a N. and S. fence.

S. 0°12' E., on Mile 8.

3.57 The crossing closing cor. bet. secs. 14 and 23, hereinafter described.

From this cor. point, the 1/4 sec. cor. of secs. 14 and 23, bears S. 89°54' W., 20.71 chs. dist., hereinafter described.

Dependent Resurvey, Portion of the North Boundary,

	Dependent Resurvey, Portion of the North Boundary, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
40.13	The 7 1/2 Mile Cor., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. from ground, with brass cap mkd.
	SCIR T5S 7 1/2 M R22E 1974
	Not remonumented
	Cor. is located in a N. and S. fence.
	Dependent Resurvey, Portion of the North Boundary, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
	Restoring the survey executed by Clarence H. Wallace, in 1888
	From the cor. of secs. 1, 6, 31 and 36, on the N. bdy of the Tp., monumented with an aluminum post, 1 ins. diam., with aluminum cap, set, mkd. and described in the field note record of the dependent resurvey of the W. bdy., T. 5 S., R. 23 E., executed concurrently under this same group.
	S. 88°40' W., bet. secs. 1 and 36, on the N. bdy., of the Tp.
	Over rolling land, through creosote and scattered mesquite.
40.53	The 1/4 sec. cor. of secs. 1 and 36, monumented with a quartz stone, 13 x 10 x 5 ins., firmly set, projecting 6 ins. from ground, mkd. 1/4 on N. face.
	A mound of stone, 3 x 1 1/2 ft. is set N. of cor.
	At the cor. point

	Dependent Resurvey, Portion of the North Boundary, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona		
CHAINS			
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd. T4S R22E S36 1/4 T5S		
	1985		
	Bury stone alongside the cor.		
	N. 89°56' W., beginning new measurement.		
40.44	Point for the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the original cor.		
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with cap mkd.		
	T4S R22E S35 S36		
	S 2 S 1 T5S 1985		
	Cor. is located, SW, 12 lks. dist., from a fence cor., fences extend S. and W.		
	Set a steel fence post alongside the cor.		
	N. 89°56' W., bet. secs. 2 and 35, on the N. bdy. of the Tp.		
	Over rolling land, through scattered creosote.		
17.745	The closing cor. with the E. bdy. of the San Carlos Indian Reservation, hereinbefore described.		
	From this cor. point, the 4 Mile Cor. of the San Carlos Indian Reservation, bears N. 0°13' W., 7.20 chs. dist., hereinbefore described.		

Dependent Resurvey, Portion of the North Boundary, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by Philip Contzen, in 1900

From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a granite stone, $14 \times 10 \times 8$ ins., firmly set, projecting 2 ins. from ground, mkd. with 2 grooves on E. face, from which the original bearing trees

- A tesota, 18 ins. diam., bears N. 75 1/4° E., 174 lks. dist., no marks visible.
- A tesota stump, 8 ins. diam., bears S. 51 3/4° E., 72 lks. dist., no marks visible.
- A mesquite, 24 ins. diam., bears N. 30 1/2° W., 73 lks. dist., no marks visible.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.

	R22E S35
S 3 T5S	S 2 R22E
198	35

from which new bearing trees

- A mesquite, 10 ins. diam., bears S. 71° E., 184 lks. dist., mkd. T5S R22E S2 BT.
- A mesquite, 4 ins. diam., bears S. 36 1/2° W., 80 lks. dist., mkd. X BT.

Bury original stone alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 53 lks. E. of a track road, bears NE and SW.

N. 89°52' E., bet. secs. 2 and 35, on the N. bdy. of the Tp.

Over gently rolling land, through creosote and scattered mesquite.

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.06	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no evidence of the original cor. position.
	A granite stone, 18 x 12 x 9 ins., mkd. with 2 grooves on one side, was found lying loose on the surface of the ground in a bladed area, no evidence of the original position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4S R22E
	S35 1/4 ———
	s 2
	T5S
	1985
	Bury stone alongside the cor.
	Set a steel fence post alongside the cor.
60.00	The closing cor., with the San Carlos Indian Reservation, hereinbefore described.
	From this cor. point, the 4 Mile Cor. of the San Carlos Indian Reservation, bears N. 0°13' W., 3.20 chs. dist., hereinbefore described.
	Dependent Resurvey, Portion of the Subdivisional Lines, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
	Restoring the resurvey executed by Will C. Gabonay, in 1983
	From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. from the ground, with brass cap mkd.
	T4S R22E
	1/4 S35 S36 1983

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	from which the original bearing trees
	A mesquite, 10 ins. diam., bears S. 86 3/4° E., 230 lks. dist., mkd. /4.
	A mesquite, 8 ins. diam., bears N. 4 1/4° W., 83 lks. dist., mkd. 1/4 S35 BT.
	from which a 1983 bearing tree
	A forked juniper, 8 ins. diam., bears S. 8° E., 51 lks. dist., mkd. 1/4 S36 BT.
	Not remonumented
	N. 0°05' W., bet. secs. 35 and 36.
	Over gently rolling land, through creosote and scattered mesquite.
20.06	Point for the N 1/16 sec. cor. of secs. 35 and 36, not monumented.
40.12	The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. from the ground, with brass cap mkd.
	T5S R22E S26 S25
	S35 S36 1983
	from which original bearing trees
	A mesquite stump, 4 ins. diam., bears S. 25° E., 64 lks. dist., no marks visible.
	A mesquite, 6 ins. diam., bears S. 62 1/4° W., 113.5 lks. dist., no marks visible.
	A mesquite, 6 ins. diam., bears N. 46 1/2° W., 82 lks. dist., no marks visible.

CHAINS

from which the 1983 bearing trees

- A mesquite, 8 ins. diam., bears S. 81° E., 188 lks. dist., mkd. T5S R22E S36 BT.
- A mesquite, 6 ins. diam., bears S. 19° W., 35 lks. dist., mkd. T5S R22E S35 BT.

Not remonumented

From this cor. point, U.S.C.&G.S. triangulation station "STEER 1945", bears S. 24°37'18" W., 197.422 chs. dist., monumented with a stan. brass cap, 3 1/2 ins. diam., set in an iron pipe, 10 ins. above ground, and in a mound of stone, 3 ft. base, mkd. U.S.C.&G.S. STEER 1945, and a triangle in the center.

Restoring the survey executed by Philip Contzen, in 1900

From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with a granite stone, $12 \times 8 \times 6$ ins., firmly set, projecting 6 ins. from the ground, mkd. with 5 notches on the N. face.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with cap mkd.

from which

- A mesquite, 5 ins. diam., bears S. 62° W., 85 lks. dist., mkd. T5S R22E S36 BT.
- A mesquite, 5 ins. diam., bears N. 14° W., 47 lks. dist., mkd. T5S R22E S25 BT.

Bury stone alongside the cor.

CHAINS

S. 89°53' W., bet. secs. 25 and 36.

Over gently rolling land, through creosote and scattered mesquite.

Point for the E 1/16 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.

Cor. is located, N. 37 1/2° W., 87.5 lks. dist. from a fence cor., fences extend N. and W.

Set a steel fence post alongside the cor.

38.475 The 1/4 sec. cor. of secs. 25 and 36, determined from an original bearing tree

A mesquite, 16 ins. diam., bears N. 89° E., 3.00 lks. dist., mkd. 25 BT.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

from which

A mesquite, 8 ins. diam., bears S. 53° W., 3.19 lks. dist., mkd. 1/4 S36 BT.

A quartz stone, $18 \times 12 \times 3$ ins., was found lying loose, mkd. 1/4 24 on one side and 24 on another, no evidence of original position.

	T. 5 S., R. 22 E., Gila and Sait River Meridian, Arizona
CHAINS	
	Bury original stone alongside the cor.
	Cor. is located S. 65° E., 19 lks. dist., from cor. of corral, fences extend E. and S.
	Set a steel fence post alongside cor.
	S. 89°49' W., beginning new measurement.
40.99	The cor. of secs. 25, 26, 35 and 36.
	Restoring the resurvey executed by Will C. Gabonay, in 1983
	N. 0°06' W., bet. secs. 25 and 26.
	Over rolling land, through creosote and mesquite.
40.14	The 1/4 sec. cor. of secs. 25 and 26, monumented with an aluminum post, 3/4 in. diam., set 6 ins. below surface of ground, with aluminum cap mkd.
	T5S R22E
	1/4
	S26 S25 1983
	from which 1983 reference monuments
	An aluminum post, 3/4 in. diam., projecting 4 ins. from the ground, for a reference monument, bears N. 20°05' E., 76.19 ft. dist., with cap mkd. RM T5S R22E 1/4 S25 76.19 FT 1983, and an arrow pointing to the cor.
	An aluminum post, 3/4 in. diam., projecting 4 ins. from the ground, for a reference monument, bears N. 49°03' W., 76.09 ft. dist., with cap mkd. RM T5S R22E 1/4 S26 76.09 FT 1983, and an arrow pointing to the cor.
	Not remonumented
	Cor. is located in Black Rock Wash, 80 lks. wide, drains NE.

Dependent Resurvey, Portion of the Subdivisional Lines,

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°06' W., beginning new measurement.
20.07	Point for the N 1/16 sec. cor. of secs. 25 and 26.
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with cap mkd.
	T5S R22E
	N 1/16
	S26 S25
	1985
	Set a steel fence post alongside the cor.
40.14	The cor. of secs. 23, 24, 25 and 26, monumented with an aluminum post, 3/4 in. diam., projecting 4 ins. from the ground, with aluminum cap mkd.
	T5S R22E
	S23 S24
	026 025
	S26 S25 1983
	from which the original bearing trees
	A mesquite stump, 5 ins. diam., bears N. 17 1/2° E., 235 lks. dist., no marks visible. (Record: 232 lks. dist.)
	A mesquite, 4 ins. diam., bears S. 71° E., 192 lks. dist., no marks visible. (Record: 194 lks. dist.)
	A mesquite, 6 ins. diam., bears S. 51° W., 217 lks. dist., no marks visible (Record: 219 lks. dist.)
	Not remonumented
	A mound of stone, 2 1/2 x 1 1/2 ft. is set W. of cor.
	Cor. is located 2.25 chs. N. of a wash, 60 lks. wide, drains easterly.
	From this cor. point , a Bench Mark, bears N. 11°51'53" W., 15.612 chs. dist., monumented with a brass tablet, 3 ins. diam., set in a base of concrete, 12 x 12 x 5 ins., with cap mkd. ELEVATION ABOVE SEA 3172 FEET 32B 1943, and a triangle and cross in center of cap, with a 4 x 4 in. wood post, projecting 3 ft. from the ground, in a mound of stone, 2 ft. base, 1 ft. high, alongside Bench Mark.

CHAINS

Restoring the survey executed by Philip Contzen, in 1900

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented with a granite stone, 18 x 8 x 8 ins., firmly set, projecting 8 ins. from the ground, mkd. with 2 notches on the S. edge and 4 notches on the N. edge.

A mound of stone, 2 x 1 ft. is set S. of cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

T5S R22E R23E S24 | S19 S25 | S19

Bury stone alongside the cor.

Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

S. 89°52' W., bet. secs. 24 and 25.

Over rolling land, through creosote and scattered mesquite.

19.125 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 28 ins. long, 1 in. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with cap mkd.

Set a steel fence post alongside the cor.

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
39.185	The $1/4$ sec. cor. of secs. 24 and 25, monumented with a granite stone, $14 \times 6 \times 7$ ins., projecting 7 ins. from the ground, mkd. $1/4$ 24 on N. face and 25 on S. face.
	A mound of stone, $3 \times 1 \frac{1}{2}$ ft. is set along side the cor.
	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 26 ins. in the ground, with cap mkd.
	T5S R22E
	1/4 ———
	S25
	1985
	Bury stone alongside the cor.
	Rebuild the mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.
	Set a steel fence post alongside the cor.
	S. 89°57' W., beginning new measurement.
20.075	Point for the W 1/16 sec. cor. of secs. 24 and 25.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with cap mkd.
	T5S R22E
	S24
	W 1/16 ——————————————————————————————————
	1985
	from which
	A mesquite, 8 ins. diam., bears N. 76° E., 115 lks. dist., mkd. W 1/16 S24 BT.
	A mesquite, 12 ins. diam., bears S. 45 1/2° W., 111 lks. dist., mkd. W 1/16 S25 BT.

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a steel fence post alongside the cor.
	Cor. is located 30 lks. N. of a wash, 25 lks. wide, drains SE.
40.15	The cor. of secs. 23, 24, 25 and 26.
	N. 0°05' W., bet. secs. 23 and 24.
	Over rolling land, through creosote and scattered juniper.
40.15	The 1/4 sec. cor. of secs. 23 and 24, monumented with a granite stone, 15 x 10 x 6 ins., loosely set, projecting 8 ins. from the ground, mkd. 1/4 23 on W. face and 24 on E. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T5S R22E 1/4
	S23 S24 1985
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Bury stone alongside the cor.
	Set a steel fence post alongside the cor.
	N. 0°07' W., beginning new measurement.
40.22	Cor. of secs. 13, 14, 23 and 24, monumented with a granite stone, 13 x 7 x 7 ins., firmly set, projecting 10 ins. from the ground, mkd. with 3 grooves on the S. face, and 1 groove on the E. face, from which an original bearing tree.
	A mesquite, 14 ins. diam., bears S. 11 1/4° E., 228 lks. dist., mkd. T5S R22E S24 BT. (Record: 224 lks. dist.)

CHAINS

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

from which new bearing trees

- A mesquite, 13 ins. diam., bears N. 49 3/4° E., 250 lks. dist., mkd. T5S R22E S13 BT.
- A mesquite, 9 ins. diam., bears S. 36°28' W., 79.5 lks. dist., mkd. T5S R22E S23 BT.

Deposit a magnet in a $1 \times 1 \times 2 = 5/8$ ins. white colored plastic case beneath the stainless steel post.

Bury stone alongside the cor.

Set a steel fence post alongside the cor.

From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with a granite stone, 8 x 12 ins., firmly set, with 3 notches on the N. edge and 3 notches on the S. edge, from which original bearing trees

- A mesquite, 6 ins. diam., bears S. 40° W., 290 lks. dist., no marks visible.
- A mesquite, 6 ins. diam., bears N. 81° W., 197 lks. dist., no marks visible.

At the cor. point

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with cap mkd.

Bury stone alongside the cor.

S. 89°58' W., bet. secs. 13 and 24.

Over rolling land, through medium creosote and scattered mesquite.

38.84

The 1/4 sec. cor. of secs. 13 and 24, monumented with a granite stone, 16 x 10 x 5 ins., firmly set, projecting 8 ins. from the ground, mkd. 1/4 13 on N. face and 24 on S. face, from which original bearing trees

- A mesquite stump, 6 ins. diam., bears S. 49 3/4° W., 76 lks. dist., with illegible scribe marks.
- A mesquite, 8 ins. diam., bears N. 17° W., 355 lks. dist., with illegible scribe marks. (Record: N. 17° E.)

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Bury original stone alongside the cor.

Set a steel fence post alongside the cor.

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 89°58' W., beginning new measurement.
40.21	The cor. of secs. 13, 14, 23 and 24.
	S. 89°54' W., bet. secs. 14 and 23.
	Over rolling land, through medium creosote and scattered mesquite.
19.49	Point for a crossing closing cor. at the intersection with the E. bdy. of the San Carlos Indian Reservation.
	T5S R22E S S14 S14 C CC
	1985
	From this cor. point, the 7 Mile Cor., on the San Carlos Indian Reservation, bears N. 0°12' W., 3.57 chs. dist., hereinbefore described.
40.20	The 1/4 sec. cor. of secs. 14 and 23, monumented with a granite stone, 12 x 8 x 5 ins., firmly set, projecting 4 ins. from the ground, mkd. 1/4 14 on N. face and 23 on S. face, from which original bearing trees
	A mesquite, 8 ins. diam., bears N. 13 1/4° E., 105 lks. dist., with illegible scribe marks. (Record: 104 lks. dist.)
	A mesquite, 10 ins. diam., bears S. 48° E., 112 lks. dist., with marks visible 1/4 S23. (Record: S 49 1/2° E, 113 lks. dist.)
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T5S R22E
	S14
	1/4 ————————————————————————————————————
	1985
	Set a steel fence post alongside the cor.
1	1

	1. 5 5., R. 22 E., GIIA AM DAIL RIVEL PERIODAL, ALIZONA
CHAINS	
	From the cor. of secs. 13, 14, 23 and 24.
	N. 0°06' W., bet. secs. 13 and 14.
	Over rolling land, through creosote and scattered mesquite.
40.18	The 1/4 sec. cor. of secs. 13 and 14, monumented with a granite stone, 14 x 10 x 9 ins., firmly set, projecting 6 ins. from the ground, mkd. 1/4 14 on W. face and 13 on E. face
	A scattered mound of stone is set W. of cor.
	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base to top, with cap mkd.
	T5S R22E
	1/4 S14 S13
	1985
	Bury stone alongside the cor.
	Set a steel fence post alongside the cor.
	N. 0°10' W., beginning new measurement.
12.47	A granite stone, 10 x 12 x 8 ins., firmly set, projecting 10 ins. from the ground, mkd. CGMR on N. face and CC on S. face, set for a closing cor. for secs. 13 and 14, in 1900.
	A mound of stone, 3 ft. x 6 ins. is set S. of cor.
	Mark the cor. AM and bury in place.
13.08	Point for the closing cor. at intersection with the SE bdy of the Camp Goodwin Military Reservation, (abandoned).
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T5S R22E
	CGMR S13
	S14 S13 C C
	1985

α u	TA	rc

Rebuild old mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor. point, Cor. No. 3 of Camp Goodwin Military Reservation, (abandoned), bears S. 44°57' W., 27.63 chs. dist., hereinbefore described.

From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89°58' W., bet. secs. 12 and 13.

Over rolling land, through creosote and scattered mesquite.

38.36

The 1/4 sec. cor. of secs. 12 and 13, monumented with a granite stone, $10 \times 10 \times 5$ ins., firmly set, projecting 6 ins. from the ground, mkd. 1/4 12 on N. face, from which original bearing trees

A tesota stump, 8 ins. diam., bears S. 34 1/2° W., 139 lks. dist., no marks visible.

A mesquite, 15 ins. diam., bears N. 71° W., 171 lks. dist., no marks visible.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

from which new bearing trees

A mesquite, 10 ins. diam., bears S. 77 1/4° W., 69 lks. dist., mkd. 1/4 S13 BT.

A mesquite, 8 ins. diam., bears N. 19° W., 163 lks. dist., mkd. 1/4 S12 BT.

Bury original stone alongside the cor.

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white colored plastic case beneath the stainless steel post.
	Set a steel fence post alongside the cor.
	Cor. is located 50 lks. N. of a wash, 20 lks. wide, drains NE.
	S. 89°53' W., beginning new measurement.
12.44	A granite stone, 14 x 14 x 7 ins., firmly set, projecting 6 ins. from the ground, mkd. CGMR on N. face and CC on S. face, set for a closing cor. for secs. 12 and 13, in 1900.
	A scattered mound of stone is set E. of cor.
	Mark the cor. AM and bury in place.
13.42	Point for the closing cor. at intersection with the SE bdy. of the Camp Goodwin Military Reservation , (abandoned).
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T5S R22E C S12 G / S12 M / S13 1985
	Rebuild the mound of stone, 3 ft. base, 1 1/2 ft. high, E. of cor.
	Set a steel fence post alongside the cor.
	From this point, Cor. No. 3 of Camp Goodwin Military Reservation, (abandoned), bears S. 44°57' W., 65.765 chs. dist., hereinbefore described.
1	

CHAINS

Restoring the survey executed by Clarence H. Wallace, in 1888

From the cor. of secs. 11, 12, 13 and 14, monumented with a quartz stone, 24 x 18 x 10 ins., firmly set, projecting 12 ins. from the ground, mkd. with 4 grooves on S. face and 1 on E. face

A mound of stone, 2 1/2 x 1 ft. is set W. of cor.

At the cor. point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.

Bury stone alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 3 lks. E. of a N. and S. fence.

S. 0°49' W., bet. secs. 13 and 14.

Over nearly level land, through creosote and scattered mesquite.

Point for a closing cor. at intersection with the SE bdy. of the Camp Goodwin Military Reservation, (abandoned).

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Set a steel fence post alongside the cor.

CHAINS

From this cor. point, a granite stone, 14 x 7 x 6 ins., firmly set, projecting 9 ins. from the ground, set for a closing cor. for secs. 13 and 14, in 1888, bears S. 0°49' W., 60 lks. dist.

A scattered mound of stone is set N. of cor.

Mark the cor. AM and bury in place.

Rebuild mound of stone, 3 ft. base, 1 1/2 ft. high, N. of the cor.

From this same cor. point, Cor. No. 3 of Camp Goodwin Military Reservation (abandoned), bears S. 44°57' W., 61.78 chs. dist., hereinbefore described.

From the cor. of secs. 11, 12, 13 and 14.

N. 87°43' E., bet. secs. 12 and 13.

Over gently rolling land, through creosote and scattered mesquite.

Point for the closing cor. for secs. 12 and 13 at intersection with the SE bdy. of the Camp Goodwin Military Reservation, (abandoned).

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Set a steel fence post alongside the cor.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of the cor.

CHAINS

From this cor. point, a granite stone, 13 x 8 x 8 ins., firmly set, projecting 6 ins. from the ground, mkd. CGMR CC on W. face, set for a closing cor. for secs. 12 and 13, in 1888, bears N. 87°43' E., 1.01 chs. dist.

A scattered mound of stone is set W. of cor.

Mark the cor. AM and bury in place.

From this same cor. point, Cor. No. 3 of SE bdy. of the Camp Goodwin Military Reservation, (abandoned), bears S. 44°57' W., 61.78 chs. dist., hereinbefore described.

From the cor. of secs. 11, 12, 13 and 14.

S. 89°58' W., bet. secs. 11 and 14.

Over gently rolling land, through creosote and scattered mesquite.

17.56 Point for the closing cor. at the intersection with the E. bdy. of the San Carlos Indian Reservation, .

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.

Cor. is located in a N. and S. fence and 90 lks. S. of a wash, 20 lks. wide, drains SE.

From this cor. point, a quartz stone, 16 x 16 x 6 ins., firmly set, projecting 8 ins. from the ground, mkd. CGMR CC on E. face, set for a closing cor., in 1900, with the San Carlos Indian Reservation, bears S. 89°58' W., 70 lks. dist.

CHAINS

From this same cor. point, the 6 Mile Cor. of the San Carlos Indian Reservation, bears N. 0°10' W., 7.32 chs. dist., hereinbefore described.

A mound of stone, 2 1/2 ft. x 6 ins. is set E. of cor.

Mark the cor. AM and bury in place.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, E. of the cor.

From the cor. of secs. 11, 12, 13 and 14.

N. 0°07' W., bet. secs. 11 and 12.

Over gently rolling land, through creosote, scattered mesquite and cacti, along a fence line.

40.11 The 1/4 sec. cor. of secs. 11 and 12, monumented with a quartz stone, 12 x 10 x 6 ins., firmly set, projecting 10 ins. from the ground, mkd. 1/4 on W. face.

A scattered mound of stone is set W. of cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with cap mkd.

T5S R22E 1/4 S11 | S12 1985

Bury stone alongside the cor.

Set a steel fence post alongside the cor.

Cor. is located 3 lks. E. of a N. and S. fence

Dependent Resurvey, Portion of the Subdivisional Lines,

_		T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
	CHAINS	
i		N. 0°21' W., beginning new measurement.
	40.24	Cor. of secs. 1, 2, 11 and 12, monumented with a quartz stone, 14 x 10 x 6 ins., projecting 10 ins. from the ground, mkd. with 1 groove on the E. edge and 5 grooves on the S. edge.
		A scattered mound of stone is set W. of cor.
		At the cor. point
		Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.
		T5S R22E S 2 S 1
		S11 S12 1985
		Bury original stone alongside the cor.
		Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
		Cor. is located 2 lks. E. of a N. and S. fence.
		From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., described in the field notes of the dependent resurvey of the W. bdy. of T. 5 S., R. 23 E., resurveyed concurrently under this group.
		N. 89°57' W., bet. secs. 1 and 12.
		over rolling land, through medium creosote
	40.53	The 1/4 sec. cor. of secs. 1 and 12, monumented with a sandstone, 22 x 9 x 5 ins., loosely set, no marks visible
		A mound of stone 3 x 1 ft. is set N. of cor.
		At the cor. point
-		

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.

Bury stone alongside the cor.

Set a steel fence post alongside the cor.

S. 89°24' W., beginning new measurement.

40.34 The cor. of secs. 1, 2, 11 and 12

S. 89°46' W., bet. secs. 2 and 11.

Over rolling land, through creosote.

Point for the closing cor. at intersection with the E. bdy. of the San Carlos Indian Reservation.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.

From this cor. point, a quartz stone, 17 x 10 x 9 ins., firmly set, projecting 10 ins. from the ground, mkd. CGMR CC on E. face, set for a closing cor., in 1888, with the E. bdy. of the San Carlos Indian Reservation, bears S. 89°46' W., 25.5 lks. dist..

A scattered mound of stone is set E. of cor.

Mark the cor. AM and bury in place.

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
,	From this same cor. point, the 5 Mile Cor. of the San Carlos Indian Reservation, bears N. 0°15' W., 7.135 chs. dist., hereinbefore described. Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E. of
	cor.
	Cor. is located 1.5 lks. W. of a N. and S. fence.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 0°12' E., bet. secs. 1 and 2.
	Over rolling land, through medium creosote, alongside a fence line.
39.92	The $1/4$ sec. cor. of secs. 1 and 2, monumented with a quartz stone, $18 \times 9 \times 5$ ins., firmly set, projecting 10 ins. from the ground, mkd. $1/4$ on W. face.
	A mound of stone 3 x 1 ft. is set W. of cor.
	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.
	T5S R22E
	1/4
	S 2 S 1 1985
	Bury stone alongside the cor.
	Cor. is located 3 lks. E. of a N. and S. fence.
	Set a steel fence post alongside the cor.
	N. 0°33' W., beginning new measurement.
40.19	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.

CHAINS

Restoring the survey by Philip Contzen, in 1900

From the 1/4 sec. cor. of secs. 11 and 14, monumented with a schist stone, $14 \times 12 \times 6$ ins., firmly set, projecting 8 ins. from the ground, mkd. 1/4 11 on N. face, from which an original bearing tree

A dead standing mesquite, 6 ins. diam., bears S. 46 1/4° E., 186 lks. dist., no marks visible on blaze.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.

Bury stone alongside the cor.

Set a steel fence post alongside the cor.

N. 89°56' E., bet. secs. 11 and 14.

Over rolling land, through creosote and scattered mesquite.

19.85 A quartz stone, 16 x 10 x 6 ins., firmly set, projecting 8 ins. from the ground, mkd. CGMR on E. face and 11 on N. face, 14 on S. face and CC on W. face, set for a closing cor., 1n 1900, with the E. bdy. of the San Carlos Indian Reservation.

A scattered mound of stone is set W. of cor.

Mark this cor. AM and bury in place.

Dependent Resurvey, Portion of the Subdivisional Lines, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

20.55

Point for the closing cor. at the intersection with the E. bdy. of the San Carlos Indian Reservation.

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

Cor. is located in a N. and S. fence.

From this cor. point, the 6 Mile Cor. of the San Carlos Indian Reservation bdy., bears N. 0°10' W., 3.45 chs. dist., hereinbefore described.

From the 1/4 sec. cor. of secs. 2 and 11, monumented with a quartz stone, $16 \times 12 \times 6$ ins., firmly set, projecting 4 ins. from the ground, mkd. 1/4 2 on N. face and 11 on S. face, with a scattered mound of stone N. of cor., from which original bearing trees

- A mesquite, 9 ins. diam., bears N. 77° E., 69 lks. dist., no marks visible. (Record: N 74 1/2° E)
- A mesquite, 7 ins. diam., bears S. 49 1/2° E., 87 lks. dist., no marks visible.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.

Subdivision of Selected Sections, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Bury original stone alongside the cor.
	Set a steel fence post alongside the cor.
	N. 89°50' E., bet. secs. 2 and 11.
	Over rolling land, through medium creosote.
20.25	The closing cor. on the E. bdy. of the San Carlos Indian Reservation, hereinbefore described.
	From this cor. point, the 5 Mile Cor. of the San Carlos Indian Reservation, bears N. 0°15' W., 3.315 chs. dist., hereinbefore described.
	Subdivision of Selected Sections, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
	Section 24
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°03' W., on the N. and S. center line of sec. 24.
	Over rolling land, through creosote.
20.07	Point for the center S 1/16 sec. cor. of sec. 24.
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.
	T5S R22E
	S 1/16 C S24
	1985
	Set a steel fence post alongside the cor.
	Cor. is located 150 lks. S. of a track road, bears SE and NW.
	1

Subdivision of Selected Sections, T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.14	Point for the center 1/4 sec. cor. of sec. 24, at the intersection with the E. and W. center line of sec. 24.
	Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.
	T5S R22E
	C 1/4
	1985
	Set a steel fence post alongside the cor.
80.30	The 1/4 sec. cor. of secs. 13 and 24.
	From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., monumented with a sandstone, 16 x 8 x 6 ins., firmly set, projecting 8 ins. from the ground, mkd. 1/4 2 visible on the W. face, from which an original bearing tree
	A mesquite, 6 ins. diam., bears S. 50° W., 196 lks. dist., mkd. 1/4 S24 BT.
	At the cor. point
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.
	T5s
	R22E R23E
	1/4 S24 1982
	1502
	from which
	A mesquite, 6 ins. diam., bears S. 85° W., 73 lks. dist., mkd. 1/4 S24 BT.
	Bury stone alongside the cor.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

T. 5	5	S.,	R.	22	E.,	Gila	and	Salt	River	Meridian,	Arizona
------	---	-----	----	----	-----	------	-----	------	-------	-----------	---------

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 89°58' W., on the E. and W. center line of sec. 24.
18.945	Over rolling land, through medium creosote. Point for the center E 1/16 sec. cor. of sec. 24.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.
	T5S R22E E 1/16 C ————————————————————————————————————
	Set a steel fence post alongside the cor.
39.01	The center 1/4 sec. cor. of sec. 24.
79.19	The 1/4 sec. cor. of secs. 23 and 24.
	SE 1/4 of Section 24
	From the E 1/16 sec. cor. of secs. 24 and 25.
	N. 0°03' W., on the N. and S. center line of the SE 1/4 of sec. 24.
	Over rolling land, through creosote and scattered mesquite.
20.055	Point for the SE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the SE 1/4 of sec. 24.
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.
	T5S R22E
	SE 1/16 S24
	1985
	Set a steel fence post alongside the cor.
40.11	The center E 1/16 sec. cor. of sec. 24.

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

CHAINS

From the S 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., is at midpoint bet. the 1/4 sec. cor. of sec. 24 only, and the cor. of secs. 24 and 25 only.

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.

T5S R22E R23E S 1/16 | S24 | 1985

Set a steel fence post alongside the cor.

S. 89°54' W., on the E. and W. center line of the SE 1/4 of sec. 24.

Over rolling land, through medium creosote.

19.03 The SE 1/16 sec. cor. of sec. 24.

39.09 The center S 1/16 sec. cor. of sec. 24.

Section 25

From the 1/4 sec. cor. of secs. 25 and 36.

N. 0°41' W., on the N. and S. center line of sec. 25.

Over rolling land, through medium creosote.

20.05 Point for the center S 1/16 sec. cor. of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap mkd.

T5S R22E C S 1/16 | S25 C 1985

	Subdivision of Selected Sections,
CHAINS	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
Chains	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor. Set a steel fence post alongside the cor.
	The management of the second o
	Cor. is located 57 lks. N of a fence, bears SE and NW.
40.10	Point for the center 1/4 sec. cor. of sec. 25, at the intersection with the E. and W. center line of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T5S R22E C 1/4 S25 1985
	from which
	A mesquite, 12 ins. diam., bears N. 66° E., 145.5 lks. dist., mkd. C 1/4 S25 BT.
	A mesquite, 7 ins. diam., bears S. 15 1/2° W., 50.5 lks. dist., mkd. C 1/4 S25 BT.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
60.15	Point for the center N 1/16 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass aluminum cap mkd.
	T5S R22E
	N 1/16 S25
	1985
	from which
	A mesquite, 15 ins. diam., bears N. 68 1/4° E., 217 lks. dist., mkd. C-N 1/16 S25 BT.
	A mesquite, 6 ins. diam., bears S. 65° W., 76 lks. dist., mkd. C-N 1/16 S25 BT.
	1

T. 5 S., R. 22 E., Gila and Salt River Meridian, A	. 5	T.	5 S., R	. 22 E.	, Gila an	d Salt River	Meridian,	Arizona
--	-----	----	---------	---------	-----------	--------------	-----------	---------

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
80.20	The 1/4 sec. cor. of secs. 24 and 25.
	From the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., is at midpoint on the E. bdy. of sec. 25.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap mkd.
	T5S R22E R23E 1/4 S25 1982
	from which
	A mesquite, 10 ins. diam., bears N. 57° W., 120 lks. dist., mkd. T5S R22E 1/4 S25 BT.
	Cor. is set in a wash, 20 lks. wide, drains NE.
	S. 89°53' W., on the E. and W. center line of sec. 25.
	Over Black Rock Wash bottom, through medium underbrush, mesquite, cottonwood and ash.
18.975	Point for the center E 1/16 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T5S R22E E 1/16 C ————————————————————————————————————
	from which
	A mesquite, 28 ins. diam., bears S. 11° W., 132.5 lks. dist., mkd. C-E 1/16 S25 BT.

	Subdivision of Selected Sections,
CHAINS	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Set a steel fence post alongside the cor.
	Cor. is located in Black Rock Wash bottom land.
38.83	The center 1/4 sec. cor. of sec. 25.
59.115	Point for the center W 1/16 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap mkd.
	T5S R22E
	W 1/16
	.c —— c
	S25
	1985 from which
	A mesquite, 15 ins. diam., bears S. 18° W., 107.5 lks. dist., mkd. C-W 1/16 S25 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Set a steel fence post alongside the cor.
	Cor. is located in Black Rock Wash bottom land.
79.40	The 1/4 sec. cor. of secs. 25 and 26.
	SE 1/4 of Section 25
	From the E 1/16 sec. cor. of secs. 25 and 26.
	N. 0°24' W., on the N. and S. center line of the SE 1/4 of sec. 25.
	Over rolling land, through creosote, scattered mesquite and yucca.
E .	

Subdivision of Selected Sections, 5 S., R. 22 E., Gila and Salt River Meridian, Ari

	T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona
CHAINS	
20.05	Point for the SE 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the SE 1/4 of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T5S R22E SE 1/16 S25 1985
	Cor is located S. 26° W., 129 lks. dist., from a fence cor., fences extend N., S. and W.
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
40.10	The center E 1/16 sec. cor. of sec. 25.
	From the S 1/16 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., is at midpoint on the E bdy. of sec. 25, bet. the 1/4 sec. cor. of sec. 25 only, and the cor. of secs. 25 and 36 only.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T5S R22E R23E S 1/16 S25 1985
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
	S. 89°53' W., on the E. and W. center line of the SE 1/4 of sec. 25.
	Over gently rolling land, through medium creosote and scattered mesquite.
18.90	The SE 1/16 sec. cor. of sec. 25.
38.65	The center S 1/16 sec. cor. of sec. 25
-	

	T.	<u>5</u>	S.,	R.	22	E.,	Gila	and	Salt	River	Meridian,	Arizona
TH A INC												

	1. J S., R. 22 E., Gila and Sait River Ferruran, Arizona
CHAINS	NW 1/4 of Section 25
	From the center W 1/16 sec. cor. of sec. 25.
	N. 0°23' W., on the N. and S. center line of the NW 1/4 of sec. 25.
	Over Black Rock Wash bottom land, through mesquite and catclaw.
9.00	Leave Black Rock Wash bottom land, then through creosote, mesquite and catclaw.
20.06	Point for the NW 1/16 sec. cor. of sec. 25, at intersection with the E. and W. center line of the NW 1/4 of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T5S R22E NW 1/16 S25 1985
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	Set a steel fence post alongside the cor.
40.12	The W 1/16 sec. cor. of secs. 24 and 25.
	From the center N 1/16 sec. cor. of sec. 25.
	S. 89°55' W., on the E. and W. center line of the NW 1/4 of sec. 25.
	Over gently rolling land, through creosote, catclaw and mesquite.
20.18	The NW 1/16 sec. cor. of sec. 25.
40.36	The N 1/16 sec. cor. of secs. 25 and 26.

T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona

	1. J S., R. 22 E., Gila and Sait River Meridian, Arizona
CHAINS	GENERAL DESCRIPTION
	The land encompassed in this survey is located about 8 miles southwest of the town of Fort Thomas, Arizona. Black Rock Wash is the predominant wash in the area and runs through a part of this survey. The average elevation is about 3,100 feet above sea level, with the terrain ranging from level and brushy with scattered mesquite and creosote, to broken and open, with hills, gullies and dry washes formed by erosion. The soil is clay-like.
	The area is principally used for livestock grazing.
	No mining activity was noticed.
	The mean magnetic declination is 13 1/2° E.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

FIELD ASSISTANTS	
CAPACITY	
Surveying Technician	
Surveying Technician	
Survey Aid	
Survey Aid	

CERTIFICATE OF SURVEY

We, Paul L. Reeves, Will C. Gabonay, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 8th day of April , 1982, We have dependently portions, of the Camp Goodwin Military Reservation, (abandoned), of the north boundary, of the subdivisional lines, the east boundary of the San Carlos Indian Reservation and the subdivision of selected sections, of Township 5 South, Range 22 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Surveying Instructions, 1973 and in specific manner described in the foregoing field notes.

Paul L Reeves and Will C. Gabonay are no longer assigned th this office and are not available for signatures.

(Field Supervisor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of portions, of the Camp Goodwin Military Reservation, (abandoned), of the north boundary, of the subdivisional lines, the east boundary of the San Carlos Indian Reservation and subdivision of selected section, of Township 5 South, Range 22 East, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves and Will C. Gabonay, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 11 1991

(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I Certify that the foregoing transcript of the field notes of the above-described surveys in T. 5 S., R. 22 E., Gila and Salt River Meridian, Arizona is a true copy of the original field notes.

(Chief Cadastral Surveyor of Arizona)